

Comment	Description	Designator	Footprint	Quantity
100nF	Capacitor	C1, C3, C4, C11, C13, C14, C15	C0402	7
1nF	Capacitor	C6	C0603	1
10uF/50V	Capacitor	C12, C19	C1206	2
100nF/50V	Capacitor	C16	C0402	1
22uF	Capacitor	C17, C18	C0603	2
1uF	Capacitor	C21	C0603	1
220uF/35V	Polarized Capacitor (Axial)	C24	CAPR-5mm	1
1N4148W	Diode	D1, D4	SOD-123	2
MB10S		D3	SOIC245P670X290-4N	1
500mA	Fuse	F1, F2	1206	2
GZ1608D601TF	Ferrite_Bead	FB1, FB2, FB3	0603	3
LGS5145	60-V, 600-mA High Efficiency Wide Input Voltage Range Buck Converter	IC1	SOT95P280X110-6N (SOT23-6L)	1
C720477	Tactile Switch	J2, J3	TS-1088-AR02016	2
FFC 0.5mm 10Pin 90°	FFC 0.5mm 10P Bottom Connection C262659	J4	TE_1-1734592-0	1
Terminalblock X2		J6, J7	Terminalblock_X2_5mm	2
CMI321609X100KT (10uH)	15uH	L1	L1210	1
KF2EDGR-3.5-2Pin	KF2EDGR-3.5-2Pin	P6	CONN-TH_2P-P3.50_KF2EDGR-3.5	1
Header	4 Pin male	P7	TE_826647-4	1
AO3400A	30V N-Channel MOSFET	Q1	SOT23 Normal	1
1	Resistor	R2	R0805	1
1k	Resistor	R3, R29	0402	2
100k	Resistor	R4	0402	1
10k	Resistor	R8, R9, R18, R23, R47	0402	5
15k	Resistor	R12	0402	1
10	Resistor	R27	R0603	1
470k	Resistor	R28	R0603	1
4.7k	Resistor	R30	R0603	1
100k	Resistor	R31	R0603	1
8.2k	Resistor	R32	R0603	1
18k	Resistor	R33	R0603	1
33k	Resistor	R46	R0603	1
CH32V003F4U6	CPU Core:RISC-V CPU Maximum Speed:48MHz Program Storage Size:16KB Number of I/O:18 Applications:-	U1	QFN-20_L3.0-W3.0-P0.40-TL-EP1.7	1
LMV331IDBVRG4	Single General Purpose Low-Voltage Comparator 5-SOT-23	U2	SOT23-5	1
AT24C256C-SSHL-T	AT24C256C-SSHL-T	U3	SOIC127P600X265-8N (SOIC-8)	1