

Comment	Description	Designator	Footprint	Quantity
100nF	Capacitor	C1, C3, C4, C11, C13, C14, C15	C0402	7
10uF/50V	Capacitor	C12, C19	C1206	2
100nF/50V	Capacitor	C16	C0402	1
22uF	Capacitor	C17, C18	C0603	2
1uF	Capacitor	C21	C0603	1
220uF/50V	Polarized Capacitor (Axial)	C24	CAPR-5mm	1
18V	Zener	D1	SOD-323	1
MB10S		D3	SOIC245P670X290-4N	1
BAV99	Diode Array 1 Pair Series Connection Standard 100V 215mA (DC) Surface Mount TO-236-3, SC-59, SOT-23-3	D4	SOT23	1
B5819W SL	Diode	D6, D7, D9	SOD-123	3
500mA	Fuse	F1, F2	1206	2
GZ1608D601TF	Ferrite_Bead	FB1	0603	1
LGS5145	60-V, 600-mA High Efficiency Wide Input Voltage Range Buck Converter	IC1	SOT95P280X110-6N (SOT23-6L)	1
C720477	Tactile Switch	J2, J3	TS-1088-AR02016	2
C262302	FFC/FPC Connector 10 Position 0.5mm Pitch Single-side Contact/ Vertical Surface Mount	J4	CONN-TH-10P_AFC11-S10ICC-00	1
CMI321609X100KT (10uH)	15uH	L1	L1210	1
KF2EDGR-3.5-4Pin	KF2EDGR-3.5-4Pin	P5	CONN-TH_4P-P3.50_KF2EDGR-3.5-4P	1
KF2EDGR-3.5-2Pin	KF2EDGR-3.5-2Pin	P6	CONN-TH_2P-P3.50_KF2EDGR-3.5	1
Header	4 Pin male	P7	TE_826647-4	1
AO3400A	30V N-Channel MOSFET	Q1	SOT23 Normal	1
AO3401A	30V P-Channel MOSFET	Q2	SOT23 Normal	1
MMBT5401	60V, 600 mA, PNP switching transistor	Q3	SOT23 Reverse	1
MMBT5551	NPN General Purpose Transistor	Q5	SOT23 Reverse	1
100k	Resistor	R1, R5, R11, R31	R0603	4
1	Resistor	R2	R0805	1
1k	Resistor	R3, R29	0402	2
100k	Resistor	R4	0402	1
10k	Resistor	R6, R7	R0603	2
10k	Resistor	R8, R9, R18, R23, R47	0402	5
0	Resistor	R10	R0603	1
15k	Resistor	R12	0402	1
22	0	R19, R20	0402	2
1.5k	Resistor	R21	R0603	1
10	Resistor	R27, R41, R42	R0603	3
1M	Resistor	R28	R0603	1
4.7k	Resistor	R30	R0603	1
8.2k	Resistor	R32	R0603	1
18k	Resistor	R33	R0603	1
33k	Resistor	R46	R0603	1
CH32V003F4U6	CPU Core:RISC-V CPU Maximum Speed:48MHz Program Storage Size:16KB Number of I/O:18 Applications:-	U1	QFN-20_L3.0-W3.0-P0.40-TL-EP1.7	1
LMV331IDBVRG4	Single General Purpose Low-Voltage Comparator 5-SOT-23	U2	SOT23-5	1
AT24C256C-SSHL-T	AT24C256C-SSHL-T	U3	SOIC127P600X265-8N (SOIC-8)	1