

NXP Automotive Processors—Product Map



General Purpose MCUs Built on Arm® Cortex-M Technology | Supporting ASIL B/D Safety

Device	Core	Frequency	Flash	RAM	ECC	EEPROM	FOTA	MPU	DMA	Security	CRC	UART/LIN	SPI	CAN /ISO CAN-FD	I²C	I³C	FlexIO	Ethernet 100MBit	Serial Audio Interface (SAI)	External Memory Interface	Timer	Other	ADC 12 bit	Operating Voltage	Temp. Range	Debug	Package Options
*S32K358	M7 Lockstep + M7	240 MHz	8 MB	1152 KB	Flash + RAM	-	A/B Swap; Rollback (HW); automatic address translation	1	32-ch	HSE-B	1	16	6	8	2	1	32-ch	1	2	Quad SPI	eMIOS (3)	LCU, BCTU	3x 24ch	3.3V, 5V, or split	V,M	SWD, SWO, JTAG	172 MaxQFP, 289 MAPBGA
*S32K348	M7 Lockstep	160 MHz	8 MB	1152 KB	Flash + RAM	-	A/B Swap; Rollback (HW); automatic address translation	1	32-ch	HSE-B	1	16	6	8	2	1	32-ch	1	2	Quad SPI	eMIOS (3)	LCU, BCTU	3x 24ch	3.3V, 5V, or split	V,M	SWD, SWO, JTAG	172 MaxQFP, 289 MAPBGA
*S32K338	3x M7	240 MHz	8 MB	1152 KB	Flash + RAM	-	A/B Swap; Rollback (HW); automatic address translation	1	32-ch	HSE-B	1	16	6	8	2	1	32-ch	1	2	Quad SPI	eMIOS (3)	LCU, BCTU	3x 24ch	3.3V, 5V, or split	V,M	SWD, SWO, JTAG	172 MaxQFP, 289 MAPBGA
*S32K328	2x M7	160 MHz	8 MB	1152 KB	Flash + RAM	-	A/B Swap; Rollback (HW); automatic address translation	1	32-ch	HSE-B	1	16	6	8	2	1	32-ch	1	2	Quad SPI	eMIOS (3)	LCU, BCTU	3x 24ch	3.3V, 5V, or split	V,M	SWD, SWO, JTAG	172 MaxQFP, 289 MAPBGA
S32K344	M7 Lockstep	160 MHz	4 MB	512 KB	Flash + RAM	-	A/B Swap; Rollback (HW); automatic address translation	1	32-ch	HSE-B	1	16	6	6	2		32-ch	1	2	Quad SPI	eMIOS (3)	LCU, BCTU	3x 24ch	3.3V, 5V, or split	V,M	SWD, SWO, JTAG	172 MaxQFP, 257 MAPBGA
S32K342	M7 Lockstep	160 MHz	2 MB	256 KB	Flash + RAM	-	A/B Swap; Rollback (HW); automatic address translation	1	32-ch	HSE-B	1	4	4	4	2	1	32-ch	1	2	Quad SPI	eMIOS (2)	LCU, BCTU	2x 24ch	3.3V, 5V, or split	V,M	SWD, SWO, JTAG	100/172 MaxQFP
S32K341	M7 Lockstep	160 MHz	1 MB	256 KB	Flash + RAM	-	A/B Swap; Rollback (HW); automatic address translation	1	32-ch	HSE-B	1	16	4	4	2	1	32-ch	1	2	Quad SPI	eMIOS (3)	LCU, BCTU	3x 24ch	3.3V, 5V, or split	V,M	SWD, SWO, JTAG	100/172 MaxQFP
S32K324	2x M7	160 MHz	4 MB	512 KB	Flash + RAM	-	A/B Swap; Rollback (HW); automatic address translation	1	32-ch	HSE-B	1	16	6	6	2		32-ch	1	2	Quad SPI	eMIOS (3)	LCU, BCTU	3x 24ch	3.3V, 5V, or split	V,M	SWD, SWO, JTAG	172 MaxQFP, 257 MAPBGA
S32K322	2x M7	160 MHz	2 MB	256 KB	Flash + RAM	-	A/B Swap; Rollback (HW); automatic address translation	1	32-ch	HSE-B	1	4	4	4	2	1	32-ch	1	2	Quad SPI	eMIOS (2)	LCU, BCTU	2x 24ch	3.3V, 5V, or split	V,M	SWD, SWO, JTAG	100/172 MaxQFP
S32K314	M7	160 MHz	4 MB	512 KB	Flash + RAM	-	A/B Swap; Rollback (HW); automatic address translation	1	32-ch	HSE-B	1	16	6	6	2		32-ch	1	2	Quad SPI	eMIOS (3)	LCU, BCTU	3x 24ch	3.3V, 5V, or split	V,M	SWD, SWO, JTAG	172 MaxQFP, 257 MAPBGA
S32K312	M7	120 MHz	2 MB	192 KB	Flash + RAM	-	A/B Swap; Rollback (HW); automatic address translation	1	12-ch	HSE-B	1	8	4	6	2	1	32-ch				eMIOS (2)	LCU, BCTU	2x 24ch	3.3V, 5V, or split	V,M	SWD, SWO, JTAG	100/172 MaxQFP
S32K311	M7	120 MHz	1 MB	128 KB	Flash + RAM	-	A/B Swap; Rollback (HW); automatic address translation	1	12-ch	HSE-B	1	4	4	3	2	1	16-ch				eMIOS (2)	LCU, BCTU	2x 24ch	3.3V, 5V, or split	V,M	SWD, SWO, JTAG	48 LQFP, 100 MaxQFP
S32K148	M4F	112 MHz	2 MB	256 KB	Flash + RAM	4 KB emulated	A/B Swap** + Rollback (SW)	1	16-ch.	CSEc	1	3	3	3 / 3	2		1	1x IEEE-1588 MAC w/ Timestamping	2 modules (I²S, TDM, AC97)	1x QuadSPI w/ HyperBus	FlexTimer (8)	PDB	2 x 32-ch.	2.7 - 5.5	V,M	SWD, SWO, JTAG	100, 144, 176 LQFP 100 MAPBGA
S32K146	M4F	112 MHz	1 MB	128 KB	Flash + RAM	4 KB emulated	A/B Swap** + Rollback (SW)	1	16-ch.	CSEc	1	3	3	3 / 2	1		1				FlexTimer (6)	PDB	2 x 24-ch.	2.7 - 5.5	V,M	SWD, SWO, JTAG	64, 100, 144 LQFP; 100 MAPBGA
S32K144	M4F	112 MHz	512 KB	64 KB	Flash + RAM	4 KB emulated	Rollback (SW)	1	16-ch.	CSEc	1	3	3	3 / 1	1		1				FlexTimer (4)	PDB	2 x 16-ch.	2.7 - 5.5	V,M,W	SWD, SWO, JTAG	48, 64, 100 LQFP 100 MAPBGA
S32K142	M4F	112 MHz	256 KB	32 KB	Flash + RAM	4 KB emulated	Rollback (SW)	1	16-ch.	CSEc	1	2	2	2 / 1	1		1				FlexTimer (4)	PDB	2 x 16-ch.	2.7 - 5.5	V,M,W	SWD, SWO, JTAG	48, 64, 100 LQFP
S32K118	M0+	48 MHz	256 KB	25 KB	Flash + RAM	2 KB emulated	Rollback (SW)	1	4-ch.	CSEc	1	2	2	1 / 1	1		1				FlexTimer (2)	PDB	1 x 16-ch.	2.7 - 5.5	V,M	SWD	48, 64 LQFP
S32K116	M0+	48 MHz	128 KB	17 KB	Flash + RAM	2 KB emulated	Rollback (SW)	1	4-ch.	CSEc	1	2	1	1 / 1	1		1				FlexTimer (2)	PDB	1 x 13-ch.	2.7 - 5.5	V,M	SWD	32 QFN, 48 LQFP
KEAZ128	M0+	48 MHz	128 KB	16 KB		Emulated					1	3	2	1	2						6-ch. + 2-ch. + 2-ch.		1 x 16-ch.	2.7 - 5.5	C,V,M	SWD	64 LQFP, 80 LQFP
KEAZ64	M0+	48 MHz	64 KB	8 KB		Emulated					1	3	2	1	2						6-ch. + 2-ch. + 2-ch.		1 x 16-ch.	2.7 - 5.5	C,V,M	SWD	64 LQFP, 80 LQFP
KEAZN32	M0+	40 MHz	32 KB	4 KB		256 B					1	3	2		2						6-ch. + 2-ch. + 2-ch.		1 x 16-ch.	2.7 - 5.5	C,V,M	SWD	32 LQFP, 64 LQFP
KEAZN64	M0+	40 MHz	64 KB	4 KB		256 B					1	3	2		2						6-ch. + 2-ch. + 2-ch.		1 x 16-ch.	2.7 - 5.5	C,V,M	SWD	32 LQFP, 64 LQFP
KEAZN16	M0+	40 MHz	16 KB	2 KB		256 B					1	3	2		2						6-ch. + 2-ch. + 2-ch.		1 x 16-ch.	2.7 - 5.5	C,V,M	SWD	32 LQFP, 64 LQFP
KEAZN8	M0+	48 MHz	8 KB	1 KB		Emulated					1	1	1		1						6-ch. + 2-ch.		1 x 12-ch.	2.7 - 5.5	C,V,M	SWD	16 TSSOP, 24 QFN

*Feature set under evaluation and subject to change
**Without HW swap support, code compiled as position independent code

Temperature Legend

C = -40°C TO +85°C M = -40°C TO +125°C
V = -40°C TO +105°C W = -40°C TO +150°C



MagniV Integrated Solutions – MCU + VReg + CAN Phy / LIN Phy / Gate Drive Unit | Supporting ASIL B Safety

Device	Bus Frequency	Flash	RAM	EEPROM	ECC	CAN	CAN-PHY	SCI	LIN-PHY	SPI	I2C	Ext. Analog (ADC)	PWM	Timer	KWU	Motor	High-Voltage Input	Other Analog	Vreg	Ext. Supply	Operating Voltage	Temp Range	Packaging Options
S12ZVCA	32 MHz	64-192 KB	4-12 KB	1-2 KB	Flash+RAM	1	1	2		1-2	1	10-16-ch. 12-bit	8-ch. 8-bit or 4-ch. 16-bit	8+4-ch. 16-bit	34		2-ch. HVI, VSUPSense	2-ch. ACMP, DAC/OpAmp, 4-ch. NGPIO(5V/25mA)	2	5 V/20 mA + CAN-supply	5.5 to 18 (max 40V)	C, V, M, W	48 LQFP, 64 LQFP-EP
S12ZVC	32 MHz	64-192 KB	4-12 KB	1-2 KB	Flash+RAM	1	1	2		1-2	1	10-16-ch. 10-bit	8-ch. 8-bit or 4-ch. 16-bit	8+4-ch. 16-bit	34		2-ch. HVI, VSUPSense	4-ch. NGPIO (5V/25mA)	2	5 V/20 mA + CAN-supply	5.5 to 18 (max 40V)	C, V, M, W	48 LQFP, 64 LQFP-EP
S12ZVLA	32 MHz	64-128 KB	4-8 KB	1-2 KB	Flash+RAM	1		2	1	1	1	6-10-ch. 12 bit	8-ch. 8-bit or 8-ch. 16-bit	6+2-ch. 16-bit	23		1-ch. HVI, VSUPSense	3-ch. NGPIO (5V/25mA),1-ch. ACMP, DAC/OpAmp, PGA	1	5 V/20 mA	3.5 to 18 (max 40V)	C, V, M, W	48-LQFP,32-LQFP, 32-QFN
S12ZVL	32 MHz	8-128 KB	1-8 KB	0.1-2 KB	Flash+RAM	0-1		2	1	1	1	6-10-ch. 10 bit	8-ch. 8-bit or 4-ch. 16-bit	6+2-ch. 16-bit	23		1-ch. HVI, VSUPSense	3-ch. NGPIO (5 V/25 mA)	1	5 V/20 mA	3.5 to 18 (max 40V)	C, V, M, W	48 LQFP, 32 LQFP, 32 QFN
S12ZVLS	32 Mhz	16-32 KB	1 KB	128 KB	Flash+RAM			2	1	1	1	6-ch. 10-bit	8-ch. 8-bit or 4-ch. 16-bit	6+2-ch. 16-bit	15		1-ch. HVI, VSUPSense	3-ch. NGPIO (5V/25mA)	1	5 V/20 mA	5.5 to 18 (max 40V)	C, V, M	32 QFN
S12ZVMC256	50 MHz	256KB	32kB	1KB	Flash+RAM	1	1	2		1		8+8-ch. 12-bit	6-ch. 15-bit, 8-ch. 8-bit or 4-ch. 16-bit	4+2-ch. 16-bit	18	PMSM/BLDC/SRM/DC	1-ch. HVI, VSUPSense	6-ch. Gate Drive Unit, 2x Current Sensing	4	5 V/20 mA + CAN-supply + 2x Ext.	3.5 to 18 (max 40V)	V, M, W	80 LQFP-EP
S12ZVML	50 MHz	32-128 KB	4-8 KB	0.1-0.5KB	Flash+RAM	0-1		1-2	1	1		4+5-ch. 12-bit	6-ch., 15-bit	4-ch. 16-bit	18	PMSM/BLDC/DC	VSUP Sense	6-ch. Gate Drive Unit, 2x Current Sensing	1	5 V/20 mA	3.5 to 18 (max 40V)	V, M, W	48 LQFP-EP, 64 LQFP-EP
S12ZVMC	50 MHz	64-128 KB	4-8 KB	512 B	Flash+RAM	1		2		1		4+5-ch. 12-bit	6-ch., 15-bit	4-ch. 16-bit	18	PMSM/BLDC/DC	VSUP Sense	6-ch. Gate Drive Unit, 2x Current Sensing	2	5 V/20 mA + CAN-supply	3.5 to 18 (max 40V)	V, M, W	64 LQFP-EP
S12ZVM	50 MHz	16-32 KB	2-4 KB	128 B	Flash+RAM			1-2		1		4+5-ch. 12-bit	6-ch., 15-bit	4-ch. 16-bit	18	PMSM/BLDC/DC	VSUP Sense	6-ch. Gate Drive Unit, 2x Current Sensing, HV-PHY (PWM)	1	5 V/20 mA	3.5 to 18 (max 40V)	V, M, W	64 LQFP-EP, 48 LQFP-EP
S12ZVMB	32 MHz	48-64 KB	4 KB	512 B	Flash+RAM			2	1	1		5-9-ch. 10-bit	6-ch., 15-bit	4+4ch. 16-bit	17	DC (bidirectional, H-Bridge)	VSUP Sense	4-ch. Gate Drive Unit, Current Sensing	1	5 V/20 mA	5.5 to 18 (max 40V)	V, M, W	64 LQFP, 48 LQFP
S12ZVMA	32 MHz	16-32 KB	1-2 KB	128 B	Flash+RAM			1	1	1		8-ch. 10-bit	6-ch., 15-bit	2+2ch. 16-bit	17	DC (unidirectional, Half-Bridge)	VSUP Sense	2-ch. Gate Drive Unit, Current Sensing, NGPIO (5V/25mA)	1	5 V/20 mA	3.5 to 18 (max 40V)	V, M, W	32 LQFP, 48 LQFP
S12VR	25 MHz	16-64 KB	2 KB	0.1-0.5 kB	Flash			1-2	1	1		2-6 ch. 10-bit	8-ch. 8-bit or 4-ch. 16-bit	4-ch. 16-bit	16	DC (bidirectional, relay)	4-ch. HVI, VBATSense, VSUP Sense	1-2ch. high-side	1	5 V/20 mA	5.5 to 18 (max 40V)	C, V, M	32 LQFP, 48 LQFP
S12VRP	25 MHz	48-64 KB	6 KB	2 - 4 KB	Flash			1-2	1			6-ch. 10-bit	8-ch. 8-bit or 4-ch. 16-bit	2+2-ch. 16-bit	16	DC (bidirectional, relay)	4-ch. HVI, VBATSense, VSUP Sense	1-ch. general low-side, 2-ch.high-side	1	5 V/20 mA	5.5 to 18 (max 40V)	C, V, M	32 LQFP, 48 LQFP
S12ZVH	32 MHz	64-128 KB	4-8 KB	4 KB	Flash+RAM	1	1	2		1	1	8-ch. 10-bit	8-ch. 8-bit or 4-ch. 16-bit	8+8ch. 16-bit	24	4 Stepper	VBAT Sense, VSUP Sense	40 X 4 LCD, Simple Sound Generator, RTC	2		5.5 to 18 (max 40V)	C, V	100 LQFP, 144 LQFP
S12ZVHY	32 MHz	32-64 KB	2-4 KB	2 KB	Flash+RAM	1		2		1	1	8-ch. 10-bit	8-ch. 8-bit or 4-ch. 16-bit	8+8ch. 16-bit	24	2 Stepper	VBAT Sense, VSUP Sense	40 X 4 LCD, Simple Sound Generator, RTC	1		5.5 to 18 (max 40V)	C, V	100 LQFP, 144 LQFP
S12ZVHL	32 MHz	64 KB	4 KB	2 KB	Flash+RAM	1		2	1	1	1	8-ch. 10-bit	8-ch. 8-bit or 4-ch. 16-bit	8+8ch. 16-bit	24	2 Stepper	VBAT Sense, VSUP Sense	40 X 4 LCD, Simple Sound Generator, RTC	1		5.5 to 18 (max 40V)	C, V	100 LQFP, 144 LQFP
S12ZVFP	32 MHz	64 KB	4 KB	2 KB	Flash+RAM	1		2	1	1	1	8-ch. 10-bit	8-ch. 8-bit or 4-ch. 16-bit	8+8ch. 16-bit	24		VBAT Sense, VSUP Sense	40 X 4 LCD, Simple Sound Generator, RTC	1		5.5 to 18 (max 40V)	C, V	100 LQFP, 144 LQFP

16-bit S12 MagniV MCUs (Integrated MCU + PHY/GDU) Supports ASIL B Safety

Vision MPUs Built on Arm Cortex-A Technology | Supporting ASIL B/C Safety

Device	Core Platform	Core Frequency	Cache	SRAM	DMA	Video Accelerator	Graphics Accelerator	Image Processor	Camera Input	Display Interface	DRAM Support	External Memory Interface	CAN	SD/MMC SDIO	I²C	SPI	UART	Ethernet	PIT	3.3 V GPIO	Operating Voltage	Temp. Range	Package Options
S32V234	Quad Arm Cortex-A53	4 x 1 GHz	L1: 32 KB/ 32 KB I/D per core L2: 256 KB unified per cluster	4 MB	32-ch.	H.264 and MJPEG encode and decode	3DGPU w/ OpenCV	Image signal processor (ISP) + Dual APEX2-CL + eIQ Auto	MIPI-CSI, VIU-Lite	TFT, up to 150 MPixels/sec (e.g. 1920 x 1080 60 Hz)	x64 LPDDR2, DDR3 and DDR3L	PCIe, QuadSPI	2 x CAN-FD	1	3	4	2	1 GB with IEEE® 1588	2	P	1.0 ± 5% for digital core input supply voltage	V	621 Flip Chip BGA

32-bit MPC57xx MCUs Built on Power Architecture Technology | Supporting ASIL B/C/D Safety

Device	Core Platform	Core Frequency	Program Flash	SRAM	D-Flash for Emulated EEPROM	DMA	Crypto	SCI (LINFlex)	SPI	CAN/ISO CAN-FD	I2C	FlexRay	Ethernet	Other Peripherals	Motor Control Peripherals	PIT	Analog (ADC)	Safety Level	Operating Voltage	Temp. Range	Debug	Package Options
MPC5777M	2 x z7 w/Lockstep + 1 x z4	300 MHz, 200MHz	8 MB	596 KB	544kB	2 x 64-ch.	HSM	6	8	5/1	2	x	x	SENT, PSi5, EBI, CRC, Zipwire	248-ch. GTM	8	52-ch. 16-bit, 84ch. 12-bit	ASIL-D	3.3, 5	M	Nexus 3+, Aurora, JTAG	416, 512 TEPBGA
MPC5777C	2 x z7 w/Lockstep	264 MHz or 300 MHz	8 MB	512 KB	256kB	2 x 64-ch.	CSE	5	5	6/2			x	SENT, PSi5, EBI, CRC, Zipwire	96-ch. eTPU+ 32-ch. eMIOS	4	20-ch. 16-bit, 70ch. 12-bit	ASIL-D	3.3, 5	M	Nexus 3+, Aurora, JTAG	416, 516 MAPBGA
MPC5775E	2 x z7 w/Lockstep	264 MHz	4 MB	512 KB	256kB	2 x 64-ch.	CSE	5	5	6/2			x	SENT, EBI, CRC	96-ch. eTPU+ 32-ch. eMIOS	4	20-ch. 16-bit, 70ch. 12-bit	ASIL-D	3.3, 5	M	Nexus 3+, JTAG	416 MAPBGA
MPC5775B	2 x z7 w/Lockstep	220 MHz	4 MB	512 KB	256kB	2 x 64-ch.	CSE	5	5	6/2			x	SENT, EBI, CRC	32-ch. eMIOS	4	40ch. 12-bit	ASIL-D	3.3, 5	M	Nexus 3+, JTAG	416 MAPBGA
MPC5746R	2 x z4 w/Lockstep	200 MHz	4 MB	256 KB	256 KB	64-ch.		6	7	4			x	SENT, CRC, Zipwire	64-ch. eTPU + 32-ch.eMIOS, CTU	8	48ch. 16-bit, 96ch. 12-bit	ASIL-D	3.3, 5	M	Nexus 3+, Aurora, JTAG	176 LQFP, 252 MAPBGA
MPC5745R	2 x z4 w/Lockstep	200 MHz	3 MB	192 KB	256 KB	64-ch		6	7	4			x	SENT, CRC, Zipwire	64-ch. eTPU + 32-ch.eMIOS, CTU	8	48ch. 16-bit, 96ch. 12-bit	ASIL-D	3.3, 5	M	Nexus 3+, Aurora, JTAG	176 LQFP, 252 MAPBGA
MPC5743R	z4 w/Lockstep	200 MHz	2 MB	128 KB	256 KB	64-ch		5	6	4			x	SENT, CRC, Zipwire	64-ch. eTPU + 32-ch.eMIOS, CTU	8	48ch. 16-bit, 96ch. 12-bit	ASIL-D	3.3, 5	M	Nexus 3+, Aurora, JTAG	144, 176 LQFP
MPC5744P	z4 w/Lockstep	200 MHz	2.5 MB	384 KB	96 KB	32-ch		2	4	3		x	x	SENT, CRC, Zipwire	18-ch. E-Timer, 24-ch. PWM, CTU	4	25-ch. 12-bit	ASIL-D	3.3	M, K	Nexus 3+, MDO and Aurora interface	144 LQFP, 257 MAPBGA
MPC5743P	z4 w/Lockstep	200 MHz	2 MB	256 KB	96 KB	32-ch		2	4	3		x	x	SENT, CRC, Zipwire	18-ch. E-Timer, 24-ch. PWM, CTU	4	25-ch. 12-bit	ASIL-D	3.3	M, K	Nexus 3+, MDO and Aurora interface	144 LQFP, 257 MAPBGA
MPC5742P	z4 w/Lockstep	200 MHz	1.5 MB	192 KB	96 KB	32-ch		2	4	3		x	x	SENT, CRC, Zipwire	18-ch. E-Timer, 24-ch. PWM, CTU	4	25-ch. 12-bit	ASIL-D	3.3	M, K	Nexus 3+, MDO and Aurora interface	144 LQFP, 257 MAPBGA
MPC5741P	z4 w/Lockstep	200 MHz	1 MB	128 KB	96 KB	32-ch		2	4	3		x	x	SENT, CRC, Zipwire	18-ch. E-Timer, 24-ch. PWM, CTU	4	25-ch. 12-bit	ASIL-D	3.3	M, K	Nexus 3+, MDO and Aurora interface	144 LQFP, 257 MAPBGA
MPC5748G	2 x z4 + z2	160 MHz, 80 MHz	6 MB	768 KB	192kB	32-ch.	HSM Option	18	4+6	8/8	4	x	x	USB, SDHC, I2S, CRC, MLB	96-ch. eMIOS, CTU	16	32-ch. 12-bit, 48-ch.10-bit	ASIL-B	3.3, 5	C, V, M	Nexus 3+, JTAG	176 LQFP, 256, 324 MAPBGA
MPC5747G	2 x z4 + z2	160 MHz, 80 MHz	4 MB	768 KB	192kB	32-ch.	HSM Option	18	4+6	8/8	4	x	x	USB, SDHC, I2S, CRC, MLB	96-ch. eMIOS, CTU	16	32-ch. 12-bit, 48-ch.10-bit	ASIL-B	3.3, 5	C, V, M	Nexus 3+, JTAG	176 LQFP, 256, 324 MAPBGA
MPC5746G	2 x z4 + z2	160 MHz, 80 MHz	3 MB	768 KB	192kB	32-ch.	HSM Option	18	4+6	8/8	4	x	x	USB, SDHC, I2S, CRC, MLB	96-ch. eMIOS, CTU	16	32-ch. 12-bit, 48-ch.10-bit	ASIL-B	3.3, 5	C, V, M	Nexus 3+, JTAG	176 LQFP, 256, 324 MAPBGA
MPC5748C	z4 + z2	160 MHz, 80 MHz	6 MB	768 KB	128kB	32-ch.	HSM Option	16	4+6	8/8	4	x	x	USB, SDHC, I2S, CRC	96-ch. eMIOS, CTU	16	32-ch. 12-bit, 48-ch.10-bit	ASIL-B	3.3, 5	C, V, M	Nexus 3+, JTAG	176 LQFP, 256, 324 MAPBGA
MPC5747C	z4 + z2	160 MHz, 80 MHz	4 MB	512 KB	128kB	32-ch.	HSM Option	16	4+6	8/8	4	x	x	USB, SDHC, I2S, CRC	96-ch. eMIOS, CTU	16	32-ch. 12-bit, 48-ch.10-bit	ASIL-B	3.3, 5	C, V, M	Nexus 3+, JTAG	176 LQFP, 256, 324 MAPBGA
MPC5746C	z4 + z2	160 MHz, 80 MHz	3 MB	384 KB	128kB	32-ch.	HSM Option	16	4+4	8/8	4	x	x	I2S, CRC	64-ch. eMIOS, CTU	16	16-ch. 12-bit, 32-ch.10-bit	ASIL-B	3.3, 5	C, V, M	Nexus 3+, JTAG	176 LQFP, 100, 252 MAPBGA
MPC5745C	z4 + z2	160 MHz, 80 MHz	2 MB	256 KB	128kB	32-ch.	HSM Option	16	4+4	8/8	4	x	x	I2S, CRC	64-ch. eMIOS, CTU	16	16-ch. 12-bit, 32-ch.10-bit	ASIL-B	3.3, 5	C, V, M	Nexus 3+, JTAG	176 LQFP, 100, 252 MAPBGA
MPC5744C	z4 + z2	160 MHz, 80 MHz	1.5 MB	192 KB	128kB	32-ch.	HSM Option	16	4+4	8/8	4	x	x	I2S, CRC	64-ch. eMIOS, CTU	16	16-ch. 12-bit, 32-ch.10-bit	ASIL-B	3.3, 5	C, V, M	Nexus 3+, JTAG	176 LQFP, 100, 252 MAPBGA
MPC5746B	z4	160MHz	3 MB	384 KB	128kB	32-ch.	HSM Option	12	4+4	6/6	4	x	x	I2S, CRC	64-ch. eMIOS, CTU	16	16-ch. 12-bit, 32-ch.10-bit	ASIL-B	3.3, 5	C, V, M	Nexus 3+, JTAG	176 LQFP, 100, 252 MAPBGA
MPC5745B	z4	160MHz	2 MB	256 KB	128kB	32-ch.	HSM Option	12	4+4	6/6	4	x	x	I2S, CRC	64-ch. eMIOS, CTU	16	16-ch. 12-bit, 32-ch.10-bit	ASIL-B	3.3, 5	C, V, M	Nexus 3+, JTAG	176 LQFP, 100, 252 MAPBGA
MPC5744B	z4	160MHz	1.5 MB	192 KB	128kB	32-ch.	HSM Option	12	4+4	6/6	4	x	x	I2S, CRC	64-ch. eMIOS, CTU	16	16-ch. 12-bit, 32-ch.10-bit	ASIL-B	3.3, 5	C, V, M	Nexus 3+, JTAG	176 LQFP, 100, 252 MAPBGA

i.MX Automotive Processors

Family	Device	Core Platform	Differentiator						Qualification Tier	Temperature	Package
			DSP	GPU	VPU	LCD	USB	Ethernet			
i.MX 8QuadXPlus	MIMX8QX6AVLFZAC	4 x 1.2 GHz A35 + 1 x 264 MHz M4F	Y	Y	Y	Y	USB3, USB2	2 x 1Gb (AVB)	Automotive	105C	609 FCPBGA
i.MX 8QuadXPlus	MIMX8QX5AVLFZAC	4 x 1.2 GHz A35 + 1 x 264 MHz M4F		Y	Y	Y	USB3, USB2	2 x 1Gb (AVB)	Automotive	105C	609 FCPBGA
i.MX 8QuadXPlus	MIMX8QX2AVLFZAC	4 x 1.2 GHz A35 + 1 x 264 MHz M4F	Y				USB3, USB2	2 x 1Gb (AVB)	Automotive	105C	609 FCPBGA
i.MX 8QuadXPlus	MIMX8QX1AVLFZAC	4 x 1.2 GHz A35 + 1 x 264 MHz M4F					USB3, USB2	2 x 1Gb (AVB)	Automotive	105C	609 FCPBGA
i.MX 8QuadXPlus	MIMX8QX2AVOFZAC	4 x 1.2 GHz A35 + 1 x 264 MHz M4F	Y				USB2	2 x 1Gb (AVB)	Automotive	105C	417 FCPBGA
i.MX 8QuadXPlus	MIMX8QX1AVOFZAC	4 x 1.2 GHz A35 + 1 x 264 MHz M4F					USB2	2 x 1Gb (AVB)	Automotive	105C	417 FCPBGA
i.MX 8DualXPlus	MIMX8DX6AVLFZAC	2 x 1.2 GHz A35 + 1 x 264 MHz M4F	Y	Y	Y	Y	USB3, USB2	2 x 1Gb (AVB)	Automotive	105C	609 FCPBGA
i.MX 8DualXPlus	MIMX8DX5AVLFZAC	2 x 1.2 GHz A35 + 1 x 264 MHz M4F		Y	Y	Y	USB3, USB2	2 x 1Gb (AVB)	Automotive	105C	609 FCPBGA
i.MX 8DualXPlus	MIMX8DX2AVLFZAC	2 x 1.2 GHz A35 + 1 x 264 MHz M4F	Y				USB3, USB2	2 x 1Gb (AVB)	Automotive	105C	609 FCPBGA
i.MX 8DualXPlus	MIMX8DX1AVLFZAC	2 x 1.2 GHz A35 + 1 x 264 MHz M4F					USB3, USB2	2 x 1Gb (AVB)	Automotive	105C	609 FCPBGA
i.MX 8DualXPlus	MIMX8DX2AVOFZAC	2 x 1.2 GHz A35 + 1 x 264 MHz M4F	Y				USB2	2 x 1Gb (AVB)	Automotive	105C	417 FCPBGA
i.MX 8DualXPlus	MIMX8DX1AVOFZAC	2 x 1.2 GHz A35 + 1 x 264 MHz M4F					USB2	2 x 1Gb (AVB)	Automotive	105C	417 FCPBGA
i.MX 8DualX	MIMX8UX6AVLFZAC	2 x 1.2 GHz A35 + 1 x 264 MHz M4F	Y	Y	Y	Y	2 x USB2	1Gb (AVB) + 10/100	Automotive	105C	609 FCPBGA
i.MX 8DualX	MIMX8UX5AVLFZAC	2 x 1.2 GHz A35 + 1 x 264 MHz M4F		Y	Y	Y	2 x USB2	1Gb (AVB) + 10/100	Automotive	105C	609 FCPBGA
i.MX 8DualX	MIMX8UX6AVOFZAC	2 x 1.2 GHz A35 + 1 x 264 MHz M4F	Y	Y	Y	Y	USB2	1Gb (AVB) + 10/100	Automotive	105C	417 FCPBGA
i.MX 8DualX	MIMX8UX5AVOFZAC	2 x 1.2 GHz A35 + 1 x 264 MHz M4F		Y	Y	Y	USB2	1Gb (AVB) + 10/100	Automotive	105C	417 FCPBGA
i.MX8DualXLite	MIMX8DL2A	2 x 1.2 GHz A35 + 1 x 264 MHz M4F				Y (Parallel)	2 x USB2	2 x 1Gb (1 x AVB + TSN)	Automotive	105C	388 BGA
i.MX8DualXLite	MIMX8DL1A	2 x 1.2 GHz A35 + 1 x 264 MHz M4F				Y (Parallel)	2 x USB2	2 x 1Gb (1 x AVB + TSN)	Automotive	105C	388 BGA
i.MX8SoloLite	MIMX8SL2A	1 x 1.2 GHz A35 + 1 x 264 MHz M4F				Y (Parallel)	2 x USB2	2 x 1Gb (1 x AVB + TSN)	Automotive	105C	388 BGA
i.MX8SoloLite	MIMX8SL1A	1 x 1.2 GHz A35 + 1 x 264 MHz M4F				Y (Parallel)	2 x USB2	2 x 1Gb (1 x AVB + TSN)	Automotive	105C	388 BGA
iMXRT1176	MIMXRT1176AVM8A	1 x 800 MHz M7 + 1 x 240 MHz M4F		Y		Y	2 x USB2	1Gb (AVB + TSN) + 10/100	Automotive	125C	289 MAPBGA
iMXRT1175	MIMXRT1175AVM8A	1 x 800 MHz M7 + 1 x 240 MHz M4F		Y			2 x USB2	1Gb (AVB + TSN) + 10/100	Automotive	125C	289 MAPBGA
iMXRT1171	MIMXRT1176AVM8A	1 x 800 MHz M7		Y			2 x USB2	1Gb (AVB + TSN) + 10/100	Automotive	125C	289 MAPBGA
iMXRT1172	MIMXRT1172AVM8A	1 x 800 MHz M7		Y		Y	2 x USB2	1Gb (AVB) + 10/100	Automotive	125C	289 MAPBGA

Useful Links

[nxp.com/ProductLongevity](#)

[nxp.com/SafeAssure](#)

[community.nxp.com/](#)

[nxp.com/S32](#)

[nxp.com/S32K](#)

[nxp.com/S32G](#)

[nxp.com/S32S](#)

[nxp.com/S32V](#)

[nxp.com/iMX8](#)

[nxp.com/magniV](#)

[nxp.com/autoMCU](#)

[nxp.com/autoDevKits](#)

[nxp.com/autoSWtools](#)

[www.nxp.com](#)

NXP, the NXP logo, MagniV, SafeAssure and the SafeAssure logo are trademarks of NXP B.V. All other product or service names are the property of their respective owners. Arm and Cortex are registered trademarks of Arm Limited (or its subsidiaries) in the EU and/or elsewhere. Arm926, Arm1136 and NEON are trademarks of Arm Limited (or its subsidiaries) in the EU and/or elsewhere. All rights reserved. The Power Architecture and Power.org word marks and the Power and Power.org logos and related marks are trademarks and service marks licensed by Power.org. © 2014–2019 NXP B.V.

