



ALBERT-LUDWIGS-
UNIVERSITÄT FREIBURG

Institut für Informatik
Autonome Intelligente Systeme
Prof. Dr. Wolfram Burgard

**Inferring Symbolic Actions
from Demonstrations
for Solving Manipulation Tasks
in the Real World**

Masterarbeit

Nichola V. Abdo
Februar 2012

Betreuer: PD Dr. Cyrill Stachniss
Henrik Kretzschmar

Eidesstattliche Erklärung

Hiermit erkläre ich, dass ich diese Arbeit selbständig verfasst habe, keine anderen als die angegebenen Quellen/Hilfsmittel verwendet habe und alle Stellen, die wörtlich oder sinngemäß aus veröffentlichten Schriften entnommen wurden, als solche kenntlich gemacht habe. Darüber hinaus erkläre ich, dass diese Arbeit nicht, auch nicht auszugsweise, bereits für eine andere Prüfung angefertigt wurde.

(Nichola V. Abdo)
Freiburg, den 22. Februar 2012

1 Abstract

As there are more and more cars on the streets from day to day it gets more and more complicated to find a parking space, especially in the center of the city, where one has spacial constraints on building new parking lots.

Therefore it comes in handy to map and predict the occupancy of parking spaces. This information, when integrated into planners commonly found in cell phones and GPS navigation systems, can drastically improve the experience of searching for a parking lot.

In this thesis we present an automated approach of gathering and interpreting the parking lot occupancy information using a mobile platform.

It allows for planning the route not only with respect to spatial information but also taking into account parking lot occupancy information.

The proposed approach repeatedly detects and maps the parked cars in the area of interest and estimates the occupancy probability of each found position throuout all runs. The framework is easily extendable to account for searching for occupancy on specific date or even time of day.

Furthemore, we also introduce the planner that relies on the occupancy probability of each found parking lot to find the optimal path in the means of time spent on searching for a parking lot, while considering spacial constraints like the distance to the end destination.

2 Related Works

The problem of finding a free parking lot receives more attention with the neverending growth of the cities and their population. However, most of the work is oriented on providing people with simple information on the occupancy status of a particular parking garage or parking lot. There is quite significant amount of work done in the field of detection of the parked vehicles using either a static monocular camera or a set of such cameras. In the works of Qi Wu (2006) the authors present an unsupervised system to monitor the occupied parking slots. They were using a stationary monocular camera to detect parked vehicles. In their work car detection is solely based on color, SVM is used to distinguish between occupied and free parking lots. The authors preprocess the ground truth images of the parking lots and search for color differences between actual measurements and the ground truth measured for an empty parking lot.

Another work True is showing a similar approach. Alike with the previous paper, an unsupervised system for parking lots detection is presented. The author is using an overhead static camera. He uses human-labeled parking lots' positions to define the spacial arrangement of the parking lots. The author distributes chrominance channels of the images from the camera into bins, storing a histogram of these values for each parking lot. The histograms are then classified into free vs. occupied using either k-nearest neighbors or SVM. He also presents a variant of the work based on classifying color patches that are situated around corner detector's regions of interest, this however proves to be not sufficiently efficient.

The authors of the next paper R. Yusnita (2012) proposed a system to detect occupancy status of the parking lots of the indoor parkings. They are using an overhead, strictly vertically oriented camera. The parking lots are manually labeled by a marker that states their occupancy state. For each query parking lot the authors produce a binary image which is then analyzed to find if the parking slot is empty or occupied. This process is carried out by comparing the shape of the detection with the shape of the prior that reassembles the circle shape of the marker drawn on the floor of the parking slot.

Another work that utilizes a static monocular camera Marc Tschentscher shows a comparison of several different features for occupancy analysis. As in the works presented above the authors of this paper have an overhead camera pointing to the parking lots, which are manually labeled in the images. They compare a couple of visual features such as color histograms, gradient histograms, difference of gaussian histograms and Haar features. They also explore different methods for training a classifier such as k-nearest neighbors, linear discriminant analysis and SVM. They achieved detection rate of 98%

while performing in real time.

In another work, Ching-Chun Huang (a), Ching-Chun Huang (b), using a static monocular overhead camera and a 3-layer Bayesian hierarchical framework (BHF) the authors of the paper specifically addressed the challenges of vacant parking space inference that come from dramatic luminance variations, shadow effect, perspective distortion, and the inter-occlusion among vehicles showing great detection rates.

The authors of these papers K.Fintzel, F. Abad here modeling free parking lots locally based on the 3D sonar sensor mounted on the car with conjunction with a visual 3d estimation setup based on the tracking of points in the images seen from different angles. In these papers they used the ultrasonic sensor and 3D vision sensor that detects points of interest on the bodies of the parked cars and tracking them compare their occupancy positions from different points of view. The cars are then modeled by vertical planes of two different orientations that are fit into the 3D data from the sensors. Empty parking lots are then modeled by empty spaces between the planes.

The authors of this paper H. Ichihashi have developed a system that uses a system of overhead cameras for occupancy detection in indoor and outdoor scenes. The focus is put on the clustering algorithms, showing that the performance of the detector based on the fuzzy c-means (FCM) clustering and the hyperparameter tuning by particle swarm optimization (PSO) significantly outperforms SVM both in speed and accuracy of detection.

The authors of this paper Vladimir Coric move focus from static overhead cameras on the developed parking lot to estimating parking lots for on-street parking. In this paper they use an ultra-sonic sensor mounted to the side of the car to estimate the parking possibilities along particular streets. Uses a straightforward threshold method to distinguish between free and occupied space. They also make use of an idea that the more time a car was observed in a place the more it is likely that the space occupied by this car is a valid parking spot. As a result all measurements were incorporated with the GPS measurements to form a global map of parked cars, which the authors used to detect wrongly parked cars.

This paper Matthias R. Schmid and Wuensche (2012) utilizes an on-board short-range radar. The measurements from three radars are stored into a 3D occupancy grid, that represents the local surroundings of the car. Free parking lots are then detected on the given grid by analyzing cells on curb and on other parked cars. This provides relatively precise estimation of the parking lot in 3D.

The authors of this paper Jae Kyu Suhr (2010) proposed a system that is able to detect parking lots from 3D data acquired from stereo-based multiview 3D reconstruction. The authors select point correspondences using a de-rotation-based method and mosaic 3D structures by estimating similarity transformation. While relying solely on this information and not using the odometry they were able to achieve reliable results with the detection rate of 90%

The authors of this paper Jae Kyu Suhr (2013) proposed a system to a fully automatical

detection of parking slots markings. They are utilizing a tree structure performing a bottom-up and a top-down approach in order to classify all parking slots as such and leave out all false detections.

3 Background

In order to be able to solve the given problem we will have to rely on several well known approaches, which I will briefly introduce in this chapter.

3.1 Occupancy Grids

In this thesis we partly make use of the grid maps to model the environment with respect to modeling the probability of cars to be present in the particular part of the world. Grid maps partition the space into a grid of rectangular cells. Each grid contains information about the corresponding area in the environment. In this thesis we make use of one particular realization of grid maps - the occupancy grid maps. Occupancy grid maps assume that each grid cell is either occupied by an obstacle or free. In our case, each cell therefore stores the probability that the particular cell is occupied by a car. The occupancy grid maps are an efficient approach for representing uncertainty. Grid maps allow for detailed representation of an environment without a predefined feature extractor. As they have the ability to represent occupied space, empty space and unknown (unobserved) space, grid maps are well suited for tasks such as path-planning, obstacle avoidance and exploration. In contrast to most representations based on features, grid maps offer constant time access to cells. However, grid maps suffer from discretization errors.

3.2 Object Detection

In this thesis we made extensive use of object detection to be able to detect cars from visual information. Based on the work of N. Dalal we made use of the histograms of oriented gradients (HOG) features placed in a dense grid on the query images. The histograms from the training data, describing positive and negative sets are then divided into positive and negative groups via support vector machines (SVM). The HOG/SIFT representation has several advantages. It captures edge or gradient structure that is very characteristic of local shape, and it does so in a local representation with an easily controllable degree of invariance to local geometric and photometric transformations: translations or rotations make little difference if they are much smaller than the local spatial or orientation bin size.

3.3 Markov Decision Processes

Markov decision processes are used to carry out complex decisions in a fully observable environment with a stochastic transition model. A specification of the outcome probabilities for each action in each possible state is called a transition model, we will use $T(s, a, s')$ to denote the probability of reaching state s' if and action a is carried out in state s . The transitions in the model are assumed to be Markovian. That is, the probability of reaching s' from s depends only on s and not on the history of earlier states. We also need to define the reward function $R(s, a, s')$, that defines a reward for reaching state s' from state s carrying out action a . Overall, the MDP is defined by three components:

- Initial state: S_0
- Transition Model: $T(s, a, s')$
- Reward Function: $R(s, a, s')$

These components allow us to define the utility function, which is a measure of how good the state is in the long run:

$$U^\pi(s) = E \left[\sum_{t=0}^{\infty} \gamma^t R(s_t) \mid \pi, s_0 = s \right] \quad (3.1)$$

The optimal action is then chosen using the Maximum Utility Principle, that is, choose: the action that maximizes the expected utility of the subsequent state:

$$\pi^*(s) = \operatorname{argmax}_a \sum_{s'} T(s, a, s') U(s') \quad (3.2)$$

Provided, that the utility of the state is the expected sum of discounted rewards from that point onwards, we can define the utility via Bellman Equation:

$$U(s) = R(s) + \gamma \max_a \sum_{s'} T(s, a, s') U(s') \quad (3.3)$$

4 Our Approach

4.1 Overview

Unlike the works presented in the related works we were interested in integrating all stages of solving the problem such as perception, mapping model and action planning into one system. We further present an integrated framework for carrying out the task of detecting the parked autos, integrating occupancy information into a model that is suitable for further planning and planning for actions itself, when carrying out a decision of finding an unoccupied parking lot. We will further describe the different steps that we have taken on this road as well as the connections between them.

4.2 Perception

In order to detect the positions of the parked cars we first needed to find a way for visual recognition of autos. To achieve this goal we looked at a number of approaches for object detection and classification.

- Haar-cascade detection as presented by Paul Viola (2001)
- Local binary patterns as presented by _____
- HOG descriptor based classifier by Dalal and Triggs (2005)

need a citation here

After analyzing the good and the bad sides of these methods we decided to go with the HOG-based method as it outperforms the Haar-based method while providing us with shorter training times when comparing to the local binary patterns based methods.

4.3 Model

4.4 Action Planning

Bibliography

- Sheng-Jyh Wang Ching-Chun Huang. A hierarchical bayesian generation framework for vacant parking space detection. *IEEE Transactions on Circuits and Systems for Video Technology*, a.
- Yao-Jen Chang Tsuhan Chen Ching-Chun Huang, Sheng-Jyh Wang. A bayesian hierarchical detection framework for parking space detection. b.
- Navneet Dalal and Bill Triggs. Histograms of oriented gradients for human detection. *Computer Vision and Pattern Recognition*, 2005.
- S. Wybo S. Bougnoux C. Vestri T. Kakinami F. Abad, R. Bendahan. Parking space detection.
- M. Fujiyoshi A. Notsu K. Honda H. Ichihashi, T. Katada. Improvement in the performance of camera based vehicle detector for parking lot.
- Ho Gi Jung Jae Kyu Suhr. Full-automatic recognition of various parking slot markings using a hierarchical tree structure. *Optical Engineering*, 2013.
- Kwanghyuk Bae Jaihie Kim Jae Kyu Suhr, Ho Gi Jung. Automatic free parking space detection by using motion stereo-based 3d reconstruction. *Machine Vision and Applications*, 2010.
- C.Vestri S.Bougnoux T.Kakinami K.Fintzel, R.Bendahan. 3d parking assistant system.
- Marcel Neuhauser Marc Tschentscher. Video-based parking space detection.
- J. Dickmann F. von Hundelshausen Matthias R. Schmid, S. Ates and H.-J. Wuensche. Parking space detection with hierarchical dynamic occupancy grids. *IEEE Intelligent Vehicles Symposium*, 2012.
- Michael Jones Paul Viola. Rapid object detection using a boosted cascade of simple features. *Conference on Computer Vision and Pattern Recognition*, 2001.
- Yi Zhang Qi Wu. Parking lots space detection. 2006.
- Norazwinawati Basharrudin R. Yusnita, Fariza Norbaya. Intelligent parking space detection system based on image processing. *International Journal of Innovation, Management and Technology*, 3rd, 2012.

Nicholas True. Vacant parking space detection in static images.

Marco Gruteser Vladimir Coric. Crowdsensing maps of on-street parking spaces.