

# .NET App Dev Hands-On Lab

## Razor Pages Lab 7 – Custom Validation

This optional lab walks you through creating custom validation attributes and the related client-side scripts. Prior to starting this lab, you must have completed Razor Pages Lab 6.

### Part 1: Create the Server-Side validation attributes

- Add the following global using statements to the `GlobalUsings.cs` file in the `AutoLot.Web` project:

```
global using System.ComponentModel.DataAnnotations;
global using System.Reflection;
global using System.ComponentModel;
global using Microsoft.AspNetCore.Mvc.ModelBinding.Validation;
```

#### Step 1: Create the `MustBeGreaterThanZeroAttribute` attribute

- Create a new folder in the `AutoLot.Web` project named `Validation`. Add a new class named `MustBeGreaterThanZeroAttribute.cs`. Make the class public, inherit from `ValidationAttribute`, and implement `IClientModelValidator`. Add a primary constructor and a secondary constructor:

```
namespace AutoLot.Web.Validation;
public class MustBeGreaterThanZeroAttribute(string errorMessage)
    : ValidationAttribute(errorMessage), IClientModelValidator
{
    public MustBeGreaterThanZeroAttribute() : this("{0} must be greater than 0") { }
    public void AddValidation(ClientModelValidationContext context)
    {
    }
}
```

- Override the `FormatErrorMessage` method to properly format the `ErrorMessageString` (which is a property on the base `ValidationAttribute` class)

```
public override string FormatErrorMessage(string name) => string.Format(ErrorMessageString, name);
```

- Override the `IsValid` method to test if the value is greater than zero. This is used for server-side processing:

```
protected override ValidationResult IsValid(object value, ValidationContext validationContext)
{
    if (value is not int intValue)
    {
        return new ValidationResult(FormatErrorMessage(validationContext.DisplayName));
    }
    return intValue <= 0
        ? new ValidationResult(FormatErrorMessage(validationContext.DisplayName))
        : ValidationResult.Success;
}
```

- Implement the AddValidation method. This method is used when generating the client-side implementation of the property.

```
public void AddValidation(ClientModelValidationContext context)
{
    string propertyDisplayName =
        context.ModelMetadata.DisplayName ?? context.ModelMetadata.PropertyName;
    string errorMessage = FormatErrorMessage(propertyDisplayName);
    context.Attributes.Add("data-val-greaterthanzero", errorMessage);
}
```

- Add the following global using statements to the GlobalUsings.cs file in the AutoLot.Web project:

```
global using AutoLot.Web.Validation;
```

## Step 2: Create the MustNotBeGreaterThanAttribute attribute

- Add a new class named MustNotBeGreaterThanAttribute.cs. Make the class public, inherit from ValidationAttribute, and implement IClientModelValidator. Add the AttributeUsage attribute to the class so it targets properties and can be used more than once in a class, and add a primary constructor and another constructor:

```
namespace AutoLot.Web.Validation;
[AttributeUsage(AttributeTargets.Property, AllowMultiple = true)]
public class MustNotBeGreaterThanAttribute(
    string otherPropertyName, string errorMessage, string prefix)
    : ValidationAttribute(errorMessage), IClientModelValidator
{
    readonly string _otherPropertyName = otherPropertyName;
    string _otherPropertyDisplayName = otherPropertyName;
    readonly string _prefix = prefix;
    public MustNotBeGreaterThanAttribute(string otherPropertyName, string prefix = "")
        : this(otherPropertyName, "{0} must not be greater than {1}", prefix) { }
    public void AddValidation(ClientModelValidationContext context)
    {
    }
}
```

- Override the FormatErrorMessage method to format the ErrorMessageString properly:

```
public override string FormatErrorMessage(string name)
    => string.Format(ErrorMessageString, name, _otherPropertyDisplayName);
```

- Add the SetOtherPropertyName method, which will get the Display property of the other property.

```
internal void SetOtherPropertyName(PropertyInfo otherPropertyInfo)
{
    _otherPropertyDisplayName =
        otherPropertyInfo.GetCustomAttributes<DisplayAttribute>().FirstOrDefault()?.Name
        ?? otherPropertyInfo.GetCustomAttributes<DisplayNameAttribute>().FirstOrDefault()?.DisplayName
        ?? _otherPropertyName;
}
```

- Override the IsValid method to test if the value is less than or equal to the other property. Once again, this is used for server-side processing:

```
protected override ValidationResult IsValid(object value, ValidationContext validationContext)
{
    var otherPropertyInfo = validationContext.ObjectType.GetProperty(_otherPropertyName);
    if (otherPropertyInfo == null)
    {
        return new ValidationResult("Unable to validate property. Please contact support");
    }
    SetOtherPropertyName(otherPropertyInfo);
    if (value is not int intValue)
    {
        return new ValidationResult(FormatErrorMessage(validationContext.DisplayName));
    }
    var otherPropObjectValue = otherPropertyInfo.GetValue(validationContext.ObjectInstance, null);
    if (otherPropObjectValue is not int otherValue)
    {
        return new ValidationResult(FormatErrorMessage(validationContext.DisplayName));
    }
    return intValue > otherValue
        ? new ValidationResult(FormatErrorMessage(validationContext.DisplayName))
        : ValidationResult.Success;
}
```

- Implement the AddValidation method. This method uses a helper method to get the Display attribute (if it exists) or the straight property name of the other property. This method is used when generating the client-side implementation of the property.

```
public void AddValidation(ClientModelValidationContext context)
{
    string propertyDisplayName = context.ModelMetadata.GetDisplayName();
    var propertyInfo = context.ModelMetadata.ContainerType.GetProperty(_otherPropertyName);
    SetOtherPropertyName(propertyInfo);
    string errorMessage = FormatErrorMessage(propertyDisplayName);
    context.Attributes.Add("data-val-notgreaterthan", errorMessage);
    context.Attributes.Add("data-val-notgreaterthan-otherpropertyname", _otherPropertyName);
    context.Attributes.Add("data-val-notgreaterthan-prefix", _prefix);
}
```

## Part 2: Create the Client-Side validation scripts

### Step 1: Create the Validators

- Add a new folder named `validations` under the `wwwroot/js` folder. Add a new JavaScript file named `validators.js` in the new folder. Add the validator method for the `GreaterThanZero` validation. This name must match the name from the `AddValidation` method in the C# class. Also add the adapter. The `rules` property is simply set to `true` to enable validation, and the message is message from the `AddValidation` method:

```
$.validator.addMethod("greaterthanzero", function (value, element, params) {
    return value > 0;
});
$.validator.unobtrusive.adapters.add("greaterthanzero", function (options) {
    options.rules["greaterthanzero"] = true;
    options.messages["greaterthanzero"] = options.message;
});
```

- Add the validator method for the `NotGreaterThan` validation. As with the previous example, the name must match the name from the `AddValidation` method. Also add the adapter:

```
$.validator.addMethod("notgreaterthan", function (value, element, params) {
    return +value <= +$(params).val();
});
$.validator.unobtrusive.adapters.add("notgreaterthan", ["otherpropertyname", "prefix"], function (options) {
    options.rules["notgreaterthan"] = "#" + options.params.prefix +
options.params.otherpropertyname;
    options.messages["notgreaterthan"] = options.message;
});
```

### Step 2: Create the Error Formatter code

- Create a new JavaScript file named `errorFormatting.js` in the `validations` folder. Update the code to match the following:

```
$.validator.setDefaults({
    highlight: function (element, errorClass, validClass) {
        if (element.type === "radio") {
            this.findByName(element.name).addClass(errorClass).removeClass(validClass);
        } else {
            $(element).addClass(errorClass).removeClass(validClass);
            $(element).closest('.form-group').addClass('has-error');
        }
    },
    unhighlight: function (element, errorClass, validClass) {
        if (element.type === "radio") {
            this.findByName(element.name).removeClass(errorClass).addClass(validClass);
        } else {
            $(element).removeClass(errorClass).addClass(validClass);
            $(element).closest('.form-group').removeClass('has-error');
        }
    }
});
```

## Step 3: Minify the JavaScript Files

To minimize specific files or to create bundles, add configuration options into the `AddWebOptimizer` method in the `Program.cs` file.

- Use `AddJavaScriptBundle` to bundle files. The first argument is the bundle name, next, are the files to be bundled:

```
builder.Services.AddWebOptimizer(options =>
{
    options.AddJavaScriptBundle("js/validations/validationCode.js", "js/validations/**/*.js");
    //This is another format to bundle and minify the files
    //options.AddJavaScriptBundle("js/validations/validationCode.js",
    // "js/validations/validators.js", "js/validations/errorFormatting.js");
});
```

## Part 3: Update the `_ValidationScriptsPartial.cshtml`

- Open `Views\Shared\_ValidationScriptsPartial.cshtml`. Add the following at the end of the development block:

```
<script src="~/js/validations/validators.js" asp-append-version="true"></script>
<script src="~/js/validations/errorFormatting.js" asp-append-version="true"></script>
```

- Open `Views\Shared\_ValidationScriptsPartial.cshtml`. Add the following at the end of the non-development block:

```
<script src="~/js/validations/validationCode.js"></script>
```

## Part 4: Use the Attribute

### Step 1: Create the `AddToCartViewModel`

- Create a new folder named `Models` in the `AutoLot.Web` project. In this folder, add a new class named `AddToCartViewModel` and update it to the following:

```
namespace AutoLot.Web.Models;

public class AddToCartViewModel
{
    public int Id { get; set; }
    [Display(Name="Stock Quantity")]
    public int StockQuantity { get; set; }
    public int ItemId { get; set; }
    [Required, MustBeGreaterThanZero, MustNotBeGreaterThan(nameof(StockQuantity))]
    public int Quantity { get; set; }
}
```

- Add the following global using statements to the `GlobalUsings.cs` file in the `AutoLot.Web` project:

```
global using AutoLot.Web.Models;
```

## Step 2: Create the Validation Page

- Create a new Razor Page named Validation in the Pages directory, and update the code behind to the following:

```
namespace AutoLot.Web.Pages;
public class ValidationModel : PageModel
{
    [ViewData]
    public string Title => "Validation Example";
    [BindProperty]
    public AddToCartViewModel Entity { get; set; }
    public void OnGet()
    {
        Entity = new AddToCartViewModel
        {
            Id = 1,
            ItemId = 1,
            StockQuantity = 2,
            Quantity = 0
        };
    }
    public IActionResult OnPost()
    {
        if (!ModelState.IsValid)
        {
            return Page();
        }
        return RedirectToPage("Validation");
    }
}
```

- Next, update the markup to the following:

```
@page
@model AutoLot.Web.Pages.ValidationModel
<h1>Validation</h1>
<h4>Add To Cart</h4><hr />
<div class="row">
  <div class="col-md-4">
    <form asp-page="/Validation">
      <div asp-validation-summary="ModelOnly" class="text-danger"></div>
      <div>
        <label asp-for="Entity.Id" class="col-form-label"></label>
        <input asp-for="Entity.Id" class="form-control" />
        <span asp-validation-for="Entity.Id" class="text-danger"></span>
      </div>
      <div><label asp-for="Entity.StockQuantity" class="col-form-label"></label>
        <input asp-for="Entity.StockQuantity" class="form-control" />
        <span asp-validation-for="Entity.StockQuantity" class="text-danger"></span>
      </div>
      <div><label asp-for="Entity.ItemId" class="col-form-label"></label>
        <input asp-for="Entity.ItemId" class="form-control" />
        <span asp-validation-for="Entity.ItemId" class="text-danger"></span>
      </div>
      <div>
        <label asp-for="Entity.Quantity" class="col-form-label"></label>
        <input asp-for="Entity.Quantity" class="form-control" />
        <span asp-validation-for="Entity.Quantity" class="text-danger"></span>
      </div>
      <div style="margin-top:5px"><input type="submit" value="Save" class="btn btn-primary" />
      </div>
    </form>
  </div>
</div>
@section Scripts {
  @{await Html.RenderPartialAsync("_ValidationScriptsPartial");}
}
```

### Step 3: Update the \_Menu Partial

- Add the following menu item to the \_Menu.cshtml partial:

```
<li class="nav-item">
  <a class="nav-link text-dark" asp-area="" asp-page="/Validation" title="Validation
Example">Validation<i class="fas fa-check"></i></a>
</li>
```

## Summary

This lab added custom validation attributes and demonstrated how to use them.

## Next Steps

The next lab creates an admin area for Make maintenance.