The frontend currently uses the following fields:
id, name, phone, ward, status

-Common Headers (All APIs)
Authorization: Bearer <token>
Content-Type: application/json

1️⃣ Get Councillors List
Endpoint
GET /admin/councillors

Success Response (200)

```
{
  "success": true,
  "message": "Councillors fetched successfully",
  "data": [
    {
      "id": 1,
      "name": "Rajesh Sharma",
      "phone": "+91 9876543210",
      "ward": "Ward 15",
      "status": "active"
    },
    {
```

```
    "id": 2,
    "name": "Priya Desai",
    "phone": "+91 9876543211",
    "ward": "Ward 12",
    "status": "inactive"
  }
 ]
}
```


2️⃣ Create Councillor

Endpoint

POST /admin/councillors

Description

Create a new councillor from Super Admin panel.

Request Body


```
{
  "name": "Amit Kumar",
  "phone": "+91 9876543212",
  "ward": "Ward 8"
}
```


Success Response (201)

{
  "success": true,
  "message": "Councillor created successfully",
  "data": {
    "id": 3,
    "name": "Amit Kumar",
    "phone": "+91 9876543212",
    "ward": "Ward 8",
    "status": "active"
  }
}

3️⃣ Update Councillor (Edit)

Endpoint

PUT /admin/councillors/:id

Description

Update councillor details from edit modal.

Request Body

{
  "name": "Rajesh Sharma",
  "phone": "+91 9876549999",

"ward": "Ward 20"
}

Success Response (200)

{
"success": true,
"message": "Councillor updated successfully"
}

-Status Values (Used in UI)

active

inactive