

Detailed Analysis of Selected Papers

Paper 1: Humanity Lifeline: A Resilient Communication and Sensor Network Framework for Disaster Response

Authors: Ozgun Pinarer, Omer Komili

Year: 2025

Source: IEEE Access (Journal)

A. Communication Architecture

Aspect	Details
Technology	Hybrid: BLE + LoRa + LoRaWAN
Gateway or Decentralized?	Hybrid: LifeLink devices aggregate data via BLE and transmit to LoRa-Router-Gateways. Gateways connect to cloud via LoRaWAN OR use peer-to-peer LoRa mesh when cloud unavailable
Reliance on Cellular Backhaul?	No - System is infrastructure-independent. Can operate in pure peer-to-peer mode without any cellular or internet connectivity

B. Application Domain

Domain	Applicability
Disaster Recovery	✓ Primary focus - tested for post-disaster communication
Trekking Safety	X Not specifically mentioned
Vehicular Communication	X Not applicable
Emergency Alert Systems	✓ Yes - emergency messaging from victims to responders
IoT Monitoring	✓ Yes - environmental and location monitoring

C. Range and Topology

Parameter	Details
Topology	Hybrid: Star (BLE to LifeLink) + Mesh (LoRa peer-to-peer between gateways) + Star (LoRaWAN to cloud)
Multi-hop Capability	✓ Yes - LoRa-Router-Gateways can relay messages peer-to-peer when LoRaWAN unavailable
Maximum Tested Range	• BLE: 30m (urban), 70m (rural) • LoRa: 5km (urban), 15km (rural) • Test area: 5km × 5km in Istanbul
Scalability Limits	Tested with: 100 LifeLinks, 500 mobile phones, 5 gateways. Performance degrades beyond 1000 users (latency ↑, data loss ↑)

D. Latency and Reliability

Metric	Value
End-to-End Delay	• Average latency: 1.5 seconds • Multi-hop (4 hops): 300 ms latency
Packet Delivery Success Rate	• Overall: 99% successful message delivery • High traffic: 98.8% success • During disruptions: 99.8% data accuracy
Message Prioritization	Uses QoS Ranking (QRank) field in LoRa frame structure to classify priority vs. non-priority data

E. Intelligence Placement

Aspect	Assessment
Purely Data Relay?	No - Includes data aggregation, processing, and adaptive mechanisms
Local Processing/AI?	Limited - Uses AWS cloud for processing and analysis. Some local data aggregation at LifeLink level
Deterministic Safety Logic?	No - System focuses on reliable data transport, not autonomous safety decision-making

F. Identified Limitations (From Paper)

Limitation	Description
GSM/Cloud Dependence	Can operate without cloud via peer-to-peer mode, but full functionality requires cloud connectivity
Hardware Constraints	Custom hardware required (LifeLinks, gateways) - not integrated into existing devices
Scalability Challenges	Performance degrades with >1000 concurrent users
Energy Consumption	Battery life limited to 24-72 hours depending on usage
Interference Susceptibility	Urban/industrial environments show degraded performance

G. Expected Gaps Analysis

Gap	Present?	Notes
Integration with wearable sensors	 No	Uses stationary LifeLinks, not wearable/helmet-integrated

Gap	Present?	Notes
Fatigue/physiological awareness	✗ No	No monitoring of user vital signs or fatigue
Voice-based emergency detection	✗ No	Predefined text messages only
Hybrid online–offline adaptation	✓ Yes	Seamlessly switches between LoRaWAN (online) and peer-to-peer LoRa (offline)
ID-based secure addressing	✓ Yes	Uses AES CTR encryption and unique node IDs (28-bit)
Deterministic emergency prioritization	✗ No	No autonomous prioritization logic at edge

H. Summary of Gaps Supporting Your Novelty

Opportunity for Helmet-Centric System:

While Humanity Lifeline provides a robust hybrid communication infrastructure, it is designed around **stationary infrastructure nodes** (LifeLinks) rather than **personal wearable devices**. The system lacks:

- Integration with **rider's helmet** or wearable sensors
- **Physiological monitoring** (fatigue, pulse, impact detection)
- **Voice-activated emergency detection**
- **Edge-based deterministic safety logic**

Your proposed helmet-centric system can address these gaps by embedding communication directly into the rider's gear, enabling **context-aware emergency detection** and **autonomous safety responses** without relying on external stationary nodes.

Paper 2: A LoRa based Emergency Communication Device for Disaster Response

Authors: Pradeep Kumar R, Diliban Selvarathinam K P, Dr. C.N. Gnanaprakasam

Year: 2025

Source: International Conference on Communications (ICTCIM)

A. Communication Architecture

Aspect	Details
Technology	LoRa + LoRaWAN with Arduino hardware
Gateway or Decentralized?	Gateway-based: End devices → LoRaWAN network → Web interface/app
Reliance on Cellular Backhaul?	No - Uses LoRaWAN independent of cellular; receiver has WiFi for web interface but system functions without it

B. Application Domain

Domain	Applicability
Disaster Recovery	✓ Primary focus - search and rescue operations
Trekking Safety	✓ Applicable for remote area trekking
Vehicular Communication	✗ Not applicable
Emergency Alert Systems	✓ Yes - SOS messaging with GPS
IoT Monitoring	✓ Yes - oxygen level monitoring, GPS tracking

C. Range and Topology

Parameter	Details
Topology	Star (via LoRaWAN)
Multi-hop Capability	✗ No - Direct transmission to gateway; no mesh/routing protocol implemented
Maximum Tested Range	Not explicitly stated; LoRa typically 5-15km depending on environment
Scalability Limits	Not addressed - single device prototype focus

D. Latency and Reliability

Metric	Value
End-to-End Delay	Not explicitly measured; focuses on successful transmission
Packet Delivery Success Rate	Demonstrated successful SOS message transmission; quantitative PDR not provided
Message Prioritization	✗ None mentioned - basic SOS and pre-formatted messages

E. Intelligence Placement

Aspect	Assessment
Purely Data Relay?	✓ Yes - Device collects GPS + oxygen data and relays pre-formatted messages
Local Processing/AI?	✗ No - Arduino processes sensor data but no AI/learning

Aspect	Assessment
Deterministic Safety Logic?	✗ No - User must manually select and send messages

F. Identified Limitations (From Paper)

Limitation	Description
Urban Obstruction	LoRa signal range limited in dense urban environments with obstructions
Power Sustainability	Hand-crank generator may not be feasible for extended high-stress operations
Bandwidth Limitation	LoRaWAN's limited data rate prevents multimedia communication
No Mesh Support	Single-hop only; no alternative paths if gateway unreachable
Manual Operation	Requires user to select and send messages - not automatic

G. Expected Gaps Analysis

Gap	Present?	Notes
Integration with wearable sensors	✗ No	Standalone device with oxygen sensor only
Fatigue/physiological awareness	✗ No	No monitoring of user vital signs
Voice-based emergency detection	✗ No	Button-press activation only
Hybrid online–offline adaptation	✗ No	LoRaWAN-only; no fallback mesh mode

Gap	Present?	Notes
ID-based secure addressing	✗ No	Not addressed in paper
Deterministic emergency prioritization	✗ No	No autonomous logic

H. Summary of Gaps Supporting Your Novelty

Opportunity for Helmet-Centric System:

This device requires **manual activation** by the user - problematic if the user is unconscious or incapacitated. Your proposed helmet system can:

- **Automatically detect** crashes/falls via embedded sensors
 - Monitor **physiological state** (fatigue, pulse)
 - Trigger **autonomous SOS** without user intervention
 - Integrate seamlessly into **existing gear** rather than requiring separate device
-

Paper 3: R-AODV: Reverse Ad-Hoc On-Demand Distance Vector Routing Algorithm With LoRa Mesh Based for Emergency Alert System

Authors: Jirawat Thaenthong, Taiwit Pimsen, Kemmathad Chidchuea

Year: 2023

Source: International Conference on Information Technology and Electrical Engineering (ICITEE)

A. Communication Architecture

Aspect	Details
Technology	LoRa Mesh
Gateway or Decentralized?	Decentralized mesh with gateway as destination. Nodes relay messages using R-AODV routing algorithm

Aspect	Details
Reliance on Cellular Backhaul?	No - Completely infrastructure-independent mesh network
B. Application Domain	
Domain	Applicability
Disaster Recovery	✓ Yes - emergency notification when networks fail
Trekking Safety	✓ Applicable for remote areas
Vehicular Communication	✗ Not specifically addressed
Emergency Alert Systems	✓ Primary focus - emergency alerts from buildings, elevators, etc.
IoT Monitoring	✗ No - alert-only, no environmental monitoring
C. Range and Topology	
Parameter	Details
Topology	Mesh - all nodes can relay
Multi-hop Capability	✓ Yes - up to 4 hops tested (230m/330m distance)
Maximum Tested Range	• Point-to-point: 100m • Multi-hop: 230m (2-3 hops) • With node failure: 330m (alternative route)
Scalability Limits	Tested with 4 nodes (gateway + 3 nodes). Not tested at scale

D. Latency and Reliability

Metric	Value
End-to-End Delay	• Point-to-point: 0.82s • Multi-hop (normal): 1.54s • Multi-hop (node failure): 11.65s (route rediscovery)
Packet Delivery Success Rate	Successful transmission demonstrated; quantitative PDR not provided
Message Prioritization	R-AODV algorithm prioritizes shortest path; nodes periodically broadcast "ready" messages to maintain active routes

E. Intelligence Placement

Aspect	Assessment
Purely Data Relay?	No - Network-layer intelligence in R-AODV routing algorithm
Local Processing/AI?	Limited - Nodes maintain routing tables, select shortest path, detect node failures
Deterministic Safety Logic?	No - Routing intelligence only; no application-layer safety logic

F. Identified Limitations (From Paper)

Limitation	Description
Power Consumption	High communication loads reduce node service time
Route Discovery Delay	Node failure causes significant delay (11.65s) while new route discovered

Limitation	Description
Limited Scale Testing	Tested only with small network (4 nodes)
No Multiple Gateway Support	Single gateway point of failure (acknowledged as future work)
Low Data Rate	Suitable only for alerts, not multimedia

G. Expected Gaps Analysis

Gap	Present?	Notes
Integration with wearable sensors	✗ No	Fixed nodes only
Fatigue/physiological awareness	✗ No	No user monitoring
Voice-based emergency detection	✗ No	Button-triggered alerts only
Hybrid online–offline adaptation	✓ Yes	Mesh operates entirely offline
ID-based secure addressing	✗ No	Not addressed
Deterministic emergency prioritization	✗ No	No priority levels for emergencies

H. Summary of Gaps Supporting Your Novelty

Opportunity for Helmet-Centric System:

R-AODV provides excellent **decentralized mesh routing** but:

- Nodes are **stationary infrastructure** (building-mounted)
- Alerts are **user-triggered** (button press)
- No **sensor integration** or context awareness

Your helmet system can leverage similar mesh routing while adding:

- **Mobile nodes** (riders moving through environment)
- **Automatic event detection** (crashes, falls)
- **Physiological monitoring** for fatigue/health status
- **Prioritized alerts** based on severity

Paper 4: A Crash Response System using LoRa-based V2X Communications

Authors: Bruno Carneiro, Daniel Macedo Batista, Roberto Hirata Junior, Kifayat Ullah

Year: 2023

Source: International Workshop on Intelligent Transportation and Autonomous Vehicles Technologies (ITAVT)

A. Communication Architecture

Aspect	Details
Technology	LoRa (physical layer only - not LoRaWAN)
Gateway or Decentralized?	Purely decentralized - broadcast-based multi-hop routing between vehicles
Reliance on Cellular Backhaul?	No - Completely infrastructure-independent V2X communication

B. Application Domain

Domain	Applicability
Disaster Recovery	X Not specifically
Trekking Safety	X Not applicable
Vehicular Communication	✓ Primary focus - V2X crash response

Domain	Applicability
Emergency Alert Systems	✓ Yes - automatic crash notification
IoT Monitoring	✗ No

C. Range and Topology

Parameter	Details
Topology	Mesh via broadcast flooding
Multi-hop Capability	✓ Yes - messages propagate through intermediate vehicles
Maximum Tested Range	Simulated area: 10km × 10km ; messages successfully transmitted across several km
Scalability Limits	Tested: 10 to 320 nodes. PDR improves with density; latency increases with density

D. Latency and Reliability

Metric	Value
End-to-End Delay	• Low density (10 nodes): ~0.02s • High density (320 nodes): ~0.14s • Average across all densities: minimal latency (<150ms)
Packet Delivery Success Rate	• 10 nodes: ~60% • 320 nodes: ~95% • Density critical factor - more vehicles = better delivery

Metric	Value
Message Prioritization	✗ None - simple broadcast flooding; no prioritization mechanism
E. Intelligence Placement	
Aspect	Assessment
Purely Data Relay?	✓ Yes - Nodes simply rebroadcast received beacons
Local Processing/AI?	✗ No - No intelligence; loop prevention via hop count and attempts fields
Deterministic Safety Logic?	Limited - Message format includes event type, location, people count, speed - but no autonomous decision-making
F. Identified Limitations (From Paper)	
Limitation	Description
Interference Issues	Pure LoRa uses ALOHA protocol; collisions increase with density
No Authentication/Security	Messages unencrypted; vulnerable to spoofing/manipulation
Static Node Assumption	Simulation used static nodes; mobility/Doppler shift not modeled
Rural Area Limitation	Requires vehicle density; sparse rural areas may have no connectivity

Limitation	Description
No Acknowledgment Mechanism	Caller doesn't know if message reached responder

G. Expected Gaps Analysis

Gap	Present?	Notes
Integration with wearable sensors	✗ No	Vehicle-mounted only
Fatigue/physiological awareness	✗ No	No rider monitoring
Voice-based emergency detection	✗ No	Automatic crash detection (assumed), but no voice
Hybrid online–offline adaptation	✓ Yes	Pure offline operation
ID-based secure addressing	✗ No	No security/authentication
Deterministic emergency prioritization	✗ No	All events equal

H. Summary of Gaps Supporting Your Novelty

Opportunity for Helmet-Centric System:

This V2X system is **vehicle-centric** not **rider-centric**. It assumes:

- Vehicle detects crash (airbag sensors, etc.)
- Vehicle has power and connectivity
- No monitoring of **rider condition** post-crash

Your helmet system can:

- Monitor **rider vital signs** after crash
- Detect if rider is **conscious/responsive**

- Provide **voice interface** for distress communication
- Operate even if **vehicle systems fail**
- Integrate with V2X networks while adding **personal context**

Summary Table: Gap Analysis Across All Papers

Gap	Paper 1 (Humanity Lifeline)	Paper 2 (LoRa Emergency Device)	Paper 3 (R- AODV)	Paper 4 (V2X Crash)
Integration with wearable sensors	✗ No	✗ No	✗ No	✗ No
Fatigue/physiological awareness	✗ No	✗ No	✗ No	✗ No
Voice-based emergency detection	✗ No	✗ No	✗ No	✗ No
Hybrid online–offline adaptation	✓ Yes	✗ No	✓ Yes	✓ Yes
ID-based secure addressing	✓ Yes	✗ No	✗ No	✗ No
Deterministic emergency prioritization	✗ No	✗ No	✗ No	✗ No

Key Findings Supporting Your Novelty

Your Proposed Feature

Gap in Literature

Helmet-integrated communication

All systems reviewed use separate devices (LifeLinks, handheld units, vehicle-mounted) - none integrate into rider's helmet

Physiological monitoring

None monitor rider fatigue, pulse, or consciousness

Automatic crash/emergency detection

Paper 4 assumes vehicle detects crash; Papers 1-3 require manual activation

Voice-based emergency interface

None support voice detection or hands-free operation

Edge-based deterministic safety logic

All focus on communication, not autonomous decision-making at the edge

Personal context integration

None combine rider vital signs + location + environmental data for intelligent alerting