



PHP MySQL Prepared Statements

[< Previous](#)[Next >](#)

Prepared statements are very useful against SQL injections.

Prepared Statements and Bound Parameters

A prepared statement is a feature used to execute the same (or similar) SQL statements repeatedly with high efficiency.

Prepared statements basically work like this:

1. Prepare: An SQL statement template is created and sent to the database. Certain values are left unspecified, called parameters (labeled "?"). Example:
`INSERT INTO MyGuests VALUES(?, ?, ?)`
2. The database parses, compiles, and performs query optimization on the SQL statement template, and stores the result without executing it
3. Execute: At a later time, the application binds the values to the parameters, and the database executes the statement. The application may execute the statement as many times as it wants with different values

Compared to executing SQL statements directly, prepared statements have three main advantages:

- Prepared statements reduce parsing time as the preparation on the query is done only once (although the statement is executed multiple times)
- Bound parameters minimize bandwidth to the server as you need send only the parameters each time, and not the whole query
- Prepared statements are very useful against SQL injections, because parameter values, which are transmitted later using a different protocol, need not be correctly escaped. If the original statement template is not derived from external input, SQL injection cannot occur.



The following example uses prepared statements and bound parameters in MySQLi:

Example (MySQLi with Prepared Statements)

[Get your own PHP Server](#)

```
<?php
$servername = "localhost";
$username = "username";
$password = "password";
$dbname = "myDB";

// Create connection
$conn = new mysqli($servername, $username, $password, $dbname);

// Check connection
if ($conn->connect_error) {
    die("Connection failed: " . $conn->connect_error);
}

// prepare and bind
$stmt = $conn->prepare("INSERT INTO MyGuests (firstname, lastname, email)
VALUES (?, ?, ?)");
$stmt->bind_param("sss", $firstname, $lastname, $email);

// set parameters and execute
$firstname = "John";
$lastname = "Doe";
$email = "john@example.com";
$stmt->execute();

$firstname = "Mary";
$lastname = "Moe";
$email = "mary@example.com";
$stmt->execute();

$firstname = "Julie";
$lastname = "Dooley";
$email = "julie@example.com";
$stmt->execute();

echo "New records created successfully";
```



Code lines to explain from the example above:

```
"INSERT INTO MyGuests (firstname, lastname, email) VALUES (?, ?, ?)"
```

In our SQL, we insert a question mark (?) where we want to substitute in an integer, string, double or blob value.

Then, have a look at the `bind_param()` function:

```
$stmt->bind_param("sss", $firstname, $lastname, $email);
```

This function binds the parameters to the SQL query and tells the database what the parameters are. The "sss" argument lists the types of data that the parameters are. The s character tells mysql that the parameter is a string.

The argument may be one of four types:

- i - integer
- d - double
- s - string
- b - BLOB

We must have one of these for each parameter.

By telling mysql what type of data to expect, we minimize the risk of SQL injections.

Note: If we want to insert any data from external sources (like user input), it is very important that the data is sanitized and validated.



Example (PDO with Prepared Statements)

```
<?php
$servername = "localhost";
$username = "username";
$password = "password";
$dbname = "myDBPDO";

try {
    $conn = new PDO("mysql:host=$servername;dbname=$dbname", $username,
$password);
    // set the PDO error mode to exception
    $conn->setAttribute(PDO::ATTR_ERRMODE, PDO::ERRMODE_EXCEPTION);

    // prepare sql and bind parameters
    $stmt = $conn->prepare("INSERT INTO MyGuests (firstname, lastname, email)
VALUES (:firstname, :lastname, :email)");
    $stmt->bindParam(':firstname', $firstname);
    $stmt->bindParam(':lastname', $lastname);
    $stmt->bindParam(':email', $email);

    // insert a row
    $firstname = "John";
    $lastname = "Doe";
    $email = "john@example.com";
    $stmt->execute();

    // insert another row
    $firstname = "Mary";
    $lastname = "Moe";
    $email = "mary@example.com";
    $stmt->execute();

    // insert another row
    $firstname = "Julie";
    $lastname = "Dooley";
    $email = "julie@example.com";
    $stmt->execute();

    echo "New records created successfully";
```

[Tutorials ▼](#)[Exercises ▼](#)[Services ▼](#)[Sign Up](#)[Log in](#)

 [HTML](#) [CSS](#) [JAVASCRIPT](#) [SQL](#) [PYTHON](#) [JAVA](#) [PHP](#) [HOW TO](#) [W3.CSS](#) [C](#)

 [?>](#)


[< Previous](#)[Next >](#)

W3schools Pathfinder

Track your progress - it's free!

[Sign Up](#)[Log in](#)

ADVERTISEMENT

[Tutorials ▼](#)[Exercises ▼](#)[Services ▼](#)[Sign Up](#)[Log in](#)[CSS](#)[JAVASCRIPT](#)[SQL](#)[PYTHON](#)[JAVA](#)[PHP](#)[HOW TO](#)[W3.CSS](#)[C](#)

COLOR PICKER

[Tutorials ▼](#)[Exercises ▼](#)[Services ▼](#)[Sign Up](#)[Log in](#)[CSS](#)[JAVASCRIPT](#)[SQL](#)[PYTHON](#)[JAVA](#)[PHP](#)[HOW TO](#)[W3.CSS](#)[C](#)

ADVERTISEMENT

ADVERTISEMENT

ADVERTISEMENT



[Tutorials ▼](#)[Exercises ▼](#)[Services ▼](#)[Sign Up](#)[Log in](#)[CSS](#)[JAVASCRIPT](#)[SQL](#)[PYTHON](#)[JAVA](#)[PHP](#)[HOW TO](#)[W3.CSS](#)[C](#)[PLUS](#)[SPACES](#)[GET CERTIFIED](#)[FOR TEACHERS](#)[FOR BUSINESS](#)[CONTACT US](#)

Top Tutorials

- [HTML Tutorial](#)
- [CSS Tutorial](#)
- [JavaScript Tutorial](#)
- [How To Tutorial](#)
- [SQL Tutorial](#)
- [Python Tutorial](#)
- [W3.CSS Tutorial](#)
- [Bootstrap Tutorial](#)
- [PHP Tutorial](#)
- [Java Tutorial](#)
- [C++ Tutorial](#)
- [jQuery Tutorial](#)

Top References

- [HTML Reference](#)
- [CSS Reference](#)
- [JavaScript Reference](#)
- [SQL Reference](#)
- [Python Reference](#)
- [W3.CSS Reference](#)
- [Bootstrap Reference](#)
- [PHP Reference](#)
- [HTML Colors](#)
- [Java Reference](#)
- [Angular Reference](#)
- [jQuery Reference](#)

Top Examples

- [HTML Examples](#)
- [CSS Examples](#)
- [JavaScript Examples](#)
- [How To Examples](#)
- [SQL Examples](#)
- [Python Examples](#)
- [W3.CSS Examples](#)
- [Bootstrap Examples](#)
- [PHP Examples](#)
- [Java Examples](#)
- [XML Examples](#)
- [jQuery Examples](#)

Get Certified

- [HTML Certificate](#)
- [CSS Certificate](#)
- [JavaScript Certificate](#)
- [Front End Certificate](#)
- [SQL Certificate](#)
- [Python Certificate](#)
- [PHP Certificate](#)
- [jQuery Certificate](#)
- [Java Certificate](#)
- [C++ Certificate](#)
- [C# Certificate](#)
- [XML Certificate](#)



[Tutorials ▼](#)[Exercises ▼](#)[Services ▼](#)[Sign Up](#)[Log in](#)[CSS](#)[JAVASCRIPT](#)[SQL](#)[PYTHON](#)[JAVA](#)[PHP](#)[HOW TO](#)[W3.CSS](#)[C](#)

cannot warrant full correctness

of all content. While using W3Schools, you agree to have read and accepted our [terms of use](#), [cookie](#) and [privacy policy](#).

Copyright 1999-2024 by Refsnes Data. All Rights Reserved. [W3Schools](#) is Powered by [W3.CSS](#).