

MVC - Architecture

Que. Model Kaise Banaya?

Anr. Java class ka use karke.

Que. Controller Kaise Banaya?

Anr. Base Ctl me HTTP Servlet ko extend Kiya hai or Sabhi Ctl me Base Ctl ko extend karwaya hai.

Que. View Kaise Banaya hai?

Anr. JSP pages ko extend karke.

Que. Model kisko dekh kar Banaya hai?

Anr. Database ko dekh kar or Database banaya hai ER diagram ko dekh kar.

Que. Controller kisko dekh kar Banaya hai?

Anr. Controller - View ko dekh kar Banaya hai.

Que. View kisko dekh kar Banaya hai?

Anr. wireframe diagram ko dekh kar.

Que. Bean kisko dekh kar Banaya hai?

Anr. UML diagram ko dekh kar.

UML → Unified Modeling Language.

ER → Entity Relationship.

wireframe → Abstract design for User Interface.

Que. what is pom.xml ?

Ans. It is a xml file that contains information about the project & contains configuration details used by maven to build the project. (Isme dependencies hoti hai).

Que. what is web.xml ?

Ans. It is xml file that contains application configurations and it is also called deployment descriptor.

Isme index page or 404 Error (page not found) ki mapping hoti hai.

⇒ Index page ki mapping `<welcome-file-list>` tag ke andar `<welcome-file>` tag me hoti hai.

```
<welcome-file-list>
```

```
    <welcome-file> index.JSP </welcome-file>
```

```
</welcome-file-list>
```

⇒ 404 Error ki mapping `<error-page>` tag ke andar `<error-code>` tag me 404 likhte hai or `<location>` tag ke andar `ErrorView.JSP` ka address dete hai.

```
<Error-page>
```

```
    <Error-code> 404 </Error-code>
```

```
    <location> ErrorView.JSP </location>
```

```
</Error-page>
```

Que. which are the dependencies in pom.xml page ?

Ans. JavaMail 1.4.7

Servlet 3.1.0

log4j 2.11.7 1.2.17

mysql 8.0.29

C3PO 0.9.5

Que. How to change port no. of JBoss?

Ans. JBoss → Standalone → Configuration → standalone.xml file
→ <Socket-binding> tag me http port no. ko change
karke hoti hai.

Que. How to change port no. of Tomcat?

Ans. Tomcat → Conf → Server (.xml file) → <connector port....>
me port no. change karte hai.

Que. How to Create war file?

Ans. Right click on project → Run as → Maven Build
→ Write "Clean install" in Goals
→ click right on skip test ☒ skip test
→ Apply & Run.

war file 2 Jagah Jagah banti hai

1. Ek war file target me banti hai.
2. Ek war file C: drive me .m2 folder me.

Que. How to deploy on tomcat?

Ans. → target folder se war file ko copy kiya
→ JBoss folder me → Standalone folder → deployment folder me
paste kiya → phir JBoss ke bin folder me standalone
Batch file ko run kar denge.

Que. How to Create maven project?

Anr. go to file → go to new (or press Alt+shift+N)
go to maven project → click on next
→ Select maven-archetype-webapp ^{Artifact Id} 1.0 ^{Version}
→ select next → write in co. anything in GroupId.
→ ~~project name~~ write project name in ArtifactId
→ click on next finish

Que. what is root - folder?

Anr. Java Resource me Src/main/java root folder hai.

Que. what are user components.

Anr. 1.) UserBean.java 2.) UserModel.java 3.) UserView.jsp
4.) UserCtl.java 5.) UserListCtl.java 6.) UserListView.jsp
7.) ForgotPasswordCtl.java 8.) ForgotPasswordView.jsp
9.) MyProfileCtl.java 10.) MyProfileView.jsp
11.) ChangePasswordCtl.java 12.) ChangePasswordView.jsp
13.) UserRegistrationCtl.java 14.) UserRegistrationView.java

Que. what's the use of get view method?

Anr. Jis bhi ctl par ho uske same view par forward karne k liye.

Que. How many methods in BaseCtl? and which are they?

Anr. there are 5 method in BaseCtl

1.) Validate() 2.) preload() 3.) populateBean()
4.) Service() 5.) getView() (getView() is abstract method)

Que.] need of validation, or why we use validation?

Ans.] To validate input data.

Que.] Types of Validation?

Ans.] Two types of validation in our project

1. Server Side Validations

2. Client Side Validations

→ Input Validations

→ Use JavaScript.

→ Declarative

→ Programmatic

→ Business Validation (check from database)

Que.] who call validate method?

Ans.] Service method.

Que.] who call Service method?

Ans.] Container

Que.] who call Container?

Ans.] JVM

Que.] who call JVM?

Ans.] User

Que.] what is ORS? definition of ORS?

Ans.] It's a online Result System, which manages student - Marksheet Record.

Que.] what is port no. of JBoss?

Ans.] 8080

List out

Que.] ^5 names of Application Server?

Ans.] 1.) JBoss 2.) webLogics 3.) GlassFish
4.) webSphere 5.) Jetty

List out

Que.] ^5 names of web Server?

1.) Apache Tomcat 2.) Resin 3.) Kona
4.) Oracle web Tier

Que.] How do you know on which Server we are working?

Ans.] Run Application → go to View Site Information
→ there will be written ⇒ localhost:8080/ORS-Project4/
→ clean ORS-Project4 → and Enter press Enter button
→ Server name will written on last line.

Que.] what is Hyper text?

Ans.] It is a ~~hyper~~ text which contain links

Que.] what is Hyper link?

Ans.] hyper link contains hyper text.

Que.] what is HTTP?

Ans.] Hyper text transfer protocol, which communicate between web clients and servers.

Que.] Hyper Text / hyper links Kaha hote hai?

Ans.] JSP pages par.

Que.1 Links kaise banayi?

Ans.1 Anchor tag ke hyperlink (href) attribute ka use karke.

Que.1 If repository is private then how will we share code?

Ans.1 go to git $\Rightarrow$ Settings $\Rightarrow$ Collaboration $\Rightarrow$ github id of with whom you want to share (it will validate for 7 days only)

Que.1 code ki merging kaise hoti hai?

Ans.1 meld merge se.

Que.1 Tools you used in your application?

Ans.1 " Eclipse Mars 1

" SQL

" Argo UML

" ERwin

Que.1 Technologies you used in your application?

Ans.1 JDK 11

JSP 2.3 / Servlet 4.2

JDBC 4.2

MySQL 8.0.29

Java Mail API 1.4.7

Log4J 1.2.17

⇒ Git push

Local to global

1. Access github website.
2. Add login Credentials.
3. Create a new Code Repository.
4. Copy the url of this newly created Repository.
5. on local machine create a new target folder.
6. open cmd in this target folder.
7. type :-

7.1 Git init

7.2 git Config -- global user.email " "

7.3 git Config -- global user.name " "

7.4 git Config -- global user.password " "

7.5 git clone "url of git repository"

7.6 ~~git add filename~~ git add .

7.7 git Commit -m "msg"

7.8 git push origin main

⇒ Git pull

Global to local

1. Locate the repository on github web. & copy the url
2. Create a target folder in local machine.
3. open cmd.
4.
 - 4.1 git init
 - 4.2 git clone "url of repository"
 - git pull origin main

Q.1 How Co

1. Right

2. g

3. The

4. C

5. S

6. C

Q.1 How

1. Ce

2. f

To R

3.

Q.1 How

1. p

2. p

3. v

4.

5.

Q.1 How Can the war file be Created?

1. Right click on project.
2. go to Run As.
3. Inside Run as go to Maven build...
4. write "clean Install" in goals.
5. Select "Skip test".
6. click on Apply & then on Run.

Q.1 How Can war file be deployed?

1. Copy war file from target folder.
2. paste in JBoss → standalone → deployment
- To Run
3. go to JBoss → bin → standalone-hatch

Q.1 How Can java doc be Created?

1. Input message by Alt + Shift + J
2. Menu bar of Eclipse → project → generate java doc
3. visibility = private
4. Configure java doc exe path & Destination path
5. apply & Run

Q.1 Index page kyu khul raha hai?
Index.jsp ki mapping ki hai web.xml me.

Q.1 Mapping kis tag me ki hai aur kaise?

```
<welcome-file-list>  
  <welcome-file> Index.jsp </welcome-file>  
</welcome-file-list>
```

Q.1 Agar mapping nahi karunge toh
Server ke web.xml me by default mapping hoti hai.

Q.1 Index page k alawa or kis cheez ki mapping hoti hai
web.xml me.

404 page not found, Error message ki.

Q.1 Yeh kaise pata chal raha hai ki yeh hyperlink hai?

1.1 when we move cursor on the link it convert into
finger pointer.

2.1 ^{down} on the left side next page ka address show hota hai.

3.1 we have under-line all the ~~link~~ hyperlink in our
application.

Q.1 How Can the under-line of a hyperlink be removed?

A.1 (text-decoration: none)

Q.1 welcome to ORS page pe kitne pages hai?
welcome.jsp page pe header.jsp aur footer.jsp ko include
kariya hai.

<% @ include file = "header.jsp" %>

Q.1 welcome page par kitni links hai?
two → (welcome aur login) separated by pipe (|)

Q.1 Hi Guest, kis scope me hai?
page k scope me.

Q.1 page k scope me kaise aaya?
By default.

Q.1 image kaise aa rahi hai?
img tag k "src" attribute mei image ka path pass kra hai

Q.1 image weight mei kaise aa rahi hai?
<td> tag k andar <h1 align = "right"> krka hai.

Q.1 © kaise lagaya?

~~©~~ copy

~~©~~ ©

Q.1 Input Validation perform karo?

ya
SignIn par click karo!
click on SignIn without filling data (null validation)

Q.1 ye kya aagaya?

Input Validation messages

Q.1 Red me kyu aa raha hai?
Error message hai

Q.1 Input Validation Error message kaise aa raha hai
on
Input Validation flow

1. SignIn par click karo.

2. LoginCtrl par gaya.

3. BaseCtrl ko extend kara hua hai.

4. BaseCtrl ki extend method ko override kara hua hai.

5. validate() k andar condition di hai

If dataValidator is null.

6. Key value pair mei message ko set kia hai.

request.setAttribute("key", value)

key = "login"

value = propertyReader.getValue("error.require", "loginId")

error.require System properties me diya hai.

7. respective View par get kia

Expression tag
% = ServletUtility.getErrorMessage(key, request) %
login

All messages are in Request scope, whether Input Validation message or business Validation messages.

Q.1 Business Validation perform karo.

Id sahi aur password galat enter karo. login() model ← Authenticate (do post)

Q.1 In messages (Business Validation messages) ko kaise set aur get kia?

1. Respective Ctl pe set kia hai

ServletUtility.set error messages "msg" (request) ke form mei.
Invalid login And Password

2. Respective View pe get kia hai

<% = ServletUtility.get error message (request) %>

scope

USER REGISTRATION

Q.1 Input Validation perform karo.

click on signup without filling any data (null validation)

Q.1 Kya hua

Input Validation flow.

Q.1 User Registration View par kesa field preload hai?

Crender

Q.1 Kaise preload hai?

Static preload hai

Q.1 Kaise banayi?

hashmap ka object use par banaya hai.

htmlutility ki get list() ka use kia hai.

Q.1 kaha par kiya hai

User Registration View par

Q.1 Aese Aese Kaise pura batao static preload.

1. Hashmap ka object banaya

```
HashMap map = new HashMap();
```

2. Map ki method put ko call kiya aur key value mei set kia

```
map.put("male", "male");
```

```
map.put("female", "female");
```

3. HTML utility.getlist uske andar 3 parameter pass krige
name, selected value, hashmap ka object

```
& name = Gender
```

```
selected value = bean.getGender();
```

```
HashMap ka object = map
```

4. <% = HTML list %>

view par pass krta, jisse list print ho gayi.

Q.1 Date (calendar) k liye kya kiya hai? (User Registration View)

1. Jquery ki 3 library add ki hai

1.1 jquery 1.12.4.js

1.2 jquery ui 1.12.1.js

1.3 jquery ui 1.12.1.css

2. Date picker function banaya hai.

3. Id mei function ko pass krta hai.

Q.1 Input type = Date

1. JS disable

2. Custom parameter

Q.1 Kiski id mei pass krta hai aur kaise?

Input tag mei

type = text

name = dob

Id = date picker

Q.1 password aur confirm password same kyu hona chahiye?

• equals method ka use kiya hai.

Q.2 Kaise use kiya hai equals method ka?

If password.equals(confirm password)

Q.3 SignUp Flow

1. SignUp par click kara.

2. UserRegistration View.jsp se UserRegistration Ctl pe gaya.

3. UserRegistration Ctl ki do post() mei gaya.

4. Operation get kia.

5. Operation "SignUp" mila.

Usermodel

6. Model ka object banaya.

request

7. Date ko populate kia aur bin me hold kia.

8. Model ki Registered User() call ki aur usme bean pass kia aur long pk mei hold kia.

long pk = model.Registered User(bean)

bean.setId(pk)

9. Success message set kiya aur View par get kia.

forward kia or

Q.1 Sign In flow

1. Sign In par click kiya
2. LoginView.jsp se loginCtrl par chale gaye.
3. loginCtrl ki do post() mei gaye.
4. Operation ko get karaa.
5. Operation "SignIn" mila.
6. Bean ko populate kiya.
7. model ka object banaya.
8. model ki authenticate() call ki aur usme bean.getLoginId() aur bean.getPassword() pass kiya aur bean mei hold karaya.
9. check kiya pf (bean != null)
then, session mei user ko set kiya
Session.setAttribute("user", bean)
LoginView par forward kar diya.

LoginId*

Password*

<table> tag → <tr> tag → <th> tag LoginId

* </th>

input type = text name = "login"

password

input type = "password" name = "password"

After loginIn

Q.1 Hi, Ravi(admin) kis k scope me hai?

1. HP page k scope me hai kyunki wo humne hard coding
2. me likha hai or Ravi(admin) session k scope me hai.

Q.2 yeh aa kaise uraha hai?

1. Session se user ko get kia.
2. userbean k object mei hold kara diya
3. Condition check ki

If userbean != null

toh usko user loggedIn mei hold kara diya

4. 4.1 welcome msg set karaya

String welcome msg = "Hi, "

5. phir Condition check ki

If user loggedIn

Then,

6. Session se user ke role ko get kia aur string role mei hold kara diya

7. welcome msg k sath add assignment operator (+=) ka use kar ke bean.get firstName aur role ko add kara diya.

Q.3 Brackets kaise aa urahe hai?

String mei brackets ko bhi append kia hai.

Q.4 Session se user role & first name ko get kia toh set kaha kia login Ctl par

Q.5 Session ka object kyu nhi banaya?
Session Implicit object hai.

Use Case (marksheet list)

Q.1 List kaise aa rahi hai?

1. marksheet list link pe click kiya
2. marksheet list ctrl ki do get() mei gaye.
3. page no = 1 set kiya &
page size get kiya system properties file se.
`propertyReader.getValue(pageSize)`
4. Date ko populate kar k bean k object me hold kiya.
5. model ka object banaya
6. model ki search() call ki uske andar
(bean, page no & page size) pass kiya
"aur list k object mei hold kiya"
7. Then, list, pageNo & page size ko set kiya
`ServletUtility.setList(list, Request)`
`ServletUtility.setPageNo(pageNo, Request)`
`ServletUtility.setPageSize(pageSize, Request)`
8. View par forward kiya aur get kiya & list k object
mei hold kiya.
`list = ServletUtility.getList(Request)`
9. At last list ko iterate kiya aur View par display kiya

Page 10 of 10

next to the

unacademy conf * 12012

1951 Nov 10

- ## Role

Q. 1. 2. 3. 4. 5. 6. 7. 8. 9. 10.

10/1

19 vol

Roll no: Chan get Roll no()

hai

1992

Quantifying population bean () of

- 

eye

- And physics = bean get physics

SQL query $\rightarrow$ select * from st-marksheet where 1=1 sql.append (And name like + bean.getName + %)

Q.1 pagination perform Karo?
next pe click Karo.

Q.1 Kya Query chali? Initial Index maximum no. of Record.
Select * from tablename limit (10, 10) on a page.

Q.1 Edit par click kara toh konsi primary Key ka data dikhega?
URI mei dekh jayega primary key

Q.1 Yeh Kiski primary key ka data hai?
non-business primary key

Q.1 Non-business primary key Kya hoti hai?

~~Jo database se related nhi hoti hai~~ ^{Jo} business information ^{Contain nhi} karti hai.
(because it does not relate to user data) ^{Primary Key ko hum} ise ^{non-business pk} kehte hai.

Q.1 Non-business primary key Kyu banai?

Q.1 Non-business primary key kaise banai?

Nex PK method ka use kia hai (marksheet model)

Query :-

select * max(id) from table name

Return PK+1

Data type long

Id = 18 jo query string mei dekh raha hai URI mei, it is called request parameter.

If Id = Very large then it would take to add in maresheet.

Q.1

Q.1

Q.1

Q.1

Q.1

marksheet ~~list~~ list view

Q.1 pagination parameter

```
if (page Size > 0)
{
```

```
    pageNo = (pageNo - 1) * page Size
```

```
}
```

```
sql.append (limit + pageNo, page Size)
```

Q.1 page size kaha liya hai?

System-properties file mei.

Q.1 select all kaise work kar raha hai?

2 libraries add ki hai (Script tag Kandar) respective View par.

1. jquery.min.js ☐ ^{checkbox} ~~input~~ type = "text" liya hai
2. checkbox.js ☐ id = "selectall" name = "select" > selectAll </th>

Q.1 previous disable kaise kia? (list View) ^{jo bhi hai uske}

```
if page no == 1
{
```

```
    previous
```

```
        disabled = disabled
```

```
}
```

Q.1 Next disable kaise hoga? (jo bhi hai uske list view)

```
if
```

```
list.size() < page Size
```

```
{
```

```
    Next
```

```
        disabled = disabled
```

```
}
```


Q.1 3 Id select Karo, delete pe click Karo, Kya hua?

1. Controller ke do post() mei gaye.

2. Operation ko get Karo.

3. Operation "delete" mila.

4. Id's ko get karo.

String[] ids = request.getParameterValues("ids");

5. Model ka object banayo.

6. Condition Check ki.

if (id != null)

7. marksheet bean ka object banayo {delete bean}

8. for each loop laga kar Id's ko id se iterate karo.

for (String id : ids)

9. delete bean. setId karo.

10. Model ke delete() call ki aur delete bean pass karo.

11. Success message set karo, View pe forward karo aur View par get karo.

User List

Q1 why is checkbox disabled at admin? (View)

Condition di hai

```
if (bean.getRoleId() == Rolebean.ADMIN)
```

checkbox

disabled = disabled

Q2 why is Edit - disabled for admin? (View)

Condition di hai

```
if
```

```
bean.getRoleId() == Rolebean.ADMIN
```

on click par return false kya hai?

Q3 Edit ka flow Batao. marksheet View se marksheetctl

1. Edit pe click karna.

2. View se Controller pe gaya.

3. Controller ki do get () chali.

4. Anchor tag mei id ko Query String se append karna aur
bean.getId() karna

```
<a href = "marksheetctl?id = <%= bean.getId() %> Edit </a>
```

5. model ka object banaya.

6. Id get ki

```
request.getParameterValue("id")
```

7. Condition check ki if (Id > 0)

8. Model ki "findById()" ko call karna aur bean mei hold karna.

```
bean = model.findById(pkId)
```

9. bean ko set karna ⇒ ServletUtility.setbean(bean, request).

10. Forward kar diya View par.

11. Respective field mei get kar lia.

```
<%= ServletUtility.getStringData(bean.getName()) %>
```


Forgot Password

Q.1 Go ka flow batao.

- 1.1 Go pe click kara.
- 2.1 forgot password View se go forgot password Ctrl par gaye.
- 3.1 forgot password Ctrl ke doPat() chal.
- 4.1 operation ko get kra.
- 5.1 operation "Go" mila.
- 6.1 User Model ka object banaya.
- 7.1 data ko populate kra aur bean mai hold kra.
- 8.1 model ki forgotPassword() call ki
-isme bean.getLogin() pass kra.
model.forgotPassword(bean.getLogin())
- 9.1 Success message set kra aur View par get kra.

⇒ git is a online technology to

⇒ It is a free online

⇒ git is a application &

we use some predefined & custom classes
for sending mail

we use transport class sendmail

§ Logout k liye → session.invalidate() ko call kiya hai.

Builder pattern kaise perform kiya hai

↳ Enroll builder class se

Transaction kya hota hai → change made in database
by us using CRUD operation

business validation me kya hua → authenticate method
challenge

transaction handle karne k liye conn.set
conn.setAutoCommit

Every user pe kesi() call hoti hai.
Service()

Q.1 how to remove underline of link?
will write text-decoration: none
on index.jsp on ops link.

Q.1 Copyright RAYS Technologies niche kyu aa raha hai
footer.jsp par CSS ka use kiya hai
or bottom 0 kiya hai.

Q.1 front ka error msg kyu aa raha hai?

Q.1 Logout karne par success msg kaise aa raha hai.
loginctl ki do post() me msg set kiya hai
(See code)

Q.1 Logout karne par kya hua?
Session.Invalid() chali! (loginctl → doget)

⇒ Send Redirect 2 jagha use kiya hai → reset or cancel page.

⇒ Signup par kya hai → business data hai
→ user related data

Q.1 perform front controller.
localhost:8080/ORS Project 4/LoginCtrl
clear LoginCtrl and create ctrl and press enter.

Q.1 Error msg kaise aaya.
frontCtrl par Error msg set kiya hai.
if (user == null)
ServletUtility.setErrorMessage("msg", request)
your session has been expired.

Q.1 or LoginView.jsp par get kiya hai.
ServletUtility.getErrorMessage(request)

Q.1 red colour me kya aarha hai.
style tag me font colour red set kiya hai.

Q.1 Student Name tag kaise create kiya hai.
table tag k andar tr tag k andar td k andar
label tag me StudentName likha hai.
input type me text liya hai, name = name, placeholder

Q.1 preload wali no.
input tag type = "Submit", name = "operation"

$$\begin{array}{r} 2800 \\ 1300 \\ \hline 4300 \end{array} \quad \begin{array}{r} 1: 5000 \\ - 3300 \\ \hline 1700 \end{array}$$

mvc guideline

1. one view have one ctl
2. View can only be access by a ctl.
3. Every database has one model
4. Ctl will perform bussiness operation

1. one Screen will have one View
2. one View will have one ctl
3. ~~User~~ user can't access directly accessed view it will always accessed by user via Ctl.
4. ctl responsible to fetch data from model to display View.
5. when an application need to navigate to the next View then request is forwarded to Ctl of the next View.

Q.1 How many ways to create ~~filter~~ front Controller

1. Servlet

2. filter interface ka use karke

Q.1 login karne ke baad Baki links kaise show ho
honi chahiye hai?

Iske liye humne Header JSP par Condition di hai
if (`userbean.getRoleId` == `Rolebean.Admin`)
hai to Baki links show karre.

Q.1 link kaise banayi hai?
Anchor tag ke href (hyper reference) tag me link ka
path diya hai.

Q.1 Successfully Logout Flow?
Logout par click kiya, `loginCtrl` ke `doGet` me gaye
operation get kiya
operation logout mila.
`session.invalidate` se user ko Logout kar diya
Success msg Set kiya
`serulefutility.setSuccessmsg("msg", Request);`
then `loginView` par forward kar diya.

Q.1 Front Ctrl flow?

Front Controller class me filter interface ko implement kiya.

Filter ki 3 life cycle method ko call kiya.

1. init 2. doFilter 3. destroy.

do filter me ServletRequest req, ServletResponse resp
filterchain chain as parameter pass kiye.

then

ServletRequest ko HttpServletRequest se typecast kiya

—— " —— Response —— " —— Response —— " ——

then session ka object banaya.

HTTPSession session = Request.getSession();

then condition pass ki,

if (session.getAttribute("user") == null) hai to msg ko
msg or request k form me set kiya

ServletUtility.setErrorMessage(msg, req) k form me.

Then

ServletUtility.forward se loginView par forward kiya.

or else me doFilter(req, resp) pass kiya.

⇒ Front Controller me humne wild Card mapping ki hai

@ webFilter (filterName = ("frontCtrl"), urlPattern = {"/ctrl/*", "/doc/*"})

Q.1 Front Controller kha-2 apply kiya hai?

welcome, login, user Registration, forgot password page
ko chhod kar sab jagah apply kiya hai.

Q.1 In pages par kya nhi lagaya?

Kyuki in pages par session ka scope hi nhi hota hai.

Q.1 foreign key ki query?

→ Alter table tablename add foreign key (id) references dept2tablename.id;

Q.1 request kab destroy hoti hai?

→ jab response generate hota hai.

Q.1 validate method kab-2 perform hoti hai?

→ is not null(), cancel, reset, delete, View operation ko chhod kar har operation par perform hoti hai.

Q.1 id ko agar business primary key banate hai to kya hoga.

→ agar hum id ko business primary key banate hai or agar user infuture apna data change karega or agar usse related koi foreign key hoti hai to uska data invalidate ho jayega.

is condition se bechane k liye humne id ko non-business primary key banaya hai.

⇒ Agar Rollno. business primary key hai or usse related koi foreign key hai or to hum agar roll no. change karte hai to us roll no. se related foreign key ka data invalide hoga. or agar hum Rollno. wali table k records change karte hai to wo to change ho he jayenge.

Q.1 javadoc ke kisi ctl ki methods ya attribute me humne javadoc kaha apply kiya hai?

→ java doc JSP pages or Constructor ko chhod kar har jagah apply kiya hai or javadoc k description me humne javadoc apply kiya hai.

Q.1 Edit par Click Karne k baad input Validation Kaise Kraya.

→ marksheetctl pa Ki validate() k andar condition di hai k if (physics ~~to~~ > 100) hai to msg set kiya hai.

request.setAttribute("physics", "marks can't be - - -");

or marksheetView.jsp par get kiya hai

<% = ServletUtility.getMessage("physics", request) %>

Q.2 Javadoc ki visibility private kyu ki hai?

→ agar humne program k andar koi private attribute ya method li hai to ye unhe access karlegai.

Q.3 Frontctl dusre ctl par kaise apply kiya hai.

@webServlet ctl ka name, url pattern me /ctl/ctl ka name.

Q.1 what is log4j?

log4j stands for logging messages for java. logging means record program's messages at console, file, network or data base.

Q.2 why we use this?

To track the health and flow of the application.

Q.3 Explain log4j Component?

log4j has three Component

logger :- ye responsible hota hai logging information capture karne k liye.

Appender :- ye responsible hota hai log messages ko final destination par send karne k liye.

Layouts :- ye responsible hota hai logging information ko different style me format karne k liye.

Q.4 name some of appenders in log4j?

1. Console Appender 2. Rolling File Appender 3. JDBC Appender 4. SMTP Appender

Q.5 Rolling File Appender kya hota hai?

Rolling File Appender hardin nahi log file create karta hai ya de hai file size finished ho jati hai to nahi file create karta hai.

Q.6 how many levels of log4j?

1. Debug level → at development phase

2. Info level → at QA phase

3. Warn level → at production environment

4. Error level → during application execution

5. Fatal level → any situation that stop execution of an application.