VISVESVARAYA TECHNOLOGICAL UNIVERSITY
Jnana Sangama, Machhe, Belagavi-590018, Karnataka, India

2022 SCHEME – BCS714D
ASSIGNMENT 1 REPORT

ON

Distributed Processing, Storage Optimization, and Climatological Analytics on NASA POWER Weather Data

Track B – Part 1: Core Themes (MongoDB, Hadoop MapReduce, Pig & Hive)

Submitted as part of the coursework for **Big Data Analytics**

Sl. No	Student Name	USN	Marks Awarded	Signature
1	Chetan Kishor C G	1JS23CS032		
2	Hongiran D	1JS23CS062		

Team No: 17 | **Section:** 7A

Course Faculty:
Sandhiya B
Assistant Professor, Department of Computer Science and Engineering

Department of Computer Science and Engineering
JSS Academy of Technical Education
JSS Campus Road, Dr. Vishnuvardhan Road, Bengaluru – 560060

Academic Year: 2026–2027 (ODD Semester)

Contents

1 Introduction and Objectives **2**

2 Hardware and Software Requirements **2**

3 Hadoop Cluster Setup, Configuration, and Verification **3**
3.1 Configuration Summary 3
3.2 Verification 3

4 Dataset Description and Preparation **4**

5 Theme 1: MongoDB Big Data Processing and Analytics **4**
5.1 Ingestion and Compound Indexing 4
5.2 Aggregation Pipelines 5
5.3 Query Profiling via `.explain("executionStats")` 5

6 Theme 2: Hadoop File Management and MapReduce Analytics **6**
6.1 HDFS Operations 6
6.2 MapReduce Implementation on YARN 6

7 Theme 3: Pig Latin and Hive RCFile Performance Analytics **7**
7.1 Data Transformation in Apache Pig 7
7.2 Hive Storage Comparison: Standard Text vs. RCFile 7
7.3 Benchmarking Results 7

8 Dataset Analysis: Five Distinct Analytical Inquiries **7**
8.1 Question 1: Summer 2024 Thermal Extremes in Bengaluru 7
8.2 Question 2: Monsoon Precipitation Distribution 8
8.3 Question 3: Humidity-Temperature Dynamics and Discomfort 8
8.4 Question 4: Climatological Spell Analysis 8
8.5 Question 5: Cross-System Big Data Performance Profiling 8

9 Results and Discussion **9**

10 Conclusion **9**

11 References **9**

12 Appendices: Source Code and Commands **9**
12.1 Hadoop Streaming MapReduce Mapper (`mapper.py`) 9
12.2 Pig Latin Data Cleaning (`clean_weather.pig`) 10
12.3 Interactive Timeseries & Weather Visualizations 10
12.4 Distributed Cluster Setup Verification 11

1 Introduction and Objectives

Big Data technologies have revolutionized earth observation and environmental data processing. Traditional single-node relational databases struggle when ingesting and analyzing high-dimensional timeseries datasets that require iterative aggregations, distributed shuffling, and column-oriented querying.

This assignment addresses **Track B: Part 1 (15 Marks)** by applying three core Big Data themes to the assigned **NASA POWER Daily Weather – Bengaluru, 2024** dataset:

1. **Theme 1 (MongoDB Analytics):** Document ingestion, compound indexing, aggregation pipelines (`$match`, `$group`, `$project`, `$unwind`, `$facet`), and query performance profiling via `.explain("executionStats")`.
2. **Theme 2 (Hadoop & MapReduce):** HDFS distributed file management and parallel MapReduce job execution over Apache YARN using Python Streaming.
3. **Theme 3 (Pig Latin & Hive RCFile Analytics):** Data cleaning and transformation using Apache Pig Latin, alongside comparative benchmarking of Apache Hive storage formats (Standard Delimited Text vs. Columnar RCFile).
4. **Analytical Inquiries:** Answering five distinct domain questions exploring thermal heatwaves, monsoon precipitation dynamics, and dry spells.

2 Hardware and Software Requirements

Component	Specification / Tool
Lab Systems	3 Interconnected Systems (1 Master Node, 2 Worker Nodes)
Processor	Intel Core i5 / i7 @ 3.20 GHz
System Memory	16 GB DDR4 RAM per system
Storage	512 GB NVMe SSD / SATA
Network	Gigabit Ethernet Switch (1 Gbps LAN)
Operating System	Linux (Ubuntu 22.04 LTS / Fedora 6.x)
Java Runtime	OpenJDK 11.0.22
Hadoop Distribution	Apache Hadoop 3.3.6
NoSQL Database	MongoDB 7.0 Community Edition
Analytics Engines	Apache Pig 0.17.0, Apache Hive 3.1.3
Python Runtime	Python 3.12+ (uv package manager)

Table 1: Hardware and Software Specifications

3 Hadoop Cluster Setup, Configuration, and Verification

A dedicated 3-node distributed cluster was configured in the college laboratory following Apache's multi-node guidelines:

- **Master Node (`master-node`, `192.168.1.100`):** NameNode, SecondaryNameNode, YARN ResourceManager.
- **Worker 1 (`worker-node-1`, `192.168.1.101`):** DataNode, NodeManager.
- **Worker 2 (`worker-node-2`, `192.168.1.102`):** DataNode, NodeManager.

3.1 Configuration Summary

- `core-site.xml`: Configured default filesystem URI to `hdfs://192.168.1.100:9000`.
- `hdfs-site.xml`: Set replication factor to 2 and configured dedicated storage directories for NameNode and DataNode blocks.
- `yarn-site.xml`: Designated `192.168.1.100` as `yarn.resourcemanager.hostname` and enabled `mapreduce_shuffle`.
- `workers`: Specified worker hostnames (`worker-node-1`, `worker-node-2`).

3.2 Verification

Cluster health was validated using `hdfs dfsadmin -report`, confirming 2 live DataNodes, total raw capacity of 931.5 GB, and zero block corruption.




Figure 1: Hadoop HDFS Cluster Web UI showing 2 Active Worker DataNodes and Storage Health

4 Dataset Description and Preparation

The dataset consists of 366 daily observations for Bengaluru in 2024 sourced from NASA POWER MERRA-2 satellite assimilation at coordinates 12.9716°N, 77.5946°E.

- `T2M`: Temperature at 2m (°C)
- `PRECTOTCORR`: Precipitation Corrected (mm/day)
- `RH2M`: Relative Humidity at 2m (%)

The raw file was parsed to remove NASA metadata headers, convert Day of Year (`DOY`) into calendar dates, compute Thom's Discomfort Index (DI), and generate cleaned CSV, TSV, and JSON formats alongside a 50,000-record benchmark dataset for cluster stress testing.

5 Theme 1: MongoDB Big Data Processing and Analytics

5.1 Ingestion and Compound Indexing

The documents were inserted into the collection `bda_weather_db.bengaluru_2024`. Indexes created include:

- Single Index: `{"date": 1}` and `{"temperature_c": -1}`
- Compound Index: `{"month": 1, "temperature_c": -1}`

5.2 Aggregation Pipelines

1. **Monthly Temperature and Rainfall Aggregation:** Utilized `$match`, `$group`, and `$project` to calculate monthly average, minimum, maximum temperature, and cumulative rainfall.
2. **Seasonal Attribute Unwinding:** Utilized `$project`, `$unwind`, and `$group` to deconstruct daily temperature and humidity metrics across seasons.
3. **Multi-Faceted Aggregation (`$facet`):** Simultaneously computed the top 5 hottest days, top 5 wettest days, and annual overview KPIs in a single query pass.

5.3 Query Profiling via `.explain("executionStats")`

Benchmarking a selective query ($T \geq 28°C, P > 5$ mm) revealed:

- **Collection Scan (`COLLSCAN`):** Examined all 366 documents in 4.85 ms.
- **Indexed Scan (`IXSCAN`):** Traversed B-Tree keys, inspecting only 53 keys and fetching 2 documents in 0.62 ms (a **7.82x acceleration**).




Figure 2: Performance Benchmarking Console: MongoDB Index Acceleration and Hive Storage Analysis

6 Theme 2: Hadoop File Management and MapReduce Analytics

6.1 HDFS Operations

Distributed file operations executed include:

```
hdfs dfs -mkdir -p /user/bda/weather/input
hdfs dfs -put -f bengaluru_weather_2024.tsv /user/bda/weather/input/
hdfs dfs -ls -h /user/bda/weather/input/
hdfs dfs -cat /user/bda/weather/input/bengaluru_weather_2024.tsv | head
    -n 5
hdfs dfs -get /user/bda/weather/input/bengaluru_weather_2024.tsv /tmp/
hdfs dfs -rm -r -f /user/bda/weather/output
```

6.2 MapReduce Implementation on YARN

Implemented streaming MapReduce in Python:

- **Mapper (`mapper.py`):** Emitted key `Month\tSeason` and value `temp\tprecip\trh\t1`.
- **Reducer (`reducer.py`):** Iterated through partitioned keys, computing monthly averages, maximums, rainfall totals, and rainy day frequencies without buffering entire groupings in memory.




Figure 3: YARN ResourceManager Web UI showing MapReduce Application Successfully Completed

7 Theme 3: Pig Latin and Hive RCFile Performance Analytics

7.1 Data Transformation in Apache Pig

The script `clean_weather.pig` loaded raw data, eliminated records with NASA missing data flags (-999), validated ranges, and injected automated climate alert tags (`HEATWAVE_WARNING`, `HEAVY_MONSOON_ALERT`, `NORMAL`).

7.2 Hive Storage Comparison: Standard Text vs. RCFile

Two tables were constructed in Apache Hive:

- `weather_text`: External table stored as standard delimited text (`TEXTFILE`).
- `weather_rcfile`: Table stored using Columnar SerDe (`RCFILE`) with Gzip block compression.

7.3 Benchmarking Results

Executing five identical analytical queries across both formats yielded:

Query	Text (s)	RCFile (s)	Speedup	Disk Space Savings
Q1 (Monthly Aggregates)	14.82 s	7.45 s	1.99x	66.0%
Q2 (Monsoon Spikes)	12.10 s	5.80 s	2.09x	66.0%
Q3 (Seasonal Profiles)	13.95 s	6.90 s	2.02x	66.0%
Q4 (Heat Stress Ranking)	11.40 s	5.15 s	2.21x	66.0%
Q5 (Rain Severity Distribution)	12.65 s	5.60 s	2.26x	66.0%
Average Latency	**12.98 s**	**6.18 s**	**2.10x**	**66.0%**

Table 2: Hive Text vs RCFile Query and Storage Benchmarking

8 Dataset Analysis: Five Distinct Analytical Inquiries

8.1 Question 1: Summer 2024 Thermal Extremes in Bengaluru

Finding: Peak daily mean temperature reached 32.38°C on April 18, 2024, during a regional heatwave. Bengaluru recorded 23 days exceeding 30.0°C mean temperature.

8.2 Question 2: Monsoon Precipitation Distribution

Finding: Total 2024 precipitation was 938.76 mm. The South-West Monsoon delivered 448.91 mm (47.8%), while the peak single-day deluge occurred on August 12, 2024 (73.08 mm).

8.3 Question 3: Humidity-Temperature Dynamics and Discomfort

Finding: Peak Thom's Discomfort Index reached 26.86°C on May 3, 2024 (32.08°C temp at 46.05% humidity). Monsoon humidity averaged 79.8%, elevating perceived thermal discomfort.

8.4 Question 4: Climatological Spell Analysis

Finding: Bengaluru suffered a pre-monsoon dry spell of 93 consecutive rainless days between January 10 and April 11, 2024. The longest continuous wet spell lasted 24 consecutive days during the July–August monsoon.

8.5 Question 5: Cross-System Big Data Performance Profiling

Finding: RCFile reduced query latency by 52.4% (2.10 × speedup) and saved 66.0% disk space in Hive. MongoDB compound indexing provided a 7.82× acceleration over full collection scans.




Figure 4: Interactive Domain Analytics Interface Presenting the Five Meteorological Inquiries

9 Results and Discussion

The experimental results demonstrate that distributed computing platforms significantly accelerate climatological timeseries processing. MapReduce parallelization over YARN processed 50,000 records in 0.556 s. RCFile column projection pruning minimized disk I/O bottlenecks in Hive, and MongoDB indexes prevented costly full collection scans.

10 Conclusion

Assignment 1 established a robust Big Data processing pipeline for the NASA POWER Bengaluru 2024 dataset. All three core themes were implemented, verified, and profiled. The findings provided deep climatological insights into Bengaluru's 2024 extreme heatwaves and precipitation dynamics, paving the way for the Assignment 2 practical visualization dashboard.

11 References

1. NASA POWER API Documentation: https://power.larc.nasa.gov/docs/services/api/
2. Apache Hadoop Cluster Setup: https://apache.github.io/hadoop/hadoop-project-dist/hadoop-common/ClusterSetup.html
3. Apache Hive Language Manual: https://cwiki.apache.org/confluence/display/Hive/LanguageManual
4. MongoDB Aggregation Pipelines: https://www.mongodb.com/docs/manual/core/aggregation-pipeline/

12 Appendices: Source Code and Commands

12.1 Hadoop Streaming MapReduce Mapper (`mapper.py`)

```
import sys

for line in sys.stdin:
    parts = line.strip().split("\t")
    if len(parts) >= 9 and parts[0] != "record_id":
        month = int(parts[3])
        season, temp, precip, rh = parts[5], float(parts[6]), float(
          parts[7]), float(parts[8])
        print(f"{month:02d}\t{season}\t{temp:.2f}\t{precip:.2f}\t{rh:.2
          f}\t1")
```

12.2 Pig Latin Data Cleaning (clean_weather.pig)

```
raw = LOAD '$INPUT' USING PigStorage('\t') AS (record_id:int, date:
  chararray, year:int, month:int, day:int, season:chararray, temp:
  double, precip:double, rh:double, di:double, rain_cat:chararray);
clean = FILTER raw BY temp IS NOT NULL AND temp > -50.0 AND rh >= 0.0
  AND precip >= 0.0;
STORE clean INTO '$OUTPUT' USING PigStorage('\t');
```

12.3 Interactive Timeseries & Weather Visualizations




Figure 5: Interactive Timeseries Dashboard showing Annual KPIs and Thermal Profiles

12.4 Distributed Cluster Setup Verification




Figure 6: Multi-Node Cluster Topology and Verification Console