

If you want to use the expanded inventory in your mod and also don't want it to have conflicts with other mods, here's a simple guide on how to set up Magic Pockets as an optional dependency.

In your build.gradle file, add Magic Pockets as a dependency:

```
dependencies {  
    compileOnly(files("libs/pocketsmod-*.jar"))  
}
```

Mark the dependency as optional in your neoforge.mods.toml:

```
[[dependencies.${mod_id}]]  
modId = "pocketsmod"  
type = "optional"  
versionRange = "[1.0,)"  
ordering = "BEFORE"  
side = "BOTH"
```

Add a global flag variable somewhere in the mod (probably the main mod class) that can be accessed by any menus you may want to add:

```
public static final boolean POCKETS_IS_LOADED = ModList.get().isLoaded(modTarget: "pocketsmod");
```

Then you can use the flag to change the menu and screen constructors dynamically whether or not the mod is loaded. Remember to make 2 separate textures for your menu with the default size and the expanded size.

Hope this helps! - Chewylopez

some example implementations on the next page:

Menu fields:

```
private static int ITEM_SLOT_ROWS = RedstoneVault.POCKETS_IS_LOADED ? 4 : 3;
private static int HOTBAR_SLOT_HEIGHT = RedstoneVault.POCKETS_IS_LOADED ? 127 : 109;
```

Menu construction:

```
private void addPlayerInventory(Inventory playerInventory) {
    for(int i = 0; i < ITEM_SLOT_ROWS; ++i) {
        for(int j = 0; j < 9; ++j) {
            this.addSlot(new Slot(playerInventory, slot: j+i*9+9, x: 8+j*18, y: 51+i*18));
        }
    }
}

private void addPlayerHotbar(Inventory playerInventory) {
    for(int i = 0; i < 9; ++i) {
        this.addSlot(new Slot(playerInventory, i, x: 8+i*18, HOTBAR_SLOT_HEIGHT));
    }
}
```

Screen fields:

```
private static final ResourceLocation GUI_TEXTURE = RedstoneVault.POCKETS_IS_LOADED ?
    ResourceLocation.fromNamespaceAndPath(RedstoneVault.MODID, path: "textures/gui/blockeater/blockeater_gui_pockets.png")
: ResourceLocation.fromNamespaceAndPath(RedstoneVault.MODID, path: "textures/gui/blockeater/blockeater_gui.png");

private static int IMAGE_HEIGHT = RedstoneVault.POCKETS_IS_LOADED ? 151 : 133;
private static int INVENTORY_LABEL_HEIGHT = RedstoneVault.POCKETS_IS_LOADED ? 112 : 94;
```

Screen construction:

```
public EaterScreen(EaterMenu menu, Inventory playerInventory, Component title) {
    super(menu, playerInventory, title);
    this.imageHeight = IMAGE_HEIGHT;
    this.inventoryLabelY = this.imageHeight - INVENTORY_LABEL_HEIGHT;
}

@Override
protected void renderBg(GuiGraphics guiGraphics, float pPartialTick, int pMouseX, int pMouseY) {
    RenderSystem.setShader(GameRenderer::getPositionTexShader);
    RenderSystem.setShaderColor(red: 1.0F, green: 1.0F, blue: 1.0F, alpha: 1.0F);
    RenderSystem.setShaderTexture(shaderTexture: 0, GUI_TEXTURE);

    int x = (width-imageWidth)/2;
    int y = (height-imageHeight)/2;

    guiGraphics.blit(GUI_TEXTURE, x, y, uOffset: 0, vOffset: 0, imageWidth, imageHeight);
}
```