
T34 Emulator Documentation

Release 0.1

Chezka Gaddi

Nov 16, 2019

CONTENTS

1	T34 Emulator Tutorial	1
1.1	Running the Application	1
1.2	Functionality	1
1.3	Load a Program	1
1.4	Display the content of a specific memory address	1
1.5	Display the content of a range of memory addresses	2
1.6	Edit memory locations	2
1.7	Run program starting as a specified address	2
1.8	Exit the program	2
2	Documentation for the Code	3
2.1	Emulator – auto members	3
2.2	Instructions – auto members	4
2.3	Memory – auto members	4
3	Testing the Program	5
3.1	Test Emulator	5
3.2	Test Instructions	5
4	Indices and tables	9
	Python Module Index	11
	Index	13

T34 EMULATOR TUTORIAL

This is the tutorial on how to use the T34 Emulator module.

1.1 Running the Application

1.2 Functionality

The monitor will have similar functionality as an OS. The T34 monitor has six functions;

1. *Load a Program*
2. *Display the content of a specific memory address*
3. *Display the content of a range of memory addresses*
4. *Edit memory locations*
5. *Run program starting as a specified address*
6. *Exit the program*

1.3 Load a Program

The machine can start in two modes. Either the user provided an object file (a program), if so, the program is loaded into the correct memory location, or the user just starts the emulator without any program. In both cases the monitor is started, and the user is provided with the monitor prompt (>).

To start the application with a program, run the application with the name of the object file.

```
$ python3 t34.py [filename]
```

1.4 Display the content of a specific memory address

By typing in the memory address in HEX at the Monitor prompt, the Monitor returns the byte (in HEX format) at that location.

```
> 200
200    A9
```

1.5 Display the content of a range of memory addresses

By typing in the starting address in HEX, followed by a period and finally the ending address in HEX at the Monitor prompt, the Monitor returns the bytes between those locations.

```
> 200.20F
200      A9 00 85 00 A5 00 8D 00
208      80 E6 00 4C 04 02 00 00
```

1.6 Edit memory locations

By typing in the starting address in HEX, followed by a colon, and then the new values for the memory locations at the Monitor prompt, the monitor updates the current locations.

```
> 300: A9 04 85 07 A0 00 84 06 A9 A0 91 06 C8 D0 FB E6 07
> 300.310
300      A9 04 85 07 A0 00 84 06
308      A9 A0 91 06 C8 D0 FB E6
310      07
```

1.7 Run program starting as a specified address

By typing in the starting address in HEX, followed by an R at the Monitor prompt. The monitor will execute all code starting at the address and up until the first BRK (opcode 00).

```
> 200R
PC  OPC  INS      AMOD OPRND  AC XR YR SP NV-BDIZC
200
```

1.8 Exit the program

The user should be able to exit the monitor (and python) in three ways:

1. Ctrl-C (keyboard interrupt)
2. Ctrl-D (EOF)
3. Type exit at the monitor prompt (> exit)

DOCUMENTATION FOR THE CODE

2.1 Emulator – auto members

class `t34.Emulator.Emulator` (*program_name=None*)

Class to store an emulator and runs program files.

access_memory (*address*)

Accesses the memory address and displays the contents.

Parameters **address** (*str*) – HEX address of the memory to be accessed.

Returns memory content

Return type string

access_memory_range (*begin, end*)

Accesses a memory range and displays all the contents.

Parameters

- **begin** (*str*) – beginning HEX address of the memory to be accessed.
- **end** (*str*) – end HEX address of the memory to be accessed.

Return out contents of the memory range.

Return type string

edit_memory (*address, data*)

Edits the contents of a specific memory address.

Parameters

- **address** (*str*) – HEX address of the memory to be edited.
- **data** (*str*) – data to store into the memory address.

execute_instruction (*address*)

Gets the instruction stored in memory, decodes it and executes it.

Parameters **address** – Location of the command to be executed

Return output Contents of specific

load_program ()

Loads the program.

Returns successful read

Return type bool

run_program (*address*)

Start program at specific location in memory until end of program.

Parameters **address** – Location of the command to be executed.

Return output Contents of all the registers.

Return type string

start_emulator ()

Starts the emulator and evaluates and executes commands.

2.2 Instructions – auto members

2.3 Memory – auto members

TESTING THE PROGRAM

All of the functionality of the *Emulator* class is tested with the unittest found in the TestEmulator and TestInstruction modules. All tests could be run with the command

```
python3 -m unittest discover
```

3.1 Test Emulator

class t34.test_emulator.**TestEmulator** (*methodName='runTest'*)

Unit testing class for all the functionality of the Emulator class.

setUp ()

Setup the Emulator object to be used for all the tests.

test_access_memory ()

Test access to a memory address.

test_access_memory_range ()

Test access to a memory address range.

test_edit_memory_locations ()

Test edit of a memory location.

3.2 Test Instructions

class t34.test_instructions.**TestInstructions** (*methodName='runTest'*)

Unit testing class for all instructions in the Instructions class.

setUp ()

Hook method for setting up the test fixture before exercising it.

test_asl ()

Test asl instruction.

test_clc ()

Test clc instruction.

test_cld ()

Test cld instruction.

test_cli ()

Test cli instruction.

test_clv()
Test clv instruction.

test_dex()
Test dex instruction.

test_dex_xnegative()
Test dex to negative instruction.

test_dey()
Test dey instruction.

test_dey_ynegative()
Test dey to negative instruction.

test_inx()
Test inx instruction.

test_iny()
Test iny instruction.

test_lsr()
Test lsr instruction.

test_lsr_carry()
Test lsr instruction with carry.

test_pha()
Test pha instruction.

test_php()
Test php instruction.

test_pla()
Test php instruction.

test_rol()
Test rol instruction.

test_ror()
Test ror instruction.

test_run_program_nop()
Test run program with no operand.

test_sec()
Test sec instruction.

test_sed()
Test sed instruction.

test_sei()
Test sei instruction.

test_tax()
Test tax instruction.

test_tay()
Test tay instruction.

test_tsx()
Test tsx instruction.

test_txa()
Test txa instruction.

test_txs()
Test txs instruction.

test_tya()
Test tya instruction.

INDICES AND TABLES

- `genindex`
- `modindex`
- `search`

PYTHON MODULE INDEX

e

Emulator, 3

i

Instructions, 4

m

Memory, 4

t

t34, 3

t34.Emulator, 3

t34.Instructions, 4

t34.Memory, 4

t34.test_emulator, 5

t34.test_instructions, 5

TestEmulator, 5

TestInstructions, 5

A

`access_memory()` (*t34.Emulator.Emulator method*), 3
`access_memory_range()` (*t34.Emulator.Emulator method*), 3

E

`edit_memory()` (*t34.Emulator.Emulator method*), 3
`Emulator` (class in *t34.Emulator*), 3
`Emulator` (module), 3
`execute_instruction()` (*t34.Emulator.Emulator method*), 3

I

`Instructions` (module), 4

L

`load_program()` (*t34.Emulator.Emulator method*), 3

M

`Memory` (module), 4

R

`run_program()` (*t34.Emulator.Emulator method*), 3

S

`setUp()` (*t34.test_emulator.TestEmulator method*), 5
`setUp()` (*t34.test_instructions.TestInstructions method*), 5
`start_emulator()` (*t34.Emulator.Emulator method*), 4

T

`t34` (module), 3
`t34.Emulator` (module), 3
`t34.Instructions` (module), 4
`t34.Memory` (module), 4
`t34.test_emulator` (module), 5
`t34.test_instructions` (module), 5
`test_access_memory()` (*t34.test_emulator.TestEmulator method*), 5

`test_access_memory_range()` (*t34.test_emulator.TestEmulator method*), 5
`test_asl()` (*t34.test_instructions.TestInstructions method*), 5
`test_clc()` (*t34.test_instructions.TestInstructions method*), 5
`test_cld()` (*t34.test_instructions.TestInstructions method*), 5
`test_cli()` (*t34.test_instructions.TestInstructions method*), 5
`test_clv()` (*t34.test_instructions.TestInstructions method*), 5
`test_dex()` (*t34.test_instructions.TestInstructions method*), 6
`test_dex_xnegative()` (*t34.test_instructions.TestInstructions method*), 6
`test_dey()` (*t34.test_instructions.TestInstructions method*), 6
`test_dey_ynegative()` (*t34.test_instructions.TestInstructions method*), 6
`test_edit_memory_locations()` (*t34.test_emulator.TestEmulator method*), 5
`test_inx()` (*t34.test_instructions.TestInstructions method*), 6
`test_iny()` (*t34.test_instructions.TestInstructions method*), 6
`test_lsr()` (*t34.test_instructions.TestInstructions method*), 6
`test_lsr_carry()` (*t34.test_instructions.TestInstructions method*), 6
`test_pha()` (*t34.test_instructions.TestInstructions method*), 6
`test_php()` (*t34.test_instructions.TestInstructions method*), 6
`test_pla()` (*t34.test_instructions.TestInstructions method*), 6
`test_rol()` (*t34.test_instructions.TestInstructions method*), 6

`test_ror()` (*t34.test_instructions.TestInstructions*
 method), 6

`test_run_program_nop()`
 (*t34.test_instructions.TestInstructions method*),
 6

`test_sec()` (*t34.test_instructions.TestInstructions*
 method), 6

`test_sed()` (*t34.test_instructions.TestInstructions*
 method), 6

`test_sei()` (*t34.test_instructions.TestInstructions*
 method), 6

`test_tax()` (*t34.test_instructions.TestInstructions*
 method), 6

`test_tay()` (*t34.test_instructions.TestInstructions*
 method), 6

`test_tsx()` (*t34.test_instructions.TestInstructions*
 method), 6

`test_txa()` (*t34.test_instructions.TestInstructions*
 method), 6

`test_txs()` (*t34.test_instructions.TestInstructions*
 method), 7

`test_tya()` (*t34.test_instructions.TestInstructions*
 method), 7

`TestEmulator` (*class in t34.test_emulator*), 5

`TestEmulator` (*module*), 5

`TestInstructions` (*class in t34.test_instructions*), 5

`TestInstructions` (*module*), 5