

# Experiments

## Overall Performance

Weibo

Method	Class	Acc.	Prec.	Rec.	$F_1$
DTC	F T	0.831	0.847 0.815	0.815 0.824	0.831 0.819
SVM-RBF	F T	0.879	0.777 0.579	0.656 0.708	0.708 0.615
SVM-TS	F T	0.885	0.950 0.124	0.932 0.047	0.938 0.059
RvNN	F T	0.908	0.912 0.904	0.897 0.918	0.905 0.911
PPC_RNN+CNN	F T	0.916	0.884 0.955	0.957 0.876	0.919 0.913
Bi-GCN	F T	<b>0.961</b>	<b>0.961</b> <b>0.962</b>	<b>0.964</b> <b>0.962</b>	<b>0.961</b> <b>0.960</b>

Twitter15

Method	Acc.	N	F	T	U
		$F_1$	$F_1$	$F_1$	$F_1$
DTC	0.454	0.415	0.355	0.733	0.317
SVM-RBF	0.318	0.225	0.082	0.455	0.218
SVM-TS	0.544	0.796	0.472	0.404	0.483
SVM-TK	0.750	0.804	0.698	0.765	0.733
RvNN	0.723	0.682	0.758	0.821	0.654
PPC_RNN+CNN	0.477	0.359	0.507	0.300	0.640
Bi-GCN	<b>0.886</b>	<b>0.891</b>	<b>0.860</b>	<b>0.930</b>	<b>0.864</b>

Twitter16

Method	Acc.	N	F	T	U
		$F_1$	$F_1$	$F_1$	$F_1$
DTC	0.473	0.254	0.080	0.190	0.482
SVM-RBF	0.553	0.670	0.085	0.117	0.361
SVM-TS	0.574	0.755	0.420	0.571	0.526
SVM-TK	0.732	0.740	0.709	0.836	0.686
RvNN	0.737	0.662	0.743	0.835	0.708
PPC_RNN+CNN	0.564	0.591	0.543	0.394	0.674
Bi-GCN	<b>0.880</b>	<b>0.847</b>	<b>0.869</b>	<b>0.937</b>	<b>0.865</b>

- Observe that the **deep learning methods performs significantly better** than those using hand-crafted features.
- Demonstrates the importance and necessity of studying deep learning for rumor detection.

# Experiments

## Overall Performance

**Weibo**

Method	Class	Acc.	Prec.	Rec.	$F_1$
DTC	F T	0.831	0.847 0.815	0.815 0.824	0.831 0.819
SVM-RBF	F T	0.879	0.777 0.579	0.656 0.708	0.708 0.615
SVM-TS	F T	0.885	0.950 0.124	0.932 0.047	0.938 0.059
RvNN	F T	0.908	0.912 0.904	0.897 0.918	0.905 0.911
PPC_RNN+CNN	F T	0.916	0.884 0.955	0.957 0.876	0.919 0.913
Bi-GCN	F T	<b>0.961</b>	<b>0.961</b> <b>0.962</b>	<b>0.964</b> <b>0.962</b>	<b>0.961</b> <b>0.960</b>

**Twitter15**

Method	Acc.	N	F	T	U
		$F_1$	$F_1$	$F_1$	$F_1$
DTC	0.454	0.415	0.355	0.733	0.317
SVM-RBF	0.318	0.225	0.082	0.455	0.218
SVM-TS	0.544	0.796	0.472	0.404	0.483
SVM-TK	0.750	0.804	0.698	0.765	0.733
RvNN	0.723	0.682	0.758	0.821	0.654
PPC_RNN+CNN	0.477	0.359	0.507	0.300	0.640
Bi-GCN	<b>0.886</b>	<b>0.891</b>	<b>0.860</b>	<b>0.930</b>	<b>0.864</b>

**Twitter16**

Method	Acc.	N	F	T	U
		$F_1$	$F_1$	$F_1$	$F_1$
DTC	0.473	0.254	0.080	0.190	0.482
SVM-RBF	0.553	0.670	0.085	0.117	0.361
SVM-TS	0.574	0.755	0.420	0.571	0.526
SVM-TK	0.732	0.740	0.709	0.836	0.686
RvNN	0.737	0.662	0.743	0.835	0.708
PPC_RNN+CNN	0.564	0.591	0.543	0.394	0.674
Bi-GCN	<b>0.880</b>	<b>0.847</b>	<b>0.869</b>	<b>0.937</b>	<b>0.865</b>

- Bi-GCN outperforms PPC\_RNN+CNN in terms of all the performance measures, indicates the effectiveness of incorporating the **dispersion structure** for rumor detection.
- Since RNN & CNN **can't process data with the graph structure**, so ignore important structure features of dispersion.