



JavaScript Standard Library

for stage 2

Mattijs Hoitink
Micheal Saboff

Agenda

- Proposal Status
- Standard Library Namespace
- Immutable APIs

Current Status

Current Proposal:

<https://github.com/tc39/proposal-javascript-standard-library>

JSL Namespace

How do you import from the JSL?

JSL Module Importing

- Following the same syntax for importing modules (*section 15.2*)
- This uses a *StringLiteral* to denote the *ModuleSpecifier*
- A JSL *ModuleSpecifier* will use the URI format:

 “<prefix>:<modulename>”
- The prefix is used to denote the functional domain of the module

JSL Module Specifier

Example

```
import { CivilDate } from "js:Temporal";
```

Why Module Domains?

- Give developers clear guidance where a module can be used
- Facilitates writing portable JavaScript code




KV Storage Built In Module

Example

```
import { storage } from "web:kv-storage";
```


Host Specific Prefixes

- Namespace prefixes should split along host environments



Namespaces

To be registered with IANA

Initial

js: JavaScript Language

web: Web Specific APIs

nodejs: Node.js Standard Library

Future?

iot: Embedded Devices (TC53)

html: HTML Apis


browser: Browser Plugin API

/

Module Loading

Chained Loader

Loading Chain



Polyfilling: Scenarios

- Add missing modules
- Update incomplete implementations
- Patch broken parts or changing behavior

import-maps should handle these cases

Polyfilling: Why import-maps

- import-maps is a host feature
 - It is implemented within the host's security framework.
 - It fits within the proposed tiered loading process.
- The host is already involved in loading remote resources.
 - It already has a notion of what a resource is

Polyfilling: Alternatives

- ModuleSpecifier fallback
- Import statement callback
- Runtime hooks

ModuleSpecifier fallbacks

```
import * from "js:Temporal|https://domain.me/Temporal-patched.js";
```


ModuleSpecifier fallbacks

- Pros
 - Defined semantic
- Cons
 - Not global, i.e. the polyfill alternative needs to be provided at every import.
 - Doesn't handle the "Update" or "Patch" cases polyfill cases.
 - Still requires delegating to host.
 - Has poor ergonomics.

Import statement callback

```
import * from do {  
  try {  
    import { CivilDate } from "js:Temporal";  
  } catch {  
    import * from "https://domain.me/Temporal-patched.js";  
  }  
}
```

Import statement callback

- Pros
 - Very flexible
- Cons
 - Poor module user ergonomic
 - Security concerns
 - Doesn't handle the “incomplete implementation” or “patch broken module” cases

Runtime Hooks

```
Loader.register("js:Temporal", "https://domain.me/Temporal-patched.js");
```

Runtime Hooks

- Pros
 - Very flexible
- Cons
 - Major security concerns.
 - Global substitution. What about multiple registrations?
 - Poor developer experience
 - Doesn't handle the “incomplete implementation” or “patch broken module” cases

Runtime Hooks

```
Loader.update("js:Temporal", function (exports) {  
  if (!exports) {  
    // Provide missing implementation  
    return { /* My Temporal Implementation */ };  
  }  
  
  // Patch existing CivilDate  
  const { CivilDate } = exports;  
  CivilDate.prototype.from = function (/* ... */) {  
    /* ... */  
  };  
  
  return { ...exports, CivilDate };  
});
```

Runtime Hooks

```
Loader.intercept(async function (moduleName, exports) {  
  if (moduleName === "js:Temporal") {  
    return fetch("https://domain.me/Temporal-patched.js");  
  }  
  
  return exports;  
});
```

Questions?

Thank you!