



Huawei E3131



HUAWEI E3131 Specifications

Manufacturer:	Huawei	Huawei	Huawei	Huawei	Huawei
model:	E3131s-1	E3131s-2	E3131s-2 HiLink	E3131s-6	E3131s-65
interface:	USB 2.0 (A plug)				
GSM frequency bands (MHz):	850 / 900 / 1800 / 1900				
UMTS frequency bands (MHz):	2100	2100 / 900	2100 / 900	2100 / 1900 / 850	1900 / 850
HSPA+:	21.6 Mbps				
HSDPA:	7,2 Mbps				
HSUPA:	5.76 Mbps				
EDGE:	236.8 Kbps				
GPRS:	57.6 Kbps				
CSD:					
connector for external antenna:	+	+	+		
connector type:	CRC-9 plug	CRC-9 plug	CRC-9 plug		
internal antenna diversity:					
voice telephony:	enabled	enabled	-		
NAND-flashmemory:	+	+	+		
microSD-drive:	+ (up to 32 GB)	+	+		
H/W version:	CH2E303SM	CH2E303SM	CH2E303SM		
Chipset:	HiSilicon	HiSilicon	HiSilicon		
web interface	-	-	+		
Weight:					
Supported System:					
Rebranded versions:	3 (Drei) (AT)	T-Mobile (DE)	Huawei HiLink		



Devices Huawei E3131 are produced in two versions: standard and HiLink. HiLink devices have the other firmware than a standard E3131!

1 of 2 06/15/2016 06:55 PM



Threads for this page

There are no threads for this page. Be the first to start a new thread.

2 of 2 06/15/2016 06:55 PM