

Study of Jet Substructure Variables for the Future Detector

*Chih-Hsiang Yeh¹, Shin-Shan Eiko Yu¹, Ashutosh Kotwal^{2,3}, Sergei Chekanov⁴, Nhan Viet Tran³

1. Department of Physics, National Central University, Chung-Li, Taoyuan City 32001, Taiwan

2. Department of Physics, Duke University, Durham, NC 27708, USA

3. Fermi National Accelerator Laboratory, Batavia, IL 6051, USA


4. HEP Division, Argonne National Laboratory, 9700 S. Cass Avenue, Argonne, IL 60439, USA



Abstract:

In this poster, we study the performance of hadron calorimeter in SiFCC for the future $\sqrt{s}=100$ TeV pp collider. The GEANT4 full simulation includes calorimeters with different cell sizes. We aim to efficiently separate signal $Z' \rightarrow ww$ or $Z' \rightarrow tt$ and background $Z' \rightarrow qq$. Various jet substructure variables and Z' masses from 5 to 40 TeV are also compared.

Geant 4 Simulation of Future Detector SiFCC



Barrel	Technology	pitch/cell	radii (cm)	z size (cm)
Vertex detector	silicon pixels/5 layers	25 μm	1.3 - 6.3	38
Outer tracker	silicon strips/5 layers	50 μm	39 - 209	921
ECAL	silicon pixels+W	2 \times 2 cm	210 - 230	976
HCAL	scintillator+steel	5 \times 5 cm	230 - 470	980
Solenoid	5 T (inner), -0.6 T (outer)	-	480 - 560	976
Muon detector	RPC+steel	3 \times 3 cm	570 - 903	1400

Basic Jet Reconstruction Algorithm

$$d_{ij} = \min(k_{ti}^{2p}, k_{tj}^{2p}) \frac{\Delta_{ij}^2}{R^2} \quad \Delta_{ij}^2 = (y_i - y_j)^2 + (\phi_i - \phi_j)^2$$

(1) i, j: the i and j particle
(2) k_{ti} , k_{tj} : the transverse momenta of particles i and j

If $d_{ij} < d_{ib}$, i and j particle will be merged into one particle

1. p=0 : Cambridge/Aachen algorithm

2. p=1 : kt algorithm

3. p=-1 : anti-kt algorithm

Jet Substructure Variables

1. N-subjettiness:

$$\tau_N = \frac{1}{d_0} \sum_k P_{t,k} \min\{\Delta R_{1,k}, \Delta R_{2,k} \dots \Delta R_{N,k}\}$$

$$d_0 = \sum_k P_{t,k} R_0$$

$\Delta R_{i,k}$: The distance between constituent in the eta - phi plane

R_0 : The cone size we want to cluster

$$\tau_{21} = \frac{\tau_2}{\tau_1}, \tau_{32} = \frac{\tau_3}{\tau_2}$$

2. Energy correlation function:

$$ECF(N, \beta) = \sum_{i_1 < i_2 < \dots < i_N \in J} \left(\prod_{a=1}^N P_{T_{i_a}} \right) \left(\prod_{b=1}^{N-1} \prod_{c=b+1}^N \Delta R_{i_b i_c} \right)^\beta$$

$$C_N^{(\beta)} \equiv \frac{ECF(N+1, \beta) ECF(N-1, \beta)}{ECF(N, \beta)^2}$$

3. Soft drop:

$$\frac{\min(P_{T1}, P_{T2})}{P_{T1} + P_{T2}} < Z_{\text{cut}} \left(\frac{\Delta R_{12}}{R_0} \right)^\beta$$


$\beta > 0$: Remove both soft and wide - angle

$\beta = 0$: Depend on the cut of pT asymmetry



$\beta < 0$: Remove both soft and collinear

Signal and Background Process:

Background:




Signal:




Variables Study in $C_2^{(1)}, \tau_{21}, \tau_{32}$:

Distribution of $Z' \rightarrow WW$, $Z' \rightarrow qq$ and $Z' \rightarrow tt$, $Z' \rightarrow qq$:



Comparison of different detector sizes:




Summary for $C_2^{(1)}, \tau_{21}, \tau_{32}$:


Is it the best for smallest detector cell size?

	$\sqrt{s} = 5\text{TeV}$	$\sqrt{s} = 10\text{TeV}$	$\sqrt{s} = 20\text{TeV}$	$\sqrt{s} = 40\text{TeV}$
$C_2^{(1)}$	X	X	X	X
τ_{21}	O	X	X	X
τ_{32}	O	O	O	O

Study of Soft Drop at $\beta = 0$ (CMS), $\beta = 2$:



Comparison of different detector size:



Summary for soft drop at $\beta = 0$ (CMS), $\beta = 2$:

Is it the best for smallest detector cell size?

Fix central (from near highest)	$\sqrt{s} = 5\text{TeV}$	$\sqrt{s} = 10\text{TeV}$	$\sqrt{s} = 20\text{TeV}$	$\sqrt{s} = 40\text{TeV}$
$\beta = 0$ Signal=WW	O	O	X	X
$\beta = 2$ Signal=WW	X	X	X	X
$\beta = 0$ Signal=tt	X	O	O	X
$\beta = 2$ Signal=tt	X	X	X	X

Reference

Initial performance studies of a general-purpose detector for multi-TeV physics at a 100 TeV pp collider JINST 12 (2017) P06009