

****Test Script should be in a table format, with header as shown below. There should be at least 3 distinct test classes (as indicated in the description) per function.**

Test descriptions are supposed to be unique and should indicate classes/groups of test cases on what is being tested. For example, given the function `getAreaTri()` which computes the area of a triangle given the base and height as parameters, the following are 3 distinct classes of tests:

- i.) testing with base and height values smaller than 1
- ii.) testing with whole number values for base and height
- iii.) testing with floating point number values for base and height, larger than 1.

The following test descriptions are incorrectly formed:

Too specific: testing with base containing 0.25 and height containing 0.75

Too general: testing if function can generate correct area of triangle

Not necessary -- since already defined in pre-condition: testing with base or height containing negative values

FILL-UP THE FOLLOWING TABLE (the 1st three rows are just examples; delete it in your own document). Add new rows as you deem necessary...

Class: Pirate Crew						
Method	#	Test Description	Sample Input Data	Expected Output	Actual Output	P/F
recruitMember	1	Recruits Luffy into Straw Hat Pirates	Pirate: Luffy (unaffiliated)	true	true	P
	2	Recruits Zoro into Straw Hat Pirates	Pirate: Zoro (unaffiliated)	true	true	P
	3	Rejects Luffy re-recruiting into a second crew	Pirate: Luffy (already in Straw Hats)	false	false	P
setCaptain	4	Sets Luffy as captain once he is a crew member	Pirate: Luffy (recruited to Straw Hats)	true	true	P
getTotalBounty	5	Sums bounties of Luffy (300,000,000) + Zoro (111,000,000), both FREE	strawHats.getTotalBounty()	411000000	411000000	P
	6	Excludes Zoro's bounty after he is captured	zoro.setStatus(CAPTURED)	300000000	300000000	P
displayPirateInfo	7	Prints crew summary with correct captain and size	Straw Hat Pirates (2 members, captain Luffy)	Crew Size: 2, Captain: Monkey D. Luffy	Crew Size: 2, Captain: Monkey D. Luffy	P

Class: Marine						
Method	#	Test Description	Sample Input Data	Expected Output	Actual Output	P/F
Constructor	1	Creates Smoker with rank VICE_ADMIRAL	"Smoker", "White Hunter", VICE_ADMIRAL, wallet 10000	marineRank = VICE_ADMIRAL	VICE_ADMIRAL	P
performDuty	2	Prints VICE_ADMIRAL-specific duty	smoker.performDuty()	"Leading a Buster Call fleet..."	"Leading a Buster Call fleet..."	P

Class: MarineCorps						
Method	#	Test Description	Sample Input Data	Expected Output	Actual Output	P/F
Constructor	1	Stores operational funds provided at creation	"Marine G-5", "Enies Lobby", "Doberman", 500000	getOpFunds() = 500000	500000	P
recruitMarine	2	Recruits Smoker into Marine G-5	Marine: Smoker (unaffiliated)	true	true	P
displayMarineInfo	3	Prints corps summary with correct funds and unit size	Marine G-5 (1 member)	Operational Funds: 500000, Unit Size: 1	Operational Funds: 500000, Unit Size: 1	P

Class: DevilFruit						
Method	#	Test Description	Sample Input Data	Expected Output	Actual Output	P/F
assignNewOwner	1	Assigns Gomu Gomu no Mi to Luffy (no prior fruit)	gomuGomu.assignNewOwner(luffy)	true	true	P
displayFruit	2	Shows Luffy as current owner after assignment	gomuGomu.displayFruit()	Current Owner: Monkey D. Luffy	Current Owner: Monkey D. Luffy	P
triggerReincarnation	3	Clears current owner when Luffy dies	luffy.setStatus(DEAD)	Current Owner: None	Current Owner: None	P
	4	Adds Luffy to the fruit's historical owners	gomuGomu.getHistoricalOwners()	contains Monkey D. Luffy	contains Monkey D. Luffy	P

Class: Character						
Method	#	Test Description	Sample Input Data	Expected Output	Actual Output	P/F
setStatus	1	Clears devilFruitPower when Luffy's status becomes DEAD	luffy.setStatus(DEAD)	hasDevilFruit() = false	false	P

Class: CharacterDatabase						
Method	#	Test Description	Sample Input Data	Expected Output	Actual Output	P/F
createPirate / createMarine / createCivilian / createPirateHunter	1	Registers all 5 created characters	Luffy, Zoro, Smoker, Kaya, Zoro(hunter)	5 characters listed	5 characters listed (IDs 1-5)	P