

**\*\*Test Script should be in a table format, with header as shown below. There should be at least 3 distinct test classes (as indicated in the description) per function.**

Test descriptions are supposed to be unique and should indicate classes/groups of test cases on what is being tested. For example, given the function `getAreaTri()` which computes the area of a triangle given the base and height as parameters, the following are 3 distinct classes of tests:

- i.) testing with base and height values smaller than 1
- ii.) testing with whole number values for base and height
- iii.) testing with floating point number values for base and height, larger than 1.

The following test descriptions are incorrectly formed:

Too specific: testing with base containing 0.25 and height containing 0.75

Too general: testing if function can generate correct area of triangle

Not necessary -- since already defined in pre-condition: testing with base or height containing negative values

FILL-UP THE FOLLOWING TABLE (the 1<sup>st</sup> three rows are just examples; delete it in your own document). Add new rows as you deem necessary...

| Class: Pirate Crew |   |                                                                      |                                              |                                           |                                           |     |
|--------------------|---|----------------------------------------------------------------------|----------------------------------------------|-------------------------------------------|-------------------------------------------|-----|
| Method             | # | Test Description                                                     | Sample Input Data                            | Expected Output                           | Actual Output                             | P/F |
| recruitMember      | 1 | Recruits Luffy into Straw Hat Pirates                                | Pirate: Luffy (unaffiliated)                 | true                                      | true                                      | P   |
|                    | 2 | Recruits Zoro into Straw Hat Pirates                                 | Pirate: Zoro (unaffiliated)                  | true                                      | true                                      | P   |
|                    | 3 | Rejects Luffy re-recruiting into a second crew                       | Pirate: Luffy (already in Straw Hats)        | false                                     | false                                     | P   |
| setCaptain         | 4 | Sets Luffy as captain once he is a crew member                       | Pirate: Luffy (recruited to Straw Hats)      | true                                      | true                                      | P   |
| getTotalBounty     | 5 | Sums bounties of Luffy (300,000,000) + Zoro (111,000,000), both FREE | strawHats.getTotalBounty()                   | 411000000                                 | 411000000                                 | P   |
|                    | 6 | Excludes Zoro's bounty after he is captured                          | zoro.setStatus(CAPTURED)                     | 300000000                                 | 300000000                                 | P   |
| displayPirateInfo  | 7 | Prints crew summary with correct captain and size                    | Straw Hat Pirates (2 members, captain Luffy) | Crew Size: 2,<br>Captain: Monkey D. Luffy | Crew Size: 2,<br>Captain: Monkey D. Luffy | P   |

| Class: Marine |   |                                       |                                                      |                                  |                                  |     |
|---------------|---|---------------------------------------|------------------------------------------------------|----------------------------------|----------------------------------|-----|
| Method        | # | Test Description                      | Sample Input Data                                    | Expected Output                  | Actual Output                    | P/F |
| Constructor   | 1 | Creates Smoker with rank VICE_ADMIRAL | "Smoker", "White Hunter", VICE_ADMIRAL, wallet 10000 | marineRank = VICE_ADMIRAL        | VICE_ADMIRAL                     | P   |
| performDuty   | 2 | Prints VICE_ADMIRAL-specific duty     | smoker.performDuty()                                 | "Leading a Buster Call fleet..." | "Leading a Buster Call fleet..." | P   |

| Class: MarineCorps |   |                                                       |                                                 |                                         |                                         |     |
|--------------------|---|-------------------------------------------------------|-------------------------------------------------|-----------------------------------------|-----------------------------------------|-----|
| Method             | # | Test Description                                      | Sample Input Data                               | Expected Output                         | Actual Output                           | P/F |
| Constructor        | 1 | Stores operational funds provided at creation         | "Marine G-5", "Enies Lobby", "Doberman", 500000 | getOpFunds() = 500000                   | 500000                                  | P   |
| recruitMarine      | 2 | Recruits Smoker into Marine G-5                       | Marine: Smoker (unaffiliated)                   | true                                    | true                                    | P   |
| displayMarineInfo  | 3 | Prints corps summary with correct funds and unit size | Marine G-5 (1 member)                           | Operational Funds: 500000, Unit Size: 1 | Operational Funds: 500000, Unit Size: 1 | P   |

| Class: DevilFruit    |   |                                                   |                                |                                |                                |     |
|----------------------|---|---------------------------------------------------|--------------------------------|--------------------------------|--------------------------------|-----|
| Method               | # | Test Description                                  | Sample Input Data              | Expected Output                | Actual Output                  | P/F |
| assignNewOwner       | 1 | Assigns Gomu Gomu no Mi to Luffy (no prior fruit) | gomuGomu.assignNewOwner(luffy) | true                           | true                           | P   |
| displayFruit         | 2 | Shows Luffy as current owner after assignment     | gomuGomu.displayFruit()        | Current Owner: Monkey D. Luffy | Current Owner: Monkey D. Luffy | P   |
| triggerReincarnation | 3 | Clears current owner when Luffy dies              | luffy.setStatus(DEAD)          | Current Owner: None            | Current Owner: None            | P   |
|                      | 4 | Adds Luffy to the fruit's historical owners       | gomuGomu.getHistoricalOwners() | contains Monkey D. Luffy       | contains Monkey D. Luffy       | P   |

| Class: Character |   |                                                         |                       |                                |                                |     |
|------------------|---|---------------------------------------------------------|-----------------------|--------------------------------|--------------------------------|-----|
| Method           | # | Test Description                                        | Sample Input Data     | Expected Output                | Actual Output                  | P/F |
| setStatus        | 1 | Clears devilFruitPower when Luffy's status becomes DEAD | luffy.setStatus(DEAD) | hasDevilFruit() = false        | false                          | P   |
| performDuty      | 2 | Prints Luffy's Captain-role duty line                   | luffy.performDuty()   | "LET'S GET THIS SHIP SAILING!" | "LET'S GET THIS SHIP SAILING!" | P   |

| Class: CharacterDatabase                                          |   |                                    |                                         |                     |                               |     |
|-------------------------------------------------------------------|---|------------------------------------|-----------------------------------------|---------------------|-------------------------------|-----|
| Method                                                            | # | Test Description                   | Sample Input Data                       | Expected Output     | Actual Output                 | P/F |
| createPirate / createMarine / createCivilian / createPirateHunter | 1 | Registers all 5 created characters | Luffy, Zoro, Smoker, Kaya, Zoro(hunter) | 5 characters listed | 5 characters listed (IDs 1-5) | P   |