
```
FILE: package.json (.json file)
"name": "pcb-client",
"version": "0.1.0",
"private": true,
   "dependencies": {
     "Qtesting-library/dom": "^10.4.1",
"Qtesting-library/jest-dom": "^6.7.0",
"Qtesting-library/react": "^16.3.0",
    "@testing-library/react": "^16.3.0",
"@testing-library/user-event": "^13.5.0",
"@types/jest": "^27.5.2",
"@types/node": "^16.18.126",
"@types/react": "^19.1.10",
"@types/react-dom": "^19.1.7",
"react": "^19.1.1",
     "react-dom": "^19.1.1"
     "react-scripts": "5.0.1",
"typescript": "^4.9.5",
"web-vitals": "^2.1.4"
  },
   "scripts": {
    scripts": {
    "start": "react-scripts start",
    "build": "react-scripts build",
    "test": "react-scripts test",
    "eject": "react-scripts eject",
     "dev": "react-scripts start"
   "eslintConfig": {
     "extends": [
       "react-app"
       "react-app/jest"
    1
   "browserslist": {
     "production": [
       ">0.2%",
       "not dead"
       "not op_mini all"
     "development": [
       "last 1 chrome version",
       "last 1 firefox version",
       "last 1 safari version"
 }
}
FILE: public\index.html (.html file)
______
<!DOCTYPE html>
<html lang="en">
  <head>
     <meta charset="utf-8" />
    <meta name="theme-color" content="#000000" />
       name="description"
       content="Web site created using create-react-app"
     <link rel="apple-touch-icon" href="%PUBLIC_URL%/logo192.png" />
     <!--
       manifest.json provides metadata used when your web app is installed on a
       user's mobile device or desktop. See https://developers.google.com/web/fundamentals/web-app-manifest/
     <link rel="manifest" href="%PUBLIC URL%/manifest.ison" />
     <!--
       Notice the use of %PUBLIC_URL% in the tags above.
       It will be replaced with the URL of the `public` folder during the build.
       Only files inside the 'public' folder can be referenced from the \ensuremath{\mathsf{HTML}}.
       Unlike "/favicon.ico" or "favicon.ico", "%PUBLIC_URL%/favicon.ico" will work correctly both with client-side routing and a non-root public URL.
       Learn how to configure a non-root public URL by running `npm run build`.
    <title>React App</title>
  </head>
  <body>
     <noscript>You need to enable JavaScript to run this app.</noscript>
     <div id="root"></div>
```

```
File - C:\Users\ck\Documents\dev\source\CSCA\csca-java\5448\pcb\pcb-client\w3-client.txt
       This HTML file is a template.
       If you open it directly in the browser, you will see an empty page.
       You can add webfonts, meta tags, or analytics to this file.
       The build step will place the bundled scripts into the <body> tag.
      To begin the development, run `npm start` or `yarn start`.
To create a production bundle, use `npm run build` or `yarn build`.
   </body>
 </html>
FILE: public\manifest.json (.json file)
 ______
  "short_name": "React App",
  "name": "Create React App Sample",
"icons": [
    {
    "src": "favicon.ico",
    "44v44 32x32
      "sizes": "64x64 32x32 24x24 16x16",
"type": "image/x-icon"
    {
    "src": "logo192.png",
    "type": "image/png",
    "sizes": "192x192"
      "src": "logo512.png",
      "type": "image/png",
      "sizes": "512x512"
    }
  ],
  "start_url": ".",
"display": "standalone",
"theme_color": "#000000"
   "background_color": "#ffffff"
 }
 ______
 FILE: src\App.css (.css file)
 text-align: center;
  max-width: 1200px;
  margin: 0 auto;
  padding: 20px;
 .App-header {
  background-color: #282c34;
  padding: 20px;
   color: white;
  margin-bottom: 30px;
  border-radius: 8px;
 .App-header h1 {
  margin: 0;
  font-size: 2rem;
main {
  display: flex;
   flex-direction: column;
  gap: 30px;
 /* Simulation Controls */
 . \verb|simulation-controls| \{
  background-color: #f5f5f5;
  padding: 20px;
border-radius: 8px;
  text-align: left;
 .simulation-controls h2 {
  margin-top: 0;
  color: #333;
```

$File-C:\Users\ck\Documents\dev\source\CSCA\csca-java\5448\pcb\pcb-client\w3-client.txt$

```
.control-group {
 margin-bottom: 15px;
.control-group label {
  display: block;
margin-bottom: 5px;
  font-weight: bold;
.control-group select,
.control-group input {
  padding: 8px;
border: 1px solid #ddd;
border-radius: 4px;
  font-size: 16px;
  margin-left: 10px;
.button-group {
  display: flex;
  gap: 10px;
  margin-bottom: 15px;
  flex-wrap: wrap;
.btn-primary,
.btn-secondary,
.btn-danger {
  padding: 10px 20px;
  border: none;
  border-radius: 4px;
  cursor: pointer;
  font-size: 16px;
  transition: background-color 0.3s;
.btn-primary {
  background-color: #007bff;
  color: white;
.btn-primary:hover:not(:disabled) {
  background-color: #0056b3;
.btn-secondary {
  background-color: #6c757d;
  color: white;
.btn-secondary:hover:not(:disabled) {
  background-color: #545b62;
.btn-danger {
  background-color: #dc3545;
color: white;
.btn-danger:hover:not(:disabled) {
  background-color: #c82333;
button:disabled {
  opacity: 0.6;
  cursor: not-allowed;
/* Messages */
.message {
  padding: 15px;
  border-radius: 4px;
margin: 10px 0;
  font-weight: bold;
.message.success {
  background-color: #d4edda;
color: #155724;
  border: 1px solid #c3e6cb;
.message.error {
 background-color: #f8d7da;
color: #721c24;
  border: 1px solid #f5c6cb;
```

File - C:\Users\ck\Documents\dev\source\CSCA\csca-java\5448\pcb\pcb-client\w3-client.txt

```
.loading {
  padding: 15px;
  background-color: #fff3cd;
  color: #856404;
  border: 1px solid #ffeaa7;
  border-radius: 4px;
  margin: 10px 0;
  font-weight: bold;
/* Results */
.results-container {
  text-align: left;
.results {
  background-color: #fff;
  border: 1px solid #ddd;
border-radius: 8px;
  padding: 20px;
.simulation-result {
  margin-bottom: 30px;
  padding: 20px;
border: 1px solid #eee;
  border-radius: 8px;
  background-color: #fafafa;
.simulation-result h3 {
  margin-top: 0;
  color: #333;
  border-bottom: 2px solid #007bff;
  padding-bottom: 10px;
.simulation-result h4 {
  color: #555;
  margin-top: 20px;
.summary {
  display: grid;
  grid-template-columns: repeat(auto-fit, minmax(200px, 1fr));
  gap: 10px;
  margin: 15px 0;
padding: 15px;
  background-color: #e9f7ff;
  border-radius: 4px;
.summary p {
  margin: 0;
.failures,
.defects {
  margin: 20px 0;
table {
  width: 100%;
  border-collapse: collapse;
  margin: 10px 0;
table th,
table td {
  border: 1px solid #ddd;
  padding: 12px;
  text-align: left;
table th {
  background-color: #f8f9fa;
  font-weight: bold;
table tr:nth-child(even) {
  background-color: #f9f9f9;
.formatted-report \{
  margin-top: 20px;
.formatted-report pre {
  background-color: #f8f9fa;
```

```
padding: 15px;
  border-radius: 4px;
  overflow-x: auto;
  white-space: pre-wrap;
font-family: 'Courier New', monospace;
  font-size: 14px;
  line-height: 1.4;
/* Responsive design */
@media (max-width: 768px) {
  } aaA.
   padding: 10px;
  .button-group {
   flex-direction: column;
  .btn-primary,
  .btn-secondary,
  .btn-danger {
   width: 100%;
  .summary {
   grid-template-columns: 1fr;
 }
FILE: src\App.test.tsx (.tsx file)
______
import React from 'react';
import { render, screen } from '@testing-library/react';
import App from './App';
test('renders learn react link', () => {
 render(<App />);
  const linkElement = screen.getByText(/learn react/i);
  expect(linkElement).toBeInTheDocument();
______
FILE: src\App.tsx (.tsx file)
______
import React, { useState } from 'react';
import './App.css';
function App() {
  const [results, setResults] = useState<SimulationReport[]>([]);
  const [isLoading, setIsLoading] = useState(false);
  const [message, setMessage] = useState<string>('');
  const [error, setError] = useState<string>('');
  const showMessage = (msg: string) => {
   setMessage(msg);
   setError('');
setTimeout(() => setMessage(''), 3000);
  const showError = (err: string) => {
   setError(err);
setMessage('');
   setTimeout(() => setError(''), 5000);
 };
  const handleRunSimulation = async (pcbType: PCBType, quantity: number) => {
   setIsLoading(true);
   try {
     const response = await apiService.runSimulation(pcbType, quantity);
     showMessage(response);
   } catch (error) {
     showError(`Failed to start simulation: ${error}`);
   } finally {
     setIsLoading(false);
 };
```

```
File - C:\Users\ck\Documents\dev\source\CSCA\csca-java\5448\pcb\pcb-client\w3-client.txt
```

```
const handleRunAllSimulations = async (quantity: number) => {
    setIsLoading(true);
    try {
      const response = await apiService.runAllSimulations(quantity);
      showMessage(response);
    } catch (error) {
      showError(`Failed to start simulations: ${error}`);
    } finally {
      setIsLoading(false);
    }
  };
  const handleGetResults = async (pcbType?: PCBType) => {
    setIsLoading(true);
    try {
      if (pcbType) {
        const result = await apiService.getSimulationResults(pcbType);
        setResults([result]);
        showMessage(`Results retrieved for ${pcbType}`);
        const allResults = await apiService.getAllSimulationResults();
        setResults(allResults);
        showMessage(`Retrieved ${allResults.length} simulation results`);
    } catch (error) {
      showError(`Failed to get results: ${error}`);
    } finally {
      setIsLoading(false);
    }
  };
  const handleClearResults = async () => {
    setIsLoading(true);
    try {
      const response = await apiService.clearAllResults():
      setResults([]):
      showMessage(response);
    } catch (error) {
      showError(`Failed to clear results: ${error}`);
    } finally {
      setIsLoading(false);
  };
  return (
    <div className="App">
      <header className="App-header">
        <h1>PCB Assembly Line Simulation Client</h1>
      </header>
      <main>
        <SimulationControls
          onRunSimulation={handleRunSimulation}
          onRunAllSimulations={handleRunAllSimulations}
          onGetResults={handleGetResults}
          onClearResults={handleClearResults}
          isLoading={isLoading}
        {message && <div className="message success">{message}</div>}
        {error && <div className="message error">{error}</div>}
        {isLoading && <div className="loading">Processing...</div>}
        <div className="results-container">
          {results.length > 0 \&\& (}
            <div className="results">
             <h2>Simulation Results</h2>
             {results.map((result, index) => (
               <SimulationResult key={index} report={result} />
         ))}
</div>
             ))}
        </div>
      </main>
    </div>
);
export default App;
______
FILE: src\components\SimulationControls.tsx (.tsx file)
______
import React, { useState } from 'react';
import { PCBType } from '../types';
```

File - C:\Users\ck\Documents\dev\source\CSCA\csca-java\5448\pcb\pcb-client\w3-client.txt

```
interface SimulationControlsProps {
  onRunSimulation: (pcbType: PCBType, quantity: number) => void;
  onRunAllSimulations: (quantity: number) => void;
  onGetResults: (pcbType?: PCBType) => void;
  onClearResults: () => void;
 isLoading: boolean;
const SimulationControls: React.FC<SimulationControlsProps> = ({
  onRunAllSimulations,
 onGetResults,
  onClearResults.
  isLoading,
  const [selectedPcbType, setSelectedPcbType] = useState<PCBType>('test');
  const [quantity, setQuantity] = useState<number>(1000);
  const pcbTypes: { value: PCBType; label: string }[] = [
    { value: 'test', label: 'Test Board' }, 
{ value: 'sensor', label: 'Sensor Board' }, 
{ value: 'gateway', label: 'Gateway Board' },
 ];
 return (
    <div className="simulation-controls">
      <h2>PCB Simulation Controls</h2>
      <div className="control-group">
        <label>
          PCB Type:
          <select
            value={selectedPcbType}
            onChange={(e) => setSelectedPcbType(e.target.value as PCBType)}
disabled={isLoading}
             {pcbTypes.map((type) => (
               <option key={type.value} value={type.value}>
                 {type.label}
               </option>
            ))}
           </select>
        </label>
      </div>
      <div className="control-group">
        <label>
          Quantity:
           -
input
            type="number"
            value={quantity}
            onChange={(e) => setQuantity(parseInt(e.target.value))}
            min="1
            max="10000"
            disabled={isLoading}
          />
        </label>
      </div>
      <div className="button-group">
          onClick={() => onRunSimulation(selectedPcbType, quantity)}
          disabled={isLoading}
          className="btn-primary"
          Run Single Simulation
        </button>
        <button
          onClick={() => onRunAllSimulations(quantity)}
          disabled={isLoading}
          className="btn-primary"
          Run All Simulations
        </button>
      </div>
      <div className="button-group">
        <button
          onClick={() => onGetResults(selectedPcbType)}
          disabled={isLoading}
          className="btn-secondary"
          Get Single Results
        </button>
          onClick={() => onGetResults()}
          disabled={isLoading}
```

```
className="btn-secondary"
        Get All Results
      </button>
     </div>
     <div className="button-group">
      <button
        onClick={onClearResults}
        disabled={isLoading}
        className="btn-danger"
        Clear All Results
      </button>
     </div>
);
};
   </div>
export default SimulationControls;
______
FILE: src\components\SimulationResult.tsx (.tsx file)
-----
import React from 'react';
import { SimulationReport } from '../types';
interface SimulationResultProps {
  report: SimulationReport;
const SimulationResult: React.FC<SimulationResultProps> = ({ report }) => {
  return (
   <div className="simulation-result">
     <h3>{report.pcbType} Results</h3>
     <div className="summary">
      <strong>Total Failed:</strong> {report.totalFailedPcbs}
      <strong>Success Rate://strong> {((report.totalPcbsProduced / report.pcbsRun) * 100).toFixed(2)}%
     </div>
     <div className="failures">
      <h4>Station Failures</h4>
      <thead>
         Station
           Failures
         </thead>
        {Object.entries(report.stationFailures).map(([station, failures]) => (
           {station}
            {failures}
           ))}
        </div>
     <div className="defects">
      <h4>Defect Failures</h4>
      <thead>
         Defect Type
           Failures
         </thead>
        {Object.entries(report.defectFailures).map(([defect, failures]) => (
           {defect}
            {failures}
           ))}
        </div>
     <div className="formatted-report">
      <h4>Detailed Report</h4>
      <freport.formattedReport}</pre>
     </div>
```

```
File - C:\Users\ck\Documents\dev\source\CSCA\csca-java\5448\pcb\pcb-client\w3-client.txt
   </div>
export default SimulationResult;
_______
FILE: src\index.css (.css file)
bodv {
  margin: 0:
  font-family: -apple-system, BlinkMacSystemFont, 'Segoe UI', 'Roboto', 'Oxygen',
           'Cantarell', 'Fira Sans', 'Droid Sans', 'Helvetica Neue',
   sans-serif;
  -webkit-font-smoothing: antialiased;
  -moz-osx-font-smoothing: grayscale;
code {
  font-family: source-code-pro, Menlo, Monaco, Consolas, 'Courier New',
   monospace;
_____
FILE: src\index.tsx (.tsx file)
______
import React from 'react';
import ReactDOM from 'react-dom/client';
import './index.css';
import App from './App';
import reportWebVitals from './reportWebVitals';
const root = ReactDOM.createRoot(
  document.getElementById('root') as HTMLElement
root.render(
  <React.StrictMode>
   <App />
  </React.StrictMode>
// If you want to start measuring performance in your app, pass a function
// to log results (for example: reportWebVitals(console.log))
// or send to an analytics endpoint. Learn more: https://bit.ly/CRA-vitals
reportWebVitals();
FILE: src\react-app-env.d.ts (.ts file)
______
/// <reference types="react-scripts" />
_____
FILE: src\reportWebVitals.ts (.ts file)
______
import { ReportHandler } from 'web-vitals';
const reportWebVitals = (onPerfEntry?: ReportHandler) => {
  if (onPerfEntry && onPerfEntry instanceof Function) {
  import('web-vitals').then(({ getCLS, getFID, getFCP, getLCP, getTTFB }) => {
     getCLS(onPerfEntry);
     getFID(onPerfEntry);
     getFCP(onPerfEntry);
     getLCP(onPerfEntry);
     getTTFB(onPerfEntry);
   });
export default reportWebVitals;
_____
FILE: src\services\api.ts (.ts file)
______
import { SimulationReport, PCBType } from '../types';
```

```
File - C:\Users\ck\Documents\dev\source\CSCA\csca-java\5448\pcb\pcb-client\w3-client.txt
const BASE URL = 'http://localhost:8080/api/simulation';
 class ApiService {
  private async fetchWithErrorHandling<T>(url: string, options?: RequestInit): Promise<T> {
    try {
      const response = await fetch(url, options);
      if (!response.ok) {
        throw new Error(`HTTP error! status: ${response.status}`);
      return await response.json();
    } catch (error) {
      console.error('API call failed:', error);
       throw error;
  async runSimulation(pcbType: PCBType, quantity: number = 1000): Promise<string> {
    const response = await fetch(`${BASE_URL}/run/${pcbType}?quantity=${quantity}`, {
      method: 'POST',
      headers: {
        'Content-Type': 'application/json',
      }.
    });
    if (!response.ok) {
      throw new Error(`Failed to start simulation: ${response.status}`);
    return await response.text();
   async runAllSimulations(quantity: number = 1000): Promise<string> {
    const response = await fetch(`${BASE_URL}/run/all?quantity=${quantity}`, {
      method: 'POST',
      \  \  \, \text{headers: } \{
        'Content-Type': 'application/json',
      },
    }):
    if (!response.ok) {
      throw new Error(`Failed to start simulations: ${response.status}`);
    return await response.text();
   async getSimulationResults(pcbType: PCBType): Promise<SimulationReport> {
    return this.fetchWithErrorHandling<SimulationReport>(`${BASE_URL}/results/${pcbType}`);
  async getAllSimulationResults(): Promise<SimulationReport[]> {
    return this.fetchWithErrorHandling<SimulationReport[]>(`${BASE_URL}/results/all`);
  async getPcbTypes(): Promise<string[]> {
    return this.fetchWithErrorHandling<string[]>(`${BASE_URL}/types`);
   async clearAllResults(): Promise<string> {
    const response = await fetch(`${BASE_URL}/results`, {
  method: 'DELETE',
    if (!response.ok) {
    throw new Error(`Failed to clear results: ${response.status}`);
    return await response.text();
 export const apiService = new ApiService();
 FILE: src\setupTests.ts (.ts file)
 ______
 // jest-dom adds custom jest matchers for asserting on DOM nodes.
 // allows you to do things like:
 // expect(element).toHaveTextContent(/react/i)
 // learn more: https://github.com/testing-library/jest-dom
 import '@testing-library/jest-dom';
```

File - C:\Users\ck\Documents\dev\source\CSCA\csca-java\5448\pcb\pcb-client\w3-client.txt

```
FILE: src\types.ts (.ts file)
export interface SimulationReport {
  pcbType: string;
  pcbsRun: number;
stationFailures: Record<string, number>;
defectFailures: Record<string, number>;
  totalFailedPcbs: number;
  totalPcbsProduced: number;
  {\tt formattedReport: string;}
export type PCBType = 'test' | 'sensor' | 'gateway';
______
FILE: tsconfig.json (.json file)
{
  "compilerOptions": {
    "target": "es5",
    "lib": [
    "----"
      "dom",
"dom.iterable",
      "esnext"
    ],
"allowJs": true,
"skipLibCheck": true,
"esModuleInterop": true,
     "allowSyntheticDefaultImports": true,
    "strict": true,
"forceConsistentCasingInFileNames": true,
"noFallthroughCasesInSwitch": true,
    "module": "esnext",
"moduleResolution": "node",
"resolveJsonModule": true,
    "isolatedModules": true,
    "noEmit": true,
"jsx": "react-jsx"
 },
"include": [
    "src"
  ]
}
```

```
______
FILE: src\main\java\com\cu5448\pcb\PcbApplication.java
package com.cu5448.pcb;
import org.springframework.boot.SpringApplication;
import org.springframework.boot.autoconfigure.SpringBootApplication;
import\ org. spring framework. boot. context. properties. Enable Configuration Properties;
import\ org.spring framework.scheduling.annotation. Enable Async;
 * Main Spring Boot Application with Configuration Properties Support
 \star Demonstrates Dependency Injection design pattern implementation:
 \star - <code>@EnableConfigurationProperties</code> enables property-driven configuration - REST API endpoints
 * available for running simulations on demand - All dependencies managed by Spring IoC container

    * - @EnableAsync enables asynchronous method execution for simulation processing

 \star Server starts and waits for client API calls to run simulations and retrieve results.
@SpringBootApplication
@EnableConfigurationProperties
@EnableAsync
public class PcbApplication {
    public static void main(String[] args) {
       SpringApplication.run(PcbApplication.class, args);
}
______
FILE: src\main\java\com\cu5448\pcb\api\SimulationApiController.java
package com.cu5448.pcb.api;
import java.util.ArrayList;
import java.util.List;
import java.util.Map;
import org.springframework.http.ResponseEntity;
import org.springframework.web.bind.annotation.*;
import com.cu5448.pcb.controller.SimulationController;
import com.cu5448.pcb.dto.SimulationReportDto;
import com.cu5448.pcb.dto.SimulationReportMapper;
import com.cu5448.pcb.service.StatisticsCollector;
import lombok.RequiredArgsConstructor;
 \star REST API Controller for PCB simulation operations. Implements the server-side requirement: run
 \star simulations to gather failure results in memory, then wait for client API calls to retrieve the
 * stored simulation results as JSON.
 * Provides separate endpoints for running simulations and retrieving stored results, ensuring
 * results are maintained in memory between API calls.
@RestController
@RequestMapping("/api/simulation")
@CrossOrigin(origins = "http://localhost:3000")
@RequiredArgsConstructor
public class SimulationApiController {
    private final SimulationController simulationController:
    private final SimulationReportMapper reportMapper;
    \star Start simulation for a specific PCB type asynchronously and store results in memory.
     * @param pcbType the type of PCB to simulate (test, sensor, gateway)
     * @param quantity number of PCBs to process (default: 1000)
     * @return 201 Created status to indicate simulation started
    @PostMapping("/run/{pcbType}")
    public ResponseEntity<String> runSimulation(
           @PathVariable String pcbType, @RequestParam(defaultValue = "1000") int quantity) {
        // Start simulation asynchronously using @Async method
        simulationController.runSimulationAsync(pcbType, quantity);
       return ResponseEntity.status(201)
               .body(
                       String.format(
                               "Simulation started asynchronously for PCB type: %s with quantity: %d",
```

```
pcbTvpe, quantity)):
 * Start simulations for all three PCB types asynchronously and store results in memory.
 * @param quantity number of PCBs to process for each type (default: 1000)
 * @return 201 Created status to indicate simulations started
@PostMapping("/run/all")
public ResponseEntity<String> runAllSimulations(
     @RequestParam(defaultValue = "1000") int quantity) {
    // Start all simulations asynchronously using @Async method
    simulationController.runAllSimulationsAsync();
    return ResponseEntity.status(201)
             .body(
                     String.format(
                              "Simulations started asynchronously for all PCB types with quantity: %d",
                              quantity));
}
/**
 * Retrieve stored simulation results for a specific PCB type.
 * @param pcbType the type of PCB to get results for
 \star <code>@return simulation report as JSON, or 404 if not found</code>
@GetMapping("/results/{pcbType}")
public ResponseEntity<SimulationReportDto> getSimulationResults(@PathVariable String pcbType) {
    StatisticsCollector stats = simulationController.getSimulationResults(pcbType);
    if (stats == null) {
        return ResponseEntity.notFound().build();
    SimulationReportDto report = reportMapper.toDto(stats, pcbType);
    return ResponseEntity.ok(report);
}
 * Retrieve all stored simulation results.
 * @return list of simulation reports for all stored results
@GetMapping("/results/all")
public ResponseEntity<List<SimulationReportDto>> getAllSimulationResults() {
    Map<String, StatisticsCollector> allResults =
             simulationController.getAllSimulationResults();
    if (allResults.isEmpty()) {
        return ResponseEntity.notFound().build();
    List<SimulationReportDto> reports = new ArrayList<>();
    for (Map.Entry<String, StatisticsCollector> entry : allResults.entrySet()) {
   SimulationReportDto report = reportMapper.toDto(entry.getValue(), entry.getKey());
        reports.add(report);
    return ResponseEntity.ok(reports);
}
 * Get available PCB types.
 * @return list of supported PCB types
@GetMapping("/types")
public ResponseEntity<List<String>> getPcbTypes() {
    List<String> types = List.of("Test Board", "Sensor Board", "Gateway Board");
    return ResponseEntity.ok(types);
}
 * Clear all stored simulation results.
 * @return success response
@DeleteMapping("/results")
public ResponseEntity<String> clearAllResults() {
    simulationController.clearAllResults();
    return ResponseEntity.ok("All simulation results cleared");
```

}

```
_____
FILE: src\main\java\com\cu5448\pcb\config\CorsConfig.java
package com.cu5448.pcb.config;
import org.springframework.context.annotation.Bean;
import org.springframework.context.annotation.Configuration:
import org.springframework.web.cors.CorsConfiguration;
import\ org.springframework.web.cors. Cors Configuration Source;
import\ org.spring framework.web.cors. Url Based Cors Configuration Source;
import org.springframework.web.servlet.config.annotation.CorsRegistry;
import org.springframework.web.servlet.config.annotation.WebMvcConfigurer;
* CORS configuration to allow React client (localhost:3000) to communicate with the Spring Boot
* server (localhost:8080).
@Configuration
public class CorsConfig implements WebMvcConfigurer {
   public void addCorsMappings(CorsRegistry registry) {
   registry.addMapping("/api/**")
              .allowedOrigins("http://localhost:3000")
              .allowedMethods("GET", "POST", "PUT", "DELETE", "OPTIONS")
              .allowedHeaders("*")
              .allowCredentials(true);
   }
   public CorsConfigurationSource corsConfigurationSource() {
       CorsConfiguration configuration = new CorsConfiguration();
configuration.addAllowedOrigin("http://localhost:3000");
       configuration.addAllowedMethod("*");
       configuration.addAllowedHeader("*");
       configuration.setAllowCredentials(true);
       return source;
   }
}
______
FILE: src\main\java\com\cu5448\pcb\config\PCBProperties.java
______
package com.cu5448.pcb.config;
import\ org. spring framework. boot. context. properties. Configuration Properties;
import org.springframework.stereotype.Component;
import com.cu5448.pcb.model.DefectRates;
import lombok.Data;
\star PCB Configuration Properties that directly create DefectRates instances. This approach eliminates
* nested property classes and provides direct access to DefectRates objects for each PCB type.
@Data
@Component
@ConfigurationProperties(prefix = "pcb")
public class PCBProperties {
   private DefectRates testboard = new DefectRates():
   private DefectRates sensorboard = new DefectRates();
   private DefectRates gatewayboard = new DefectRates();
}
FILE: src\main\java\com\cu5448\pcb\config\PCBSimulationConfig.java
______
package com.cu5448.pcb.config;
import java.util.List;
import org.springframework.context.annotation.Bean;
import org.springframework.context.annotation.Configuration;
import com.cu5448.pcb.factory.StationFactory;
import com.cu5448.pcb.station.*;
```

```
import lombok.RequiredArgsConstructor;
 \star Spring Configuration Class using Abstract Factory Pattern for PCB Assembly Line Stations. The
 \star configuration delegates station creation to a StationFactory, maintaining the factory pattern
 * while leveraging Spring's dependency injection.
@Configuration
@RequiredArgsConstructor
public class PCBSimulationConfig {
    private final StationFactory stationFactory:
     \star Creates ordered list of stations for the assembly line using the abstract factory pattern.
     \star This ensures consistent station creation and proper manufacturing process flow.
    @Bean
    public List<Station> createAssemblyLineStations() {
       return List.of(
                stationFactory.createStation("ApplySolderPaste"),
stationFactory.createStation("PlaceComponents"),
stationFactory.createStation("ReflowSolder"),
                stationFactory.createStation("OpticalInspection"),
                stationFactory.createStation("HandSoldering"),
                stationFactory.createStation("Cleaning"),
                stationFactory.createStation("Depanelization"),
                stationFactory.createStation("Test"));
   }
}
______
FILE: src\main\iava\com\cu5448\pcb\config\StationProperties.iava
package com.cu5448.pcb.config;
import org.springframework.boot.context.properties.ConfigurationProperties;
import org.springframework.stereotype.Component;
import lombok.Data;
/** Station Configuration Properties using Lombok @Data generates all necessary boilerplate code */
@Data
@Component
@ConfigurationProperties(prefix = "station")
public class StationProperties {
    private double failureRate = 0.002;
______
FILE: src\main\java\com\cu5448\pcb\controller\SimulationController.java
package com.cu5448.pcb.controller;
import java.util.HashMap;
import java.util.Map;
import java.util.concurrent.CompletableFuture;
import org.springframework.scheduling.annotation.Async;
import\ org. spring framework. stereotype. Component;
import com.cu5448.pcb.service.AssemblyLine;
import com.cu5448.pcb.service.StatisticsCollector;
import lombok.RequiredArgsConstructor;
 * Main Simulation Controller using Spring Dependency Injection and Lombok @RequiredArgsConstructor
  generates constructor for final fields. This controller orchestrates PCB simulations and manages
 * results storage for REST API access.
 \star Supports the server-side requirement: run simulations to gather failure results in memory,
 * then wait for client API calls to retrieve the stored simulation results.
@Component
@RequiredArgsConstructor
public class SimulationController {
    private final AssemblyLine assemblyLine;
    private final Map<String, StatisticsCollector> results = new HashMap<>();
```

```
\star Run simulation for a specific PCB type asynchronously and store results in memory.
 * @param pcbType the type of PCB to simulate
 \star @param quantity number of PCBs to process
 * @return CompletableFuture with the statistics collector results
@Async
\verb|public CompletableFuture < StatisticsCollector > \verb|runSimulationAsync(String pcbType, int quantity)| \\
    StatisticsCollector stats = assemblyLine.runSimulation(pcbType, quantity);
    results.put(pcbType, stats);
    return CompletableFuture.completedFuture(stats);
}
 * Run simulation for a specific PCB type synchronously (for internal use).
 * @param pcbType the type of PCB to simulate
 * @param quantity number of PCBs to process
 * @return the statistics collector with simulation results
public StatisticsCollector runSimulation(String pcbType, int quantity) {
    StatisticsCollector stats = assemblyLine.runSimulation(pcbType, quantity);
    results.put(pcbType, stats);
    return stats;
}
 * Run simulation for a specific PCB type with default quantity (1000).
 * @param pcbType the type of PCB to simulate
 * @return the statistics collector with simulation results
public StatisticsCollector runSimulation(String pcbType) {
    return runSimulation(pcbType, 1000);
 * Run simulations for all three PCB types asynchronously and store results in memory.
 \star @return CompletableFuture that completes when all simulations are done
@Async
public CompletableFuture<Map<String, StatisticsCollector>> runAllSimulationsAsync() {
    runSimulation("Test Board"):
    runSimulation("Sensor Board");
    runSimulation("Gateway Board");
    return CompletableFuture.completedFuture(new HashMap<>(results));
}
 * Run simulations for all three PCB types synchronously (for internal use).
 * @return map of all simulation results by PCB type
public Map<String, StatisticsCollector> runAllSimulations() {
   runSimulation("Test Board");
    runSimulation("Sensor Board");
    runSimulation("Gateway Board");
    return new HashMap<>(results);
}
/**
 * Retrieve stored simulation results for a specific PCB type.
 * @param pcbType the type of PCB to get results for
 \boldsymbol{\star} @return the statistics collector with results, or null if not found
public StatisticsCollector getSimulationResults(String pcbType) {
    return results.get(pcbType);
/**
 * Retrieve all stored simulation results.
 * @return map of all simulation results by PCB type
public Map<String, StatisticsCollector> getAllSimulationResults() {
    return new HashMap<>(results);
 * Check if simulation results exist for a specific PCB type.
 * @param pcbType the type of PCB to check
 * @return true if results exist, false otherwise
public boolean hasSimulationResults(String pcbType) {
```

```
return results.containsKey(pcbType);
   /** Clear all stored simulation results. */
   public void clearAllResults() {
       results.clear();
    * Print results to console (for debugging/testing purposes).
    * @param pcbType the type of PCB to print results for
   public void printResults(String pcbType) {
       StatisticsCollector stats = results.get(pcbType);
       if (stats != null) {
          System.out.println(stats.generateReport(pcbType));
       } else {
          System.out.printf("No results found for PCB type: %s\n", pcbType);
}
FILE: src\main\java\com\cu5448\pcb\dto\SimulationReportDto.java
_____
package com.cu5448.pcb.dto;
import java.util.Map;
import com.fasterxml.jackson.annotation.JsonProperty;
import lombok.AllArgsConstructor;
import lombok.Data;
import lombok.NoArgsConstructor;
* Data Transfer Object for simulation report data used in REST API communication between server and
 * client applications.
@Data
@NoArgsConstructor
@AllArgsConstructor
public class SimulationReportDto {
   @JsonProperty("pcbType")
   private String pcbType;
   @JsonProperty("pcbsRun")
   private int pcbsRun;
   @JsonProperty("stationFailures")
   private Map<String, Integer> stationFailures;
   @JsonProperty("defectFailures")
   private Map<String, Integer> defectFailures;
   @JsonProperty("totalFailedPcbs")
   private int totalFailedPcbs;
   @JsonProperty("totalPcbsProduced")
   private int totalPcbsProduced;
   @JsonProperty("formattedReport")
   private String formattedReport;
}
_____
FILE: src\main\java\com\cu5448\pcb\dto\SimulationReportMapper.java
______
package com.cu5448.pcb.dto;
import org.springframework.stereotype.Component;
import com.cu5448.pcb.service.StatisticsCollector;
* Mapper class to convert StatisticsCollector data to SimulationReportDto for API communication.
*/
@Component
public class SimulationReportMapper {
   public SimulationReportDto toDto(StatisticsCollector stats, String pcbType) {
```

```
File - C:\Users\ck\Documents\dev\source\CSCA\csca-java\5448\pcb\w3-code.txt
         SimulationReportDto dto = new SimulationReportDto();
         dto.setPcbType(pcbType);
         dto.setPcbsRun(stats.getPcbsSubmitted());
         dto.setStationFailures(stats.getStationFailures());
        dto.setDefectFailures(stats.getDefectFailures());
dto.setTotalFailedPcbs(stats.getPcbsSubmitted() - stats.getCompletedPCBs());
         dto.setTotalPcbsProduced(stats.getCompletedPCBs());
         dto.setFormattedReport(stats.generateReport(pcbType));
         return dto;
    }
 }
 _____
 FILE: src\main\java\com\cu5448\pcb\factory\PCBFactory.java
 package com.cu5448.pcb.factory;
 import org.springframework.stereotype.Component;
 import com.cu5448.pcb.config.PCBProperties;
 import com.cu5448.pcb.model.GatewayBoard;
 import com.cu5448.pcb.model.PCB;
 import com.cu5448.pcb.model.SensorBoard;
 import com.cu5448.pcb.model.TestBoard;
 import lombok.RequiredArgsConstructor;
 \star Factory Pattern Implementation using Spring Dependency Injection and
  * Lombok @RequiredArgsConstructor generates constructor for final fields This factory creates PCB
  * instances with configuration-driven defect rates.
 @Component
 @RequiredArgsConstructor
 public class PCBFactory {
     private final PCBProperties pcbProperties;
     public PCB createPCB(String type) {
         return switch (type.toLowerCase()) {
  case "testboard", "test", "test board" -> new TestBoard(pcbProperties.getTestboard());
  case "sensorboard", "sensor", "sensor board" ->
                    new SensorBoard(pcbProperties.getSensorboard());
             case "gatewayboard", "gateway", "gateway board" ->
                    new GatewayBoard(pcbProperties.getGatewayboard());
             default -> throw new IllegalArgumentException("Unknown PCB type: " + type);
        };
    }
 }
 _______
 FILE: src\main\java\com\cu5448\pcb\factory\StationFactory.java
 package com.cu5448.pcb.factory;
 import java.util.Map;
 import java.util.function.Function;
 import org.springframework.stereotype.Component;
 import com.cu5448.pcb.config.StationProperties;
 import com.cu5448.pcb.station.*;
 import lombok.RequiredArgsConstructor;
 /**
 * Abstract Factory for creating PCB manufacturing stations using Spring Dependency Injection. This
  * factory uses a registry pattern to eliminate the need for individual creation methods for each
  * station type, making it more extensible and following the Abstract Factory pattern.
 @Component
 @RequiredArasConstructor
 public class StationFactory {
     private final StationProperties stationProperties;
     // Registry of station constructors using method references
     private final Map<String, Function<Double, Station>> stationRegistry =
             Map.of(
                     "ApplySolderPaste", ApplySolderPasteStation::new,
                     "PlaceComponents", PlaceComponentsStation::new,
```

```
File - C:\Users\ck\Documents\dev\source\CSCA\csca-java\5448\pcb\w3-code.txt
                     "ReflowSolder", ReflowSolderStation::new,
                     "OpticalInspection", OpticalInspectionStation::new,
                     "HandSoldering", HandSolderingStation::new,
                     "Cleaning", CleaningStation::new,
                     "Depanelization", DepanelizationStation::new,
                     "Test", TestStation::new);
     /**
      * Creates a station by type name using the Abstract Factory pattern. This method uses a
      \star registry of constructor method references to eliminate the need for individual creation
      \star @param stationType the type of station to create (e.g., "ApplySolderPaste", "Test")
      * @return Station instance of the specified type
      * @throws IllegalArgumentException if station type is unknown
     public Station createStation(String stationType) {
        Function<Double, Station> constructor = stationRegistry.get(stationType); if (constructor == null) {
             throw new IllegalArgumentException("Unknown station type: " + stationType);
         return constructor.apply(stationProperties.getFailureRate());
    }
}
 _____
FILE: src\main\iava\com\cu5448\pcb\model\DefectRates.iava
 package com.cu5448.pcb.model;
 import lombok.AllArgsConstructor;
 import lombok.Builder;
 import lombok.Data;
 import lombok.NoArgsConstructor;
 \star DefectRates encapsulates defect rates for different manufacturing stations. This class replaces
 * the Map<String, Double> approach with a type-safe, immutable object.
  \star Only four stations can detect defects: PlaceComponents, OpticalInspection, HandSoldering, and
 @Data
 @Builder
 @AllArgsConstructor
 @NoArgsConstructor
 public class DefectRates {
     private double placeComponentsDefectRate;
     private double opticalInspectionDefectRate;
     private double handSolderingDefectRate;
     private double testDefectRate;
     * Gets the defect rate for a specific station type.
      * @param stationType the station type name
      \star @return the defect rate for the station, or 0.0 if the station doesn't detect defects
     public double getDefectRate(String stationType) {
         return switch (stationType) {
             case "PlaceComponents" -> placeComponentsDefectRate;
case "OpticalInspection" -> opticalInspectionDefectRate;
             case "HandSoldering" -> handSolderingDefectRate;
             case "Test" -> testDefectRate;
             default -> 0.0; // Stations that don't detect defects
        };
    }
 }
```

```
FILE: src\main\java\com\cu5448\pcb\model\GatewayBoard.java

package com.cu5448.pcb.model;

import lombok.EqualsAndHashCode;

/** Gateway Board PCB Implementation using Lombok */
@EqualsAndHashCode(callSuper = true)
public class GatewayBoard extends PCB {

private final DefectRates defectRates;
```

```
File - C:\Users\ck\Documents\dev\source\CSCA\csca-java\5448\pcb\w3-code.txt
    public GatewayBoard(DefectRates defectRates) {
       super("GatewayBoard");
        this.defectRates = defectRates;
    @Override
    public double getDefectRate(String stationType) {
       return defectRates.getDefectRate(stationType);
    @Override
    public DefectRates getDefectRates() {
       return defectRates;
}
______
FILE: src\main\java\com\cu5448\pcb\model\PCB.java
 -----
package com.cu5448.pcb.model;
import java.util.UUID;
import lombok.Getter;
import lombok.ToString;
 \star Abstract PCB Model using Lombok @Getter generates getters for all fields @ToString generates
 * toString method
@Getter
@ToString
public abstract class PCB {
    private final String id;
    private final String type;
    private boolean failed = false;
    private String failureReason = null;
    public PCB(String type) {
       this.id = UUID.randomUUID().toString();
       this.type = type;
    public void setFailed(String reason) {
       this.failed = true;
       this.failureReason = reason;
    public abstract double getDefectRate(String stationType);
    public abstract DefectRates getDefectRates();
}
______
FILE: src\main\java\com\cu5448\pcb\model\SensorBoard.java
package com.cu5448.pcb.model;
import lombok.EqualsAndHashCode;
/** Sensor Board PCB Implementation using Lombok */
@EqualsAndHashCode(callSuper = true)
public class SensorBoard extends PCB {
    private final DefectRates defectRates:
    public SensorBoard(DefectRates defectRates) {
       super("SensorBoard");
       this.defectRates = defectRates;
    public double getDefectRate(String stationType) {
       return defectRates.getDefectRate(stationType);
    @Override
    public DefectRates getDefectRates() {
       return defectRates;
```

```
_____
FILE: src\main\java\com\cu5448\pcb\model\TestBoard.java
package com.cu5448.pcb.model;
import lombok.EqualsAndHashCode;
/** Test Board PCB Implementation using Lombok */
@EqualsAndHashCode(callSuper = true)
public class TestBoard extends PCB {
   private final DefectRates defectRates;
   public TestBoard(DefectRates defectRates) {
       super("TestBoard");
       this.defectRates = defectRates;
   }
   @Override
   public double getDefectRate(String stationType) {
       return defectRates.getDefectRate(stationType);
   @Override
   public DefectRates getDefectRates() {
       return defectRates;
}
______
FILE: src\main\java\com\cu5448\pcb\service\AssemblyLine.java
______
package com.cu5448.pcb.service;
import java.util.List;
import org.springframework.context.ApplicationContext;
import org.springframework.stereotype.Service;
import com.cu5448.pcb.factory.PCBFactory;
import com.cu5448.pcb.model.PCB;
import com.cu5448.pcb.station.Station;
import lombok.RequiredArgsConstructor;
* Assembly Line Service using Spring Dependency Injection. Station beans are injected as an ordered
\star list, eliminating the need for manual station creation and initialization.
@Service
@RequiredArgsConstructor
public class AssemblyLine {
   private final List<Station> stations;
   private final PCBFactory factory;
   private final ApplicationContext applicationContext;
   public void processPCB(PCB pcb, StatisticsCollector stats) {
       for (Station station : stations) {
           station.process(pcb, stats);
           if (pcb.isFailed()) {
              break;
          }
       }
   \verb"public StatisticsCollector runSimulation(String pcbType, int quantity) \{
       // Get a new prototype instance of StatisticsCollector for this simulation
       StatisticsCollector stats = applicationContext.getBean(StatisticsCollector.class);
       for (int i = 0; i < quantity; i++) {
           PCB pcb = factory.createPCB(pcbType);
           stats.recordSubmission();
           processPCB(pcb, stats):
           if (!pcb.isFailed()) {
              stats.recordCompletion();
```

```
File - C:\Users\ck\Documents\dev\source\CSCA\csca-java\5448\pcb\w3-code.txt
                                           }
                              return stats;
                 public List<Station> getStations() {
                              return List.copyOf(stations);
   }
   _____
   FILE: src\main\java\com\cu5448\pcb\service\StatisticsCollector.java
    ______
   package com.cu5448.pcb.service;
   import java.util.HashMap;
   import java.util.Map;
   import\ org. spring framework. context. annotation. Scope;
   import org.springframework.stereotype.Service;
   import lombok.Getter;
       {\color{blue}\star} \ {\color{blue}\texttt{Observer}} \ {\color{blue}\texttt{Pattern}} \ {\color{blue}\texttt{Implementation}} \ {\color{blue}\texttt{as}} \ {\color{blue}\texttt{Spring}} \ {\color{blue}\texttt{Service}} \ {\color{blue}\texttt{using}} \ {\color{blue}\texttt{Lombok}} \ {\color{blue}\texttt{@Getter}} \ {\color{blue}\texttt{generates}} \ {\color{blue}\texttt{getter}} \ {\color{blue}\texttt{methods}} 
       \star for all fields This service observes events from stations during PCB processing. Uses prototype
       * scope to create new instances for each simulation run.
   @Service
   @Scope("prototype")
   @Getter
   public class StatisticsCollector {
                 private int pcbsSubmitted;
                 private final Map<String, Integer> defectFailures;
                 private final Map<String, Integer> stationFailures;
                 private int completedPCBs;
                 public StatisticsCollector() {
                              this.pcbsSubmitted = 0:
                               this.defectFailures = new HashMap<>();
                               this.stationFailures = new HashMap<>();
                              this.completedPCBs = 0;
                }
                 public void recordSubmission() {
                              pcbsSubmitted++;
                 public void recordDefectFailure(String station) {
                              defectFailures.merge(station, 1, Integer::sum);
                 public void recordStationFailure(String station) {
                               stationFailures.merge(station, 1, Integer::sum);
                 public void recordCompletion() {
                              completedPCBs++;
                 public String generateReport(String pcbType) {
                              StringBuilder report = new StringBuilder();
                              // Format according to project specification % \left( 1\right) =\left( 1\right) \left( 1\right) \left
                              report.append(String.format("PCB type: %s\n", pcbType));
report.append(String.format("PCBs run: %d\n", pcbSybmitted));
                              report.append("\nStation Failures\n");
                               // Show all stations in assembly order
                               String[] stationNames = {
                                             "Apply Solder Paste",
"Place Components",
                                             "Reflow Solder",
                                             "Optical Inspection",
                                             "Hand Soldering/Assembly",
                                             "Cleaning",
                                             "Depanelization",
                                             "Test (ICT or Flying Probe)"
                              };
                              String[] stationKeys = {
```

```
File - C:\Users\ck\Documents\dev\source\CSCA\csca-java\5448\pcb\w3-code.txt
```

```
"ApplvSolderPaste",
            "PlaceComponents",
            "ReflowSolder",
            "OpticalInspection",
            "HandSoldering",
            "Cleaning",
            "Depanelization",
            "Test"
       };
       for (int i = 0; i < stationNames.length; i++) { int failures = stationFailures.getOrDefault(stationKeys[i], 0);
           report.append(String.format("%s: %d\n", stationNames[i], failures));
       report.append("\nPCB Defect Failures\n");
        // Only show defect-detecting stations
       String[] defectStationNames = {
            "Place Components",
            "Optical Inspection",
            "Hand Soldering/Assembly"
            "Test (ICT or Flying Probe)"
       String[] defectStationKeys = {
            "PlaceComponents", "OpticalInspection", "HandSoldering", "Test"
       for (int i = 0; i < defectStationNames.length; i++) {
           int\ failures\ =\ defectFailures.getOrDefault(defectStationKeys[i],\ 0);
           report.append(String.format("%s %d\n", defectStationNames[i], failures));
        // Calculate total failures and successful PCBs
       int totalFailed = pcbsSubmitted - completedPCBs;
       report.append("\nFinal Results\n");
report.append(String.format("Total failed PCBs: %d\n", totalFailed));
       report.append(String.format("Total PCBs produced: %d\n", completedPCBs));
       return report.toString();
}
______
FILE: src\main\java\com\cu5448\pcb\station\ApplySolderPasteStation.java
package com.cu5448.pcb.station;
import com.cu5448.pcb.model.PCB;
public class ApplySolderPasteStation extends Station {
    public ApplySolderPasteStation(double failureRate) {
        super("ApplySolderPaste", failureRate);
    protected boolean performOperation(PCB pcb) {
       return true;
}
_____
FILE: src\main\java\com\cu5448\pcb\station\CleaningStation.java
package com.cu5448.pcb.station;
import com.cu5448.pcb.model.PCB;
public class CleaningStation extends Station {
    public CleaningStation(double failureRate) {
        super("Cleaning", failureRate);
   protected boolean performOperation(PCB pcb) {
       return true;
}
```

```
______
FILE: src\main\java\com\cu5448\pcb\station\DepanelizationStation.java
package com.cu5448.pcb.station;
import com.cu5448.pcb.model.PCB;
public class DepanelizationStation extends Station {
   public DepanelizationStation(double failureRate) {
      super("Depanelization", failureRate);
   }
   protected boolean performOperation(PCB pcb) {
      return true;
______
FILE: src\main\java\com\cu5448\pcb\station\HandSolderingStation.java
package com.cu5448.pcb.station;
import com.cu5448.pcb.model.PCB;
import lombok.EqualsAndHashCode;
/** Hand Soldering Station using Lombok */
@EqualsAndHashCode(callSuper = true)
public class HandSolderingStation extends Station {
   public HandSolderingStation(double failureRate) {
      super("HandSoldering", failureRate);
   @Override
   protected boolean performOperation(PCB pcb) {
      double defectRate = pcb.getDefectRate("HandSoldering");
      return random.nextDouble() >= defectRate;
   }
}
_____
FILE: \verb| src\main\java\com\cu5448\pcb\station\OpticalInspection\Station.java| \\
______
package com.cu5448.pcb.station;
import com.cu5448.pcb.model.PCB;
import lombok.EqualsAndHashCode:
/** Optical Inspection Station using Lombok */
@EqualsAndHashCode(callSuper = true)
public class OpticalInspectionStation extends Station {
   public OpticalInspectionStation(double failureRate) {
      super("OpticalInspection", failureRate);
   @Override
   protected boolean performOperation(PCB pcb) {
      double defectRate = pcb.getDefectRate("OpticalInspection");
      return random.nextDouble() >= defectRate;
}
FILE: src\main\java\com\cu5448\pcb\station\PlaceComponentsStation.java
______
package com.cu5448.pcb.station;
import com.cu5448.pcb.model.PCB;
import lombok.EqualsAndHashCode;
* Place Components Station using Lombok @EqualsAndHashCode(callSuper = true) includes parent class
* fields in equals/hashCode
```

```
@EqualsAndHashCode(callSuper = true)
public class PlaceComponentsStation extends Station {
   public PlaceComponentsStation(double failureRate) {
       super("PlaceComponents", failureRate);
   protected boolean performOperation(PCB pcb) {
       double defectRate = pcb.getDefectRate("PlaceComponents");
return random.nextDouble() >= defectRate;
   }
}
______
FILE: src\main\java\com\cu5448\pcb\station\ReflowSolderStation.java
package com.cu5448.pcb.station;
import com.cu5448.pcb.model.PCB:
public class ReflowSolderStation extends Station {
   public ReflowSolderStation(double failureRate) {
       super("ReflowSolder", failureRate);
   protected boolean performOperation(PCB pcb) {
       return true;
}
______
FILE: src\main\java\com\cu5448\pcb\station\Station.java
______
package com.cu5448.pcb.station;
import java.util.Random;
import com.cu5448.pcb.model.PCB;
import com.cu5448.pcb.service.StatisticsCollector;
import lombok. Getter:
* Abstract Station class that can be used as a Spring bean. StatisticsCollector is injected per
 * simulation run rather than at construction time.
@Getter
public abstract class Station {
   protected final String name;
   protected final double stationFailureRate;
   protected final Random random = new Random();
   public Station(String name, double failureRate) {
       this.name = name;
       this.stationFailureRate = failureRate;
   public void process(PCB pcb, StatisticsCollector stats) {
       if (pcb.isFailed()) {
           return;
       }
       if (checkStationFailure()) {
           stats.recordStationFailure(name);
           pcb.setFailed("Station failure at " + name);
           return;
       }
       boolean operationSuccessful = performOperation(pcb);
       if (!operationSuccessful) {
           stats.recordDefectFailure(name);
           pcb.setFailed("Defect detected at " + name);
       }
   protected boolean checkStationFailure() {
```

```
File - C:\Users\ck\Documents\dev\source\CSCA\csca-java\5448\pcb\w3-code.txt
       return random.nextDouble() < stationFailureRate;</pre>
    protected abstract boolean performOperation(PCB pcb);
}
------
FILE: src\main\java\com\cu5448\pcb\station\TestStation.java
 _____
package com.cu5448.pcb.station:
import com.cu5448.pcb.model.PCB;
import lombok.EqualsAndHashCode;
/** Test Station using Lombok */
@EqualsAndHashCode(callSuper = true)
public class TestStation extends Station {
    public TestStation(double failureRate) {
    super("Test", failureRate);
    @Override
    protected boolean performOperation(PCB pcb) {
       double defectRate = pcb.getDefectRate("Test");
return random.nextDouble() >= defectRate;
}
_______
FILE: src\test\java\com\cu5448\pcb\PcbApplicationTests.java
package com.cu5448.pcb:
import org.junit.jupiter.api.Test;
import org.springframework.boot.test.context.SpringBootTest;
@SpringBootTest
class PcbApplicationTests {
    void contextLoads() {}
}
FILE: src\test\java\com\cu5448\pcb\config\SpringBeanConfigurationTest.java
_____
package com.cu5448.pcb.config:
import static org.junit.jupiter.api.Assertions.*;
import java.util.List;
import org.junit.jupiter.api.Test;
import org.springframework.boot.test.context.SpringBootTest;
import org.springframework.test.context.TestConstructor;
import com.cu5448.pcb.service.AssemblyLine;
import com.cu5448.pcb.station.*;
import lombok.RequiredArgsConstructor;
/** Test class to verify Spring bean configuration using Abstract Factory Pattern */
@SpringBootTest
@TestConstructor(autowireMode = TestConstructor.AutowireMode.ALL)
@RequiredArgsConstructor
class SpringBeanConfigurationTest {
    private final AssemblyLine assemblyLine;
    private final List<Station> stations;
    void testAssemblyLineInjection() {
   assertNotNull(assemblyLine, "AssemblyLine should be injected");
       List<Station> assemblyStations = assemblyLine.getStations();
        assertEquals(8, assemblyStations.size(), "Assembly line should have 8 stations");
```

```
@Test
    void testStationListOrder() {
        assertNotNull(stations, "Station list should be injected");
        assertEquals(8, stations.size(), "Should have 8 stations");
        // Verify the correct order of stations
        // Veily the context order of stations
assertEquals("ApplySolderPaste", stations.get(0).getName());
assertEquals("PlaceComponents", stations.get(1).getName());
        assertEquals("ReflowSolder", stations.get(2).getName());
        assertEquals("OpticalInspection", stations.get(3).getName());
assertEquals("HandSoldering", stations.get(4).getName());
        assertEquals("Cleaning", stations.get(5).getName());
assertEquals("Depanelization", stations.get(6).getName());
        assertEquals("Test", stations.get(7).getName());
    }
    @Test
    void testStationFailureRatesAreConfigured() {
        // All stations should have the same configured failure rate
        double expectedFailureRate = 0.002; // From application.properties
        for (Station station : stations) {
            assertEquals(
                    expectedFailureRate,
                    station.getStationFailureRate(),
                     "Station " + station.getName() + " should have configured failure rate");
        }
    }
    @Test
    void testAssemblyLineStationsAreSameAsInjectedList() {
        List<Station> assemblyStations = assemblyLine.getStations();
        // Verify same stations are used (but different list instance due to List.copv0f)
        assertEquals(stations.size(), assemblyStations.size());
        for (int i = 0; i < stations.size(); i++) {
            assertSame(
                    stations.get(i),
                    assemblyStations.get(i),
                     "Station " + i + " should be the same bean instance");
    }
}
______
FILE: src\test\java\com\cu5448\pcb\config\SpringConfigurationTest.java
______
package com.cu5448.pcb.config;
import static org.junit.jupiter.api.Assertions.*;
import org.junit.jupiter.api.Test;
import org.springframework.boot.test.context.SpringBootTest;
import org.springframework.test.context.TestConstructor;
import com.cu5448.pcb.controller.SimulationController;
import com.cu5448.pcb.factory.PCBFactory;
import com.cu5448.pcb.service.AssemblyLine;
import lombok.RequiredArgsConstructor;
@SpringBootTest
@TestConstructor(autowireMode = TestConstructor.AutowireMode.ALL)
@RequiredArgsConstructor
class SpringConfigurationTest {
    private final SimulationController simulationController;
    private final AssemblyLine assemblyLine;
    private final PCBFactory pcbFactory;
    private final StationProperties stationProperties;
    private final PCBProperties pcbProperties;
    void testSpringDependencyInjection() {
        // Verify that all Spring beans are properly injected
        assertNotNull(simulationController);
        assertNotNull(assemblyLine);
        assertNotNull(pcbFactory);
```

```
File - C:\Users\ck\Documents\dev\source\CSCA\csca-java\5448\pcb\w3-code.txt
```

```
@Test
      void testConfigurationProperties() {
              // Verify that configuration properties are loaded correctly
              assertEquals(0.002, stationProperties.getFailureRate(), 0.0001);
             // Test PCB defect rates from properties (using Lombok-generated getters) \,
             assert Equals (0.05, pcbProperties.getTestboard().getPlaceComponentsDefectRate(), 0.0001); \\ assert Equals (0.002, pcbProperties.getSensorboard().getPlaceComponentsDefectRate(), 0.0001); \\ assert Equals (0.002, pcbProperties.getSensorboard(), 0.0001); \\ assert Equals (0.002, pcbProperties.getSensorboard(), 0.0001); \\ assert Equals (0.002, pcbProperties.getSensorboard(), 0.0001); \\ assert Equals (0.002, pcbPro
             assertEquals(0.004, pcbProperties.getGatewayboard().getPlaceComponentsDefectRate(), 0.0001);
      }
      @Test
      void testPCBFactorvWithConfiguration() {
             // Test that PCB factory creates boards with configuration-driven defect rates
              var testBoard = pcbFactory.createPCB("Test Board");
              assertEquals("TestBoard", testBoard.getType());
             assert Equals (0.05,\ testBoard.getDefectRate ("PlaceComponents"),\ 0.0001);
             var sensorBoard = pcbFactory.createPCB("Sensor Board");
             assertEquals("SensorBoard", sensorBoard.getType());
             assertEquals(0.002, sensorBoard.getDefectRate("PlaceComponents"), 0.0001);
      }
}
_____
FILE: src\test\java\com\cu5448\pcb\factory\PCBFactoryTest.java
______
package com.cu5448.pcb.factory;
import static org.junit.jupiter.api.Assertions.*;
import org.junit.jupiter.api.BeforeEach;
import org.junit.jupiter.api.Test;
import com.cu5448.pcb.config.PCBProperties;
import com.cu5448.pcb.model.*;
class PCBFactoryTest {
      private PCBFactory factory;
      @BeforeEach
      void setUp() {
             factory = new PCBFactory(new PCBProperties());
      void testCreateTestBoard() {
             PCB pcb = factory.createPCB("testboard");
             assertInstanceOf(TestBoard.class, pcb);
             assertEquals("TestBoard", pcb.getType());
      }
      @Test
      void testCreateSensorBoard() {
             PCB pcb = factory.createPCB("sensorboard");
             assertInstanceOf(SensorBoard.class, pcb);
             assertEquals("SensorBoard", pcb.getType());
      }
      @Test
      void testCreateGatewayBoard() {
             PCB pcb = factory.createPCB("gatewayboard");
              assertInstanceOf(GatewayBoard.class, pcb);
             assertEquals("GatewayBoard", pcb.getType());
      }
       void testCreateWithAlternativeNames() {
             assertInstanceOf(TestBoard.class,\ factory.createPCB("test"));\\
             assertInstance Of (Sensor Board.class,\ factory.create PCB ("sensor"));\\
             assertInstanceOf(GatewayBoard.class, factory.createPCB("gateway"));
      @Test
      void testCreateWithInvalidType() {
             assertThrows(IllegalArgumentException.class, () -> factory.createPCB("invalid"));
}
______
FILE: src\test\java\com\cu5448\pcb\factory\StationFactoryTest.java
```

```
File - C:\Users\ck\Documents\dev\source\CSCA\csca-java\5448\pcb\w3-code.txt
 package com.cu5448.pcb.factory;
 import static org.junit.jupiter.api.Assertions.*;
 import org.junit.jupiter.api.Test;
 import\ org.springframework.boot.test.context.SpringBootTest;
 import org.springframework.test.context.TestConstructor;
 import com.cu5448.pcb.station.*;
 import lombok.RequiredArgsConstructor;
 /** Test class for StationFactory implementation */
 @SpringBootTest
 @TestConstructor(autowireMode = TestConstructor.AutowireMode.ALL)
 @RequiredArgsConstructor
 class StationFactoryTest {
     private final StationFactory stationFactory;
     void testFactoryInjection() {
         assertNotNull(stationFactory, "StationFactory should be injected");
     void testCreateIndividualStations() {
         // Test station creation using abstract factory method
         Station applySolderPaste = stationFactory.createStation("ApplySolderPaste");
         assertNotNull(applySolderPaste);
assertEquals("ApplySolderPaste", applySolderPaste.getName());
         Station placeComponents = stationFactory.createStation("PlaceComponents");
         assertNotNull(placeComponents);
         assertEquals("PlaceComponents", placeComponents.getName());
         Station reflowSolder = stationFactory.createStation("ReflowSolder");
         assertNotNull(reflowSolder);
         assertEquals("ReflowSolder", reflowSolder.getName());
         Station opticalInspection = stationFactory.createStation("OpticalInspection");
         assertNotNull(opticalInspection);
         assertEquals("OpticalInspection", opticalInspection.getName());
         Station handSoldering = stationFactory.createStation("HandSoldering");
         assertNotNull(handSoldering);
         assertEquals("HandSoldering", handSoldering.getName());
         Station cleaning = stationFactory.createStation("Cleaning");
         assertNotNull(cleaning);
         assertEquals("Cleaning", cleaning.getName());
         Station depanelization = stationFactory.createStation("Depanelization");
         assertNotNull(depanelization);
         assertEquals("Depanelization", depanelization.getName());
         Station test = stationFactory.createStation("Test");
         assertNotNull(test);
assertEquals("Test", test.getName());
     }
     void testCreateStationByType() {
         // Test station creation by type name using abstract factory
         Station applySolder = stationFactory.createStation("ApplySolderPaste");
         assertInstanceOf(ApplySolderPasteStation.class, applySolder);
         assertEquals("ApplySolderPaste", applySolder.getName());
         {\tt Station \ placeComponents = stationFactory.createStation("PlaceComponents");}
         assertInstanceOf(PlaceComponentsStation.class, placeComponents);
         assertEquals("PlaceComponents", placeComponents.getName());
         Station test = stationFactory.createStation("Test");
         assertInstanceOf(TestStation.class, test);
         assertEquals("Test", test.getName());
     void testCreateStationByTypeInvalid() {
         // Test invalid station type using abstract factory
         assertThrows(
                 IllegalArgumentException.class,
                 () -> stationFactory.createStation("InvalidStation"),
                 "Should throw exception for invalid station type");
         assertThrows(
                 IllegalArgumentException.class,
                 () -> stationFactory.createStation(""),
                 "Should throw exception for empty station type");
```

```
assertThrows(
               IllegalArgumentException.class,
               () -> stationFactory.createStation("SomeRandomName"),
               "Should throw exception for random station type");
   }
   @Test
   void testAllStationTypesSupported() {
       // Test all expected station types are supported by abstract factory
       String[] stationTypes = {
           "ApplySolderPaste",
           "PlaceComponents",
           "ReflowSolder"
           "OpticalInspection",
           "HandSoldering",
           "Cleaning",
           "Depanelization",
           "Test"
       for (String stationType : stationTypes) {
           assertDoesNotThrow(
                   () -> {
                      Station station = stationFactory.createStation(stationType);
                      assertNotNull(
                              station, "Station should be created for type: " + stationType);
                  },
"Should be able to create station for type: " + stationType);
       }
   }
}
_______
FILE: src\test\java\com\cu5448\pcb\model\DefectRatesTest.java
-----
package com.cu5448.pcb.model:
import static org.junit.jupiter.api.Assertions.*;
import org.junit.jupiter.api.Test;
/** Test class for DefectRates model */
class DefectRatesTest {
   void testBuilderPattern() {
       DefectRates rates =
              DefectRates.builder()
                      .placeComponentsDefectRate(0.01)
                       .opticalInspectionDefectRate(0.02)
                       .handSolderingDefectRate(0.03)
                       .testDefectRate(0.04)
                      .build();
       assertEquals(0.01, rates.getPlaceComponentsDefectRate());
       assertEquals(0.02, rates.getOpticalInspectionDefectRate());
       assertEquals(0.03, rates.getHandSolderingDefectRate());
       assertEquals(0.04, rates.getTestDefectRate());
   void testGetDefectRateWithValidStations() {
       DefectRates rates =
              DefectRates.builder()
                      .placeComponentsDefectRate(0.05)
                      .opticalInspectionDefectRate(0.10)
                       .handSolderingDefectRate(0.05)
                       .testDefectRate(0.10)
                      .build();
       assertEquals(0.05, rates.getDefectRate("PlaceComponents"));
       assertEquals(0.10, rates.getDefectRate("OpticalInspection"));
       assertEquals(0.05, rates.getDefectRate("HandSoldering"));
       assertEquals(0.10, rates.getDefectRate("Test"));
   }
   @Test
   void testGetDefectRateWithInvalidStation() {
       DefectRates rates
               DefectRates.builder()
                      .placeComponentsDefectRate(0.05)
                       .opticalInspectionDefectRate(0.10)
                      .handSolderingDefectRate(0.05)
                       .testDefectRate(0.10)
                       .build();
```

```
assertEquals(0.0, rates.getDefectRate("ApplySolderPaste"));
        assertEquals(0.0, rates.getDefectRate("ReflowSolder"));
        assertEquals(0.0, rates.getDefectRate("Cleaning"));
        assertEquals(0.0, rates.getDefectRate("Depanelization"));
        assert Equals (0.0, \ rates.getDefectRate("NonExistentStation"));\\
    }
    void testPCBIntegration() {
        // Test that PCB implementations can use {\tt DefectRates}
       DefectRates testRates =
                DefectRates.builder()
                        .placeComponentsDefectRate(0.05)
                         .opticalInspectionDefectRate(0.10)
                        .handSolderingDefectRate(0.05)
                         .testDefectRate(0.10)
       .build();
TestBoard testBoard = new TestBoard(testRates);
        DefectRates defectRates = testBoard.getDefectRates();
        assertNotNull(defectRates);
        assert Equals (0.05, \ testBoard.getDefectRate ("PlaceComponents"));\\
       assertEquals(0.05, defectRates.getDefectRate("PlaceComponents"));
        DefectRates sensorRates =
                DefectRates.builder()
                        .placeComponentsDefectRate(0.002)
                         .opticalInspectionDefectRate(0.002)
                         .handSolderingDefectRate(0.004)
                        .testDefectRate(0.004)
                         .build();
        SensorBoard sensorBoard = new SensorBoard(sensorRates);
        DefectRates actualSensorRates = sensorBoard.getDefectRates();
        assertNotNull(actualSensorRates):
        assertEquals(0.002, sensorBoard.getDefectRate("PlaceComponents"));
        assertEquals(0.002, actualSensorRates.getDefectRate("PlaceComponents"));
   }
}
FILE: src\test\java\com\cu5448\pcb\service\StatisticsCollectorTest.java
package com.cu5448.pcb.service;
import static org.junit.jupiter.api.Assertions.*;
import org.junit.jupiter.api.BeforeEach;
import org.junit.jupiter.api.Test;
class StatisticsCollectorTest {
    private StatisticsCollector stats;
    @BeforeEach
    void setUp() {
        stats = new StatisticsCollector();
    @Test
    void testInitialState() {
        assertEquals(0, stats.getPcbsSubmitted());
        assertEquals(0, stats.getCompletedPCBs());
        assertTrue(stats.getDefectFailures().isEmpty());
       assertTrue(stats.getStationFailures().isEmpty());
    @Test
    void testRecordSubmission() {
        stats.recordSubmission();
        stats.recordSubmission():
        assertEquals(2, stats.getPcbsSubmitted());
   }
    @Test
    void testRecordCompletion() {
       stats.recordCompletion();
        stats.recordCompletion();
        assertEquals(2, stats.getCompletedPCBs());
    @Test
    void testRecordDefectFailure() {
        stats.recordDefectFailure("PlaceComponents");
        stats.recordDefectFailure("PlaceComponents");
```

```
stats.recordDefectFailure("Test");
            assertEquals(2, stats.getDefectFailures().get("PlaceComponents"));
            assertEquals(1, stats.getDefectFailures().get("Test"));
      @Test
      void testRecordStationFailure() {
   stats.recordStationFailure("ApplySolderPaste");
            stats.recordStationFailure("Cleaning");
            assertEquals(1, stats.getStationFailures().get("ApplySolderPaste"));
assertEquals(1, stats.getStationFailures().get("Cleaning"));
      @Test
      void testGenerateReport() {
            stats.recordSubmission();
            stats.recordSubmission();
            stats.recordCompletion();
            stats.recordDefectFailure("Test");
            stats.recordStationFailure("Cleaning");
            String report = stats.generateReport("Test Board");
           assertTrue(report.contains("PCB type: Test Board"));
assertTrue(report.contains("PCBs run: 2"));
assertTrue(report.contains("Total failed PCBs: 1"));
assertTrue(report.contains("Total PCBs produced: 1"));
assertTrue(report.contains("Test (ICT or Flying Probe) 1"));
assertTrue(report.contains("Cleaning: 1"));
}
```

