LG Energy Solution ESS AZ., Tenant Improvement, Phase I

- Truck Court Concrete Repair

West 202 Logistics, 555 and 675 N. 55th Ave., Phoenix, AZ 85043

City Submittal - 02/19/2026

LG Energy Solution

HACE INC, 2102 Business Center Dr.,
Irvine, CA 92612
T.949.892.9732 E. hseo@haceinc.com

REGISTERED ARCHITECT
CERTIFICATE NO.
75220
HYUNG JIN
SEO
Date Signed 02/12/26
ARIZONA, U.S.A.
S. HyungJin
EXPIRES 03/31/28

LG Energy Solution ESS AZ.
Tenant Improvement West 202 Logistics
555 and 675 N. 55th Ave.,
Phoenix, AZ 85043
Bldg. F: 675 N. 55th Ave.
Bldg. G: 555 N. 55th Ave.

Revision	Description	Date
-	CITY SUBMITTAL/100% BID SET	02/12/26

Key Plan N.T.S.

Date	Drawn By
Project Numbers 202601.05	Checked By

Sheet Title: COVER

Sheet Number: A000

ABBREVIATIONS

&	AND	JAN.	JANITOR
L	ANGLE	JT.	JOINT
@	AT		
℄	CENTERLINE	KIT.	KITCHEN
ø	DIAMETER OR ROUND		
(E)	EXISTING	LAB.	LABORATORY
#	POUND OR NUMBER	LAM.	LAMINATE
		LAV.	LAVATORY
ACOUS.	ACOUSTICAL	LKR.	LOCKER
A.D.	AREA DRAIN	LT.	LIGHT
AESS.	ARCHITECTURAL AESTHETIC STEEL		
		MAX.	MAXIMUM
AGGR.	AGGREGATE	M.C.	MEDICINE CABINET
ALUM.	ALUMINUM	MECH.	MECHANICAL
APPROX.	APPROXIMATE	MEMB.	MEMBRANE
ARCH.	ARCHITECTURAL	MET.	METAL
ASPH.	ASPHALT	MFR.	MANUFACTURER
		MH.	MANHOLE
BD.	BOARD	MIN.	MINIMUM
BITUM.	BITUMINOUS	MIR.	MIRROR
BLDG.	BUILDING	MISC.	MISCELLANEOUS
BLK.	BLOCK	M.O.	MASONRY OPENING
BLKG.	BLOCKING	MTD.	MOUNTED
BM.	BEAM	MTL.	MATERIAL
BOT.	BOTTOM	MUL.	MULLION
CAB.	CABINET	N.I.C.	NOT IN CONTRACT
C.B.	CATCH BASIN	NO.	NUMBER
CEM.	CEMENT	NOM.	NOMINAL
CER.	CERAMIC	N.T.S.	NOT TO SCALE
C.G.	CORNER GUARD		
C.I.	CAST IRON	O.A.	OVERALL
CLG.	CEILING	OBS.	OBSCURE
CLKG.	CAULKING	O.C.	ON CENTER
CLO.	CLOSET	O.D.	OUTSIDE DIAMETER
CLR.	CLEAR	OFF.	OFFICE
CNTR.	CENTER	OPNG.	OPENING
C.O.	CASED OPENING	OPP.	OPPOSITE
COL.	COLUMN	O.L.F.	OCCUPANT LOAD FACTOR
CONC.	CONCRETE		
CONN.	CONNECTION	PRCST.	PRE-CAST
CONSTR.	CONSTRUCTION	PL.	PLATE
CONT.	CONTINUOUS	P. LAM.	PLASTIC LAMINATE
CORR.	CORRIDOR	PLAS.	PLASTER
CTSK.	COUNTERSUNK	PLYWD.	PLYWOOD
CTR.	COUNTER	PR.	PAIR
		PT.	POINT
DBL.	DOUBLE	P.T.D.	PAPER TOWEL DISPENSER COMBINATION
DEPT.	DEPARTMENT	P.T.D./R	PAPER TOWEL DISPENSER & RECEPTACLE
DET.	DETAIL		
D.F.	DRINKING FOUNTAIN	PTN.	PARTITION
DIA.	DIAMETER	P.T.R.	PAPER TOWEL RECEPTACLE
DIM.	DIMENSION		
DISP.	DISPENSER	Q.T.	QUARRY TILE
DN.	DOWN		
D.O.	DOOR OPENING	R.	RISER
DR.	DOOR	RAD.	RADIUS
D.S.	DOWNSPOUT	R.D.	ROOF DRAIN
D.S.P.	DRY STANDPIPE	REF.	REFERENCE
DWG.	DRAWING	REFR.	REFRIDGERATOR
DWR.	DRAWER	RGTR.	REGISTER
		REINF.	REINFORCED
EA.	EACH	REQ.	REQUIRED
E.D.F.	ELECTRICAL DRINKING FOUNTAIN	RESIL.	RESILIENT
E.J.	EXPANSION JOINT	RM.	ROOM
EL.	ELEVATION	R.O.	ROUGH OPENING
ELEC.	ELECTRICAL	RWD.	REDWOOD
ELEV.	ELEVATOR	R.W.L.	RAIN WATER LEADER
EMER.	EMERGENCY		
ENCL.	ENCLOSURE	S.C.	SOLID CORE
E.P.	ELECTRICAL PANELBOARD	S.C.D.	SEAT COVER DISPENSER
EQ.	EQUAL	SCHED.	SCHEDULE
EQPT.	EQUIPMENT	S.D.	SOAP DISPENSER
E.W.C.	ELECTRICAL WATER COOLER	SECT.	SECTION
EXST.	EXISTING	SH.	SHELL
EXP.	EXPANSION	SHR.	SHOWER
EXPO.	EXPOSED	SHT.	SHEET
EXT.	EXTERIOR	SIM.	SIMILAR
		S.N.D.	SANITARY NAPKIN DISPENSER
F.A.	FIRE ALARM	S.N.R.	SANITARY NAPKIN RECEPTACLE
F.B.	FLAT BAR	SPEC.	SPECIFICATION
F.D.	FLOOR DRAIN	SQ.	SQUARE
FDN.	FOUNDATION	S.ST.	STAINLESS STEEL
F.E.	FIRE EXTINGUISHER	S.SK.	SERVICE SINK
F.E.C.	FIRE EXTINGUISHER CABINET	STA.	STATION
F.F.	FINISH FLOOR	STD.	STANDARD
F.H.C.	FIRE HOSE CABINET	STL.	STEEL
FIN.	FINISH	STOR.	STORAGE
FL.	FLOOR	STRL.	STRUCTURAL
FLASH.	FLASHING	SUSP.	SUSPENDED
FLUOR.	FLUORESCENT	SYM.	SYMMETRICAL
F.O.C.	FACE OF CONCRETE		
F.O.F.	FACE OF FINISH	TRD.	TREAD
F.O.M.	FACE OF MASONRY	T.B.	TOWEL BAR
F.O.S.	FACE OF STUD	T.C.	TOP OF CURB
FPRF.	FIREPROOF	TEL.	TELEPHONE
F.R.	FIRE-RATED	TER.	TERRAZZO
F.S.	FULL SIZE	T.&G.	TONGUE AND GROOVE
FT.	FOOT OR FEET	THK.	THICK
FTG.	FOOTING	T.O.C.	TOP OF CANOPY
FURR.	FURRING	T.O.M.S.	TOP OF MECHANICAL SCREEN
FUT.	FUTURE	T.O.P.	TOP OF PARAPET
		T.O.S.	TOP OF SURFACE
GA.	GAUGE	T.O.W.	TOP OF WALL
GALV.	GALVINIZED	T.P.	TOP OF PAVEMENT
G.B.	GRAB BAR	T.P.D.	TOILET PAPER DISPENSER
G.I.S.M.	GALVANIZED IRON SHEET METAL	T.V.	TELEVISION
GL.	GLASS	TYP.	TYPICAL
GND.	GROUND		
GR.	GRADE	U.O.N.	UNLESS OTHERWISE NOTED
GYP.	GYPSUM		
		VERT.	VERTICAL
H.B.	HOSE BIB	VEST.	VESTIBULE
H.C.	HOLLOW CORE		
HDWD.	HARDWOOD	W/	WITH
HDWE.	HARDWARE	W.C.	WATER CLOSET
H.M.	HOLLOW METAL	WD.	WOOD
HORIZ.	HORIZONTAL	W/O	WITHOUT
HR.	HOUR	W.P.	WATERPROOF
HGT.	HEIGHT	WT.	WEIGHT
I.D.	INSIDE DIAMETER		
IN.	INCH OR INCHES		
INSUL.	INSULATION		
INT.	INTERIOR		

SYMBOLS

1
A
COLUMN LINE

03
A3.1
SECTION
SECTION IDENTIFICATION
SHEET WHERE SECTION IS DRAWN

03
A3.1
ELEVATION
ELEVATION IDENTIFICATION
SHEET WHERE ELEVATION IS DRAWN

04
A8.1
DETAIL
DETAIL IDENTIFICATION
SHEET WHERE DETAIL IS DRAWN

A B C D
04
A5.1
INTERIOR ELEVATIONS
ELEVATION IDENTIFICATION
SHEET WHERE ELEVATION IS DRAWN

KITCHEN
105
ROOM NUMBER
ROOM NAME
ROOM NUMBER

1
REVISION
CLOUD AROUND REVISED AREA
REVISION NUMBER

DATUM POINT

1
KEYNOTE

ALIGN

SHADED AREA DENOTES MILLWORK

GENERAL CONSTRUCTION NOTES

1. ALL CONSTRUCTION AND MATERIALS SHALL BE AS SPECIFIED AND IN ACCORDANCE WITH ALL APPLICABLE CODES, ORDINANCES, LAWS, PERMITS, AND THE CONTRACT DOCUMENTS.
2. THE CONTRACTOR SHALL BE RESPONSIBLE FOR THE ACCURATE PLACEMENT OF ALL NEW CONSTRUCTION ON THE SITE.
3. THE CONTRACTOR IS RESPONSIBLE FOR ALL EXISTING SURVEY MONUMENTS WHICH MAY BE DISTURBED THROUGH CONSTRUCTION ACTIVITIES DEEMED NECESSARY FOR PRESERVATION BY THE CIVIL ENGINEER. IF SUCH MONUMENTS WERE DISTURBED, THE APPLICANT SHALL HAVE A LICENSED LAND SURVEYOR QUALIFIED REGISTERED CIVIL ENGINEER REESTABLISH ANY SUCH MONUMENTATION DAMAGED OR DESTROYED DURING THE CONSTRUCTION OF THE PROJECT AND SUBMIT "PRELIMINARY CORNER RECORDS" TO THE CIVIL ENGINEER AFTER REPLACEMENT. AFTER APPROVAL BY THE CIVIL ENGINEER, THE APPLICANT SHALL FILE THE CORNER RECORDS WITH THE COUNTY SURVEYOR. PRIOR TO THE EXONERATION OF ANY SECURITY, EVIDENCE OF SUCH FILING SHALL BE FURNISHED TO THE CIVIL ENGINEER.
4. THE CONTRACTOR IS RESPONSIBLE TO ENSURE THAT TRUCK ROUTES SHALL BE STEERED AWAY FROM RESIDENTIAL AREAS. SEE IFC CHAPTER 4.
5. THE CONTRACTOR SHALL ENSURE THAT TRUCKS HAULING DIRT ON PUBLIC ROADS TO AND FROM THE SITE SHALL BE COVERED OR WILL MAINTAIN A 6" DIFFERENTIAL BETWEEN THE MAXIMUM HEIGHT OF ANY HAULED MATERIAL AND THE TOP OF THE HAUL TRAILER. HAUL TRUCK DRIVERS SHALL WATER THE LOAD PRIOR TO LEAVING THE SITE TO PREVENT SOIL LOSS DURING TRANSPORT.
6. THE CONTRACTOR SHALL ENSURE THAT GRADED SURFACES USED FOR OFF ROAD PARKING, MATERIALS LAY-DOWN, OR AWAITING FUTURE CONSTRUCTION SHALL BE STABILIZED FOR DUST CONTROL AS NEEDED. FREQUENTLY ACCESSED UNPAVED AREAS SHALL BE PAVED AS EARLY AS POSSIBLE TO MINIMIZE DIRT TRACKOUT TO PUBLIC RIGHTS-OF-WAY.
7. THE CONTRACTOR SHALL COORDINATE ANY LANE CLOSURES OR DETOURS WITH THE CITY. FLAG PERSONS AND APPROPRIATE TRAFFIC CONTROL DEVICES SHALL BE USED AS NEEDED TO MINIMIZE CONSTRUCTION ACTIVITY INTERFERENCE WITH OFF-SITE TRAFFIC.
8. THE CONTRACTOR SHALL VERIFY ALL DIMENSIONS AND SITE CONDITIONS BEFORE STARTING WORK. SHOULD A DISCREPANCY APPEAR IN THE CONTRACT DOCUMENTS, OR BETWEEN THE CONTRACT DOCUMENTS AND EXISTING CONDITIONS, NOTIFY THE ARCHITECT AT ONCE FOR INSTRUCTION ON HOW TO PROCEED.
9. SHOULD A CONFLICT OCCUR BETWEEN DRAWINGS AND SPECIFICATIONS, THE MORE RESTRICTIVE CONDITION SHALL TAKE PRECEDENCE, UNLESS A WRITTEN DECISION THE ARCHITECT HAS BEEN OBTAINED WHICH DESCRIBES A CLARIFICATION OR ALTERNATE METHOD AND/OR MATERIALS.
10. THE CONTRACTOR SHALL CONFINE HIS OPERATIONS ON THE SITE TO AREAS PERMITTED BY OWNER.
11. THE JOB SITE SHALL BE MAINTAINED IN A CLEAN, ORDERLY CONDITION FREE OF DEBRIS AND LITTER AND SHALL NOT BE UNREASONABLY ENCUMBERED WITH ANY MATERIALS OR EQUIPMENT. EACH SUBCONTRACTOR IMMEDIATELY UPON COMPLETION OF EACH PHASE OF HIS WORK SHALL REMOVE ALL TRASH AND DEBRIS AS A RESULT OF HIS OPERATION.
12. ALL MATERIAL STORED ON THE SITE SHALL BE PROPERLY STACKED AND PROTECTED TO PREVENT DAMAGE AND DETERIORATION. FAILURE TO PROTECT MATERIALS MAY CAUSE FOR REJECTION OF WORK.
13. THE CONTRACTOR SHALL DO ALL CUTTING, FITTING, OR PATCHING OF HIS WORK THAT MAY BE REQUIRED TO MAKE ITS SEVERAL PARTS FIT TOGETHER PROPERLY AND SHALL NOT ENDANGER ANY OTHER WORK BY CUTTING, EXCAVATING, OR OTHERWISE ALTERING THE TOTAL WORK OR ANY PART OF IT. ALL PATCHING, REPAIRING, AND REPLACING OF MATERIALS AND SURFACES, CUT OR DAMAGED IN EXECUTION OF WORK, SHALL BE DONE WITH APPLICABLE MATERIALS SO THAT SURFACES REPLACED WILL, UPON COMPLETION, MATCH SURROUNDING SIMILAR SURFACES. SEE IFC CHAPTER 26.
14. STRUCTURAL OBSERVATION BY THE ENGINEER/ARCHITECT SHALL BE PERFORMED. A STATEMENT IN WRITING SHALL BE GIVEN TO THE BUILDING OFFICIAL, STATING THAT THE SITE VISITS HAVE BEEN MADE AND WHETHER OR NOT ANY OBSERVED DEFICIENCIES HAVE BEEN CORRECTED TO CONFORM TO THE APPROVED PLANS AND SPECIFICATIONS.
15. PROVIDE FIRE EXTINGUISHERS PER THE REQUIREMENTS OF LOCAL GOVERNING AGENCIES.
16. PROVIDE ALL ACCESS PANELS AS REQUIRED BY GOVERNING CODES TO ALL CONCEALED SPACES, VOIDS, ATTICS, ETC. VERIFY TYPE REQUIRED WITH ARCHITECT PRIOR TO INSTALLATION.
17. NO PORTION OF WORK REQUIRING A SHOP DRAWING OR SAMPLE SUBMISSION SHALL BE COMMENCED UNTIL THE SUBMISSION HAS BEEN REVIEWED BY THE ARCHITECT. ALL SUCH PORTIONS OF THE WORK SHALL BE IN ACCORDANCE WITH CORRECTED SHOP DRAWINGS AND SAMPLES.
18. DIMENSIONS:
    A. ALL DIMENSIONS SHALL TAKE PRECEDENCE OVER SCALE.
    B. ALL DIMENSIONS ARE TO THE FINISH UNLESS OTHERWISE NOTED.
    C. CEILING HEIGHT DIMENSIONS ARE FROM FINISHED FLOOR SLAB TO FACE OF FINISH CEILING MATERIAL UNLESS OTHERWISE NOTED.
19. DO NOT SCALE DRAWINGS.
20. PROVIDE ALL NECESSARY BLOCKING, BACKING, AND FRAMING FOR LIGHT FIXTURES, ELECTRIC UNITS, A.C. EQUIPMENT, RECESSED ITEMS, AND ALL OTHER ITEMS AS REQUIRED.
21. WHERE LARGER STUDS OR FURRING ARE REQUIRED TO COVER PIPING AND CONDUITS, THE LARGER STUD SIZE OR FURRING SHALL EXTEND THE FULL SURFACE OF THE WALL WIDTH AND LENGTH WHERE THE FURRING OCCURS.
22. ALL LEGAL EXIT DOORS SHALL BE OPERABLE FROM THE INSIDE WITHOUT THE USE OF A KEY OR SPECIAL KNOWLEDGE OR EFFORT. EXIT SIGNS SHALL BE PROVIDED AT ALL EXITS AS REQUIRED BY THE IBC SECTION 1011. ALL DOOR SWINGS SERVING AN OCCUPANT LOAD OF 50 OR GREATER SHALL SWING IN THE DIRECTION OF TRAVEL.
23. ALL GLASS AND GLAZING SHALL COMPLY WITH IBC CHAPTER 24.
24. THE LIVE LOADS FOR WHICH EACH FLOOR OR PORTION THEREOF OF A COMMERCIAL OR INDUSTRIAL BUILDING IS OR HAS BEEN DESIGNED SHALL HAVE SUCH DESIGN LIVE LOADS CONSPICUOUSLY POSTED BY THE OWNER IN THAT PART OF EACH STORY IN WHICH THEY APPLY, USING DURABLE METAL SIGNS, AND IT SHALL BE UNLAWFUL TO REMOVE OR DEFACE SUCH NOTICES. THE OCCUPANT OF THE BUILDING SHALL BE RESPONSIBLE FOR KEEPING THE ACTUAL LOAD BELOW THE ALLOWABLE LIMITS. IBC SECTION 1607.3.5.
25. IN CASE OF ANY DISCREPANCIES CONTACT THE A.O.R. THE MORE STRINGENT CRITERIA SHALL ALWAYS GOVERN.
26. A PREDEMOLITION MEETING WITH THE INSPECTION DEPARTMENT IS REQUIRED PRIOR TO THE START OF DEMOLITION. CALL (602) 262-7501 TO SCHEDULE AN INSPECTION.
27. SPRINKLER AND/OR ALARM SYSTEM PLANS MUST BE REVIEWED AND APPROVED BY THE PHOENIX FIRE AUTHORITY PRIOR TO ANY SPRINKLER ALARM SYSTEM MODIFICATION OR ALTERATION.

APPLICABLE CODES AND STANDARDS

INTERNATIONAL BUILDING CODE, 2024 EDITION WITH PHOENIX AMENDMENT
INTERNATIONAL MECHANICAL CODE, 2024 EDITION WITH PHOENIX AMENDMENT
NATIONAL ELECTRICAL CODE, 2024 EDITION WITH PHOENIX AMENDMENT
UNIFORM PLUMBING CODE, 2024 EDITION WITH PHOENIX AMENDMENT
INTERNATIONAL ENERGY CONSERVATION CODE, 2024 EDITION
INTERNATIONAL FIRE CODE, 2018 EDITION WITH PHOENIX AMENDMENT

PLANNING NOTES

- LEGAL JURISDICTION: CITY OF PHOENIX
- ZONING CATEGORY: A-1 AND A-2 (LIGHT AND HEAVY INDUSTRIAL)
- VILLAGE: ESTRELLA

CODE ANALYSIS

CONSTRUCTION TYPE:	III-B 400'-0" TRAVEL DISTANCE
AUTOMATIC FIRE SPRINKLERS:	YES
OCCUPANCY TYPE:	B, S-1, AND F-1 GROUP NON SEPARATED MIXED USE
GROSS BUILDING AREA:	BLDG. F: 301,711 SF, UNLIMITED AREA BLDG. G: 295,586 SF, UNLIMITED AREA
NUMBER OF STORIES:	1

FIRE RESISTANCE RATED ASSEMBLIES CONSTRUCTED OR ALTERED IN SCOPE OF WORK:

STRUCTURAL FRAME:	0
EXTERIOR WALLS (BEARING):	2
INTERIOR WALLS (BEARING):	0
EXTERIOR WALLS (NONBEARING):	0
INTERIOR WALLS (NONBEARING):	0
FLOOR CONSTRUCTION:	0
ROOF CONSTRUCTION:	0

PARKING: NO CHANGE
BLDG. F.: 208 SPACES (7 ACCESSIBLE STALLS)
BLDG. G.: 197 SPACES (6 ACCESSIBLE STALLS)

SHEET INDEX

DATE ISSUED | DWGS IN THIS ISSUE

ARCHITECTURAL

CVR	COVER SHEET
A001	GENERAL INFORMATION & SHEET INDEX
A002	SPECIFICATIONS
A101	SITE PLAN

STRUCTURAL

S001	STRUCTURAL GENERAL NOTES
S501	TYPICAL CONCRETE DETAILS
S1.10	CONCRETE SLAB PLAN

PROJECT DIRECTORY

OWNER
CRP LDF 55TH AVENUE LLC (C/O CAPROCK PARTNERS)
1300 DOVE STREET SUITE 200 NEWPORT BEACH, CA 92660
CONTACT: RICK GOEBEL PH: 702-501-4906
E-MAIL: RGOEBEL@CAPROCK-PARTNERS.COM

TENANT
LG ENERGY SOLUTION,
675 N. 55TH AVE., PHOENIX, AZ 85043
CONTACT: JUNG HO LEE PH: 011-82-10-7187-6127
E-MAIL: LEEJH6127@LGENSOL.COM

GENERAL CONTRACTOR
SUN STATE BUILDERS,
1050 W WASHINGTON ST #214, TEMPE, AZ 85288
CONTACT: MIKE FORST PH: 480-894-1286
E-MAIL: MFORST@SUNSTATEBUILDERS.COM

ARCHITECT
HACE INC
2102 BUSINESS CENTER DR., IRVINE, CA 92612
CONTACT: HYUNG JIN SEO PH: 949-892-9732
E-MAIL: HSEO@HACEINC.COM

STRUCTURAL
BURKE STRUCTURAL ENGINEERS
151 KALMUS DR, STE E140, COSTA MESA, CA 92626
CONTACT: MOHAMED BADAWI PH: 657-289-0460
E-MAIL: MOHAMED@BURKESE.COM

ELECTRICAL, MECHANICAL, AND PLUMBING ENGINEER
3S MEP+S
27475 FERRY ROAD WARRENVILLE, IL 60555
CONTACT: SUSHIL KUMAR P.E. PH: 312-446-3327
E-MAIL: SUSHIL@3SMEP.COM

SCOPE OF WORK

INTERIOR TENANT IMPROVEMENT FOR LGES PHASE I. THE SCOPE OF WORK INCLUDES THE REMOVAL OF THE EXISTING TRUCK COURT CONCRETE AND THE INSTALLATION OF NEW HEAVY-DUTY CONCRETE, ALONG WITH ASSOCIATED ELECTRICAL AND PLUMBING LINES TO SUPPORT FUTURE WATER TESTING EQUIPMENT AND DATA CENTER OPERATIONS.

VICINITY MAP



PROPOSED SITE - ADDRESS:
555 and 675 N. 55th Ave.,
Phoenix, AZ 85043

DEFFERED SUBMITTALS

THIS PROJECT HAS BEEN PERMITTED WITHOUT REVIEW AND/OR APPROVAL OF THE FOLLOWING DEFERRED SUBMITTALS. PLANS APPROVED BY THE TOWNSHIP SHALL BE OBTAINED FOR EACH DEFERRED ITEM LISTED BELOW PRIOR TO COMMENCING ANY WORK WITHIN THE SCOPE OF SUCH DEFERRAL. DEFERRALS MUST BE REVIEWED AND ACCEPTED BY THE ARCHITECT OR ENGINEER OF RECORD PRIOR TO SUBMITTING FOR REVIEW WITH THE CITY.

FIRE PROTECTION
FIRE ALARM

LG Energy Solution

HACE INC. 2102 Business Center Dr., Irvine, CA 92612
T.949.892.9732 E. hseo@haceinc.com

REGISTERED ARCHITECT
CERTIFICATE NO. 75220
HYUNG JIN SEO
ARIZONA U.S.A.
S. HyungJin
EXPIRES 03/31/28

LG Energy Solution ESS AZ.
Tenant Improvement West 202 Logistics
555 and 675 N. 55th Ave.,
Phoenix, AZ 85043
Bldg. F: 675 N. 55th Ave.
Bldg. G: 555 N. 55th Ave.

Revision	Description	Date

Revision	Description	Date
	CITY SUBMITTAL	02/12/26

Key Plan N.T.S.

Date	Drawn By
Project Numbers 202601.05	Checked By

Sheet Title
GENERAL NOTES, INDEX, & CODE ANALYSIS

Sheet Number
A001

1.0 GENERAL CONDITIONS

1.1 THE DRAWINGS SHOW GENERAL INFORMATION ONLY. THE GENERAL CONTRACTOR IS RESPONSIBLE FOR CHECKING CONTRACT DOCUMENTS, FIELD CONDITIONS AND DIMENSIONS FOR ACCURACY AND CONFIRMING WORK IS 'BUILDABLE' AS SHOWN BEFORE PROCEEDING WITH CONSTRUCTION. IF THERE ARE ANY QUESTIONS OR DISCREPANCIES REGARDING THESE OR OTHER COORDINATION QUESTIONS, THE GENERAL CONTRACTOR IS RESPONSIBLE FOR OBTAINING A CLARIFICATION FROM THE ARCHITECT BEFORE PROCEEDING WITH WORK OR RELATED WORK IN QUESTION.

1.2 GENERAL CONTRACTOR SHALL INFORM THE ARCHITECT OF ANY CONFLICTS PRIOR TO CONSTRUCTION THAT EXIST IN LOCATIONS OF ANY AND ALL MECHANICAL, TELEPHONE, ELECTRICAL, LIGHTING, PLUMBING AND SPRINKLER EQUIPMENT (TO INCLUDE ALL PIPING, DUCT WORK AND CONDUIT) THAT ALL REQUIRED CLEARANCE FOR INSTALLATION AND MAINTENANCE OF ABOVE EQUIPMENT ARE PROVIDED.

1.3 THE PRESENCE OF THE ARCHITECT ON THE JOB SITE DOES NOT IMPLY THE CONCURRENCE OR APPROVAL OF WORK. THE GENERAL CONTRACTOR WILL CALL SPECIFIC ITEMS TO THE ATTENTION OF THE DESIGNER'S PROJECT MANAGER IF HE/SHE WISHES TO OBTAIN APPROVAL.

1.4 THE GENERAL CONTRACTOR AND SUB-CONTRACTORS SHALL PURCHASE AND MAINTAIN CERTIFICATIONS OF INSURANCE WITH RESPECT TO WORKMAN'S COMPENSATION, PUBLIC LIABILITY AND PROPERTY DAMAGE FOR THE LIMITS AS REQUIRED BY LAW. THE GENERAL CONTRACTOR SHALL BE RESPONSIBLE FOR INITIATING, MAINTAINING, AND SUPERVISING ALL SAFETY PRECAUTIONS IN CONNECTION WITH THE WORK.

1.5 PRIOR TO BEGINNING ANY WORK, THE GENERAL CONTRACTOR SHALL FURNISH A CONSTRUCTION SCHEDULE SHOWING THE CHRONOLOGICAL PHASES OF HIS WORK, AND ALL RELATED WORK FOR THAT OF THE PROJECT. THIS SCHEDULE SHALL INDICATE ALL ORDERING LEAD TIMES, LENGTH OF TIME FOR EACH PHASE (AS APPLICABLE), ITS START AND COMPLETION, WITH A PROJECTED COMPLETION DATE.

1.6 ALL WORK PERFORMED BY THE CONTRACTOR/SUBCONTRACTORS SHALL CONFORM TO THE REQUIREMENTS OF MUNICIPAL, LOCAL, FEDERAL AND STATE LAWS, AS WELL AS OTHER GOVERNING REQUIREMENTS, WHETHER OR NOT SPECIFIED ON THE DRAWINGS.

1.7 WHERE THE CONTRACT, NOTES, OR DRAWINGS CALL FOR ANY WORK OF A MORE STRINGENT NATURE THAN THAT REQUIRED BY THE BUILDING CODE OR ANY OTHER DEPARTMENT HAVING JURISDICTION OVER THE WORK, THE WORK OF THE MORE STRINGENT NATURE CALLED FOR BY THE CONTRACT, CONSTRUCTION NOTES OR DRAWINGS SHALL BE FURNISHED IN ALL CASES.

1.8 THE CONTRACTOR SHALL BE FULLY AND SOLELY RESPONSIBLE FOR THE REMOVAL, REPLACEMENT AND RECTIFICATION OF ALL DAMAGED AND DEFECTIVE MATERIAL AND WORKMANSHIP IN CONNECTION WITH THE CONTRACT WORK. HE SHALL REPLACE OR REPAIR AS DIRECTED ALL SUCH DAMAGED OR DEFECTIVE MATERIALS WITHIN A PERIOD OF FIVE (5) BUSINESS DAYS FROM THE DATE OF SUBSTANTIAL COMPLETION, UNLESS OTHERWISE AGREED UPON IN WRITING BY OWNER.

1.9 THE CONTRACTOR/SUBCONTRACTORS SHALL OBTAIN AND PAY FOR ALL LEGALLY REQUIRED APPROVALS AND PERMITS NECESSARY FOR THE EXECUTION AND COMPLETION OF HIS WORK.

1.10 ALL DRAWINGS AND ALL CONSTRUCTION NOTES ARE COMPLEMENTARY, AND WHAT IS CALLED FOR BY EITHER, WILL BE BINDING AS IF CALLED FOR BY ALL. ANY WORK SHOWN OR REFERRED TO ON ANY ONE SET OF DRAWINGS SHALL BE PROVIDED AS THOUGH SHOWN ON ALL RELATED DRAWINGS.

1.11 THE GENERAL CONTRACTOR IS WHOLLY RESPONSIBLE FOR THE COORDINATION AND SCHEDULING OF THE WORK EFFORT FOR ALL SUBCONTRACTORS, CRAFTSMEN AND TRADESMEN REQUIRED TO COMPLETE THE JOB.

1.12 THE GENERAL CONTRACTOR SHALL NOTIFY ARCHITECT IMMEDIATELY IF HE CANNOT COMPLY WITH ALL WORK CALLED FOR ON THESE DRAWINGS.

1.13 THE GENERAL CONTRACTOR SHALL NOTIFY ARCHITECT IMMEDIATELY OF DISCREPANCIES OR OMISSIONS BETWEEN THE DRAWINGS, THESE NOTES, AND FIELD CONDITIONS BEFORE COMMENCING ANY WORK AND REQUEST FOR CLARIFICATION.

1.14 BEFORE SUBMITTING A FINAL PRICING, ALL CONTRACTORS SHALL VISIT THE PREMISES, FAMILIARIZE THEMSELVES WITH EXISTING CONDITIONS AND SATISFY THEMSELVES AS TO THE NATURE AND SCOPE OF THE WORK AND THE DIFFICULTIES THAT ATTEND ITS EXECUTION.

1.15 THE SUBMISSION OF A PROPOSAL SHALL BE CONSTRUED AS EVIDENCE THAT SUCH AN EXAMINATION HAS BEEN MADE. LATER CLAIMS FOR LABOR, EQUIPMENT, OR MATERIAL REQUIRED FOR DIFFICULTIES ENCOUNTERED, WHICH COULD HAVE BEEN FORESEEN HAD SUCH AN EXAMINATION BEEN MADE, WILL NOT BE RECOGNIZED.

1.16 EACH CONTRACTOR AND SUBCONTRACTOR SHALL CHECK AND VERIFY ALL DIMENSIONS AND CONDITIONS AT JOB SITE AS IT RELATES TO THEIR WORK AND NOTIFY THE ARCHITECT/OWNER IF THERE ARE OBSTRUCTIONS, AND WORK CANNOT BE ACCOMPLISHED AS REFLECTED IN THE CONTRACT DOCUMENTS. CONTRACTOR / SUBCONTRACTORS SHALL OBTAIN CLARIFICATION / DIRECTIVE FROM THE ARCHITECT / OWNER PRIOR TO THE START OF ANY WORK.

1.17 THE GENERAL CONTRACTOR AND THE SUBCONTRACTORS INVOLVED IN THIS PROJECT SHALL TAKE NOTE THAT ANY COST CAUSED BY DEFECTIVE OR ILL-TIMED WORK, AS A RESULT OF, BUT NOT LIMITED TO IMPROPER WORKMANSHIP OR MATERIALS, IMPROPER SCHEDULING OR DELINQUENT ORDERING SHALL BE BORNE BY THE PARTY RESPONSIBLE.

1.18 WITH SUBMISSION OF FINAL PRICING, THE GENERAL CONTRACTOR SHALL ALSO SUBMIT A LIST OF LONG LEAD TIME ITEMS THAT PREVENT COMPLETION OF THE PROJECT BY PROJECTED MOVE-IN DATE. WHERE SPECIAL ITEMS REQUIRE EXTENDED LEAD TIME PREVENTING INSTALLATION BY PROJECTED MOVE-IN DATE, CONTRACTOR IS TO PROPOSE AN AVAILABLE ALTERNATE FOR APPROVAL BY OWNER AND TENANT, AS WELL AS, TO PREPARE PRICING FOR POSSIBLE TEMPORARY ASSEMBLIES.

1.19 THE USE OF THE WORDS "PROVIDE" OR "PROVIDED" IN CONNECTION WITH ANY ITEM SPECIFIED, IS INTENDED TO MEAN, UNLESS OTHERWISE NOTED, THAT WHICH SHALL BE FURNISHED AND INSTALLED AND CONNECTED WHERE SO REQUIRED.

1.20 WHERE THE TERMS "APPROVED EQUAL", "EQUAL TO", "ACCEPTABLE" OR THE OTHER GENERAL QUALIFYING TERMS ARE USED IN THESE NOTES, IT SHALL BE UNDERSTOOD THAT REFERENCE IS MADE TO THE RULING AND JUDGMENT OF ARCHITECT.

1.21 THE GENERAL CONTRACTOR SHALL HAVE FIVE (5) WORKING DAYS FROM AWARD OF THE CONTRACT TO SUBMIT ANY "OR EQUAL" SUBSTITUTIONS FOR SPECIFIED PRODUCTS OR WORK FOR REVIEW BY ARCHITECT. IT SHALL INCLUDE CUT SHEETS WITH SPECIFICATIONS AND REASONS FOR SUBSTITUTION. ARCHITECT SHALL RESPOND IN FIVE (5) WORKING DAYS TO SUBMITTAL. NO SUBSTITUTIONS SHALL BE ACCEPTED AFTER THE INITIAL TEN (10) DAY TIME LIMIT HAS PASSED.

1.22 ALL WOODWORK, BLOCKING, ETC., TO BE FIRE RETARDANT TREATED, AS REQUIRED BY CODE.

1.23 THE GENERAL CONTRACTOR SHALL EXERCISE STRICT DUST CONTAINMENT CONTROL OVER JOB TO PREVENT DIRT OR DUST FROM LEAVING THE JOBSITE.

1.24 THE GENERAL CONTRACTOR SHALL INCLUDE IN HIS ESTIMATE ALL COSTS (INCLUDING OVERTIME WORK) FOR REMOVAL, NEW INSTALLATION AND REINSTALLATION WORK FOR ALL REQUIRED WORK WITHIN THE CEILING PLENUM.

1.25 ALL EXISTING FIXTURES NOT BEING REMOVED SHALL BE REFURBISHED WHERE REQUIRED, ALL LOOSE ITEMS TIGHTENED (LIGHT FIXTURES, EXIT SIGNS, ETC.) AND ALL MISSING PARTS REPLACED BY THE GENERAL CONTRACTOR TO ACHIEVE A FINISHED INSTALLATION AND APPEARANCE.

1.26 THE CONSTRUCTION NOTES AND/OR DRAWINGS ARE SUPPLIED TO ILLUSTRATE THE DESIGN INTENT AND THE GENERAL TYPE OF CONSTRUCTION DESIRED, AND ARE INTENDED TO APPLY TO THE FINEST QUALITY OF CONSTRUCTION, MATERIAL AND WORKMANSHIP THROUGHOUT.

1.27 THE GENERAL CONTRACTOR SHALL MAINTAIN A COMPLETE, CURRENT AND APPROVED SET OF CONSTRUCTION DRAWINGS AND BUILDING PERMIT ON SITE DURING ALL PHASES OF CONSTRUCTION FOR USE OF ALL TRADES.

1.28 THE GENERAL CONTRACTOR SHALL SEE THAT ALL SUBCONTRACTORS RECEIVE COMPLETE AND UPDATED SETS OF WORKING DRAWINGS AND ASSUME FULL RESPONSIBILITY FOR COORDINATION OF WORK.

1.29 THE GENERAL CONTRACTOR UPON AWARD OF THE CONTRACT FOR CONSTRUCTION, ASSUMES FULL RESPONSIBILITY FOR THE CONSTRUCTION, MATERIALS, AND WORKMANSHIP OF THE WORK DESCRIBED IN THESE NOTES AND DRAWINGS.

1.30 ALL REQUIRED EXITS, WAYS OF APPROACH THERETO, AND WAYS OF TRAVEL FROM THE EXIT INTO THE STREET SHALL CONTINUOUSLY BE MAINTAINED FREE FROM ALL OBSTRUCTIONS AND IMPEDIMENTS FOR UNOBSTRUCTED EGRESS IN THE CASE OF FIRE OR OTHER EMERGENCY.

1.31 DURING THE ENTIRE PERIOD OF DEMOLITION AND CONSTRUCTION, ALL EXISTING EXITS, EXIT LIGHTING, FIRE PROTECTIVE DEVICES AND ALARMS SHALL BE CONTINUOUSLY MAINTAINED.

1.32 THE GENERAL CONTRACTOR SHALL PROVIDE AND INSTALL FIRE EXTINGUISHERS AS REQUIRED BY FEDERAL OCCUPATIONAL SAFETY AND HEALTH ACT (OSHA) AND THE FIRE AUTHORITY REGULATIONS.

1.33 THE GENERAL CONTRACTOR SHALL REPLACE ANY BROKEN OR CRACKED WINDOW GLAZING.

1.34 THE GENERAL CONTRACTOR SHALL VERIFY SIZE, ELECTRICAL REQUIREMENTS, LOCATION AND CHARACTERISTICS OF ALL WORK AND/OR EQUIPMENT SUPPLIED BY THE OWNER OR TENANT, WITH THE MANUFACTURER OR SUPPLIER PRIOR TO THE START OF RELATED WORK.

1.35 THE GENERAL CONTRACTOR SHALL SUBMIT ALL APPLICATIONS FOR PAYMENT TO THE OWNER FOR REVIEW AND APPROVAL.

1.36 CONTRACTOR DOES NOT MAINTAIN EXCLUSIVE ACCESS TO THE WORK AREA. CONTRACTOR SHALL COORDINATE WITH THE ARCHITECT, CONSULTANTS, UTILITY WORKERS AND OTHER CONTRACTORS AS NEEDED TO ALLOW FOR THE PROGRESS OF WORK.

1.37 THE ARCHITECT HAS MADE EVERY EFFORT TO DESIGN THIS SPACE PLAN IN CONFORMANCE WITH CURRENT CALIFORNIA BUILDING CODES. HOWEVER, DUE TO THE UNPREDICTABILITY OF FINAL CODE INTERPRETATION BY INDIVIDUAL CITY AND COUNTY BUILDING DEPARTMENT OFFICIALS, THE ARCHITECT SHALL NOT BE RESPONSIBLE FOR CHANGES OR ADDITIONAL REQUIREMENTS TO THE WORKING DRAWINGS MADE BY THE BUILDING DEPARTMENT IN ORDER TO SECURE THE PERMIT OR ANY SUBSEQUENT FIELD CHANGES REQUIRED BY THE FIELD INSPECTOR DURING THE CONSTRUCTION PHASE.

1.38 THE DRAWINGS AND CONCEPTS SUBMITTED HEREWITH, U.O.N. ARE PROVIDED FOR USE REGARDING INTERIOR DESIGN, SPACE PLANNING AND COLOR SUGGESTIONS ONLY. STATEMENTS OF DESIGN AND INTENT CONTAINED HEREON DO NOT CONSIDER THE STRUCTURAL OR ENGINEERING SOUNDNESS OF ANY OF THE SUGGESTIONS OR IDEAS SUGGESTED.

1.39 ADDITIONALLY, U.O.N. THERE HAS BEEN NO STUDY DONE NOR ONE REQUESTED AS TO THE STRUCTURAL INTEGRITY OF THE BUILDING ITSELF OR PARTS THEREOF TO SUPPORT THE VARIOUS DESIGN ITEMS AND CONCEPTS SET FORTH. NO ENGINEERING OR STRUCTURAL INVESTIGATION HAS BEEN PERFORMED AND IT IS THE OBLIGATION OF THE PARTY RECEIVING THESE DRAWINGS TO HAVE ALL OF THE CONCEPTS REVIEWED REGARDING SUCH WORK AS IS NECESSARY TO ENSURE THE STRUCTURAL INTEGRITY AND ENGINEERING SOUNDNESS OF ANY OF THE CONCEPTS CONTAINED HEREIN.

1.40 CONTRACT CLOSE -OUT SHALL OCCUR ONLY AFTER THE ARCHITECT HAS ISSUED THE PUNCHLIST AND PUNCHLIST ITEMS HAVE BEEN CORRECTED BY THE CONTRACTOR.

1.41 GENERAL CONTRACTOR SHALL PROVIDE PROTECTION TO ALL EXISTING FINISHES IN THE ELEVATOR, LOBBY AND PUBLIC CORRIDORS AS WELL AS PROTECTIVE COVERINGS FOR CARPET, FURNISHINGS AND EXISTING FINISHES IN AREAS OF DEMOLITION AND CONSTRUCTION. CONTRACTOR SHALL BE RESPONSIBLE FOR THE REPAIR OF ANY DAMAGES CAUSED BY HIM OR HIS SUB-CONTRACTORS.

1.42 WHERE WORK OR EQUIPMENT IS INDICATED N.I.C., SUCH WORK AND/OR EQUIPMENT SHALL BE PROVIDED BY OTHERS. CONTRACTOR SHALL COORDINATE AND COOPERATE TO ENSURE SUCH INSTALLATION.

1.43 ALL WORK ON DRAWINGS SHALL BE PERFORMED IN COMPLIANCE WITH REQUIREMENTS OF THE LEASE WORK LETTER AND BUILDING STANDARD SPECIFICATIONS AND REGULATIONS WHETHER OR NOT LISTED ON DRAWINGS AND/OR INCLUDED HEREIN.

2.0 EXISTING CONDITIONS/DEMOLITION

2.1 THE DRAWINGS SHOW GENERAL INFORMATION ONLY. IT SHALL BE THE RESPONSIBILITY OF THE GENERAL CONTRACTOR TO EXAMINE THE SITE TO DETERMINE THE EXACT EXISTING CONDITIONS AND CHARACTER AND EXTENT OF THE WORK TO BE PERFORMED AND OPERATIONS REQUIRED.

2.2 THE FAILURE OR OMISSION OF THE GENERAL CONTRACTOR TO VISIT THE SITE AND ACQUAINT HIMSELF WITH THE EXISTING CONDITIONS SHALL IN NO WAY RELIEVE HIM FROM OBLIGATIONS WITH RESPECT TO THIS CONTRACT.

2.3 THE INFORMATION INDICATED IN THE DRAWINGS REPRESENTS THE BEST INFORMATION AVAILABLE FROM THE OWNER AS TO THE CHARACTER OF THE MATERIALS TO BE ENCOUNTERED AND THEIR LOCATIONS.

2.4 IT IS EXPRESSLY UNDERSTOOD AND AGREED THAT THE OWNER ASSUMES NO RESPONSIBILITY WHATSOEVER IN RESPECT TO THE SUFFICIENCY OR ACCURACY OF THE DRAWINGS OR THE INTERPRETATION THEREOF, AND THERE IS NO WARRANTY OR GUARANTEE, EITHER EXPRESSED OR IMPLIED, THAT THE CONDITIONS AND LOCATIONS INDICATED ARE REPRESENTATIVE OF THOSE EXISTING THROUGHOUT THE CONSTRUCTION OR THAT UNFORESEEN DEVELOPMENTS MAY NOT OCCUR.

2.5 THE GENERAL CONTRACTOR SHALL FURNISH ALL LABOR AND MATERIALS AS REQUIRED TO COMPLETE DEMOLITION AND REMOVAL OF ALL ITEMS INDICATED IN DRAWINGS OR AS OTHERWISE DIRECTED BY ARCHITECT.

2.6 THE GENERAL CONTRACTOR SHALL FURNISH OWNER WITH A COMPLETE INVENTORY LIST OF ALL ITEMS THAT CAN BE REUSED AND/OR STORED IN BUILDING STOCK, AND OBTAIN DIRECTIVE REGARDING THEIR DISPOSITION.

2.7 THE GENERAL CONTRACTOR SHALL EXECUTE ALL WORK WITHIN THE REGULATIONS OF PROPERTY MANAGEMENT FOR DEMOLITION AND REMOVAL OF DEBRIS, INCLUDING AFTER HOURS WORK, AS MAY BE REQUIRED.

2.8 ALL WORK DEMOLISHED SHALL BE REMOVED FROM THE PREMISES, EXCEPT ITEMS TO BE REUSED OR RETURNED TO OWNER OR AS OTHERWISE NOTED.

2.9 THE GENERAL CONTRACTOR SHALL REMOVE ALL RUBBISH AND WASTE MATERIALS, BOTH FROM HIS OWN AND OTHER SUBCONTRACTORS EMPLOYEES, AND PROVIDE FOR ITS REMOVAL FROM THE SITE.

2.10 THE GENERAL CONTRACTOR SHALL REMOVE FROM PREMISES ALL CONDUITS, BOXES, PLATES, BRIDGES, OR ANY OTHER TELEPHONE AND/OR ELECTRICAL WIRING AND EQUIPMENT LEFT AFTER WALL DEMOLITION.

2.11 THE GENERAL CONTRACTOR SHALL PROVIDE A VISQUEEN SEAL FROM FLOOR TO CEILING AT ALL INTERFACES TO PROTECT ADJACENT BUILDING PROPERTY WHILE DEMOLITION AND CONSTRUCTION ARE IN PROGRESS.THIS SEAL IS TO BE KEPT CLOSED AT ALL TIMES.

2.12 THE GENERAL CONTRACTOR SHALL CAP AND FLUSH OFF BEHIND FINISHED SURFACES ALL PLUGGED PLUMBING, FLOOR ELECTRICAL/TELEPHONE OUTLETS, AND ALL OTHER PROJECTING ITEMS WHICH ARE BEING ABANDONED.

2.13 CONTRACTOR SHALL INVENTORY AND MARK DAMAGED CONDITIONS AT PERIMETER WINDOW FRAME BEFORE PROJECT COMMENCEMENT. DOCUMENT EXISTING DAMAGE WITH BUILDING MANAGEMENT AND THE ARCHITECT U.O.N. CONTRACTOR TO INCLUDE IN SCOPE TO REPAIR/PAINT AS REQUIRED.

2.14 AT ANY EXISTING PARTITION SCHEDULED TO BE SLAB TO SLAB, CONTRACTOR TO VERIFY CONDITIONS AND DETERMINE IF EXISTING WALL CAN BE MODIFIED. PROTECT AND PREPARE FOR MODIFICATION OR DEMOLISH AS NECESSARY. REFER TO STANDARD DETAIL.

2.15 AT WALLS SCHEDULED FOR NEW FINISH, CONTRACTOR TO VERIFY EXISTING WALL CONDITIONS AND PROVIDE APPROPRIATE DEMOLITION OR PREPARATION TO ACCOMMODATE NEW FINISH INSTALLATION. U.O.N. THIS IS TO INCLUDE REMOVING LOOSE OR DEFECTIVE DRYWALL MATERIAL AND ANY WALLCOVERING EXISTING ON A WALL SCHEDULED TO RECEIVE A NEW FINISH. REFER TO FINISH PLAN FOR SCOPE.

2.16 UPON COMPLETION OF THE DEMOLITION WORK, THE GENERAL CONTRACTOR SHALL ENSURE THAT ALL AREAS ARE LEFT BROOM CLEAN.

2.17 BACKGROUND DRAWINGS ARE BASED ON ORIGINAL CONSTRUCTION DOCUMENTS, NOT AS-BUILT DRAWINGS. PLEASE VERIFY ALL CONDITIONS AND DIMENSIONS PRIOR TO CONSTRUCTION. REPORT ANY DISCREPANCIES TO THE ARCHITECT.

2.18 EXISTING CONDITIONS DAMAGED OR REMOVED AS A RESULT OF ALL WORK REQUIRED TO BE DONE UNDER THIS CONTRACT SHALL BE REPAIRED OR REPLACED TO ORIGINAL CONDITION AND FINISHED TO MATCH ADJACENT SURFACES.

2.19 PROTECT ALL AREAS NOT SCHEDULED FOR DEMOLITION/MODIFICATION.

2.20 DEMOLITION CONTRACTORS ARE TO CONSULT CLOSELY WITH MECHANICAL, ELECTRICAL AND PLUMBING CONTRACTORS, AS WELL AS THE OWNER'S TELEPHONE/CABLING/EQUIPMENT VENDOR PRIOR TO COMMENCEMENT OF DEMOLITION.

2.21 DUE TO THE POSSIBILITY OF DISCOVERING UNFORESEEN CONDITIONS DURING DEMOLITION, IT SHALL BE THE RESPONSIBILITY OF THE CONTRACTOR TO ALSO STUDY THE FULL INTENT OF REQUIRED DEMOLITION BY INCORPORATING A COMPLETE ANALYSIS OF THE PROPOSED NEW CONSTRUCTION.

2.22 EACH AREA OF DEMOLITION IS TO BE CLEAR OF DEBRIS AND IS TO BE SWEPT CLEAN. METHOD OF DEBRIS REMOVAL MUST BE IDENTIFIED BY THE CONTRACTOR AND APPROVED BY THE BUILDING OWNER.

2.23 THE GENERAL CONTRACTOR IS RESPONSIBLE FOR CHECKING CONSTRUCTION DOCUMENTS AND FIELD CONDITIONS FOR ACCURACY AND CONFIRMING THAT THE WORK CAN BE DONE AS SHOWN, BEFORE PROCEEDING WITH THE DEMOLITION. IF THERE ARE COORDINATION QUESTIONS, THE CONTRACTOR IS RESPONSIBLE FOR OBTAINING A CLARIFICATION FROM THE DESIGNER BEFORE PROCEEDING WITH THE WORK IN QUESTION.

2.24 ANY PENETRATIONS MADE TO FLOOR SLABS DURING DEMOLITION/REMODEL OPERATIONS, OR EXISTING PENETRATIONS, SHALL BE FIRE RATED WITH U.L. APPROVED MATERIALS AND METHODS TO MAINTAIN EXISTING FIRE RATING.

2.25 ALL EXISTING PENETRATIONS FOUND TO BE NON-CONFORMING SHALL ALSO BE FIRE-SAFE AS PART OF THIS PROJECT.

2.26 THE GENERAL CONTRACTOR AND ALL SUBCONTRACTORS SHALL CAREFULLY STUDY THE DRAWINGS AND COMPARE THEM TO THE EXISTING CONDITIONS AND NOTIFY THE ARCHITECT OF ANY DISCREPANCIES PRIOR TO SUBMISSION OF BIDS TO GENERAL CONTRACTOR AND/OR TENANT. CHANGE ORDER REQUESTS FOR OBVIOUS EXISTING CONDITION, DISCREPANCIES WILL NOT BE CONSIDERED BY TENANT NOR ARCHITECT.

2.26 REPAIR AND/OR REPLACE DAMAGE TO ANY PARTITIONS NOT DESIGNATED TO BE DEMOLISHED DURING DEMOLITION AND/OR CONSTRUCTION. ALL SURFACES THAT ARE SCHEDULED TO RECEIVE NEW FINISH SHALL BE PREPARED ACCORDINGLY AND APPROPRIATELY. REFER ALSO TO FINISH PLAN.

2.27 GENERAL CONTRACTOR, SHALL FIELD-IDENTIFY ALL OBJECTS PROTRUDING ABOVE SLAB AND FLOOR. VERIFY USE/PURPOSE OF ANY SUCH DEVICES AND PROTECT ALL THAT ARE INTENDED TO REMAIN OR BE RE-USED AS PART OF THE FINAL REMODEL CONSTRUCTION. OTHERWISE, REMOVE, GRIND SMOOTH AND/OR CAP AS MECHANICAL, PLUMBING, AND ELECTRICAL DESIGN-BUILD DOCUMENTS FOR COMPLETE COORDINATION.

2.28 CONTRACTOR TO ASSESS EXISTING CONDITION OF SUBSTRATE AT FLOORING DEMOLITION. PROVIDE ALL DEMOLITION REQUIRED. WHERE DEMOLITION CAUSES UNEVENNESS OR VOIDS IN THE FLOOR CONTRACTOR SHALL CLEAN, SCRAPE AND LEVEL THE FLOOR WITH THE EXISTING ADJACENT SURFACE. PREPARE SURFACE AS REQUIRED TO ACCEPT NEW FINISH AND IN A MANNER CONSISTENT WITH HIGH QUALITY WORKMANSHIP.

2.29 U.N.O. AT ANY ROOM WITH EXISTING VCT FLOORING SCHEDULED TO RECEIVE NEW FINISH, CONTRACTOR TO EVALUATE THE REMOVAL OF THE FLOORING. IF THE VCT FLOORING REMAINS, PREPARE EXISTING SURFACE AS REQUIRED BY MANUFACTURER RECOMMENDATIONS TO RECEIVE NEW FINISH. REFER TO FINISH PLAN FOR SCOPE.

2.30 ANY PROJECTING OR SURFACE MOUNTED ITEMS BEING ABANDONED (EXISTING DUCT WORK, PIPING, PLUMBING FIXTURES AND CONDUITS) OR SCHEDULED TO BE DEMOLISHED AT WALLS SCHEDULED TO BE DEMOLISHED SHALL BE DEMOLISHED BACK TO POINT OF ORIGIN. ANY SUCH ITEMS TO REMAIN SHALL BE REROUTED AND CONCEALED. SEE DESIGN/BUILD AND/OR ENGINEERED DOCUMENTS FOR EXTENT OF WORK. REFER TO BUILDING STANDARDS FOR GUIDELINES ON REMOVAL AND/OR DISPOSITION OF MECHANICAL, PLUMBING AND ELECTRICAL SYSTEMS/DEVICES. REFER TO MECHANICAL/PLUMBING /ELECTRICAL PLANS FOR SPECIFIC DIRECTION.

2.31 ALL MATERIAL DISMANTLED FROM EXISTING WORK SHALL BECOME THE PROPERTY OF THE OWNER AND SHALL BE STORED OR DISPOSED OF PER OWNER'S INSTRUCTIONS TO THE CONTRACTOR. ALL EQUIPMENT AND MATERIAL WHICH ARE IN OPERATING CONDITIONS WHEN REMOVED SHALL BE MAINTAINED IN SUCH. [illegible]

2.32 GENERAL CONTRACTOR TO MAKE NECESSARY ADJUSTMENTS TO EXISTING HVAC SYSTEM AS REQUIRED TO ACCOMMODATE NEW CONSTRUCTION. REFER TO MECHANICAL PLANS FOR PROVIDING PROPER ZONING AND INSTALLATION OF APPROPRIATE ZONE CONTROLS.

2.33 ADEQUATE CLEAN-UP PROTECTION AND REPLACEMENT OF ANY CEILING TILES REMOVED DURING THE COURSE OF UNDER FLOOR WORK MUST BE REPLACED BEFORE THE START OF BUSINESS MONDAY FOLLOWING ANY OVERTIME WEEKEND WORK PERFORMED IN ORDER THAT THE TENANT WILL NOT BE INCONVENIENCED IN THE NORMAL CONTINUATION OF HIS REGULAR BUSINESS HOURS.

2.34 CONTRACTOR TO COMPLY WITH THE CONSTRUCTION AND DEMOLITION (C&D). IT IS THE RESPONSIBILITY OF THE CONTRACTOR TO PROPERLY DOCUMENT THE RECYCLING, RE-USING OR DONATION OF THE C&D WASTE.

2.35 SPRINKLERS, STROBE ALARMS, DETECTORS, NOT SHOWN ON PLAN. CONTRACTOR TO ASSESS REQUIREMENTS FOR NEW IMPROVEMENTS AND RELOCATE AS NECESSARY PER BUILDING STANDARD/STATE CODE. CONTRACTOR TO COORDINATE MODIFICATIONS WITH BUILDING ENGINEERING/OWNER BEFORE DEMOLITION COMMENCEMENT.

2.36 U.N.O. CONTRACTOR TO TAKE ALL PRECAUTIONS TO PRESERVE AT MAXIMUM THE SUSPENDED CEILING ASSEMBLIES, DRYWALL, LIGHTING AND MECHANICAL FIXTURES. CONTRACTOR RESPONSIBLE FOR REVIEW AND UNDERSTANDING OF WALL DEMOLITION/NEW WALL CONSTRUCTION AS RELATES TO CEILING SCOPE. REFER TO REFLECTED CEILING PLAN.

2.37 U.N.O. ALL CEILING TILE REMOVED FROM DEMOLITION THAT IS IN GOOD CONDITION SHOULD BE SALVAGED FOR REUSE/REINSTALLATION. AT CEILING AFFECTED BY CONSTRUCTION OF WALL LOCATIONS, CONTRACTOR TO EVALUATE TO REPAIR OR TO REPLACE GRID/TILES.

2.38 AFTER CEILING REMOVAL CONTRACTOR RESPONSIBLE FOR VERIFICATION OF ITEMS IN PLENUM REQUIRING MODIFICATION OR RELOCATION. CONTRACTOR TO COORDINATE WITH BUILDING ENGINEER/OWNER FOR DISPOSITION OF PLENUM AS SUITE TO CLEAR ABANDONED CABLES. DO NOT AFFECT OR REMOVE ANY PLENUM CONDITIONS FOR EXISTING DATA CABLE AT PREMISES WITHOUT AUTHORIZATION. DO NOT REMOVE ANY COMMUNICATION CABLES UTILIZED BY TENANT WITHOUT AUTHORIZATION.

2.39 CUTTING WORK SHALL BE DONE WITH MINIMUM DAMAGE TO SURROUNDING SURFACES TO BE RETAINED. VERIFY LOCATIONS OF ALL ABOVE CEILING BRACING WIRES.

2.40 ELECTRICAL CONTRACTOR OR DESIGN-BUILD IS RESPONSIBLE TO VERIFY EXISTING CONDITIONS PRIOR TO DEMOLITION COMMENCEMENT. CONTRACTOR RESPONSIBLE FOR FIELD VERIFICATION, REMOVAL AND/OR REPLACEMENT OF ELECTRICAL SYSTEMS. ELECTRICAL CONTRACTOR TO ASSESS ALL REQUIREMENTS FOR NEW SCOPE.

2.41 U.N.O. ELECTRICAL CONTRACTOR RESPONSIBLE TO INVENTORY QUANTITY OF LIGHT FIXTURES AND EXIT SIGNS. ELECTRICAL CONTRACTOR TO ASSESS REQUIREMENTS FOR NEW SCOPE AND DETERMINE QUANTITY OF FIXTURES/EXIT SIGNS TO REMOVE/RELOCATE. REFER TO REFLECTED CEILING PLAN FOR REQUIREMENTS. VERIFY THAT LIGHT FIXTURES/EXIT SIGNS ARE FULLY FUNCTIONING, ARE IN GOOD CONDITION AND COMPLY WITH BUILDING STANDARD. U.N.O. ALL LIGHT FIXTURES/EXIT SIGNS SCHEDULE TO BE REMOVED SHOULD BE SAVED FOR RELOCATION.

2.42 U.N.O. CONTRACTOR TO REMOVE ANY DISCOLORED OR DAMAGED LIGHT FIXTURES LENS. PREPARE FOR REPLACE WITH NEW.

2.43 ANY LIGHT FIXTURE/EXIT SIGN THAT IS IN CONFLICT WITH A NEW WALL SHOULD BE REMOVED. SAVE FOR RELOCATION. REFER TO REFLECTED CEILING PLAN FOR SCOPE.

2.44 U.N.O. AT DEMO WALL LOCATIONS VERIFY USE OF EXISTING LIGHT SWITCH. BREAK SWITCH LEGS FOR NEW LIGHTING CONFIGURATION. RELOCATE SWITCH OR PROVIDE NEW AS REQUIRED. CONTRACTOR TO ENSURE THAT AT ALL FIXTURES TO MAINTAIN CONTROL BY A SWITCH/MOTION SENSOR. REFER TO BUILDING STANDARDS.

2.38 U.N.O. EXISTING OUTLETS, RECEPTACLES/ ELECTRICAL PANELS, NOT SHOWN ON PLAN. ELECTRICAL SUBCONTRACTOR TO ASSESS REQUIREMENTS FOR DEMOLITION AND NEW IMPROVEMENTS. REFER TO POWER PLAN FOR REQUIREMENTS. CONTRACTOR TO INVENTORY QUANTITY FOR ACCURATE BID. IF A PROPOSED OUTLET IS WITHIN 12" OF AN EXISTING, A NEW DEVICE IS NOT REQUIRED.

2.39 U.N.O. REMOVE ANY EXISTING OUTLETS, ALARMS, SWITCHES, THERMOSTATS THAT ARE IN CONFLICT WITH NEW CONSTRUCTION (NEW PARTITIONS, NEW MILLWORK). CONTRACTOR TO COORDINATE RELOCATION AS NECESSARY.

2.40 U.N.O. ANY ELECTRICAL/DATA OUTLETS AND CONDUITS EXISTING AT WALLS SCHEDULED TO BE DEMOLISHED, CONTRACTOR TO REMOVE DEVICES, CONDUITS, SAFE-OFF POWER, PULL LINES AND CLEAN PLENUM. CONTRACTOR TO INVENTORY QUANTITY.

2.41 U.N.O. ANY ELECTRICAL PANEL IF EXISTING AT WALLS SCHEDULED TO BE DEMOLISHED, CONTRACTOR TO TAKE ALL CIRCUITS BACK TO BUILDING PANEL, OR PREPARE TO RE-ROUTE TO NEW PANEL LOCATION.

2.42 WHERE OCCURS CONTRACTOR SHOULD DETERMINE IF ELECTRICAL PANEL SHOULD BE RELOCATED AND ADVISE THE ARCHITECT TO COORDINATE NEW LOCATION AND PARTITION REQUIREMENTS.

2.43 AT ANY TELEPHONE BOARD EXISTING AT WALLS SCHEDULED TO BE DEMOLISHED, CONTRACTOR TO REMOVE BOARD, PULL LINES AND CLEAN PLENUM.

2.44 MECHANICAL CONTRACTOR TO FIELD VERIFY EXISTING MECHANICAL EQUIPMENT. VERIFY THAT ALL SYSTEMS ARE FULLY FUNCTIONING AND SAFE-OFF ANY ITEMS SCHEDULED FOR RE-INSTALLATION.

2.45 HVAC FIXTURES IN CONFLICT WITH NEW WALLS TO BE REMOVED. HVAC CONTRACTOR TO DETERMINE TO DEMO/RELOCATE AND ROUTING OF DUCTWORK AS REQUIRED.

2.46 AT DEMO WALL LOCATIONS, THERMOSTATS SHOULD BE TAKEN TO PLENUM BEFORE DEMOLITION AND SAVED FOR REUSE.

2.47 U.N.O. ALL HVAC GRILLES THAT ARE REMOVED SHOULD BE SALVAGED FOR REUSE/REINSTALLATION. ALL SUPPLIES AND RETURNS TO BE IN GOOD CONDITION. UNUSED FIXTURES TO BE RETURNED TO BUILDING OWNER.

2.48 MECHANICAL CONTRACTOR IS RESPONSIBLE FOR TERMINATING ANY THERMOSTATS DURING DEMOLITION. NOT DEMOLITION CONTRACTOR.

3.0 PATCHING & CUTTING

3.1 THE GENERAL CONTRACTOR SHALL DO ALL CUTTING, FITTING AND PATCHING WORK THAT MAY BE REQUIRED TO MAKE ALL PARTS COME TOGETHER PROPERLY, AND FIT TO RECEIVE OR BE RECEIVED BY WORK OF OTHER CONTRACTORS WHERE SHOWN, OR REASONABLY IMPLIED BY, THE DRAWINGS AND NOTES.

3.2 THE GENERAL CONTRACTOR SHALL PROVIDE ALL FLOOR CUT-OUTS AND PATCHING REQUIRED FOR THE INSTALLATION OF ALL WORK.

3.3 THE GENERAL CONTRACTOR SHALL SURVEY ALL EXISTING FINISHED SURFACES TO REMAIN FOR CHIPS, CRACKS, HOLES, AND OTHER DAMAGE. THESE DEFECTIVE SURFACES SHALL BE REPAIRED, OR IF BEYOND REPAIRING, THEN THE GENERAL CONTRACTOR SHALL REMOVE ALL EXISTING AND REPLACE WITH NEW TO MATCH EXISTING TO THE SATISFACTION OF OWNER AND TENANT.

3.4 THE GENERAL CONTRACTOR SHALL INSPECT ALL EXISTING SURFACES TO REMAIN, AFTER DEMOLITION OF EXISTING FINISHES (I.E. WALLCOVERING, WALL BASE, ETC.). IF SURFACE IS NOT SMOOTH AND FLUSH TO RECEIVE NEW FINISH, SUBCONTRACTOR SHALL SKIM COAT AND SAND SMOOTH.

3.5 IN ALL AREAS WHERE DEMOLITION CAUSES AN UNEVENNESS IN SLAB OR LIGHTWEIGHT CONCRETE, THE CONTRACTOR SHALL PATCH TO LEVEL AS REQUIRED TO RECEIVE NEW FLOORING FINISH.

3.6 ALL EXISTING OR NEW CONSTRUCTION WORK SHOWN ON DRAWINGS THAT IS DAMAGED AS A RESULT OF WORK FOR THIS PROJECT, SHALL BE PATCHED AS REQUIRED TO MATCH IMMEDIATE EXISTING ADJACENT AREAS IN MATERIALS, FIRE RATING, FINISH AND COLOR, UNLESS OTHERWISE NOTED.

3.7 CONTRACTOR TO DOWEL/FILL/PATCH SLAB AFTER SAWCUTTING TO ENSURE SLAB STRUCTURAL INTEGRITY.

3.8 THE GENERAL CONTRACTOR SHALL PATCH ALL CRACKS, HOLES OR OTHER IMPERFECTIONS (PROJECTIONS SHALL BE REMOVED AND PATCHED) TO PROVIDE A CONTINUOUS SMOOTH FLOOR SURFACE.

3.9 THE GENERAL CONTRACTOR SHALL NOTIFY ARCHITECT AFTER FLOOR PATCHING IS DONE AND RECEIVE THEIR REVIEW PRIOR TO INSTALLATION OF FINISHED FLOORING.

4.0 PARTITIONS

4.1 THE GENERAL CONTRACTOR SHALL PROVIDE AND INSTALL ALL PARTITIONS AS DESIGNATED ON ARCHITECT DRAWINGS.

4.2 THE GENERAL CONTRACTOR SHALL PROVIDE CHALK LINE MARKINGS ON THE FLOOR OF ALL PARTITIONS FOR ARCHITECT AND TENANT REVIEW PRIOR TO FRAMING. SITE MEETING TO REVIEW CHALK LINES SHALL BE SCHEDULED BY THE GENERAL CONTRACTOR THREE (3) DAYS IN ADVANCE OF THE MEETING.

4.3 ALL WALL DIMENSIONS ARE FINISHED FACE OF WALL TO FINISHED FACE OF WALL, UNLESS OTHERWISE NOTED. AT BUILDING PERIMETER, WALLS SHALL BE CENTERED ON MULLIONS, UNLESS OTHERWISE NOTED.

4.4 WALLS SHOWN ALIGNED WITH EXISTING PARTITIONS SHALL BE FLUSH AND SMOOTH WITH EXISTING PARTITIONS, UNLESS OTHERWISE NOTED.

4.5 THE GENERAL CONTRACTOR SHALL USE METAL CORNER BEADS AT ALL EXPOSED CORNERS AND EXPOSED ENDS IN PLASTER AND DRYWALL PARTITIONS.

4.6 ALL PARTITIONS SHALL BE ANCHORED FIRMLY AS PER MANUFACTURER'S SPECIFICATIONS AND AS REQUIRED BY STATE AND LOCAL CODES.

4.7 THE GENERAL CONTRACTOR SHALL CONSTRUCT RETURN AIR OPENINGS IN SLAB TO SLAB PARTITIONS ABOVE HUNG CEILINGS. SIZE OF OPENING TO MATCH AREA CALCULATION REQUIREMENTS AS SHOWN ON ENGINEERED DRAWINGS. ALL OPENINGS IN DEMISING AND SOUND ATTENUATED WALLS TO HAVE SOUND BOOTS. OPENINGS IN FIRE RATED WALLS SHALL HAVE FIRE DAMPERS AS REQUIRED BY LOCAL BUILDING CODES. CONTRACTOR TO COORDINATE WITH ENGINEERING DRAWINGS AND INFORM ARCHITECT OF DISCREPANCIES PRIOR TO FINAL BIDDING.

4.8 THE GENERAL CONTRACTOR SHALL PROVIDE SUFFICIENT FRAMING FOR ALL WALL PENETRATIONS FOR DUCT WORK, RETURN AIR OPENINGS AND GRILL OPENINGS ABOVE AND BELOW SUSPENDED CEILINGS. THESE ARE TO BE COORDINATED WITH HVAC ENGINEERING DRAWINGS AND THE GENERAL CONTRACTOR'S MECHANICAL CONTRACTOR'S SHOP DRAWINGS. ALL OPENINGS SHALL BE PROPERLY SEALED FOR SOUNDPROOFING AND VIBRATION.

4.9 WHERE OPENINGS OCCUR IN EXISTING FIRE RATED FLOOR ASSEMBLY OR PARTITIONS, DUE TO EXISTING OR NEW CONDUIT RUNS, DUCTWORK, CABLES, PIPING, ETC., AND/OR WHERE EXISTING FIREPROOFING HAS BEEN REMOVED AS A RESULT OF EXISTING OR NEW CONSTRUCTION WORK, THE GENERAL CONTRACTOR SHALL CLOSE AND/OR PATCH AS REQUIRED ALL OPENINGS TO MATCH EXISTING ADJACENT AREAS IN MATERIAL, FINISH AND FIRE RATING.

4.10 ALL PENETRATIONS THROUGH FIRE RATED WALLS, FLOORS AND CEILINGS SHALL BE PROTECTED PER APPROVED "UL" METHODS.

4.11 ARCHITECT IS TO BE NOTIFIED OF ANY REQUIRED DEVIATION FROM CONSTRUCTION DIMENSIONS OR CLEARANCES AS DESIGNATED ON PLAN OR OF ANY APPARENT CONSTRUCTION CONFLICTS. BACKGROUND DRAWINGS ARE BASED ON ORIGINAL CONSTRUCTION DOCUMENTS, NOT AS-BUILT DRAWINGS. PLEASE VERIFY ALL CONDITIONS AND DIMENSIONS PRIOR TO CONSTRUCTION. REPORT ANY DISCREPANCIES TO THE ARCHITECT

4.12 EXISTING CONDITIONS DAMAGED OR REMOVED AS A RESULT OF ALL WORK REQUIRED TO BE DONE UNDER THIS CONTRACT SHALL BE REPAIRED OR REPLACED TO ORIGINAL CONDITION AND FINISHED TO MATCH ADJACENT SURFACES.

4.13 PROVIDE SEPARATE CIRCUITS AND CONTROLS FOR ALL LIGHTING AND ELECTRICAL SYSTEMS SO THAT THERE IS NO CROSSOVER BETWEEN REMODEL AND EXISTING ADJACENT SUITES, OFFICES, CONF. ROOMS, ETC.

4.14 PROVIDE SEPARATE MECHANICAL CONTROLS, DUCT WORK AND MECHANICAL SYSTEMS SUCH THAT THEY ARE CONTROLLED INDEPENDENTLY FOR THIS REMODEL AND DO NOT CROSSOVER INTO EXISTING ADJACENT SUITES.

4.15 DRYWALL: PATCH WALLS TO REMAIN WHERE DAMAGED AND/OR WHERE DEVICES/WALLS HAVE BEEN REMOVED. MAINTAIN RATINGS.

4.16 DRYWALL FINISH: GENERAL CONTRACTOR TO PROVIDE LEVEL 4 QUALITY AT ALL WALLS, AND LEVEL 5 FINISH AT CEILINGS/SOFFITS.

4.17 BACKING: PROVIDE 6" X 20 GA. BACKING IN WALL FOR CUSTOMER PROVIDED EQUIPMENT OR REQUIREMENTS: WALL MOUNTED MILLWORK, ETC. GENERAL CONTRACTOR TO COORDINATE LOCATIONS AND MOUNTING HEIGHT WITH CUSTOMER IN THE FIELD.

4.18 SEE SHEET A9.1 FOR DOOR INFO.

4.19 CONTRACTOR TO ENSURE SLAB IS IN ADEQUATE CONDITION FOR INSTALLATION OF NEW FINISH. PREPARE FLOOR AS REQUIRED PER MANUFACTURER'S RECOMMENDATIONS. NOTICEABLE DEFECTS THROUGH NEW WORK SHALL RESULT IN REINSTALLATION OF FINISH TO SATISFACTION OF TENANT.

4.20 UNLESS OTHERWISE DIRECTED, CONTRACTOR TO INCLUDE IN THE SCOPE TO SKIM COAT AT ALL WALLS WHERE WALLCOVERING HAS BEEN REMOVED. WHERE WALLCOVERING DEMOLITION DAMAGES DRYWALL CONDITIONS BEYOND WHICH SKIMCOAT WILL REPAIR FOR SPECIFIED FINISH, REPAIR/REPLACE DRYWALL.

4.21 U.N.O. WHERE EXISTING BASE BUILDING CONSTRUCTION INTERFACES WITH NEW CONSTRUCTION, CONTRACTOR TO PATCH AND REPAIR EXISTING SURFACES. SURFACES SHALL BE RESTORED TO APPEAR AS NEW AND READY TO RECEIVE NEW FINISH. PATCH, FILL ALL GOUGES, HOLES, CRACKS AND DENTS FOR UNIFORM FINAL FINISH ON ALL EXISTING SURFACES. U.N.O. CONTRACTOR TO PREP AND PUTTY COAT WALLS AT AREAS WHERE DEMO HAS OCCURRED OR WHERE PRIOR BASE INSTALLATION WILL RESULT IN VISIBLE ADHESIVE LINE WITH NEW BASE INSTALLATION. REFER TO FINISH PLAN FOR NEW REQUIREMENTS.

4.22 UNLESS OTHERWISE DIRECTED, WHERE ELECTRICAL AND COMMUNICATIONS OUTLETS HAVE BEEN REMOVED, CONTRACTOR TO PATCH AND REPAIR PARTITION TO MATCH EXISTING.

4.23 U.N.O. PROVIDE ADEQUATE FURRING TO ACCOMMODATE ANY RECESSED ELECTRICAL PANEL AT A NEW WALL. COORDINATE WITH ELECTRICAL DESIGN/BUILD ENGINEER FOR EXACT REQUIREMENTS. U.N.O. PROVIDE ADEQUATE FURRING TO ACCOMMODATE ANY RECESSED FIRE EXTINGUISHER. VERIFY SIZE TO PROVIDE ACCURATE DEPTH.

4.24 AT ALL DOOR LOCATIONS, INVENTORY THE REQUIREMENTS. MODIFY OR ADD TO CONSTRUCTION AS REQUIRED TO ACCEPT BUILDING STANDARD OR TENANT STANDARD DOOR ASSEMBLY. REFER TO DOOR SCHEDULE FOR REQUIREMENTS.

4.25 AT ANY WALL LOCATION SCHEDULED TO ACCOMMODATE PLUMBING FIXTURE SUPPORT AND SUPPLY/WASTE, PROVIDE FULLY INSULATED PLUMBING PARTITION 3 5/8" METAL STUD WITH GREEN BOARD AND BACKING AS REQUIRED. IF THE PARTITION IS EXISTING, MODIFY AS REQUIRED. TOTAL WALL THICKNESS SHALL BE AS NECESSARY WHERE BACK TO BACK INSTALLATION OCCURS. COORDINATE WITH PLUMBING PLANS AND SPECIFICATIONS.

4.26 AT ANY GLAZING INSTALLATION, CONTRACTOR TO VERIFY GLASS THICKNESS TO BE APPROPRIATE FOR INSTALLATION AND FRAME TYPE. NOTIFY THE ARCHITECT IF MODIFICATIONS FROM SPECIFICATIONS ARE REQUIRED.

4.27 ALL "HOLD" DIMENSIONS MUST BE MAINTAINED. DIMENSIONS ARE NOT ADJUSTABLE WITHOUT APPROVAL OF THE ARCHITECT UNLESS OTHERWISE NOTED.

4.28 ALL PARTITIONS SHOWN "ALIGN" ARE TO BE SMOOTH AND FLUSH WITH EXISTING CONSTRUCTION FOR ONE CONTINUOUS SURFACE. WHERE NEW PARTITIONS ARE TO ALIGN WITH EXISTING PARTITIONS, REMOVE EXISTING CORNER BEAD(S), ALIGN, FLOAT FLUSH WITH NEW PARTITION.

4.29 AT ALL COLUMN FURRING, GENERAL CONTRACTOR SHALL ENSURE THAT FURRING IS KEPT TO MINIMUM POSSIBLE DIMENSIONS UNLESS OTHERWISE NOTED.

4.30 HINGE SIDE OF ALL DOORS SHALL BE 4" PERPENDICULAR FROM FINISH WALL, U.O.N.

5.0 CEILING

5.1 THE GENERAL CONTRACTOR SHALL PROVIDE AND INSTALL NEW SUSPENDED ACOUSTICAL TILE AND GRID SYSTEM IN AREAS DESIGNED ON REFLECTED CEILING PLAN AND FASCIAS OR ANY BREAK IN THE CEILING HEIGHTS SHALL BE AS SHOWN ON DRAWINGS AND SHALL BE FORMED OF GYPSUM WALLBOARD ON METAL FRAMING.

5.3 SUSPENDED CEILING HEIGHTS SHALL BE AS SHOWN ON DRAWINGS AND DETAILS. ANY DEVIATION FROM HEIGHTS SHOWN BASED UPON EXISTING FIELD CONDITIONS SHALL BE SUBMITTED TO ARCHITECT FOR REVIEW PRIOR TO START OF WORK IN QUESTION, OR RELATED WORK. ENSURE CLEARANCES FOR FIXTURES, DUCTS, ETC. NECESSARY TO MAINTAIN THE SPECIFIED FINISH CEILING HEIGHT AS NOTED ON THE DRAWINGS.

5.4 THE CEILING SUBCONTRACTOR SHALL CLOSELY COORDINATE HIS WORK WITH OTHER SUBCONTRACTORS AND TENANT'S VENDORS AND/OR PREPARE COMPOSITE SHOP DRAWINGS WHENEVER THEIR RESPECTIVE WORK IS CONTIGUOUS.

5.5 THE GENERAL CONTRACTOR SHALL PROVIDE AND INSTALL ALL CEILING ACCESS PANELS IN GYPSUM BOARD CEILINGS AS REQUIRED FOR MECHANICAL, ELECTRICAL AND PLUMBING ACCESS PER LOCAL CODES, WHETHER INDICATED ON DRAWINGS OR NOT. COORDINATE LOCATIONS SIZE AND TYPE WITH ARCHITECT PRIOR TO INSTALLATION.

5.6 PRIOR TO CLOSING UP ANY CEILING, ALL PLENUM SYSTEMS (HVAC, PLUMBING, ELECTRICAL, ETC.) SHALL BE INSPECTED AND WHERE REQUIRED, TESTED BY CONTRACTOR'S ENGINEERS, TO INSURE THEIR PROPER INSTALLATION AND FUNCTION. CONTRACTOR IS RESPONSIBLE FOR VERIFICATION OF ITEMS IN PLENUM REQUIRING MODIFICATION AND RELOCATION DUE TO NEW REQUIREMENTS.

5.7 ALL DOWNLIGHTS, WALL WASHERS, SPRINKLER HEADS, SPEAKERS, SENSORS, AND OTHER CEILING-MOUNTED FIXTURES SHALL BE CENTERED ON THE 2'X2' MODULE CREATED BY CEILING GRIDS AND CEILING TILE SCORE LINES AND SHALL ALIGN IN STRAIGHT LINE, UNLESS OTHERWISE NOTED.

5.8 CEILINGS IN CLOSETS SHALL BE OF THE SAME HEIGHTS AND CONSTRUCTION AS THAT OF ADJOINING SPACE, EXCEPT AS OTHERWISE NOTED.

5.9 THE GENERAL CONTRACTOR SHALL PROVIDE CUT-OUTS AND OTHER SPECIAL PROVISIONS IN ACOUSTICAL WORK AS REQUIRED FOR LIGHTING FIXTURES, REGISTERS, AND DIFFUSERS AND OTHER INSERTED ITEMS.

5.11 THE GENERAL CONTRACTOR SHALL REMOVE, REPAIR AND/OR REPLACE ANY AND ALL CEILING TILES THAT ARE DISCOLORED OR DAMAGED OR IN ORDER TO FACILITATE PLENUM SYSTEM INSTALLATIONS. INTENT IS TO ALLOW FOR CONSISTENT COLOR AND DIRECTION IN DEFINED AREAS AS NECESSARY.

5.12 ALL FIRE/LIFE SAFETY DEVICES TO BE BUILDING STANDARD. ALL SPRINKLERS IN DRYWALL CEILING AREAS SHALL HAVE CONCEALED HEAD ASSEMBLIES. COLOR OF TRIM SHALL MATCH ADJACENT CEILING.

5.13 BACKGROUND DRAWINGS ARE BASED ON ORIGINAL CONSTRUCTION DOCUMENTS, NOT AS-BUILTS. VERIFY ALL CONDITIONS AND DIMENSIONS PRIOR TO CONSTRUCTION. REPORT ANY DISCREPANCIES TO THE ARCHITECT

5.14 EXISTING CONDITIONS DAMAGED OR REMOVED AS A RESULT OF ALL WORK REQUIRED TO BE DONE UNDER THIS CONTRACT SHALL BE REPAIRED OR REPLACED TO ORIGINAL CONDITION AND FINISHED TO MATCH ADJACENT SURFACES.

5.15 CONTRACTOR TO FIELD VERIFY (E) DEMISING PARTITIONS & CONFIRM THAT PARTITION CONTAINS INSULATION WITH BATT INSULATION & IS FULL HEIGHT PRIOR TO BID. IF NOT PROVIDED G.C. TO INCLUDE IN BID.

5.16 PROVIDE SEPARATE CIRCUITS AND CONTROLS FOR ALL LIGHTING AND ELECTRICAL SYSTEMS SO THAT THERE IS NO CROSSOVER BETWEEN REMODEL AND EXISTING ADJACENT SUITES, OFFICES, CONF. ROOMS, ETC.

5.17 PROVIDE SEPARATE MECHANICAL CONTROLS, DUCT WORK AND MECHANICAL SYSTEMS SUCH THAT THEY ARE CONTROLLED INDEPENDENTLY FOR THIS REMODEL AND DO NOT CROSSOVER INTO EXISTING ADJACENT SUITES.

5.18 EXCEPT WHERE RIGID BRACES ARE USED TO LIMIT LATERAL DEFLECTION, SPRINKLER HEADS AND OTHER PENETRATIONS THROUGH THE CEILING TILE REQUIRE MINIMUM 2-INCH RINGS. SLEEVES OR ADAPTERS THAT WILL ALLOW A MINIMUM 1-INCH CEILING MOVEMENT IN ALL HORIZONTAL DIRECTIONS. ALTERNATIVELY, A SWING JOINT CAN BE PROVIDED AT THE TOP OF THE SPRINKLER HEAD EXTENSION TO ACCOMMODATE THE 1-INCH MOVEMENT.

5.19 PROVIDE CLASS "C" FLAME SPREAD AND SMOKE DENSITY FOR WALL AND CEILING FINISHES IN ACCORDANCE WITH CBC TABLE 803.5.

5.20 CONTRACTOR TO PROVIDE AND INSTALL LATERAL AND SEISMIC SUPPORT FOR ALL SUSPENDED CEILINGS AND CEILING RELATED ELEMENTS AS REQUIREDz e BY APPLICABLE LOCAL CODES. SUSPENDED CEILINGS, ACOUSTIC OR GYPSUM BOARD EXCEEDING 144 SQUARE FEET IN NET AREA SHALL HAVE COMPRESSION STRUTS. STRUT SHALL CONSIST OF 3 5/8" METAL STUDS ATTACHED TO UNDERSIDE OF ROOF STRUCTURE TO CEILING GRID/CARRYING CHANNEL. SPACE STRUT AT 12-FEET ON CENTER IN BOTH DIRECTIONS AND 48" FROM WALLS.

5.21 CEILING MOUNTED HVAC HARDWARE IS TO BE LOCATED MINIMUM 18" HORIZONTALLY AWAY FROM WALLS, SHELVING, FILES, OR UPPER CABINET UNITS AS INDICATED ON PLANS.

5.22 MATERIAL DESIGN AND WORKMANSHIP SHALL COMPLY WITH REQUIREMENTS FOR A DIRECT HUNG CEILING OF **A.S.T.M. C-635, A.S.T.M. C 636** AND PROVISIONS AND EXCEPTIONS SPECIFIED.

5.23 ALL SUSPENSION WIRES SHALL BE MINIMUM 12GA. GALVANIZED IRON WIRES. SUSPENSION WIRES SHALL NOT HANG MORE THAN 1-" IN 6-" OUT OF PLUMB UNLESS COUNTER SLOPING WIRES ARE PROVIDED.

5.24 CROSS RUNNERS OVER 12" LONG AND ALL MAIN RUNNERS NOT CONNECTED TO WALLS MUST BE INTERCONNECTED NEAR THE FREE END WITH 16GA. WIRE OR A METAL STRUT SECURELY ATTACHED TO PREVENT SPREADING.

5.25 ALL CEILING WIRE, NON-SUPPORTED DUCT AND PIPES MUST BE SEPARATED BY MINIMUM 6".

5.26 ALL LIGHT FIXTURES SHALL BE ATTACHED TO THE CEILING GRID IN SUCH A MANNER SO AS TO RESIST A HORIZONTAL FORCE EQUAL TO THE WEIGHT OF THE FIXTURES.

5.27 WHERE THE CEILING LOADS DO NOT EXCEED 5 POUNDS PER SQUARE FOOT AND WHERE PARTITIONS ARE NOT CONNECTED TO THE CEILING SYSTEM, THE FOLLOWING BRACING METHOD MAY BE EMPLOYED.

A. LATERAL SUPPORT FOR SUSPENDED CEILING MUST BE PROVIDED **(I.B.C. CHAPTER 16)** WHERE CEILING LOADS ARE LESS THAN 5 PSF AND NOT SUPPORTING INTERIOR PARTITIONS, CEILING BRACING SHALL BE PROVIDED BY FOUR NO. 12GA. WIRES SECURED TO THE MAIN RUNNER WITHIN 2" OF THE CROSS RUNNER INTERSECTION AND SPLAYED 90 DEGREES FROM EACH OTHER AT AN ANGLE NOT EXCEEDING 45 DEGREES FROM THE PLANE OF THE CEILING. THESE HORIZONTAL RESTRAINTS POINTS SHALL BE PLACED 12-FEET O.C. IN BOTH DIRECTIONS WITH THE FIRST POINT WITHIN 4-FEET FROM EACH WALL. ATTACHMENT OF THE RESTRAINT WIRES TO THE STRUCTURE SHALL BE ADEQUATE FOR THE LOAD IMPOSED.

B. ALLOWANCE SHALL BE MADE FOR LATERAL MOVEMENT OF THE SYSTEM. MAIN RUNNERS AND CROSS RUNNERS MAY BE ATTACHED AT TWO ADJACENT WALLS WITH CLEARANCE BETWEEN THE WALL AND THE RUNNERS MAINTAINED AT THE OTHER TWO WALLS.

C. VERTICAL SUPPORT SHALL BE PROVIDED AS REQUIRED IN C.B.C. WITH THE ADDED REQUIREMENTS THAT DISCONTINUOUS ENDS OF CROSS RUNNERS AND MAIN RUNNERS BE VERTICALLY SUPPORTED WITHIN 8" OF SUCH ENDS AS THIS MAY OCCUR WHERE THE CEILING IS DISRUPTED BY A WALL.

D. LIGHTING FIXTURES AND AIR DIFFUSERS SHALL BE SUPPORTED DIRECTLY BY WIRES TO THE STRUCTURE ABOVE.

EXCEPTION: RECESSED LIGHTING FIXTURE NOT OVER 58 LBS. IN WEIGHT AND SUSPENDED AND PENDANT HUNG FIXTURES NOT OVER 20 LBS. IN WEIGHT, MAY BE SUPPORTED AND ATTACHED DIRECTLY TO THE CEILING SYSTEM RUNNERS BY A POSITIVE ATTACHMENT SUCH AS SCREWS OR BOLTS.

5.28 AIR DIFFUSERS WHICH WEIGH NOT MORE THAN 20 LBS. AND WHICH RECEIVE NO TRIBUTARY LOADING FROM DUCT WORK MAY BE POSITIVELY ATTACHED TO AND SUPPORTED BY THE CEILING RUNNERS.

5.29 THE ABOVE REQUIREMENTS ARE INTENDED TO BE IDENTICAL TO THOSE CURRENTLY ENFORCED BY **I.B.C. CHAPTER 16**. OTHER METHODS MAY BE USED PROVIDING THEY ARE SUBSTANTIATED BY DESIGN CALCULATIONS USING THE LOADS SPECIFIED IN CHAPTER 16.

5.30 GENERAL INSTALLATION REQUIREMENTS: INSTALL CEILINGS UNDER THE SUPERVISION OF AN EXPERIENCED SUPERINTENDENT. CONSULT WITH AND COORDINATE INSTALLATION WITH OTHER TRADES. INSTALL CEILINGS WATER LEVEL WITHIN A TOLERANCE OF 1/8" IN 12 FEET IN ANY DIRECTION. CONFORM TO REVIEWED SUBMITTALS.

5.31 PATTERN: UNLESS OTHERWISE INDICATED OR SPECIFIED, INSTALL CEILING IN REGULAR PATTERN, JOINT LINES PARALLEL TO WALLS. INSTALL ACOUSTICAL UNITS SYMMETRICALLY ABOUT CENTER LINES OF EACH ROOM OR SPACE, AVOIDING NARROW UNITS (LESS THAN HALF A TILE) AT WALLS.

5.32 FRAMING FOR LIGHTING AND MECHANICAL FIXTURES: OBTAIN NECESSARY DATA FROM OTHER TRADES AND PROVIDE ADDITIONAL HANGER WIRES AND FRAMING IN SUSPENDED GRIDS AS REQUIRED TO SUPPORT LIGHTING AND MECHANICAL FIXTURES.

5.33 CROSS TEES TO COMPLETE THE GRID. INSTALL MAIN TEES ALONG ALL THE EDGES OF MECHANICAL AND LIGHTING FIXTURES. LOCK SUSPENSION PARTS IN PLACE TO FORM A GRID CAPABLE OF WITHSTANDING A LATERAL FORCE OF 100 POUNDS MINIMUM IN TENSION AND COMPRESSION. INSTALL ACOUSTICAL UNITS WITH TIGHT FLUSH JOINTS NOT SUPPORTED ON TEES. PROVIDE MOLDINGS AT VERTICAL SURFACE AND AT PENETRATIONS.

5.34 EXPOSED GRID: SPACE THE MAIN TEES AT MAXIMUM 48" CENTERS AND INSTALL CROSS TEES TO COMPLETE THE GRID. INSTALL MAIN TEES ALONG SUSPENSION PARTS IN PLACE TO FORM A GRID CAPABLE OF RESISTING A LATERAL FORCE OF 100 POUNDS MINIMUM IN BOTH TENSION AND COMPRESSION. INSTALL ACOUSTICAL UNITS WITH TIGHT FLUSH JOINTS, ALL JOINT LINES STRAIGHT AND ALIGNED. CUT UNITS TO FIT TIGHTLY AROUND CEILING PENETRATIONS, AND ACCURATELY SCRIBE TO WALLS. INSTALL ACOUSTICAL UNITS WITH EDGES BEARING ON TEES, ALL EDGES SECURED WITH HOLD-DOWN CLIPS. JOINTS TIGHTLY BUTTED AND MITER CUT AT ANGLES. COPE THE BOTTOMS OF EXPOSED TEES FOR FLUSH JOINTS WITH WALL ANGLES OR CHANNELS. CONFORM TO THE UL DESIGN APPROVED FOR THE GRID.

5.35 CEILING OFFSETS: PROVIDE TRIMS WHERE SHOWN OR NECESSARY TO PROPERLY FINISH AT OFFSETS OR CEILING BREAKS, TYPES AS INDICATED, DIRECTED AND REVIEWED.

5.36 REPAIR, CLEANING AND COMPLETION: REMOVE AND REPLACE ALL DISCOLORED, BROKEN OR DAMAGED MATERIALS. COMPLETED CEILINGS SHALL PRESENT A SMOOTH LEVEL SURFACE FREE OF EDGE OR CORNER OFFSETS, CUPPING, SCRATCHES, GOUGES, OR OTHER DEFECTS. CLEAN EXPOSED SURFACE AND REMOVE FOREIGN MATTER. ALL CEILING LOCATIONS AFFECTED BY DEMOLITION/NEW CONSTRUCTION SHALL BE PATCHED AND REPAIRED FOR A CONTINUOUS APPEARANCE.

5.37 SLACK WIRES FOR LIGHT FIXTURES TO BE INSTALLED AT OPPOSITE CORNERS OF EACH FIXTURE. CEILING CONTRACTOR TO INSTALL.

5.38 ARCHITECTURAL REFLECTED CEILING PLAN TAKES PRECEDENCE OVER ELECTRICAL LIGHTING PLANS FOR LOCATION OF LIGHT FIXTURES, SWITCHING AND EXIT SIGNAGE.

5.39 U.N.O. CONTRACTOR IN INCLUDE IN SCOPE ANY COMMON AREA CORRIDOR AFFECTED BY DEMOLITION / NEW CONSTRUCTION. REPLICATE EXISTING CONDITIONS AT CEILING. PROVIDE NEW CEILING ASSEMBLY WITH REQUIRED LIGHTING TO MATCH EXISTING. MODIFY HVAC SUPPLY AND RETURN, SMOKE/FIRE DAMPERS AND SPRINKLERS AS NECESSARY.

5.40 WHEN A PROJECTION UNIT, PROJECTOR, VIDEO MONITOR, TENANT SIGNAGE, OR ANY OTHER EQUIPMENT REQUIRED TO BE INSTALLED AT THE CEILING, CONTRACTOR TO COORDINATE WITH VENDOR ALL THE NECESSARY REQUIREMENTS TO PROVIDE ADEQUATE SUPPORT.

5.41 PROVIDE NECESSARY ANGLE TRIMS AT CEILING PENETRATIONS BY WALLS AT ROOMS PERIMETER DUE TO INDEPENDENT CEILINGS.

5.42 IF ANY NEW OR RELOCATED FIXTURES ARE SHOWN AT A LOCATION THAT REQUIRES CUTTING A MAIN RUNNER, ADVISE ARCHITECT FOR SPECIFICATION OF REVISED LOCATION BEFORE GRID MODIFICATION AND LIGHTING POSITIONING.

5.42 CONTRACTOR IS RESPONSIBLE FOR FIRE/LIFE SAFETY ON A **DESIGN-BUILD BASIS.** CONTRACTOR TO FIELD VERIFY AND EVALUATE EXISTING CONDITIONS AT THE SPACE TO ACCOMMODATE NEW REQUIREMENTS AND PROVIDE ADEQUATE LIFE SAFETY COVERAGE AS REQUIRED FOR CODE. FIRE/LIFE SAFETY CONTRACTOR RESPONSIBLE TO PROVIDE **DESIGN/ BUILD** PLANS AND OBTAIN THEIR OWN PERMIT.

5.43 SPRINKLERS, SPEAKER/STROBE DEVICES/FIRE ALARMS ARE NOT SHOWN ON THIS PLAN. CONTRACTOR RESPONSIBLE FOR VERIFICATION, INVENTORY OF EXISTING FIRE/SAFETY DEVICES AVAILABLE FOR RELOCATION.

6.0 LIGHTING, POWER AND COMMUNICATIONS

6.1 THE CONTRACTOR SHALL FURNISH AND INSTALL ALL LIGHTING FIXTURES AND ELECTRICAL WORK AS SHOWN OR IMPLIED ON ALL DRAWINGS AND NOTES.

6.2 THE CONTRACTOR SHALL COORDINATE HIS WORK WITH MANUFACTURER'S SPECIFICATIONS.

6.3 THE WORK SHALL BE INSTALLED IN STRICT ACCORDANCE WITH THE REQUIREMENTS OF THE NATIONAL BOARD OF FIRE UNDERWRITERS, PUBLIC UTILITIES COMPANY, TELEPHONE COMPANY, AND ALL OTHER AUTHORITIES HAVING JURISDICTION.

6.4 UNLESS OTHERWISE NOTED, ALL NEW MATERIALS REQUIRED SHALL CONFORM WITH THE STANDARDS OF THE UNDERWRITERS LABORATORIES, INC., WHERE SUCH STANDARDS HAVE BEEN ESTABLISHED FOR THE PARTICULAR TYPE OF MATERIAL OR FIXTURE IN QUESTION.

6.5 PROPOSALS SHALL BE BASED UPON FURNISHING AND INSTALLING NEW LIGHTING FIXTURES AND REMOVING AND REINSTALLING EXISTING LIGHTING FIXTURES (INCLUDING NEW LAMPING) OF TYPES AND MANUFACTURERS AS INDICATED ON REFLECTED CEILING PLAN, AND/OR TO "MATCH EXISTING" WHERE NOTED.

6.6 THE GENERAL AND ELECTRICAL CONTRACTORS SHALL CHECK ALL CEILING HEIGHTS AND CEILING PLENUM CONDITIONS FOR CLEARANCE OF DUCTWORK, LIGHTING AND OTHER OBSTRUCTIONS TO ASSURE THE FINISHED CEILING HEIGHT SHOWN ON DRAWINGS IS ACHIEVABLE AND CONTINUOUS. ANY DISCREPANCIES SHALL BE BROUGHT TO ARCHITECT'S ATTENTION PRIOR TO FINAL PRICING.

6.7 ALL RECESSED FIXTURES SHALL BE SET FLUSH INTO CEILINGS.

6.8 THE ELECTRICAL CONTRACTOR SHALL SUBMIT CUTS OF ALL NON-BUILDING STANDARD FIXTURES AS SHOWN IN THE DRAWINGS, FOR REVIEW BY THE ARCHITECT AND ELECTRICAL ENGINEER.

6.9 THE ELECTRICAL SUBCONTRACTOR SHALL COORDINATE ANY ELECTRICAL OR LIGHTING INSTALLATION INTO CABINETWORK WITH CABINET SUBCONTRACTOR AS REQUIRED.

6.10 THE ELECTRICAL SUBCONTRACTOR SHALL COORDINATE ANY TELEPHONE / DATA / SECURITY AND AUDIO-VISUAL REQUIREMENTS WITH THE TENANT'S VENDORS AS REQUIRED.

6.11 THE ELECTRICAL SUBCONTRACTOR SHALL PROVIDE ALL TEMPORARY LIGHTING AND ELECTRICAL SERVICE FOR ALL TRADES AS REQUIRED.

6.12 WHERE MORE THAN ONE SWITCH OCCURS IN THE SAME LOCATION, THEY SHALL BE INSTALLED IN GANG TYPE BOX UNDER ONE COVER PLATE.

6.13 ALL ELECTRICAL, DATA/TELEPHONE RECEPTACLES AND LIGHT FIXTURES SHALL BE LOCATED WHERE DIMENSIONED ON PLANS. ALL FURNITURE FEEDS/J-BOXES TO BE LOCATED PER DIMENSIONS PROVIDED BY TENANT'S FURNITURE VENDOR.

6.14 ALL NEW OUTLETS ON COLUMNS WILL BE CENTERED ON FACE, UNLESS OTHERWISE NOTED.

6.15 UNLESS OTHERWISE NOTED, ALL TELEPHONE, DATA AND POWER OUTLETS SHALL BE INSTALLED VERTICALLY AT 18" ABOVE FINISH FLOOR TO CENTER OF BOX. (MINIMUM 15" FROM BOTTOM OF BOX)

6.16 UNLESS OTHERWISE NOTED, ALL THERMOSTATS AND CONTROL DEVICES SHALL BE A MAXIMUM OF 48" ABOVE FINISH FLOOR TO THE TOP OF THE BOX. THERMOSTATS AND LIGHTING CONTROLS OCCURRING WITHIN THE SAME ROOM SHALL BE LOCATED PER TYPICAL INSTALLATION ELEVATION IN DRAWINGS.

6.17 UNLESS OTHERWISE NOTED, ALL SIDE BY SIDE OUTLETS SHALL BE NO MORE THAN 6" ON CENTER, APART.

6.18 PROVIDE NEW BLANK COVER PLATES FOR EXISTING OUTLETS NOT BEING USED WHEN NOTED. COVER PLATES TO MATCH BUILDING STANDARD, AND/OR TO MATCHING EXISTING, UNLESS OTHERWISE NOTED.

6.19 OUTLETS AT BACK TO BACK LOCATIONS ARE TO BE STAGGERED.

6.20 ALL LAMPS SHALL BE IDENTICAL FROM THE SAME MANUFACTURER. CONTRACTOR SHALL REPLACE ALL NON-CONFORMING LAMPS.

6.21 ALL OUTLETS OCCURRING ON MILLWORK, OR OTHER FINISH PANELS SHALL BE INSTALLED FLUSH WITH FACE OF MILLWORK, OR FINISH PANEL.

6.22 UNLESS OTHERWISE NOTED, VOICE/DATA OUTLETS SHALL CONSIST OF A 2-GANG BOX WITH A PULL STRING AND 3/4" CONDUIT, STUBBED 6" ABOVE CEILING.

6.23 U.N.O. CONTRACTOR IS RESPONSIBLE FOR FIELD VERIFICATION AND EVALUATION OF EXISTING ELECTRICAL SYSTEMS INCLUDING VOICE/DATA, POWER, SECURITY AND ELECTRICAL.

6.24 U.N.O. EXISTING OUTLETS ARE NOT SHOWN ON PLAN. PROVIDE REQUIRED OUTLETS PER PLAN AND RE-USE ANY EXISTING OUTLETS WHERE POSSIBLE. PROVIDE NEW DEVICE AND COVER PLATE AS REQUIRED TO MATCH BUILDING STANDARD. ALL DATA/POWER SHOWN GROUPED ARE TO REMAIN WITHIN 4" OF ONE ANOTHER. HEIGHT OF ANY EXISTING OUTLETS TO REMAIN. NEW ARE TO MATCH BUILDING STANDARD AND COMPLY WITH CURRENT CODE.

6.25 COMMUNICATIONS, DATA, SECURITY, CABLING, AND EQUIPMENT: N.I.C. BY TENANT'S VENDOR. ALL CABLING TO BE PLENUM RATED WHEN LOCATED IN RETURN AIR PLENUM.

6.26 FIRE LIFE SAFETY SYSTEM: MODIFY EXISTING SYSTEM TO PROVIDE FULL FIRE LIFE SAFETY SYSTEM TO MEET TENANT'S REQUIREMENTS. GENERAL CONTRACTOR TO COORDINATE DRAWINGS AND INSTALLATION WITHIN THIS SCOPE OF WORK. SEE ELECTRICAL.

6.27 FURNITURE. N.I.C.: (BY CUSTOMER) FURNITURE CONSULTANT TO PROVIDE REQUIREMENTS. AT WORKSTATIONS WITH PANELS PROVIDE J-BOX FEED, AT WORKSTATIONS WITHOUT PANELS PROVIDE POWER/DATA AT NEAREST WALL/COLUMN.

6.28 GFI OUTLETS.: ALL OUTLETS WITHIN 6'-0" OF SINK TO BE GROUND FAULT INTERRUPTED.

6.29 OUTLETS.: PROVIDE BUILDING STANDARD OUTLETS/DEVICES AND COVER

6.30 CONTRACTOR IS RESPONSIBLE FOR MARKING ALL POWER AND SIGNAL LOCATIONS ON SLAB AND HAVING THEM REVIEWED BY THE ARCHITECT.

6.31 ALL DIMENSIONS ARE TO THE CENTERLINE OF OUTLET, PAIR OR GROUPING OF OUTLETS, UNLESS OTHERWISE NOTED.

6.32 WALL MOUNT TELEPHONE OUTLETS AT +48" A.F.F. AND SHALL BE INSTALLED VERTICALLY.

6.33 PRIOR TO FINAL HOOK-UP THE CONTRACTOR SHALL REQUEST THE ARCHITECT. TO REVIEW LOCATIONS OF ELECTRICAL FIXTURES FOR POSSIBLE ADJUSTMENTS (WITHIN 24-INCHES ONE DIRECTION AND 48-INCHES THE OTHER DIRECTION).

6.34 FOR APPLIANCES SUBMIT MANUFACTURER'S LITERATURE INCLUDING FULL PRODUCT DESCRIPTIONS, ILLUSTRATIONS, SPECIFICATIONS AND LINE DRAWINGS SHOWING CLEARANCES AND ROUGH-IN INFORMATION.

6.35 ALL TELEPHONE WORK SHALL BE COORDINATED BY THE GENERAL CONTRACTOR WITH TENANT'S CONSULTANT AND TELEPHONE COMPANY. ELECTRICAL CONTRACTOR TO PROVIDE 1" CONDUIT AT ALL BACK TO BACK WALL MOUNTED TELEPHONE OUTLETS. ELECTRICAL CONTRACTOR TO OBTAIN ALL ADDITIONAL TELEPHONE CONDUIT REQUIREMENTS FROM THE TENANT'S TELEPHONE CONSULTANT.

6.36 ELECTRICAL CONTRACTOR TO INSTALL CONDUIT WHEN SPECIFIED FOR AV, NETWORKING AND COMMUNICATIONS EQUIPMENT. CONDUIT SHALL BE ROUTED AT LEAST 6" FROM ALL A/C CONDUIT. 24" FROM LIGHT FIXTURES, 72" FROM ELEVATOR SHAFTS AND ELECTRICAL ROOMS OR ANY DEVICE WHICH MAY CAUSE INTERFERENCE WITH DATA TRANSMISSION OR RECEPTION.

6.37 PROVIDE BOXES, WIRING DEVICES, PLATES, CONDUIT AND WIRING TO J-BOXES AND ALL HOLD OPEN DOORS.

6.38 PROVIDE TRANSFORMERS WHEN NECESSARY FOR LOW VOLTAGE LIGHTING, BUSY LIGHTS OR OTHER SPECIAL ITEMS. VERIFY LOCATION WITH THE ARCHITECT.

6.39 ELECTRICAL CONTRACTOR TO CALCULATE VOLTAGE REQUIREMENTS NECESSARY TO SIZE SWITCHES AND PLAN CIRCUIT LOADS.

6.40 ELECTRICAL CONTRACTOR SHALL SUBMIT ALL NECESSARY DRAWINGS, CATALOG CUTS, ETC., FOR ARCHITECT REVIEW. SUBSTITUTIONS SHALL NOT BE MADE UNLESS ARCHITECT CONCURRENCE IS RECEIVED AND SHOP DRAWINGS ARE SUBMITTED FOR REVIEW. REFER TO BUILDING STANDARDS FOR ADDITIONAL INFORMATION AND SPECIFICATIONS. CONTRACTOR TO VERIFY LEAD TIME FOR ALL LIGHT FIXTURES SPECIFIED BEFORE CONSTRUCTION.

6.41 THE ARCHITECTURAL REFLECTED CEILING PLANS SHALL BE USED TO DETERMINE THE LOCATION, QUANTITY, EXTENT, AND TYPE OF LIGHT FIXTURES. ANY CONFLICTS BETWEEN DRAWINGS SHALL BE SUBMITTED IN WRITING TO THE ARCHITECT AND DESIGN/BUILD ENGINEERS DURING THE PRICING PERIOD. ALL CONFLICTS ARISING DURING THE CONSTRUCTION SHALL BE SUBMITTED IN WRITING TO THE ARCHITECT.

6.42 ALL SWITCHES SHOWN SHALL BE 42" ABOVE FINISH FLOOR, UNLESS OTHERWISE NOTED ON PLAN. ALL HEIGHTS ARE GIVEN FROM TOP OF ROUGH FLOOR TO CENTERLINE OF COVER PLATES, MOUNTED VERTICALLY LENGTHWISE, U.N.O. ALL GANGED SWITCHES SHALL BE COVERED WITH A ONE-PIECE PLATE. COLOR TO BE BUILDING STANDARD. IF IMPROVEMENT IS REUSING EXISTING DEVICES, NEW DEVICE AND COVER PLATE SHALL MATCH EXISTING. CONTRACTOR SHALL VERIFY.

6.43 REFER TO ELECTRICAL DESIGN/BUILD DRAWINGS FOR LOCATION OF EXIT LIGHTS AND OTHER LIFE SAFETY EQUIPMENT. VERIFY LOCATION WITH THE ARCHITECT POWER FOR EXIT LIGHTS AND EMERGENCY LIGHTING MUST CONFORM TO CURRENT C.B.C. REQUIREMENTS SECTIONS 1012 AND 1013. PROVIDE TWO SOURCES OF POWER IF THERE ARE 50 OR MORE OCCUPANTS.

6.44 CONTRACTOR RESPONSIBLE TO VERIFY THAT EXIT SIGNS AND EGRESS LIGHT FIXTURES ARE TO BE CIRCUITED TO AN EMERGENCY PANEL, OR TO BE SELF CONTAINED BATTERY BACK-UP. VERIFY BUILDING STANDARDS. LOCATION FOR EXITS SIGNS SHALL BE PROVIDED BY THE ARCHITECT. LOCATION FOR EGRESS LIGHT FIXTURE SHALL BE PROVIDED BY ELECTRICAL CONTRACTOR.

6.45 GENERAL CONTRACTOR AND ELECTRICIAN ARE RESPONSIBLE FOR FINAL CONNECTION AND INSTALLATION OF ELECTRICAL COMPONENTS FOR SYSTEMS FURNITURE.

6.46 AT ANY EXISTING SPACE THAT IS DIVIDED INTO A TWO SEPARATE SUITES, CONTRACTOR TO SPLIT ELECTRICAL SYSTEMS AS REQUIRED, SO EACH SUITE OPERATES INDEPENDENTLY.

6.47 CONTRACTOR RESPONSIBLE FOR BUILDING STANDARD EXIT SIGNS INVENTORY. VERIFY NUMBER AND CONDITION AVAILABLE FOR RELOCATION. REFER TO REFLECTED CEILING PLAN FOR REQUIREMENTS.

6.48 CONTRACTOR RESPONSIBLE TO COORDINATE WITH BUILDING ENGINEER/OWNER TO REWORK OR TO PROVIDE NEW LIGHTING CONTROL SYSTEM FOR DAY-LIGHTING CONTROL AND AFTER HOUR CONTROL OF LIGHT FIXTURES. CONTRACTOR TO ENSURE COMPLIANCE WITH TITLE 24.

6.49 CONTRACTOR TO ENSURE THAT ALL FIXTURES SCHEDULED TO REMAIN OR NEW MAINTAIN CONTROL BY EXISTING/NEW SWITCHING OR MOTION SENSOR. REFER TO BUILDING STANDARDS.

6.50 U.N.O. ALL RECESSED LIGHT FIXTURES TO BE CENTERED WITHIN TILE, BOTH DIRECTIONS.

7.0 HVAC

7.1 THE GENERAL CONTRACTOR SHALL NOTIFY THE MECHANICAL ENGINEER FOR REVIEW OF MECHANICAL WORK PRIOR TO INSPECTION AND CLOSING-UP CEILING.

7.2 THE HVAC CONTRACTOR SHALL BE RESPONSIBLE FOR FIELD SUPERVISION OF ALL THEIR WORK DURING INSTALLATION AND SHALL INSPECT ALL SYSTEMS FOR PROPER OPERATIONS AT COMPLETION OF JOB.

7.3 SHOP DRAWINGS OF ALL HVAC EQUIPMENT, REGISTERS; INCLUDING ACCESS PANELS IF REQUIRED, SHALL BE SUBMITTED TO ARCHITECT AND MECHANICAL ENGINEER FOR REVIEW PRIOR TO PROCEEDING WITH FABRICATION AND/OR INSTALLATION OR RELOCATION.

7.4 INSTALLATION SHALL BE COORDINATED WITH ALL TRADES AS REQUIRED FOR PROPER ASSEMBLY. CEILING DIFFUSERS TO BE RELOCATED TO ACCOMMODATE NEW LIGHT FIXTURE PATTERNS.

7.5 INTERIOR SPACES SHALL BE MECHANICALLY VENTILATED IN ACCORDANCE WITH APPLICABLE CODES.

7.6 THE HVAC ENGINEER SHALL PROVIDE NECESSARY ENGINEERING DRAWINGS AND CALCULATIONS TO REWORK ALL EXISTING EQUIPMENT AND TO DETERMINE ALL NEW EQUIPMENT TO MEET THE TENANT'S REQUIREMENT.

7.7 THERMOSTATS, SUPPLY AND RETURN AIR GRILLE LOCATIONS NOT SHOWN ON THIS PLAN. IF THE SCOPE OF WORK IS "DUCTWORK-ONLY", OR IF NEW UNITS, MECHANICAL DESIGN/BUILD ENGINEER IS RESPONSIBLE TO PROVIDE PLANS REFLECTING EXISTING AND/OR NEW LAYOUT OF HVAC DUCTWORK, SUPPLY AND RETURN AIR GRILLES.

7.8 HVAC ENGINEER TO PROVIDE ALL NECESSARY TITLE 24 REPORTS REQUIRED TO OBTAIN PERMIT

7.9 FOR ANY EXHAUST SYSTEM REQUIRED AT THE SPACE, CONTRACTOR TO COORDINATE WITH BUILDING ENGINEER/OWNER FOR DUCTWORK CONFIGURATION.

7.10 AT ANY SPACE THAT IS DIVIDED INTO TWO SEPARATE SUITES, CONTRACTOR TO SPLIT MECHANICAL SYSTEMS AS REQUIRED, SO EACH SUITE OPERATES INDEPENDENTLY. PROVIDE INDEPENDENT CONTROL. VERIFY THAT ALL DUCTWORK, SUPPLIES, RETURNS AND THERMOSTATS ARE SPLIT PROPERLY. RELOCATE EXISTING AS NECESSARY. PROVIDE PROPER ZONING AND INSTALL APPROPRIATE ZONE CONTROLS.

7.11 FOR ANY EXHAUST SYSTEM REQUIRED AT THE SPACE, CONTRACTOR TO COORDINATE WITH BUILDING ENGINEER/OWNER FOR DUCTWORK CONFIGURATION.

7.12 FOR DETAILS OF BUILDING STANDARD CIRCUITING AIR CONDITIONING, DUCT WORK, AIR SUPPLY DIFFUSERS, AIR RETURN GRILLES, THERMOSTATS, SMOKE DETECTORS, ETC., SEE ORIGINAL BUILDING MECHANICAL DRAWINGS AND SPECIFICATIONS AND COORDINATE WITH BUILDING ENGINEER/OWNER.

7.13 SEE MECHANICAL ENGINEER'S DRAWINGS FOR THERMOSTAT LOCATIONS. GENERAL CONTRACTOR SHALL NOT INSTALL THERMOSTATS WITHOUT APPROVAL OF LOCATIONS FROM THE ARCHITECT. MOUNT ALL THERMOSTATS 42" A.F.F. NEXT TO LIGHT SWITCH. (U.N.O.).

8.0 PLUMBING

8.1 THE PLUMBING SUBCONTRACTOR SHALL SUPPLY AND INSTALL ALL PLUMBING ROUGH-INS, FIXTURES AND ACCESSORIES AS SHOWN OR IMPLIED ON CONSTRUCTION DRAWINGS, AND PER CODE.

8.2 THE PLUMBING SUBCONTRACTOR SHALL SUBMIT CUTS OF ALL NEW FIXTURES, FITTINGS AND ACCESSORIES TO ARCHITECT AND PLUMBING ENGINEER FOR REVIEW PRIOR TO PLACING ORDER.

8.3 THE PLUMBING SUBCONTRACTOR SHALL COORDINATE HIS WORK WITH MANUFACTURER'S SPECIFICATIONS AND WITH ALL OF THE OTHER TRADES.

8.4 FURNISH ALL VALVES AS INDICATED ON THE DRAWINGS, OR AS MAY BE REQUIRED FOR THE PROPER CONTROL OF THE VARIOUS APPARATUS AND PIPELINES INSTALLED UNDER THIS SECTION SO THAT ANY FIXTURE LINES OR PIECE OF APPARATUS MAY BE CUT OFF FOR REPAIR WITHOUT INTERFERENCE OR INTERRUPTION OF THE SERVICE TO THE REST OF THE BUILDING.

8.5 BEFORE BEING COVERED UP OR BUILT-IN, PIPING SHALL BE TESTED AS REQUIRED BY THE AUTHORITIES HAVING JURISDICTION.

8.6 HOT WATER AND DRAIN PIPES UNDER LAVATORIES AND SINKS SHALL BE INSULATED OR OTHERWISE COVERED.

9.0 CABINET WORK

9.1 REFERENCE FINISH PLANS AND DETAILS FOR MILLWORK FINISH AND MATERIAL QUALITY SPECIFICATIONS TO MEET OR EXCEED AWI STANDARDS.

9.2 THE GENERAL CONTRACTOR SHALL CLOSELY COORDINATE HIS WORK WITH THAT OF THE CABINET SUBCONTRACTOR.

9.3 ALL "INSTALLED" CABINETRY SHALL COMPLY WITH ALL LOCAL APPLICABLE BUILDING CODES, REGULATIONS, ORDINANCES AND ADA.

9.4 ALL "INSTALLED" CABINETS SHALL BE SCRIBED TO WALL OR CEILING.

9.5 THE CABINET CONTRACTOR SHALL SUBMIT THREE (3) SETS OF SHOP DRAWINGS AND FINISH SAMPLES TO THE ARCHITECT, AS REQUESTED IN THE DRAWINGS AND SPECIFICATIONS, FOR REVIEW.

9.6 THE CABINET CONTRACTOR SHALL CHECK AND FIELD VERIFY ALL DIMENSIONS AND CONDITIONS AT JOB SITE. ALL DISCREPANCIES BETWEEN THE ARCHITECT AND EXISTING CONDITIONS ARE TO BE IMMEDIATELY BROUGHT TO THE ATTENTION OF THE ARCHITECT FOR CLARIFICATION PRIOR TO THE COMMENCEMENT OF WORK.

9.7 ALL FINISHED WORK SHALL, AS FAR AS PRACTICAL, BE ASSEMBLED AND FINISHED IN THE SHOP AND DELIVERED TO THE BUILDING READY TO ERECT IN PLACE.

9.8 ALL THE WORK SHALL BE FABRICATED, ASSEMBLED, FINISHED AND ERECTED TO MEET WIC "STANDARD" GRADE FOR PLASTIC LAMINATE AND "PREMIUM" GRADE FOR ALL WOOD.

9.9 WHERE FILES ARE SHOWN AS BEING SET INTO CABINETWORK, THE CABINET CONTRACTOR SHALL SET AND BOLT ALL FILES TOGETHER.

9.10 ALL MILLWORK SHOP DRAWINGS ARE TO CALL OUT ALL MATERIALS AND FINISHES. ALL JOINTS, CORNERS, EDGES ARE TO BE DETAILED IN INDIVIDUAL DETAILS. ALL DIMENSIONS CRITICAL, OR OTHERWISE ARE TO BE CALLED OUT ON THE SHOP DRAWINGS. ARCHITECT WILL NOT REVIEW DRAWINGS, WHICH ARE INCOMPLETE OR SHOW MINIMAL REQUIRED DETAILING AND INFORMATION.

9.11 FILE DRAWERS REQUIRED ARE TO BE COMPLETE WITH FILE HANGERS TO ACCOMMODATE LEGAL AND LETTER SIZE FILE OPTIONS. DRAWER DEPTH TO BE ADJUSTED TO ALLOW FOR ADEQUATE CLEARANCE OF FILE FOLDER TABS.

9.12 SPECIFIED GROMMETS TO BE FIELD DRILLED AS REQUIRED TO ACCESS ELECTRICAL OUTLETS. SEE ELEVATIONS FOR LOCATION AND QUANTITY. GROMMETS TO BE LOCATED AT BACK OF SURFACE, CLOSE TO WALL, TYPICAL. SIZE TO BE 3-" TYPICAL. PULLS TO BE AS SPECIFIED ON ELEVATIONS. COLOR TO BE AS SPECIFIED ON ELEVATIONS.

9.13 SEE VARIOUS ELEVATIONS FOR MISCELLANEOUS HARDWARE AND FINISH SPECIFICATIONS.

9.14 U.N.O., BASE OF MILLWORK IS TO BE FINISHED WITH MATERIAL TO MATCH CABINETRY. PLASTIC LAMINATE OVER 3/4" PLYWOOD FRAMING, U.O.N.

9.15 HINGES ARE TO BE "SOSS" CONCEALED HINGES GS OVERLAY 1006 (OR EQUAL).

9.16 COORDINATION OF MILLWORK, STONE, OR OTHER SPECIALTIES CONTRACTORS IS THE RESPONSIBILITY OF THE GENERAL CONTRACTOR.

9.17 MILLWORK CONTRACTOR TO PROVIDE ALL NECESSARY CUT- OUTS FOR PLUMBING, ELECTRICAL AND ALL OTHER REQUIRED COORDINATION WITH OTHER TRADES. WHERE ELECTRICAL WORK IS SPECIFIED, ALL LAMPS, FIXTURES, OUTLET, SWITCHES, PLUG MOLDS, ETC. ARE TO BE PROVIDED BY CABINET CONTRACTOR OR COORDINATED WITH ELECTRICAL CONTRACTOR.

9.18 FULLY CONCEALED CABINET INTERIORS TO BE "MELAMINE"; WHITE AT PLASTIC LAMINATE AND BLACK AT WOOD VENEER CABINETS, UNLESS OTHERWISE NOTED.

9.19 COMPLETION OF WORK WILL INCLUDE CLEAN-UP AND REMOVAL OF ALL EXTRANEOUS ARTICLES AND DEBRIS GENERATED BY WORK. ALL MILLWORK TO BE CHECKED FOR PROPER MECHANICAL OPERATION.

9.20 ALL MILLWORK TO BE ATTACHED TO WALLS OR STRUCTURE AS REQUIRED FOR STABLE INSTALLATION.

9.21 CONTRACTOR TO SUBMIT ALL SHOP DRAWINGS, FINISH, DOOR AND HARDWARE SCHEDULES, SAMPLES AND CUT SHEETS FOR APPROVAL PRIOR TO START OF WORK.

9.22 ALL PAINTED WOOD SURFACES TO BE PROPERLY SEALED, SANDED AND SHOP PRIMED TO RECEIVE FINISH COAT

9.23 MILLWORK CONTRACTOR TO SUBMIT WOOD, PAINT AND/OR STAIN SAMPLES AND FINISHES FOR APPROVAL BY H.H.D.A. PRIOR TO FABRICATION. WOOD SPECIES SPECIFIED SHALL BE SUBMITTED WITH SPECIFIED FINISH.

9.24 ALL PLASTIC LAMINATE SHEETS ARE TO BE PROPERLY BACKED TO PREVENT WARPAGE OF THE SUBSTRATE.

9.25 ALL WOOD VENEER AND PLASTIC LAMINATE PANELS OR SHELVES ARE TO HAVE GRAIN RUNNING PER ELEVATIONS. ALL EXPOSED EDGES TO BE BANDED WITH MATCHING MATERIAL.

9.26 GENERAL CONTRACTOR TO PROVIDE AND INSTALL WALL BACKING. 16 GA. GALV. MET 4-" WIDE COVERING MINIMUM THREE STUDS AND SCREWED TO STUDS FOR ALL MILLWORK, TOILET ACCESSORIES, HANGING WALL EQUIPMENT, ETC. VERIFY LOCATIONS WITH MILLWORK CONTRACTOR.

9.27 ALL DRAWERS ARE TO BE FULL DEPTH COMPLETE WITH FULL EXTENSION DRAWER SLIDES RATED 50 LBS. WITH ROLLING BALLS, STEEL ROLLERS AND SELF-LUBRICATING BEARINGS.

9.28 FOR ADJUSTABLE SHELVING PROVIDE EUROPEAN STYLE, 5MM HOLES, 32MM ON CENTER WITH 5MM SHELF PINS, UNLESS NOTED OTHERWISE.

10.0 DOORS, FRAMES, AND HARDWARE

10.1 THE GENERAL CONTRACTOR SHALL PROVIDE AND INSTALL REQUIRED DOOR AND FRAME ASSEMBLIES AS SHOWN ON THE DRAWINGS, UNLESS OTHERWISE NOTED.

10.2 DETAILED DOOR AND HARDWARE SCHEDULES AND CUT SHEETS SHALL BE SUBMITTED TO ARCHITECT FOR REVIEW. FABRICATION OF MATERIAL SHALL NOT BE COMMENCED UNTIL SUCH REVIEW HAS BEEN COMPLETE AND RETURNED.

10.3 ALL EXISTING/ RELOCATED AND NEW DOOR ASSEMBLIES SHALL MEET ALL CURRENT TITLE 24 AND ADA ACCESSIBILITY REQUIREMENTS. MODIFY AND PROVIDE NEW AS NECESSARY FOR COMPLETE ASSEMBLY.

10.4 GENERAL CONTRACTOR IS RESPONSIBLE TO PROVIDE COMPLIANCE WITH LOCAL APPLICABLE CODES WITH RESPECT TO FIRE RATING OF DOORS, FRAMES, AND RELATED HARDWARE. NOTIFY THE ARCHITECT OF ANY DISCREPANCIES BETWEEN CODES AND SPECIFICATIONS.

10.5 GENERAL CONTRACTOR TO PROVIDE AND INSTALL ALL DOORS, FRAMES AND RELATED HARDWARE, UNLESS NOTED OTHERWISE.

10.6 CONTRACTOR RESPONSIBLE FOR DOOR INVENTORY. REUSE MAXIMUM NUMBER OF DOORS FROM DEMOLITION. PRIOR TO ORDERING NEW DOOR ASSEMBLIES, CONTRACTOR TO VERIFY QUANTITY OF DOOR AVAILABLE FOR REUSE. RELOCATE DOOR ASSEMBLIES WHERE POSSIBLE. TOUCH UP EXISTING DOORS FOR BEST POSSIBLE APPEARANCE WHERE APPLIES. IF RELOCATED DOORS ARE NOT AVAILABLE, ORDER NEW PER TYPE LISTED. REVIEW BUILDING STOCK FOR AVAILABILITY.

10.7 WHEN APPLICABLE, GENERAL CONTRACTOR TO BE RESPONSIBLE FOR PROVIDING KEYING. CONTRACTOR TO VERIFY THE BUILDING KEYWAY SYSTEM AND COORDINATE REQUIREMENTS WITH BUILDING OWNER AND TENANT. ALL LOCKSETS ARE TO BE KEYED SEPARATELY WITH MASTER KEY PROVIDED, UNLESS NOTED OTHERWISE. GENERAL CONTRACTOR SHALL SUBMIT A DETAILED KEYING SCHEDULE AND FURNISH HARDWARE SAMPLES AT THE REQUEST OF THE ARCHITECT.

10.8 AT ANY FIRE RATED DOORS REQUIRED TO HAVE ACCESS CONTROL, OR MAGNETIC HOLD OPEN DEVICES COORDINATE INSTALLATION WITH FIRE ALARM AND SMOKE DETECTION SYSTEMS INTERFACE WIRING REQUIREMENTS.

10.9 AT ANY DOORS REQUIRED TO HAVE ACCESS CONTROL, COORDINATE WITH TENANT SECURITY VENDOR AND ELECTRICIAN FOR SECURITY ACCESSORIES. DOORS WITH SECURITY SYSTEM SHALL HAVE BUILDING STANDARD LEVER AND ELECTRIC COMPONENTS COMPATIBLE WITH BUILDING. PROVIDE KEY OVERRIDE FOR BUILDING ENGINEER/OWNER ACCESS. AT EXISTING DOOR ASSEMBLIES MODIFY OR PROVIDE NEW AS REQUIRED.

10.10 CONTRACTOR TO VERIFY FRAME SIZE REQUIRED DUE TO STUD SIZE REQUIREMENT, AS NOTED IN PARTITION PLAN.

10.11 PROVIDE DOOR, FRAME AND HARDWARE SUBMITTALS FOR REVIEW BEFORE ORDER PLACEMENT. PROVIDE STAIN SUBMITTAL ON SPECIFIED WOOD SPECIES FOR APPROVAL.

10.12 ALL EXISTING DOOR ASSEMBLIES TO BE VERIFIED. PROVIDE MISSING OR COMPLIANT HARDWARE AS REQUIRED. REFER TO DOOR SCHEDULE.

10.13 U.N.O. AT NEW DOOR ASSEMBLIES: ALL FRAMES TO MATCH EXISTING.

10.14 U.N.O. SELF-CLOSING DEVICES TO BE BUILDING STANDARD.

10.15 ALL EXISTING DOORS COMPLY WITH RATING REQUIREMENTS, 20 MINUTE ON RATED CORRIDOR, AND LEVER HARDWARE, U.O.N. ALL DOORS MEET OR EXCEED MIN. SIZE REQUIREMENT OF 3'-0" X 6'-8".

10.16 MAXIMUM EFFORT TO OPERATE DOORS SHALL NOT EXCEED 5 POUNDS FOR EXTERIOR AND INTERIOR DOORS.

10.17 ALL DOORS SHALL BE OPERABLE FROM THE INSIDE WITHOUT THE USE OF KEY OR ANY SPECIAL KNOWLEDGE OR EFFORT.

10.18 ALL DOORS TO RECEIVE APPROPRIATE BUILDING STANDARD DOOR STOPS. ALL FLOOR-MOUNTED STOPS ARE TO BE INSTALLED AFTER THE INSTALLATION OF THE FINISHED FLOOR MATERIAL.

10.19 THE GENERAL CONTRACTOR SHALL UNDERCUT DOORS AS REQUIRED TO CLEAR FLOORING MATERIAL BY 1/4". ALL RATED DOORS, IF ANY, SHALL BE ORDERED SO AS TO CLEAR FLOORING MATERIAL BY 1/4".

10.20 PROVIDE PAIR OF DOORS WITH APPLICABLE ASTRAGALS, AUTOMATIC FLUSH BOLTS, SELF-CLOSERS AND COORDINATORS.

10.21 DOORS AND FRAMES THAT ARE PART OF 20-MINUTE FIRE ASSEMBLY SHALL HAVE SELF CLOSERS OR AUTOMATIC CLOSERS WITH SMOKE DETECTORS AND SMOKE SEALS.

11.0 GENERAL FINISHES

11.1 ALTERNATES TO SPECIFIED FINISHES SHALL NOT BE ACCEPTED WITHOUT PRIOR WRITTEN CONSENT OF THE ARCHITECT.

11.2 ALL FLOOR AND WALL FINISHES SUPPLIED AND INSTALLED BY CONTRACTOR UNLESS NOTED OTHERWISE.

11.3 CONTRACTOR TO PROVIDE MAINTENANCE SPECIFICATIONS AND RECOMMENDATIONS, AND MATERIAL AND LABOR WARRANTIES TO TENANT/OWNER AT PROJECT COMPLETION.

11.4 ALL SUBSTRATES SHALL BE CLEANED AND PREPARED IN ACCORDANCE WITH MANUFACTURER'S RECOMMENDATIONS. CONTRACTOR TO INCLUDE ALL NECESSARY TESTING (MOISTURE, MOLD, ASBESTOS ETC.) AS REQUIRED INSTALL NEW FINISHES PER MANUFACTURERS RECOMMENDATIONS AND MAINTAIN PRODUCT WARRANTIES.

11.5 THE INTERIOR FINISHES SHALL COMPLY WITH **2019 I.B.C. CHAPTERS 803.1, 804.1, AND TABLE 803.9.** ALL DECORATIVE MATERIALS SHALL BE MAINTAINED IN A FLAME RETARDANT CONDITION. THE MAXIMUM FLAME SPREAD CLASS OF ALL FINISH MATERIALS SPECIFIED FOR INTERIOR WALLS AND CEILINGS DOES NOT EXCEED THAT SET FORTH IN **TABLE 803.9.**

11.6 FLOOR AND WALL COVERING IN CLOSETS SHALL BE THE SAME AS THAT OF THE SPACE INTO WHICH THE CLOSET DOORS OPEN, UNLESS OTHERWISE NOTED.

11.7 REFER TO BUILDING STANDARDS FOR ADDITIONAL INFORMATION.

12.0 WALL FINISHES

12.1 WALLS SHALL INCLUDE SURFACES FROM FLOOR TO CEILING, INCLUDING PILASTERS, FASCIAS, AND ALL VERTICAL SURFACES NOT INCLUDED IN CEILING, UNLESS OTHERWISE NOTED.

12.2 WALLCOVERING SUBCONTRACTOR TO REVIEW PERTINENT WALL PATCHING NOTES IN "SECTION 3.01, PATCHING AND CUTTING" ON THIS SHEET, AND ENSURE SURFACES ARE PROPERLY PREPPED PRIOR TO COMMENCING WORK.

12.3 11.3 THE GENERAL CONTRACTOR SHALL SUBMIT THREE SAMPLES (12"X12") OF EACH FINISH FOR REVIEW BY ARCHITECT. THIS INCLUDES, BUT IS NOT LIMITED TO ALL PAINT, WALLCOVERINGS, ETC.

12.4 ALL WALLS AND CEILINGS SHALL BE PROPERLY PREPARED, PATCHED, SANDED, ETC. UNEVENNESS IN EXISTING PARTITIONS SHALL BE SANDED OR CHIPPED AWAY AND SURFACES PATCHED TO INSURE A PERFECTLY EVEN SURFACE. PROVIDE A LEVEL 4 FINISH AND PROVIDE LEVEL 5 FINISH ONLY WHERE INDICATED ON PLAN.

12.5 ALL OPEN PORES IN WOOD SHELVING AND PAINTED DOORS SHALL BE FILLED AND SHALL RECEIVE PRIMING, SANDING AND TWO FULL COATS OF SEMI-GLOSS ENAMEL, FREE OF BRUSH MARKS, U.O.N.

12.6 THE CONTRACTOR SHALL, REMOVE ALL ELECTRICAL SWITCH PLATES AND OUTLET PLATES, SURFACE HARDWARE, ETC., PRIOR TO PAINTING, PROTECTING AND REPLACING SAME WHEN PAINTING HAS BEEN COMPLETED. HE SHALL REMOVE ALL PAINT FROM WHERE IT HAS SPILLED, SPLASHED OR SPLATTERED ON SURFACES, INCLUDING BUT NOT LIMITED TO LIGHT FIXTURES, DIFFUSERS, REGISTERS, ETC.

12.7 EXISTING LOOSE PAINT SHALL BE REMOVED AND THE SURFACE SANDED SMOOTH TO RECEIVE NEW FINISH.

12.8 THE CONTRACTOR SHALL USE A LATEX BASE PAINT IN COLORS AND FINISHES SELECTED BY ARCHITECT. PRIOR TO APPLICATION OF PAINT ALL SURFACES ARE TO BE PROPERLY PREPARED, TAPED, AND TEXTURED, AS REQUIRED FOR SMOOTH SURFACE. ALL SURFACES TO RECEIVE ONE (1) PRIMER COAT AND TWO (2) FINISH COATS OF PAINT IN COLOR SELECTED BY ARCHITECT. USE APPROPRIATE COLOR OF PRIMER TO AVOID "READ" THROUGH AT NEW WALL FINISH LOCATIONS.

12.9 ALL PAINTING BIDS HAVE TO INCLUDE REPAINTING WINDOW MULLIONS AND DOOR FRAMES AS NEEDED WHERE SPECIFIED, TYP.

12.10 U.N.O. ALL TELEPHONE BACKBOARD OR ELECTRICAL PANELS TO BE PAINTED. U.N.O. COLOR TO MATCH WALL COLOR. PAINT ALL ACCESS PLATES, PANEL BOXES, ETC. TO MATCH ADJACENT PAINTED SURFACE, UNLESS OTHER WISE NOTED.

12.11 THE GENERAL CONTRACTOR SHALL INSTALL WALLCOVERINGS AS PER MANUFACTURER'S INSTALLATION SPECIFICATIONS, WHERE DESIGNATED. ALL WALLCOVERINGS SHALL BE SMOOTH, WITH NO WRINKLES, BUBBLES OR LOOSE EDGES, ALL PASTE AND BRUSH MARKS SHALL BE THOROUGHLY REMOVED. WALLCOVERING ADJOINING WOOD OR METAL TRIM SHALL BE CUT STRAIGHT AND SQUARE. CONTRACTOR TO TEST HANG (3) PANELS OF ALL TYPES OF COVERINGS FOR REVIEW AND APPROVAL BY THE ARCHITECT PRIOR TO FULL INSTALLATION.

12.12 AT ANY WALLCOVERING INSTALLATION SCHEDULED TO MATCH ADJACENT EXISTING CONDITIONS, CONTRACTOR RESPONSIBLE FOR ADEQUATE PRODUCT INSTALLATION SO THAT CONSISTENT WALLCOVERING SHADING EXTENDS FROM CORNER TO CORNER.

12.13 U.O.N. IF NEW DOORS ARE NOT PRE-FINISHED, COORDINATE WITH DOOR CONTRACTOR AND PROVIDE SPECIFIED FINISH AT ALL DOORS.

12.14 U.N.O. ANY RELOCATED DOORS TO BE TOUCHED-UP, U.N.O. DOORS TO BE FINISHED AS SPECIFIED FOR "BEST POSSIBLE APPEARANCE".

12.15 THE CONTRACTOR SHALL EXAMINE ALL AREAS OF CONSTRUCTION AFTER COMPLETION OF WORK BY ALL TRADES (INCLUDING TELEPHONE INSTALLATION, FLOORING, ETC.) AND COMPLETE ALL NECESSARY "TOUCH-UP" PAINTING AND/OR PATCHING PRIOR TO SCHEDULING A PUNCHWALK.

12.16 REFER TO MILLWORK ELEVATIONS FOR PLASTIC LAMINATE, WOOD VENEER ETC.FINISH LOCATIONS.

12.17 IT IS THE INTENT OF THE DRAWINGS THAT ALL EXPOSED SURFACES RECEIVE FINISHES UNLESS SPECIFICALLY NOTED OTHERWISE ON THE DRAWINGS. ANY SURFACES WHICH DO NOT HAVE A SPECIFIC FINISH NOTED, OR ARE NOTED TO REMAIN UNFINISHED, SHALL BE BROUGHT TO THE ATTENTION OF THE ARCHITECT AND FINISHED PER ARCHITECT'S INSTRUCTIONS.

12.18 PROVIDE CLASS "C" FLAME SPREAD AND SMOKE DENSITY FOR WALL AND CEILING FINISHES.

13.0 FLOOR COVERING

13.1 FLOORING SUBCONTRACTOR TO REVIEW PERTINENT FLOOR PATCHING NOTES IN "SECTION 3.01, PATCHING & CUTTING" ON THIS SHEET, AND ENSURE SURFACES ARE PROPERLY PREPPED PRIOR TO COMMENCING WORK.

13.2 FLOOR PREPARATION IS THE RESPONSIBILITY OF THE FLOOR SUBCONTRACTOR. CONTRACTOR SHALL FILL, SAND, AND LEVEL AS REQUIRED PRIOR TO INSTALLING FINISH MATERIAL. ALL SELF LEVELING COMPOUNDS USED SHALL BE CEMENTITIOUS.

13.3 ALL NEW FLOORING IS TO BE PROVIDED AND INSTALLED BY GENERAL CONTRACTOR AND SHALL BE AS SPECIFIED ON CONSTRUCTION DOCUMENTS, UNLESS OTHERWISE NOTED.

13.4 TILE SHALL BE LAID IN SQUARE PATTERN WITH COURSES PARALLEL TO WALLS, UNLESS OTHERWISE INDICATED ON DRAWINGS. THE TILE SHALL BE SECURELY CEMENTED AND SHALL BE LAID WITH TIGHT JOINTS. THE ADHESIVE USED FOR CEMENTING TILE SHALL BE APPLIED FAR ENOUGH IN ADVANCE OF THE SETTING TO PERMIT THE ADHESIVE TO REACH ITS INITIAL SET, BUT NOT ITS FINAL SET. ALL STONE AND TILE FLOORING SHALL BE INSTALLED OVER CRACKED ISOLATION/WATERPROOFING MEMBRANE PER CTI STANDARDS. CONTRACTOR TO TEST SLAB FOR MOISTURE PRIOR TO INSTALLATION OF RESILIENT FLOORING, AND INSTALL PER MANUFACTURER'S INSTRUCTIONS.

13.5 SPACES BEING SURFACED SHALL BE CLOSED TO TRAFFIC AND OTHER WORK DURING THE LAYING OF FLOORING. STONE FLOORS SHALL BE COVERED AFTER INSTALLATION FOR PROTECTION.

13.6 ALL MASONRY WALLS AND DRYWALL PARTITIONS SHALL HAVE SPECIFIED STRAIGHT RESILIENT BASE IN CUT PILE CARPETED AREAS AND COVE RESILIENT BASE IN LOOP PILE CARPET AND RESILIENT AREAS, UNLESS OTHERWISE NOTED.

13.7 UPON COMPLETION, ALL WORK SHALL BE CLEANED BY THE CONTRACTOR, REMOVING ALL SPOTS OF ADHESIVE AND SURFACE STAINS AND ALL SCRAPS, CARTONS AND CONTAINERS SHALL BE REMOVED FROM THE BUILDING.

13.8 WHEN SPECIFICALLY DIRECTED, AFTER CLEANING, THE GENERAL CONTRACTOR SHALL GIVE RESILIENT TILE FLOOR TWO (2) APPLICATIONS OF AN APPROVED NON-SLIP WAX, WHICH IS TO BE THOROUGHLY MACHINE BUFFED AND LEFT IN CONDITION SATISFACTORY TO OWNER. STONE/TILE & GROUT TO BE SEALED AS REQUIRED PER MANUFACTURER'S RECOMMENDATIONS AND BASE TO BE CAULKED WITH CLEAR SILICONE.

13.9 THE GENERAL CONTRACTOR SHALL PROVIDE AND MAINTAIN ADEQUATE PROTECTION FOR ALL FLOORING WORK FOR THE DURATION OF THE CONTRACT, AND REMOVE ALL PROTECTION PRIOR TO PUNCHLIST. ONLY OWNER APPROVED CARPET PROTECTION SHALL BE USED, ENSURING NO RESIDUE WILL REMAIN UPON REMOVAL.

13.10 STONE, WOOD AND TILE FLOORING CONTRACTORS TO SUBMIT ACTUAL DIMENSIONED LAYOUT PLAN FOR ARCHITECT'S REVIEW PRIOR TO INSTALLATION.

13.11 CONTRACTOR TO ENSURE THAT EXISTING CONCRETE FLOOR SLAB TO BE EVEN AND THAT SURFACE VARYING NO MORE THAN 1/4" IN 10'-0". FLOAT FLOOR AS NECESSARY. EACH SIDE OF THE DOOR SHALL BE LEVEL 5'-0" X 5'-0".

13.12 AT ALL CARPET TO VCT TRANSITIONS, PROVIDE RUBBER TRANSITION STRIP TO MATCH RUBBER BASE. ENSURE NO "TRIPPING HAZARDS." REFER TO FINISH LEGEND FOR SPEC.

13.13 ALL STONE TO CARPET TRANSITIONS TO BE STAINLESS STEEL SCHLUTER STRIP. REFER TO FINISH LEGEND FOR SPECIFICATION.

13.14 U.N.O. AT TRANSITION BETWEEN DIRECT GLUE CARPET AND CARPET OVER PAD, FLOAT FLOOR AS REQUIRED TO PROVIDE A SMOOTH AND EVEN TRANSITION. FLOOR FLOAT TO BE UNDETECTABLE.

13.15 U.N.O. AT ANY VCT INSTALLATION, A FULL TILE SHOULD BE INSTALLED AT CENTERLINE OF A DOOR OPENING.

13.16 WHEN NEW FLOOR FINISH IS SCHEDULED TO BE INSTALLED AT ROOMS WITH KITCHEN CABINETS, NEW FLOORING TO BE INSTALLED BELOW SINK CABINET.

13.17 U.N.O. ANY VCT FLOORING SCHEDULED TO REMAIN IS TO BE STRIPPED, CLEANED, SEALED/POLISHED AND BUFFED PER MANUFACTURERS RECOMMENDATIONS.

13.18 CONTRACTOR TO COORDINATE WITH CARPET VENDOR TO ENSURE THAT EXISTING FLOOR HAS BEEN PREPARED PER MANUFACTURER'S RECOMMENDATIONS AND THE LATEST GUIDELINES OF THE CARPET AND RUG INSTITUTE PRIOR TO FULL INSTALLATION. IF SUBSTRATE IS DAMAGED CONTRACTOR TO QUALIFY BEST METHOD TO PREPARE FLOORING TO RECEIVE NEW FINISH. NOTICEABLE DEFECTS THOUGH NEW WORK, SHALL RESULT REINSTALLATION OF FINISH TO SATISFACTION OF END USER.

13.19 ALL CARPET IS TO BE FROM SAME DYE LOT. SUBMIT A SEAMING DIAGRAM TO ARCHITECT FOR REVIEW & APPROVAL BEFORE ORDER PLACEMENT.

13.20 CARPET CONTRACTOR TO PROVIDE SEAMING DIAGRAM AND THREE (3) 12 X 12 SAMPLES TO ARCHITECT FOR REVIEW PRIOR TO INSTALLATION OF ALL SPECIFIED FLOOR COVERINGS AND BASE MATERIALS.

13.21 U.N.O AT ANY OCCUPIED SPACE SCHEDULED TO RECEIVED NEW FLOOR FINISH, CONTRACTOR SHALL BE RESPONSIBLE TO MOVE EXISTING FURNITURE TO INSTALL NEW CARPET. COORDINATE WITH BUILDING MANAGEMENT/CONSTRUCTION MANAGER/OWNER FOR AFTER-HOURS SCHEDULE.

13.22 AT ANY BASE INSTALLATION TO MATCH EXISTING, BASE TO BE CONSISTENT FOR COLOR AND SEAMLESS APPEARANCE. ALL RUBBER/VINYL BASE IS TO BE CONTINUOUS ROLLED GOODS, U.N.O.

13.23 WHERE WOOD BASE EXISTS IN OFFICES AND NEW FINISHES TO BE INSTALLED, WOOD BASE SHOULD BE REMOVED AND REINSTALLED. CONTRACTOR TO INCLUDE IN THE BID TO PROVIDE A NEW BASE SUPPLEMENTED TO MATCH EXISTING CONDITIONS IF REQUIRED.

13.24 CONTRACTOR TO COORDINATE ALL FLOORING CONTRACTORS INVOLVED TO ASSURE FLUSH INSTALLATION OF VARYING FLOOR MATERIALS USED. ALL TRANSITION METHODS TO BE APPROVED BY ARCHITECT.

13.25 ALL FLOOR SURFACES TO BE PREPPED AS REQUIRED BY MANUFACTURER'S INSTRUCTIONS.

13.26 FLOOR COVERING MATERIALS SHALL COMPLY WITH ASTM E 648, AND HAVING A SMOKE DENSITY RATING OF LESS THAN 450 PER ASTM E 84. CBC 804.4.1.

14.0 WINDOW COVERINGS

14.1 ALL WINDOW COVERINGS SHALL BE INSPECTED BY THE CONTRACTOR AND ALL INOPERABLE OR DAMAGED CONDITIONS SHALL BE REPAIRED OR REPLACED.

14.2 ALL EXISTING WINDOW COVERINGS SHALL BE PROTECTED DURING CONSTRUCTION PERIOD.

13.3 PROVIDE NEW BUILDING STANDARD WINDOW COVERINGS AT ALL EXTERIOR WINDOWS IN FIRST GENERATION SPACES.

16.0 CLEANING

16.1 THE "EXISTING TO REMAIN", "EXISTING TO BE RELOCATED" OR "NEW" ITEMS INSTALLED BY THE GENERAL CONTRACTOR, IN ADDITION TO BEING AMPLY PROTECTED THROUGHOUT THE PERIOD OF CONSTRUCTION SHALL BE THOROUGHLY CLEANED TO THE SATISFACTION OF OWNER AND TENANT PRIOR TO BEING TURNED OVER TO THE TENANT.

17.0 SUBMITTAL PROCEDURES

17.1 GENERAL CONTRACTOR SHALL SUBMIT ALL REQUESTED FABRICATION SHOP DRAWINGS, SAMPLES AND FIXTURE CUTS TO ARCHITECT FOR REVIEW. THREE (3) SETS OF REPRODUCIBLE PAPER COPIES SHALL BE PROVIDED. ALL SHOP DRAWINGS AND CUT SHEETS SIGNED "REVIEWED" SHALL SUPERSEDE ORIGINAL DRAWINGS IN DESIGN APPEARANCE ONLY. SUBCONTRACTORS SHALL ASSUME RESPONSIBILITY FOR ERRORS IN THEIR DRAWINGS.

17.2 GENERAL CONTRACTOR SHALL REVIEW SUBCONTRACTOR'S SUBMITTED DRAWINGS AND DATA, VERIFY FIELD MEASUREMENTS, APPLY REVIEW STAMP AND SUBMIT TO ARCHITECT PROMPTLY.

17.3 GENERAL CONTRACTOR SHALL INDICATE ON REVIEW STAMP THAT THE CONTRACTOR HAS REVIEWED SUBCONTRACTOR'S SUBMITTAL FOR CONFORMANCE TO THE SPECIFIED PRODUCT.

17.4 GENERAL CONTRACTOR SHALL DISAPPROVE AND RETURN TO SUBCONTRACTOR ANY SUBMITTALS NOT MEETING THE REQUIREMENTS OF THE CONTRACT DOCUMENTS. GENERAL CONTRACTOR SHALL MAINTAIN AN UP-TO-DATE SUBMITTAL LOG, AND DISTRIBUTE THE LOG WEEKLY.

17.5 THE ARCHITECT WILL REVIEW, AND EITHER ACCEPT OR REJECT, WITH REASONABLE PROMPTNESS AND AS OUTLINED IN THE ACCEPTED SUBMITTAL SCHEDULE, DATA AND DRAWINGS SUBMITTED BY THE CONTRACTOR. THE ARCHITECT WILL REVIEW SUBMITTALS FOR CONFORMANCE WITH THE INTENT OF THE DESIGN, AND FOR COMPLIANCE WITH SPECIFIC AND RELEVANT REQUIREMENTS OF THE CONTRACT DOCUMENTS.

17.6 THE ARCHITECT WILL REJECT AND RETURN TO THE CONTRACTOR, SHOP DRAWINGS AND PRODUCT LITERATURE SUBMITTED WITHOUT THE CONTRACTOR'S REVIEW STAMP AND/OR NOT THOROUGHLY REVIEWED BY CONTRACTOR PRIOR TO SUBMITTAL.

17.7 THE ARCHITECT IS NOT RESPONSIBLE FOR DELAYS CAUSED BY REJECTION OF SHOP DRAWINGS SUBMITTED BY THE CONTRACTOR.

17.8 REVIEW WILL NOT RELIEVE THE CONTRACTOR FROM RESPONSIBILITY FOR ERRORS.

17.9 REVIEW OF SUBMITTALS BY THE ARCHITECT SHALL NOT BE CONSTRUED AS AUTHORIZING CHANGES IN THE CONTRACT SUM OR CONTRACT TIME, NOR SHALL IT BE CONSTRUED AS RELIEVING THE CONTRACTOR OF HIS RESPONSIBILITY FOR COORDINATION OF WORK WITH OTHER TRADES, OR INTERPRETED AS APPROVING QUANTITIES AND DIMENSIONS.

17.10 THE ARCHITECT'S REVIEW OF SUBMITTALS OR DATA SHALL NOT RELIEVE THE CONTRACTOR FROM RESPONSIBILITY FOR DEVIATIONS FROM CONTRACT DRAWINGS OR SPECIFICATIONS UNLESS THE CONTRACTOR HAS CALLED THE ARCHITECT'S AND OWNER'S ATTENTION TO SUCH DEVIATIONS AND SECURED WRITTEN ACCEPTANCE, NOR SHALL IT RELIEVE HIM OF RESPONSIBILITY FOR ERRORS IN SHOP DRAWINGS OR OTHER DATA.

18.0 SUBSTITUION PROCEDURES

18.1 THE GENERAL CONTRACTOR SHALL SUBMIT HIS WRITTEN REQUEST FOR A PROPOSED SUBSTITUTION AND ALL DATA SUBSTANTIATING HIS REQUEST. THE GENERAL CONTRACTOR SHALL INCLUDE SAMPLES OF THE PROPOSED SUBSTITUTION WITH HIS REQUEST

18.2 IT SHALL BE THE RESPONSIBILITY OF THE GENERAL CONTRACTOR TO SUBMIT COMPLETE INFORMATION TO THE ARCHITECT SO THAT PROPER EVALUATION CAN BE MADE. THE BURDEN OF PROOF OF EQUIVALENCY OF THE SUBSTITUTION ITEM SHALL BE ON THE GENERAL CONTRACTOR. ACCEPTANCE OF SUCH SUBSTITUTIONS IS ENTIRELY AT THE DISCRETION OF THE ARCHITECT AND THE BUILDING OWNER. ALL MATERIALS AND/OR ITEMS OF MANUFACTURER, WHICH THE GENERAL CONTRACTOR PROPOSES TO SUBSTITUTE FOR THOSE SPECIFIED MUST BE REVIEWED BY THE ARCHITECT BEFORE THEY MAY BE ORDERED. SUBSTITUTIONS SHALL BE SUBMITTED PRIOR TO CONSTRUCTION.

18.3 NO SUBSTITUTION WILL BE REVIEWED FOR ANY MATERIALS AND/OR ITEM OF MANUFACTURER CALLED FOR IN THE CONSTRUCTION DOCUMENTS WHICH IS NOT OF EQUAL QUALITY AND PERFORMANCE AND WHICH DOES NOT POSSESS EQUIVALENT DESIGN AND/OR COLOR CHARACTERISTICS TO THOSE OF SPECIFIED MATERIAL OR ITEM.

18.4 IF, IN THE OPINION OF THE ARCHITECT, BUILDING OWNER OR END USER, THE PROPOSED SUBSTITUTION IS NOT EQUIVALENT OR BETTER IN EVERY RESPECT TO THAT SO INDICATED OR SPECIFIED, OR WAS NOT SUBMITTED FOR REVIEW IN THE MANNER OUTLINED ABOVE, THE GENERAL CONTRACTOR SHALL FURNISH THE SPECIFIED MATERIALS. THESE MATERIALS SHALL BE SUPPLIED AT NO ADDITIONAL COST TO THE BUILDING OWNER/END USER.

LG Energy Solution

HACE INC. 2102 Business Center Dr., Irvine, CA 92612
T.949.892.9732 E.hseo@haceinc.com

REGISTERED ARCHITECT
CERTIFICATE NO.
75220
HYUNG JIN
SEO
ARIZONA, U.S.A.
Dated 02/12/26
S. HyungJin
EXPIRES 03/31/28

LG Energy Solution ESS AZ.
Tenant Improvement West 202 Logistics
555 and 675 N. 55th Ave.,
Phoenix, AZ 85043
Bldg. F: 675 N. 55th Ave.
Bldg. G: 555 N. 55th Ave.

Revision	Description	Date

Revision	Description	Date
-	CITY SUBMITTAL/100% BID SET	02/12/26

Key Plan N.T.S.

Date	Drawn By
Project Numbers 202601.05	Checked By

Sheet Title

SPECIFICATIONS

Sheet Number

A002



01 SITE PLAN

REF. SCALE : 1" = 40'-0"

LEGEND

- AREA 3 – DRIVE AISLE FOR STRADDLE CARRIER
- AREA 4 – REACH STACKER OPERATION
  CONTRACTOR TO PROVIDE PAINT MARKING IN ORANGE PER OSHA 1910.144(a)
- AREA 1 – OUTDOOR STORAGE
- AREA 2 – DRIVE AISLE FOR STRADDLE CARRIER AND REACH STACKER WITH ENCLOSURE

KEYNOTES

5. REMOVE EXISTING CONCRETE RAMP, AND PREP. FOR NEW PLATFORM (SEPARATE PERMIT)
6. 750 kW GENERATOR (SEPARATE PERMIT)
7. INSTALL 1" CONDUIT UNDERGROUND FOR POWER
1. INSTALL MIN. 4" CONDUIT UNDERGROUND FOR FUTURE DATA CENTER AND IDF
2. INSTALL 2" CONDUIT UNDERGROUND FOR DATA
3. INSTALL 1/2" CONDUIT UNDERGROUND FOR FUTURE WATER TEST
4. INSTALL 3/4" DIA. DOMESTIC WATER PIPE UNDERGROUND

LG Energy Solution

HACE INC, 2102 Business Center Dr.,
Irvine, CA 92612
T.949.892.9732 E. hseo@haceinc.com

REGISTERED ARCHITECT
CERTIFICATE NO.
75220
HYUNG JIN
SEO
Date Signed 02/12/26
ARIZONA, U.S.A.
EXPIRES 03/31/28

LG Energy Solution ESS AZ.
Tenant Improvement West 202 Logistics
555 and 675 N. 55th Ave.,
Phoenix, AZ 85043

Bldg. F: 675 N. 55th Ave.
Bldg. G: 555 N. 55th Ave.

Revision	Description	Date

Revision	Description	Date
-	CITY SUBMITTAL/100% BID SET	02/12/26

Key Plan N.T.S.

Date	Drawn By
Project Numbers 202601.05	Checked By

Sheet Title
SITE PLAN

Sheet Number
A101

GENERAL STRUCTURAL NOTES:

1. COORDINATION: THE CONTRACTOR SHALL VERIFY ALL DIMENSIONS AND CONDITIONS AT THE JOB SITE AND SHALL BE RESPONSIBLE FOR COORDINATION OF ALL WORK AND MATERIALS INCLUDING THOSE FURNISHED BY SUBCONTRACTORS.
2. DISCREPANCIES: THE CONTRACTOR SHALL INFORM THE ENGINEER IN WRITING, OF ANY DISCREPANCIES OR OMISSIONS NOTED ON THE DRAWINGS THAT DO NOT CONFORM TO CODES, RULES AND REGULATIONS. UPON RECEIPT OF SUCH INFORMATION, THE ENGINEER WILL SEND INSTRUCTIONS TO ALL CONCERNED. ANY SUCH DISCREPANCY, OMISSION, OR VARIATION NOT REPORTED SHALL BE THE RESPONSIBILITY OF THE CONTRACTOR.
3. TYPICAL DETAILS AND GENERAL STRUCTURAL NOTES SHALL APPLY, UNLESS SPECIFICALLY SHOWN OR NOTED OTHERWISE. CONSTRUCTION DETAILS NOT FULLY SHOWN OR NOTED SHALL BE SIMILAR TO DETAILS SHOWN FOR SIMILAR CONDITIONS. ALL CONSTRUCTION WORK SHALL COMPLY WITH ALL APPLICABLE BUILDING CODES, REGULATIONS AND SAFETY REQUIREMENTS.
4. TRADE NAMES: WHERE AN ITEM IS IDENTIFIED BY A TRADE NAME THE SUFFIX "OR APPROVED EQUIVALENT" SHALL BE IMPLIED UNLESS SPECIFICALLY NOTED OTHERWISE.
5. STANDARDS: EXCEPT WHERE MORE STRINGENT REQUIREMENTS ARE NOTED OR SHOWN IN THE PLANS OR SPECIFICATIONS, ALL PHASES OF WORK SHALL CONFORM TO THE MINIMUM STANDARDS OF THE ***2024 INTERNATIONAL BUILDING CODE (IBC).***
6. INSPECTION: WHEREVER SPECIAL AND/OR CONTINUOUS INSPECTION IS CALLED FOR IN THESE NOTES OR THE BUILDING CODES, SUCH INSPECTION SHALL BE PERFORMED BY A TESTING LABORATORY EMPLOYED BY THE OWNER. JOB SITE VISITS BY THE ENGINEER SHALL NOT CONSTITUTE AN OFFICIAL INSPECTION.
7. PRE-CONSTRUCTION MEETING: PRIOR TO THE COMMENCEMENT OF THE CONSTRUCTION, THE ARCHITECT SHALL CONDUCT A MEETING TO ESTABLISH SUBMITTAL ROUTES, SCHEDULES AND SERVICING REQUIREMENTS FOR THE CONSTRUCTION ADMINISTRATION OF THE PROJECT. REPRESENTATIVES FROM THE ENGINEER, TESTING LABORATORY*, BUILDING DEPARTMENT*, CONTRACTOR, AND OTHER DESIGN PROFESSIONALS AS MAY BE APPROPRIATE WILL ATTEND. (* IF NECESSARY).
8. OTHER TRADES: SEE ARCHITECTURAL AND CONSULTANT DRAWINGS FOR SIZE AND LOCATION OF PIPE, OTHER OPENINGS, ANCHOR BOLT REQUIREMENTS FOR EQUIPMENT AND OTHER DETAILS NOT SHOWN ON THESE STRUCTURAL DRAWINGS. ALL DIMENSIONS ARE TO BE CHECKED AND VERIFIED WITH THE ARCHITECTURAL DRAWINGS.
9. MATERIALS AND WORKMANSHIP: THE CONTRACTOR SHALL SUPPLY ALL LABOR, MATERIALS, EQUIPMENT AND SERVICES OF EVERY KIND, INCLUDING WATER AND POWER, NECESSARY FOR THE PROPER EXECUTION OF THE WORK SHOWN OR INDICATED ON THESE DRAWINGS. ALL MATERIAL SHALL BE NEW MATERIALS. SUBCONTRACTORS SHALL BE SKILLED IN THEIR TRADE.
10. MATERIALS AND WORKMANSHIP WARRANTY: THE CONTRACTOR SHALL REPLACE ANY DEFECTIVE MATERIALS AND CORRECT POOR WORKMANSHIP WITH NO ADDITIONAL COSTS TO THE OWNER, AND SHALL REMEDY ANY DEFECTS IN MATERIAL OR WORKMANSHIP WHICH APPEAR IN ONE YEAR FROM THE DATE OF COMPLETION OF THE PROJECT. THIS WARRANTY APPLIES TO THE WORK DONE BY THE SUBCONTRACTORS AS WELL AS THE WORK DONE BY THE EMPLOYEES OF THE CONTRACTOR.
11. SAFETY: THE CONTRACTOR SHALL ADEQUATELY PROTECT HIS WORK, ADJACENT PROPERTY AND THE PUBLIC, AND BE RESPONSIBLE FOR DAMAGE OR INJURY DUE TO HIS ACT OR NEGLECT.
12. SIDEWALK PROTECTION: PEDESTRIAN TRAFFIC SHALL BE PROTECTED AS SPECIFIED IN SECTION 3306 OF THE BUILDING CODE.
13. SHORING: IT SHALL BE THE CONTRACTOR'S SOLE RESPONSIBILITY TO DESIGN AND PROVIDE ADEQUATE SHORING, BRACING AND FORM-WORK, ETC., AS REQUIRED FOR THE PROTECTION OF LIFE AND PROPERTY DURING THE CONSTRUCTION OF THIS BUILDING.
14. EXCAVATION: THE CONTRACTOR SHALL BE SOLELY RESPONSIBLE FOR ALL EXCAVATION PROCEDURES INCLUDING LAGGING, SHORING, AND PROTECTION OF ADJACENT PROPERTY, STRUCTURES, STREETS AND UTILITIES IN ACCORDANCE WITH THE STANDARDS OF THE CITY OF NEWPORT BEACH AND WITH THE JOINING PROPERTY. THE PREMISES SHALL BE KEPT FROM ACCUMULATION OF WASTE MATERIALS, AND DEBRIS, AND AT THE END OF THE JOB THE CONTRACTOR SHALL REMOVE ALL RUBBISH, SURPLUS OF MATERIALS, AND TOOLS AND LEAVE THE BUILDING BROOM CLEAN.
15. SHOP DRAWINGS: SHOP DRAWINGS ARE AN AID FOR FIELD PLACEMENT AND ARE SUPERSEDED BY THE STRUCTURAL DRAWINGS. IT SHALL BE THE RESPONSIBILITY OF THE GENERAL CONTRACTOR TO MAKE CERTAIN CONSTRUCTION IS IN FULL AGREEMENT WITH THE LATEST CONSTRUCTION DOCUMENTS.
16. SHOP DRAWING CHECK: THE REVIEW OF SHOP DRAWINGS BY THE STRUCTURAL ENGINEER IS ONLY FOR GENERAL COMPLIANCE WITH THE STRUCTURAL DRAWINGS AND SPECIFICATIONS. THIS REVIEW DOES NOT GUARANTEE IN ANY WAY THAT THE SHOP DRAWINGS ARE CORRECT NOR DOES IT INFER THAT THEY SUPERSEDE THE STRUCTURAL DRAWINGS.
17. SUBSTITUTIONS: BEFORE SUBSTITUTIONS FOR ANY MATERIALS OR SYSTEMS SHOWN ON THE DRAWINGS OR CALLED OUT IN THE SPECIFICATIONS WILL BE CONSIDERED, THE PERSON PROPOSING THE SUBSTITUTION SHALL SUBMIT A WRITTEN LETTER TO THE STRUCTURAL ENGINEER STATING THE FOLLOWING:
    A. THE PROPOSER AGREES TO PAY THE ENGINEER FOR THE COST OF EVALUATING THE PROPOSED CHANGE.
    B. THE PROPOSER AGREES TO PAY THE ENGINEER FOR THE COST OF CHANGING THE DRAWINGS AND DETAILS SHOULD THIS BE REQUIRE BY THE BUILDING DEPARTMENT OR SHOULD THE ENGINEER DECIDE IT IS NECESSARY.
    C. THE NET SAVING SHALL BE PASSED ON TO THE OWNER SHOULD THE SUBSTITUTION BE APPROVED.
19. THE CONTRACTOR SHALL NOTIFY THE ARCHITECT AND STRUCTURAL ENGINEER WHERE A CONFLICT OR DISCREPANCY OCCURS BETWEEN THE STRUCTURAL DRAWINGS AND ANY OTHER PORTION OF THE CONTRACT DOCUMENTS OR EXISTING FIELD CONDITIONS. SUCH NOTIFICATION SHALL BE GIVEN IN DUE TIME SO AS NOT TO AFFECT THE CONSTRUCTION SCHEDULE. IN CASE OF A CONFLICT BETWEEN STRUCTURAL DRAWINGS AND SPECIFICATIONS THE MORE RESTRICTIVE CONDITION SHALL TAKE PRECEDENCE UNLESS WRITTEN APPROVAL HAS BEEN GIVEN FOR THE LEAST RESTRICTIVE. CONTRACTOR SHALL VERIFY ALL DIMENSIONS WITH ARCHITECTURAL PRIOR TO COMMENCING ANY WORK.

FOUNDATION NOTES:

1. DESIGN: FOUNDATION DESIGNED IN CONFORMANCE WITH THE RECOMMENDATIONS BY SPEEDIE AND ASSOCIATES
   REPORT NO(S). 210029SA
   DATED: MARCH 05, 2021
   SIGNED BY:KEITH R. GRAVEL
   PHONE # (602) 997-6391
   ADDRESS: 3331 EAST WOOD STREET, PHOENIX, AZ 85040
2. FOOTINGS: ALL FOOTINGS SHALL EXTEND A MINIMUM DEPTH BELOW FINISHED OR NATURAL GRADE INTO ACCEPTABLE GEOLOGICAL MATERIAL AS FOLLOWS UNLESS NOTED OTHERWISE.
   2.1. EXTERIOR FOOTINGS = 24"
   2.2. INTERIOR FOOTINGS = 24"
   2.3. FOUNDATION WALL FOOTINGS = 24"
3. FOUNDATION DESIGN SOIL VALUES
   ALLOWABLE BEARING PRESSURE = 1500 PSF
   ALLOWABLE PASSIVE PRESSURE = 250 PCF
   COEFFICIENT OF FRICTION = 0.25
   3.1. ALLOWABLE BEARING PRESSURE MAY BE INCREASED $\frac{1}{3}$ FOR WIND OR SEISMIC
   3.2. ALLOWABLE PASSIVE AND FRICTION MAY BE COMBINED 100% TO RESIST SLIDING
4. BACKFILL: PARTIAL BACKFILLING OF RETAINING WALLS MAY COMMENCE ONLY WITH WRITTEN DIRECTION FROM THE ENGINEER OF RECORD (EOR).

CONCRETE NOTES:

1. COMPRESSIVE STRENGTH: THE MINIMUM ULTIMATE COMPRESSIVE STRENGTH OF ALL CONCRETE SHALL BE 4500 PSI MIN AT 28 DAYS, UNLESS NOTED OTHERWISE. REFER TO PLANS AND TABLE BELOW FOR THE DESIGN STRENGTH OF CONCRETE FOR SPECIFIC STRUCTURAL ELEMENTS. DESIGN OF MIXES SHALL BE BY AN APPROVED TESTING LABORATORY AND SIGNED BY A REGISTERED ENGINEER.
   1.1. SLAB ON GRADE — f'_c = 6000 PSI MIN
   1.2. CONVENTIONAL FOOTINGS — f'_c = 4500 PSI MIN
   1.3. GRADE BEAMS — f'_c = 4500 PSI MIN
   1.4. ALL CONCRETE IN CONTACT WITH SOIL — f'_c = 4500 PSI MIN
2. WEIGHT: ALL CONCRETE SHALL BE "NORMAL WEIGHT" UNLESS NOTED OTHERWISE.
3. CONCRETE SHALL HAVE A MAXIMUM WATER-CEMENTITIOUS MATERIAL RATIO, BY WEIGHT, OF 0.45
4. CEMENT: CEMENT SHALL CONFORM TO THE ASTM C150-09 TYPE V.
5. AGGREGATE: AGGREGATE SHALL CONFORM TO ASTM C33-08.
6. SPECIAL INSPECTIONS: SEE THE SPECIAL INSPECTION TABLE AND THE SPECIAL INSPECTION NOTE SHEET FOR ANY INSPECTIONS REQUIRED TO BE MADE.
7. CONCRETE PLACEMENT AND QUALITY: SHALL CONFORM TO APPLICABLE RECOMMENDATIONS OF ACI SP-15. A COPY OF SP-15 SHALL BE AVAILABLE AT CONSTRUCTION SITE DURING THE PROJECT.
8. DEBRIS: REMOVE ALL DEBRIS FROM FORMS BEFORE PLACING OF CONCRETE.
9. DOWELING: ALL WALLS AND COLUMNS SHALL BE DOWELED INTO FOOTINGS, WALLS, BEAMS, OR SLABS AS SHOWN OR NOTED ON THE DRAWINGS.
10. SPLICES: VERTICAL WALL BARS SHALL BE SPLICED AT OR NEAR FLOOR LINES. SPLICE BARS IN SPANDRELS, WALLS, BEAMS, GRADE BEAMS, ETC., UNLESS NOTED OTHERWISE AS FOLLOWS; TOP BARS AT MID-POINT OF SPAN, BOTTOM BARS AT THE SUPPORT. ALL REINFORCING STEEL SHALL BE SECURELY WIRED AND PROPERLY SUPPORTED ABOVE THE GROUND AND AWAY FROM FORMS AS SHOWN OR NOTED.
11. INSERTS: ALL ITEMS TO BE CAST IN CONCRETE SUCH AS REINFORCING, DOWELS, BOLTS, ANCHORS, PIPES, SLEEVES, ETC., SHALL BE SECURE AND POSITIONED BEFORE PLACING OF CONCRETE.
12. CONDUIT AND PIPES: CONDUIT AND PIPES SHALL NOT BE EMBEDDED IN STRUCTURAL CONCRETE EXCEPT WHERE SPECIFICALLY APPROVED BY THE ENGINEER OF RECORD. MAXIMUM CONDUIT AND PIPE SIZE SHALL BE 1/3 OF THE SLAB OR WALL THICKNESS AND LOCATED AT ITS MID DEPTH. MINIMUM SPACING SHALL BE 3 TIMES THE CONDUIT/PIPE DIAMETER. CONDUIT AND PIPES SHALL NOT IMPAIR THE STRENGTH OF THE MEMBER. CONDUIT AND PIPES SHALL NOT BE ALUMINUM. CONDUIT AND PIPES SHALL NOT DISPLACE MORE THAN 4% OF THE CROSS SECTION AREA.
13. CONSTRUCTION JOINTS: SHALL HAVE ENTIRE SURFACE REMOVED TO EXPOSE CLEAN AGGREGATE SOLIDLY EMBEDDED. THE CONTRACTOR SHALL OBTAIN THE APPROVAL OF CONSTRUCTION JOINT LOCATION IN ALL SLABS, BEAMS, AND WALLS.
14. NON-SHRINK CEMENT GROUT SHALL HAVE A MINIMUM 28 DAY COMPRESSIVE STRENGTH OF 9000 PSI. USE "SIKA GROUT 212" OR MASTERFLOW 928

- TIEBACKS: USING DYWIDAG PERMANENT STRAND ANCHOR SYSTEM WITH DCP (DOUBLE CORROSION PROTECTION). STRANDS ARE TO BE 0.6" Ø 7-WIRE, LOW RELAXATION 270KSI, CONFORMING TO ASTM A882 OR ASTM A416 AND MANUFACTURER SPECIFICATIONS. MINIMUM GROUT STRENGTH OF 4500PSI WITH A 0.45 WATER TO CEMENT RATIO. INSTALL PER MANUFACTURER SPECIFICATIONS.

REINFORCING STEEL NOTES:

1. GRADE: ALL REINFORCING STEEL SHALL BE DEFORMED BARS WHICH SHALL CONFORM TO THE STANDARD SPECIFICATIONS OF ASTM A615 GRADE 60, UNO. ALL REINFORCEMENT TO BE WELDED SHALL BE ASTM A706 GRADE 60, UNO. ALL REINFORCEMENT THAT IS PART OF THE SEISMIC FORCE RESISTING SYSTEM SHALL BE ASTM A706 GRADE 60, UNO
2. WELDED WIRE MESH: ELECTRIC WELDED WIRE MESH SHALL CONFORM TO ASTM A-185. SIZE SHALL BE AS SHOWN ON THE DRAWINGS. MINIMUM LAPS TO BE 12".
3. MINIMUM LAP: SEE LAP/SPLICE DETAILS.
4. MINIMUM COVER: REINFORCING STEEL TO HAVE THE FOLLOWING MINIMUM COVER:
   A. CONCRETE AGAINST EARTH (NOT FORMED) .... 3"
   B. CONCRETE EXPOSED TO EARTH OR WEATHER (FORMED OR TROWELED)
      #6 - #18 BARS .... 2"
      #5 AND SMALLER .... 1½"
   C. SLAB-ON-GRADE .... @ CL OF SLAB
   D. WALLS .... 1½"
   E. CONCRETE SLAB (FORMED) .... 1"
   F. STRUCTURAL SLAB AND WALLS .... 1"
   G. BEAMS AND COLUMNS
   (PRIMARY REINFORCEMENT, TIES, STIRRUPS, SPIRALS) .... 1½"
5. WELDING: LOW HYDROGEN WELDING RODS SHALL BE USED FOR ALL WELDING TO REINFORCING BARS, BUT ONLY WHERE SHOWN OR NOTED BY THE STRUCTURAL ENGINEER.
6. WELDING: GRADE 60 REBAR SHALL BE PREHEATED, WHEN WELDING, AS PRESCRIBED BY AWS D1.4 FOR VARIOUS SIZE BARS. REBAR SHALL BE ASTM A 706 GRADE 60.
7. DOWELING: DOWELS SHALL BE PROVIDED AT CONSTRUCTION JOINTS AND SHALL BE THE SAME SIZE AND SPACING AS DETAILED OR #3 @ 12"O.C. X 3'-0" LONG (MINIMUM).
8. TOLERANCE FOR REBAR PLACEMENT: TOLERANCE FOR LONGITUDINAL LOCATION OF BENDS AND ENDS OF REINFORCEMENT SHALL BE PLUS OR MINUS 2 INCHES EXCEPT AT DISCONTINUOUS ENDS OF MEMBERS WHERE TOLERANCES SHALL BE PLUS OR MINUS 1/2 INCH.
9. TEMPERATURE REINFORCEMENT: SHALL HAVE A LAP OF 48 BAR DIAMETERS BUT NOT LESS THAN 12 INCHES, AND THE SPLICE IN ADJACENT BARS SHALL BE NOT LESS THAN 5 FEET APART.

STRUCTURAL STEEL NOTES:

1. MATERIALS: ALL STRUCTURAL STEEL SHAPES SHALL CONFORM TO THE FOLLOWING UNO:

SHAPE	ASTM DESIGNATION	YEILD STRESS
a. W (WIDE FLANGE)	ASTM A992	(FY=50KSI)
b. WT (TEE)	ASTM A992	(FY=50KSI)
c. C (CHANNEL)	ASTM A36 OR A992	(FY=36, 50KSI)
d. MC (MISCELLANEOUS CHANNEL)	ASTM A36	(FY=36KSI)
e. L (ANGLE)	ASTM A36	(FY=36KSI)
f. M, S, MT AND ST	ASTM A36	(FY=36KSI)
g. HP (BEARING PILES)	ASTM A572 GRADE 50	(FY=50KSI)
h. HSS RECTANGLE	ASTM A500 GRADE C	(FY=50KSI)
i. HSS ROUND	ASTM A500 GRADE C	(FY=50KSI)
j. PLATES AND BARS	ASTM A572 GRADE 50	(FY=50KSI)
k. MISCELLANEOUS STEEL	ASTM A572 GRADE 50	(FY=50KSI)

2. WELDING: ALL WELDS SHALL BE IN CONFORMITY WITH THE STAND CODE FOR ARC AND GAS WELDING OF AMERICAN WELDING SOCIETY (AWS) AND THE AMERICAN INSTITUTE OF STEEL CONSTRUCTION (AISC). ALL STRUCTURAL WELDING SHALL BE PERFORMED BY CERTIFIED WELDERS USING THE SHIELDED ELECTRIC ARC PROCESS WITH APPROVED ELECTRODES. ALL WELDS FOR LATERAL FORCE RESISTANCE COMPONENTS SHALL BE OF A NOTCH TOUGH WELD METAL (CVN 20FT#@0-DEG.F. AND 40FT#@70DEG.F.) AND E70XX (70KSI) ELECTRODES SUCH AS E7018 FOR SHIELDED METAL ARC WELDING OR EQUIVALENT ACCORDING TO (AWS) REQUIREMENTS. ALL OTHER WELDS SHALL BE OF MIN E70XX (70KSI) ELECTRODES.
3. SHOP WELDING: SHOP WELDING SHALL BE PERFORMED ONLY IN THE SHOP OF AN APPROVED LICENSED FABRICATOR.
4. FIELD WELDING: ALL FIELD WELDING SHALL BE PERFORMED BY CERTIFIED WELDERS AND SHALL BE CONTINUOUSLY INSPECTED BY A REGISTERED SPECIAL INSPECTOR.
5. BOLTS: ALL BOLTS SHALL BE UNFINISHED BOLTS CONFORMING THE FOLLOWING UNO:
   a. HIGH STRENGTH CONVENTIONAL — ASTM F3125 GR. A325 OR GR. A490
   b. HIGH STRENGTH TENSION-CONTROL — ASTM F3125 GR. F1852 OR GR. F2280
6. NUTS AND WASHER SHALL CONFORM TO THE FOLLOWING UNO:
   a. NUTS — ASTM A563
   b. HARDENED WASHERS — ASTM F436
   c. DIRECT-TENSION INDICATOR WASHER — ASTM F959
7. ANCHOR RODS SHALL BE ASTM F1554 GRADE 55 S1, THREADED AND NUTTED UNLESS NOTED OTHERWISE. PLATE WASHERS SHALL BE ASTM A572 GR. 50. ANCHOR ROD WASHER MAY BE ASTM F844 WHERE PLATE WASHERS ARE NOT REQUIRED. A PLATE WASHER SHALL BE BETWEEN DOUBLE NUT AT EMBEDDED END OF ANCHOR ROD U.N.O.
8. BOLT HOLES: BOLT HOLES IN STEEL TO BE 1/16" LARGER DIAMETER THAN THE NOMINAL BOLT SIZE USED EXCEPT AS NOTED OTHERWISE.
9. STEEL HEADED STUD ANCHORS SHALL BE ASTM A108, TYPE B, 65 KSI, UNLESS NOTED OTHERWISE.

STRUCTURAL STEEL NOTES:

10. STEEL FRAMES: ALL STRUCTURAL STEEL FOR FRAMES SHALL CONFORM TO ASTM A992 GR. 50 PER AISC. ALL WELDS FOR STEEL FRAMES SHALL BE OF A NOTCH TOUGH WELD METAL (CVN 20FT#@-0DEG.F. AND 40FT#@70DEG.F.) AND E70XX (70KSI) ELECTRODES SUCH AS E7018 FOR SHIELDED METAL ARC WELDING OR EQUIVALENT ACCORDING TO (AWS) REQUIREMENTS, UNLESS OTHERWISE NOTED IN THESE DRAWINGS. COMPLETE-JOINT-PENETRATION WELDS SHALL HAVE THE BACKUP BARS REMOVED, THE EXPOSED WELD BACK GOUGED, GROUND TO SOUND BRIGHT METAL, AND FINALLY REINFORCED WITH A MINIMUM $\frac{5}{16}$" FILLET WELD TO COMPLY WITH CURRENT STANDARDS.
11. SHOP DRAWINGS: SHOP DRAWINGS SHALL BE SUBMITTED TO THE ARCHITECT FOR REVIEW AND COMMENT PRIOR TO FABRICATION.
12. DETAILING: ALL CONNECTIONS AND DETAILING PRACTICE SHALL CONFORM TO THE 14TH EDITION OF A.I.S.C. SPECIFICATIONS.
13. CERTIFICATION: AT COMPLETION OF FABRICATION, THE APPROVED FABRICATOR SHALL SUBMIT A CERTIFICATE OF COMPLIANCE TO THE BUILDING OFFICIAL STATING THAT THE WORK WAS PERFORMED IN ACCORDANCE WITH THE APPROVED CONSTRUCTION DOCUMENTS.

SPECIAL INSPECTION NOTES:

1. GENERAL: IN ADDITION TO THE INSPECTIONS REQUIRED BY SECTION 110 OF THE 2019 CBC, THE OWNER SHALL EMPLOY A SPECIAL INSPECTOR DURING CONSTRUCTION ON THE FOLLOWING TYPES OF WORK. ALL SPECIAL INSPECTIONS SHALL BE PERFORMED IN ACCORDANCE WITH CHAPTER 17 OF THE 2024 IBC.
2. CONCRETE: SEE SPECIAL INSPECTION SHEET
3. STRUCTURAL STEEL: SEE SPECIAL INSPECTION SHEET
4. EPOXY ANCHORS: REFER TO ICC-ES REPORTS
8. SELECTION OF THE SPECIAL INSPECTOR: THE OWNER SHALL SUBMIT TO THE ARCHITECT A LIST OF 3 FIRMS CHOSEN TO PERFORM THE SPECIAL INSPECTION DUTIES. THE SPECIAL INSPECTION FIRM SHALL HAVE AT LEAST 5 YEARS OF EXPERIENCE IN THE WORK TO BE INSPECTED. THE ARCHITECT SHALL RECOMMEND A FIRM FROM THOSE SUBMITTED.
9. FIELD INSPECTOR: ALL FIELD INSPECTORS SHALL HAVE A MINIMUM OF 2 YEARS EXPERIENCE IN THE SPECIFIC CONSTRUCTION BEING INSPECTED

STRUCTURAL STEEL AND MISCELLANEOUS METAL (ALL OTHER STEEL) WELDING:

1. ALL WELDING AND WELDED JOINTS SHALL BE IN STRICT CONFORMANCE WITH THE LATEST EDITION OF AWSD1.1 AND THE CALIFORNIA BUILDING CODE WITH ALL APPLICABLE AMENDMENTS. ALL NON PRE-QUALIFIED WELDED JOISTS SHALL BE QUALIFIED BY TEST AND PROCEDURE QUALIFICATION TEST RECORD INCLUDED PER THE LATEST EDITION OF AWS D1.1
2. WELDING OF SHEET METAL AND METAL STUDS SHALL BE IN ACCORDANCE WITH AWS D1.3
3. A WRITTEN "WELDING PROCEDURE SPECIFICATION" (WPS) SHALL BE DEVELOPED BY THE FABRICATOR/ERECTOR, AND REVIEWED BY THE OWNER'S REPRESENTATIVE AND BUILDING DEPARTMENT. THE WPS SHALL CONTAIN ALL THE NECESSARY INFORMATION REQUIRED BY THE CODE, THE SPECIFICATIONS, AND ANY OTHER INFORMATION NECESSARY TO PRODUCE WELDS THAT ARE IN COMPLIANCE WITH THESE REQUIREMENTS. THE WPS SHALL INCLUDE THE WELDING PARAMETERS RECOMMENDED BY THE ELECTRODE MANUFACTURE. ALL WELDERS AND INSPECTORS SHALL ADHERE TO THE WPS AND SHALL RETAIN A COPY.
4. ALL WELDS SHALL HAVE A FILER METAL WITH CHARPY V-NOTCH TOUGHNESS OF 20 FT-LBS AVERAGE AT MINUS TWENTY DEGREES FAHRENHEIT AND 40 FT-LBS AT SEVENTY DEGREES FAHRENHEIT. CERTIFY CONFORMANCE TO CHAPRY V-NOTCH TOUGHNESS REQUIREMENTS WITH TEST BY AN INDEPENDENT TESTING LABORATORY.
5. WELD LENGTHS CALLED FOR ON THE PLANS ARE THE NET EFFECTIVE LENGTH REQUIRED. WELD SIZE SHALL BE AISC MINIMUMS UNLESS A LARGER SIZE IS NOTED. WHERE LENGTH OF WELD IS NOT SHOWN, IT SHALL BE FULL LENGTH OF JOINT. ALL BUTT AND GROOVE WELDS SHALL BE FULL PENETRATION, UNLESS NOTED OTHERWISE.
6. ALL WELDING ELECTRODES AND ELECTRODE FLUX COMBINATIONS (FILLER METAL) SHALL BE MINIMUM 70 KSI, UNO, AND SHALL MEET THE REQUIREMENTS PER AISC SEISMIC PROVISIONS.
7. GMAW AND FCAW-G WELDING PROCESSES SHALL NOT BE PERMITTED WHEN WIND SPEED EXCEEDS 3 MPH.
8. WHERE FIELD WELDING IS NOTED, THE DESIGNATION IS GIVEN AS A SUGGESTED CONSTRUCTION PROCEDURE ONLY. THE CONTRACTOR IS SOLELY RESPONSIBLE FOR IDENTIFY THE METHOD OF FABRICATION.
9. ALL SHOP WELDS SHALL BE PERFORMED BY A FABRICATOR LICENSED BY THE LOCAL JURISDICTION.
10. ALL WELDERS SHALL BE QUALIFIED FOR THE WORK THEY WILL BE PERFORMING SHALL HAVE CURRENT VALID CERTIFICATIONS ISSUED BY AWS AND THE GOVERNING JURISDICTION.

SIMPSON STRONG-TIE SET-3G EPOXY ADHESIVE ANCHORS:

1. ANCHOR MANUFACTURER: WHERE ADHESIVE ANCHORS ARE CALLED FOR ON THESE PLANS, THE CONTRACTOR SHALL USE THE "SIMPSON STRONG-TIE SET-3G EPOXY ADHESIVE ANCHOR SYSTEM" BY SIMPSON STRONG-TIE COMPANY INC, INSTALLED PER REQUIREMENTS OF ICC-ES REPORT NO. ESR-4057, DATED APRIL 2025.
2. ADHESIVE REQUIREMENT: THE ADHESIVE USED WITH THESE ANCHORS SHALL BE "SIMPSON SET-3G EPOXY ADHESIVE", INSTALLATION OF WHICH SHALL PER THE ABOVE REFERENCED ICC-ES REPORT AND BE UNDER THE CONTINUOUS OBSERVATION OF A SPECIAL INSPECTOR PER THE ICC-ES REPORT.
3. ANCHOR RODS: ANCHOR RODS SHALL BE CONTINUOUSLY THREADED STEEL RODS CONFORMING TO ASTM A 193, GRADE B7.
4. INSTALLATION INFORMATION: THE CONTRACTOR SHALL OBTAIN AND RETAIN ON THE PREMISES A COPY OF THE ABOVE REFERENCED ICC-ES REPORT.
5. ANCHOR LOCATIONS: REFER TO THE DRAWING AND DETAILS FOR LOCATION AND SPECIFIC ANCHOR SIZE, SPACING AND EMBEDMENT.
6. CONCRETE SHALL BE CURED AT LEAST 21 DAYS BEFORE INSTALLING EPOXY ANCHORS.

SIMPSON STRONG-TIE SET-3G EPOXY ADHESIVE POST-INSTALLED REINFORCING BARS:

1. MANUFACTURER: WHERE ADHESIVE POST-INSTALLED REINFORCING BAR CONNECTIONS ARE CALLED FOR ON THESE PLANS, THE CONTRACTOR SHALL USE THE "SIMPSON STRONG-TIE SET-3G EPOXY ADHESIVE POST-INSTALLED REINFORCING BAR CONNECTIONS" BY SIMPSON STRONG-TIE COMPANY INC, INSTALLED PER REQUIREMENTS OF ICC-ES REPORT NO. ESR-4057, DATED APRIL 2025.
2. ADHESIVE REQUIREMENT: THE ADHESIVE USED WITH THESE ANCHORS SHALL BE "SIMPSON SET-3G EPOXY ADHESIVE", INSTALLATION OF WHICH SHALL PER THE ABOVE REFERENCED ICC-ES REPORT AND BE UNDER THE CONTINUOUS OBSERVATION OF A SPECIAL INSPECTOR PER THE ICC-ES REPORT.
3. REINFORCING BARS: REINFORCING BARS SHALL DEFORMED BARS CONFORMING TO ASTM A615 GR. 60 OR ASTM A706 GR 60. EMBEDDED PORTIONS OF THE REINFORCING BARS MUSH BE STRAIGHT, AND FREE OF MILL SCALE, RUST, MUD, OIL AND OTHER COATINGS THAT MAY IMPAIR THE BOND WITH THE ADHESIVE. REINFORCING BARS MUST NOT BE BENT AFTER INSTALLATION.
4. INSTALLATION INFORMATION: THE CONTRACTOR SHALL OBTAIN AND RETAIN ON THE PREMISES A COPY OF THE ABOVE REFERENCED ICC-ES REPORT.
5. REINFORCING BAR LOCATIONS: REFER TO THE DRAWING AND DETAILS FOR LOCATION AND SPECIFIC REINFORCING BAR SIZE, SPACING AND EMBEDMENT.

ABBREVIATIONS

@	AT	L	ANGLE
AB	ANCHOR BOLT	LAT	LATERAL
ABV	ABOVE	LBS, #	POUNDS
ACI	AMERICAN CONCRETE INSTITUTE	LF	LINEAR FEET (FOOT)
ADD'L	ADDITIONAL	LL	LIVE LOAD
AISC	AMERICAN INSTITUTE OF STEEL CONSTRUCTION	LLH	LONG LEG HORIZONTAL
		LLV	LONG LEG VERTICAL
APA	AMERICAN PLYWOOD ASSOCIATION	LONG	LONGITUDINAL
APPROX	APPROXIMATE	LSL	TIMBER STRAND
ARCH	ARCHITECT	LVL	MICROLAM
ARCH'L	ARCHITECTURAL		
ASTM	AMERICAN SOCIETY FOR TESTING & MATERIALS	MAT'L	MATERIAL
		MAX	MAXIMUM
AWS	AMERICAN WELDING SOCIETY	MB	MACHINE BOLT
		MECH'L	MECHANICAL
B/	BOTTOM OF	MEMB	MEMBRANE
BE	BOUNDARY ELEMENT	MANF	MANUFACTURER
BLW	BELOW	MIN	MINIMUM
BLD'G	BUILDING	MISC	MISCELLANEOUS
BLK	BLOCK	MTL	MATERIAL
BLK'G	BLOCKING		
BM	BEAM	(N)	NEW
BN	BOUNDARY NAILING	N/A	NON APPLICABLE
BO	BOTTOM OF (FOOTING, BEAM, ETC)	NIC	NOT IN CONTRACT
BTM	BOTTOM	NO	NUMBER
BTWN	BETWEEN	NOM	NOMINAL
		NTE	NOT TO EXCEED
CALCS	CALCULATIONS	NTS	NOT TO SCALE
CANT	CANTILEVER		
CF	CUBIC FOOT	O/	OVER
CFS	COLD FORMED STEEL	OC	ON CENTER
CJ	CONTROL JOINT	OD	OUTSIDE DIAMETER
CL	CENTERLINE or CLEAR	OF / OSF	OUTSIDE FACE
CLR	CLEAR	OPN'G	OPENING
CMU	CONCRETE MASONRY UNIT	OPP	OPPOSITE
COL	COLUMN	OPT'L	OPTIONAL
CONC	CONCRETE	OWWJ	OPEN WEB WOOD JOIST
CONN	CONNECTION		
CONST	CONSTRUCTION	PA	POST ABOVE
CONT	CONTINUOUS	PB	POST BELOW
CONTR	CONTRACTOR	PAR	PARALLEL
COORD	COORDINATE	PEN	PENETRATION
CTR	CENTER(ED)	PERP	PERPENDICULAR
CTSK	COUNTERSINK	PL	PLATE
		PLF	POUNDS PER LINEAR FOOT
d	PENNY	PLY	PLYWOOD
D	DEPTH	PRELIM	PRELIMINARY
DBA	DEFORMED BAR ANCHOR	PSF	POUNDS PER SQUARE FOOT
DBL	DOUBLE	PSI	POUNDS PER SQUARE INCH
DF	DOUGLAS FIR	PSL	PARALLEL STRAND LUMBER
DIA, Ø	DIAMETER	PT	PRESSURE TREATED
DIAPH	DIAPHRAGM		
DIM	DIMENSION	QTY	QUANTITY
DK'G	DECKING		
DL	DEAD LOAD	REF	REFERENCE
DTL	DETAIL	REINF	REINFORCEMENT
DWG	DRAWING	REQ'D	REQUIRED
DWL	DOWEL	RET	RETAINING
		REV	REVISION
		RND	ROUND
(E)	EXISTING		
EA	EACH	SCHED	SCHEDULE
EE	EACH END	SF	SQUARE FEET (FOOT)
EF	EACH FACE	SFRS	SEISMIC FORCE RESISTING SYSTEM
ELEV	ELEVATION		
EN	EDGE NAIL	SHT	SHEET
ENGR	ENGINEER	SHT'G	SHEATHING
EQ	EQUAL	SIM	SIMILAR
EQUIP	EQUIPMENT	SN	SILL NAIL
ES	EACH SIDE	SOG	SLAB ON GRADE
EW	EACH WAY	SPEC	SPECIFICATION
		SQ	SQUARE
F/	FACE OF	S.S.	STAINLESS STEEL
FB	FLAT BAR	SS	STRUCTURAL SELECT
FDN	FOUNDATION	STD	STANDARD
FF	FINISHED FLOOR	STL	STEEL
FG	FINISHED GRADE	STR'L	STRUCTURAL
FLR	FLOOR	SY	SQUARE YARD
FN	FIELD NAIL		
FOC	FACE OF CONCRETE	T	TOP
FOS	FACE OF STEEL	T & B	TOP & BOTTOM
FRM'G	FRAMING	T & G	TONGUE & GROOVE
FT	FEET (FOOT)	T/	TOP OF
FTG	FOOTING	THRD	THREADED
		THKN	THICKENED
GA / ga	GAUGE	TL	TOTAL LOAD
GALV	GALVANIZED	TN	TOE NAIL
GEN	GENERAL	TOF	TOP OF FOOTING / FOUNDATION
GLB	GLUED LAMINATED BEAM		
GR	GRADE	TOSh	TOP OF SHEATHING
		TOSl	TOP OF SLAB
HD	HOLDOWN	TOSt	TOP OF STEEL
HDR	HEADER	TRANV	TRANSVERSE
HGR	HANGER	TYP	TYPICAL
HSS	HOLLOW STRUCTURAL SECTION		
HT	HEIGHT	UNO	UNLESS NOTED OTHERWISE
IBC	INTERNATIONAL BUILDING CODE	VAR	VARIES
ID	INSIDE DIAMETER	VERT	VERTICAL
IF / ISF	INSIDE FACE	VIF	VERIFY IN FIELD
IN	INCHES	VL	VERSA-LAM
INFO	INFORMATION		
INSP	INSPECTION	W/	WITH
INT	INTERIOR	W/O	WITHOUT
INTER	INTERMEDIATE	WD	WOOD
		WF	WIDE FLANGE
JST	JOIST	WS	WOOD SCREWS
K	KIPS		
KSF	KIPS PER SQUARE FOOT		
KSI	KIPS PER SQUARE INCH		
KO	KNOCK OUT		
KP	KING POST		

BASIS OF DESIGN

1. BUILDING CODE: 2024 EDITION OF THE INTERNATIONAL BUILDING CODE (IBC)
2. BUILDING LIVE LOADS:
   ROOF — 20 PSF**
   FLOOR — 100 PSF
   **REDUCIBLE DEPENDING UPON TRIBUTARY AREA, AND SLOPE
3. WIND LOADS:
   ULTIMATE WIND SPEED V_{ULT} = 101 MPH
   NOMINAL DESIGN WIND SPEED:
   $V_{ASD} = V_{ULT}*SQRT(0.6)$ = 78 MPH
   RISK CATEGORY — II
   EXPOSURE — C
   INTERNAL PRESSURE COEFFICIENT (GCpI) = ±0.18
4. RISK CATEGORY:
   RISK CATEGORY — II
   SEISMIC IMPORTANCE FACTOR — 1.0
5. SEISMIC LOADS:
   SITE CLASS — D
   SEISMIC DESIGN CATEGORY — D
   RESPONSE MODIFICATION FACTORS
   R = 4.0 (CONCRETE SHEAR WALLS)
   MAPPED SPECTRAL RESPONSE ACCELERATIONS
   S_S = 0.17
   S_1 = 0.059
6. SPECTRAL RESPONSE COEFFICIENTS
   S_{DS} = 0.19
   S_{D1} = 0.11

.\BSE LOGO 4.png

BURKE STRUCTURAL ENGINEERS, PC
151 KALMUS DRIVE, BLDG. E-140
COSTA MESA, CA., 92626
(657) 289-0460

STAMP

Registered Professional Engineer (Civil)
CERTIFICATE NO.
80212
MOHAMED BADAWI
ARIZONA U.S.A.

REVISION SCHEDULE

DELTA	ISSUED BY	ISSUE DATE

STRUCTURAL GENERAL NOTES

HACE, INC

TENANT IMPROVEMENT WEST 202 LOGISTICS
675-555 N. 55th AVE, PHOENIX, AZ 85043

DATE: 2026-02-10
SCALE: AS SHOWN
PROJECT MANAGER: MEB
CHECKED BY: MEB
DRAWN BY: NMN
JOB NO.: 26011
SHEET: S001



STRAIGHT BAR DEVELOPMENT, L_d

Fy=60 ksi NORMAL-WEIGHT CONCRETE								
BAR SIZE	f'c=2500 psi		f'c=3000 psi		f'c=4000 psi		f'c=5000 psi	
	TOP	OTHER	TOP	OTHER	TOP	OTHER	TOP	OTHER
#3	20"	15"	18"	14"	16"	12"	14"	12"
#4	32"	24"	29"	22"	25"	19"	23"	17"
#5	45"	35"	42"	32"	36"	28"	32"	25"
#6	61"	47"	55"	43"	48"	37"	43"	33"
#7	96"	74"	88"	68"	76"	59"	68"	52"
#8	117"	90"	107"	83"	93"	72"	83"	64"
#9	132"	102"	121"	93"	105"	81"	94"	72"
#10	149"	115"	136"	105"	118"	91"	106"	81"
#11	165"	127"	151"	116"	131"	101"	117"	90"
#14	199"	153"	181"	140"	157"	121"	141"	108"
#18	265"	204"	242"	186"	209"	161"	187"	144"

SESIMIC STRAIGHT BAR DEVELOPMENT

Fy=60 ksi NORMAL-WEIGHT CONCRETE, 1.25*L_d								
BAR SIZE	f'c=2500 psi		f'c=3000 psi		f'c=4000 psi		f'c=5000 psi	
	TOP	OTHER	TOP	OTHER	TOP	OTHER	TOP	OTHER
#3	24"	19"	22"	17"	19"	15"	17"	15"
#4	39"	30"	36"	28"	31"	24"	28"	22"
#5	57"	44"	52"	40"	45"	35"	40"	31"
#6	76"	58"	69"	53"	60"	46"	54"	41"
#7	120"	92"	110	84"	95"	73"	85"	65"
#8	147"	113"	134"	103"	116"	89"	104"	80"
#9	165"	127"	151"	116"	131"	101"	117"	90"
#10	186"	143"	170"	131"	147"	113"	132"	102"
#11	207"	159"	189"	145"	164"	126"	146"	113"
#14	248"	191"	227"	174"	196"	151"	176"	135"
#18	331"	254"	302"	232"	261"	201"	234"	180"

LAP SPLICE SCHEDULE, CLASS B

Fy=60 ksi NORMAL-WEIGHT CONCRETE, 1.3L_d								
BAR SIZE	f'c=2500 psi		f'c=3000 psi		f'c=4000 psi		f'c=5000 psi	
	TOP	OTHER	TOP	OTHER	TOP	OTHER	TOP	OTHER
#3	25"	20"	23"	18"	20"	16"	18"	16"
#4	41"	32"	38"	29"	33"	25"	29"	23"
#5	59"	45"	54"	42"	47"	36"	42"	32"
#6	79"	61"	72"	55"	62"	48"	56"	43"
#7	125"	96"	114"	88"	99"	76"	88"	68"
#8	153"	117"	139"	107"	121"	93"	108"	83"
#9	172"	132	157"	121"	136"	105"	122"	94"
#10	194"	149"	177"	136"	153"	118"	137"	106"
#11	215"	165"	196"	151"	170"	131"	152"	117"

SEISMIC LAP SPLICE SCHEDULE, CLASS B

Fy=60 ksi NORMAL-WEIGHT CONCRETE, 1.25*1.3*L_d								
BAR SIZE	f'c=2500 psi		f'c=3000 psi		f'c=4000 psi		f'c=5000 psi	
	TOP	OTHER	TOP	OTHER	TOP	OTHER	TOP	OTHER
#3	32"	24"	29"	22"	25"	20"	22"	20"
#4	51"	39"	47"	36"	41"	31"	36"	28"
#5	74"	57"	67"	52"	58"	45"	52"	40"
#6	98"	76"	90"	69"	78"	60"	70"	54"
#7	156"	120"	142"	110"	123"	95"	110"	85"
#8	191"	147"	174"	134"	151"	116"	135"	104"
#9	215"	165"	196"	151"	170"	131"	152"	117"
#10	242"	186"	221"	170"	191"	147"	171"	132"
#11	269"	207"	245"	189"	212"	164"	190"	146"

STANDARD HOOK DEVELOPMENT l_{dh}

Fy=60 ksi NORMAL-WEIGHT CONCRETE				
BAR SIZE	f'c=2500psi	f'c=3000psi	f'c=4000psi	f'c=5000psi
#3	9"	9"	8"	7"
#4	12"	11"	10"	9"
#5	15"	14"	12"	11"
#6	18"	17"	15"	13"
#7	21"	20"	17"	15"
#8	24"	22"	19"	17"
#9	28"	25"	22"	20"
#10	31"	28"	25"	22"
#11	34"	31"	27"	24"
#14	41"	38"	33"	29"
#18	55"	50"	43"	39"

SEISMIC HOOK DEVELOPMENT l_{dh}

Fy=60 ksi NORMAL-WEIGHT CONCRETE, 1.25*l_{dh}				
BAR SIZE	f'c=2500psi	f'c=3000psi	f'c=4000psi	f'c=5000psi
#3	12"	11"	9"	8"
#4	15"	14"	12"	11"
#5	19"	18"	15"	14"
#6	23"	21"	18"	16"
#7	27"	24"	21"	19"
#8	30"	28"	24"	22"
#9	34"	31"	27"	24"
#10	39"	35"	31"	27"
#11	43"	39"	34"	30"
#14	51"	47"	41"	36"
#18	68"	62"	54"	48"

SEISMIC DEVELOPMENT AND LAP LENGTHS:

1. MINIMUM SEISMIC DEVELOPMENT AND LAP LOCATIONS
   A. SPECIAL CONCRETE SHEAR WALLS
      - LAP OF VERTICAL REINFORCEMENT AT BASE OF WALL
      - DEVELOPMENT OF REINFORCEMENT IN FOUNDATION ELEMENT
      - DEVELOPMENT OF DIAGONAL REBAR OF COUPLER BEAMS INTO WALLS

   B. SPECIAL CONCRETE MOMENT FRAMES
      - DEVELOPMENT OF LONGITUDINAL BEAM REINFORCEMENT IN CONFINED CORE OF COLUMN. ANY PORTION OF STRAIGHT BAR DEVELOPMENT OUTSIDE THE CONFINED CORE SHALL BE INCREASED BY A FACTOR OF 1.6.
      - COLUMN LONGITUDINAL REBAR DEVELOPMENT INTO FOUNDATION ELEMENTS.

2. SEE PLAN AND DETAILS FOR ADDITIONAL SEISMIC DEVELOPMENT AND LAP LOCATIONS

NOTES:
1. TOP BARS ARE DEFINED AS HORIZONTAL REINFORCEMENT WHERE MORE THAN 12" OF FRESH CONCRETE IS PLACED BELOW THE BARS BEING DEVELOPED OR SPLICED
2. VALUES IN TABLES ABOVE ARE FOR NORMAL WEIGHT CONCRETE ONLY. INCREASE LENGTHS BY 33.3% (MULTIPLY BY 1.33) FOR LIGHTWEIGHT CONCRETE
3. #14 AND #18 REQUIRE WELDED SPLICE OR MECHANICAL SPLICE
4. FOR F'c GREATER THAN 5000 PSI, USE VALUES FOR F'c = 5000 PSI.
5. FOR F'C = 4500 PSI, USE VALUES FOR F'c = 4000 PSI.

CONCRETE REBAR DEVELOPMENT, LAP SPLICES AND BENDS

11 DETAIL scale ¾"=1'-0"



DOWEL CONSTRUCTION JOINT

NOTES
1. INSTALL DOWEL SLEEVE PER MANUFACTURE INSTALLATION INSTRUCTIONS.
2. INSTALL DOWEL INTO SLEEVE PER MANUFACTURE INSTRUCTIONS.
3. ⅛" RADIUS EACH SIDE OF JOINT AS REQUIRED TO PROPERLY LOCATE SAW CUTS

DOWEL SIZE AND SPACING FOR CONSTRUCTION JOINT

SLAB THICKNESS INCHES	DOWEL SIZE	SPACING INCHES ON CENTER
<= 6"	0.75" DIA X 18"	18"
>6" to 8"	1.0" DIA X 18"	12"
>8"	1.25" DIA X 18"	12"

NOTES
1. DOWELS SHALL BE A36 OR GREATER STRENGTH STEEL

3 DETAIL scale ¾"=1'-0"



NOTES:
1. REINFORCEMENT NOT REQ'D FOR OPENINGS LESS THAN 24"x24"
2. FOR OPENINGS LARGER THAN 6FTx6FT, USE TURNED DOWN SLAB ON GRADE EDGE DETAIL

5 DETAIL scale ¾"=1'-0"



NOTES:
1. SEE SOILS REPORT FOR CAPILLARY BREAK INFORMATION. MINIMUM REQUIREMENT IS 4" OF AGGREGATE.
2. SEE ARCHITECTURAL DRAWINGS FOR VAPOR BARRIER. 15MIL MIN MINIMUM REQUIREMENT IS A 15 MILL VAPOR BARRIER.

8 DETAIL scale ¾"=1'-0"



NOTE:
SLAB JOINTS SHALL BE INSTALLED AT INTERVALS NOT EXCEEDING 12'-0" IN BOTH DIRECTIONS
(PREFERABLY A SQUARE PATTERN BUT NOT TO EXCEED 1:1½)

SLAB ON GRADE CRACK CONTROL JOINT

9 DETAIL scale ¾"=1'-0"



13 DETAIL scale ¾"=1'-0"



14 DETAIL scale ¾"=1'-0"

.\BSE LOGO 4.png

BURKE STRUCTURAL ENGINEERS, PC
151 KALMUS DRIVE, BLDG. E-140
COSTA MESA, CA., 92626
(657) 289-0460

STAMP

REVISION SCHEDULE

DELTA	ISSUED BY	ISSUE DATE

TYPICAL CONCRETE DETAILS

HACE, INC

TENANT IMPROVEMENT WEST 202 LOGISTICS
675-555 N. 55th AVE, PHOENIX, AZ 85043

DATE	2026-02-10
SCALE	AS SHOWN
PROJECT MANAGER	MEB
CHECKED BY	MEB
DRAWN BY	NMN
JOB NO.	26011
SHEET	S501



CONCRETE SLAB PLAN

scale 1/32"=1'-0"

.\BSE LOGO 4.png

BURKE STRUCTURAL ENGINEERS, PC
151 KALMUS DRIVE, BLDG. E-140
COSTA MESA, CA., 92626
(657) 289-0460

STAMP

Registered Professional Engineer (Civil)
CERTIFICATE NO. 80212
MOHAMED BADAWI
Date Signed 2026-02-19
ARIZONA U.S.A.

REVISION SCHEDULE

DELTA	ISSUED BY	ISSUE DATE

CONCRETE SLAB PLAN

HACE, INC

TENANT IMPROVEMENT WEST 202 LOGISTICS

675-555 N. 55th AVE, PHOENIX, AZ 85043

DATE	2026-02-10
SCALE	AS SHOWN
PROJECT MANAGER	MEB
CHECKED BY	MEB
DRAWN BY	NMN
JOB NO.	26011
SHEET	S1.10