Shop QA Platform — Engineering Handbook

> One Gherkin spec, three frameworks, two languages, orchestrated by a fleet of agents.

Generated 2026-10-25T14:44:29.572Z from the live repositories and contract layer.

1. At a glance


5	12	48	119
Repositories	Contracts	Scenarios	Cells covered

6	3
Open gaps	Surfaces


Three test frameworks in two languages drive one application across three surfaces, all from a single set of feature files. Coverage is tracked in a requirements traceability matrix that agents can query, and the gaps in it are the work queue.

2. Architecture


2.1 System topology




2.2 Agent orchestration



2.3 Closing a gap, end to end




2.4 Framework layering (strict)



Step definitions assert. Page, Screen and Service objects interact and wait. Neither does the other's job.

2.5 Data model



3. Repositories and components

shop-platform

Role. System under test. Agents have READ-ONLY access.

Stack. Spring Boot 3.3.5 · Java 21 · PostgreSQL 16 · React 18 + Vite · React Native (Expo)

Component	Responsibility
`backend/`	Spring Boot API. 12 domains, Flyway V1–V6, JWT, springdoc OpenAPI, Actuator.
`backend/.../testsupport/`	Triple-gated fixture endpoints: `@Profile("test")` + `X-Test-Token` + per-user scoping.
`web/`	React SPA. `data-testid` on every interactive element.
`mobile/`	Expo React Native app. `testID` on every interactive element.
`packages/types/`	TypeScript types generated from the live OpenAPI document.

shop-qa-orchestrator

Role. QA centre of excellence: contracts, MCP servers, agents, CI.

Stack. Node 22 · @cucumber/gherkin · MCP SDK

Component	Responsibility
`contracts/features/`	The ONLY copy of the Gherkin. 12 contracts, 48 scenarios.
`contracts/fixtures/`	Single source of test data: users, products, cards.
`contracts/coverage/coverage.yaml`	GENERATED by `link_implementation`. Never hand-edited.
`mcp/contract-mcp/`	Traceability MCP + `selftest.js` and `smoke.js`.
`mcp/shop-app-mcp/`	Test data management MCP.
`mcp/android-mcp/`	Emulator lifecycle MCP.
`.github/agents/`	Five agent definitions.
`ci/`	Jenkins pipeline + job XML, TestLink compose.
`scripts/merge-allure.ps1`	Merges three surfaces into one Allure report.
`scripts/start-env.ps1`	Checks prerequisites, starts the Docker stack, emulator and Appium, and installs the released APK.

shop-api-automation

Role. API BDD suite.

Stack. cucumber-jvm 7.20.1 · Rest Assured 5.5.0 · JUnit Platform · Allure

Component	Responsibility
`steps/`	Assertions only. No URLs, no request building.
`support/ShopApi.java`	Facade. The single dependency of the step layer.
`services/*Api.java`	Request building. No assertions.
`fixtures/Fixtures.java`	Repository over the shared fixture files.
`context/ScenarioContext.java`	Per-scenario state, injected by PicoContainer.
`hooks/Hooks.java`	`@BeforeAll` stock replenish; `@After` attaches the request/response dump.

shop-web-automation

Role. Web BDD suite.

Stack. playwright-bdd 9.2 · Playwright 1.62 · allure-playwright

Component	Responsibility
`src/steps/`	Assertions only.
`src/pages/`	Page and component objects. Interactions and waits only.
`src/fixtures/test.ts`	Playwright fixtures — the DI container. Must be listed in `steps`.
`src/api/ShopApi.ts`	Facade used only to seed state.
`playwright.config.ts`	`bddgen` config, `missingSteps: skip-scenario`, `workers: 1`.

shop-mobile-automation

Role. Android BDD suite.

Stack. cucumber-jvm 7.20.1 · Appium java-client 9.4.0 · Selenium pinned 4.26.0

Component	Responsibility
`steps/`	Assertions only.
`screens/`	Screen objects. `BaseScreen.byTestId` wraps `UiSelector.resourceId`.
`driver/DriverManager.java`	ThreadLocal driver factory.
`hooks/Hooks.java`	Clears app data per scenario; attaches screenshot, page source, logcat.

4. The contract layer

Feature files live in **one place only**: `shop-qa-orchestrator/contracts/features`. No framework owns a copy.

Rules enforced mechanically by `mcp/contract-mcp/selftest.js`:

- Every scenario carries a contract id, a priority and at least one surface tag.
- No step text is used as both a setup and an assertion.
- The reserved gaps stay declared but unlinked.

The distinction that makes it work. A surface tag *declares intent to cover*. An untagged surface reports `n/a`; a tagged but unlinked surface reports `gap`. Without that difference, `find_gaps` returns

nothing and the orchestration demo has no work to do.

5. Traceability matrix

Contract	Journey	Scenarios	api	web	mobile	TestLink
ADDRESS-01	Managing delivery addresses	4	covered	covered	covered	SHOP-9
ADMIN-01	Administering the catalog	4	covered	covered	covered	SHOP-12
AUTH-01	Creating an account	3	covered	covered	covered	SHOP-5
AUTH-02	Account access	4	covered	covered	covered	SHOP-1
CART-01	Managing the cart	5	covered	covered	GAP	SHOP-3
CATALOG-01	Browsing the catalog	5	covered	covered	covered	SHOP-2
CHECKOUT-01	Checking out	4	covered	GAP	GAP	SHOP-4
COUPON-01	Applying a discount coupon	5	covered	covered	covered	SHOP-10
ORDERS-01	Reviewing past orders	3	covered	covered	covered	SHOP-7
PRODUCT-01	Viewing a product	3	covered	covered	covered	SHOP-6
REVIEWS-01	Reviewing a product	4	covered	covered	covered	SHOP-11
WISHLIST-01	Saving products for later	4	covered	covered	covered	SHOP-8

Open gaps

6 gaps remain. These are deliberate: they are the work the orchestrator fans out to specialists, and at least one is reserved to be filled live on stage.

Gap	Scenarios
`CART-01 @mobile`	2
`CHECKOUT-01 @mobile`	2
`CHECKOUT-01 @web`	2

6. Test details

ADDRESS-01 — Managing delivery addresses (4 scenarios)

`address.feature` · priority P2 · TestLink `SHOP-9`

Scenario	Surfaces	Steps
The first saved address becomes the default	`@api` `@web` `@mobile`	3
A second address does not displace the default	`@api` `@web` `@mobile`	4
The default can be switched	`@api` `@web` `@mobile`	5
Deleting the default promotes another address	`@api` `@web` `@mobile`	5

Steps

```
Given the shop is available
And I am signed in as "demo@shop.in"
And I have no saved addresses
When I save my "Home" address
Then I have 1 saved address
And "Home" is my default address
Given I have saved my "Home" address
When I save my "Office" address
Then I have 2 saved addresses
And I have saved my "Office" address
When I make "Office" my default address
Then "Office" is my default address
And exactly one address is marked default
When I delete my "Home" address
```

ADMIN-01 — Administering the catalog (4 scenarios)

`admin.feature` · priority P2 · TestLink `SHOP-12`

Scenario	Surfaces	Steps
An administrator sees every product	`@api` `@web` `@mobile`	3
An ordinary shopper is refused	`@api` `@web`	3
An administrator can change stock	`@api` `@web` `@mobile`	3
Hiding a product removes it from the shopper catalog	`@api` `@web` `@mobile`	4

Steps

```
Given the shop is available
Given I am signed in as "admin@shop.in"
When I open the product administration list
Then I see all 12 products including hidden ones
Given I am signed in as "demo@shop.in"
Then the request is refused as forbidden
When I set the stock of "Mechanical Keyboard" to 3
Then "Mechanical Keyboard" reports 3 in stock
When I hide "Wireless Mouse" from the catalog
Then the shopper catalog holds 11 products
And restoring "Wireless Mouse" brings the catalog back to 12
```

AUTH-01 — Creating an account (3 scenarios)

`registration.feature` · priority P1 · TestLink `SHOP-5`

Scenario	Surfaces	Steps
Register a brand new account	`@api` `@web` `@mobile`	3
Registering an email that is already taken is refused	`@api` `@web` `@mobile`	3
A new account starts with an empty cart	`@api`	3

Steps

```
Given the shop is available
Given "newcomer@shop.in" has no account
When I register as "newcomer@shop.in"
Then I am recognised as "newcomer@shop.in"
Given I am a registered shopper "demo@shop.in"
When I attempt to register as "demo@shop.in"
Then I am told the email is already registered
Then my cart is now empty
```

AUTH-02 — Account access (4 scenarios)

`auth.feature` · priority P1 · TestLink `SHOP-1`

Scenario	Surfaces	Steps
Sign in with valid credentials	`@api` `@web` `@mobile`	3
Sign in is rejected with the wrong password	`@api` `@web` `@mobile`	4
Sign out ends the session	`@api` `@web` `@mobile`	3
A protected resource cannot be reached without signing in	`@api`	3

Steps

```
Given the shop is available
Given I am a registered shopper "demo@shop.in"
When I sign in as "demo@shop.in"
Then I am recognised as "demo@shop.in"
When I attempt to sign in as "demo@shop.in" with the wrong password
Then I am told the credentials are invalid
And I am no longer signed in
Given I am signed in as "demo@shop.in"
When I sign out
Then I am no longer signed in
Given I am not signed in
When I request my cart
Then the request is refused as unauthorised
```

CART-01 — Managing the cart (5 scenarios)

`cart.feature` · priority P1 · TestLink `SHOP-3`

Scenario	Surfaces	Steps
Add a product to the cart	`@api` `@web` `@mobile`	3
Increase the quantity of a cart line	`@api` `@web` `@mobile`	4
Remove a product from the cart	`@api` `@web` `@mobile`	3
Adding the same product twice merges into one line	`@api` `@web` `@mobile`	4
Reducing a quantity to zero removes the line	`@api`	3

Steps

```
Given the shop is available
And I am signed in as "demo@shop.in"
And my cart is empty
When I add "Espresso Machine" to my cart
Then my cart contains 1 line
And my cart shows 1 of "Espresso Machine"
Given my cart contains 1 of "Espresso Machine"
When I change the quantity of "Espresso Machine" to 3
Then my cart shows 3 of "Espresso Machine"
And my cart total is the price of 3 "Espresso Machine"
When I remove "Espresso Machine" from my cart
Then my cart is now empty
And my cart shows 2 of "Espresso Machine"
When I change the quantity of "Espresso Machine" to 0
```

CATALOG-01 — Browsing the catalog (5 scenarios)

`catalog.feature` · priority P1 · TestLink `SHOP-2`

Scenario	Surfaces	Steps
Browse every product	`@api` `@web` `@mobile`	2
Search narrows the catalog by name	`@api` `@web` `@mobile`	3
Filter the catalog by category *(outline, 4 examples)*	`@api` `@web` `@mobile`	2
Clearing the filters restores the full catalog	`@api` `@web` `@mobile`	3
A search with no matches reports an empty catalog	`@api` `@web` `@mobile`	3

Steps

```
Given the shop is available
And the catalog is seeded with the demo products
When I open the catalog
Then I see 12 products
When I search the catalog for "espresso"
Then I see 1 product
And the results include "Espresso Machine"
When I filter the catalog by category "<category>"
Then every result belongs to category "<category>"
Given I have searched the catalog for "espresso"
When I clear the catalog filters
When I search the catalog for "xyzzy"
Then I see 0 products
And I am told no products matched
```

CHECKOUT-01 — Checking out (4 scenarios)

`checkout.feature` · priority P1 · TestLink `SHOP-4`

Scenario	Surfaces	Steps
Pay with an approved card	`@api` `@web` `@mobile`	4
A declined card does not place an order	`@api` `@web` `@mobile`	4
A card with insufficient funds does not place an order	`@api`	3
Checking out an empty cart is refused	`@api`	4

Steps

```
Given the shop is available
And I am signed in as "demo@shop.in"
And my cart contains 1 of "Espresso Machine"
When I check out with the approved card
Then my order is confirmed
And I am given an order number
And my cart is now empty
When I check out with the declined card
Then the payment is declined
And no order is placed
And my cart shows 1 of "Espresso Machine"
When I check out with the insufficient-funds card
Given my cart is empty
Then I am told the cart is empty
```

COUPON-01 — Applying a discount coupon (5 scenarios)

`coupon.feature` · priority P2 · TestLink `SHOP-10`

Scenario	Surfaces	Steps
A valid coupon reduces the total	`@api` `@web` `@mobile`	3
A coupon below its minimum order is refused	`@api` `@web` `@mobile`	2
An inactive coupon is refused	`@api` `@web` `@mobile`	2
An unknown coupon is refused	`@api` `@web` `@mobile`	2
A coupon can be removed	`@api` `@web` `@mobile`	3

Steps

```
Given the shop is available
And I am signed in as "demo@shop.in"
And my cart contains 1 of "Espresso Machine"
When I apply coupon "SAVE10"
Then my cart shows a 10 percent discount
And my cart total is the subtotal minus the discount
When I apply coupon "SAVE25"
Then I am told the coupon cannot be used
When I apply coupon "EXPIRED"
When I apply coupon "NOSUCHCODE"
Given I have applied coupon "SAVE10"
When I remove the coupon
Then my cart has no discount
```

ORDERS-01 — Reviewing past orders (3 scenarios)

`orders.feature` · priority P1 · TestLink `SHOP-7`

Scenario	Surfaces	Steps
A placed order appears in my history	`@api` `@web` `@mobile`	3
Order history is empty for a shopper who has never bought anything	`@api` `@web` `@mobile`	4
One shopper cannot see another shopper's order	`@api`	3

Steps

```
Given the shop is available
And I am signed in as "demo@shop.in"
Given I have already placed an order for "Espresso Machine"
When I open my order history
Then my most recent order is listed as confirmed
Given I am signed in as "priya@shop.in"
And I have no order history
Then I am told I have no orders
Given "priya@shop.in" has placed an order
Then that order is not listed
```

PRODUCT-01 — Viewing a product (3 scenarios)

`product.feature` · priority P2 · TestLink `SHOP-6`

Scenario	Surfaces	Steps
Open a product from the catalog	`@api` `@web` `@mobile`	3
A product shows its category and stock state	`@api` `@web` `@mobile`	3
Requesting a product that does not exist is refused	`@api`	2

Steps

```
Given the shop is available
And the catalog is seeded with the demo products
When I open the product "Espresso Machine"
Then I see the product details for "Espresso Machine"
And the product shows the price of 1 "Espresso Machine"
When I open the product "4K Monitor"
Then the product belongs to category "Peripherals"
And the product is shown as in stock
When I request the product with id 999999
Then the product is reported as not found
```

REVIEWS-01 — Reviewing a product (4 scenarios)

`reviews.feature` · priority P2 · TestLink `SHOP-11`

Scenario	Surfaces	Steps
A buyer can review what they bought	`@api` `@web` `@mobile`	4
Reviewing again edits the existing review	`@api` `@web` `@mobile`	5
A shopper who never bought the product cannot review it	`@api`	2
Reviews are readable without signing in	`@api` `@web` `@mobile`	5

Steps

```
Given the shop is available
And I am signed in as "demo@shop.in"
And I have no order history
Given I have already placed an order for "Desk Lamp"
When I review "Desk Lamp" with 5 stars
Then "Desk Lamp" has 1 review
And "Desk Lamp" has an average rating of 5
And I have reviewed "Desk Lamp" with 5 stars
When I review "Desk Lamp" with 3 stars
And "Desk Lamp" has an average rating of 3
When I review "Standing Desk" with 5 stars
Then I am told only buyers can review
And I have reviewed "Desk Lamp" with 4 stars
When anyone views the reviews for "Desk Lamp"
And reviewing is not offered
```

WISHLIST-01 — Saving products for later (4 scenarios)

`wishlist.feature` · priority P2 · TestLink `SHOP-8`

Scenario	Surfaces	Steps
Save a product for later	`@api` `@web` `@mobile`	3
Saving the same product twice keeps one entry	`@api` `@web` `@mobile`	3
Remove a saved product	`@api` `@web` `@mobile`	3
Removing a product that was never saved is refused	`@api`	2

Steps

```
Given the shop is available
And I am signed in as "demo@shop.in"
And my wishlist is empty
When I save "Espresso Machine" for later
Then my wishlist holds 1 product
And my wishlist includes "Espresso Machine"
Given I have saved "Espresso Machine" for later
When I remove "Espresso Machine" from my wishlist
Then my wishlist is now empty
When I remove "Desk Lamp" from my wishlist
Then I am told the product was not saved
```

7. Running the tests

7.1 Prerequisites

Tool	Version	Needed by
JDK	21 (Temurin)	API + mobile suites, backend
Node	20+	web suite, MCP servers
Docker Desktop	any recent	Docker stack (Postgres, backend, web), CI
Android SDK + emulator	API 35	mobile suite only
Appium	3.x + uiautomator2	mobile suite only

`start-env.ps1` checks these first and lists everything that is missing, with where to get it. Docker, `adb`, the emulator, Appium and its `uiautomator2` driver are required (the last four unless you pass `-SkipMobile`). JDK 21, Maven and Node 20+ only produce a warning, because the Docker stack does not need them; they are needed to run the suites, and are required with `-Native`.

> Verify the JDK with `mvn -v` — it must report `Java version: 21`. A bare `java -version` can report a different JDK when the machine PATH shadows it; that is harmless, because Maven and Gradle use `JAVA_HOME`.

7.2 Start the environment

One command (Windows). Start Docker Desktop and run:

```
powershell -ExecutionPolicy Bypass -File shop-qa-orchestrator/scripts/start-env.ps1
```

Run it from the repo root (the folder you cloned). Use forward slashes as shown; they work in PowerShell, cmd and Git Bash, where backslashes are swallowed.

It checks prerequisites first, then starts only what is not already healthy and waits on each health check before moving on. By default it runs the Docker stack from the repo-root `docker-compose.yml`, and gets the APK from the repo's GitHub Release, verified against a SHA-256. Re-running it is safe.

Option	Effect
(none)	Docker stack (Postgres, backend, web), emulator, Appium; downloads and installs the released APK if the app is not on the emulator
`-SkipMobile`	Docker stack only: no emulator, Appium or APK
`-Native`	Run backend and web from source instead of Docker (needs JDK 21, Maven, and `npm ci` in `shop-platform/web`)
`-BuildApk`	Build the release APK with Gradle instead of downloading it (needs the generated `android/` folder)
`-ReinstallApk`	Install the APK even if `com.shop.mobile` is already on the emulator
`-Avd <name>`	Use a different AVD (default `shop_test`)

Docker stack only. From the repo root, `docker compose up -d --build` starts Postgres, the backend (:8081) and the web app (:5173); `docker compose down` stops it (`-v` also wipes the database). Every

credential in the compose file is a demo value for local use only. The repo root also holds `docker/web.Dockerfile` and a `README.md` quick start.

Manual steps. Run each from the Shop root. PowerShell does not accept the bash `VAR=value command` form; set `$env:VAR` first.

Step	bash (macOS / Linux / CI)	Windows PowerShell
Stack (Docker, default)	`docker compose up -d --build`	`docker compose up -d --build`
Postgres (native)	`cd shop-platform && docker compose up -d postgres`	`cd shop-platform; docker compose up -d postgres`
Backend (native)	`cd shop-platform/backend && SPRING_PROFILES_ACTIVE=test mvn spring-boot:run`	`cd shop-platform\backend; $env:SPRING_PROFILES_ACTIVE="test"; mvn spring boot:run`
Web app (native)	`cd shop-platform/web && VITE_API_BASE_URL=http://localhost:8081 npx vite dev --port 5173`	`cd shop-platform\web; $env:VITE_API_BASE_URL="http://localhost:8081" npx vite dev --port 5173`
Emulator	`emulator -avd shop_test -no-boot-anim -gpu swiftshader_indirect`	`emulator -avd shop_test -no-boot-anim -gpu swiftshader_indirect`
Appium	`appium --port 4723`	`appium --port 4723`
Mobile APK (released)	Download `app-release.apk` from the repo's GitHub Releases page, then `adb install -r app-release.apk`	Download `app-release.apk` from the repo's GitHub Releases page, then `adb install -r app-release.apk`
Mobile APK (build)	`cd shop-platform/mobile/android && NODE_ENV=production ./gradlew assembleRelease`	`cd shop-platform\mobile\android; $env:NODE_ENV="production"; .\gradlew.bat assembleRelease`

If you cannot type into the emulator with the PC keyboard, the AVD has `hw.keyboard = no` in `%USERPROFILE%\.android\avd\shop_test.avd\config.ini`. Set it to `yes` and cold boot (`adb emu kill`, then start with `-no-snapshot-load`). If clicking a field shows a small floating toolbar instead of the keyboard, run `adb shell settings put secure stylus_handwriting_enabled 0`. `start-env.ps1` applies both.

Once running:

What	URL
Web app	http://localhost:5173
Backend health	http://localhost:8081/actuator/health
Swagger UI (API endpoints)	http://localhost:8081/swagger-ui.html
OpenAPI JSON	http://localhost:8081/v3/api-docs
Appium status	http://127.0.0.1:4723/status

7.3 Run a suite

Suite	Repository	Command	Requires	Expected
API	shop-api-automation	`mvn -B test`	backend :8081	51 scenarios
Web	shop-web-automation	`npx bddgen && npx playwright test`	web :5173 + backend	40 passed, 2 skipped
Mobile	shop-mobile-automation	`mvn -B test`	emulator + Appium + backend	37 scenarios
Merged report	shop-qa-orchestrator	`pwsh scripts/merge-allure.ps1`	any suite already run	one Allure report

7.4 Configuration

Every value is env-overridable; nothing is hardcoded to localhost.

Variable	Default	Used by
`SHOP_API_BASE_URL`	`http://localhost:8081`	all three suites
`WEB_BASE_URL`	`http://localhost:5173`	web suite
`APPIUM_URL`	`http://127.0.0.1:4723`	mobile suite
`TEST_SUPPORT_TOKEN`	`local-test-token`	seeding endpoints
`CONTRACTS_DIR`	`../shop-qa-orchestrator/contracts`	fixture + feature lookup
`APP_PACKAGE`	`com.shop.mobile`	mobile suite

7.5 Filtering

```
# API: smoke only
mvn -B test -Dcucumber.filter.tags="@api and @smoke"

# API: one journey
mvn -B test -Dcucumber.filter.tags="@api and @CHECKOUT-01"

# Web: by tag
npx bddgen && npx playwright test --grep @smoke
```

7.6 Exploring the API interactively

The backend publishes a live OpenAPI 3 document and a Swagger UI with **Try it out** enabled, so every endpoint can be called from the browser without a REST client.

What	URL
Swagger UI	http://localhost:8081/swagger-ui.html
OpenAPI JSON	http://localhost:8081/v3/api-docs

To call a protected endpoint:

1. `POST /api/auth/login` with a seeded account and copy the `token`.
2. Press **Authorize**, paste the token under `bearerAuth`, confirm.
3. The `X-Test-Token` scheme (`testToken`) unlocks the `/api/test-support/**` seeding endpoints; the local value is `local-test-token`.

Authorisation is persisted across reloads, and the same `/v3/api-docs` document is what regenerates `packages/types` for the web and mobile apps — so the spec cannot silently drift from the code.

8. Test data

All test data comes from `contracts/fixtures`. A literal email, password, price or card number in a step definition is a defect.

Seeded accounts

Key	Email	Password	Role
`demo`	`demo@shop.in`	`Demo@12345`	CUSTOMER
`priya`	`priya@shop.in`	`Priya@12345`	CUSTOMER
`admin`	`admin@shop.in`	`Admin@12345`	ADMIN
`legacy`	`shopper@example.com`	`Password123`	CUSTOMER

Payment cards

Card	Number	Outcome
`approved`	`4111111111111111`	APPROVED
`declined`	`4000000000000002`	DECLINED
`insufficientFunds`	`4000000000009995`	INSUFFICIENT_FUNDS

Any future expiry, any three-digit CVC. The gateway routes on card number alone and is fully deterministic.

Coupons

Code	Discount	Condition
`SAVE10`	10%	Orders over ₹5,000
`SAVE25`	25%	Orders over ₹50,000
`EXPIRED`	50%	Inactive — always refused

Catalog: 12 products across Audio, Furniture, Kitchen, Peripherals. Prices are stored in **paise**; money is never a float.

9. MCP servers

Server	Tools	Purpose
`contract-mcp`	list_scenarios, get_scenario, get_coverage_matrix, find_gaps, link_implementation, get_fixture	The traceability layer, exposed as agent-queryable tools
`shop-app-mcp`	health, seed_user, seed_cart, reset_user, get_state, get_openapi	Test data management for the system under test
`android-mcp`	list_avds, list_devices, start_emulator, wait_for_boot, install_apk, clear_app_data, screenshot, tail_logcat, dump_ui, get_appium_status	Emulator and APK lifecycle

Each server ships a `smoke.js` that drives it over real JSON-RPC stdio — including an assertion that **no array parameter is missing `items`**. Strict clients reject such schemas, and the failure is otherwise silent.

10. Agents

Agent	Owns	Tools
`shop-qa-orchestrator`	Intent parsing, delegation, reconciliation	`contract/*, shop-app/*, runSubagent`
`contract`	Authoring and validating Gherkin	`edit, contract/*`
`api-automation`	shop-api-automation only	`edit, contract/*, shop-app/*`
`web-automation`	shop-web-automation only	`edit, contract/*, shop-app/*, playwright/*`
`mobile-automation`	shop-mobile-automation only	`edit, contract/*, shop-app/*, android/*`

> **No agent has write access to `shop-platform`.** If a test fails because the application is wrong, the agent reports it rather than editing the app.

Agents cannot message each other. Coordination happens only through delegation, the shared contract files (a blackboard architecture), and MCP servers.

Delegation brief

```
CONTRACT:      CHECKOUT-01
SCENARIOS:     Pay with an approved card
SURFACE:       web
TARGET REPO:   shop-web-automation
FIXTURES:      users.demo, cards.approved
PRECONDITIONS: seed cart via shop-app MCP
DELIVERABLES:  step definitions + green local run + link_implementation

REPORT BACK (machine-parseable, required):
  files_created: []
  files_modified: []
  contract_id: ""
  scenarios: []
  local_result: pass | fail
  failure_reason: ""
  app_bug_suspected: true | false
```

11. Reporting

Allure everywhere — the only OSS reporter with first-class adapters for both cucumber-jvm and Playwright, so three frameworks in two languages merge into a single report.

Surface	Attached on failure
`api`	Full request/response dump (status, headers, body, timing)
`web`	Screenshot + Playwright trace
`mobile`	Screenshot + page source XML + logcat tail

Evidence is attached by hooks through a publisher. Step definitions never call the reporter directly.

```
pwsh shop-qa-orchestrator/scripts/merge-allure.ps1 -Open
```

12. CI

Jenkins on **:8092**, TestLink on **:8082** — deliberately different ports from the InspireFranchises stack (8080/8090) so both can run side by side.

The pipeline validates the contract layer first, then runs the selected surfaces, prints the coverage matrix, and publishes one merged Allure report.

> Job XML must declare choice parameters as `<choices><string>`. Serialising `java.util.Arrays$ArrayList` yields null choices and the job page then fails with HTTP 500.

```
cd shop-qa-orchestrator/ci
docker compose up -d          # Jenkins :8092, TestLink :8082
```

13. Traps and their fixes

Every entry below cost real debugging time on this project. They are also encoded in the agent instruction files so specialists do not rediscover them.

Trap	Symptom	Fix
Cucumber matches step TEXT only	The Given/Then keyword is ignored, so one phrase cannot be both a precondition and an assertion.	Distinct wording: `my cart is empty` vs `my cart is now empty`. Enforced by `selftest.js`.
Allure silently writes zero results	Registering the plugin via `@ConfigurationParameter` produces attachments but no `-result.json`, so the report looks empty.	Register in `junit-platform.properties`.
Playwright reporter override	`playwright test --reporter=list` REPLACES the configured reporters, so Allure writes nothing.	Never pass `--reporter` on the CLI.
Suite runs twice	Setting both `cucumber.features` and a surefire `` creates two independent selectors; the mobile suite ran twice against one Appium session.	Pick one. Mobile uses includes + `@SelectDirectories`; API uses `cucumber.features`.
RN testID is a raw resource-id	`AppiumBy.id()` prefixes the app package and never matches.	Use `UiSelector().resourceId("...")` via `BaseScreen.byTestId`.
Debug APK is an empty shell	A debug build loads its JS bundle from Metro; without Metro every locator times out.	Always `assembleRelease` with `NODE_ENV=production`.
Release APK blocks plain HTTP	Android 9+ blocks cleartext; the app renders but shows no data, with no error.	`expo-build-properties` with `usesCleartextTraffic: true`.
noReset leaks the session	The previous scenario stays signed in, so the header shows Log out where the test expects Log in.	Clear app data in `@Before`.
Virtualised lists	Only mounted rows are queryable, so a product further down cannot be located.	Search for it first; assert counts via the app's own `result-count`.
Stock is consumed permanently	Every checkout decrements stock, so a repeatable suite eventually starves.	`@BeforeAll` replenishes the catalog through the admin API.
Shared demo account	Parallel web workers interleave cart and order state for the same user.	Web suite runs `workers: 1`.
PowerShell corrupts binaries	`adb exec-out screencap -p > file.png` re-encodes and yields an invalid PNG.	`adb shell screencap` then `adb pull`.
Git does not track empty folders	A Dockerfile that copies an empty folder (`web/public`) builds on the author's machine but fails on a fresh clone with "not found".	Never `COPY` a folder that may be empty. Test the Docker build from a fresh clone, not the working copy.

Trap	Symptom	Fix
Windows line endings can break scripts in containers	With `core.autocrlf`, a Windows checkout can turn `mvnw` into CRLF, and the backend image build then fails with “bad interpreter”.	`.gitattributes` pins `mvnw`, `gradlew` and Dockerfiles to LF.
One dead Appium session fails everything after it	When the emulator or UiAutomator2 hangs, every later scenario reports `Session ID is null` or a request timeout, which looks like many unrelated failures.	Look at the FIRST broken scenario. Restart the emulator and Appium, then re-run before investigating the app.

14. Design standards

Patterns. Page/Screen/Service Object · Component Object · Factory · ThreadLocal singleton · Builder · Template Method · Strategy · Facade · Dependency Injection · Repository.

SOLID	Enforcement here
S	One class per page/screen/resource. Step defs hold no locators.
O	A new scenario needs a NEW step method, not edits to existing files.
L	Concrete pages usable through their abstract base.
I	Small interfaces: seedable, report publisher, test-management client.
D	Step defs depend on abstractions; the DI container wires implementations.

Rejected outright

Inline locators in steps · `Thread.sleep` or any fixed wait · assertions in page objects · static mutable state · duplicated locators · mechanical Gherkin · editing the app to make a test pass.

Definition of done for a scenario

1. Step definitions written in the correct layer.
2. Suite run locally and green.
3. `link_implementation` called on the contract MCP.
4. `get_coverage_matrix` shows the cell as covered.

Shop QA Platform handbook · generated 2026-10-25T14:44:29.572Z · regenerate with `node mcp/contract-mcp/generate-docs.mjs`