centos系统zookeeper安装教程

1、安装前准备

```
S C:\Users\Lee\AppData\Local\Temp\scp38878\10.6.208.146_root_32044\usr\local\app\zookeeper-3.7.0\README.md (pricecalculation) - Sublime Text (UNREGISTERED)
File Edit Selection Find View Goto Tools Project Preferences Help

README.md ×

37 ## Java 8

38

39 If you are going to compile with Java 1.8, you should use a

40 recent release at u211 or above.
```

安装前确认已经安装过jdk,且jdk不低于1.8 u211版本

2、官网下载

官网地址: https://zookeeper.apache.org/

3.7版本下载地址: https://www.apache.org/dyn/closer.lua/zookeeper/zookeeper-3.7.0/apache-zookeeper-3.7.0-bin.tar.gz

2.1、联网下载

```
# 直接使用命令下载
wget https://mirrors.bfsu.edu.cn/apache/zookeeper/zookeeper-3.7.0/apache-zookeeper-3.7.0-bin.tar.gz
# 解压缩
tar -zxvf apache-zookeeper-3.7.0-bin.tar.gz
# 移动到安装目录
mv apache-zookeeper-3.7.0-bin /usr/local/app
cd /usr/local/app
mv apache-zookeeper-3.7.0-bin zookeeper-3.7.0
```

2.2、下载后上传至指定文件夹

3、修改环境变量

```
vim /etc/profile

# 末尾位置添加如下内容

export ZOOKEEPER_HOME=/usr/local/app/zookeeper-3.7.0

export PATH=$PATH:$ZOOKEEPER_HOME/bin

# 保存

wq

# 配置生效

source /etc/profile
```

4、修改zoo.cfg

```
1 # 打开配置目录
2 cd /usr/local/app/zookeeper-3.7.0/conf
3 # 将zoo_simple.cfg改名为zoo.cfg
4 mv zoo_sample.cfg zoo.cfg
5 # 修改配置
6 vim zoo.cfg
7 # 修改配置项 (快照日志目录,必须)
8 dataDir=/usr/local/zookeeper-3.4.11/dataDir
9 # 添加配置项 (事务日志目录,不配会和快照日志共享)
10 dataLogDir=/usr/local/zookeeper-3.4.11/dataLogDir
11 # 保存退出后,创建目录
12 mkdir dataDir
13 mkdir dataLogDir
```

5、Zookeeper启动与客户端连接

```
1# 服务管理命令:2zkServer.sh start|stop|restart|status3# 客户端连接:4zkCli.sh -server ${ip}:${port}5#客户端关闭:6quit #或者按 Ctrl + C
```

6、注意

6.1

Error: Could not find or load main class org.apache.zookeeper.server.quorum.QuorumPeerMain 解决方案

因为在安装时,选用了 apache-zookeeper-{version}.tar.gz 包而不是 apache-zookeeper-{version}-bin.tar.gz 包,后面使用 apache-zookeeper-{version}-bin.tar.gz (文件名包含bin)重新安装后,可以解决问题。

6.2

Problem starting AdminServer on address 0.0.0.0, port 8080 and command URL /commands 解决方案

8080端口确实被占用, 可在zoo.cfg中配置admin.serverPort=8081修改端口