CASE STUDY 25: Progressive Water Tariff Analysis

1. Problem Statement

Calculate water bills for several households using consumption slabs, a fixed fee, and an extra penalty for very high usage. Compare usage and flag excessive consumption.

2. Objectives

• Calculate the bill using progressive slabs.
• Add a fixed fee and a high-usage penalty.
• Find the household with the highest usage and flag excessive usage.


3. Assumptions

• Rates are ■5 per unit for the first 10 units, ■8 per unit for the next 10, and ■12 per unit above 20.
• Fixed fee is ■30 per household.
• Consumption above 30 units gets a ■50 penalty.
• All consumption values are non-negative.

4. Algorithm

1. Read the number of households.
2. For each household, read its name and water units.
3. Calculate slab charges, add the fixed fee, and apply the penalty if needed.
4. Display each bill and mark usage above 30 units as excessive.

5. Flowchart (text inside standard symbols)



Oval: Start/Stop | Parallelogram: Input/Output | Rectangle: Process | Diamond: Decision

6. Pseudocode

```
START
INPUT number_of_households
FOR each household:
    INPUT name, units
    IF units <= 10: charge = units * 5
    ELSE IF units <= 20: charge = 10*5 + (units-10)*8
    ELSE: charge = 10*5 + 10*8 + (units-20)*12
    bill = charge + 30
    IF units > 30: bill = bill + 50
    DISPLAY name, units, bill
END FOR
STOP
```

7. Python Source Code

```
n = int(input("Number of households: "))
highest_name = ""
highest_units = -1

for i in range(n):
    name = input("Household name: ")
    units = int(input("Water units used: "))

    if units < 0:
        print("Invalid units")
        continue
    if units <= 10:
        charge = units * 5
    elif units <= 20:
        charge = 10 * 5 + (units - 10) * 8
    else:
        charge = 10 * 5 + 10 * 8 + (units - 20) * 12

    bill = charge + 30
    if units > 30:
        bill += 50
```

```
        print("Excessive usage!")

    print(name, "bill = Rs.", bill)
    if units > highest_units:
        highest_units = units
        highest_name = name

if highest_units >= 0:
    print("Highest usage:", highest_name, highest_units, "units")
```

8. Test Cases

Household	Units	Expected result
Asha	8	■70
Balu	15	■120
Chitra	35	■360 + ■50 penalty = ■410

9. Sample Output

```
Number of households: 2
Household name: Asha
Water units used: 8
Asha bill = Rs. 70
Household name: Chitra
Water units used: 35
Excessive usage!
Chitra bill = Rs. 410
Highest usage: Chitra 35 units
```

10. Conclusion

The program calculates progressive water bills, applies penalties, and identifies excessive usage.

CASE STUDY 26: Nested Loop Examination Seating Generator

1. Problem Statement

Create a classroom seating plan using row and column numbers. Some seats are reserved, and alternate seats must remain empty.

2. Objectives

• Generate seats using nested loops.
• Mark reserved seats clearly.
• Leave alternate seats empty and show the final arrangement.


3. Assumptions

• Rows and columns are positive integers.
• Seat numbering starts from row 1 and column 1.
• Seats (1, 2) and (2, 3) are reserved when they exist.
• Seats where row + column is even are left empty as an alternate-seat rule.

4. Algorithm

1. Read rows and columns.
2. Visit each position using nested loops.
3. If the seat is reserved, print R; otherwise if it is an alternate empty seat, print X; else print S.
4. Print each row on a new line.

5. Flowchart (text inside standard symbols)



Oval: Start/Stop | Parallelogram: Input/Output | Rectangle: Process | Diamond: Decision

6. Pseudocode

```
START
INPUT rows, columns
FOR row = 1 TO rows:
    FOR col = 1 TO columns:
        IF (row,col) is reserved: PRINT R
        ELSE IF (row+col) is even: PRINT X
        ELSE: PRINT S
    END FOR
    PRINT newline
END FOR
STOP
```

7. Python Source Code

```
rows = int(input("Number of rows: "))
cols = int(input("Number of columns: "))
reserved = [(1, 2), (2, 3)]

if rows <= 0 or cols <= 0:
    print("Invalid classroom size")
else:
    for r in range(1, rows + 1):
        for c in range(1, cols + 1):
            if (r, c) in reserved:
                print("R", end=" ")
            elif (r + c) % 2 == 0:
                print("X", end=" ")
            else:
                print("S", end=" ")
        print()

print("S = Available, R = Reserved, X = Empty alternate seat")
```

8. Test Cases

Rows × Columns	Expected result
2 × 3	R and X/S markers shown in 2 rows
0 × 4	Invalid classroom size

9. Sample Output

```
Number of rows: 2
Number of columns: 3
X R X
S X R
S = Available, R = Reserved, X = Empty alternate seat
```

10. Conclusion

Nested loops help create a simple seating chart while following reserved-seat and alternate-seat rules.

CASE STUDY 27: Advanced Numeric Pattern Generator

1. Problem Statement

Print a hollow diamond pattern using a user-given size. Reject invalid sizes so the output stays properly aligned.

2. Objectives

• Use loops to print spaces and stars.
• Create a hollow diamond pattern.
• Validate the size entered by the user.


3. Assumptions

• Size must be an integer from 1 to 20.
• The pattern uses stars (*) for the border.
• For size 1, one star is displayed.

4. Algorithm

1. Read size.
2. If size is outside 1–20, display an error.
3. Print the top half and bottom half using loops.
4. Print stars only at the two border positions, except the first and last rows.

5. Flowchart (text inside standard symbols)



Oval: Start/Stop | Parallelogram: Input/Output | Rectangle: Process | Diamond: Decision

6. Pseudocode

```
START
INPUT n
IF n < 1 OR n > 20: PRINT error
ELSE:
    FOR i = 1 TO n:
        PRINT leading spaces and hollow upper row
    FOR i = n-1 DOWN TO 1:
        PRINT leading spaces and hollow lower row
STOP
```

7. Python Source Code

```
n = int(input("Enter diamond size (1-20): "))

if n < 1 or n > 20:
    print("Invalid size")
elif n == 1:
    print("*")
else:
    for i in range(n):
        spaces = n - i - 1
        if i == 0:
            print(" " * spaces + "*")
        else:
            print(" " * spaces + "*" + " " * (2*i - 1) + "*")

    for i in range(n - 2, -1, -1):
        spaces = n - i - 1
        if i == 0:
            print(" " * spaces + "*")
        else:
            print(" " * spaces + "*" + " " * (2*i - 1) + "*")
```

8. Test Cases

Input	Expected result
1	One star

Input	Expected result
4	Hollow diamond with 7 rows
0	Invalid size

9. Sample Output

```
Enter diamond size (1-20): 3
  *
 * *
*   *
 * *
  *
```

10. Conclusion

The program uses loops and conditions to print a hollow diamond and validates the given size.

CASE STUDY 28: Repeated Transaction Detection

1. Problem Statement

Read transaction IDs and amounts, identify repeated IDs, flag transactions above a set limit, and display suspicious entries.

2. Objectives

• Store transaction IDs and amounts.
• Detect duplicate transaction IDs.
• Flag amounts greater than ■10,000.


3. Assumptions

• Each transaction has an ID and a non-negative amount.
• An ID appearing more than once is treated as a duplicate.
• Any amount above ■10,000 is a threshold violation.

4. Algorithm

1. Read the number of transactions.
2. For each transaction, read ID and amount.
3. Check whether its ID was already seen and whether its amount exceeds ■10,000.
4. Print a warning for each suspicious transaction.

5. Flowchart (text inside standard symbols)



Oval: Start/Stop | Parallelogram: Input/Output | Rectangle: Process | Diamond: Decision

6. Pseudocode

```
START
INPUT n
seen = empty set
FOR each transaction:
    INPUT id, amount
    suspicious = false
    IF id in seen: suspicious = true; mark duplicate
    ADD id to seen
    IF amount > 10000: suspicious = true; mark high amount
    IF suspicious: DISPLAY transaction as suspicious
STOP
```

7. Python Source Code

```
n = int(input("Number of transactions: "))
seen = set()

for i in range(n):
    tid = input("Transaction ID: ")
    amount = float(input("Amount: "))
    reasons = []

    if tid in seen:
        reasons.append("duplicate ID")
    seen.add(tid)

    if amount > 10000:
        reasons.append("amount above Rs. 10000")

    if reasons:
        print("Suspicious:", tid, amount, "-", ", ".join(reasons))
    else:
        print("Normal:", tid, amount)
```

8. Test Cases

ID	Amount	Expected result
T01	500	Normal
T01	700	Suspicious: duplicate ID
T03	15000	Suspicious: high amount

9. Sample Output

```
Number of transactions: 3
Transaction ID: T01
Amount: 500
Normal: T01 500.0
Transaction ID: T01
Amount: 700
Suspicious: T01 700.0 - duplicate ID
Transaction ID: T03
Amount: 15000
Suspicious: T03 15000.0 - amount above Rs. 10000
```

10. Conclusion

The program detects repeated IDs and unusually large transactions for further checking.

CASE STUDY 29: Password Policy Validation Engine

1. Problem Statement

Check sample passwords against basic rules: minimum length, uppercase, lowercase, digit, special character, repeated characters, and a prohibited word.

2. Objectives

• Check each password rule.
• Explain which conditions fail.
• Display whether the password passes all rules.


3. Assumptions

• Minimum length is 8 characters.
• A valid password needs uppercase, lowercase, digit, and special character.
• Three identical characters in a row are not allowed.
• The word 'password' is prohibited, ignoring letter case.

4. Algorithm

1. Read a password.
2. Check each rule and collect failed conditions.
3. If no conditions fail, print Valid; otherwise print Invalid and the reasons.

5. Flowchart (text inside standard symbols)



Oval: Start/Stop | Parallelogram: Input/Output | Rectangle: Process | Diamond: Decision

6. Pseudocode

```
START
INPUT password
errors = empty list
CHECK length, uppercase, lowercase, digit, special character
CHECK three repeated characters
CHECK prohibited word 'password'
IF errors is empty: PRINT Valid
ELSE: PRINT Invalid and errors
STOP
```

7. Python Source Code

```
import string

password = input("Enter password: ")
errors = []

if len(password) < 8:
    errors.append("must have at least 8 characters")
if not any(ch.isupper() for ch in password):
    errors.append("needs an uppercase letter")
if not any(ch.islower() for ch in password):
    errors.append("needs a lowercase letter")
if not any(ch.isdigit() for ch in password):
    errors.append("needs a digit")
if not any(ch in string.punctuation for ch in password):
    errors.append("needs a special character")
if any(password[i] == password[i+1] == password[i+2]
       for i in range(len(password) - 2)):
    errors.append("three repeated characters are not allowed")
if "password" in password.lower():
    errors.append("must not contain the word 'password'")

if errors:
    print("Invalid password:")
    for error in errors:
        print("-", error)
```

```
else:
    print("Valid password")
```

8. Test Cases

Password	Expected result
Abc@1234	Valid password
abc	Invalid: multiple rules fail
Password123!	Invalid: prohibited word

9. Sample Output

```
Enter password: abc
Invalid password:
- must have at least 8 characters
- needs an uppercase letter
- needs a digit
- needs a special character
```

10. Conclusion

The program checks several password rules and clearly explains any failed conditions.

CASE STUDY 30: Student Email and Identifier Validation

1. Problem Statement

Validate student email addresses and registration IDs using simple formatting rules and report invalid entries.

2. Objectives

• Check email structure.
• Check registration ID structure.
• Explain invalid formatting.


3. Assumptions

• Email must contain one @, a dot after @, and no spaces.
• Registration ID format is two uppercase letters followed by four digits, such as CS2026.
• This is a basic classroom validator, not a complete internet email validator.

4. Algorithm

1. Read an email and registration ID.
2. Check the email rules.
3. Check the registration ID using length and character positions.
4. Display valid/invalid status and reasons.

5. Flowchart (text inside standard symbols)



Oval: Start/Stop | Parallelogram: Input/Output | Rectangle: Process | Diamond: Decision

6. Pseudocode

```
START
INPUT email, reg_id
IF email has one @, dot after @, and no spaces: email valid
ELSE: email invalid
IF reg_id has 2 uppercase letters + 4 digits: ID valid
ELSE: ID invalid
DISPLAY results
STOP
```

7. Python Source Code

```
email = input("Enter student email: ")
reg_id = input("Enter registration ID: ")

if (email.count("@") == 1 and " " not in email
        and "." in email.split("@")[-1]
        and email.split("@")[-1].find(".") > 0):
    print("Email: Valid")
else:
    print("Email: Invalid format")

if (len(reg_id) == 6 and reg_id[:2].isalpha()
        and reg_id[:2].isupper() and reg_id[2:].isdigit()):
    print("Registration ID: Valid")
else:
    print("Registration ID: Invalid format")
```

8. Test Cases

Email / ID	Expected result
student@college.in / CS2026	Both valid
student college.in / cs20A6	Both invalid

9. Sample Output

```
Enter student email: student@college.in
Enter registration ID: CS2026
```

```
Email: Valid
Registration ID: Valid
```

10. Conclusion

The program applies simple string checks to identify correctly formatted student emails and IDs.

CASE STUDY 31: String-Based Examination Answer Evaluation

1. Problem Statement

Compare a student's answer string with an answer key, count correct, incorrect, and unanswered questions, apply negative marking, and show the score.

2. Objectives

• Compare each answer with the key.
• Count correct, wrong, and blank answers.
• Calculate the final score using negative marking.


3. Assumptions

• Answers are entered as letters separated by spaces.
• Correct answer = +1 mark; wrong answer = -0.25 mark; blank answer = 0.
• The answer key and student answers have equal length.

4. Algorithm

1. Read the answer key and student answers.
2. Split both into lists.
3. Compare answers position by position.
4. Count correct, wrong, and blank answers, then calculate score.

5. Flowchart (text inside standard symbols)



Oval: Start/Stop | Parallelogram: Input/Output | Rectangle: Process | Diamond: Decision

6. Pseudocode

```
START
INPUT key_string, answer_string
key = split(key_string); answers = split(answer_string)
SET correct=0, wrong=0, blank=0
FOR each position:
    IF answer is blank: blank += 1
    ELSE IF answer equals key: correct += 1
    ELSE: wrong += 1
score = correct - wrong*0.25
DISPLAY counts and score
STOP
```

7. Python Source Code

```
key = input("Answer key (use spaces): ").upper().split()
answers = input("Student answers (use spaces; use - for blank): ").upper().split()

if len(key) != len(answers):
    print("Error: answer counts do not match")
else:
    correct = wrong = blank = 0
    for k, a in zip(key, answers):
        if a == "-":
            blank += 1
        elif a == k:
            correct += 1
        else:
            wrong += 1

    score = correct - wrong * 0.25
    print("Correct:", correct)
    print("Incorrect:", wrong)
    print("Unanswered:", blank)
    print("Final score:", score)
```

8. Test Cases

Key / Answers	Expected result
A B C D / A B - A	2 correct, 1 wrong, 1 blank, score 1.75
A B / A B	2 correct, score 2.0

9. Sample Output

```
Answer key (use spaces): A B C D
Student answers (use spaces; use - for blank): A B - A
Correct: 2
Incorrect: 1
Unanswered: 1
Final score: 1.75
```

10. Conclusion

The program evaluates answers, counts each response type, and calculates a score with negative marking.

CASE STUDY 32: Text-Based Invoice Data Extraction

1. Problem Statement

Read invoice records written in a simple text format and extract product code, quantity, and amount. Flag records that do not follow the format.

2. Objectives

• Split invoice text into fields.
• Extract code, quantity, and amount.
• Identify malformed records.


3. Assumptions

• Record format is CODE,QUANTITY,AMOUNT, for example P101,2,150.50.
• Quantity must be a positive integer and amount must be non-negative.
• Fields are separated by commas.

4. Algorithm

1. Read a record.
2. Split it using commas.
3. Check that there are exactly three fields.
4. Convert quantity and amount and print the values; report an error if conversion or validation fails.

5. Flowchart (text inside standard symbols)



Oval: Start/Stop | Parallelogram: Input/Output | Rectangle: Process | Diamond: Decision

6. Pseudocode

```
START
INPUT record
fields = split record by comma
IF number of fields is not 3: PRINT malformed
ELSE:
    TRY convert quantity and amount
    IF quantity <= 0 OR amount < 0: PRINT malformed
    ELSE: DISPLAY code, quantity, amount
    IF conversion fails: PRINT malformed
STOP
```

7. Python Source Code

```
record = input("Enter invoice record (CODE,QUANTITY,AMOUNT): ")
fields = record.split(",")

if len(fields) != 3:
    print("Malformed invoice record")
else:
    code = fields[0].strip()
    try:
        quantity = int(fields[1].strip())
        amount = float(fields[2].strip())
        if code == "" or quantity <= 0 or amount < 0:
            print("Malformed invoice record")
        else:
            print("Product code:", code)
            print("Quantity:", quantity)
            print("Amount: Rs.", amount)
    except ValueError:
        print("Malformed invoice record: quantity/amount is not numeric")
```

8. Test Cases

Record	Expected result
P101,2,150.50	Valid; code P101, quantity 2, amount 150.50

Record	Expected result
P102,two,90	Malformed: quantity is not numeric
P103,0,20	Malformed: quantity must be positive

9. Sample Output

```
Enter invoice record (CODE,QUANTITY,AMOUNT): P101,2,150.50
Product code: P101
Quantity: 2
Amount: Rs. 150.5
```

10. Conclusion

The program uses basic string operations and exception handling to extract invoice details safely.

CASE STUDY 33: Campus Registration Identifier Analyzer

1. Problem Statement

Check student registration IDs, extract their branch and admission year, and classify valid records.

2. Objectives

• Validate the identifier format.
• Extract branch and admission year.
• Display the classification for each ID.


3. Assumptions

• Format is BRANCH + YEAR + NUMBER, e.g. CSE2026123.
• Branch is three uppercase letters, year is four digits, and final number is three digits.
• The total ID length is 10 characters.

4. Algorithm

1. Read a registration ID.
2. Check its length and character groups.
3. If valid, extract branch, year, and number.
4. Display the parts; otherwise display Invalid ID.

5. Flowchart (text inside standard symbols)



Oval: Start/Stop | Parallelogram: Input/Output | Rectangle: Process | Diamond: Decision

6. Pseudocode

```
START
INPUT reg_id
IF length is 10 AND first 3 are uppercase letters
   AND next 4 are digits AND last 3 are digits:
    branch = first 3 characters
    year = next 4 characters
    number = last 3 characters
    DISPLAY branch, year, number
ELSE: DISPLAY Invalid ID
STOP
```

7. Python Source Code

```
reg_id = input("Enter registration ID: ")

if (len(reg_id) == 10 and reg_id[:3].isalpha()
        and reg_id[:3].isupper() and reg_id[3:7].isdigit()
        and reg_id[7:10].isdigit()):
    branch = reg_id[:3]
    year = reg_id[3:7]
    number = reg_id[7:10]
    print("Branch:", branch)
    print("Admission year:", year)
    print("Student number:", number)
else:
    print("Invalid registration ID")
```

8. Test Cases

Input	Expected result
CSE2026123	Valid: CSE, 2026, 123
cs2026123	Invalid: wrong length/branch case
CSE20A6123	Invalid: year contains a letter

9. Sample Output

```
Enter registration ID: CSE2026123
Branch: CSE
Admission year: 2026
Student number: 123
```

10. Conclusion

The program separates a valid campus ID into branch, admission year, and student number.

CASE STUDY 34: Student Feedback Sentiment Scoring

1. Problem Statement

Analyse feedback sentences using positive and negative keywords, calculate a simple score, and classify each sentence.

2. Objectives

• Count positive and negative words.
• Calculate a sentiment score.
• Classify feedback as Positive, Negative, or Neutral.


3. Assumptions

• Positive words: good, helpful, excellent, clear.
• Negative words: bad, confusing, poor, slow.
• Score = positive count – negative count. Score above 0 is Positive, below 0 is Negative, and 0 is Neutral.

4. Algorithm

1. Read a feedback sentence and convert it to lowercase.
2. Count positive and negative keywords found in the sentence.
3. Calculate the score.
4. Classify the feedback based on the score and display the result.

5. Flowchart (text inside standard symbols)



Oval: Start/Stop | Parallelogram: Input/Output | Rectangle: Process | Diamond: Decision

6. Pseudocode

```
START
INPUT feedback
text = lowercase(feedback)
positive_count = count positive keywords
negative_count = count negative keywords
score = positive_count - negative_count
IF score > 0: sentiment = Positive
ELSE IF score < 0: sentiment = Negative
ELSE: sentiment = Neutral
DISPLAY counts, score, sentiment
STOP
```

7. Python Source Code

```
feedback = input("Enter student feedback: ").lower()
positive_words = ["good", "helpful", "excellent", "clear"]
negative_words = ["bad", "confusing", "poor", "slow"]

positive_count = 0
negative_count = 0

for word in positive_words:
    if word in feedback:
        positive_count += 1
for word in negative_words:
    if word in feedback:
        negative_count += 1

score = positive_count - negative_count
if score > 0:
    sentiment = "Positive"
elif score < 0:
    sentiment = "Negative"
else:
    sentiment = "Neutral"

print("Positive keywords:", positive_count)
print("Negative keywords:", negative_count)
```

```
print("Score:", score)
print("Sentiment:", sentiment)
```

8. Test Cases

Feedback	Expected result
The class was good and clear	Positive (score 2)
The lesson was confusing and slow	Negative (score -2)
The class starts at ten	Neutral (score 0)

9. Sample Output

```
Enter student feedback: The class was good and clear
Positive keywords: 2
Negative keywords: 0
Score: 2
Sentiment: Positive
```

10. Conclusion

The program demonstrates a beginner-friendly keyword method for scoring and classifying student feedback.