

Lecture #37

Friday: HKN surveys. [Extra points awarded to those who participate!](#)

Today: A little side excursion into nitty-gritty stuff: Storage management.

Last modified: Mon Nov 26 15:00:50 2012

CS61B: Lecture #37 1

Scope and Lifetime

- *Scope* of a declaration is portion of program text to which it applies (is *visible*).
 - Need not be contiguous.
 - In Java, is static: independent of data.
- *Lifetime* or *extent* of storage is portion of program execution during which it exists.
 - Always contiguous
 - Generally dynamic: depends on data
- *Classes of extent*:
 - *Static*: entire duration of program
 - *Local* or *automatic*: duration of call or block execution (local variable)
 - *Dynamic*: From time of allocation statement (**new**) to deallocation, if any.

Last modified: Mon Nov 26 15:00:50 2012

CS61B: Lecture #37 2

Explicit vs. Automatic Freeing

- Java has no means to free dynamic storage.
- However, when no expression in any thread can possibly be influenced by or change an object, it might as well not exist:

```
IntList wasteful ()
{
    IntList c = new IntList (3, new IntList (4, null));
    return c.tail;
    // variable c now deallocated, so no way
    // to get to first cell of list
}
```

- At this point, Java runtime, like Scheme's, recycles the object *c* pointed to: *garbage collection*.

Last modified: Mon Nov 26 15:00:50 2012

CS61B: Lecture #37 3

Under the Hood: Allocation

- Java pointers (references) are represented as integer addresses.
- Corresponds to machine's own practice.
- In Java, cannot convert integers \leftrightarrow pointers,
- But crucial parts of Java runtime implemented in *C*, or sometimes machine code, where you can.
- Crude allocator in *C*:


```
char store[STORAGE_SIZE]; // Allocated array
size_t remainder = STORAGE_SIZE;

/** A pointer to a block of at least N bytes of storage */
void* simpleAlloc (size_t n) { // void*: pointer to anything
    if (n > remainder) ERROR ();
    remainder = (remainder - n) & ~0x7; // Make multiple of 8
    return (void*) (store + remainder);
}
```

Last modified: Mon Nov 26 15:00:50 2012

CS61B: Lecture #37 4

Example of Storage Layout: Unix



- OS gives way to turn chunks of unallocated region into heap.
- Happens automatically for stack.

Last modified: Mon Nov 26 15:00:50 2012

CS61B: Lecture #37 5

Explicit Deallocating

- C/C++ normally require explicit deallocation, because of
 - Lack of run-time information about what is array
 - Possibility of converting pointers to integers.
 - Lack of run-time information about *unions*:


```
union Various {
    int Int;
    char* Pntr;
    double Double;
} X; // X is either an int, char*, or double
```
- Java avoids all three problems; automatic collection possible.
- Explicit freeing can be somewhat faster, but rather error-prone:
 - Memory corruption
 - Memory leaks

Last modified: Mon Nov 26 15:00:50 2012

CS61B: Lecture #37 6


Free Lists

- Explicit allocator grabs chunks of storage from OS and gives to applications.
- Or gives recycled storage, when available.
- When storage is freed, added to *free list* data structure to be re-cycled.
- Used both for explicit freeing and some kinds of automatic garbage collection.
- Problem: free memory *fragments*.

Last modified: Mon Nov 26 15:00:50 2012

CS61B: Lecture #37 7

Boundary Tag Methods



```
G1 = malloc(96);
X = malloc(115);
Y = malloc(156);
G2 = malloc(19);
Z = malloc(26);
G3 = malloc(155);
free(G1); free(G3); free(G2);
```

Admin word


Size Free?/Prev Free?

Last modified: Mon Nov 26 15:00:50 2012

CS61B: Lecture #37 8

Simplifying Coalescence: The Buddy System


- Allocate in powers of 2.
- Coalesce only with your buddy:
 - For object of size 2^n at byte # M , buddy at byte # $(M \oplus (1 \ll n))$.
 - Just need a bit to indicate if it is allocated, plus list of free blocks for each n .



Last modified: Mon Nov 26 15:00:50 2012

CS61B: Lecture #37 9

Buddy System at Work




Last modified: Mon Nov 26 15:00:50 2012

CS61B: Lecture #37 10

Garbage Collection: Reference Counting

- Idea: Keep count of number of pointers to each object. Release when count goes to 0.




Last modified: Mon Nov 26 15:00:50 2012

CS61B: Lecture #37 11

Garbage Collection: Mark and Sweep

Roots (locals + statics)



1. Traverse and **mark** graph of objects.
2. **Sweep** through memory, freeing unmarked objects.

Before sweep:

A	B*	C	D*	E*	F	G*
42	D	G	F	A	7	G

After sweep:

B	D	G	D	7	G	D	G

Last modified: Mon Nov 26 15:00:50 2012

CS61B: Lecture #37 12

Copying Garbage Collection

- Mark-and-sweep algorithms don't move any existing objects—pointers stay the same.
- The total amount of work depends on the amount of memory swept—i.e., the total amount of active (non-garbage) storage + amount of garbage. Not necessarily a big hit: the garbage had to be active at one time, and hence there was always some “good” processing in the past for each byte of garbage scanned.
- Another approach: *copying garbage collection* takes time proportional to amount of active storage:
 - Traverse the graph of active objects breadth first, *copying* them into a large contiguous area (called “to-space”).
 - As you copy each object, mark it and put a *forwarding pointer* into it that points to where you copied it.
 - The next time you have to copy a marked object, just use its forwarding pointer instead.
 - When done, the space you copied from (“from-space”) becomes the next to-space; in effect, all its objects are freed in constant time.

Copying Garbage Collection Illustrated

