HCM University of Technology

Machine Elements

ME2007

Lab Report

Submitted To:

Phan Dinh Huan

PhD

Faculty of Mechanical Engineering

Submitted By :

Nguyen Quy Khoi

1852158

CC02

HK192

Contents

List of Tables

List of Figures

Chapter 1

Slip coefficient and Slip curve of Belt drive

1.1 Nomenclature

a	center distance, mm	n	rotational speed, rpm
f	coefficient of friction	Q	load, $kg \cdot F$
d	diameter, mm	α	wrap angle, $^\circ$
F_0	initial tension, N	β	slack angle due to load Q, $^\circ$
F_{ms}	friction force, N	Δh	difference between h_i and h_f, mm
F_t	tangential force, N	ϕ	drag coefficient
g	gravitational acceleration at sea level, m/s^2	$\overline{\xi}$	average slip coefficient kW
		ξ	slip coefficient
h_f	distance between outer sides of the belt after applying load Q, mm	$_1$	subscript for driving pulley
		$_2$	subscript for driven pulley
h_i	distance between outer sides of the belt before applying load Q, mm		

1.2 Purpose

1. Investigate slip in belt drives
2. Find relative slip coefficient and conduct experiment to find ξ
3. Find F_0
4. Draw slip curve with respect to Q

1.3 Safety Procedures

Students must follow safety rules in the lab.

1.4 Conduct Experiment

1.4.1 Find parameters of the experiment kit

- $d_1 = 67.8\,\text{mm}$, $d_2 = 165\,\text{mm}$, $a = 315\,\text{mm}$
- Belt type: flat belt
- $\alpha_1 = 180 - 57 \times \dfrac{d_2 - d_1}{a} \approx 162.3°$
- $\alpha_2 = 180 + 57 \times \dfrac{d_2 - d_1}{a} \approx 197.6°$

1.4.2 Find F_0

- $h_i = 124\,\text{mm}$, $h_f = 94\,\text{mm}$, $Q = 4.1\,\text{kg} \cdot \text{F}$
- $\Delta_h = |h_f - f_i| = 30\,\text{mm}$, $\beta = \arctan \dfrac{2\Delta_h}{a} \approx 10.78°$
- $F_0 = \dfrac{Qg}{2\sin\beta} \approx 107.48\,\text{N}$

1.4.3 Measurements

Using the formulas $\xi = 1 - \dfrac{d_2 n_2}{d_1 n_1}$ and $\phi = \dfrac{F_t}{2F_0}$, we obtain the following table: Averaging the values of ξ yields $\bar{\xi} \approx 0.0198$

No.	F_0 N	n_1 rpm	n_2 rpm	ξ	F_t N	ϕ
1	107.48	283.62	114.04	0.018	3.1	0.014
2	107.48	330.47	133.35	0.018	8.8	0.041
3	107.48	273.83	110.27	0.02	14.4	0.067
4	107.48	307.52	123.71	0.021	20.2	0.094
5	107.48	354.42	142.43	0.022	22.1	0.103

Table 1.1: Observed data

1.4.4 Draw the slip curve graph

From the data above, we can approximate the best fitted line through the data points (assuming linearity since ϕ does not reach critical value)



Figure 1.1: Slip curve of belt drive

1.5 Conclusions

In summary:

- Slip coefficient from experiment is in allowable range ($0.01 \div 0.02$).
- The slip curve is in agreement with theory (error is smaller than 5%). Since ϕ does not exceed critical value (the motor is frequency-controlled), we can safely assume linearity for the curve.
- Possible errors:
  - manually measure dimensions in the kit.
  - rounding.
  - incorrect reading of rotational speeds.
- The slip coefficient and slip curve is considerably accurate due to reliable instrument

1.6 Review questions

1. There are

Chapter 2

Tension on Bolts

2.1 Nomenclature

$[F_{cb}]$	tension force at failure of common bolt, N
$[F_{sb}]$	tension force at failure of steel bolt, N
$[\sigma_{cb}]$	tension at failure of common bolt, MPa
$[\sigma_{sb}]$	tension at failure of steel bolt, MPa
d	nominal diameter of M8 bolt, mm
F_c	tension force of hydraulic cylinder
F_{cb}	tension force at failure of common bolt, N
F_{sb}	tension force at failure of steel bolt, N

2.2 Purpose

Provide basic knowledge on conducting experiment regarding ultimate strength of materials

2.3 Safety Procedures

Close the machine door before every operation.

2.4 Conduct Experiment

No.	Experiment with $d = 8$ mm	
	F_{sb}	F_{cb}
1	33898	37377
2	33574	37053
3	34211	36426
4	33727	37053
5	34211	36426
Average	33323.4	36867

Table 2.1: Tension force at failure of common and steel bolts

2.5 Data graphs



Figure 2.1: Tension force at failure of common bolt



Figure 2.2: Tension force at failure of steel bolt