

Convert markdown to pdf using themekit

2024/12/09

1. Special Note

Because `typst 0.12` does not currently provide a function to obtain the operating system type, this template cannot pre-set the preferred font for the user. You need to check and set the font before execution. The details are described in the [Fonts] section in `userguide.pdf`.

The font settings are saved in the `themekit/0.5.3/fonts.typst`.

2. Requirements and Installation

1. pandoc `3.5` Download and installation instructions, <https://pandoc.org/installing.html>
2. typst `0.12.0` Download and installation instructions, <https://github.com/typst/typst/releases/tag/v0.12.0>

First download pandoc and typst, and put them in the system environment variable `PATH` where they can be found.

- MacOS/Linux OS: You can use command line software tools such as `brew`, `apt`, `mise`, `asdf`, etc. to install.
- Windows OS: You can use command line software tools such as `scoop`, `Chocolatey`, etc. to install. Or after downloading, add the directories where the pandoc and typst executable programs are located to the system variable `PATH`.

3. Installing themekit

Copy or link to the typst local package directory. The default directory of typst local package is different for different operating systems, as follows:

Install `themekit` as typst local package. The directory specification of typst local package is: `{data-dir}/typst/packages/{namespace}/{name}/{version}`. The `{data-dir}` is different for different operating systems, as follows:

- linux: `$XDG_DATA_HOME` or `~/.local/share`
- maxos: `~/Library/Application Support`

- whidowns: `%APPDATA%`

According to convention, `{namespace}` is `local`, the name of this template package is `themekit`, and the current `{version}` is `0.5.3`.

Copy or link the themekit directory to the `{data-dir}/typst/packages/local` directory.

```
mkdir -p "{data-dir}/typst/packages/local"
cp -R themekit "{data-dir}/typst/packages/local"
# or
ln -s themekit "{data-dir}/typst/packages/local/themekit"
```

Change `{data-dir}` to the directory corresponding to your OS.

4. How To Run

```
cd markdown/FILES/DIRECTORY
template="{data-dir}/typst/packages/local/themekit/0.5.3/pandoc/ANY_PANDOC_
TEMPLATE.typst"
pandoc_args="markdown_mmd+emoji+strikeout+fancy_lists+task_lists+implicit_
figures+link_attributes+inline_notes+tex_math_single_backslash+simple_tables+
grid_tables+multiline_tables+table_captions+yaml_metadata_block-blank_before_
blockquote"
cat markdownfiles.md |
  pandoc --from $pandoc_args \
  -t pdf --pdf-engine typst --template="$template" \
  -o "OUTPUT.pdf"
```

Change `{data-dir}` to the directory corresponding to your operating system. Any typst template file in the pandoc directory, distinguished by [page size](#), [dark/light background](#), [code highlight theme](#).

There are example shell scripts in the directory, see `{data-dir}/typst/packages/themekit/0.5.3/examples.sh`

5. Integration with Sublime Text

When developing this template, I edited markdown based on the Sublime Text text editor and used the build system to execute the above commands. For more operation instructions and style design instructions for the template, see [Integration with Sublime Text](#) in `userguide.pdf`

`example.markdown.sublime-build` is the build command of Sublime Text 4. Modify `THEMEKIT_DIR` to the directory where themekit is located, that is, the parent directory of themekit. After modification, save it to the Sublime Text `Packages/User` directory. After editing the markdown file in Sublime Text, `cmd` + `shift` + `p` opens the command palette, input `pdf` or `typst`, select the corresponding conversion command, and press `enter`. PDF, png images, and typst documents can be generated.