

GTOS Detailed Volume - Volume 04

Portal And Experience Architecture

GTOS Enterprise Engineering Handbook - Final Edition 1.0

Source Chapters

- Web Shop — Portal Orientation and Information Architecture
- Web Shop — Routes, Pages, Components, and BFF Contracts
- Web Shop — Identity, Session, Authorization, and Trust Boundaries
- Web Shop — UX States, Accessibility, Localization, Analytics, and E2E
- Web Admin — Portal Orientation and Information Architecture
- Web Admin — Routes, Pages, Components, and BFF Contracts
- Web Admin — Identity, Session, Authorization, and Trust Boundaries
- Web Admin — UX States, Accessibility, Localization, Analytics, and E2E
- Web Operator — Portal Orientation and Information Architecture
- Web Operator — Routes, Pages, Components, and BFF Contracts
- Web Operator — Identity, Session, Authorization, and Trust Boundaries
- Web Operator — UX States, Accessibility, Localization, Analytics, and E2E
- Warehouse Operator — Portal Orientation and Information Architecture
- Warehouse Operator — Routes, Pages, Components, and BFF Contracts
- Warehouse Operator — Identity, Session, Authorization, and Trust Boundaries
- Warehouse Operator — UX States, Accessibility, Localization, Analytics, and E2E
- Customer Portal — Portal Orientation and Information Architecture
- Customer Portal — Routes, Pages, Components, and BFF Contracts
- Customer Portal — Identity, Session, Authorization, and Trust Boundaries
- Customer Portal — UX States, Accessibility, Localization, Analytics, and E2E
- Provider Portal — Portal Orientation and Information Architecture
- Provider Portal — Routes, Pages, Components, and BFF Contracts
- Provider Portal — Identity, Session, Authorization, and Trust Boundaries
- Provider Portal — UX States, Accessibility, Localization, Analytics, and E2E
- Partner Portal — Portal Orientation and Information Architecture
- Partner Portal — Routes, Pages, Components, and BFF Contracts

- Partner Portal — Identity, Session, Authorization, and Trust Boundaries
- Partner Portal — UX States, Accessibility, Localization, Analytics, and E2E
- Developer Portal — Portal Orientation and Information Architecture
- Developer Portal — Routes, Pages, Components, and BFF Contracts
- Developer Portal — Identity, Session, Authorization, and Trust Boundaries
- Developer Portal — UX States, Accessibility, Localization, Analytics, and E2E
- WhatsApp Admin — Portal Orientation and Information Architecture
- WhatsApp Admin — Routes, Pages, Components, and BFF Contracts
- WhatsApp Admin — Identity, Session, Authorization, and Trust Boundaries
- WhatsApp Admin — UX States, Accessibility, Localization, Analytics, and E2E
- ESG Dashboard — Portal Orientation and Information Architecture
- ESG Dashboard — Routes, Pages, Components, and BFF Contracts
- ESG Dashboard — Identity, Session, Authorization, and Trust Boundaries
- ESG Dashboard — UX States, Accessibility, Localization, Analytics, and E2E
- Quality Dashboard — Portal Orientation and Information Architecture
- Quality Dashboard — Routes, Pages, Components, and BFF Contracts
- Quality Dashboard — Identity, Session, Authorization, and Trust Boundaries
- Quality Dashboard — UX States, Accessibility, Localization, Analytics, and E2E
- Scenario Simulator — Portal Orientation and Information Architecture
- Scenario Simulator — Routes, Pages, Components, and BFF Contracts
- Scenario Simulator — Identity, Session, Authorization, and Trust Boundaries
- Scenario Simulator — UX States, Accessibility, Localization, Analytics, and E2E
- Mobile Applications — Portal Orientation and Information Architecture
- Mobile Applications — Routes, Pages, Components, and BFF Contracts
- Mobile Applications — Identity, Session, Authorization, and Trust Boundaries
- Mobile Applications — UX States, Accessibility, Localization, Analytics, and E2E
- Portal Cross-Route and Persona Matrix

Web Shop — Portal Orientation and Information Architecture

Metadata	Value
Volume	4
Chapter ID	V04-P01-00
Subject	WebShopPortal
Status	Generated First-Draft Architecture Skeleton - Domain-Specific Expansion Required
Content maturity	TEMPLATE_DERIVED_REFERENCE_SKELETON unless repository citations prove otherwise
Default implementation classification	REFERENCE_ARCHITECTURE / REQUIRES_REPOSITORY_REVIEW
Accountable owner	Portal Architecture / Web Shop
Evidence rule	No implementation claim without inspected executable evidence
Repository	chinair88-prog/allinb2c

1. Executive Orientation

This chapter defines how GTOS shall **define personas, navigation, route ownership, domain dependencies and experience boundaries for customers and anonymous shoppers, covering catalog, marketplace, pricing, cart, checkout, order, payment, delivery, returns.**

The specification separates reality, observations, knowledge, Decisions, Intent, execution, and outcomes. A component name, database row, UI label, AI answer, or workflow state does not acquire authority merely because it is visible or technically convenient.

Reality or external outcome

- ≠ Observation
- ≠ Claim
- ≠ derived Perspective
- ≠ Prediction
- ≠ Recommendation
- ≠ authorized Decision
- ≠ execution Intent

1.1 Accountable ownership

The accountable owner is **Portal Architecture / Web Shop**. Supporting applications, shared infrastructure, integration adapters, analytics, and AI coordinate or present the capability but shall not silently own its authoritative propositions.

1.2 Scope

- create and identify the subject
- validate evidence and policy
- make authorized Decisions
- execute typed Commands
- publish completed-fact Events
- query current and historical perspectives
- correct and reconcile outcomes

1.3 Non-goals

- treating a registered Gradle module, catalog record, README, frontend route, migration plan, or generated report as proof of end-to-end implementation;

- direct cross-Domain database writes;
- generic status values that combine lifecycle, approval, provider, document, payment, dispute, and correction state;
- silent replacement of history;
- AI-created authority or fabricated external outcomes.

2. Ubiquitous Language and Subject Model

Subject	Required interpretation
WebShopPortal	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit
WebShopPortalVersion	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit
WebShopPortalDecision	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit
WebShopPortalEvidenceSet	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit
WebShopPortalException	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit

Reference aggregate:

```
WebShopPortal {
  subjectId
  tenantId
  organizationContext
  sourceIdentityRefs[]
  sourceVersionRefs[]
  lifecycleState
  relationshipRefs[]
  decisionRefs[]
  intentRefs[]
  evidenceSetRef
  knowledgeCutoff
  policyRefs[]
  authorityRef
  jurisdictionRefs[]
  createdAt
  effectiveAt
  updatedAt
  version
  correctionOf?
  correlationId
}
```

2.1 Core invariants

- Stable identity precedes relationship, state, and cross-system correlation.
- Effective time and recorded time remain distinct where business truth changes over time.
- Recommendation, Decision, Intent, execution, and outcome are separate concepts.
- No Portal, report, search index, cache, workflow, or AI Agent becomes a shadow owner of Domain truth.
- Binding submitted, approved, issued, accepted, or signed versions are immutable.
- Corrections append governed facts and preserve the original record.
- External authority and provider outcomes retain their source and qualification.
- Tenant and represented-principal context come from trusted authentication and mandate evaluation.
- Retried writes are idempotent and concurrency guarded.
- Outcome Unknown is explicit and reconciled before risky duplicate execution.

2.2 Required standards

- stable identifiers
- typed contracts
- immutable binding versions
- transactional outbox
- idempotent Commands
- explicit Outcome Unknown
- correction lineage

- machine-verifiable conformance

3. Actors, Roles, and Authority

A conformant design distinguishes:

- the natural person acting;
- the service or AI identity invoking a Tool;
- the organization or principal represented;
- the role or relationship granting context;
- the mandate or delegation granting action authority;
- the Policy and jurisdiction limiting the action;
- the reviewer or approver responsible for a binding Decision.

Authority is evaluated at action time. Authentication alone does not grant business authority. Cached permissions and browser-supplied tenant headers are insufficient for high-impact actions.

4. Lifecycle and State Model

State	Semantics
PROPOSED	Distinct governed condition with entry, exit, timeout, correction and authority semantics
VALIDATION_PENDING	Distinct governed condition with entry, exit, timeout, correction and authority semantics
APPROVAL_PENDING	Distinct governed condition with entry, exit, timeout, correction and authority semantics
ACTIVE	Distinct governed condition with entry, exit, timeout, correction and authority semantics
SUSPENDED	Distinct governed condition with entry, exit, timeout, correction and authority semantics
CORRECTION_PENDING	Distinct governed condition with entry, exit, timeout, correction and authority semantics
RETIRED	Distinct governed condition with entry, exit, timeout, correction and authority semantics

```
stateDiagram-v2
    [*] --> PROPOSED
    PROPOSED --> VALIDATION_PENDING
    VALIDATION_PENDING --> APPROVAL_PENDING
    APPROVAL_PENDING --> ACTIVE
    ACTIVE --> SUSPENDED
    SUSPENDED --> CORRECTION_PENDING
    CORRECTION_PENDING --> RETIRED
```

The diagram is a primary reading path. Real implementations may add parallel review, amendment, appeal, timeout, suspension, partial completion, reconciliation, correction, and terminal failure without collapsing their meaning.

4.1 Transition rules

- transition through a typed, authorized Command;
- require exact expected version where concurrent change matters;
- record actor, represented principal, mandate, Policy, reason, and Evidence;
- use an idempotency key for retried writes;
- publish a completed-fact Event after durable state change;
- expose Outcome Unknown for unresolved external completion;
- preserve original and corrected states in historical reconstruction.

5. Decision, Evidence, and Knowledge Cutoff

Reference Decision:

```
Decision {
    decisionId
```

```

decisionType
subjectRef
sourceVersionRefs[]
knowledgeCutoff
evidenceSetRef
policyVersionRefs[]
recommendationRefs[]
principalId
representedOrganizationId
mandateRef
rationale
outcome
decidedAt
effectiveAt
correctionOf?
}

```

Evidence records identify issuer or observer, subject, version, observed time, received time, effective interval, integrity, confidence, qualification, contradiction, correction, retention, residency, and access class. A recommendation may assist the Decision but cannot promote itself to the Decision.

6. Commands, Events, Queries, and Contracts

Reference Commands:

- CreateWebShopPortal
- ValidateWebShopPortal
- ApproveWebShopPortal
- ActivateWebShopPortal
- SuspendWebShopPortal
- CorrectWebShopPortal
- RetireWebShopPortal

Reference Events:

- WebShopPortalCreated
- WebShopPortalValidated
- WebShopPortalApproved
- WebShopPortalActivated
- WebShopPortalSuspended
- WebShopPortalCorrected
- WebShopPortalRetired

Reference queries:

- GetWebShopPortal
- ListWebShopPortalRecords
- GetWebShopPortalTimeline
- GetWebShopPortalEvidence
- GetWebShopPortalDecisionPackage
- GetWebShopPortalExceptions
- GetWebShopPortalAuditTrail

Reference API surface:

```

POST /api/v1/webshopportal/commands
GET  /api/v1/webshopportal/{id}
GET  /api/v1/webshopportal/{id}/timeline
GET  /api/v1/webshopportal/{id}/evidence
GET  /api/v1/webshopportal/{id}/decisions
POST /api/v1/webshopportal/{id}/exceptions
POST /api/v1/webshopportal/{id}/corrections

```

These endpoints are reference contracts, not claims that exact routes exist.

7. Workflow, Failure, and Compensation

flowchart TD

```

A[Validate identity version and authority] --> B[Collect required evidence]
B --> C[Policy and evidence gates pass?]
C -- No --> D[Open exception or request correction]
D --> B

```

```

C -- Yes --> E[Record Decision or execution Intent]
E --> F[Execute Domain command or external request]
F --> G{Outcome known?}
G -- Success --> H[Record fact and publish Event]
G -- Failure --> I[Record failure and compensation options]
G -- Unknown --> J[Enter Outcome Unknown]
J --> K[Query source or wait for verified callback]
K --> G
H --> L[Update projections and downstream workflow]

```

Representative failure modes:

- stale or wrong source version
- duplicate submission or replay
- external timeout after possible success
- contradictory source observations
- lost Event after committed state
- approval or mandate revoked during execution
- downstream action before a mandatory gate
- partial completion across multiple subjects
- evidence later retracted or corrected
- tenant, facility, channel or jurisdiction mismatch

Recovery shall query the authoritative source before duplicate execution, preserve partial success, use compensating Intent rather than destructive rewrite, publish corrections, quarantine high-impact ambiguity, and record affected downstream subjects.

8. Data and Persistence Architecture

Reference table families:

Table family	Purpose
webshopportal_aggregate	authoritative subject
webshopportal_version	immutable submitted, approved, issued, or signed versions
webshopportal_relationship	governed relationships
webshopportal_decision	binding Decisions and rationale
webshopportal_evidence_link	provenance and evidence relationships
webshopportal_event_outbox	transactional Event publication
webshopportal_idempotency	duplicate-write protection
webshopportal_exception	exception, claim, dispute, or hold
webshopportal_correction	correction and supersession lineage
webshopportal_audit	privileged action evidence

The owning service controls schema and migration. Cross-Domain references use stable identifiers or contracts. Analytics, reports, caches, search, and vector indexes remain projections. Backup, restore, retention, legal hold, privacy, residency, and decommissioning requirements are explicit.

9. Portal and Experience Requirements

- Web Shop: primary experience for customers and anonymous shoppers.
- Operator and support views: diagnose failed or ambiguous journeys without assuming Domain ownership.
- Domain services: own authoritative data and action eligibility; the Portal consumes typed contracts.

Every Portal displays exact version, owner, state, freshness, required action, and uncertainty. It supports loading, empty, partial, stale, denied, error, timeout, and Outcome Unknown states; accessibility; locale, currency, unit, date, and RTL/LTR correctness; evidence audit; safe retry; and correction history.

10. AI Participation and Tool Governance

Permitted AI tasks:

- extract and classify evidence
- detect anomalies and missing fields
- summarize timelines and contradictions

- recommend next actions with sources and uncertainty

AI shall not own Domain records, grant itself authority, suppress contradictions, silently edit approved versions, fabricate external outcomes, or execute high-impact actions outside typed Tools, policy, approval, idempotency, sandbox, and outcome observation.

Every Agent Run records source context, prompt/model/tool versions, structured output, confidence and limitations, Policy result, approval, Tool calls, provider responses, final outcome, and recovery actions.

11. Security, Privacy, and Trust Boundaries

- least privilege and separation of duties
- tenant, organization, facility, channel and jurisdiction isolation
- integrity protection for binding evidence
- verified external callbacks and anti-replay controls

Additional controls include secret isolation, callback signature verification, audit of privileged action, emergency-access review, sensitive-data minimization, purpose limitation, and threat models for impersonation, tampering, replay, confused deputy, fraud, prompt injection, and exfiltration.

12. Reliability, SLOs, and Operations

SLI	Reference objective
authoritative read availability	99.9% monthly unless a stricter tier applies
acknowledged Command durability	no acknowledged write may be silently lost
Event publication	99.9% within five minutes after committed fact
duplicate prevention	100% for same tenant, Command class, and idempotency key
binding Decision audit completeness	100%
state-state detection	bounded by business deadline

Dashboards and runbooks cover backlog, error budget, dependency failure, retry budget, DLQ, workflow stall, provider outage, reconciliation, capacity, backup/restore, release/rollback, incident command, and post-incident correction.

13. Testing and Continuous Conformance

- aggregate invariant and transition tests
- authorization, delegation, separation-of-duties and tenant-isolation tests
- idempotency and optimistic-concurrency tests
- database migration, key, constraint and rollback tests
- contract, outbox/inbox, duplicate, replay and DLQ tests
- workflow restart, timeout and compensation tests
- Portal E2E tests for success, partial, stale, denied, error and Outcome Unknown states
- accessibility, locale, currency, unit and RTL/LTR tests
- security adversarial, fraud and data-exfiltration tests
- AI evaluation, prompt-injection, policy-bypass and unauthorized-tool tests
- historical reconstruction, correction and audit-completeness tests
- performance, capacity, recovery and operational exercise tests

Release evidence links each invariant and control to the test, environment, input data, result, owner, and artifact proving it. Generated test counts never replace semantic coverage.

14. Repository Review Boundary

- This chapter is a repository-review specification. Exact executable implementation has not been inspected for every target behavior.
- Registered modules, catalog entries, README claims, frontend contracts, or plans are not proof of complete implementation.

Area	Classification
target aggregate, API, tables, state and workflow in this chapter	REFERENCE_ARCHITECTURE
registered module or catalog claim	DOCUMENTATION_ONLY_CLAIM until source inspection
uninspected integration	REQUIRES_REPOSITORY_REVIEW
behavior proven in another repository-grounded chapter	retain that chapter's evidence and classification
contradictory ownership or path claims	CONFLICT_REQUIRES_CANONICALIZATION

No statement upgrades implementation status merely because a file, directory, module name, frontend contract, database entry, plan, or report exists.

15. Worked Conformance Scenario

An authorized principal initiates a Command against an exact subject version. The service validates identity, tenant, mandate, Policy, Evidence, and idempotency. It records the state transition and outbox entry atomically. If an external dependency participates, timeout produces Outcome Unknown; reconciliation queries the source or waits for a verified callback instead of repeating the action blindly.

Portals show source, freshness, version, required action, and uncertainty. AI may extract, compare, summarize, detect anomalies, and recommend through typed Tools, but cannot own the subject or fabricate success. Later correction appends new facts, identifies affected projections and workflows, and preserves the historical Decision context.

16. Conformance Checklist

- ☐ stable identity and proposition ownership are explicit;
- ☐ authority and mandate are evaluated at action time;
- ☐ state, Recommendation, Decision, Intent, execution, and outcome remain distinct;
- ☐ Commands are typed, authorized, idempotent, and version guarded;
- ☐ Events describe completed facts;
- ☐ Evidence includes provenance, time, integrity, qualification, and correction;
- ☐ external outcomes retain their authority source;
- ☐ Portals show freshness and uncertainty;
- ☐ AI is bounded by typed Tools, Policy, approval, and outcome observation;
- ☐ security, tenant, facility, channel, and jurisdiction boundaries are enforced;
- ☐ Outcome Unknown and reconciliation exist where needed;
- ☐ corrections preserve history;
- ☐ tests prove invariants and recovery;
- ☐ implementation status is not upgraded without executable evidence.

17. Status Vocabulary

Status	Meaning
VERIFIED_IMPLEMENTED	Executable source and relevant behavior were inspected.
IMPLEMENTED_WITH_GAP	Executable behavior exists with a material governance or completeness gap.
PARTIAL_IMPLEMENTATION	Only part of the target capability is evidenced.
REFERENCE_ARCHITECTURE	Normative target behavior; no claim that it exists today.
PLANNED_NOT_IMPLEMENTED	Explicitly planned but not evidenced as executable.
DOCUMENTATION_ONLY_CLAIM	Documentation or client contract claims behavior without verified backend evidence.
CONFLICT_REQUIRES_CANONICALIZATION	Sources disagree and no final owner has been established.
REQUIRES_REPOSITORY_REVIEW	Necessary executable evidence has not yet been inspected.

Web Shop — Routes, Pages, Components, and BFF Contracts

Metadata	Value
Volume	4
Chapter ID	V04-P01-01
Subject	WebShopRouteRegistry
Status	Generated First-Draft Architecture Skeleton - Domain-Specific Expansion Required
Content maturity	TEMPLATE_DERIVED_REFERENCE_SKELETON unless repository citations prove otherwise
Default implementation classification	REFERENCE_ARCHITECTURE / REQUIRES_REPOSITORY_REVIEW
Accountable owner	Portal Architecture / Web Shop
Evidence rule	No implementation claim without inspected executable evidence
Repository	chinair88-prog/allinb2c

1. Executive Orientation

This chapter defines how GTOS shall **inventory routes, layouts, pages, components, server/client boundaries, BFFs, APIs, realtime channels and ownership for customers and anonymous shoppers, covering catalog, marketplace, pricing, cart, checkout, order, payment, delivery, returns.**

The specification separates reality, observations, knowledge, Decisions, Intent, execution, and outcomes. A component name, database row, UI label, AI answer, or workflow state does not acquire authority merely because it is visible or technically convenient.

Reality or external outcome

- ≠ Observation
- ≠ Claim
- ≠ derived Perspective
- ≠ Prediction
- ≠ Recommendation
- ≠ authorized Decision
- ≠ execution Intent

1.1 Accountable ownership

The accountable owner is **Portal Architecture / Web Shop**. Supporting applications, shared infrastructure, integration adapters, analytics, and AI coordinate or present the capability but shall not silently own its authoritative propositions.

1.2 Scope

- create and identify the subject
- validate evidence and policy
- make authorized Decisions
- execute typed Commands
- publish completed-fact Events
- query current and historical perspectives
- correct and reconcile outcomes

1.3 Non-goals

- treating a registered Gradle module, catalog record, README, frontend route, migration plan, or generated report as proof of end-to-end implementation;
- direct cross-Domain database writes;
- generic status values that combine lifecycle, approval, provider, document, payment, dispute, and correction state;
- silent replacement of history;
- AI-created authority or fabricated external outcomes.

2. Ubiquitous Language and Subject Model

Subject	Required interpretation
WebShopRouteRegistry	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit
WebShopRouteRegistryVersion	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit
WebShopRouteRegistryDecision	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit
WebShopRouteRegistryEvidenceSet	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit
WebShopRouteRegistryException	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit

Reference aggregate:

```
WebShopRouteRegistry {  
  subjectId  
  tenantId  
  organizationContext  
  sourceIdentityRefs[]  
  sourceVersionRefs[]  
  lifecycleState  
  relationshipRefs[]  
  decisionRefs[]  
  intentRefs[]  
  evidenceSetRef  
  knowledgeCutoff  
  policyRefs[]  
  authorityRef  
  jurisdictionRefs[]  
  createdAt  
  effectiveAt  
  updatedAt  
  version  
  correctionOf?  
  correlationId  
}
```

2.1 Core invariants

- Stable identity precedes relationship, state, and cross-system correlation.
- Effective time and recorded time remain distinct where business truth changes over time.
- Recommendation, Decision, Intent, execution, and outcome are separate concepts.
- No Portal, report, search index, cache, workflow, or AI Agent becomes a shadow owner of Domain truth.
- Binding submitted, approved, issued, accepted, or signed versions are immutable.
- Corrections append governed facts and preserve the original record.
- External authority and provider outcomes retain their source and qualification.
- Tenant and represented-principal context come from trusted authentication and mandate evaluation.
- Retried writes are idempotent and concurrency guarded.
- Outcome Unknown is explicit and reconciled before risky duplicate execution.

2.2 Required standards

- stable identifiers
- typed contracts
- immutable binding versions

- transactional outbox
- idempotent Commands
- explicit Outcome Unknown
- correction lineage
- machine-verifiable conformance

3. Actors, Roles, and Authority

A conformant design distinguishes:

- the natural person acting;
- the service or AI identity invoking a Tool;
- the organization or principal represented;
- the role or relationship granting context;
- the mandate or delegation granting action authority;
- the Policy and jurisdiction limiting the action;
- the reviewer or approver responsible for a binding Decision.

Authority is evaluated at action time. Authentication alone does not grant business authority. Cached permissions and browser-supplied tenant headers are insufficient for high-impact actions.

4. Lifecycle and State Model

State	Semantics
PROPOSED	Distinct governed condition with entry, exit, timeout, correction and authority semantics
VALIDATION_PENDING	Distinct governed condition with entry, exit, timeout, correction and authority semantics
APPROVAL_PENDING	Distinct governed condition with entry, exit, timeout, correction and authority semantics
ACTIVE	Distinct governed condition with entry, exit, timeout, correction and authority semantics
SUSPENDED	Distinct governed condition with entry, exit, timeout, correction and authority semantics
CORRECTION_PENDING	Distinct governed condition with entry, exit, timeout, correction and authority semantics
RETIRED	Distinct governed condition with entry, exit, timeout, correction and authority semantics

```
stateDiagram-v2
    [*] --> PROPOSED
    PROPOSED --> VALIDATION_PENDING
    VALIDATION_PENDING --> APPROVAL_PENDING
    APPROVAL_PENDING --> ACTIVE
    ACTIVE --> SUSPENDED
    SUSPENDED --> CORRECTION_PENDING
    CORRECTION_PENDING --> RETIRED
```

The diagram is a primary reading path. Real implementations may add parallel review, amendment, appeal, timeout, suspension, partial completion, reconciliation, correction, and terminal failure without collapsing their meaning.

4.1 Transition rules

- transition through a typed, authorized Command;
- require exact expected version where concurrent change matters;
- record actor, represented principal, mandate, Policy, reason, and Evidence;
- use an idempotency key for retried writes;
- publish a completed-fact Event after durable state change;
- expose Outcome Unknown for unresolved external completion;
- preserve original and corrected states in historical reconstruction.

5. Decision, Evidence, and Knowledge Cutoff

Reference Decision:

```
Decision {
  decisionId
  decisionType
  subjectRef
  sourceVersionRefs[]
  knowledgeCutoff
  evidenceSetRef
  policyVersionRefs[]
  recommendationRefs[]
  principalId
  representedOrganizationId
  mandateRef
  rationale
  outcome
  decidedAt
  effectiveAt
  correctionOf?
}
```

Evidence records identify issuer or observer, subject, version, observed time, received time, effective interval, integrity, confidence, qualification, contradiction, correction, retention, residency, and access class. A recommendation may assist the Decision but cannot promote itself to the Decision.

6. Commands, Events, Queries, and Contracts

Reference Commands:

- CreateWebShopRouteRegistry
- ValidateWebShopRouteRegistry
- ApproveWebShopRouteRegistry
- ActivateWebShopRouteRegistry
- SuspendWebShopRouteRegistry
- CorrectWebShopRouteRegistry
- RetireWebShopRouteRegistry

Reference Events:

- WebShopRouteRegistryCreated
- WebShopRouteRegistryValidated
- WebShopRouteRegistryApproved
- WebShopRouteRegistryActivated
- WebShopRouteRegistrySuspended
- WebShopRouteRegistryCorrected
- WebShopRouteRegistryRetired

Reference queries:

- GetWebShopRouteRegistry
- ListWebShopRouteRegistryRecords
- GetWebShopRouteRegistryTimeline
- GetWebShopRouteRegistryEvidence
- GetWebShopRouteRegistryDecisionPackage
- GetWebShopRouteRegistryExceptions
- GetWebShopRouteRegistryAuditTrail

Reference API surface:

```
POST /api/v1/webshoprouteregistry/commands
GET  /api/v1/webshoprouteregistry/{id}
GET  /api/v1/webshoprouteregistry/{id}/timeline
GET  /api/v1/webshoprouteregistry/{id}/evidence
GET  /api/v1/webshoprouteregistry/{id}/decisions
POST /api/v1/webshoprouteregistry/{id}/exceptions
POST /api/v1/webshoprouteregistry/{id}/corrections
```

These endpoints are reference contracts, not claims that exact routes exist.

7. Workflow, Failure, and Compensation

flowchart TD

```
A[Validate identity version and authority] --> B[Collect required evidence]
B --> C{Policy and evidence gates pass?}
C -- No --> D[Open exception or request correction]
D --> B
C -- Yes --> E[Record Decision or execution Intent]
E --> F[Execute Domain command or external request]
F --> G{Outcome known?}
G -- Success --> H[Record fact and publish Event]
G -- Failure --> I[Record failure and compensation options]
G -- Unknown --> J[Enter Outcome Unknown]
J --> K[Query source or wait for verified callback]
K --> G
H --> L[Update projections and downstream workflow]
```

Representative failure modes:

- stale or wrong source version
- duplicate submission or replay
- external timeout after possible success
- contradictory source observations
- lost Event after committed state
- approval or mandate revoked during execution
- downstream action before a mandatory gate
- partial completion across multiple subjects
- evidence later retracted or corrected
- tenant, facility, channel or jurisdiction mismatch

Recovery shall query the authoritative source before duplicate execution, preserve partial success, use compensating Intent rather than destructive rewrite, publish corrections, quarantine high-impact ambiguity, and record affected downstream subjects.

8. Data and Persistence Architecture

Reference table families:

Table family	Purpose
webshoproutreregistry_aggregate	authoritative subject
webshoproutreregistry_version	immutable submitted, approved, issued, or signed versions
webshoproutreregistry_relationship	governed relationships
webshoproutreregistry_decision	binding Decisions and rationale
webshoproutreregistry_evidence_link	provenance and evidence relationships
webshoproutreregistry_event_outbox	transactional Event publication
webshoproutreregistry_idempotency	duplicate-write protection
webshoproutreregistry_exception	exception, claim, dispute, or hold
webshoproutreregistry_correction	correction and supersession lineage
webshoproutreregistry_audit	privileged action evidence

The owning service controls schema and migration. Cross-Domain references use stable identifiers or contracts. Analytics, reports, caches, search, and vector indexes remain projections. Backup, restore, retention, legal hold, privacy, residency, and decommissioning requirements are explicit.

9. Portal and Experience Requirements

- Web Shop: primary experience for customers and anonymous shoppers.
- Operator and support views: diagnose failed or ambiguous journeys without assuming Domain ownership.
- Domain services: own authoritative data and action eligibility; the Portal consumes typed contracts.

Every Portal displays exact version, owner, state, freshness, required action, and uncertainty. It supports loading, empty, partial, stale, denied, error, timeout, and Outcome Unknown states; accessibility; locale, currency, unit, date, and RTL/LTR correctness; evidence audit; safe retry; and correction history.

10. AI Participation and Tool Governance

Permitted AI tasks:

- extract and classify evidence
- detect anomalies and missing fields
- summarize timelines and contradictions
- recommend next actions with sources and uncertainty

AI shall not own Domain records, grant itself authority, suppress contradictions, silently edit approved versions, fabricate external outcomes, or execute high-impact actions outside typed Tools, policy, approval, idempotency, sandbox, and outcome observation.

Every Agent Run records source context, prompt/model/tool versions, structured output, confidence and limitations, Policy result, approval, Tool calls, provider responses, final outcome, and recovery actions.

11. Security, Privacy, and Trust Boundaries

- least privilege and separation of duties
- tenant, organization, facility, channel and jurisdiction isolation
- integrity protection for binding evidence
- verified external callbacks and anti-replay controls

Additional controls include secret isolation, callback signature verification, audit of privileged action, emergency-access review, sensitive-data minimization, purpose limitation, and threat models for impersonation, tampering, replay, confused deputy, fraud, prompt injection, and exfiltration.

12. Reliability, SLOs, and Operations

SLI	Reference objective
authoritative read availability	99.9% monthly unless a stricter tier applies
acknowledged Command durability	no acknowledged write may be silently lost
Event publication	99.9% within five minutes after committed fact
duplicate prevention	100% for same tenant, Command class, and idempotency key
binding Decision audit completeness	100%
state-state detection	bounded by business deadline

Dashboards and runbooks cover backlog, error budget, dependency failure, retry budget, DLQ, workflow stall, provider outage, reconciliation, capacity, backup/restore, release/rollback, incident command, and post-incident correction.

13. Testing and Continuous Conformance

- aggregate invariant and transition tests
- authorization, delegation, separation-of-duties and tenant-isolation tests
- idempotency and optimistic-concurrency tests
- database migration, key, constraint and rollback tests
- contract, outbox/inbox, duplicate, replay and DLQ tests
- workflow restart, timeout and compensation tests
- Portal E2E tests for success, partial, stale, denied, error and Outcome Unknown states
- accessibility, locale, currency, unit and RTL/LTR tests
- security adversarial, fraud and data-exfiltration tests
- AI evaluation, prompt-injection, policy-bypass and unauthorized-tool tests
- historical reconstruction, correction and audit-completeness tests
- performance, capacity, recovery and operational exercise tests

Release evidence links each invariant and control to the test, environment, input data, result, owner, and artifact proving it. Generated test counts never replace semantic coverage.

14. Repository Review Boundary

- This chapter is a repository-review specification. Exact executable implementation has not been inspected for every target behavior.
- Registered modules, catalog entries, README claims, frontend contracts, or plans are not proof of complete implementation.

Area	Classification
target aggregate, API, tables, state and workflow in this chapter	REFERENCE_ARCHITECTURE
registered module or catalog claim	DOCUMENTATION_ONLY_CLAIM until source inspection
uninspected integration	REQUIRES_REPOSITORY_REVIEW
behavior proven in another repository-grounded chapter	retain that chapter's evidence and classification
contradictory ownership or path claims	CONFLICT_REQUIRES_CANONICALIZATION

No statement upgrades implementation status merely because a file, directory, module name, frontend contract, database entry, plan, or report exists.

15. Worked Conformance Scenario

An authorized principal initiates a Command against an exact subject version. The service validates identity, tenant, mandate, Policy, Evidence, and idempotency. It records the state transition and outbox entry atomically. If an external dependency participates, timeout produces Outcome Unknown; reconciliation queries the source or waits for a verified callback instead of repeating the action blindly.

Portals show source, freshness, version, required action, and uncertainty. AI may extract, compare, summarize, detect anomalies, and recommend through typed Tools, but cannot own the subject or fabricate success. Later correction appends new facts, identifies affected projections and workflows, and preserves the historical Decision context.

16. Conformance Checklist

- ☐ stable identity and proposition ownership are explicit;
- ☐ authority and mandate are evaluated at action time;
- ☐ state, Recommendation, Decision, Intent, execution, and outcome remain distinct;
- ☐ Commands are typed, authorized, idempotent, and version guarded;
- ☐ Events describe completed facts;
- ☐ Evidence includes provenance, time, integrity, qualification, and correction;
- ☐ external outcomes retain their authority source;
- ☐ Portals show freshness and uncertainty;
- ☐ AI is bounded by typed Tools, Policy, approval, and outcome observation;
- ☐ security, tenant, facility, channel, and jurisdiction boundaries are enforced;
- ☐ Outcome Unknown and reconciliation exist where needed;
- ☐ corrections preserve history;
- ☐ tests prove invariants and recovery;
- ☐ implementation status is not upgraded without executable evidence.

17. Status Vocabulary

Status	Meaning
VERIFIED_IMPLEMENTED	Executable source and relevant behavior were inspected.
IMPLEMENTED_WITH_GAP	Executable behavior exists with a material governance or completeness gap.
PARTIAL_IMPLEMENTATION	Only part of the target capability is evidenced.
REFERENCE_ARCHITECTURE	Normative target behavior; no claim that it exists today.
PLANNED_NOT_IMPLEMENTED	Explicitly planned but not evidenced as executable.
DOCUMENTATION_ONLY_CLAIM	Documentation or client contract claims behavior without verified backend evidence.
CONFLICT_REQUIRES_CANONICALIZATION	Sources disagree and no final owner has been established.
REQUIRES_REPOSITORY_REVIEW	Necessary executable evidence has not yet been inspected.

Web Shop — Identity, Session, Authorization, and Trust Boundaries

Metadata	Value
Volume	4
Chapter ID	V04-P01-02
Subject	WebShopAccessModel
Status	Generated First-Draft Architecture Skeleton - Domain-Specific Expansion Required
Content maturity	TEMPLATE_DERIVED_REFERENCE_SKELETON unless repository citations prove otherwise
Default implementation classification	REFERENCE_ARCHITECTURE / REQUIRES_REPOSITORY_REVIEW
Accountable owner	Portal Architecture / Web Shop
Evidence rule	No implementation claim without inspected executable evidence
Repository	chinair88-prog/allinb2c

1. Executive Orientation

This chapter defines how GTOS shall **govern login, session, role, relationship, tenant, facility, channel, delegation, impersonation and privileged action for customers and anonymous shoppers, covering catalog, marketplace, pricing, cart, checkout, order, payment, delivery, returns.**

The specification separates reality, observations, knowledge, Decisions, Intent, execution, and outcomes. A component name, database row, UI label, AI answer, or workflow state does not acquire authority merely because it is visible or technically convenient.

Reality or external outcome
≠ Observation
≠ Claim
≠ derived Perspective
≠ Prediction
≠ Recommendation
≠ authorized Decision
≠ execution Intent

1.1 Accountable ownership

The accountable owner is **Portal Architecture / Web Shop**. Supporting applications, shared infrastructure, integration adapters, analytics, and AI coordinate or present the capability but shall not silently own its authoritative propositions.

1.2 Scope

- create and identify the subject
- validate evidence and policy
- make authorized Decisions
- execute typed Commands
- publish completed-fact Events
- query current and historical perspectives
- correct and reconcile outcomes

1.3 Non-goals

- treating a registered Gradle module, catalog record, README, frontend route, migration plan, or generated report as proof of end-to-end implementation;
- direct cross-Domain database writes;
- generic status values that combine lifecycle, approval, provider, document, payment, dispute, and correction state;
- silent replacement of history;
- AI-created authority or fabricated external outcomes.

2. Ubiquitous Language and Subject Model

Subject	Required interpretation
WebShopAccessModel	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit
WebShopAccessModelVersion	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit
WebShopAccessModelDecision	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit
WebShopAccessModelEvidenceSet	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit
WebShopAccessModelException	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit

Reference aggregate:

```
WebShopAccessModel {
  subjectId
  tenantId
  organizationContext
  sourceIdentityRefs[]
  sourceVersionRefs[]
  lifecycleState
  relationshipRefs[]
  decisionRefs[]
  intentRefs[]
  evidenceSetRef
  knowledgeCutoff
  policyRefs[]
  authorityRef
  jurisdictionRefs[]
  createdAt
  effectiveAt
  updatedAt
  version
  correctionOf?
  correlationId
}
```

2.1 Core invariants

- Stable identity precedes relationship, state, and cross-system correlation.
- Effective time and recorded time remain distinct where business truth changes over time.
- Recommendation, Decision, Intent, execution, and outcome are separate concepts.
- No Portal, report, search index, cache, workflow, or AI Agent becomes a shadow owner of Domain truth.
- Binding submitted, approved, issued, accepted, or signed versions are immutable.
- Corrections append governed facts and preserve the original record.
- External authority and provider outcomes retain their source and qualification.
- Tenant and represented-principal context come from trusted authentication and mandate evaluation.
- Retried writes are idempotent and concurrency guarded.
- Outcome Unknown is explicit and reconciled before risky duplicate execution.

2.2 Required standards

- stable identifiers
- typed contracts
- immutable binding versions

- transactional outbox
- idempotent Commands
- explicit Outcome Unknown
- correction lineage
- machine-verifiable conformance

3. Actors, Roles, and Authority

A conformant design distinguishes:

- the natural person acting;
- the service or AI identity invoking a Tool;
- the organization or principal represented;
- the role or relationship granting context;
- the mandate or delegation granting action authority;
- the Policy and jurisdiction limiting the action;
- the reviewer or approver responsible for a binding Decision.

Authority is evaluated at action time. Authentication alone does not grant business authority. Cached permissions and browser-supplied tenant headers are insufficient for high-impact actions.

4. Lifecycle and State Model

State	Semantics
PROPOSED	Distinct governed condition with entry, exit, timeout, correction and authority semantics
VALIDATION_PENDING	Distinct governed condition with entry, exit, timeout, correction and authority semantics
APPROVAL_PENDING	Distinct governed condition with entry, exit, timeout, correction and authority semantics
ACTIVE	Distinct governed condition with entry, exit, timeout, correction and authority semantics
SUSPENDED	Distinct governed condition with entry, exit, timeout, correction and authority semantics
CORRECTION_PENDING	Distinct governed condition with entry, exit, timeout, correction and authority semantics
RETIRED	Distinct governed condition with entry, exit, timeout, correction and authority semantics

```
stateDiagram-v2
    [*] --> PROPOSED
    PROPOSED --> VALIDATION_PENDING
    VALIDATION_PENDING --> APPROVAL_PENDING
    APPROVAL_PENDING --> ACTIVE
    ACTIVE --> SUSPENDED
    SUSPENDED --> CORRECTION_PENDING
    CORRECTION_PENDING --> RETIRED
```

The diagram is a primary reading path. Real implementations may add parallel review, amendment, appeal, timeout, suspension, partial completion, reconciliation, correction, and terminal failure without collapsing their meaning.

4.1 Transition rules

- transition through a typed, authorized Command;
- require exact expected version where concurrent change matters;
- record actor, represented principal, mandate, Policy, reason, and Evidence;
- use an idempotency key for retried writes;
- publish a completed-fact Event after durable state change;
- expose Outcome Unknown for unresolved external completion;
- preserve original and corrected states in historical reconstruction.

5. Decision, Evidence, and Knowledge Cutoff

Reference Decision:

```
Decision {
  decisionId
  decisionType
  subjectRef
  sourceVersionRefs[]
  knowledgeCutoff
  evidenceSetRef
  policyVersionRefs[]
  recommendationRefs[]
  principalId
  representedOrganizationId
  mandateRef
  rationale
  outcome
  decidedAt
  effectiveAt
  correctionOf?
}
```

Evidence records identify issuer or observer, subject, version, observed time, received time, effective interval, integrity, confidence, qualification, contradiction, correction, retention, residency, and access class. A recommendation may assist the Decision but cannot promote itself to the Decision.

6. Commands, Events, Queries, and Contracts

Reference Commands:

- CreateWebShopAccessModel
- ValidateWebShopAccessModel
- ApproveWebShopAccessModel
- ActivateWebShopAccessModel
- SuspendWebShopAccessModel
- CorrectWebShopAccessModel
- RetireWebShopAccessModel

Reference Events:

- WebShopAccessModelCreated
- WebShopAccessModelValidated
- WebShopAccessModelApproved
- WebShopAccessModelActivated
- WebShopAccessModelSuspended
- WebShopAccessModelCorrected
- WebShopAccessModelRetired

Reference queries:

- GetWebShopAccessModel
- ListWebShopAccessModelRecords
- GetWebShopAccessModelTimeline
- GetWebShopAccessModelEvidence
- GetWebShopAccessModelDecisionPackage
- GetWebShopAccessModelExceptions
- GetWebShopAccessModelAuditTrail

Reference API surface:

```
POST /api/v1/webshopaccessmodel/commands
GET  /api/v1/webshopaccessmodel/{id}
GET  /api/v1/webshopaccessmodel/{id}/timeline
GET  /api/v1/webshopaccessmodel/{id}/evidence
GET  /api/v1/webshopaccessmodel/{id}/decisions
POST /api/v1/webshopaccessmodel/{id}/exceptions
POST /api/v1/webshopaccessmodel/{id}/corrections
```

These endpoints are reference contracts, not claims that exact routes exist.

7. Workflow, Failure, and Compensation

flowchart TD

```
A[Validate identity version and authority] --> B[Collect required evidence]
B --> C{Policy and evidence gates pass?}
C -- No --> D[Open exception or request correction]
D --> B
C -- Yes --> E[Record Decision or execution Intent]
E --> F[Execute Domain command or external request]
F --> G{Outcome known?}
G -- Success --> H[Record fact and publish Event]
G -- Failure --> I[Record failure and compensation options]
G -- Unknown --> J[Enter Outcome Unknown]
J --> K[Query source or wait for verified callback]
K --> G
H --> L[Update projections and downstream workflow]
```

Representative failure modes:

- stale or wrong source version
- duplicate submission or replay
- external timeout after possible success
- contradictory source observations
- lost Event after committed state
- approval or mandate revoked during execution
- downstream action before a mandatory gate
- partial completion across multiple subjects
- evidence later retracted or corrected
- tenant, facility, channel or jurisdiction mismatch

Recovery shall query the authoritative source before duplicate execution, preserve partial success, use compensating Intent rather than destructive rewrite, publish corrections, quarantine high-impact ambiguity, and record affected downstream subjects.

8. Data and Persistence Architecture

Reference table families:

Table family	Purpose
webshopaccessmodel_aggregate	authoritative subject
webshopaccessmodel_version	immutable submitted, approved, issued, or signed versions
webshopaccessmodel_relationship	governed relationships
webshopaccessmodel_decision	binding Decisions and rationale
webshopaccessmodel_evidence_link	provenance and evidence relationships
webshopaccessmodel_event_outbox	transactional Event publication
webshopaccessmodel_idempotency	duplicate-write protection
webshopaccessmodel_exception	exception, claim, dispute, or hold
webshopaccessmodel_correction	correction and supersession lineage
webshopaccessmodel_audit	privileged action evidence

The owning service controls schema and migration. Cross-Domain references use stable identifiers or contracts. Analytics, reports, caches, search, and vector indexes remain projections. Backup, restore, retention, legal hold, privacy, residency, and decommissioning requirements are explicit.

9. Portal and Experience Requirements

- Web Shop: primary experience for customers and anonymous shoppers.
- Operator and support views: diagnose failed or ambiguous journeys without assuming Domain ownership.
- Domain services: own authoritative data and action eligibility; the Portal consumes typed contracts.

Every Portal displays exact version, owner, state, freshness, required action, and uncertainty. It supports loading, empty, partial, stale, denied, error, timeout, and Outcome Unknown states; accessibility; locale, currency, unit, date, and RTL/LTR correctness; evidence audit; safe retry; and correction history.

10. AI Participation and Tool Governance

Permitted AI tasks:

- extract and classify evidence
- detect anomalies and missing fields
- summarize timelines and contradictions
- recommend next actions with sources and uncertainty

AI shall not own Domain records, grant itself authority, suppress contradictions, silently edit approved versions, fabricate external outcomes, or execute high-impact actions outside typed Tools, policy, approval, idempotency, sandbox, and outcome observation.

Every Agent Run records source context, prompt/model/tool versions, structured output, confidence and limitations, Policy result, approval, Tool calls, provider responses, final outcome, and recovery actions.

11. Security, Privacy, and Trust Boundaries

- least privilege and separation of duties
- tenant, organization, facility, channel and jurisdiction isolation
- integrity protection for binding evidence
- verified external callbacks and anti-replay controls

Additional controls include secret isolation, callback signature verification, audit of privileged action, emergency-access review, sensitive-data minimization, purpose limitation, and threat models for impersonation, tampering, replay, confused deputy, fraud, prompt injection, and exfiltration.

12. Reliability, SLOs, and Operations

SLI	Reference objective
authoritative read availability	99.9% monthly unless a stricter tier applies
acknowledged Command durability	no acknowledged write may be silently lost
Event publication	99.9% within five minutes after committed fact
duplicate prevention	100% for same tenant, Command class, and idempotency key
binding Decision audit completeness	100%
state-state detection	bounded by business deadline

Dashboards and runbooks cover backlog, error budget, dependency failure, retry budget, DLQ, workflow stall, provider outage, reconciliation, capacity, backup/restore, release/rollback, incident command, and post-incident correction.

13. Testing and Continuous Conformance

- aggregate invariant and transition tests
- authorization, delegation, separation-of-duties and tenant-isolation tests
- idempotency and optimistic-concurrency tests
- database migration, key, constraint and rollback tests
- contract, outbox/inbox, duplicate, replay and DLQ tests
- workflow restart, timeout and compensation tests
- Portal E2E tests for success, partial, stale, denied, error and Outcome Unknown states
- accessibility, locale, currency, unit and RTL/LTR tests
- security adversarial, fraud and data-exfiltration tests
- AI evaluation, prompt-injection, policy-bypass and unauthorized-tool tests
- historical reconstruction, correction and audit-completeness tests
- performance, capacity, recovery and operational exercise tests

Release evidence links each invariant and control to the test, environment, input data, result, owner, and artifact proving it. Generated test counts never replace semantic coverage.

14. Repository Review Boundary

- This chapter is a repository-review specification. Exact executable implementation has not been inspected for every target behavior.
- Registered modules, catalog entries, README claims, frontend contracts, or plans are not proof of complete implementation.

Area	Classification
target aggregate, API, tables, state and workflow in this chapter	REFERENCE_ARCHITECTURE
registered module or catalog claim	DOCUMENTATION_ONLY_CLAIM until source inspection
uninspected integration	REQUIRES_REPOSITORY_REVIEW
behavior proven in another repository-grounded chapter	retain that chapter's evidence and classification
contradictory ownership or path claims	CONFLICT_REQUIRES_CANONICALIZATION

No statement upgrades implementation status merely because a file, directory, module name, frontend contract, database entry, plan, or report exists.

15. Worked Conformance Scenario

An authorized principal initiates a Command against an exact subject version. The service validates identity, tenant, mandate, Policy, Evidence, and idempotency. It records the state transition and outbox entry atomically. If an external dependency participates, timeout produces Outcome Unknown; reconciliation queries the source or waits for a verified callback instead of repeating the action blindly.

Portals show source, freshness, version, required action, and uncertainty. AI may extract, compare, summarize, detect anomalies, and recommend through typed Tools, but cannot own the subject or fabricate success. Later correction appends new facts, identifies affected projections and workflows, and preserves the historical Decision context.

16. Conformance Checklist

- ☐ stable identity and proposition ownership are explicit;
- ☐ authority and mandate are evaluated at action time;
- ☐ state, Recommendation, Decision, Intent, execution, and outcome remain distinct;
- ☐ Commands are typed, authorized, idempotent, and version guarded;
- ☐ Events describe completed facts;
- ☐ Evidence includes provenance, time, integrity, qualification, and correction;
- ☐ external outcomes retain their authority source;
- ☐ Portals show freshness and uncertainty;
- ☐ AI is bounded by typed Tools, Policy, approval, and outcome observation;
- ☐ security, tenant, facility, channel, and jurisdiction boundaries are enforced;
- ☐ Outcome Unknown and reconciliation exist where needed;
- ☐ corrections preserve history;
- ☐ tests prove invariants and recovery;
- ☐ implementation status is not upgraded without executable evidence.

17. Status Vocabulary

Status	Meaning
VERIFIED_IMPLEMENTED	Executable source and relevant behavior were inspected. Executable behavior exists with a material governance or completeness gap.
IMPLEMENTED_WITH_GAP	
PARTIAL_IMPLEMENTATION	Only part of the target capability is evidenced.
REFERENCE_ARCHITECTURE	Normative target behavior; no claim that it exists today.
PLANNED_NOT_IMPLEMENTED	Explicitly planned but not evidenced as executable.
DOCUMENTATION_ONLY_CLAIM	Documentation or client contract claims behavior without verified backend evidence.
CONFLICT_REQUIRES_CANONICALIZATION	Sources disagree and no final owner has been established.
REQUIRES_REPOSITORY_REVIEW	Necessary executable evidence has not yet been inspected.

Web Shop — UX States, Accessibility, Localization, Analytics, and E2E

Metadata	Value
Volume	4
Chapter ID	V04-P01-03
Subject	WebShopExperienceStandard
Status	Generated First-Draft Architecture Skeleton - Domain-Specific Expansion Required
Content maturity	TEMPLATE_DERIVED_REFERENCE_SKELETON unless repository citations prove otherwise
Default implementation classification	REFERENCE_ARCHITECTURE / REQUIRES_REPOSITORY_REVIEW
Accountable owner	Portal Architecture / Web Shop
Evidence rule	No implementation claim without inspected executable evidence
Repository	chinair88-prog/allinb2c

1. Executive Orientation

This chapter defines how GTOS shall **specify loading, empty, partial, stale, error, denied, offline, accessibility, RTL/LTR, analytics, audit and test journeys for customers and anonymous shoppers, covering catalog, marketplace, pricing, cart, checkout, order, payment, delivery, returns.**

The specification separates reality, observations, knowledge, Decisions, Intent, execution, and outcomes. A component name, database row, UI label, AI answer, or workflow state does not acquire authority merely because it is visible or technically convenient.

Reality or external outcome

- ≠ Observation
- ≠ Claim
- ≠ derived Perspective
- ≠ Prediction
- ≠ Recommendation
- ≠ authorized Decision
- ≠ execution Intent

1.1 Accountable ownership

The accountable owner is **Portal Architecture / Web Shop**. Supporting applications, shared infrastructure, integration adapters, analytics, and AI coordinate or present the capability but shall not silently own its authoritative propositions.

1.2 Scope

- create and identify the subject
- validate evidence and policy
- make authorized Decisions
- execute typed Commands
- publish completed-fact Events
- query current and historical perspectives
- correct and reconcile outcomes

1.3 Non-goals

- treating a registered Gradle module, catalog record, README, frontend route, migration plan, or generated report as proof of end-to-end implementation;
- direct cross-Domain database writes;
- generic status values that combine lifecycle, approval, provider, document, payment, dispute, and correction state;
- silent replacement of history;
- AI-created authority or fabricated external outcomes.

2. Ubiquitous Language and Subject Model

Subject	Required interpretation
WebShopExperienceStandard	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit
WebShopExperienceStandardVersion	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit
WebShopExperienceStandardDecision	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit
WebShopExperienceStandardEvidenceSet	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit
WebShopExperienceStandardException	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit

Reference aggregate:

```
WebShopExperienceStandard {  
  subjectId  
  tenantId  
  organizationContext  
  sourceIdentityRefs[]  
  sourceVersionRefs[]  
  lifecycleState  
  relationshipRefs[]  
  decisionRefs[]  
  intentRefs[]  
  evidenceSetRef  
  knowledgeCutoff  
  policyRefs[]  
  authorityRef  
  jurisdictionRefs[]  
  createdAt  
  effectiveAt  
  updatedAt  
  version  
  correctionOf?  
  correlationId  
}
```

2.1 Core invariants

- Stable identity precedes relationship, state, and cross-system correlation.
- Effective time and recorded time remain distinct where business truth changes over time.
- Recommendation, Decision, Intent, execution, and outcome are separate concepts.
- No Portal, report, search index, cache, workflow, or AI Agent becomes a shadow owner of Domain truth.
- Binding submitted, approved, issued, accepted, or signed versions are immutable.
- Corrections append governed facts and preserve the original record.
- External authority and provider outcomes retain their source and qualification.
- Tenant and represented-principal context come from trusted authentication and mandate evaluation.
- Retried writes are idempotent and concurrency guarded.
- Outcome Unknown is explicit and reconciled before risky duplicate execution.

2.2 Required standards

- stable identifiers
- typed contracts
- immutable binding versions

- transactional outbox
- idempotent Commands
- explicit Outcome Unknown
- correction lineage
- machine-verifiable conformance

3. Actors, Roles, and Authority

A conformant design distinguishes:

- the natural person acting;
- the service or AI identity invoking a Tool;
- the organization or principal represented;
- the role or relationship granting context;
- the mandate or delegation granting action authority;
- the Policy and jurisdiction limiting the action;
- the reviewer or approver responsible for a binding Decision.

Authority is evaluated at action time. Authentication alone does not grant business authority. Cached permissions and browser-supplied tenant headers are insufficient for high-impact actions.

4. Lifecycle and State Model

State	Semantics
PROPOSED	Distinct governed condition with entry, exit, timeout, correction and authority semantics
VALIDATION_PENDING	Distinct governed condition with entry, exit, timeout, correction and authority semantics
APPROVAL_PENDING	Distinct governed condition with entry, exit, timeout, correction and authority semantics
ACTIVE	Distinct governed condition with entry, exit, timeout, correction and authority semantics
SUSPENDED	Distinct governed condition with entry, exit, timeout, correction and authority semantics
CORRECTION_PENDING	Distinct governed condition with entry, exit, timeout, correction and authority semantics
RETIRED	Distinct governed condition with entry, exit, timeout, correction and authority semantics

```
stateDiagram-v2
    [*] --> PROPOSED
    PROPOSED --> VALIDATION_PENDING
    VALIDATION_PENDING --> APPROVAL_PENDING
    APPROVAL_PENDING --> ACTIVE
    ACTIVE --> SUSPENDED
    SUSPENDED --> CORRECTION_PENDING
    CORRECTION_PENDING --> RETIRED
```

The diagram is a primary reading path. Real implementations may add parallel review, amendment, appeal, timeout, suspension, partial completion, reconciliation, correction, and terminal failure without collapsing their meaning.

4.1 Transition rules

- transition through a typed, authorized Command;
- require exact expected version where concurrent change matters;
- record actor, represented principal, mandate, Policy, reason, and Evidence;
- use an idempotency key for retried writes;
- publish a completed-fact Event after durable state change;
- expose Outcome Unknown for unresolved external completion;
- preserve original and corrected states in historical reconstruction.

5. Decision, Evidence, and Knowledge Cutoff

Reference Decision:

```
Decision {
  decisionId
  decisionType
  subjectRef
  sourceVersionRefs[]
  knowledgeCutoff
  evidenceSetRef
  policyVersionRefs[]
  recommendationRefs[]
  principalId
  representedOrganizationId
  mandateRef
  rationale
  outcome
  decidedAt
  effectiveAt
  correctionOf?
}
```

Evidence records identify issuer or observer, subject, version, observed time, received time, effective interval, integrity, confidence, qualification, contradiction, correction, retention, residency, and access class. A recommendation may assist the Decision but cannot promote itself to the Decision.

6. Commands, Events, Queries, and Contracts

Reference Commands:

- CreateWebShopExperienceStandard
- ValidateWebShopExperienceStandard
- ApproveWebShopExperienceStandard
- ActivateWebShopExperienceStandard
- SuspendWebShopExperienceStandard
- CorrectWebShopExperienceStandard
- RetireWebShopExperienceStandard

Reference Events:

- WebShopExperienceStandardCreated
- WebShopExperienceStandardValidated
- WebShopExperienceStandardApproved
- WebShopExperienceStandardActivated
- WebShopExperienceStandardSuspended
- WebShopExperienceStandardCorrected
- WebShopExperienceStandardRetired

Reference queries:

- GetWebShopExperienceStandard
- ListWebShopExperienceStandardRecords
- GetWebShopExperienceStandardTimeline
- GetWebShopExperienceStandardEvidence
- GetWebShopExperienceStandardDecisionPackage
- GetWebShopExperienceStandardExceptions
- GetWebShopExperienceStandardAuditTrail

Reference API surface:

```
POST /api/v1/webshopexperiencstandard/commands
GET  /api/v1/webshopexperiencstandard/{id}
GET  /api/v1/webshopexperiencstandard/{id}/timeline
GET  /api/v1/webshopexperiencstandard/{id}/evidence
GET  /api/v1/webshopexperiencstandard/{id}/decisions
POST /api/v1/webshopexperiencstandard/{id}/exceptions
POST /api/v1/webshopexperiencstandard/{id}/corrections
```

These endpoints are reference contracts, not claims that exact routes exist.

7. Workflow, Failure, and Compensation

flowchart TD

```
A[Validate identity version and authority] --> B[Collect required evidence]
B --> C{Policy and evidence gates pass?}
C -- No --> D[Open exception or request correction]
D --> B
C -- Yes --> E[Record Decision or execution Intent]
E --> F[Execute Domain command or external request]
F --> G{Outcome known?}
G -- Success --> H[Record fact and publish Event]
G -- Failure --> I[Record failure and compensation options]
G -- Unknown --> J[Enter Outcome Unknown]
J --> K[Query source or wait for verified callback]
K --> G
H --> L[Update projections and downstream workflow]
```

Representative failure modes:

- stale or wrong source version
- duplicate submission or replay
- external timeout after possible success
- contradictory source observations
- lost Event after committed state
- approval or mandate revoked during execution
- downstream action before a mandatory gate
- partial completion across multiple subjects
- evidence later retracted or corrected
- tenant, facility, channel or jurisdiction mismatch

Recovery shall query the authoritative source before duplicate execution, preserve partial success, use compensating Intent rather than destructive rewrite, publish corrections, quarantine high-impact ambiguity, and record affected downstream subjects.

8. Data and Persistence Architecture

Reference table families:

Table family	Purpose
webshopexperiencestandard_aggregate	authoritative subject
webshopexperiencestandard_version	immutable submitted, approved, issued, or signed versions
webshopexperiencestandard_relationship	governed relationships
webshopexperiencestandard_decision	binding Decisions and rationale
webshopexperiencestandard_evidence_link	provenance and evidence relationships
webshopexperiencestandard_event_outbox	transactional Event publication
webshopexperiencestandard_idempotency	duplicate-write protection
webshopexperiencestandard_exception	exception, claim, dispute, or hold
webshopexperiencestandard_correction	correction and supersession lineage
webshopexperiencestandard_audit	privileged action evidence

The owning service controls schema and migration. Cross-Domain references use stable identifiers or contracts. Analytics, reports, caches, search, and vector indexes remain projections. Backup, restore, retention, legal hold, privacy, residency, and decommissioning requirements are explicit.

9. Portal and Experience Requirements

- Web Shop: primary experience for customers and anonymous shoppers.
- Operator and support views: diagnose failed or ambiguous journeys without assuming Domain ownership.
- Domain services: own authoritative data and action eligibility; the Portal consumes typed contracts.

Every Portal displays exact version, owner, state, freshness, required action, and uncertainty. It supports loading, empty, partial, stale, denied, error, timeout, and Outcome Unknown states; accessibility; locale, currency, unit, date, and RTL/LTR correctness; evidence audit; safe retry; and correction history.

10. AI Participation and Tool Governance

Permitted AI tasks:

- extract and classify evidence
- detect anomalies and missing fields
- summarize timelines and contradictions
- recommend next actions with sources and uncertainty

AI shall not own Domain records, grant itself authority, suppress contradictions, silently edit approved versions, fabricate external outcomes, or execute high-impact actions outside typed Tools, policy, approval, idempotency, sandbox, and outcome observation.

Every Agent Run records source context, prompt/model/tool versions, structured output, confidence and limitations, Policy result, approval, Tool calls, provider responses, final outcome, and recovery actions.

11. Security, Privacy, and Trust Boundaries

- least privilege and separation of duties
- tenant, organization, facility, channel and jurisdiction isolation
- integrity protection for binding evidence
- verified external callbacks and anti-replay controls

Additional controls include secret isolation, callback signature verification, audit of privileged action, emergency-access review, sensitive-data minimization, purpose limitation, and threat models for impersonation, tampering, replay, confused deputy, fraud, prompt injection, and exfiltration.

12. Reliability, SLOs, and Operations

SLI	Reference objective
authoritative read availability	99.9% monthly unless a stricter tier applies
acknowledged Command durability	no acknowledged write may be silently lost
Event publication	99.9% within five minutes after committed fact
duplicate prevention	100% for same tenant, Command class, and idempotency key
binding Decision audit completeness	100%
state-state detection	bounded by business deadline

Dashboards and runbooks cover backlog, error budget, dependency failure, retry budget, DLQ, workflow stall, provider outage, reconciliation, capacity, backup/restore, release/rollback, incident command, and post-incident correction.

13. Testing and Continuous Conformance

- aggregate invariant and transition tests
- authorization, delegation, separation-of-duties and tenant-isolation tests
- idempotency and optimistic-concurrency tests
- database migration, key, constraint and rollback tests
- contract, outbox/inbox, duplicate, replay and DLQ tests
- workflow restart, timeout and compensation tests
- Portal E2E tests for success, partial, stale, denied, error and Outcome Unknown states
- accessibility, locale, currency, unit and RTL/LTR tests
- security adversarial, fraud and data-exfiltration tests
- AI evaluation, prompt-injection, policy-bypass and unauthorized-tool tests
- historical reconstruction, correction and audit-completeness tests
- performance, capacity, recovery and operational exercise tests

Release evidence links each invariant and control to the test, environment, input data, result, owner, and artifact proving it. Generated test counts never replace semantic coverage.

14. Repository Review Boundary

- This chapter is a repository-review specification. Exact executable implementation has not been inspected for every target behavior.
- Registered modules, catalog entries, README claims, frontend contracts, or plans are not proof of complete implementation.

Area	Classification
target aggregate, API, tables, state and workflow in this chapter	REFERENCE_ARCHITECTURE
registered module or catalog claim	DOCUMENTATION_ONLY_CLAIM until source inspection
uninspected integration	REQUIRES_REPOSITORY_REVIEW
behavior proven in another repository-grounded chapter	retain that chapter's evidence and classification
contradictory ownership or path claims	CONFLICT_REQUIRES_CANONICALIZATION

No statement upgrades implementation status merely because a file, directory, module name, frontend contract, database entry, plan, or report exists.

15. Worked Conformance Scenario

An authorized principal initiates a Command against an exact subject version. The service validates identity, tenant, mandate, Policy, Evidence, and idempotency. It records the state transition and outbox entry atomically. If an external dependency participates, timeout produces Outcome Unknown; reconciliation queries the source or waits for a verified callback instead of repeating the action blindly.

Portals show source, freshness, version, required action, and uncertainty. AI may extract, compare, summarize, detect anomalies, and recommend through typed Tools, but cannot own the subject or fabricate success. Later correction appends new facts, identifies affected projections and workflows, and preserves the historical Decision context.

16. Conformance Checklist

- ☐ stable identity and proposition ownership are explicit;
- ☐ authority and mandate are evaluated at action time;
- ☐ state, Recommendation, Decision, Intent, execution, and outcome remain distinct;
- ☐ Commands are typed, authorized, idempotent, and version guarded;
- ☐ Events describe completed facts;
- ☐ Evidence includes provenance, time, integrity, qualification, and correction;
- ☐ external outcomes retain their authority source;
- ☐ Portals show freshness and uncertainty;
- ☐ AI is bounded by typed Tools, Policy, approval, and outcome observation;
- ☐ security, tenant, facility, channel, and jurisdiction boundaries are enforced;
- ☐ Outcome Unknown and reconciliation exist where needed;
- ☐ corrections preserve history;
- ☐ tests prove invariants and recovery;
- ☐ implementation status is not upgraded without executable evidence.

17. Status Vocabulary

Status	Meaning
VERIFIED_IMPLEMENTED	Executable source and relevant behavior were inspected.
IMPLEMENTED_WITH_GAP	Executable behavior exists with a material governance or completeness gap.
PARTIAL_IMPLEMENTATION	Only part of the target capability is evidenced.
REFERENCE_ARCHITECTURE	Normative target behavior; no claim that it exists today.
PLANNED_NOT_IMPLEMENTED	Explicitly planned but not evidenced as executable.
DOCUMENTATION_ONLY_CLAIM	Documentation or client contract claims behavior without verified backend evidence.
CONFLICT_REQUIRES_CANONICALIZATION	Sources disagree and no final owner has been established.
REQUIRES_REPOSITORY_REVIEW	Necessary executable evidence has not yet been inspected.

Web Admin — Portal Orientation and Information Architecture

Metadata	Value
Volume	4
Chapter ID	V04-P02-00
Subject	WebAdminPortal
Status	Generated First-Draft Architecture Skeleton - Domain-Specific Expansion Required
Content maturity	TEMPLATE_DERIVED_REFERENCE_SKELETON unless repository citations prove otherwise
Default implementation classification	REFERENCE_ARCHITECTURE / REQUIRES_REPOSITORY_REVIEW
Accountable owner	Portal Architecture / Web Admin
Evidence rule	No implementation claim without inspected executable evidence
Repository	chinair88-prog/allinb2c

1. Executive Orientation

This chapter defines how GTOS shall **define personas, navigation, route ownership, domain dependencies and experience boundaries for platform and tenant administrators, covering configuration, identity, catalog, policy, operations, finance, reporting.**

The specification separates reality, observations, knowledge, Decisions, Intent, execution, and outcomes. A component name, database row, UI label, AI answer, or workflow state does not acquire authority merely because it is visible or technically convenient.

Reality or external outcome

- ≠ Observation
- ≠ Claim
- ≠ derived Perspective
- ≠ Prediction
- ≠ Recommendation
- ≠ authorized Decision
- ≠ execution Intent

1.1 Accountable ownership

The accountable owner is **Portal Architecture / Web Admin**. Supporting applications, shared infrastructure, integration adapters, analytics, and AI coordinate or present the capability but shall not silently own its authoritative propositions.

1.2 Scope

- create and identify the subject
- validate evidence and policy
- make authorized Decisions
- execute typed Commands
- publish completed-fact Events
- query current and historical perspectives
- correct and reconcile outcomes

1.3 Non-goals

- treating a registered Gradle module, catalog record, README, frontend route, migration plan, or generated report as proof of end-to-end implementation;

- direct cross-Domain database writes;
- generic status values that combine lifecycle, approval, provider, document, payment, dispute, and correction state;
- silent replacement of history;
- AI-created authority or fabricated external outcomes.

2. Ubiquitous Language and Subject Model

Subject	Required interpretation
WebAdminPortal	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit
WebAdminPortalVersion	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit
WebAdminPortalDecision	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit
WebAdminPortalEvidenceSet	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit
WebAdminPortalException	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit

Reference aggregate:

```
WebAdminPortal {
  subjectId
  tenantId
  organizationContext
  sourceIdentityRefs[]
  sourceVersionRefs[]
  lifecycleState
  relationshipRefs[]
  decisionRefs[]
  intentRefs[]
  evidenceSetRef
  knowledgeCutoff
  policyRefs[]
  authorityRef
  jurisdictionRefs[]
  createdAt
  effectiveAt
  updatedAt
  version
  correctionOf?
  correlationId
}
```

2.1 Core invariants

- Stable identity precedes relationship, state, and cross-system correlation.
- Effective time and recorded time remain distinct where business truth changes over time.
- Recommendation, Decision, Intent, execution, and outcome are separate concepts.
- No Portal, report, search index, cache, workflow, or AI Agent becomes a shadow owner of Domain truth.
- Binding submitted, approved, issued, accepted, or signed versions are immutable.
- Corrections append governed facts and preserve the original record.
- External authority and provider outcomes retain their source and qualification.
- Tenant and represented-principal context come from trusted authentication and mandate evaluation.
- Retried writes are idempotent and concurrency guarded.
- Outcome Unknown is explicit and reconciled before risky duplicate execution.

2.2 Required standards

- stable identifiers
- typed contracts
- immutable binding versions
- transactional outbox
- idempotent Commands
- explicit Outcome Unknown
- correction lineage

- machine-verifiable conformance

3. Actors, Roles, and Authority

A conformant design distinguishes:

- the natural person acting;
- the service or AI identity invoking a Tool;
- the organization or principal represented;
- the role or relationship granting context;
- the mandate or delegation granting action authority;
- the Policy and jurisdiction limiting the action;
- the reviewer or approver responsible for a binding Decision.

Authority is evaluated at action time. Authentication alone does not grant business authority. Cached permissions and browser-supplied tenant headers are insufficient for high-impact actions.

4. Lifecycle and State Model

State	Semantics
PROPOSED	Distinct governed condition with entry, exit, timeout, correction and authority semantics
VALIDATION_PENDING	Distinct governed condition with entry, exit, timeout, correction and authority semantics
APPROVAL_PENDING	Distinct governed condition with entry, exit, timeout, correction and authority semantics
ACTIVE	Distinct governed condition with entry, exit, timeout, correction and authority semantics
SUSPENDED	Distinct governed condition with entry, exit, timeout, correction and authority semantics
CORRECTION_PENDING	Distinct governed condition with entry, exit, timeout, correction and authority semantics
RETIRED	Distinct governed condition with entry, exit, timeout, correction and authority semantics

```
stateDiagram-v2
    [*] --> PROPOSED
    PROPOSED --> VALIDATION_PENDING
    VALIDATION_PENDING --> APPROVAL_PENDING
    APPROVAL_PENDING --> ACTIVE
    ACTIVE --> SUSPENDED
    SUSPENDED --> CORRECTION_PENDING
    CORRECTION_PENDING --> RETIRED
```

The diagram is a primary reading path. Real implementations may add parallel review, amendment, appeal, timeout, suspension, partial completion, reconciliation, correction, and terminal failure without collapsing their meaning.

4.1 Transition rules

- transition through a typed, authorized Command;
- require exact expected version where concurrent change matters;
- record actor, represented principal, mandate, Policy, reason, and Evidence;
- use an idempotency key for retried writes;
- publish a completed-fact Event after durable state change;
- expose Outcome Unknown for unresolved external completion;
- preserve original and corrected states in historical reconstruction.

5. Decision, Evidence, and Knowledge Cutoff

Reference Decision:

```
Decision {
    decisionId
```

```

decisionType
subjectRef
sourceVersionRefs[]
knowledgeCutoff
evidenceSetRef
policyVersionRefs[]
recommendationRefs[]
principalId
representedOrganizationId
mandateRef
rationale
outcome
decidedAt
effectiveAt
correctionOf?
}

```

Evidence records identify issuer or observer, subject, version, observed time, received time, effective interval, integrity, confidence, qualification, contradiction, correction, retention, residency, and access class. A recommendation may assist the Decision but cannot promote itself to the Decision.

6. Commands, Events, Queries, and Contracts

Reference Commands:

- CreateWebAdminPortal
- ValidateWebAdminPortal
- ApproveWebAdminPortal
- ActivateWebAdminPortal
- SuspendWebAdminPortal
- CorrectWebAdminPortal
- RetireWebAdminPortal

Reference Events:

- WebAdminPortalCreated
- WebAdminPortalValidated
- WebAdminPortalApproved
- WebAdminPortalActivated
- WebAdminPortalSuspended
- WebAdminPortalCorrected
- WebAdminPortalRetired

Reference queries:

- GetWebAdminPortal
- ListWebAdminPortalRecords
- GetWebAdminPortalTimeline
- GetWebAdminPortalEvidence
- GetWebAdminPortalDecisionPackage
- GetWebAdminPortalExceptions
- GetWebAdminPortalAuditTrail

Reference API surface:

```

POST /api/v1/webadminportal/commands
GET  /api/v1/webadminportal/{id}
GET  /api/v1/webadminportal/{id}/timeline
GET  /api/v1/webadminportal/{id}/evidence
GET  /api/v1/webadminportal/{id}/decisions
POST /api/v1/webadminportal/{id}/exceptions
POST /api/v1/webadminportal/{id}/corrections

```

These endpoints are reference contracts, not claims that exact routes exist.

7. Workflow, Failure, and Compensation

flowchart TD

```

A[Validate identity version and authority] --> B[Collect required evidence]
B --> C{Policy and evidence gates pass?}
C -- No --> D[Open exception or request correction]
D --> B

```

```

C -- Yes --> E[Record Decision or execution Intent]
E --> F[Execute Domain command or external request]
F --> G{Outcome known?}
G -- Success --> H[Record fact and publish Event]
G -- Failure --> I[Record failure and compensation options]
G -- Unknown --> J[Enter Outcome Unknown]
J --> K[Query source or wait for verified callback]
K --> G
H --> L[Update projections and downstream workflow]

```

Representative failure modes:

- stale or wrong source version
- duplicate submission or replay
- external timeout after possible success
- contradictory source observations
- lost Event after committed state
- approval or mandate revoked during execution
- downstream action before a mandatory gate
- partial completion across multiple subjects
- evidence later retracted or corrected
- tenant, facility, channel or jurisdiction mismatch

Recovery shall query the authoritative source before duplicate execution, preserve partial success, use compensating Intent rather than destructive rewrite, publish corrections, quarantine high-impact ambiguity, and record affected downstream subjects.

8. Data and Persistence Architecture

Reference table families:

Table family	Purpose
webadminportal_aggregate	authoritative subject
webadminportal_version	immutable submitted, approved, issued, or signed versions
webadminportal_relationship	governed relationships
webadminportal_decision	binding Decisions and rationale
webadminportal_evidence_link	provenance and evidence relationships
webadminportal_event_outbox	transactional Event publication
webadminportal_idempotency	duplicate-write protection
webadminportal_exception	exception, claim, dispute, or hold
webadminportal_correction	correction and supersession lineage
webadminportal_audit	privileged action evidence

The owning service controls schema and migration. Cross-Domain references use stable identifiers or contracts. Analytics, reports, caches, search, and vector indexes remain projections. Backup, restore, retention, legal hold, privacy, residency, and decommissioning requirements are explicit.

9. Portal and Experience Requirements

- Web Admin: primary experience for platform and tenant administrators.
- Operator and support views: diagnose failed or ambiguous journeys without assuming Domain ownership.
- Domain services: own authoritative data and action eligibility; the Portal consumes typed contracts.

Every Portal displays exact version, owner, state, freshness, required action, and uncertainty. It supports loading, empty, partial, stale, denied, error, timeout, and Outcome Unknown states; accessibility; locale, currency, unit, date, and RTL/LTR correctness; evidence audit; safe retry; and correction history.

10. AI Participation and Tool Governance

Permitted AI tasks:

- extract and classify evidence
- detect anomalies and missing fields
- summarize timelines and contradictions

- recommend next actions with sources and uncertainty

AI shall not own Domain records, grant itself authority, suppress contradictions, silently edit approved versions, fabricate external outcomes, or execute high-impact actions outside typed Tools, policy, approval, idempotency, sandbox, and outcome observation.

Every Agent Run records source context, prompt/model/tool versions, structured output, confidence and limitations, Policy result, approval, Tool calls, provider responses, final outcome, and recovery actions.

11. Security, Privacy, and Trust Boundaries

- least privilege and separation of duties
- tenant, organization, facility, channel and jurisdiction isolation
- integrity protection for binding evidence
- verified external callbacks and anti-replay controls

Additional controls include secret isolation, callback signature verification, audit of privileged action, emergency-access review, sensitive-data minimization, purpose limitation, and threat models for impersonation, tampering, replay, confused deputy, fraud, prompt injection, and exfiltration.

12. Reliability, SLOs, and Operations

SLI	Reference objective
authoritative read availability	99.9% monthly unless a stricter tier applies
acknowledged Command durability	no acknowledged write may be silently lost
Event publication	99.9% within five minutes after committed fact
duplicate prevention	100% for same tenant, Command class, and idempotency key
binding Decision audit completeness	100%
state-state detection	bounded by business deadline

Dashboards and runbooks cover backlog, error budget, dependency failure, retry budget, DLQ, workflow stall, provider outage, reconciliation, capacity, backup/restore, release/rollback, incident command, and post-incident correction.

13. Testing and Continuous Conformance

- aggregate invariant and transition tests
- authorization, delegation, separation-of-duties and tenant-isolation tests
- idempotency and optimistic-concurrency tests
- database migration, key, constraint and rollback tests
- contract, outbox/inbox, duplicate, replay and DLQ tests
- workflow restart, timeout and compensation tests
- Portal E2E tests for success, partial, stale, denied, error and Outcome Unknown states
- accessibility, locale, currency, unit and RTL/LTR tests
- security adversarial, fraud and data-exfiltration tests
- AI evaluation, prompt-injection, policy-bypass and unauthorized-tool tests
- historical reconstruction, correction and audit-completeness tests
- performance, capacity, recovery and operational exercise tests

Release evidence links each invariant and control to the test, environment, input data, result, owner, and artifact proving it. Generated test counts never replace semantic coverage.

14. Repository Review Boundary

- This chapter is a repository-review specification. Exact executable implementation has not been inspected for every target behavior.
- Registered modules, catalog entries, README claims, frontend contracts, or plans are not proof of complete implementation.

Area	Classification
target aggregate, API, tables, state and workflow in this chapter	REFERENCE_ARCHITECTURE
registered module or catalog claim	DOCUMENTATION_ONLY_CLAIM until source inspection
uninspected integration	REQUIRES_REPOSITORY_REVIEW
behavior proven in another repository-grounded chapter	retain that chapter's evidence and classification
contradictory ownership or path claims	CONFLICT_REQUIRES_CANONICALIZATION

No statement upgrades implementation status merely because a file, directory, module name, frontend contract, database entry, plan, or report exists.

15. Worked Conformance Scenario

An authorized principal initiates a Command against an exact subject version. The service validates identity, tenant, mandate, Policy, Evidence, and idempotency. It records the state transition and outbox entry atomically. If an external dependency participates, timeout produces Outcome Unknown; reconciliation queries the source or waits for a verified callback instead of repeating the action blindly.

Portals show source, freshness, version, required action, and uncertainty. AI may extract, compare, summarize, detect anomalies, and recommend through typed Tools, but cannot own the subject or fabricate success. Later correction appends new facts, identifies affected projections and workflows, and preserves the historical Decision context.

16. Conformance Checklist

- ☐ stable identity and proposition ownership are explicit;
- ☐ authority and mandate are evaluated at action time;
- ☐ state, Recommendation, Decision, Intent, execution, and outcome remain distinct;
- ☐ Commands are typed, authorized, idempotent, and version guarded;
- ☐ Events describe completed facts;
- ☐ Evidence includes provenance, time, integrity, qualification, and correction;
- ☐ external outcomes retain their authority source;
- ☐ Portals show freshness and uncertainty;
- ☐ AI is bounded by typed Tools, Policy, approval, and outcome observation;
- ☐ security, tenant, facility, channel, and jurisdiction boundaries are enforced;
- ☐ Outcome Unknown and reconciliation exist where needed;
- ☐ corrections preserve history;
- ☐ tests prove invariants and recovery;
- ☐ implementation status is not upgraded without executable evidence.

17. Status Vocabulary

Status	Meaning
VERIFIED_IMPLEMENTED	Executable source and relevant behavior were inspected.
IMPLEMENTED_WITH_GAP	Executable behavior exists with a material governance or completeness gap.
PARTIAL_IMPLEMENTATION	Only part of the target capability is evidenced.
REFERENCE_ARCHITECTURE	Normative target behavior; no claim that it exists today.
PLANNED_NOT_IMPLEMENTED	Explicitly planned but not evidenced as executable.
DOCUMENTATION_ONLY_CLAIM	Documentation or client contract claims behavior without verified backend evidence.
CONFLICT_REQUIRES_CANONICALIZATION	Sources disagree and no final owner has been established.
REQUIRES_REPOSITORY_REVIEW	Necessary executable evidence has not yet been inspected.

Web Admin — Routes, Pages, Components, and BFF Contracts

Metadata	Value
Volume	4
Chapter ID	V04-P02-01
Subject	WebAdminRouteRegistry
Status	Generated First-Draft Architecture Skeleton - Domain-Specific Expansion Required
Content maturity	TEMPLATE_DERIVED_REFERENCE_SKELETON unless repository citations prove otherwise
Default implementation classification	REFERENCE_ARCHITECTURE / REQUIRES_REPOSITORY_REVIEW
Accountable owner	Portal Architecture / Web Admin
Evidence rule	No implementation claim without inspected executable evidence
Repository	chinair88-prog/allinb2c

1. Executive Orientation

This chapter defines how GTOS shall **inventory routes, layouts, pages, components, server/client boundaries, BFFs, APIs, realtime channels and ownership for platform and tenant administrators, covering configuration, identity, catalog, policy, operations, finance, reporting.**

The specification separates reality, observations, knowledge, Decisions, Intent, execution, and outcomes. A component name, database row, UI label, AI answer, or workflow state does not acquire authority merely because it is visible or technically convenient.

Reality or external outcome

- ≠ Observation
- ≠ Claim
- ≠ derived Perspective
- ≠ Prediction
- ≠ Recommendation
- ≠ authorized Decision
- ≠ execution Intent

1.1 Accountable ownership

The accountable owner is **Portal Architecture / Web Admin**. Supporting applications, shared infrastructure, integration adapters, analytics, and AI coordinate or present the capability but shall not silently own its authoritative propositions.

1.2 Scope

- create and identify the subject
- validate evidence and policy
- make authorized Decisions
- execute typed Commands
- publish completed-fact Events
- query current and historical perspectives
- correct and reconcile outcomes

1.3 Non-goals

- treating a registered Gradle module, catalog record, README, frontend route, migration plan, or generated report as proof of end-to-end implementation;
- direct cross-Domain database writes;
- generic status values that combine lifecycle, approval, provider, document, payment, dispute, and correction state;
- silent replacement of history;
- AI-created authority or fabricated external outcomes.

2. Ubiquitous Language and Subject Model

Subject	Required interpretation
WebAdminRouteRegistry	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit
WebAdminRouteRegistryVersion	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit
WebAdminRouteRegistryDecision	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit
WebAdminRouteRegistryEvidenceSet	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit
WebAdminRouteRegistryException	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit

Reference aggregate:

```
WebAdminRouteRegistry {
  subjectId
  tenantId
  organizationContext
  sourceIdentityRefs[]
  sourceVersionRefs[]
  lifecycleState
  relationshipRefs[]
  decisionRefs[]
  intentRefs[]
  evidenceSetRef
  knowledgeCutoff
  policyRefs[]
  authorityRef
  jurisdictionRefs[]
  createdAt
  effectiveAt
  updatedAt
  version
  correctionOf?
  correlationId
}
```

2.1 Core invariants

- Stable identity precedes relationship, state, and cross-system correlation.
- Effective time and recorded time remain distinct where business truth changes over time.
- Recommendation, Decision, Intent, execution, and outcome are separate concepts.
- No Portal, report, search index, cache, workflow, or AI Agent becomes a shadow owner of Domain truth.
- Binding submitted, approved, issued, accepted, or signed versions are immutable.
- Corrections append governed facts and preserve the original record.
- External authority and provider outcomes retain their source and qualification.
- Tenant and represented-principal context come from trusted authentication and mandate evaluation.
- Retried writes are idempotent and concurrency guarded.
- Outcome Unknown is explicit and reconciled before risky duplicate execution.

2.2 Required standards

- stable identifiers
- typed contracts
- immutable binding versions

- transactional outbox
- idempotent Commands
- explicit Outcome Unknown
- correction lineage
- machine-verifiable conformance

3. Actors, Roles, and Authority

A conformant design distinguishes:

- the natural person acting;
- the service or AI identity invoking a Tool;
- the organization or principal represented;
- the role or relationship granting context;
- the mandate or delegation granting action authority;
- the Policy and jurisdiction limiting the action;
- the reviewer or approver responsible for a binding Decision.

Authority is evaluated at action time. Authentication alone does not grant business authority. Cached permissions and browser-supplied tenant headers are insufficient for high-impact actions.

4. Lifecycle and State Model

State	Semantics
PROPOSED	Distinct governed condition with entry, exit, timeout, correction and authority semantics
VALIDATION_PENDING	Distinct governed condition with entry, exit, timeout, correction and authority semantics
APPROVAL_PENDING	Distinct governed condition with entry, exit, timeout, correction and authority semantics
ACTIVE	Distinct governed condition with entry, exit, timeout, correction and authority semantics
SUSPENDED	Distinct governed condition with entry, exit, timeout, correction and authority semantics
CORRECTION_PENDING	Distinct governed condition with entry, exit, timeout, correction and authority semantics
RETIRED	Distinct governed condition with entry, exit, timeout, correction and authority semantics

```
stateDiagram-v2
    [*] --> PROPOSED
    PROPOSED --> VALIDATION_PENDING
    VALIDATION_PENDING --> APPROVAL_PENDING
    APPROVAL_PENDING --> ACTIVE
    ACTIVE --> SUSPENDED
    SUSPENDED --> CORRECTION_PENDING
    CORRECTION_PENDING --> RETIRED
```

The diagram is a primary reading path. Real implementations may add parallel review, amendment, appeal, timeout, suspension, partial completion, reconciliation, correction, and terminal failure without collapsing their meaning.

4.1 Transition rules

- transition through a typed, authorized Command;
- require exact expected version where concurrent change matters;
- record actor, represented principal, mandate, Policy, reason, and Evidence;
- use an idempotency key for retried writes;
- publish a completed-fact Event after durable state change;
- expose Outcome Unknown for unresolved external completion;
- preserve original and corrected states in historical reconstruction.

5. Decision, Evidence, and Knowledge Cutoff

Reference Decision:

```
Decision {
  decisionId
  decisionType
  subjectRef
  sourceVersionRefs[]
  knowledgeCutoff
  evidenceSetRef
  policyVersionRefs[]
  recommendationRefs[]
  principalId
  representedOrganizationId
  mandateRef
  rationale
  outcome
  decidedAt
  effectiveAt
  correctionOf?
}
```

Evidence records identify issuer or observer, subject, version, observed time, received time, effective interval, integrity, confidence, qualification, contradiction, correction, retention, residency, and access class. A recommendation may assist the Decision but cannot promote itself to the Decision.

6. Commands, Events, Queries, and Contracts

Reference Commands:

- CreateWebAdminRouteRegistry
- ValidateWebAdminRouteRegistry
- ApproveWebAdminRouteRegistry
- ActivateWebAdminRouteRegistry
- SuspendWebAdminRouteRegistry
- CorrectWebAdminRouteRegistry
- RetireWebAdminRouteRegistry

Reference Events:

- WebAdminRouteRegistryCreated
- WebAdminRouteRegistryValidated
- WebAdminRouteRegistryApproved
- WebAdminRouteRegistryActivated
- WebAdminRouteRegistrySuspended
- WebAdminRouteRegistryCorrected
- WebAdminRouteRegistryRetired

Reference queries:

- GetWebAdminRouteRegistry
- ListWebAdminRouteRegistryRecords
- GetWebAdminRouteRegistryTimeline
- GetWebAdminRouteRegistryEvidence
- GetWebAdminRouteRegistryDecisionPackage
- GetWebAdminRouteRegistryExceptions
- GetWebAdminRouteRegistryAuditTrail

Reference API surface:

```
POST /api/v1/webadminrouteregistry/commands
GET  /api/v1/webadminrouteregistry/{id}
GET  /api/v1/webadminrouteregistry/{id}/timeline
GET  /api/v1/webadminrouteregistry/{id}/evidence
GET  /api/v1/webadminrouteregistry/{id}/decisions
POST /api/v1/webadminrouteregistry/{id}/exceptions
POST /api/v1/webadminrouteregistry/{id}/corrections
```

These endpoints are reference contracts, not claims that exact routes exist.

7. Workflow, Failure, and Compensation

```
flowchart TD
    A[Validate identity version and authority] --> B[Collect required evidence]
    B --> C{Policy and evidence gates pass?}
    C -- No --> D[Open exception or request correction]
    D --> B
    C -- Yes --> E[Record Decision or execution Intent]
    E --> F[Execute Domain command or external request]
    F --> G{Outcome known?}
    G -- Success --> H[Record fact and publish Event]
    G -- Failure --> I[Record failure and compensation options]
    G -- Unknown --> J[Enter Outcome Unknown]
    J --> K[Query source or wait for verified callback]
    K --> G
    H --> L[Update projections and downstream workflow]
```

Representative failure modes:

- stale or wrong source version
- duplicate submission or replay
- external timeout after possible success
- contradictory source observations
- lost Event after committed state
- approval or mandate revoked during execution
- downstream action before a mandatory gate
- partial completion across multiple subjects
- evidence later retracted or corrected
- tenant, facility, channel or jurisdiction mismatch

Recovery shall query the authoritative source before duplicate execution, preserve partial success, use compensating Intent rather than destructive rewrite, publish corrections, quarantine high-impact ambiguity, and record affected downstream subjects.

8. Data and Persistence Architecture

Reference table families:

Table family	Purpose
webadminrouterregistry_aggregate	authoritative subject
webadminrouterregistry_version	immutable submitted, approved, issued, or signed versions
webadminrouterregistry_relationship	governed relationships
webadminrouterregistry_decision	binding Decisions and rationale
webadminrouterregistry_evidence_link	provenance and evidence relationships
webadminrouterregistry_event_outbox	transactional Event publication
webadminrouterregistry_idempotency	duplicate-write protection
webadminrouterregistry_exception	exception, claim, dispute, or hold
webadminrouterregistry_correction	correction and supersession lineage
webadminrouterregistry_audit	privileged action evidence

The owning service controls schema and migration. Cross-Domain references use stable identifiers or contracts. Analytics, reports, caches, search, and vector indexes remain projections. Backup, restore, retention, legal hold, privacy, residency, and decommissioning requirements are explicit.

9. Portal and Experience Requirements

- Web Admin: primary experience for platform and tenant administrators.
- Operator and support views: diagnose failed or ambiguous journeys without assuming Domain ownership.
- Domain services: own authoritative data and action eligibility; the Portal consumes typed contracts.

Every Portal displays exact version, owner, state, freshness, required action, and uncertainty. It supports loading, empty, partial, stale, denied, error, timeout, and Outcome Unknown states; accessibility; locale, currency, unit, date, and RTL/LTR correctness; evidence audit; safe retry; and correction history.

10. AI Participation and Tool Governance

Permitted AI tasks:

- extract and classify evidence
- detect anomalies and missing fields
- summarize timelines and contradictions
- recommend next actions with sources and uncertainty

AI shall not own Domain records, grant itself authority, suppress contradictions, silently edit approved versions, fabricate external outcomes, or execute high-impact actions outside typed Tools, policy, approval, idempotency, sandbox, and outcome observation.

Every Agent Run records source context, prompt/model/tool versions, structured output, confidence and limitations, Policy result, approval, Tool calls, provider responses, final outcome, and recovery actions.

11. Security, Privacy, and Trust Boundaries

- least privilege and separation of duties
- tenant, organization, facility, channel and jurisdiction isolation
- integrity protection for binding evidence
- verified external callbacks and anti-replay controls

Additional controls include secret isolation, callback signature verification, audit of privileged action, emergency-access review, sensitive-data minimization, purpose limitation, and threat models for impersonation, tampering, replay, confused deputy, fraud, prompt injection, and exfiltration.

12. Reliability, SLOs, and Operations

SLI	Reference objective
authoritative read availability	99.9% monthly unless a stricter tier applies
acknowledged Command durability	no acknowledged write may be silently lost
Event publication	99.9% within five minutes after committed fact
duplicate prevention	100% for same tenant, Command class, and idempotency key
binding Decision audit completeness	100%
state-state detection	bounded by business deadline

Dashboards and runbooks cover backlog, error budget, dependency failure, retry budget, DLQ, workflow stall, provider outage, reconciliation, capacity, backup/restore, release/rollback, incident command, and post-incident correction.

13. Testing and Continuous Conformance

- aggregate invariant and transition tests
- authorization, delegation, separation-of-duties and tenant-isolation tests
- idempotency and optimistic-concurrency tests
- database migration, key, constraint and rollback tests
- contract, outbox/inbox, duplicate, replay and DLQ tests
- workflow restart, timeout and compensation tests
- Portal E2E tests for success, partial, stale, denied, error and Outcome Unknown states
- accessibility, locale, currency, unit and RTL/LTR tests
- security adversarial, fraud and data-exfiltration tests
- AI evaluation, prompt-injection, policy-bypass and unauthorized-tool tests
- historical reconstruction, correction and audit-completeness tests
- performance, capacity, recovery and operational exercise tests

Release evidence links each invariant and control to the test, environment, input data, result, owner, and artifact proving it. Generated test counts never replace semantic coverage.

14. Repository Review Boundary

- This chapter is a repository-review specification. Exact executable implementation has not been inspected for every target behavior.
- Registered modules, catalog entries, README claims, frontend contracts, or plans are not proof of complete implementation.

Area	Classification
target aggregate, API, tables, state and workflow in this chapter	REFERENCE_ARCHITECTURE
registered module or catalog claim	DOCUMENTATION_ONLY_CLAIM until source inspection
uninspected integration	REQUIRES_REPOSITORY_REVIEW
behavior proven in another repository-grounded chapter	retain that chapter's evidence and classification
contradictory ownership or path claims	CONFLICT_REQUIRES_CANONICALIZATION

No statement upgrades implementation status merely because a file, directory, module name, frontend contract, database entry, plan, or report exists.

15. Worked Conformance Scenario

An authorized principal initiates a Command against an exact subject version. The service validates identity, tenant, mandate, Policy, Evidence, and idempotency. It records the state transition and outbox entry atomically. If an external dependency participates, timeout produces Outcome Unknown; reconciliation queries the source or waits for a verified callback instead of repeating the action blindly.

Portals show source, freshness, version, required action, and uncertainty. AI may extract, compare, summarize, detect anomalies, and recommend through typed Tools, but cannot own the subject or fabricate success. Later correction appends new facts, identifies affected projections and workflows, and preserves the historical Decision context.

16. Conformance Checklist

- ☐ stable identity and proposition ownership are explicit;
- ☐ authority and mandate are evaluated at action time;
- ☐ state, Recommendation, Decision, Intent, execution, and outcome remain distinct;
- ☐ Commands are typed, authorized, idempotent, and version guarded;
- ☐ Events describe completed facts;
- ☐ Evidence includes provenance, time, integrity, qualification, and correction;
- ☐ external outcomes retain their authority source;
- ☐ Portals show freshness and uncertainty;
- ☐ AI is bounded by typed Tools, Policy, approval, and outcome observation;
- ☐ security, tenant, facility, channel, and jurisdiction boundaries are enforced;
- ☐ Outcome Unknown and reconciliation exist where needed;
- ☐ corrections preserve history;
- ☐ tests prove invariants and recovery;
- ☐ implementation status is not upgraded without executable evidence.

17. Status Vocabulary

Status	Meaning
VERIFIED_IMPLEMENTED	Executable source and relevant behavior were inspected. Executable behavior exists with a material governance or completeness gap.
IMPLEMENTED_WITH_GAP	
PARTIAL_IMPLEMENTATION	Only part of the target capability is evidenced.
REFERENCE_ARCHITECTURE	Normative target behavior; no claim that it exists today.
PLANNED_NOT_IMPLEMENTED	Explicitly planned but not evidenced as executable.
DOCUMENTATION_ONLY_CLAIM	Documentation or client contract claims behavior without verified backend evidence.
CONFLICT_REQUIRES_CANONICALIZATION	Sources disagree and no final owner has been established.
REQUIRES_REPOSITORY_REVIEW	Necessary executable evidence has not yet been inspected.

Web Admin — Identity, Session, Authorization, and Trust Boundaries

Metadata	Value
Volume	4
Chapter ID	V04-P02-02
Subject	WebAdminAccessModel
Status	Generated First-Draft Architecture Skeleton - Domain-Specific Expansion Required
Content maturity	TEMPLATE_DERIVED_REFERENCE_SKELETON unless repository citations prove otherwise
Default implementation classification	REFERENCE_ARCHITECTURE / REQUIRES_REPOSITORY_REVIEW
Accountable owner	Portal Architecture / Web Admin
Evidence rule	No implementation claim without inspected executable evidence
Repository	chinair88-prog/allinb2c

1. Executive Orientation

This chapter defines how GTOS shall **govern login, session, role, relationship, tenant, facility, channel, delegation, impersonation and privileged action for platform and tenant administrators, covering configuration, identity, catalog, policy, operations, finance, reporting.**

The specification separates reality, observations, knowledge, Decisions, Intent, execution, and outcomes. A component name, database row, UI label, AI answer, or workflow state does not acquire authority merely because it is visible or technically convenient.

Reality or external outcome
≠ Observation
≠ Claim
≠ derived Perspective
≠ Prediction
≠ Recommendation
≠ authorized Decision
≠ execution Intent

1.1 Accountable ownership

The accountable owner is **Portal Architecture / Web Admin**. Supporting applications, shared infrastructure, integration adapters, analytics, and AI coordinate or present the capability but shall not silently own its authoritative propositions.

1.2 Scope

- create and identify the subject
- validate evidence and policy
- make authorized Decisions
- execute typed Commands
- publish completed-fact Events
- query current and historical perspectives
- correct and reconcile outcomes

1.3 Non-goals

- treating a registered Gradle module, catalog record, README, frontend route, migration plan, or generated report as proof of end-to-end implementation;
- direct cross-Domain database writes;
- generic status values that combine lifecycle, approval, provider, document, payment, dispute, and correction state;
- silent replacement of history;
- AI-created authority or fabricated external outcomes.

2. Ubiquitous Language and Subject Model

Subject	Required interpretation
WebAdminAccessModel	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit
WebAdminAccessModelVersion	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit
WebAdminAccessModelDecision	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit
WebAdminAccessModelEvidenceSet	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit
WebAdminAccessModelException	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit

Reference aggregate:

```
WebAdminAccessModel {  
  subjectId  
  tenantId  
  organizationContext  
  sourceIdentityRefs[]  
  sourceVersionRefs[]  
  lifecycleState  
  relationshipRefs[]  
  decisionRefs[]  
  intentRefs[]  
  evidenceSetRef  
  knowledgeCutoff  
  policyRefs[]  
  authorityRef  
  jurisdictionRefs[]  
  createdAt  
  effectiveAt  
  updatedAt  
  version  
  correctionOf?  
  correlationId  
}
```

2.1 Core invariants

- Stable identity precedes relationship, state, and cross-system correlation.
- Effective time and recorded time remain distinct where business truth changes over time.
- Recommendation, Decision, Intent, execution, and outcome are separate concepts.
- No Portal, report, search index, cache, workflow, or AI Agent becomes a shadow owner of Domain truth.
- Binding submitted, approved, issued, accepted, or signed versions are immutable.
- Corrections append governed facts and preserve the original record.
- External authority and provider outcomes retain their source and qualification.
- Tenant and represented-principal context come from trusted authentication and mandate evaluation.
- Retried writes are idempotent and concurrency guarded.
- Outcome Unknown is explicit and reconciled before risky duplicate execution.

2.2 Required standards

- stable identifiers
- typed contracts
- immutable binding versions

- transactional outbox
- idempotent Commands
- explicit Outcome Unknown
- correction lineage
- machine-verifiable conformance

3. Actors, Roles, and Authority

- A conformant design distinguishes:
- the natural person acting;
 - the service or AI identity invoking a Tool;
 - the organization or principal represented;
 - the role or relationship granting context;
 - the mandate or delegation granting action authority;
 - the Policy and jurisdiction limiting the action;
 - the reviewer or approver responsible for a binding Decision.

Authority is evaluated at action time. Authentication alone does not grant business authority. Cached permissions and browser-supplied tenant headers are insufficient for high-impact actions.

4. Lifecycle and State Model

State	Semantics
PROPOSED	Distinct governed condition with entry, exit, timeout, correction and authority semantics
VALIDATION_PENDING	Distinct governed condition with entry, exit, timeout, correction and authority semantics
APPROVAL_PENDING	Distinct governed condition with entry, exit, timeout, correction and authority semantics
ACTIVE	Distinct governed condition with entry, exit, timeout, correction and authority semantics
SUSPENDED	Distinct governed condition with entry, exit, timeout, correction and authority semantics
CORRECTION_PENDING	Distinct governed condition with entry, exit, timeout, correction and authority semantics
RETIRED	Distinct governed condition with entry, exit, timeout, correction and authority semantics

```
stateDiagram-v2
    [*] --> PROPOSED
    PROPOSED --> VALIDATION_PENDING
    VALIDATION_PENDING --> APPROVAL_PENDING
    APPROVAL_PENDING --> ACTIVE
    ACTIVE --> SUSPENDED
    SUSPENDED --> CORRECTION_PENDING
    CORRECTION_PENDING --> RETIRED
```

The diagram is a primary reading path. Real implementations may add parallel review, amendment, appeal, timeout, suspension, partial completion, reconciliation, correction, and terminal failure without collapsing their meaning.

4.1 Transition rules

- transition through a typed, authorized Command;
- require exact expected version where concurrent change matters;
- record actor, represented principal, mandate, Policy, reason, and Evidence;
- use an idempotency key for retried writes;
- publish a completed-fact Event after durable state change;
- expose Outcome Unknown for unresolved external completion;
- preserve original and corrected states in historical reconstruction.

5. Decision, Evidence, and Knowledge Cutoff

Reference Decision:

```
Decision {
  decisionId
  decisionType
  subjectRef
  sourceVersionRefs[]
  knowledgeCutoff
  evidenceSetRef
  policyVersionRefs[]
  recommendationRefs[]
  principalId
  representedOrganizationId
  mandateRef
  rationale
  outcome
  decidedAt
  effectiveAt
  correctionOf?
}
```

Evidence records identify issuer or observer, subject, version, observed time, received time, effective interval, integrity, confidence, qualification, contradiction, correction, retention, residency, and access class. A recommendation may assist the Decision but cannot promote itself to the Decision.

6. Commands, Events, Queries, and Contracts

Reference Commands:

- CreateWebAdminAccessModel
- ValidateWebAdminAccessModel
- ApproveWebAdminAccessModel
- ActivateWebAdminAccessModel
- SuspendWebAdminAccessModel
- CorrectWebAdminAccessModel
- RetireWebAdminAccessModel

Reference Events:

- WebAdminAccessModelCreated
- WebAdminAccessModelValidated
- WebAdminAccessModelApproved
- WebAdminAccessModelActivated
- WebAdminAccessModelSuspended
- WebAdminAccessModelCorrected
- WebAdminAccessModelRetired

Reference queries:

- GetWebAdminAccessModel
- ListWebAdminAccessModelRecords
- GetWebAdminAccessModelTimeline
- GetWebAdminAccessModelEvidence
- GetWebAdminAccessModelDecisionPackage
- GetWebAdminAccessModelExceptions
- GetWebAdminAccessModelAuditTrail

Reference API surface:

```
POST /api/v1/webadminaccessmodel/commands
GET  /api/v1/webadminaccessmodel/{id}
GET  /api/v1/webadminaccessmodel/{id}/timeline
GET  /api/v1/webadminaccessmodel/{id}/evidence
GET  /api/v1/webadminaccessmodel/{id}/decisions
POST /api/v1/webadminaccessmodel/{id}/exceptions
POST /api/v1/webadminaccessmodel/{id}/corrections
```

These endpoints are reference contracts, not claims that exact routes exist.

7. Workflow, Failure, and Compensation

```
flowchart TD
    A[Validate identity version and authority] --> B[Collect required evidence]
    B --> C{Policy and evidence gates pass?}
    C -- No --> D[Open exception or request correction]
    D --> B
    C -- Yes --> E[Record Decision or execution Intent]
    E --> F[Execute Domain command or external request]
    F --> G{Outcome known?}
    G -- Success --> H[Record fact and publish Event]
    G -- Failure --> I[Record failure and compensation options]
    G -- Unknown --> J[Enter Outcome Unknown]
    J --> K[Query source or wait for verified callback]
    K --> G
    H --> L[Update projections and downstream workflow]
```

Representative failure modes:

- stale or wrong source version
- duplicate submission or replay
- external timeout after possible success
- contradictory source observations
- lost Event after committed state
- approval or mandate revoked during execution
- downstream action before a mandatory gate
- partial completion across multiple subjects
- evidence later retracted or corrected
- tenant, facility, channel or jurisdiction mismatch

Recovery shall query the authoritative source before duplicate execution, preserve partial success, use compensating Intent rather than destructive rewrite, publish corrections, quarantine high-impact ambiguity, and record affected downstream subjects.

8. Data and Persistence Architecture

Reference table families:

Table family	Purpose
webadminaccessmodel_aggregate	authoritative subject
webadminaccessmodel_version	immutable submitted, approved, issued, or signed versions
webadminaccessmodel_relationship	governed relationships
webadminaccessmodel_decision	binding Decisions and rationale
webadminaccessmodel_evidence_link	provenance and evidence relationships
webadminaccessmodel_event_outbox	transactional Event publication
webadminaccessmodel_idempotency	duplicate-write protection
webadminaccessmodel_exception	exception, claim, dispute, or hold
webadminaccessmodel_correction	correction and supersession lineage
webadminaccessmodel_audit	privileged action evidence

The owning service controls schema and migration. Cross-Domain references use stable identifiers or contracts. Analytics, reports, caches, search, and vector indexes remain projections. Backup, restore, retention, legal hold, privacy, residency, and decommissioning requirements are explicit.

9. Portal and Experience Requirements

- Web Admin: primary experience for platform and tenant administrators.
- Operator and support views: diagnose failed or ambiguous journeys without assuming Domain ownership.
- Domain services: own authoritative data and action eligibility; the Portal consumes typed contracts.

Every Portal displays exact version, owner, state, freshness, required action, and uncertainty. It supports loading, empty, partial, stale, denied, error, timeout, and Outcome Unknown states; accessibility; locale, currency, unit, date, and RTL/LTR correctness; evidence audit; safe retry; and correction history.

10. AI Participation and Tool Governance

Permitted AI tasks:

- extract and classify evidence
- detect anomalies and missing fields
- summarize timelines and contradictions
- recommend next actions with sources and uncertainty

AI shall not own Domain records, grant itself authority, suppress contradictions, silently edit approved versions, fabricate external outcomes, or execute high-impact actions outside typed Tools, policy, approval, idempotency, sandbox, and outcome observation.

Every Agent Run records source context, prompt/model/tool versions, structured output, confidence and limitations, Policy result, approval, Tool calls, provider responses, final outcome, and recovery actions.

11. Security, Privacy, and Trust Boundaries

- least privilege and separation of duties
- tenant, organization, facility, channel and jurisdiction isolation
- integrity protection for binding evidence
- verified external callbacks and anti-replay controls

Additional controls include secret isolation, callback signature verification, audit of privileged action, emergency-access review, sensitive-data minimization, purpose limitation, and threat models for impersonation, tampering, replay, confused deputy, fraud, prompt injection, and exfiltration.

12. Reliability, SLOs, and Operations

SLI	Reference objective
authoritative read availability	99.9% monthly unless a stricter tier applies
acknowledged Command durability	no acknowledged write may be silently lost
Event publication	99.9% within five minutes after committed fact
duplicate prevention	100% for same tenant, Command class, and idempotency key
binding Decision audit completeness	100%
state-state detection	bounded by business deadline

Dashboards and runbooks cover backlog, error budget, dependency failure, retry budget, DLQ, workflow stall, provider outage, reconciliation, capacity, backup/restore, release/rollback, incident command, and post-incident correction.

13. Testing and Continuous Conformance

- aggregate invariant and transition tests
- authorization, delegation, separation-of-duties and tenant-isolation tests
- idempotency and optimistic-concurrency tests
- database migration, key, constraint and rollback tests
- contract, outbox/inbox, duplicate, replay and DLQ tests
- workflow restart, timeout and compensation tests
- Portal E2E tests for success, partial, stale, denied, error and Outcome Unknown states
- accessibility, locale, currency, unit and RTL/LTR tests
- security adversarial, fraud and data-exfiltration tests
- AI evaluation, prompt-injection, policy-bypass and unauthorized-tool tests
- historical reconstruction, correction and audit-completeness tests
- performance, capacity, recovery and operational exercise tests

Release evidence links each invariant and control to the test, environment, input data, result, owner, and artifact proving it. Generated test counts never replace semantic coverage.

14. Repository Review Boundary

- This chapter is a repository-review specification. Exact executable implementation has not been inspected for every target behavior.
- Registered modules, catalog entries, README claims, frontend contracts, or plans are not proof of complete implementation.

Area	Classification
target aggregate, API, tables, state and workflow in this chapter	REFERENCE_ARCHITECTURE
registered module or catalog claim	DOCUMENTATION_ONLY_CLAIM until source inspection
uninspected integration	REQUIRES_REPOSITORY_REVIEW
behavior proven in another repository-grounded chapter	retain that chapter's evidence and classification
contradictory ownership or path claims	CONFLICT_REQUIRES_CANONICALIZATION

No statement upgrades implementation status merely because a file, directory, module name, frontend contract, database entry, plan, or report exists.

15. Worked Conformance Scenario

An authorized principal initiates a Command against an exact subject version. The service validates identity, tenant, mandate, Policy, Evidence, and idempotency. It records the state transition and outbox entry atomically. If an external dependency participates, timeout produces Outcome Unknown; reconciliation queries the source or waits for a verified callback instead of repeating the action blindly.

Portals show source, freshness, version, required action, and uncertainty. AI may extract, compare, summarize, detect anomalies, and recommend through typed Tools, but cannot own the subject or fabricate success. Later correction appends new facts, identifies affected projections and workflows, and preserves the historical Decision context.

16. Conformance Checklist

- ☐ stable identity and proposition ownership are explicit;
- ☐ authority and mandate are evaluated at action time;
- ☐ state, Recommendation, Decision, Intent, execution, and outcome remain distinct;
- ☐ Commands are typed, authorized, idempotent, and version guarded;
- ☐ Events describe completed facts;
- ☐ Evidence includes provenance, time, integrity, qualification, and correction;
- ☐ external outcomes retain their authority source;
- ☐ Portals show freshness and uncertainty;
- ☐ AI is bounded by typed Tools, Policy, approval, and outcome observation;
- ☐ security, tenant, facility, channel, and jurisdiction boundaries are enforced;
- ☐ Outcome Unknown and reconciliation exist where needed;
- ☐ corrections preserve history;
- ☐ tests prove invariants and recovery;
- ☐ implementation status is not upgraded without executable evidence.

17. Status Vocabulary

Status	Meaning
VERIFIED_IMPLEMENTED	Executable source and relevant behavior were inspected.
IMPLEMENTED_WITH_GAP	Executable behavior exists with a material governance or completeness gap.
PARTIAL_IMPLEMENTATION	Only part of the target capability is evidenced.
REFERENCE_ARCHITECTURE	Normative target behavior; no claim that it exists today.
PLANNED_NOT_IMPLEMENTED	Explicitly planned but not evidenced as executable.
DOCUMENTATION_ONLY_CLAIM	Documentation or client contract claims behavior without verified backend evidence.
CONFLICT_REQUIRES_CANONICALIZATION	Sources disagree and no final owner has been established.
REQUIRES_REPOSITORY_REVIEW	Necessary executable evidence has not yet been inspected.

Web Admin — UX States, Accessibility, Localization, Analytics, and E2E

Metadata	Value
Volume	4
Chapter ID	V04-P02-03
Subject	WebAdminExperienceStandard
Status	Generated First-Draft Architecture Skeleton - Domain-Specific Expansion Required
Content maturity	TEMPLATE_DERIVED_REFERENCE_SKELETON unless repository citations prove otherwise
Default implementation classification	REFERENCE_ARCHITECTURE / REQUIRES_REPOSITORY_REVIEW
Accountable owner	Portal Architecture / Web Admin
Evidence rule	No implementation claim without inspected executable evidence
Repository	chinair88-prog/allinb2c

1. Executive Orientation

This chapter defines how GTOS shall **specify loading, empty, partial, stale, error, denied, offline, accessibility, RTL/LTR, analytics, audit and test journeys for platform and tenant administrators, covering configuration, identity, catalog, policy, operations, finance, reporting.**

The specification separates reality, observations, knowledge, Decisions, Intent, execution, and outcomes. A component name, database row, UI label, AI answer, or workflow state does not acquire authority merely because it is visible or technically convenient.

Reality or external outcome

- ≠ Observation
- ≠ Claim
- ≠ derived Perspective
- ≠ Prediction
- ≠ Recommendation
- ≠ authorized Decision
- ≠ execution Intent

1.1 Accountable ownership

The accountable owner is **Portal Architecture / Web Admin**. Supporting applications, shared infrastructure, integration adapters, analytics, and AI coordinate or present the capability but shall not silently own its authoritative propositions.

1.2 Scope

- create and identify the subject
- validate evidence and policy
- make authorized Decisions
- execute typed Commands
- publish completed-fact Events
- query current and historical perspectives
- correct and reconcile outcomes

1.3 Non-goals

- treating a registered Gradle module, catalog record, README, frontend route, migration plan, or generated report as proof of end-to-end implementation;
- direct cross-Domain database writes;
- generic status values that combine lifecycle, approval, provider, document, payment, dispute, and correction state;
- silent replacement of history;
- AI-created authority or fabricated external outcomes.

2. Ubiquitous Language and Subject Model

Subject	Required interpretation
WebAdminExperienceStandard	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit
WebAdminExperienceStandardVersion	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit
WebAdminExperienceStandardDecision	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit
WebAdminExperienceStandardEvidenceSet	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit
WebAdminExperienceStandardException	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit

Reference aggregate:

```
WebAdminExperienceStandard {
  subjectId
  tenantId
  organizationContext
  sourceIdentityRefs[]
  sourceVersionRefs[]
  lifecycleState
  relationshipRefs[]
  decisionRefs[]
  intentRefs[]
  evidenceSetRef
  knowledgeCutoff
  policyRefs[]
  authorityRef
  jurisdictionRefs[]
  createdAt
  effectiveAt
  updatedAt
  version
  correctionOf?
  correlationId
}
```

2.1 Core invariants

- Stable identity precedes relationship, state, and cross-system correlation.
- Effective time and recorded time remain distinct where business truth changes over time.
- Recommendation, Decision, Intent, execution, and outcome are separate concepts.
- No Portal, report, search index, cache, workflow, or AI Agent becomes a shadow owner of Domain truth.
- Binding submitted, approved, issued, accepted, or signed versions are immutable.
- Corrections append governed facts and preserve the original record.
- External authority and provider outcomes retain their source and qualification.
- Tenant and represented-principal context come from trusted authentication and mandate evaluation.
- Retried writes are idempotent and concurrency guarded.
- Outcome Unknown is explicit and reconciled before risky duplicate execution.

2.2 Required standards

- stable identifiers
- typed contracts
- immutable binding versions

- transactional outbox
- idempotent Commands
- explicit Outcome Unknown
- correction lineage
- machine-verifiable conformance

3. Actors, Roles, and Authority

A conformant design distinguishes:

- the natural person acting;
- the service or AI identity invoking a Tool;
- the organization or principal represented;
- the role or relationship granting context;
- the mandate or delegation granting action authority;
- the Policy and jurisdiction limiting the action;
- the reviewer or approver responsible for a binding Decision.

Authority is evaluated at action time. Authentication alone does not grant business authority. Cached permissions and browser-supplied tenant headers are insufficient for high-impact actions.

4. Lifecycle and State Model

State	Semantics
PROPOSED	Distinct governed condition with entry, exit, timeout, correction and authority semantics
VALIDATION_PENDING	Distinct governed condition with entry, exit, timeout, correction and authority semantics
APPROVAL_PENDING	Distinct governed condition with entry, exit, timeout, correction and authority semantics
ACTIVE	Distinct governed condition with entry, exit, timeout, correction and authority semantics
SUSPENDED	Distinct governed condition with entry, exit, timeout, correction and authority semantics
CORRECTION_PENDING	Distinct governed condition with entry, exit, timeout, correction and authority semantics
RETIRED	Distinct governed condition with entry, exit, timeout, correction and authority semantics

```
stateDiagram-v2
    [*] --> PROPOSED
    PROPOSED --> VALIDATION_PENDING
    VALIDATION_PENDING --> APPROVAL_PENDING
    APPROVAL_PENDING --> ACTIVE
    ACTIVE --> SUSPENDED
    SUSPENDED --> CORRECTION_PENDING
    CORRECTION_PENDING --> RETIRED
```

The diagram is a primary reading path. Real implementations may add parallel review, amendment, appeal, timeout, suspension, partial completion, reconciliation, correction, and terminal failure without collapsing their meaning.

4.1 Transition rules

- transition through a typed, authorized Command;
- require exact expected version where concurrent change matters;
- record actor, represented principal, mandate, Policy, reason, and Evidence;
- use an idempotency key for retried writes;
- publish a completed-fact Event after durable state change;
- expose Outcome Unknown for unresolved external completion;
- preserve original and corrected states in historical reconstruction.

5. Decision, Evidence, and Knowledge Cutoff

Reference Decision:

```
Decision {
  decisionId
  decisionType
  subjectRef
  sourceVersionRefs[]
  knowledgeCutoff
  evidenceSetRef
  policyVersionRefs[]
  recommendationRefs[]
  principalId
  representedOrganizationId
  mandateRef
  rationale
  outcome
  decidedAt
  effectiveAt
  correctionOf?
}
```

Evidence records identify issuer or observer, subject, version, observed time, received time, effective interval, integrity, confidence, qualification, contradiction, correction, retention, residency, and access class. A recommendation may assist the Decision but cannot promote itself to the Decision.

6. Commands, Events, Queries, and Contracts

Reference Commands:

- CreateWebAdminExperienceStandard
- ValidateWebAdminExperienceStandard
- ApproveWebAdminExperienceStandard
- ActivateWebAdminExperienceStandard
- SuspendWebAdminExperienceStandard
- CorrectWebAdminExperienceStandard
- RetireWebAdminExperienceStandard

Reference Events:

- WebAdminExperienceStandardCreated
- WebAdminExperienceStandardValidated
- WebAdminExperienceStandardApproved
- WebAdminExperienceStandardActivated
- WebAdminExperienceStandardSuspended
- WebAdminExperienceStandardCorrected
- WebAdminExperienceStandardRetired

Reference queries:

- GetWebAdminExperienceStandard
- ListWebAdminExperienceStandardRecords
- GetWebAdminExperienceStandardTimeline
- GetWebAdminExperienceStandardEvidence
- GetWebAdminExperienceStandardDecisionPackage
- GetWebAdminExperienceStandardExceptions
- GetWebAdminExperienceStandardAuditTrail

Reference API surface:

```
POST /api/v1/webadminexperiencestandard/commands
GET  /api/v1/webadminexperiencestandard/{id}
GET  /api/v1/webadminexperiencestandard/{id}/timeline
GET  /api/v1/webadminexperiencestandard/{id}/evidence
GET  /api/v1/webadminexperiencestandard/{id}/decisions
POST /api/v1/webadminexperiencestandard/{id}/exceptions
POST /api/v1/webadminexperiencestandard/{id}/corrections
```

These endpoints are reference contracts, not claims that exact routes exist.

7. Workflow, Failure, and Compensation

flowchart TD

```
A[Validate identity version and authority] --> B[Collect required evidence]
B --> C{Policy and evidence gates pass?}
C -- No --> D[Open exception or request correction]
D --> B
C -- Yes --> E[Record Decision or execution Intent]
E --> F[Execute Domain command or external request]
F --> G{Outcome known?}
G -- Success --> H[Record fact and publish Event]
G -- Failure --> I[Record failure and compensation options]
G -- Unknown --> J[Enter Outcome Unknown]
J --> K[Query source or wait for verified callback]
K --> G
H --> L[Update projections and downstream workflow]
```

Representative failure modes:

- stale or wrong source version
- duplicate submission or replay
- external timeout after possible success
- contradictory source observations
- lost Event after committed state
- approval or mandate revoked during execution
- downstream action before a mandatory gate
- partial completion across multiple subjects
- evidence later retracted or corrected
- tenant, facility, channel or jurisdiction mismatch

Recovery shall query the authoritative source before duplicate execution, preserve partial success, use compensating Intent rather than destructive rewrite, publish corrections, quarantine high-impact ambiguity, and record affected downstream subjects.

8. Data and Persistence Architecture

Reference table families:

Table family	Purpose
webadminexperiencestandard_aggregate	authoritative subject
webadminexperiencestandard_version	immutable submitted, approved, issued, or signed versions
webadminexperiencestandard_relationship	governed relationships
webadminexperiencestandard_decision	binding Decisions and rationale
webadminexperiencestandard_evidence_link	provenance and evidence relationships
webadminexperiencestandard_event_outbox	transactional Event publication
webadminexperiencestandard_idempotency	duplicate-write protection
webadminexperiencestandard_exception	exception, claim, dispute, or hold
webadminexperiencestandard_correction	correction and supersession lineage
webadminexperiencestandard_audit	privileged action evidence

The owning service controls schema and migration. Cross-Domain references use stable identifiers or contracts. Analytics, reports, caches, search, and vector indexes remain projections. Backup, restore, retention, legal hold, privacy, residency, and decommissioning requirements are explicit.

9. Portal and Experience Requirements

- Web Admin: primary experience for platform and tenant administrators.
- Operator and support views: diagnose failed or ambiguous journeys without assuming Domain ownership.
- Domain services: own authoritative data and action eligibility; the Portal consumes typed contracts.

Every Portal displays exact version, owner, state, freshness, required action, and uncertainty. It supports loading, empty, partial, stale, denied, error, timeout, and Outcome Unknown states; accessibility; locale, currency, unit, date, and RTL/LTR correctness; evidence audit; safe retry; and correction history.

10. AI Participation and Tool Governance

Permitted AI tasks:

- extract and classify evidence
- detect anomalies and missing fields
- summarize timelines and contradictions
- recommend next actions with sources and uncertainty

AI shall not own Domain records, grant itself authority, suppress contradictions, silently edit approved versions, fabricate external outcomes, or execute high-impact actions outside typed Tools, policy, approval, idempotency, sandbox, and outcome observation.

Every Agent Run records source context, prompt/model/tool versions, structured output, confidence and limitations, Policy result, approval, Tool calls, provider responses, final outcome, and recovery actions.

11. Security, Privacy, and Trust Boundaries

- least privilege and separation of duties
- tenant, organization, facility, channel and jurisdiction isolation
- integrity protection for binding evidence
- verified external callbacks and anti-replay controls

Additional controls include secret isolation, callback signature verification, audit of privileged action, emergency-access review, sensitive-data minimization, purpose limitation, and threat models for impersonation, tampering, replay, confused deputy, fraud, prompt injection, and exfiltration.

12. Reliability, SLOs, and Operations

SLI	Reference objective
authoritative read availability	99.9% monthly unless a stricter tier applies
acknowledged Command durability	no acknowledged write may be silently lost
Event publication	99.9% within five minutes after committed fact
duplicate prevention	100% for same tenant, Command class, and idempotency key
binding Decision audit completeness	100%
state-state detection	bounded by business deadline

Dashboards and runbooks cover backlog, error budget, dependency failure, retry budget, DLQ, workflow stall, provider outage, reconciliation, capacity, backup/restore, release/rollback, incident command, and post-incident correction.

13. Testing and Continuous Conformance

- aggregate invariant and transition tests
- authorization, delegation, separation-of-duties and tenant-isolation tests
- idempotency and optimistic-concurrency tests
- database migration, key, constraint and rollback tests
- contract, outbox/inbox, duplicate, replay and DLQ tests
- workflow restart, timeout and compensation tests
- Portal E2E tests for success, partial, stale, denied, error and Outcome Unknown states
- accessibility, locale, currency, unit and RTL/LTR tests
- security adversarial, fraud and data-exfiltration tests
- AI evaluation, prompt-injection, policy-bypass and unauthorized-tool tests
- historical reconstruction, correction and audit-completeness tests
- performance, capacity, recovery and operational exercise tests

Release evidence links each invariant and control to the test, environment, input data, result, owner, and artifact proving it. Generated test counts never replace semantic coverage.

14. Repository Review Boundary

- This chapter is a repository-review specification. Exact executable implementation has not been inspected for every target behavior.
- Registered modules, catalog entries, README claims, frontend contracts, or plans are not proof of complete implementation.

Area	Classification
target aggregate, API, tables, state and workflow in this chapter	REFERENCE_ARCHITECTURE
registered module or catalog claim	DOCUMENTATION_ONLY_CLAIM until source inspection
uninspected integration	REQUIRES_REPOSITORY_REVIEW
behavior proven in another repository-grounded chapter	retain that chapter's evidence and classification
contradictory ownership or path claims	CONFLICT_REQUIRES_CANONICALIZATION

No statement upgrades implementation status merely because a file, directory, module name, frontend contract, database entry, plan, or report exists.

15. Worked Conformance Scenario

An authorized principal initiates a Command against an exact subject version. The service validates identity, tenant, mandate, Policy, Evidence, and idempotency. It records the state transition and outbox entry atomically. If an external dependency participates, timeout produces Outcome Unknown; reconciliation queries the source or waits for a verified callback instead of repeating the action blindly.

Portals show source, freshness, version, required action, and uncertainty. AI may extract, compare, summarize, detect anomalies, and recommend through typed Tools, but cannot own the subject or fabricate success. Later correction appends new facts, identifies affected projections and workflows, and preserves the historical Decision context.

16. Conformance Checklist

- ☐ stable identity and proposition ownership are explicit;
- ☐ authority and mandate are evaluated at action time;
- ☐ state, Recommendation, Decision, Intent, execution, and outcome remain distinct;
- ☐ Commands are typed, authorized, idempotent, and version guarded;
- ☐ Events describe completed facts;
- ☐ Evidence includes provenance, time, integrity, qualification, and correction;
- ☐ external outcomes retain their authority source;
- ☐ Portals show freshness and uncertainty;
- ☐ AI is bounded by typed Tools, Policy, approval, and outcome observation;
- ☐ security, tenant, facility, channel, and jurisdiction boundaries are enforced;
- ☐ Outcome Unknown and reconciliation exist where needed;
- ☐ corrections preserve history;
- ☐ tests prove invariants and recovery;
- ☐ implementation status is not upgraded without executable evidence.

17. Status Vocabulary

Status	Meaning
VERIFIED_IMPLEMENTED	Executable source and relevant behavior were inspected.
IMPLEMENTED_WITH_GAP	Executable behavior exists with a material governance or completeness gap.
PARTIAL_IMPLEMENTATION	Only part of the target capability is evidenced.
REFERENCE_ARCHITECTURE	Normative target behavior; no claim that it exists today.
PLANNED_NOT_IMPLEMENTED	Explicitly planned but not evidenced as executable.
DOCUMENTATION_ONLY_CLAIM	Documentation or client contract claims behavior without verified backend evidence.
CONFLICT_REQUIRES_CANONICALIZATION	Sources disagree and no final owner has been established.
REQUIRES_REPOSITORY_REVIEW	Necessary executable evidence has not yet been inspected.

Web Operator — Portal Orientation and Information Architecture

Metadata	Value
Volume	4
Chapter ID	V04-P03-00
Subject	WebOperatorPortal
Status	Generated First-Draft Architecture Skeleton - Domain-Specific Expansion Required
Content maturity	TEMPLATE_DERIVED_REFERENCE_SKELETON unless repository citations prove otherwise
Default implementation classification	REFERENCE_ARCHITECTURE / REQUIRES_REPOSITORY_REVIEW
Accountable owner	Portal Architecture / Web Operator
Evidence rule	No implementation claim without inspected executable evidence
Repository	chinair88-prog/allinb2c

1. Executive Orientation

This chapter defines how GTOS shall **define personas, navigation, route ownership, domain dependencies and experience boundaries for platform operators and support staff, covering exception management, reconciliation, workflow, service health, audit, correction.**

The specification separates reality, observations, knowledge, Decisions, Intent, execution, and outcomes. A component name, database row, UI label, AI answer, or workflow state does not acquire authority merely because it is visible or technically convenient.

Reality or external outcome

- ≠ Observation
- ≠ Claim
- ≠ derived Perspective
- ≠ Prediction
- ≠ Recommendation
- ≠ authorized Decision
- ≠ execution Intent

1.1 Accountable ownership

The accountable owner is **Portal Architecture / Web Operator**. Supporting applications, shared infrastructure, integration adapters, analytics, and AI coordinate or present the capability but shall not silently own its authoritative propositions.

1.2 Scope

- create and identify the subject
- validate evidence and policy
- make authorized Decisions
- execute typed Commands
- publish completed-fact Events
- query current and historical perspectives
- correct and reconcile outcomes

1.3 Non-goals

- treating a registered Gradle module, catalog record, README, frontend route, migration plan, or generated report as proof of end-to-end implementation;
- direct cross-Domain database writes;
- generic status values that combine lifecycle, approval, provider, document, payment, dispute, and correction state;
- silent replacement of history;
- AI-created authority or fabricated external outcomes.

2. Ubiquitous Language and Subject Model

Subject	Required interpretation
WebOperatorPortal	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit
WebOperatorPortalVersion	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit
WebOperatorPortalDecision	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit
WebOperatorPortalEvidenceSet	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit
WebOperatorPortalException	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit

Reference aggregate:

```
WebOperatorPortal {  
  subjectId  
  tenantId  
  organizationContext  
  sourceIdentityRefs[]  
  sourceVersionRefs[]  
  lifecycleState  
  relationshipRefs[]  
  decisionRefs[]  
  intentRefs[]  
  evidenceSetRef  
  knowledgeCutoff  
  policyRefs[]  
  authorityRef  
  jurisdictionRefs[]  
  createdAt  
  effectiveAt  
  updatedAt  
  version  
  correctionOf?  
  correlationId  
}
```

2.1 Core invariants

- Stable identity precedes relationship, state, and cross-system correlation.
- Effective time and recorded time remain distinct where business truth changes over time.
- Recommendation, Decision, Intent, execution, and outcome are separate concepts.
- No Portal, report, search index, cache, workflow, or AI Agent becomes a shadow owner of Domain truth.
- Binding submitted, approved, issued, accepted, or signed versions are immutable.
- Corrections append governed facts and preserve the original record.
- External authority and provider outcomes retain their source and qualification.
- Tenant and represented-principal context come from trusted authentication and mandate evaluation.
- Retried writes are idempotent and concurrency guarded.
- Outcome Unknown is explicit and reconciled before risky duplicate execution.

2.2 Required standards

- stable identifiers
- typed contracts
- immutable binding versions

- transactional outbox
- idempotent Commands
- explicit Outcome Unknown
- correction lineage
- machine-verifiable conformance

3. Actors, Roles, and Authority

- A conformant design distinguishes:
- the natural person acting;
 - the service or AI identity invoking a Tool;
 - the organization or principal represented;
 - the role or relationship granting context;
 - the mandate or delegation granting action authority;
 - the Policy and jurisdiction limiting the action;
 - the reviewer or approver responsible for a binding Decision.

Authority is evaluated at action time. Authentication alone does not grant business authority. Cached permissions and browser-supplied tenant headers are insufficient for high-impact actions.

4. Lifecycle and State Model

State	Semantics
PROPOSED	Distinct governed condition with entry, exit, timeout, correction and authority semantics
VALIDATION_PENDING	Distinct governed condition with entry, exit, timeout, correction and authority semantics
APPROVAL_PENDING	Distinct governed condition with entry, exit, timeout, correction and authority semantics
ACTIVE	Distinct governed condition with entry, exit, timeout, correction and authority semantics
SUSPENDED	Distinct governed condition with entry, exit, timeout, correction and authority semantics
CORRECTION_PENDING	Distinct governed condition with entry, exit, timeout, correction and authority semantics
RETIRED	Distinct governed condition with entry, exit, timeout, correction and authority semantics

```
stateDiagram-v2
    [*] --> PROPOSED
    PROPOSED --> VALIDATION_PENDING
    VALIDATION_PENDING --> APPROVAL_PENDING
    APPROVAL_PENDING --> ACTIVE
    ACTIVE --> SUSPENDED
    SUSPENDED --> CORRECTION_PENDING
    CORRECTION_PENDING --> RETIRED
```

The diagram is a primary reading path. Real implementations may add parallel review, amendment, appeal, timeout, suspension, partial completion, reconciliation, correction, and terminal failure without collapsing their meaning.

4.1 Transition rules

- transition through a typed, authorized Command;
- require exact expected version where concurrent change matters;
- record actor, represented principal, mandate, Policy, reason, and Evidence;
- use an idempotency key for retried writes;
- publish a completed-fact Event after durable state change;
- expose Outcome Unknown for unresolved external completion;
- preserve original and corrected states in historical reconstruction.

5. Decision, Evidence, and Knowledge Cutoff

Reference Decision:

```
Decision {
  decisionId
  decisionType
  subjectRef
  sourceVersionRefs[]
  knowledgeCutoff
  evidenceSetRef
  policyVersionRefs[]
  recommendationRefs[]
  principalId
  representedOrganizationId
  mandateRef
  rationale
  outcome
  decidedAt
  effectiveAt
  correctionOf?
}
```

Evidence records identify issuer or observer, subject, version, observed time, received time, effective interval, integrity, confidence, qualification, contradiction, correction, retention, residency, and access class. A recommendation may assist the Decision but cannot promote itself to the Decision.

6. Commands, Events, Queries, and Contracts

Reference Commands:

- CreateWebOperatorPortal
- ValidateWebOperatorPortal
- ApproveWebOperatorPortal
- ActivateWebOperatorPortal
- SuspendWebOperatorPortal
- CorrectWebOperatorPortal
- RetireWebOperatorPortal

Reference Events:

- WebOperatorPortalCreated
- WebOperatorPortalValidated
- WebOperatorPortalApproved
- WebOperatorPortalActivated
- WebOperatorPortalSuspended
- WebOperatorPortalCorrected
- WebOperatorPortalRetired

Reference queries:

- GetWebOperatorPortal
- ListWebOperatorPortalRecords
- GetWebOperatorPortalTimeline
- GetWebOperatorPortalEvidence
- GetWebOperatorPortalDecisionPackage
- GetWebOperatorPortalExceptions
- GetWebOperatorPortalAuditTrail

Reference API surface:

```
POST /api/v1/weboperatorportal/commands
GET  /api/v1/weboperatorportal/{id}
GET  /api/v1/weboperatorportal/{id}/timeline
GET  /api/v1/weboperatorportal/{id}/evidence
GET  /api/v1/weboperatorportal/{id}/decisions
POST /api/v1/weboperatorportal/{id}/exceptions
POST /api/v1/weboperatorportal/{id}/corrections
```

These endpoints are reference contracts, not claims that exact routes exist.

7. Workflow, Failure, and Compensation

flowchart TD

```
A[Validate identity version and authority] --> B[Collect required evidence]
B --> C{Policy and evidence gates pass?}
C -- No --> D[Open exception or request correction]
D --> B
C -- Yes --> E[Record Decision or execution Intent]
E --> F[Execute Domain command or external request]
F --> G{Outcome known?}
G -- Success --> H[Record fact and publish Event]
G -- Failure --> I[Record failure and compensation options]
G -- Unknown --> J[Enter Outcome Unknown]
J --> K[Query source or wait for verified callback]
K --> G
H --> L[Update projections and downstream workflow]
```

Representative failure modes:

- stale or wrong source version
- duplicate submission or replay
- external timeout after possible success
- contradictory source observations
- lost Event after committed state
- approval or mandate revoked during execution
- downstream action before a mandatory gate
- partial completion across multiple subjects
- evidence later retracted or corrected
- tenant, facility, channel or jurisdiction mismatch

Recovery shall query the authoritative source before duplicate execution, preserve partial success, use compensating Intent rather than destructive rewrite, publish corrections, quarantine high-impact ambiguity, and record affected downstream subjects.

8. Data and Persistence Architecture

Reference table families:

Table family	Purpose
weboperatorportal_aggregate	authoritative subject
weboperatorportal_version	immutable submitted, approved, issued, or signed versions
weboperatorportal_relationship	governed relationships
weboperatorportal_decision	binding Decisions and rationale
weboperatorportal_evidence_link	provenance and evidence relationships
weboperatorportal_event_outbox	transactional Event publication
weboperatorportal_idempotency	duplicate-write protection
weboperatorportal_exception	exception, claim, dispute, or hold
weboperatorportal_correction	correction and supersession lineage
weboperatorportal_audit	privileged action evidence

The owning service controls schema and migration. Cross-Domain references use stable identifiers or contracts. Analytics, reports, caches, search, and vector indexes remain projections. Backup, restore, retention, legal hold, privacy, residency, and decommissioning requirements are explicit.

9. Portal and Experience Requirements

- Web Operator: primary experience for platform operators and support staff.
- Operator and support views: diagnose failed or ambiguous journeys without assuming Domain ownership.
- Domain services: own authoritative data and action eligibility; the Portal consumes typed contracts.

Every Portal displays exact version, owner, state, freshness, required action, and uncertainty. It supports loading, empty, partial, stale, denied, error, timeout, and Outcome Unknown states; accessibility; locale, currency, unit, date, and RTL/LTR correctness; evidence audit; safe retry; and correction history.

10. AI Participation and Tool Governance

Permitted AI tasks:

- extract and classify evidence
- detect anomalies and missing fields
- summarize timelines and contradictions
- recommend next actions with sources and uncertainty

AI shall not own Domain records, grant itself authority, suppress contradictions, silently edit approved versions, fabricate external outcomes, or execute high-impact actions outside typed Tools, policy, approval, idempotency, sandbox, and outcome observation.

Every Agent Run records source context, prompt/model/tool versions, structured output, confidence and limitations, Policy result, approval, Tool calls, provider responses, final outcome, and recovery actions.

11. Security, Privacy, and Trust Boundaries

- least privilege and separation of duties
- tenant, organization, facility, channel and jurisdiction isolation
- integrity protection for binding evidence
- verified external callbacks and anti-replay controls

Additional controls include secret isolation, callback signature verification, audit of privileged action, emergency-access review, sensitive-data minimization, purpose limitation, and threat models for impersonation, tampering, replay, confused deputy, fraud, prompt injection, and exfiltration.

12. Reliability, SLOs, and Operations

SLI	Reference objective
authoritative read availability	99.9% monthly unless a stricter tier applies
acknowledged Command durability	no acknowledged write may be silently lost
Event publication	99.9% within five minutes after committed fact
duplicate prevention	100% for same tenant, Command class, and idempotency key
binding Decision audit completeness	100%
state-state detection	bounded by business deadline

Dashboards and runbooks cover backlog, error budget, dependency failure, retry budget, DLQ, workflow stall, provider outage, reconciliation, capacity, backup/restore, release/rollback, incident command, and post-incident correction.

13. Testing and Continuous Conformance

- aggregate invariant and transition tests
- authorization, delegation, separation-of-duties and tenant-isolation tests
- idempotency and optimistic-concurrency tests
- database migration, key, constraint and rollback tests
- contract, outbox/inbox, duplicate, replay and DLQ tests
- workflow restart, timeout and compensation tests
- Portal E2E tests for success, partial, stale, denied, error and Outcome Unknown states
- accessibility, locale, currency, unit and RTL/LTR tests
- security adversarial, fraud and data-exfiltration tests
- AI evaluation, prompt-injection, policy-bypass and unauthorized-tool tests
- historical reconstruction, correction and audit-completeness tests
- performance, capacity, recovery and operational exercise tests

Release evidence links each invariant and control to the test, environment, input data, result, owner, and artifact proving it. Generated test counts never replace semantic coverage.

14. Repository Review Boundary

- This chapter is a repository-review specification. Exact executable implementation has not been inspected for every target behavior.
- Registered modules, catalog entries, README claims, frontend contracts, or plans are not proof of complete implementation.

Area	Classification
target aggregate, API, tables, state and workflow in this chapter	REFERENCE_ARCHITECTURE
registered module or catalog claim	DOCUMENTATION_ONLY_CLAIM until source inspection
uninspected integration	REQUIRES_REPOSITORY_REVIEW
behavior proven in another repository-grounded chapter	retain that chapter's evidence and classification
contradictory ownership or path claims	CONFLICT_REQUIRES_CANONICALIZATION

No statement upgrades implementation status merely because a file, directory, module name, frontend contract, database entry, plan, or report exists.

15. Worked Conformance Scenario

An authorized principal initiates a Command against an exact subject version. The service validates identity, tenant, mandate, Policy, Evidence, and idempotency. It records the state transition and outbox entry atomically. If an external dependency participates, timeout produces Outcome Unknown; reconciliation queries the source or waits for a verified callback instead of repeating the action blindly.

Portals show source, freshness, version, required action, and uncertainty. AI may extract, compare, summarize, detect anomalies, and recommend through typed Tools, but cannot own the subject or fabricate success. Later correction appends new facts, identifies affected projections and workflows, and preserves the historical Decision context.

16. Conformance Checklist

- ☐ stable identity and proposition ownership are explicit;
- ☐ authority and mandate are evaluated at action time;
- ☐ state, Recommendation, Decision, Intent, execution, and outcome remain distinct;
- ☐ Commands are typed, authorized, idempotent, and version guarded;
- ☐ Events describe completed facts;
- ☐ Evidence includes provenance, time, integrity, qualification, and correction;
- ☐ external outcomes retain their authority source;
- ☐ Portals show freshness and uncertainty;
- ☐ AI is bounded by typed Tools, Policy, approval, and outcome observation;
- ☐ security, tenant, facility, channel, and jurisdiction boundaries are enforced;
- ☐ Outcome Unknown and reconciliation exist where needed;
- ☐ corrections preserve history;
- ☐ tests prove invariants and recovery;
- ☐ implementation status is not upgraded without executable evidence.

17. Status Vocabulary

Status	Meaning
VERIFIED_IMPLEMENTED	Executable source and relevant behavior were inspected.
IMPLEMENTED_WITH_GAP	Executable behavior exists with a material governance or completeness gap.
PARTIAL_IMPLEMENTATION	Only part of the target capability is evidenced.
REFERENCE_ARCHITECTURE	Normative target behavior; no claim that it exists today.
PLANNED_NOT_IMPLEMENTED	Explicitly planned but not evidenced as executable.
DOCUMENTATION_ONLY_CLAIM	Documentation or client contract claims behavior without verified backend evidence.
CONFLICT_REQUIRES_CANONICALIZATION	Sources disagree and no final owner has been established.
REQUIRES_REPOSITORY_REVIEW	Necessary executable evidence has not yet been inspected.

Web Operator — Routes, Pages, Components, and BFF Contracts

Metadata	Value
Volume	4
Chapter ID	V04-P03-01
Subject	WebOperatorRouteRegistry
Status	Generated First-Draft Architecture Skeleton - Domain-Specific Expansion Required
Content maturity	TEMPLATE_DERIVED_REFERENCE_SKELETON unless repository citations prove otherwise
Default implementation classification	REFERENCE_ARCHITECTURE / REQUIRES_REPOSITORY_REVIEW
Accountable owner	Portal Architecture / Web Operator
Evidence rule	No implementation claim without inspected executable evidence
Repository	chinair88-prog/allinb2c

1. Executive Orientation

This chapter defines how GTOS shall **inventory routes, layouts, pages, components, server/client boundaries, BFFs, APIs, realtime channels and ownership for platform operators and support staff, covering exception management, reconciliation, workflow, service health, audit, correction.**

The specification separates reality, observations, knowledge, Decisions, Intent, execution, and outcomes. A component name, database row, UI label, AI answer, or workflow state does not acquire authority merely because it is visible or technically convenient.

Reality or external outcome

- ≠ Observation
- ≠ Claim
- ≠ derived Perspective
- ≠ Prediction
- ≠ Recommendation
- ≠ authorized Decision
- ≠ execution Intent

1.1 Accountable ownership

The accountable owner is **Portal Architecture / Web Operator**. Supporting applications, shared infrastructure, integration adapters, analytics, and AI coordinate or present the capability but shall not silently own its authoritative propositions.

1.2 Scope

- create and identify the subject
- validate evidence and policy
- make authorized Decisions
- execute typed Commands
- publish completed-fact Events
- query current and historical perspectives
- correct and reconcile outcomes

1.3 Non-goals

- treating a registered Gradle module, catalog record, README, frontend route, migration plan, or generated report as proof of end-to-end implementation;
- direct cross-Domain database writes;
- generic status values that combine lifecycle, approval, provider, document, payment, dispute, and correction state;
- silent replacement of history;
- AI-created authority or fabricated external outcomes.

2. Ubiquitous Language and Subject Model

Subject	Required interpretation
WebOperatorRouteRegistry	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit
WebOperatorRouteRegistryVersion	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit
WebOperatorRouteRegistryDecision	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit
WebOperatorRouteRegistryEvidenceSet	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit
WebOperatorRouteRegistryException	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit

Reference aggregate:

```
WebOperatorRouteRegistry {
  subjectId
  tenantId
  organizationContext
  sourceIdentityRefs[]
  sourceVersionRefs[]
  lifecycleState
  relationshipRefs[]
  decisionRefs[]
  intentRefs[]
  evidenceSetRef
  knowledgeCutoff
  policyRefs[]
  authorityRef
  jurisdictionRefs[]
  createdAt
  effectiveAt
  updatedAt
  version
  correctionOf?
  correlationId
}
```

2.1 Core invariants

- Stable identity precedes relationship, state, and cross-system correlation.
- Effective time and recorded time remain distinct where business truth changes over time.
- Recommendation, Decision, Intent, execution, and outcome are separate concepts.
- No Portal, report, search index, cache, workflow, or AI Agent becomes a shadow owner of Domain truth.
- Binding submitted, approved, issued, accepted, or signed versions are immutable.
- Corrections append governed facts and preserve the original record.
- External authority and provider outcomes retain their source and qualification.
- Tenant and represented-principal context come from trusted authentication and mandate evaluation.
- Retried writes are idempotent and concurrency guarded.
- Outcome Unknown is explicit and reconciled before risky duplicate execution.

2.2 Required standards

- stable identifiers
- typed contracts
- immutable binding versions

- transactional outbox
- idempotent Commands
- explicit Outcome Unknown
- correction lineage
- machine-verifiable conformance

3. Actors, Roles, and Authority

A conformant design distinguishes:

- the natural person acting;
- the service or AI identity invoking a Tool;
- the organization or principal represented;
- the role or relationship granting context;
- the mandate or delegation granting action authority;
- the Policy and jurisdiction limiting the action;
- the reviewer or approver responsible for a binding Decision.

Authority is evaluated at action time. Authentication alone does not grant business authority. Cached permissions and browser-supplied tenant headers are insufficient for high-impact actions.

4. Lifecycle and State Model

State	Semantics
PROPOSED	Distinct governed condition with entry, exit, timeout, correction and authority semantics
VALIDATION_PENDING	Distinct governed condition with entry, exit, timeout, correction and authority semantics
APPROVAL_PENDING	Distinct governed condition with entry, exit, timeout, correction and authority semantics
ACTIVE	Distinct governed condition with entry, exit, timeout, correction and authority semantics
SUSPENDED	Distinct governed condition with entry, exit, timeout, correction and authority semantics
CORRECTION_PENDING	Distinct governed condition with entry, exit, timeout, correction and authority semantics
RETIRED	Distinct governed condition with entry, exit, timeout, correction and authority semantics

```
stateDiagram-v2
    [*] --> PROPOSED
    PROPOSED --> VALIDATION_PENDING
    VALIDATION_PENDING --> APPROVAL_PENDING
    APPROVAL_PENDING --> ACTIVE
    ACTIVE --> SUSPENDED
    SUSPENDED --> CORRECTION_PENDING
    CORRECTION_PENDING --> RETIRED
```

The diagram is a primary reading path. Real implementations may add parallel review, amendment, appeal, timeout, suspension, partial completion, reconciliation, correction, and terminal failure without collapsing their meaning.

4.1 Transition rules

- transition through a typed, authorized Command;
- require exact expected version where concurrent change matters;
- record actor, represented principal, mandate, Policy, reason, and Evidence;
- use an idempotency key for retried writes;
- publish a completed-fact Event after durable state change;
- expose Outcome Unknown for unresolved external completion;
- preserve original and corrected states in historical reconstruction.

5. Decision, Evidence, and Knowledge Cutoff

Reference Decision:

```
Decision {
  decisionId
  decisionType
  subjectRef
  sourceVersionRefs[]
  knowledgeCutoff
  evidenceSetRef
  policyVersionRefs[]
  recommendationRefs[]
  principalId
  representedOrganizationId
  mandateRef
  rationale
  outcome
  decidedAt
  effectiveAt
  correctionOf?
}
```

Evidence records identify issuer or observer, subject, version, observed time, received time, effective interval, integrity, confidence, qualification, contradiction, correction, retention, residency, and access class. A recommendation may assist the Decision but cannot promote itself to the Decision.

6. Commands, Events, Queries, and Contracts

Reference Commands:

- CreateWebOperatorRouteRegistry
- ValidateWebOperatorRouteRegistry
- ApproveWebOperatorRouteRegistry
- ActivateWebOperatorRouteRegistry
- SuspendWebOperatorRouteRegistry
- CorrectWebOperatorRouteRegistry
- RetireWebOperatorRouteRegistry

Reference Events:

- WebOperatorRouteRegistryCreated
- WebOperatorRouteRegistryValidated
- WebOperatorRouteRegistryApproved
- WebOperatorRouteRegistryActivated
- WebOperatorRouteRegistrySuspended
- WebOperatorRouteRegistryCorrected
- WebOperatorRouteRegistryRetired

Reference queries:

- GetWebOperatorRouteRegistry
- ListWebOperatorRouteRegistryRecords
- GetWebOperatorRouteRegistryTimeline
- GetWebOperatorRouteRegistryEvidence
- GetWebOperatorRouteRegistryDecisionPackage
- GetWebOperatorRouteRegistryExceptions
- GetWebOperatorRouteRegistryAuditTrail

Reference API surface:

```
POST /api/v1/weboperatorrouterregistry/commands
GET  /api/v1/weboperatorrouterregistry/{id}
GET  /api/v1/weboperatorrouterregistry/{id}/timeline
GET  /api/v1/weboperatorrouterregistry/{id}/evidence
GET  /api/v1/weboperatorrouterregistry/{id}/decisions
POST /api/v1/weboperatorrouterregistry/{id}/exceptions
POST /api/v1/weboperatorrouterregistry/{id}/corrections
```

These endpoints are reference contracts, not claims that exact routes exist.

7. Workflow, Failure, and Compensation

flowchart TD

```
A[Validate identity version and authority] --> B[Collect required evidence]
B --> C{Policy and evidence gates pass?}
C -- No --> D[Open exception or request correction]
D --> B
C -- Yes --> E[Record Decision or execution Intent]
E --> F[Execute Domain command or external request]
F --> G{Outcome known?}
G -- Success --> H[Record fact and publish Event]
G -- Failure --> I[Record failure and compensation options]
G -- Unknown --> J[Enter Outcome Unknown]
J --> K[Query source or wait for verified callback]
K --> G
H --> L[Update projections and downstream workflow]
```

Representative failure modes:

- stale or wrong source version
- duplicate submission or replay
- external timeout after possible success
- contradictory source observations
- lost Event after committed state
- approval or mandate revoked during execution
- downstream action before a mandatory gate
- partial completion across multiple subjects
- evidence later retracted or corrected
- tenant, facility, channel or jurisdiction mismatch

Recovery shall query the authoritative source before duplicate execution, preserve partial success, use compensating Intent rather than destructive rewrite, publish corrections, quarantine high-impact ambiguity, and record affected downstream subjects.

8. Data and Persistence Architecture

Reference table families:

Table family	Purpose
weboperatorrouterregistry_aggregate	authoritative subject
weboperatorrouterregistry_version	immutable submitted, approved, issued, or signed versions
weboperatorrouterregistry_relationship	governed relationships
weboperatorrouterregistry_decision	binding Decisions and rationale
weboperatorrouterregistry_evidence_link	provenance and evidence relationships
weboperatorrouterregistry_event_outbox	transactional Event publication
weboperatorrouterregistry_idempotency	duplicate-write protection
weboperatorrouterregistry_exception	exception, claim, dispute, or hold
weboperatorrouterregistry_correction	correction and supersession lineage
weboperatorrouterregistry_audit	privileged action evidence

The owning service controls schema and migration. Cross-Domain references use stable identifiers or contracts. Analytics, reports, caches, search, and vector indexes remain projections. Backup, restore, retention, legal hold, privacy, residency, and decommissioning requirements are explicit.

9. Portal and Experience Requirements

- Web Operator: primary experience for platform operators and support staff.
- Operator and support views: diagnose failed or ambiguous journeys without assuming Domain ownership.
- Domain services: own authoritative data and action eligibility; the Portal consumes typed contracts.

Every Portal displays exact version, owner, state, freshness, required action, and uncertainty. It supports loading, empty, partial, stale, denied, error, timeout, and Outcome Unknown states; accessibility; locale, currency, unit, date, and RTL/LTR correctness; evidence audit; safe retry; and correction history.

10. AI Participation and Tool Governance

Permitted AI tasks:

- extract and classify evidence
- detect anomalies and missing fields
- summarize timelines and contradictions
- recommend next actions with sources and uncertainty

AI shall not own Domain records, grant itself authority, suppress contradictions, silently edit approved versions, fabricate external outcomes, or execute high-impact actions outside typed Tools, policy, approval, idempotency, sandbox, and outcome observation.

Every Agent Run records source context, prompt/model/tool versions, structured output, confidence and limitations, Policy result, approval, Tool calls, provider responses, final outcome, and recovery actions.

11. Security, Privacy, and Trust Boundaries

- least privilege and separation of duties
- tenant, organization, facility, channel and jurisdiction isolation
- integrity protection for binding evidence
- verified external callbacks and anti-replay controls

Additional controls include secret isolation, callback signature verification, audit of privileged action, emergency-access review, sensitive-data minimization, purpose limitation, and threat models for impersonation, tampering, replay, confused deputy, fraud, prompt injection, and exfiltration.

12. Reliability, SLOs, and Operations

SLI	Reference objective
authoritative read availability	99.9% monthly unless a stricter tier applies
acknowledged Command durability	no acknowledged write may be silently lost
Event publication	99.9% within five minutes after committed fact
duplicate prevention	100% for same tenant, Command class, and idempotency key
binding Decision audit completeness	100%
state-state detection	bounded by business deadline

Dashboards and runbooks cover backlog, error budget, dependency failure, retry budget, DLQ, workflow stall, provider outage, reconciliation, capacity, backup/restore, release/rollback, incident command, and post-incident correction.

13. Testing and Continuous Conformance

- aggregate invariant and transition tests
- authorization, delegation, separation-of-duties and tenant-isolation tests
- idempotency and optimistic-concurrency tests
- database migration, key, constraint and rollback tests
- contract, outbox/inbox, duplicate, replay and DLQ tests
- workflow restart, timeout and compensation tests
- Portal E2E tests for success, partial, stale, denied, error and Outcome Unknown states
- accessibility, locale, currency, unit and RTL/LTR tests
- security adversarial, fraud and data-exfiltration tests
- AI evaluation, prompt-injection, policy-bypass and unauthorized-tool tests
- historical reconstruction, correction and audit-completeness tests
- performance, capacity, recovery and operational exercise tests

Release evidence links each invariant and control to the test, environment, input data, result, owner, and artifact proving it. Generated test counts never replace semantic coverage.

14. Repository Review Boundary

- This chapter is a repository-review specification. Exact executable implementation has not been inspected for every target behavior.
- Registered modules, catalog entries, README claims, frontend contracts, or plans are not proof of complete implementation.

Area	Classification
target aggregate, API, tables, state and workflow in this chapter	REFERENCE_ARCHITECTURE
registered module or catalog claim	DOCUMENTATION_ONLY_CLAIM until source inspection
uninspected integration	REQUIRES_REPOSITORY_REVIEW
behavior proven in another repository-grounded chapter	retain that chapter's evidence and classification
contradictory ownership or path claims	CONFLICT_REQUIRES_CANONICALIZATION

No statement upgrades implementation status merely because a file, directory, module name, frontend contract, database entry, plan, or report exists.

15. Worked Conformance Scenario

An authorized principal initiates a Command against an exact subject version. The service validates identity, tenant, mandate, Policy, Evidence, and idempotency. It records the state transition and outbox entry atomically. If an external dependency participates, timeout produces Outcome Unknown; reconciliation queries the source or waits for a verified callback instead of repeating the action blindly.

Portals show source, freshness, version, required action, and uncertainty. AI may extract, compare, summarize, detect anomalies, and recommend through typed Tools, but cannot own the subject or fabricate success. Later correction appends new facts, identifies affected projections and workflows, and preserves the historical Decision context.

16. Conformance Checklist

- ☐ stable identity and proposition ownership are explicit;
- ☐ authority and mandate are evaluated at action time;
- ☐ state, Recommendation, Decision, Intent, execution, and outcome remain distinct;
- ☐ Commands are typed, authorized, idempotent, and version guarded;
- ☐ Events describe completed facts;
- ☐ Evidence includes provenance, time, integrity, qualification, and correction;
- ☐ external outcomes retain their authority source;
- ☐ Portals show freshness and uncertainty;
- ☐ AI is bounded by typed Tools, Policy, approval, and outcome observation;
- ☐ security, tenant, facility, channel, and jurisdiction boundaries are enforced;
- ☐ Outcome Unknown and reconciliation exist where needed;
- ☐ corrections preserve history;
- ☐ tests prove invariants and recovery;
- ☐ implementation status is not upgraded without executable evidence.

17. Status Vocabulary

Status	Meaning
VERIFIED_IMPLEMENTED	Executable source and relevant behavior were inspected.
IMPLEMENTED_WITH_GAP	Executable behavior exists with a material governance or completeness gap.
PARTIAL_IMPLEMENTATION	Only part of the target capability is evidenced.
REFERENCE_ARCHITECTURE	Normative target behavior; no claim that it exists today.
PLANNED_NOT_IMPLEMENTED	Explicitly planned but not evidenced as executable.
DOCUMENTATION_ONLY_CLAIM	Documentation or client contract claims behavior without verified backend evidence.
CONFLICT_REQUIRES_CANONICALIZATION	Sources disagree and no final owner has been established.
REQUIRES_REPOSITORY_REVIEW	Necessary executable evidence has not yet been inspected.

Web Operator — Identity, Session, Authorization, and Trust Boundaries

Metadata	Value
Volume	4
Chapter ID	V04-P03-02
Subject	WebOperatorAccessModel
Status	Generated First-Draft Architecture Skeleton - Domain-Specific Expansion Required
Content maturity	TEMPLATE_DERIVED_REFERENCE_SKELETON unless repository citations prove otherwise
Default implementation classification	REFERENCE_ARCHITECTURE / REQUIRES_REPOSITORY_REVIEW
Accountable owner	Portal Architecture / Web Operator
Evidence rule	No implementation claim without inspected executable evidence
Repository	chinair88-prog/allinb2c

1. Executive Orientation

This chapter defines how GTOS shall **govern login, session, role, relationship, tenant, facility, channel, delegation, impersonation and privileged action for platform operators and support staff, covering exception management, reconciliation, workflow, service health, audit, correction.**

The specification separates reality, observations, knowledge, Decisions, Intent, execution, and outcomes. A component name, database row, UI label, AI answer, or workflow state does not acquire authority merely because it is visible or technically convenient.

Reality or external outcome
≠ Observation
≠ Claim
≠ derived Perspective
≠ Prediction
≠ Recommendation
≠ authorized Decision
≠ execution Intent

1.1 Accountable ownership

The accountable owner is **Portal Architecture / Web Operator**. Supporting applications, shared infrastructure, integration adapters, analytics, and AI coordinate or present the capability but shall not silently own its authoritative propositions.

1.2 Scope

- create and identify the subject
- validate evidence and policy
- make authorized Decisions
- execute typed Commands
- publish completed-fact Events
- query current and historical perspectives
- correct and reconcile outcomes

1.3 Non-goals

- treating a registered Gradle module, catalog record, README, frontend route, migration plan, or generated report as proof of end-to-end implementation;
- direct cross-Domain database writes;
- generic status values that combine lifecycle, approval, provider, document, payment, dispute, and correction state;
- silent replacement of history;
- AI-created authority or fabricated external outcomes.

2. Ubiquitous Language and Subject Model

Subject	Required interpretation
WebOperatorAccessModel	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit
WebOperatorAccessModelVersion	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit
WebOperatorAccessModelDecision	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit
WebOperatorAccessModelEvidenceSet	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit
WebOperatorAccessModelException	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit

Reference aggregate:

```
WebOperatorAccessModel {  
  subjectId  
  tenantId  
  organizationContext  
  sourceIdentityRefs[]  
  sourceVersionRefs[]  
  lifecycleState  
  relationshipRefs[]  
  decisionRefs[]  
  intentRefs[]  
  evidenceSetRef  
  knowledgeCutoff  
  policyRefs[]  
  authorityRef  
  jurisdictionRefs[]  
  createdAt  
  effectiveAt  
  updatedAt  
  version  
  correctionOf?  
  correlationId  
}
```

2.1 Core invariants

- Stable identity precedes relationship, state, and cross-system correlation.
- Effective time and recorded time remain distinct where business truth changes over time.
- Recommendation, Decision, Intent, execution, and outcome are separate concepts.
- No Portal, report, search index, cache, workflow, or AI Agent becomes a shadow owner of Domain truth.
- Binding submitted, approved, issued, accepted, or signed versions are immutable.
- Corrections append governed facts and preserve the original record.
- External authority and provider outcomes retain their source and qualification.
- Tenant and represented-principal context come from trusted authentication and mandate evaluation.
- Retried writes are idempotent and concurrency guarded.
- Outcome Unknown is explicit and reconciled before risky duplicate execution.

2.2 Required standards

- stable identifiers
- typed contracts
- immutable binding versions

- transactional outbox
- idempotent Commands
- explicit Outcome Unknown
- correction lineage
- machine-verifiable conformance

3. Actors, Roles, and Authority

A conformant design distinguishes:

- the natural person acting;
- the service or AI identity invoking a Tool;
- the organization or principal represented;
- the role or relationship granting context;
- the mandate or delegation granting action authority;
- the Policy and jurisdiction limiting the action;
- the reviewer or approver responsible for a binding Decision.

Authority is evaluated at action time. Authentication alone does not grant business authority. Cached permissions and browser-supplied tenant headers are insufficient for high-impact actions.

4. Lifecycle and State Model

State	Semantics
PROPOSED	Distinct governed condition with entry, exit, timeout, correction and authority semantics
VALIDATION_PENDING	Distinct governed condition with entry, exit, timeout, correction and authority semantics
APPROVAL_PENDING	Distinct governed condition with entry, exit, timeout, correction and authority semantics
ACTIVE	Distinct governed condition with entry, exit, timeout, correction and authority semantics
SUSPENDED	Distinct governed condition with entry, exit, timeout, correction and authority semantics
CORRECTION_PENDING	Distinct governed condition with entry, exit, timeout, correction and authority semantics
RETIRED	Distinct governed condition with entry, exit, timeout, correction and authority semantics

```
stateDiagram-v2
    [*] --> PROPOSED
    PROPOSED --> VALIDATION_PENDING
    VALIDATION_PENDING --> APPROVAL_PENDING
    APPROVAL_PENDING --> ACTIVE
    ACTIVE --> SUSPENDED
    SUSPENDED --> CORRECTION_PENDING
    CORRECTION_PENDING --> RETIRED
```

The diagram is a primary reading path. Real implementations may add parallel review, amendment, appeal, timeout, suspension, partial completion, reconciliation, correction, and terminal failure without collapsing their meaning.

4.1 Transition rules

- transition through a typed, authorized Command;
- require exact expected version where concurrent change matters;
- record actor, represented principal, mandate, Policy, reason, and Evidence;
- use an idempotency key for retried writes;
- publish a completed-fact Event after durable state change;
- expose Outcome Unknown for unresolved external completion;
- preserve original and corrected states in historical reconstruction.

5. Decision, Evidence, and Knowledge Cutoff

Reference Decision:

```
Decision {
  decisionId
  decisionType
  subjectRef
  sourceVersionRefs[]
  knowledgeCutoff
  evidenceSetRef
  policyVersionRefs[]
  recommendationRefs[]
  principalId
  representedOrganizationId
  mandateRef
  rationale
  outcome
  decidedAt
  effectiveAt
  correctionOf?
}
```

Evidence records identify issuer or observer, subject, version, observed time, received time, effective interval, integrity, confidence, qualification, contradiction, correction, retention, residency, and access class. A recommendation may assist the Decision but cannot promote itself to the Decision.

6. Commands, Events, Queries, and Contracts

Reference Commands:

- CreateWebOperatorAccessModel
- ValidateWebOperatorAccessModel
- ApproveWebOperatorAccessModel
- ActivateWebOperatorAccessModel
- SuspendWebOperatorAccessModel
- CorrectWebOperatorAccessModel
- RetireWebOperatorAccessModel

Reference Events:

- WebOperatorAccessModelCreated
- WebOperatorAccessModelValidated
- WebOperatorAccessModelApproved
- WebOperatorAccessModelActivated
- WebOperatorAccessModelSuspended
- WebOperatorAccessModelCorrected
- WebOperatorAccessModelRetired

Reference queries:

- GetWebOperatorAccessModel
- ListWebOperatorAccessModelRecords
- GetWebOperatorAccessModelTimeline
- GetWebOperatorAccessModelEvidence
- GetWebOperatorAccessModelDecisionPackage
- GetWebOperatorAccessModelExceptions
- GetWebOperatorAccessModelAuditTrail

Reference API surface:

```
POST /api/v1/weboperatoraccessmodel/commands
GET  /api/v1/weboperatoraccessmodel/{id}
GET  /api/v1/weboperatoraccessmodel/{id}/timeline
GET  /api/v1/weboperatoraccessmodel/{id}/evidence
GET  /api/v1/weboperatoraccessmodel/{id}/decisions
POST /api/v1/weboperatoraccessmodel/{id}/exceptions
POST /api/v1/weboperatoraccessmodel/{id}/corrections
```

These endpoints are reference contracts, not claims that exact routes exist.

7. Workflow, Failure, and Compensation

flowchart TD

```
A[Validate identity version and authority] --> B[Collect required evidence]
B --> C{Policy and evidence gates pass?}
C -- No --> D[Open exception or request correction]
D --> B
C -- Yes --> E[Record Decision or execution Intent]
E --> F[Execute Domain command or external request]
F --> G{Outcome known?}
G -- Success --> H[Record fact and publish Event]
G -- Failure --> I[Record failure and compensation options]
G -- Unknown --> J[Enter Outcome Unknown]
J --> K[Query source or wait for verified callback]
K --> G
H --> L[Update projections and downstream workflow]
```

Representative failure modes:

- stale or wrong source version
- duplicate submission or replay
- external timeout after possible success
- contradictory source observations
- lost Event after committed state
- approval or mandate revoked during execution
- downstream action before a mandatory gate
- partial completion across multiple subjects
- evidence later retracted or corrected
- tenant, facility, channel or jurisdiction mismatch

Recovery shall query the authoritative source before duplicate execution, preserve partial success, use compensating Intent rather than destructive rewrite, publish corrections, quarantine high-impact ambiguity, and record affected downstream subjects.

8. Data and Persistence Architecture

Reference table families:

Table family	Purpose
weboperatoraccessmodel_aggregate	authoritative subject
weboperatoraccessmodel_version	immutable submitted, approved, issued, or signed versions
weboperatoraccessmodel_relationship	governed relationships
weboperatoraccessmodel_decision	binding Decisions and rationale
weboperatoraccessmodel_evidence_link	provenance and evidence relationships
weboperatoraccessmodel_event_outbox	transactional Event publication
weboperatoraccessmodel_idempotency	duplicate-write protection
weboperatoraccessmodel_exception	exception, claim, dispute, or hold
weboperatoraccessmodel_correction	correction and supersession lineage
weboperatoraccessmodel_audit	privileged action evidence

The owning service controls schema and migration. Cross-Domain references use stable identifiers or contracts. Analytics, reports, caches, search, and vector indexes remain projections. Backup, restore, retention, legal hold, privacy, residency, and decommissioning requirements are explicit.

9. Portal and Experience Requirements

- Web Operator: primary experience for platform operators and support staff.
- Operator and support views: diagnose failed or ambiguous journeys without assuming Domain ownership.
- Domain services: own authoritative data and action eligibility; the Portal consumes typed contracts.

Every Portal displays exact version, owner, state, freshness, required action, and uncertainty. It supports loading, empty, partial, stale, denied, error, timeout, and Outcome Unknown states; accessibility; locale, currency, unit, date, and RTL/LTR correctness; evidence audit; safe retry; and correction history.

10. AI Participation and Tool Governance

Permitted AI tasks:

- extract and classify evidence
- detect anomalies and missing fields
- summarize timelines and contradictions
- recommend next actions with sources and uncertainty

AI shall not own Domain records, grant itself authority, suppress contradictions, silently edit approved versions, fabricate external outcomes, or execute high-impact actions outside typed Tools, policy, approval, idempotency, sandbox, and outcome observation.

Every Agent Run records source context, prompt/model/tool versions, structured output, confidence and limitations, Policy result, approval, Tool calls, provider responses, final outcome, and recovery actions.

11. Security, Privacy, and Trust Boundaries

- least privilege and separation of duties
- tenant, organization, facility, channel and jurisdiction isolation
- integrity protection for binding evidence
- verified external callbacks and anti-replay controls

Additional controls include secret isolation, callback signature verification, audit of privileged action, emergency-access review, sensitive-data minimization, purpose limitation, and threat models for impersonation, tampering, replay, confused deputy, fraud, prompt injection, and exfiltration.

12. Reliability, SLOs, and Operations

SLI	Reference objective
authoritative read availability	99.9% monthly unless a stricter tier applies
acknowledged Command durability	no acknowledged write may be silently lost
Event publication	99.9% within five minutes after committed fact
duplicate prevention	100% for same tenant, Command class, and idempotency key
binding Decision audit completeness	100%
state-state detection	bounded by business deadline

Dashboards and runbooks cover backlog, error budget, dependency failure, retry budget, DLQ, workflow stall, provider outage, reconciliation, capacity, backup/restore, release/rollback, incident command, and post-incident correction.

13. Testing and Continuous Conformance

- aggregate invariant and transition tests
- authorization, delegation, separation-of-duties and tenant-isolation tests
- idempotency and optimistic-concurrency tests
- database migration, key, constraint and rollback tests
- contract, outbox/inbox, duplicate, replay and DLQ tests
- workflow restart, timeout and compensation tests
- Portal E2E tests for success, partial, stale, denied, error and Outcome Unknown states
- accessibility, locale, currency, unit and RTL/LTR tests
- security adversarial, fraud and data-exfiltration tests
- AI evaluation, prompt-injection, policy-bypass and unauthorized-tool tests
- historical reconstruction, correction and audit-completeness tests
- performance, capacity, recovery and operational exercise tests

Release evidence links each invariant and control to the test, environment, input data, result, owner, and artifact proving it. Generated test counts never replace semantic coverage.

14. Repository Review Boundary

- This chapter is a repository-review specification. Exact executable implementation has not been inspected for every target behavior.
- Registered modules, catalog entries, README claims, frontend contracts, or plans are not proof of complete implementation.

Area	Classification
target aggregate, API, tables, state and workflow in this chapter	REFERENCE_ARCHITECTURE
registered module or catalog claim	DOCUMENTATION_ONLY_CLAIM until source inspection
uninspected integration	REQUIRES_REPOSITORY_REVIEW
behavior proven in another repository-grounded chapter	retain that chapter's evidence and classification
contradictory ownership or path claims	CONFLICT_REQUIRES_CANONICALIZATION

No statement upgrades implementation status merely because a file, directory, module name, frontend contract, database entry, plan, or report exists.

15. Worked Conformance Scenario

An authorized principal initiates a Command against an exact subject version. The service validates identity, tenant, mandate, Policy, Evidence, and idempotency. It records the state transition and outbox entry atomically. If an external dependency participates, timeout produces Outcome Unknown; reconciliation queries the source or waits for a verified callback instead of repeating the action blindly.

Portals show source, freshness, version, required action, and uncertainty. AI may extract, compare, summarize, detect anomalies, and recommend through typed Tools, but cannot own the subject or fabricate success. Later correction appends new facts, identifies affected projections and workflows, and preserves the historical Decision context.

16. Conformance Checklist

- ☐ stable identity and proposition ownership are explicit;
- ☐ authority and mandate are evaluated at action time;
- ☐ state, Recommendation, Decision, Intent, execution, and outcome remain distinct;
- ☐ Commands are typed, authorized, idempotent, and version guarded;
- ☐ Events describe completed facts;
- ☐ Evidence includes provenance, time, integrity, qualification, and correction;
- ☐ external outcomes retain their authority source;
- ☐ Portals show freshness and uncertainty;
- ☐ AI is bounded by typed Tools, Policy, approval, and outcome observation;
- ☐ security, tenant, facility, channel, and jurisdiction boundaries are enforced;
- ☐ Outcome Unknown and reconciliation exist where needed;
- ☐ corrections preserve history;
- ☐ tests prove invariants and recovery;
- ☐ implementation status is not upgraded without executable evidence.

17. Status Vocabulary

Status	Meaning
VERIFIED_IMPLEMENTED	Executable source and relevant behavior were inspected.
IMPLEMENTED_WITH_GAP	Executable behavior exists with a material governance or completeness gap.
PARTIAL_IMPLEMENTATION	Only part of the target capability is evidenced.
REFERENCE_ARCHITECTURE	Normative target behavior; no claim that it exists today.
PLANNED_NOT_IMPLEMENTED	Explicitly planned but not evidenced as executable.
DOCUMENTATION_ONLY_CLAIM	Documentation or client contract claims behavior without verified backend evidence.
CONFLICT_REQUIRES_CANONICALIZATION	Sources disagree and no final owner has been established.
REQUIRES_REPOSITORY_REVIEW	Necessary executable evidence has not yet been inspected.

Web Operator — UX States, Accessibility, Localization, Analytics, and E2E

Metadata	Value
Volume	4
Chapter ID	V04-P03-03
Subject	WebOperatorExperienceStandard
Status	Generated First-Draft Architecture Skeleton - Domain-Specific Expansion Required
Content maturity	TEMPLATE_DERIVED_REFERENCE_SKELETON unless repository citations prove otherwise
Default implementation classification	REFERENCE_ARCHITECTURE / REQUIRES_REPOSITORY_REVIEW
Accountable owner	Portal Architecture / Web Operator
Evidence rule	No implementation claim without inspected executable evidence
Repository	chinair88-prog/allinb2c

1. Executive Orientation

This chapter defines how GTOS shall **specify loading, empty, partial, stale, error, denied, offline, accessibility, RTL/LTR, analytics, audit and test journeys for platform operators and support staff, covering exception management, reconciliation, workflow, service health, audit, correction.**

The specification separates reality, observations, knowledge, Decisions, Intent, execution, and outcomes. A component name, database row, UI label, AI answer, or workflow state does not acquire authority merely because it is visible or technically convenient.

Reality or external outcome

- ≠ Observation
- ≠ Claim
- ≠ derived Perspective
- ≠ Prediction
- ≠ Recommendation
- ≠ authorized Decision
- ≠ execution Intent

1.1 Accountable ownership

The accountable owner is **Portal Architecture / Web Operator**. Supporting applications, shared infrastructure, integration adapters, analytics, and AI coordinate or present the capability but shall not silently own its authoritative propositions.

1.2 Scope

- create and identify the subject
- validate evidence and policy
- make authorized Decisions
- execute typed Commands
- publish completed-fact Events
- query current and historical perspectives
- correct and reconcile outcomes

1.3 Non-goals

- treating a registered Gradle module, catalog record, README, frontend route, migration plan, or generated report as proof of end-to-end implementation;
- direct cross-Domain database writes;
- generic status values that combine lifecycle, approval, provider, document, payment, dispute, and correction state;
- silent replacement of history;
- AI-created authority or fabricated external outcomes.

2. Ubiquitous Language and Subject Model

Subject	Required interpretation
WebOperatorExperienceStandard	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit
WebOperatorExperienceStandardVersion	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit
WebOperatorExperienceStandardDecision	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit
WebOperatorExperienceStandardEvidenceSet	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit
WebOperatorExperienceStandardException	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit

Reference aggregate:

```
WebOperatorExperienceStandard {  
  subjectId  
  tenantId  
  organizationContext  
  sourceIdentityRefs[]  
  sourceVersionRefs[]  
  lifecycleState  
  relationshipRefs[]  
  decisionRefs[]  
  intentRefs[]  
  evidenceSetRef  
  knowledgeCutoff  
  policyRefs[]  
  authorityRef  
  jurisdictionRefs[]  
  createdAt  
  effectiveAt  
  updatedAt  
  version  
  correctionOf?  
  correlationId  
}
```

2.1 Core invariants

- Stable identity precedes relationship, state, and cross-system correlation.
- Effective time and recorded time remain distinct where business truth changes over time.
- Recommendation, Decision, Intent, execution, and outcome are separate concepts.
- No Portal, report, search index, cache, workflow, or AI Agent becomes a shadow owner of Domain truth.
- Binding submitted, approved, issued, accepted, or signed versions are immutable.
- Corrections append governed facts and preserve the original record.
- External authority and provider outcomes retain their source and qualification.
- Tenant and represented-principal context come from trusted authentication and mandate evaluation.
- Retried writes are idempotent and concurrency guarded.
- Outcome Unknown is explicit and reconciled before risky duplicate execution.

2.2 Required standards

- stable identifiers
- typed contracts
- immutable binding versions

- transactional outbox
- idempotent Commands
- explicit Outcome Unknown
- correction lineage
- machine-verifiable conformance

3. Actors, Roles, and Authority

A conformant design distinguishes:

- the natural person acting;
- the service or AI identity invoking a Tool;
- the organization or principal represented;
- the role or relationship granting context;
- the mandate or delegation granting action authority;
- the Policy and jurisdiction limiting the action;
- the reviewer or approver responsible for a binding Decision.

Authority is evaluated at action time. Authentication alone does not grant business authority. Cached permissions and browser-supplied tenant headers are insufficient for high-impact actions.

4. Lifecycle and State Model

State	Semantics
PROPOSED	Distinct governed condition with entry, exit, timeout, correction and authority semantics
VALIDATION_PENDING	Distinct governed condition with entry, exit, timeout, correction and authority semantics
APPROVAL_PENDING	Distinct governed condition with entry, exit, timeout, correction and authority semantics
ACTIVE	Distinct governed condition with entry, exit, timeout, correction and authority semantics
SUSPENDED	Distinct governed condition with entry, exit, timeout, correction and authority semantics
CORRECTION_PENDING	Distinct governed condition with entry, exit, timeout, correction and authority semantics
RETIRED	Distinct governed condition with entry, exit, timeout, correction and authority semantics

```
stateDiagram-v2
    [*] --> PROPOSED
    PROPOSED --> VALIDATION_PENDING
    VALIDATION_PENDING --> APPROVAL_PENDING
    APPROVAL_PENDING --> ACTIVE
    ACTIVE --> SUSPENDED
    SUSPENDED --> CORRECTION_PENDING
    CORRECTION_PENDING --> RETIRED
```

The diagram is a primary reading path. Real implementations may add parallel review, amendment, appeal, timeout, suspension, partial completion, reconciliation, correction, and terminal failure without collapsing their meaning.

4.1 Transition rules

- transition through a typed, authorized Command;
- require exact expected version where concurrent change matters;
- record actor, represented principal, mandate, Policy, reason, and Evidence;
- use an idempotency key for retried writes;
- publish a completed-fact Event after durable state change;
- expose Outcome Unknown for unresolved external completion;
- preserve original and corrected states in historical reconstruction.

5. Decision, Evidence, and Knowledge Cutoff

Reference Decision:

```
Decision {
  decisionId
  decisionType
  subjectRef
  sourceVersionRefs[]
  knowledgeCutoff
  evidenceSetRef
  policyVersionRefs[]
  recommendationRefs[]
  principalId
  representedOrganizationId
  mandateRef
  rationale
  outcome
  decidedAt
  effectiveAt
  correctionOf?
}
```

Evidence records identify issuer or observer, subject, version, observed time, received time, effective interval, integrity, confidence, qualification, contradiction, correction, retention, residency, and access class. A recommendation may assist the Decision but cannot promote itself to the Decision.

6. Commands, Events, Queries, and Contracts

Reference Commands:

- CreateWebOperatorExperienceStandard
- ValidateWebOperatorExperienceStandard
- ApproveWebOperatorExperienceStandard
- ActivateWebOperatorExperienceStandard
- SuspendWebOperatorExperienceStandard
- CorrectWebOperatorExperienceStandard
- RetireWebOperatorExperienceStandard

Reference Events:

- WebOperatorExperienceStandardCreated
- WebOperatorExperienceStandardValidated
- WebOperatorExperienceStandardApproved
- WebOperatorExperienceStandardActivated
- WebOperatorExperienceStandardSuspended
- WebOperatorExperienceStandardCorrected
- WebOperatorExperienceStandardRetired

Reference queries:

- GetWebOperatorExperienceStandard
- ListWebOperatorExperienceStandardRecords
- GetWebOperatorExperienceStandardTimeline
- GetWebOperatorExperienceStandardEvidence
- GetWebOperatorExperienceStandardDecisionPackage
- GetWebOperatorExperienceStandardExceptions
- GetWebOperatorExperienceStandardAuditTrail

Reference API surface:

```
POST /api/v1/weboperatorexperiencstandard/commands
GET  /api/v1/weboperatorexperiencstandard/{id}
GET  /api/v1/weboperatorexperiencstandard/{id}/timeline
GET  /api/v1/weboperatorexperiencstandard/{id}/evidence
GET  /api/v1/weboperatorexperiencstandard/{id}/decisions
POST /api/v1/weboperatorexperiencstandard/{id}/exceptions
POST /api/v1/weboperatorexperiencstandard/{id}/corrections
```

These endpoints are reference contracts, not claims that exact routes exist.

7. Workflow, Failure, and Compensation

flowchart TD

```
A[Validate identity version and authority] --> B[Collect required evidence]
B --> C{Policy and evidence gates pass?}
C -- No --> D[Open exception or request correction]
D --> B
C -- Yes --> E[Record Decision or execution Intent]
E --> F[Execute Domain command or external request]
F --> G{Outcome known?}
G -- Success --> H[Record fact and publish Event]
G -- Failure --> I[Record failure and compensation options]
G -- Unknown --> J[Enter Outcome Unknown]
J --> K[Query source or wait for verified callback]
K --> G
H --> L[Update projections and downstream workflow]
```

Representative failure modes:

- stale or wrong source version
- duplicate submission or replay
- external timeout after possible success
- contradictory source observations
- lost Event after committed state
- approval or mandate revoked during execution
- downstream action before a mandatory gate
- partial completion across multiple subjects
- evidence later retracted or corrected
- tenant, facility, channel or jurisdiction mismatch

Recovery shall query the authoritative source before duplicate execution, preserve partial success, use compensating Intent rather than destructive rewrite, publish corrections, quarantine high-impact ambiguity, and record affected downstream subjects.

8. Data and Persistence Architecture

Reference table families:

Table family	Purpose
weboperatorexperiencestandard_aggregate	authoritative subject
weboperatorexperiencestandard_version	immutable submitted, approved, issued, or signed versions
weboperatorexperiencestandard_relationship	governed relationships
weboperatorexperiencestandard_decision	binding Decisions and rationale
weboperatorexperiencestandard_evidence_link	provenance and evidence relationships
weboperatorexperiencestandard_event_outbox	transactional Event publication
weboperatorexperiencestandard_idempotency	duplicate-write protection
weboperatorexperiencestandard_exception	exception, claim, dispute, or hold
weboperatorexperiencestandard_correction	correction and supersession lineage
weboperatorexperiencestandard_audit	privileged action evidence

The owning service controls schema and migration. Cross-Domain references use stable identifiers or contracts. Analytics, reports, caches, search, and vector indexes remain projections. Backup, restore, retention, legal hold, privacy, residency, and decommissioning requirements are explicit.

9. Portal and Experience Requirements

- Web Operator: primary experience for platform operators and support staff.
- Operator and support views: diagnose failed or ambiguous journeys without assuming Domain ownership.
- Domain services: own authoritative data and action eligibility; the Portal consumes typed contracts.

Every Portal displays exact version, owner, state, freshness, required action, and uncertainty. It supports loading, empty, partial, stale, denied, error, timeout, and Outcome Unknown states; accessibility; locale, currency, unit, date, and RTL/LTR correctness; evidence audit; safe retry; and correction history.

10. AI Participation and Tool Governance

Permitted AI tasks:

- extract and classify evidence
- detect anomalies and missing fields
- summarize timelines and contradictions
- recommend next actions with sources and uncertainty

AI shall not own Domain records, grant itself authority, suppress contradictions, silently edit approved versions, fabricate external outcomes, or execute high-impact actions outside typed Tools, policy, approval, idempotency, sandbox, and outcome observation.

Every Agent Run records source context, prompt/model/tool versions, structured output, confidence and limitations, Policy result, approval, Tool calls, provider responses, final outcome, and recovery actions.

11. Security, Privacy, and Trust Boundaries

- least privilege and separation of duties
- tenant, organization, facility, channel and jurisdiction isolation
- integrity protection for binding evidence
- verified external callbacks and anti-replay controls

Additional controls include secret isolation, callback signature verification, audit of privileged action, emergency-access review, sensitive-data minimization, purpose limitation, and threat models for impersonation, tampering, replay, confused deputy, fraud, prompt injection, and exfiltration.

12. Reliability, SLOs, and Operations

SLI	Reference objective
authoritative read availability	99.9% monthly unless a stricter tier applies
acknowledged Command durability	no acknowledged write may be silently lost
Event publication	99.9% within five minutes after committed fact
duplicate prevention	100% for same tenant, Command class, and idempotency key
binding Decision audit completeness	100%
state-state detection	bounded by business deadline

Dashboards and runbooks cover backlog, error budget, dependency failure, retry budget, DLQ, workflow stall, provider outage, reconciliation, capacity, backup/restore, release/rollback, incident command, and post-incident correction.

13. Testing and Continuous Conformance

- aggregate invariant and transition tests
- authorization, delegation, separation-of-duties and tenant-isolation tests
- idempotency and optimistic-concurrency tests
- database migration, key, constraint and rollback tests
- contract, outbox/inbox, duplicate, replay and DLQ tests
- workflow restart, timeout and compensation tests
- Portal E2E tests for success, partial, stale, denied, error and Outcome Unknown states
- accessibility, locale, currency, unit and RTL/LTR tests
- security adversarial, fraud and data-exfiltration tests
- AI evaluation, prompt-injection, policy-bypass and unauthorized-tool tests
- historical reconstruction, correction and audit-completeness tests
- performance, capacity, recovery and operational exercise tests

Release evidence links each invariant and control to the test, environment, input data, result, owner, and artifact proving it. Generated test counts never replace semantic coverage.

14. Repository Review Boundary

- This chapter is a repository-review specification. Exact executable implementation has not been inspected for every target behavior.
- Registered modules, catalog entries, README claims, frontend contracts, or plans are not proof of complete implementation.

Area	Classification
target aggregate, API, tables, state and workflow in this chapter	REFERENCE_ARCHITECTURE
registered module or catalog claim	DOCUMENTATION_ONLY_CLAIM until source inspection
uninspected integration	REQUIRES_REPOSITORY_REVIEW
behavior proven in another repository-grounded chapter	retain that chapter's evidence and classification
contradictory ownership or path claims	CONFLICT_REQUIRES_CANONICALIZATION

No statement upgrades implementation status merely because a file, directory, module name, frontend contract, database entry, plan, or report exists.

15. Worked Conformance Scenario

An authorized principal initiates a Command against an exact subject version. The service validates identity, tenant, mandate, Policy, Evidence, and idempotency. It records the state transition and outbox entry atomically. If an external dependency participates, timeout produces Outcome Unknown; reconciliation queries the source or waits for a verified callback instead of repeating the action blindly.

Portals show source, freshness, version, required action, and uncertainty. AI may extract, compare, summarize, detect anomalies, and recommend through typed Tools, but cannot own the subject or fabricate success. Later correction appends new facts, identifies affected projections and workflows, and preserves the historical Decision context.

16. Conformance Checklist

- ☐ stable identity and proposition ownership are explicit;
- ☐ authority and mandate are evaluated at action time;
- ☐ state, Recommendation, Decision, Intent, execution, and outcome remain distinct;
- ☐ Commands are typed, authorized, idempotent, and version guarded;
- ☐ Events describe completed facts;
- ☐ Evidence includes provenance, time, integrity, qualification, and correction;
- ☐ external outcomes retain their authority source;
- ☐ Portals show freshness and uncertainty;
- ☐ AI is bounded by typed Tools, Policy, approval, and outcome observation;
- ☐ security, tenant, facility, channel, and jurisdiction boundaries are enforced;
- ☐ Outcome Unknown and reconciliation exist where needed;
- ☐ corrections preserve history;
- ☐ tests prove invariants and recovery;
- ☐ implementation status is not upgraded without executable evidence.

17. Status Vocabulary

Status	Meaning
VERIFIED_IMPLEMENTED	Executable source and relevant behavior were inspected.
IMPLEMENTED_WITH_GAP	Executable behavior exists with a material governance or completeness gap.
PARTIAL_IMPLEMENTATION	Only part of the target capability is evidenced.
REFERENCE_ARCHITECTURE	Normative target behavior; no claim that it exists today.
PLANNED_NOT_IMPLEMENTED	Explicitly planned but not evidenced as executable.
DOCUMENTATION_ONLY_CLAIM	Documentation or client contract claims behavior without verified backend evidence.
CONFLICT_REQUIRES_CANONICALIZATION	Sources disagree and no final owner has been established.
REQUIRES_REPOSITORY_REVIEW	Necessary executable evidence has not yet been inspected.

Warehouse Operator — Portal Orientation and Information Architecture

Metadata	Value
Volume	4
Chapter ID	V04-P04-00
Subject	WarehouseOperatorPortal
Status	Generated First-Draft Architecture Skeleton - Domain-Specific Expansion Required
Content maturity	TEMPLATE_DERIVED_REFERENCE_SKELETON unless repository citations prove otherwise
Default implementation classification	REFERENCE_ARCHITECTURE / REQUIRES_REPOSITORY_REVIEW
Accountable owner	Portal Architecture / Warehouse Operator
Evidence rule	No implementation claim without inspected executable evidence
Repository	chinair88-prog/allinb2c

1. Executive Orientation

This chapter defines how GTOS shall **define personas, navigation, route ownership, domain dependencies and experience boundaries for warehouse staff and supervisors, covering receiving, putaway, inventory, picking, packing, dispatch, counts, discrepancies**.

The specification separates reality, observations, knowledge, Decisions, Intent, execution, and outcomes. A component name, database row, UI label, AI answer, or workflow state does not acquire authority merely because it is visible or technically convenient.

Reality or external outcome

- ≠ Observation
- ≠ Claim
- ≠ derived Perspective
- ≠ Prediction
- ≠ Recommendation
- ≠ authorized Decision
- ≠ execution Intent

1.1 Accountable ownership

The accountable owner is **Portal Architecture / Warehouse Operator**. Supporting applications, shared infrastructure, integration adapters, analytics, and AI coordinate or present the capability but shall not silently own its authoritative propositions.

1.2 Scope

- create and identify the subject
- validate evidence and policy
- make authorized Decisions
- execute typed Commands
- publish completed-fact Events
- query current and historical perspectives
- correct and reconcile outcomes

1.3 Non-goals

- treating a registered Gradle module, catalog record, README, frontend route, migration plan, or generated report as proof of end-to-end implementation;
- direct cross-Domain database writes;
- generic status values that combine lifecycle, approval, provider, document, payment, dispute, and correction state;
- silent replacement of history;
- AI-created authority or fabricated external outcomes.

2. Ubiquitous Language and Subject Model

Subject	Required interpretation
WarehouseOperatorPortal	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit
WarehouseOperatorPortalVersion	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit
WarehouseOperatorPortalDecision	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit
WarehouseOperatorPortalEvidenceSet	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit
WarehouseOperatorPortalException	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit

Reference aggregate:

```
WarehouseOperatorPortal {
  subjectId
  tenantId
  organizationContext
  sourceIdentityRefs[]
  sourceVersionRefs[]
  lifecycleState
  relationshipRefs[]
  decisionRefs[]
  intentRefs[]
  evidenceSetRef
  knowledgeCutoff
  policyRefs[]
  authorityRef
  jurisdictionRefs[]
  createdAt
  effectiveAt
  updatedAt
  version
  correctionOf?
  correlationId
}
```

2.1 Core invariants

- Stable identity precedes relationship, state, and cross-system correlation.
- Effective time and recorded time remain distinct where business truth changes over time.
- Recommendation, Decision, Intent, execution, and outcome are separate concepts.
- No Portal, report, search index, cache, workflow, or AI Agent becomes a shadow owner of Domain truth.
- Binding submitted, approved, issued, accepted, or signed versions are immutable.
- Corrections append governed facts and preserve the original record.
- External authority and provider outcomes retain their source and qualification.
- Tenant and represented-principal context come from trusted authentication and mandate evaluation.
- Retried writes are idempotent and concurrency guarded.
- Outcome Unknown is explicit and reconciled before risky duplicate execution.

2.2 Required standards

- stable identifiers
- typed contracts
- immutable binding versions

- transactional outbox
- idempotent Commands
- explicit Outcome Unknown
- correction lineage
- machine-verifiable conformance

3. Actors, Roles, and Authority

A conformant design distinguishes:

- the natural person acting;
- the service or AI identity invoking a Tool;
- the organization or principal represented;
- the role or relationship granting context;
- the mandate or delegation granting action authority;
- the Policy and jurisdiction limiting the action;
- the reviewer or approver responsible for a binding Decision.

Authority is evaluated at action time. Authentication alone does not grant business authority. Cached permissions and browser-supplied tenant headers are insufficient for high-impact actions.

4. Lifecycle and State Model

State	Semantics
PROPOSED	Distinct governed condition with entry, exit, timeout, correction and authority semantics
VALIDATION_PENDING	Distinct governed condition with entry, exit, timeout, correction and authority semantics
APPROVAL_PENDING	Distinct governed condition with entry, exit, timeout, correction and authority semantics
ACTIVE	Distinct governed condition with entry, exit, timeout, correction and authority semantics
SUSPENDED	Distinct governed condition with entry, exit, timeout, correction and authority semantics
CORRECTION_PENDING	Distinct governed condition with entry, exit, timeout, correction and authority semantics
RETIRED	Distinct governed condition with entry, exit, timeout, correction and authority semantics

```
stateDiagram-v2
    [*] --> PROPOSED
    PROPOSED --> VALIDATION_PENDING
    VALIDATION_PENDING --> APPROVAL_PENDING
    APPROVAL_PENDING --> ACTIVE
    ACTIVE --> SUSPENDED
    SUSPENDED --> CORRECTION_PENDING
    CORRECTION_PENDING --> RETIRED
```

The diagram is a primary reading path. Real implementations may add parallel review, amendment, appeal, timeout, suspension, partial completion, reconciliation, correction, and terminal failure without collapsing their meaning.

4.1 Transition rules

- transition through a typed, authorized Command;
- require exact expected version where concurrent change matters;
- record actor, represented principal, mandate, Policy, reason, and Evidence;
- use an idempotency key for retried writes;
- publish a completed-fact Event after durable state change;
- expose Outcome Unknown for unresolved external completion;
- preserve original and corrected states in historical reconstruction.

5. Decision, Evidence, and Knowledge Cutoff

Reference Decision:

```
Decision {
  decisionId
  decisionType
  subjectRef
  sourceVersionRefs[]
  knowledgeCutoff
  evidenceSetRef
  policyVersionRefs[]
  recommendationRefs[]
  principalId
  representedOrganizationId
  mandateRef
  rationale
  outcome
  decidedAt
  effectiveAt
  correctionOf?
}
```

Evidence records identify issuer or observer, subject, version, observed time, received time, effective interval, integrity, confidence, qualification, contradiction, correction, retention, residency, and access class. A recommendation may assist the Decision but cannot promote itself to the Decision.

6. Commands, Events, Queries, and Contracts

Reference Commands:

- CreateWarehouseOperatorPortal
- ValidateWarehouseOperatorPortal
- ApproveWarehouseOperatorPortal
- ActivateWarehouseOperatorPortal
- SuspendWarehouseOperatorPortal
- CorrectWarehouseOperatorPortal
- RetireWarehouseOperatorPortal

Reference Events:

- WarehouseOperatorPortalCreated
- WarehouseOperatorPortalValidated
- WarehouseOperatorPortalApproved
- WarehouseOperatorPortalActivated
- WarehouseOperatorPortalSuspended
- WarehouseOperatorPortalCorrected
- WarehouseOperatorPortalRetired

Reference queries:

- GetWarehouseOperatorPortal
- ListWarehouseOperatorPortalRecords
- GetWarehouseOperatorPortalTimeline
- GetWarehouseOperatorPortalEvidence
- GetWarehouseOperatorPortalDecisionPackage
- GetWarehouseOperatorPortalExceptions
- GetWarehouseOperatorPortalAuditTrail

Reference API surface:

```
POST /api/v1/warehouseoperatorportal/commands
GET  /api/v1/warehouseoperatorportal/{id}
GET  /api/v1/warehouseoperatorportal/{id}/timeline
GET  /api/v1/warehouseoperatorportal/{id}/evidence
GET  /api/v1/warehouseoperatorportal/{id}/decisions
POST /api/v1/warehouseoperatorportal/{id}/exceptions
POST /api/v1/warehouseoperatorportal/{id}/corrections
```

These endpoints are reference contracts, not claims that exact routes exist.

7. Workflow, Failure, and Compensation

flowchart TD

```
A[Validate identity version and authority] --> B[Collect required evidence]
B --> C{Policy and evidence gates pass?}
C -- No --> D[Open exception or request correction]
D --> B
C -- Yes --> E[Record Decision or execution Intent]
E --> F[Execute Domain command or external request]
F --> G{Outcome known?}
G -- Success --> H[Record fact and publish Event]
G -- Failure --> I[Record failure and compensation options]
G -- Unknown --> J[Enter Outcome Unknown]
J --> K[Query source or wait for verified callback]
K --> G
H --> L[Update projections and downstream workflow]
```

Representative failure modes:

- stale or wrong source version
- duplicate submission or replay
- external timeout after possible success
- contradictory source observations
- lost Event after committed state
- approval or mandate revoked during execution
- downstream action before a mandatory gate
- partial completion across multiple subjects
- evidence later retracted or corrected
- tenant, facility, channel or jurisdiction mismatch

Recovery shall query the authoritative source before duplicate execution, preserve partial success, use compensating Intent rather than destructive rewrite, publish corrections, quarantine high-impact ambiguity, and record affected downstream subjects.

8. Data and Persistence Architecture

Reference table families:

Table family	Purpose
warehouseoperatorportal_aggregate	authoritative subject
warehouseoperatorportal_version	immutable submitted, approved, issued, or signed versions
warehouseoperatorportal_relationship	governed relationships
warehouseoperatorportal_decision	binding Decisions and rationale
warehouseoperatorportal_evidence_link	provenance and evidence relationships
warehouseoperatorportal_event_outbox	transactional Event publication
warehouseoperatorportal_idempotency	duplicate-write protection
warehouseoperatorportal_exception	exception, claim, dispute, or hold
warehouseoperatorportal_correction	correction and supersession lineage
warehouseoperatorportal_audit	privileged action evidence

The owning service controls schema and migration. Cross-Domain references use stable identifiers or contracts. Analytics, reports, caches, search, and vector indexes remain projections. Backup, restore, retention, legal hold, privacy, residency, and decommissioning requirements are explicit.

9. Portal and Experience Requirements

- Warehouse Operator: primary experience for warehouse staff and supervisors.
- Operator and support views: diagnose failed or ambiguous journeys without assuming Domain ownership.
- Domain services: own authoritative data and action eligibility; the Portal consumes typed contracts.

Every Portal displays exact version, owner, state, freshness, required action, and uncertainty. It supports loading, empty, partial, stale, denied, error, timeout, and Outcome Unknown states; accessibility; locale, currency, unit, date, and RTL/LTR correctness; evidence audit; safe retry; and correction history.

10. AI Participation and Tool Governance

Permitted AI tasks:

- extract and classify evidence
- detect anomalies and missing fields
- summarize timelines and contradictions
- recommend next actions with sources and uncertainty

AI shall not own Domain records, grant itself authority, suppress contradictions, silently edit approved versions, fabricate external outcomes, or execute high-impact actions outside typed Tools, policy, approval, idempotency, sandbox, and outcome observation.

Every Agent Run records source context, prompt/model/tool versions, structured output, confidence and limitations, Policy result, approval, Tool calls, provider responses, final outcome, and recovery actions.

11. Security, Privacy, and Trust Boundaries

- least privilege and separation of duties
- tenant, organization, facility, channel and jurisdiction isolation
- integrity protection for binding evidence
- verified external callbacks and anti-replay controls

Additional controls include secret isolation, callback signature verification, audit of privileged action, emergency-access review, sensitive-data minimization, purpose limitation, and threat models for impersonation, tampering, replay, confused deputy, fraud, prompt injection, and exfiltration.

12. Reliability, SLOs, and Operations

SLI	Reference objective
authoritative read availability	99.9% monthly unless a stricter tier applies
acknowledged Command durability	no acknowledged write may be silently lost
Event publication	99.9% within five minutes after committed fact
duplicate prevention	100% for same tenant, Command class, and idempotency key
binding Decision audit completeness	100%
state-state detection	bounded by business deadline

Dashboards and runbooks cover backlog, error budget, dependency failure, retry budget, DLQ, workflow stall, provider outage, reconciliation, capacity, backup/restore, release/rollback, incident command, and post-incident correction.

13. Testing and Continuous Conformance

- aggregate invariant and transition tests
- authorization, delegation, separation-of-duties and tenant-isolation tests
- idempotency and optimistic-concurrency tests
- database migration, key, constraint and rollback tests
- contract, outbox/inbox, duplicate, replay and DLQ tests
- workflow restart, timeout and compensation tests
- Portal E2E tests for success, partial, stale, denied, error and Outcome Unknown states
- accessibility, locale, currency, unit and RTL/LTR tests
- security adversarial, fraud and data-exfiltration tests
- AI evaluation, prompt-injection, policy-bypass and unauthorized-tool tests
- historical reconstruction, correction and audit-completeness tests
- performance, capacity, recovery and operational exercise tests

Release evidence links each invariant and control to the test, environment, input data, result, owner, and artifact proving it. Generated test counts never replace semantic coverage.

14. Repository Review Boundary

- This chapter is a repository-review specification. Exact executable implementation has not been inspected for every target behavior.
- Registered modules, catalog entries, README claims, frontend contracts, or plans are not proof of complete implementation.

Area	Classification
target aggregate, API, tables, state and workflow in this chapter	REFERENCE_ARCHITECTURE
registered module or catalog claim	DOCUMENTATION_ONLY_CLAIM until source inspection
uninspected integration	REQUIRES_REPOSITORY_REVIEW
behavior proven in another repository-grounded chapter	retain that chapter's evidence and classification
contradictory ownership or path claims	CONFLICT_REQUIRES_CANONICALIZATION

No statement upgrades implementation status merely because a file, directory, module name, frontend contract, database entry, plan, or report exists.

15. Worked Conformance Scenario

An authorized principal initiates a Command against an exact subject version. The service validates identity, tenant, mandate, Policy, Evidence, and idempotency. It records the state transition and outbox entry atomically. If an external dependency participates, timeout produces Outcome Unknown; reconciliation queries the source or waits for a verified callback instead of repeating the action blindly.

Portals show source, freshness, version, required action, and uncertainty. AI may extract, compare, summarize, detect anomalies, and recommend through typed Tools, but cannot own the subject or fabricate success. Later correction appends new facts, identifies affected projections and workflows, and preserves the historical Decision context.

16. Conformance Checklist

- ☐ stable identity and proposition ownership are explicit;
- ☐ authority and mandate are evaluated at action time;
- ☐ state, Recommendation, Decision, Intent, execution, and outcome remain distinct;
- ☐ Commands are typed, authorized, idempotent, and version guarded;
- ☐ Events describe completed facts;
- ☐ Evidence includes provenance, time, integrity, qualification, and correction;
- ☐ external outcomes retain their authority source;
- ☐ Portals show freshness and uncertainty;
- ☐ AI is bounded by typed Tools, Policy, approval, and outcome observation;
- ☐ security, tenant, facility, channel, and jurisdiction boundaries are enforced;
- ☐ Outcome Unknown and reconciliation exist where needed;
- ☐ corrections preserve history;
- ☐ tests prove invariants and recovery;
- ☐ implementation status is not upgraded without executable evidence.

17. Status Vocabulary

Status	Meaning
VERIFIED_IMPLEMENTED	Executable source and relevant behavior were inspected. Executable behavior exists with a material governance or completeness gap.
IMPLEMENTED_WITH_GAP	
PARTIAL_IMPLEMENTATION	Only part of the target capability is evidenced.
REFERENCE_ARCHITECTURE	Normative target behavior; no claim that it exists today.
PLANNED_NOT_IMPLEMENTED	Explicitly planned but not evidenced as executable.
DOCUMENTATION_ONLY_CLAIM	Documentation or client contract claims behavior without verified backend evidence.
CONFLICT_REQUIRES_CANONICALIZATION	Sources disagree and no final owner has been established.
REQUIRES_REPOSITORY_REVIEW	Necessary executable evidence has not yet been inspected.

Warehouse Operator — Routes, Pages, Components, and BFF Contracts

Metadata	Value
Volume	4
Chapter ID	V04-P04-01
Subject	WarehouseOperatorRouteRegistry
Status	Generated First-Draft Architecture Skeleton - Domain-Specific Expansion Required
Content maturity	TEMPLATE_DERIVED_REFERENCE_SKELETON unless repository citations prove otherwise
Default implementation classification	REFERENCE_ARCHITECTURE / REQUIRES_REPOSITORY_REVIEW
Accountable owner	Portal Architecture / Warehouse Operator
Evidence rule	No implementation claim without inspected executable evidence
Repository	chinair88-prog/allinb2c

1. Executive Orientation

This chapter defines how GTOS shall **inventory routes, layouts, pages, components, server/client boundaries, BFFs, APIs, realtime channels and ownership for warehouse staff and supervisors, covering receiving, put-away, inventory, picking, packing, dispatch, counts, discrepancies.**

The specification separates reality, observations, knowledge, Decisions, Intent, execution, and outcomes. A component name, database row, UI label, AI answer, or workflow state does not acquire authority merely because it is visible or technically convenient.

Reality or external outcome

- ≠ Observation
- ≠ Claim
- ≠ derived Perspective
- ≠ Prediction
- ≠ Recommendation
- ≠ authorized Decision
- ≠ execution Intent

1.1 Accountable ownership

The accountable owner is **Portal Architecture / Warehouse Operator**. Supporting applications, shared infrastructure, integration adapters, analytics, and AI coordinate or present the capability but shall not silently own its authoritative propositions.

1.2 Scope

- create and identify the subject
- validate evidence and policy
- make authorized Decisions
- execute typed Commands
- publish completed-fact Events
- query current and historical perspectives
- correct and reconcile outcomes

1.3 Non-goals

- treating a registered Gradle module, catalog record, README, frontend route, migration plan, or generated report as proof of end-to-end implementation;
- direct cross-Domain database writes;
- generic status values that combine lifecycle, approval, provider, document, payment, dispute, and correction state;
- silent replacement of history;
- AI-created authority or fabricated external outcomes.

2. Ubiquitous Language and Subject Model

Subject	Required interpretation
WarehouseOperatorRouteRegistry	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit
WarehouseOperatorRouteRegistryVersion	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit
WarehouseOperatorRouteRegistryDecision	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit
WarehouseOperatorRouteRegistryEvidenceSet	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit
WarehouseOperatorRouteRegistryException	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit

Reference aggregate:

```
WarehouseOperatorRouteRegistry {  
  subjectId  
  tenantId  
  organizationContext  
  sourceIdentityRefs[]  
  sourceVersionRefs[]  
  lifecycleState  
  relationshipRefs[]  
  decisionRefs[]  
  intentRefs[]  
  evidenceSetRef  
  knowledgeCutoff  
  policyRefs[]  
  authorityRef  
  jurisdictionRefs[]  
  createdAt  
  effectiveAt  
  updatedAt  
  version  
  correctionOf?  
  correlationId  
}
```

2.1 Core invariants

- Stable identity precedes relationship, state, and cross-system correlation.
- Effective time and recorded time remain distinct where business truth changes over time.
- Recommendation, Decision, Intent, execution, and outcome are separate concepts.
- No Portal, report, search index, cache, workflow, or AI Agent becomes a shadow owner of Domain truth.
- Binding submitted, approved, issued, accepted, or signed versions are immutable.
- Corrections append governed facts and preserve the original record.
- External authority and provider outcomes retain their source and qualification.
- Tenant and represented-principal context come from trusted authentication and mandate evaluation.
- Retried writes are idempotent and concurrency guarded.
- Outcome Unknown is explicit and reconciled before risky duplicate execution.

2.2 Required standards

- stable identifiers
- typed contracts
- immutable binding versions

- transactional outbox
- idempotent Commands
- explicit Outcome Unknown
- correction lineage
- machine-verifiable conformance

3. Actors, Roles, and Authority

A conformant design distinguishes:

- the natural person acting;
- the service or AI identity invoking a Tool;
- the organization or principal represented;
- the role or relationship granting context;
- the mandate or delegation granting action authority;
- the Policy and jurisdiction limiting the action;
- the reviewer or approver responsible for a binding Decision.

Authority is evaluated at action time. Authentication alone does not grant business authority. Cached permissions and browser-supplied tenant headers are insufficient for high-impact actions.

4. Lifecycle and State Model

State	Semantics
PROPOSED	Distinct governed condition with entry, exit, timeout, correction and authority semantics
VALIDATION_PENDING	Distinct governed condition with entry, exit, timeout, correction and authority semantics
APPROVAL_PENDING	Distinct governed condition with entry, exit, timeout, correction and authority semantics
ACTIVE	Distinct governed condition with entry, exit, timeout, correction and authority semantics
SUSPENDED	Distinct governed condition with entry, exit, timeout, correction and authority semantics
CORRECTION_PENDING	Distinct governed condition with entry, exit, timeout, correction and authority semantics
RETIRED	Distinct governed condition with entry, exit, timeout, correction and authority semantics

```
stateDiagram-v2
    [*] --> PROPOSED
    PROPOSED --> VALIDATION_PENDING
    VALIDATION_PENDING --> APPROVAL_PENDING
    APPROVAL_PENDING --> ACTIVE
    ACTIVE --> SUSPENDED
    SUSPENDED --> CORRECTION_PENDING
    CORRECTION_PENDING --> RETIRED
```

The diagram is a primary reading path. Real implementations may add parallel review, amendment, appeal, timeout, suspension, partial completion, reconciliation, correction, and terminal failure without collapsing their meaning.

4.1 Transition rules

- transition through a typed, authorized Command;
- require exact expected version where concurrent change matters;
- record actor, represented principal, mandate, Policy, reason, and Evidence;
- use an idempotency key for retried writes;
- publish a completed-fact Event after durable state change;
- expose Outcome Unknown for unresolved external completion;
- preserve original and corrected states in historical reconstruction.

5. Decision, Evidence, and Knowledge Cutoff

Reference Decision:

```
Decision {
  decisionId
  decisionType
  subjectRef
  sourceVersionRefs[]
  knowledgeCutoff
  evidenceSetRef
  policyVersionRefs[]
  recommendationRefs[]
  principalId
  representedOrganizationId
  mandateRef
  rationale
  outcome
  decidedAt
  effectiveAt
  correctionOf?
}
```

Evidence records identify issuer or observer, subject, version, observed time, received time, effective interval, integrity, confidence, qualification, contradiction, correction, retention, residency, and access class. A recommendation may assist the Decision but cannot promote itself to the Decision.

6. Commands, Events, Queries, and Contracts

Reference Commands:

- CreateWarehouseOperatorRouteRegistry
- ValidateWarehouseOperatorRouteRegistry
- ApproveWarehouseOperatorRouteRegistry
- ActivateWarehouseOperatorRouteRegistry
- SuspendWarehouseOperatorRouteRegistry
- CorrectWarehouseOperatorRouteRegistry
- RetireWarehouseOperatorRouteRegistry

Reference Events:

- WarehouseOperatorRouteRegistryCreated
- WarehouseOperatorRouteRegistryValidated
- WarehouseOperatorRouteRegistryApproved
- WarehouseOperatorRouteRegistryActivated
- WarehouseOperatorRouteRegistrySuspended
- WarehouseOperatorRouteRegistryCorrected
- WarehouseOperatorRouteRegistryRetired

Reference queries:

- GetWarehouseOperatorRouteRegistry
- ListWarehouseOperatorRouteRegistryRecords
- GetWarehouseOperatorRouteRegistryTimeline
- GetWarehouseOperatorRouteRegistryEvidence
- GetWarehouseOperatorRouteRegistryDecisionPackage
- GetWarehouseOperatorRouteRegistryExceptions
- GetWarehouseOperatorRouteRegistryAuditTrail

Reference API surface:

```
POST /api/v1/warehouseoperatorrouteregistry/commands
GET  /api/v1/warehouseoperatorrouteregistry/{id}
GET  /api/v1/warehouseoperatorrouteregistry/{id}/timeline
GET  /api/v1/warehouseoperatorrouteregistry/{id}/evidence
GET  /api/v1/warehouseoperatorrouteregistry/{id}/decisions
POST /api/v1/warehouseoperatorrouteregistry/{id}/exceptions
POST /api/v1/warehouseoperatorrouteregistry/{id}/corrections
```

These endpoints are reference contracts, not claims that exact routes exist.

7. Workflow, Failure, and Compensation

```
flowchart TD
    A[Validate identity version and authority] --> B[Collect required evidence]
    B --> C{Policy and evidence gates pass?}
    C -- No --> D[Open exception or request correction]
    D --> B
    C -- Yes --> E[Record Decision or execution Intent]
    E --> F[Execute Domain command or external request]
    F --> G{Outcome known?}
    G -- Success --> H[Record fact and publish Event]
    G -- Failure --> I[Record failure and compensation options]
    G -- Unknown --> J[Enter Outcome Unknown]
    J --> K[Query source or wait for verified callback]
    K --> G
    H --> L[Update projections and downstream workflow]
```

Representative failure modes:

- stale or wrong source version
- duplicate submission or replay
- external timeout after possible success
- contradictory source observations
- lost Event after committed state
- approval or mandate revoked during execution
- downstream action before a mandatory gate
- partial completion across multiple subjects
- evidence later retracted or corrected
- tenant, facility, channel or jurisdiction mismatch

Recovery shall query the authoritative source before duplicate execution, preserve partial success, use compensating Intent rather than destructive rewrite, publish corrections, quarantine high-impact ambiguity, and record affected downstream subjects.

8. Data and Persistence Architecture

Reference table families:

Table family	Purpose
warehouseoperatorrouterregistry_aggregate	authoritative subject
warehouseoperatorrouterregistry_version	immutable submitted, approved, issued, or signed versions
warehouseoperatorrouterregistry_relationship	governed relationships
warehouseoperatorrouterregistry_decision	binding Decisions and rationale
warehouseoperatorrouterregistry_evidence_link	provenance and evidence relationships
warehouseoperatorrouterregistry_event_outbox	transactional Event publication
warehouseoperatorrouterregistry_idempotency	duplicate-write protection
warehouseoperatorrouterregistry_exception	exception, claim, dispute, or hold
warehouseoperatorrouterregistry_correction	correction and supersession lineage
warehouseoperatorrouterregistry_audit	privileged action evidence

The owning service controls schema and migration. Cross-Domain references use stable identifiers or contracts. Analytics, reports, caches, search, and vector indexes remain projections. Backup, restore, retention, legal hold, privacy, residency, and decommissioning requirements are explicit.

9. Portal and Experience Requirements

- Warehouse Operator: primary experience for warehouse staff and supervisors.
- Operator and support views: diagnose failed or ambiguous journeys without assuming Domain ownership.
- Domain services: own authoritative data and action eligibility; the Portal consumes typed contracts.

Every Portal displays exact version, owner, state, freshness, required action, and uncertainty. It supports loading, empty, partial, stale, denied, error, timeout, and Outcome Unknown states; accessibility; locale, currency, unit, date, and RTL/LTR correctness; evidence audit; safe retry; and correction history.

10. AI Participation and Tool Governance

Permitted AI tasks:

- extract and classify evidence
- detect anomalies and missing fields
- summarize timelines and contradictions
- recommend next actions with sources and uncertainty

AI shall not own Domain records, grant itself authority, suppress contradictions, silently edit approved versions, fabricate external outcomes, or execute high-impact actions outside typed Tools, policy, approval, idempotency, sandbox, and outcome observation.

Every Agent Run records source context, prompt/model/tool versions, structured output, confidence and limitations, Policy result, approval, Tool calls, provider responses, final outcome, and recovery actions.

11. Security, Privacy, and Trust Boundaries

- least privilege and separation of duties
- tenant, organization, facility, channel and jurisdiction isolation
- integrity protection for binding evidence
- verified external callbacks and anti-replay controls

Additional controls include secret isolation, callback signature verification, audit of privileged action, emergency-access review, sensitive-data minimization, purpose limitation, and threat models for impersonation, tampering, replay, confused deputy, fraud, prompt injection, and exfiltration.

12. Reliability, SLOs, and Operations

SLI	Reference objective
authoritative read availability	99.9% monthly unless a stricter tier applies
acknowledged Command durability	no acknowledged write may be silently lost
Event publication	99.9% within five minutes after committed fact
duplicate prevention	100% for same tenant, Command class, and idempotency key
binding Decision audit completeness	100%
state-state detection	bounded by business deadline

Dashboards and runbooks cover backlog, error budget, dependency failure, retry budget, DLQ, workflow stall, provider outage, reconciliation, capacity, backup/restore, release/rollback, incident command, and post-incident correction.

13. Testing and Continuous Conformance

- aggregate invariant and transition tests
- authorization, delegation, separation-of-duties and tenant-isolation tests
- idempotency and optimistic-concurrency tests
- database migration, key, constraint and rollback tests
- contract, outbox/inbox, duplicate, replay and DLQ tests
- workflow restart, timeout and compensation tests
- Portal E2E tests for success, partial, stale, denied, error and Outcome Unknown states
- accessibility, locale, currency, unit and RTL/LTR tests
- security adversarial, fraud and data-exfiltration tests
- AI evaluation, prompt-injection, policy-bypass and unauthorized-tool tests
- historical reconstruction, correction and audit-completeness tests
- performance, capacity, recovery and operational exercise tests

Release evidence links each invariant and control to the test, environment, input data, result, owner, and artifact proving it. Generated test counts never replace semantic coverage.

14. Repository Review Boundary

- This chapter is a repository-review specification. Exact executable implementation has not been inspected for every target behavior.
- Registered modules, catalog entries, README claims, frontend contracts, or plans are not proof of complete implementation.

Area	Classification
target aggregate, API, tables, state and workflow in this chapter	REFERENCE_ARCHITECTURE
registered module or catalog claim	DOCUMENTATION_ONLY_CLAIM until source inspection
uninspected integration	REQUIRES_REPOSITORY_REVIEW
behavior proven in another repository-grounded chapter	retain that chapter's evidence and classification
contradictory ownership or path claims	CONFLICT_REQUIRES_CANONICALIZATION

No statement upgrades implementation status merely because a file, directory, module name, frontend contract, database entry, plan, or report exists.

15. Worked Conformance Scenario

An authorized principal initiates a Command against an exact subject version. The service validates identity, tenant, mandate, Policy, Evidence, and idempotency. It records the state transition and outbox entry atomically. If an external dependency participates, timeout produces Outcome Unknown; reconciliation queries the source or waits for a verified callback instead of repeating the action blindly.

Portals show source, freshness, version, required action, and uncertainty. AI may extract, compare, summarize, detect anomalies, and recommend through typed Tools, but cannot own the subject or fabricate success. Later correction appends new facts, identifies affected projections and workflows, and preserves the historical Decision context.

16. Conformance Checklist

- ☐ stable identity and proposition ownership are explicit;
- ☐ authority and mandate are evaluated at action time;
- ☐ state, Recommendation, Decision, Intent, execution, and outcome remain distinct;
- ☐ Commands are typed, authorized, idempotent, and version guarded;
- ☐ Events describe completed facts;
- ☐ Evidence includes provenance, time, integrity, qualification, and correction;
- ☐ external outcomes retain their authority source;
- ☐ Portals show freshness and uncertainty;
- ☐ AI is bounded by typed Tools, Policy, approval, and outcome observation;
- ☐ security, tenant, facility, channel, and jurisdiction boundaries are enforced;
- ☐ Outcome Unknown and reconciliation exist where needed;
- ☐ corrections preserve history;
- ☐ tests prove invariants and recovery;
- ☐ implementation status is not upgraded without executable evidence.

17. Status Vocabulary

Status	Meaning
VERIFIED_IMPLEMENTED	Executable source and relevant behavior were inspected.
IMPLEMENTED_WITH_GAP	Executable behavior exists with a material governance or completeness gap.
PARTIAL_IMPLEMENTATION	Only part of the target capability is evidenced.
REFERENCE_ARCHITECTURE	Normative target behavior; no claim that it exists today.
PLANNED_NOT_IMPLEMENTED	Explicitly planned but not evidenced as executable.
DOCUMENTATION_ONLY_CLAIM	Documentation or client contract claims behavior without verified backend evidence.
CONFLICT_REQUIRES_CANONICALIZATION	Sources disagree and no final owner has been established.
REQUIRES_REPOSITORY_REVIEW	Necessary executable evidence has not yet been inspected.

Warehouse Operator — Identity, Session, Authorization, and Trust Boundaries

Metadata	Value
Volume	4
Chapter ID	V04-P04-02
Subject	WarehouseOperatorAccessModel
Status	Generated First-Draft Architecture Skeleton - Domain-Specific Expansion Required
Content maturity	TEMPLATE_DERIVED_REFERENCE_SKELETON unless repository citations prove otherwise
Default implementation classification	REFERENCE_ARCHITECTURE / REQUIRES_REPOSITORY_REVIEW
Accountable owner	Portal Architecture / Warehouse Operator
Evidence rule	No implementation claim without inspected executable evidence
Repository	chinair88-prog/allinb2c

1. Executive Orientation

This chapter defines how GTOS shall **govern login, session, role, relationship, tenant, facility, channel, delegation, impersonation and privileged action for warehouse staff and supervisors, covering receiving, putaway, inventory, picking, packing, dispatch, counts, discrepancies.**

The specification separates reality, observations, knowledge, Decisions, Intent, execution, and outcomes. A component name, database row, UI label, AI answer, or workflow state does not acquire authority merely because it is visible or technically convenient.

Reality or external outcome

- ≠ Observation
- ≠ Claim
- ≠ derived Perspective
- ≠ Prediction
- ≠ Recommendation
- ≠ authorized Decision
- ≠ execution Intent

1.1 Accountable ownership

The accountable owner is **Portal Architecture / Warehouse Operator**. Supporting applications, shared infrastructure, integration adapters, analytics, and AI coordinate or present the capability but shall not silently own its authoritative propositions.

1.2 Scope

- create and identify the subject
- validate evidence and policy
- make authorized Decisions
- execute typed Commands
- publish completed-fact Events
- query current and historical perspectives
- correct and reconcile outcomes

1.3 Non-goals

- treating a registered Gradle module, catalog record, README, frontend route, migration plan, or generated report as proof of end-to-end implementation;
- direct cross-Domain database writes;
- generic status values that combine lifecycle, approval, provider, document, payment, dispute, and correction state;
- silent replacement of history;
- AI-created authority or fabricated external outcomes.

2. Ubiquitous Language and Subject Model

Subject	Required interpretation
WarehouseOperatorAccessModel	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit
WarehouseOperatorAccessModelVersion	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit
WarehouseOperatorAccessModelDecision	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit
WarehouseOperatorAccessModelEvidenceSet	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit
WarehouseOperatorAccessModelException	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit

Reference aggregate:

```
WarehouseOperatorAccessModel {  
  subjectId  
  tenantId  
  organizationContext  
  sourceIdentityRefs[]  
  sourceVersionRefs[]  
  lifecycleState  
  relationshipRefs[]  
  decisionRefs[]  
  intentRefs[]  
  evidenceSetRef  
  knowledgeCutoff  
  policyRefs[]  
  authorityRef  
  jurisdictionRefs[]  
  createdAt  
  effectiveAt  
  updatedAt  
  version  
  correctionOf?  
  correlationId  
}
```

2.1 Core invariants

- Stable identity precedes relationship, state, and cross-system correlation.
- Effective time and recorded time remain distinct where business truth changes over time.
- Recommendation, Decision, Intent, execution, and outcome are separate concepts.
- No Portal, report, search index, cache, workflow, or AI Agent becomes a shadow owner of Domain truth.
- Binding submitted, approved, issued, accepted, or signed versions are immutable.
- Corrections append governed facts and preserve the original record.
- External authority and provider outcomes retain their source and qualification.
- Tenant and represented-principal context come from trusted authentication and mandate evaluation.
- Retried writes are idempotent and concurrency guarded.
- Outcome Unknown is explicit and reconciled before risky duplicate execution.

2.2 Required standards

- stable identifiers
- typed contracts
- immutable binding versions

- transactional outbox
- idempotent Commands
- explicit Outcome Unknown
- correction lineage
- machine-verifiable conformance

3. Actors, Roles, and Authority

- A conformant design distinguishes:
- the natural person acting;
 - the service or AI identity invoking a Tool;
 - the organization or principal represented;
 - the role or relationship granting context;
 - the mandate or delegation granting action authority;
 - the Policy and jurisdiction limiting the action;
 - the reviewer or approver responsible for a binding Decision.

Authority is evaluated at action time. Authentication alone does not grant business authority. Cached permissions and browser-supplied tenant headers are insufficient for high-impact actions.

4. Lifecycle and State Model

State	Semantics
PROPOSED	Distinct governed condition with entry, exit, timeout, correction and authority semantics
VALIDATION_PENDING	Distinct governed condition with entry, exit, timeout, correction and authority semantics
APPROVAL_PENDING	Distinct governed condition with entry, exit, timeout, correction and authority semantics
ACTIVE	Distinct governed condition with entry, exit, timeout, correction and authority semantics
SUSPENDED	Distinct governed condition with entry, exit, timeout, correction and authority semantics
CORRECTION_PENDING	Distinct governed condition with entry, exit, timeout, correction and authority semantics
RETIRED	Distinct governed condition with entry, exit, timeout, correction and authority semantics

```
stateDiagram-v2
    [*] --> PROPOSED
    PROPOSED --> VALIDATION_PENDING
    VALIDATION_PENDING --> APPROVAL_PENDING
    APPROVAL_PENDING --> ACTIVE
    ACTIVE --> SUSPENDED
    SUSPENDED --> CORRECTION_PENDING
    CORRECTION_PENDING --> RETIRED
```

The diagram is a primary reading path. Real implementations may add parallel review, amendment, appeal, timeout, suspension, partial completion, reconciliation, correction, and terminal failure without collapsing their meaning.

4.1 Transition rules

- transition through a typed, authorized Command;
- require exact expected version where concurrent change matters;
- record actor, represented principal, mandate, Policy, reason, and Evidence;
- use an idempotency key for retried writes;
- publish a completed-fact Event after durable state change;
- expose Outcome Unknown for unresolved external completion;
- preserve original and corrected states in historical reconstruction.

5. Decision, Evidence, and Knowledge Cutoff

Reference Decision:

```
Decision {
  decisionId
  decisionType
  subjectRef
  sourceVersionRefs[]
  knowledgeCutoff
  evidenceSetRef
  policyVersionRefs[]
  recommendationRefs[]
  principalId
  representedOrganizationId
  mandateRef
  rationale
  outcome
  decidedAt
  effectiveAt
  correctionOf?
}
```

Evidence records identify issuer or observer, subject, version, observed time, received time, effective interval, integrity, confidence, qualification, contradiction, correction, retention, residency, and access class. A recommendation may assist the Decision but cannot promote itself to the Decision.

6. Commands, Events, Queries, and Contracts

Reference Commands:

- CreateWarehouseOperatorAccessModel
- ValidateWarehouseOperatorAccessModel
- ApproveWarehouseOperatorAccessModel
- ActivateWarehouseOperatorAccessModel
- SuspendWarehouseOperatorAccessModel
- CorrectWarehouseOperatorAccessModel
- RetireWarehouseOperatorAccessModel

Reference Events:

- WarehouseOperatorAccessModelCreated
- WarehouseOperatorAccessModelValidated
- WarehouseOperatorAccessModelApproved
- WarehouseOperatorAccessModelActivated
- WarehouseOperatorAccessModelSuspended
- WarehouseOperatorAccessModelCorrected
- WarehouseOperatorAccessModelRetired

Reference queries:

- GetWarehouseOperatorAccessModel
- ListWarehouseOperatorAccessModelRecords
- GetWarehouseOperatorAccessModelTimeline
- GetWarehouseOperatorAccessModelEvidence
- GetWarehouseOperatorAccessModelDecisionPackage
- GetWarehouseOperatorAccessModelExceptions
- GetWarehouseOperatorAccessModelAuditTrail

Reference API surface:

```
POST /api/v1/warehouseoperatoraccessmodel/commands
GET  /api/v1/warehouseoperatoraccessmodel/{id}
GET  /api/v1/warehouseoperatoraccessmodel/{id}/timeline
GET  /api/v1/warehouseoperatoraccessmodel/{id}/evidence
GET  /api/v1/warehouseoperatoraccessmodel/{id}/decisions
POST /api/v1/warehouseoperatoraccessmodel/{id}/exceptions
POST /api/v1/warehouseoperatoraccessmodel/{id}/corrections
```

These endpoints are reference contracts, not claims that exact routes exist.

7. Workflow, Failure, and Compensation

flowchart TD

```
A[Validate identity version and authority] --> B[Collect required evidence]
B --> C{Policy and evidence gates pass?}
C -- No --> D[Open exception or request correction]
D --> B
C -- Yes --> E[Record Decision or execution Intent]
E --> F[Execute Domain command or external request]
F --> G{Outcome known?}
G -- Success --> H[Record fact and publish Event]
G -- Failure --> I[Record failure and compensation options]
G -- Unknown --> J[Enter Outcome Unknown]
J --> K[Query source or wait for verified callback]
K --> G
H --> L[Update projections and downstream workflow]
```

Representative failure modes:

- stale or wrong source version
- duplicate submission or replay
- external timeout after possible success
- contradictory source observations
- lost Event after committed state
- approval or mandate revoked during execution
- downstream action before a mandatory gate
- partial completion across multiple subjects
- evidence later retracted or corrected
- tenant, facility, channel or jurisdiction mismatch

Recovery shall query the authoritative source before duplicate execution, preserve partial success, use compensating Intent rather than destructive rewrite, publish corrections, quarantine high-impact ambiguity, and record affected downstream subjects.

8. Data and Persistence Architecture

Reference table families:

Table family	Purpose
warehouseoperatoraccessmodel_aggregate	authoritative subject
warehouseoperatoraccessmodel_version	immutable submitted, approved, issued, or signed versions
warehouseoperatoraccessmodel_relationship	governed relationships
warehouseoperatoraccessmodel_decision	binding Decisions and rationale
warehouseoperatoraccessmodel_evidence_link	provenance and evidence relationships
warehouseoperatoraccessmodel_event_outbox	transactional Event publication
warehouseoperatoraccessmodel_idempotency	duplicate-write protection
warehouseoperatoraccessmodel_exception	exception, claim, dispute, or hold
warehouseoperatoraccessmodel_correction	correction and supersession lineage
warehouseoperatoraccessmodel_audit	privileged action evidence

The owning service controls schema and migration. Cross-Domain references use stable identifiers or contracts. Analytics, reports, caches, search, and vector indexes remain projections. Backup, restore, retention, legal hold, privacy, residency, and decommissioning requirements are explicit.

9. Portal and Experience Requirements

- Warehouse Operator: primary experience for warehouse staff and supervisors.
- Operator and support views: diagnose failed or ambiguous journeys without assuming Domain ownership.
- Domain services: own authoritative data and action eligibility; the Portal consumes typed contracts.

Every Portal displays exact version, owner, state, freshness, required action, and uncertainty. It supports loading, empty, partial, stale, denied, error, timeout, and Outcome Unknown states; accessibility; locale, currency, unit, date, and RTL/LTR correctness; evidence audit; safe retry; and correction history.

10. AI Participation and Tool Governance

Permitted AI tasks:

- extract and classify evidence
- detect anomalies and missing fields
- summarize timelines and contradictions
- recommend next actions with sources and uncertainty

AI shall not own Domain records, grant itself authority, suppress contradictions, silently edit approved versions, fabricate external outcomes, or execute high-impact actions outside typed Tools, policy, approval, idempotency, sandbox, and outcome observation.

Every Agent Run records source context, prompt/model/tool versions, structured output, confidence and limitations, Policy result, approval, Tool calls, provider responses, final outcome, and recovery actions.

11. Security, Privacy, and Trust Boundaries

- least privilege and separation of duties
- tenant, organization, facility, channel and jurisdiction isolation
- integrity protection for binding evidence
- verified external callbacks and anti-replay controls

Additional controls include secret isolation, callback signature verification, audit of privileged action, emergency-access review, sensitive-data minimization, purpose limitation, and threat models for impersonation, tampering, replay, confused deputy, fraud, prompt injection, and exfiltration.

12. Reliability, SLOs, and Operations

SLI	Reference objective
authoritative read availability	99.9% monthly unless a stricter tier applies
acknowledged Command durability	no acknowledged write may be silently lost
Event publication	99.9% within five minutes after committed fact
duplicate prevention	100% for same tenant, Command class, and idempotency key
binding Decision audit completeness	100%
state-state detection	bounded by business deadline

Dashboards and runbooks cover backlog, error budget, dependency failure, retry budget, DLQ, workflow stall, provider outage, reconciliation, capacity, backup/restore, release/rollback, incident command, and post-incident correction.

13. Testing and Continuous Conformance

- aggregate invariant and transition tests
- authorization, delegation, separation-of-duties and tenant-isolation tests
- idempotency and optimistic-concurrency tests
- database migration, key, constraint and rollback tests
- contract, outbox/inbox, duplicate, replay and DLQ tests
- workflow restart, timeout and compensation tests
- Portal E2E tests for success, partial, stale, denied, error and Outcome Unknown states
- accessibility, locale, currency, unit and RTL/LTR tests
- security adversarial, fraud and data-exfiltration tests
- AI evaluation, prompt-injection, policy-bypass and unauthorized-tool tests
- historical reconstruction, correction and audit-completeness tests
- performance, capacity, recovery and operational exercise tests

Release evidence links each invariant and control to the test, environment, input data, result, owner, and artifact proving it. Generated test counts never replace semantic coverage.

14. Repository Review Boundary

- This chapter is a repository-review specification. Exact executable implementation has not been inspected for every target behavior.
- Registered modules, catalog entries, README claims, frontend contracts, or plans are not proof of complete implementation.

Area	Classification
target aggregate, API, tables, state and workflow in this chapter	REFERENCE_ARCHITECTURE
registered module or catalog claim	DOCUMENTATION_ONLY_CLAIM until source inspection
uninspected integration	REQUIRES_REPOSITORY_REVIEW
behavior proven in another repository-grounded chapter	retain that chapter's evidence and classification
contradictory ownership or path claims	CONFLICT_REQUIRES_CANONICALIZATION

No statement upgrades implementation status merely because a file, directory, module name, frontend contract, database entry, plan, or report exists.

15. Worked Conformance Scenario

An authorized principal initiates a Command against an exact subject version. The service validates identity, tenant, mandate, Policy, Evidence, and idempotency. It records the state transition and outbox entry atomically. If an external dependency participates, timeout produces Outcome Unknown; reconciliation queries the source or waits for a verified callback instead of repeating the action blindly.

Portals show source, freshness, version, required action, and uncertainty. AI may extract, compare, summarize, detect anomalies, and recommend through typed Tools, but cannot own the subject or fabricate success. Later correction appends new facts, identifies affected projections and workflows, and preserves the historical Decision context.

16. Conformance Checklist

- ☐ stable identity and proposition ownership are explicit;
- ☐ authority and mandate are evaluated at action time;
- ☐ state, Recommendation, Decision, Intent, execution, and outcome remain distinct;
- ☐ Commands are typed, authorized, idempotent, and version guarded;
- ☐ Events describe completed facts;
- ☐ Evidence includes provenance, time, integrity, qualification, and correction;
- ☐ external outcomes retain their authority source;
- ☐ Portals show freshness and uncertainty;
- ☐ AI is bounded by typed Tools, Policy, approval, and outcome observation;
- ☐ security, tenant, facility, channel, and jurisdiction boundaries are enforced;
- ☐ Outcome Unknown and reconciliation exist where needed;
- ☐ corrections preserve history;
- ☐ tests prove invariants and recovery;
- ☐ implementation status is not upgraded without executable evidence.

17. Status Vocabulary

Status	Meaning
VERIFIED_IMPLEMENTED	Executable source and relevant behavior were inspected.
IMPLEMENTED_WITH_GAP	Executable behavior exists with a material governance or completeness gap.
PARTIAL_IMPLEMENTATION	Only part of the target capability is evidenced.
REFERENCE_ARCHITECTURE	Normative target behavior; no claim that it exists today.
PLANNED_NOT_IMPLEMENTED	Explicitly planned but not evidenced as executable.
DOCUMENTATION_ONLY_CLAIM	Documentation or client contract claims behavior without verified backend evidence.
CONFLICT_REQUIRES_CANONICALIZATION	Sources disagree and no final owner has been established.
REQUIRES_REPOSITORY_REVIEW	Necessary executable evidence has not yet been inspected.

Warehouse Operator — UX States, Accessibility, Localization, Analytics, and E2E

Metadata	Value
Volume	4
Chapter ID	V04-P04-03
Subject	WarehouseOperatorExperienceStandard
Status	Generated First-Draft Architecture Skeleton - Domain-Specific Expansion Required
Content maturity	TEMPLATE_DERIVED_REFERENCE_SKELETON unless repository citations prove otherwise
Default implementation classification	REFERENCE_ARCHITECTURE / REQUIRES_REPOSITORY_REVIEW
Accountable owner	Portal Architecture / Warehouse Operator
Evidence rule	No implementation claim without inspected executable evidence
Repository	chinair88-prog/allinb2c

1. Executive Orientation

This chapter defines how GTOS shall **specify loading, empty, partial, stale, error, denied, offline, accessibility, RTL/LTR, analytics, audit and test journeys for warehouse staff and supervisors, covering receiving, putaway, inventory, picking, packing, dispatch, counts, discrepancies.**

The specification separates reality, observations, knowledge, Decisions, Intent, execution, and outcomes. A component name, database row, UI label, AI answer, or workflow state does not acquire authority merely because it is visible or technically convenient.

Reality or external outcome

- ≠ Observation
- ≠ Claim
- ≠ derived Perspective
- ≠ Prediction
- ≠ Recommendation
- ≠ authorized Decision
- ≠ execution Intent

1.1 Accountable ownership

The accountable owner is **Portal Architecture / Warehouse Operator**. Supporting applications, shared infrastructure, integration adapters, analytics, and AI coordinate or present the capability but shall not silently own its authoritative propositions.

1.2 Scope

- create and identify the subject
- validate evidence and policy
- make authorized Decisions
- execute typed Commands
- publish completed-fact Events
- query current and historical perspectives
- correct and reconcile outcomes

1.3 Non-goals

- treating a registered Gradle module, catalog record, README, frontend route, migration plan, or generated report as proof of end-to-end implementation;
- direct cross-Domain database writes;
- generic status values that combine lifecycle, approval, provider, document, payment, dispute, and correction state;
- silent replacement of history;
- AI-created authority or fabricated external outcomes.

2. Ubiquitous Language and Subject Model

Subject	Required interpretation
WarehouseOperatorExperienceStandard	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit
WarehouseOperatorExperienceStandardVersion	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit
WarehouseOperatorExperienceStandardDecision	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit
WarehouseOperatorExperienceStandardEvidenceSet	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit
WarehouseOperatorExperienceStandardException	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit

Reference aggregate:

```
WarehouseOperatorExperienceStandard {  
  subjectId  
  tenantId  
  organizationContext  
  sourceIdentityRefs[]  
  sourceVersionRefs[]  
  lifecycleState  
  relationshipRefs[]  
  decisionRefs[]  
  intentRefs[]  
  evidenceSetRef  
  knowledgeCutoff  
  policyRefs[]  
  authorityRef  
  jurisdictionRefs[]  
  createdAt  
  effectiveAt  
  updatedAt  
  version  
  correctionOf?  
  correlationId  
}
```

2.1 Core invariants

- Stable identity precedes relationship, state, and cross-system correlation.
- Effective time and recorded time remain distinct where business truth changes over time.
- Recommendation, Decision, Intent, execution, and outcome are separate concepts.
- No Portal, report, search index, cache, workflow, or AI Agent becomes a shadow owner of Domain truth.
- Binding submitted, approved, issued, accepted, or signed versions are immutable.
- Corrections append governed facts and preserve the original record.
- External authority and provider outcomes retain their source and qualification.
- Tenant and represented-principal context come from trusted authentication and mandate evaluation.
- Retried writes are idempotent and concurrency guarded.
- Outcome Unknown is explicit and reconciled before risky duplicate execution.

2.2 Required standards

- stable identifiers
- typed contracts
- immutable binding versions

- transactional outbox
- idempotent Commands
- explicit Outcome Unknown
- correction lineage
- machine-verifiable conformance

3. Actors, Roles, and Authority

A conformant design distinguishes:

- the natural person acting;
- the service or AI identity invoking a Tool;
- the organization or principal represented;
- the role or relationship granting context;
- the mandate or delegation granting action authority;
- the Policy and jurisdiction limiting the action;
- the reviewer or approver responsible for a binding Decision.

Authority is evaluated at action time. Authentication alone does not grant business authority. Cached permissions and browser-supplied tenant headers are insufficient for high-impact actions.

4. Lifecycle and State Model

State	Semantics
PROPOSED	Distinct governed condition with entry, exit, timeout, correction and authority semantics
VALIDATION_PENDING	Distinct governed condition with entry, exit, timeout, correction and authority semantics
APPROVAL_PENDING	Distinct governed condition with entry, exit, timeout, correction and authority semantics
ACTIVE	Distinct governed condition with entry, exit, timeout, correction and authority semantics
SUSPENDED	Distinct governed condition with entry, exit, timeout, correction and authority semantics
CORRECTION_PENDING	Distinct governed condition with entry, exit, timeout, correction and authority semantics
RETIRED	Distinct governed condition with entry, exit, timeout, correction and authority semantics

```
stateDiagram-v2
    [*] --> PROPOSED
    PROPOSED --> VALIDATION_PENDING
    VALIDATION_PENDING --> APPROVAL_PENDING
    APPROVAL_PENDING --> ACTIVE
    ACTIVE --> SUSPENDED
    SUSPENDED --> CORRECTION_PENDING
    CORRECTION_PENDING --> RETIRED
```

The diagram is a primary reading path. Real implementations may add parallel review, amendment, appeal, timeout, suspension, partial completion, reconciliation, correction, and terminal failure without collapsing their meaning.

4.1 Transition rules

- transition through a typed, authorized Command;
- require exact expected version where concurrent change matters;
- record actor, represented principal, mandate, Policy, reason, and Evidence;
- use an idempotency key for retried writes;
- publish a completed-fact Event after durable state change;
- expose Outcome Unknown for unresolved external completion;
- preserve original and corrected states in historical reconstruction.

5. Decision, Evidence, and Knowledge Cutoff

Reference Decision:

```
Decision {
  decisionId
  decisionType
  subjectRef
  sourceVersionRefs[]
  knowledgeCutoff
  evidenceSetRef
  policyVersionRefs[]
  recommendationRefs[]
  principalId
  representedOrganizationId
  mandateRef
  rationale
  outcome
  decidedAt
  effectiveAt
  correctionOf?
}
```

Evidence records identify issuer or observer, subject, version, observed time, received time, effective interval, integrity, confidence, qualification, contradiction, correction, retention, residency, and access class. A recommendation may assist the Decision but cannot promote itself to the Decision.

6. Commands, Events, Queries, and Contracts

Reference Commands:

- CreateWarehouseOperatorExperienceStandard
- ValidateWarehouseOperatorExperienceStandard
- ApproveWarehouseOperatorExperienceStandard
- ActivateWarehouseOperatorExperienceStandard
- SuspendWarehouseOperatorExperienceStandard
- CorrectWarehouseOperatorExperienceStandard
- RetireWarehouseOperatorExperienceStandard

Reference Events:

- WarehouseOperatorExperienceStandardCreated
- WarehouseOperatorExperienceStandardValidated
- WarehouseOperatorExperienceStandardApproved
- WarehouseOperatorExperienceStandardActivated
- WarehouseOperatorExperienceStandardSuspended
- WarehouseOperatorExperienceStandardCorrected
- WarehouseOperatorExperienceStandardRetired

Reference queries:

- GetWarehouseOperatorExperienceStandard
- ListWarehouseOperatorExperienceStandardRecords
- GetWarehouseOperatorExperienceStandardTimeline
- GetWarehouseOperatorExperienceStandardEvidence
- GetWarehouseOperatorExperienceStandardDecisionPackage
- GetWarehouseOperatorExperienceStandardExceptions
- GetWarehouseOperatorExperienceStandardAuditTrail

Reference API surface:

```
POST /api/v1/warehouseoperatorexperiencstandard/commands
GET  /api/v1/warehouseoperatorexperiencstandard/{id}
GET  /api/v1/warehouseoperatorexperiencstandard/{id}/timeline
GET  /api/v1/warehouseoperatorexperiencstandard/{id}/evidence
GET  /api/v1/warehouseoperatorexperiencstandard/{id}/decisions
POST /api/v1/warehouseoperatorexperiencstandard/{id}/exceptions
POST /api/v1/warehouseoperatorexperiencstandard/{id}/corrections
```

These endpoints are reference contracts, not claims that exact routes exist.

7. Workflow, Failure, and Compensation

```
flowchart TD
    A[Validate identity version and authority] --> B[Collect required evidence]
    B --> C{Policy and evidence gates pass?}
    C -- No --> D[Open exception or request correction]
    D --> B
    C -- Yes --> E[Record Decision or execution Intent]
    E --> F[Execute Domain command or external request]
    F --> G{Outcome known?}
    G -- Success --> H[Record fact and publish Event]
    G -- Failure --> I[Record failure and compensation options]
    G -- Unknown --> J[Enter Outcome Unknown]
    J --> K[Query source or wait for verified callback]
    K --> G
    H --> L[Update projections and downstream workflow]
```

Representative failure modes:

- stale or wrong source version
- duplicate submission or replay
- external timeout after possible success
- contradictory source observations
- lost Event after committed state
- approval or mandate revoked during execution
- downstream action before a mandatory gate
- partial completion across multiple subjects
- evidence later retracted or corrected
- tenant, facility, channel or jurisdiction mismatch

Recovery shall query the authoritative source before duplicate execution, preserve partial success, use compensating Intent rather than destructive rewrite, publish corrections, quarantine high-impact ambiguity, and record affected downstream subjects.

8. Data and Persistence Architecture

Reference table families:

Table family	Purpose
warehouseoperatorexperiencestandard_aggregate	authoritative subject
warehouseoperatorexperiencestandard_version	immutable submitted, approved, issued, or signed versions
warehouseoperatorexperiencestandard_relationship	governed relationships
warehouseoperatorexperiencestandard_decision	binding Decisions and rationale
warehouseoperatorexperiencestandard_evidence_link	provenance and evidence relationships
warehouseoperatorexperiencestandard_event_outbox	transactional Event publication
warehouseoperatorexperiencestandard_idempotency	duplicate-write protection
warehouseoperatorexperiencestandard_exception	exception, claim, dispute, or hold
warehouseoperatorexperiencestandard_correction	correction and supersession lineage
warehouseoperatorexperiencestandard_audit	privileged action evidence

The owning service controls schema and migration. Cross-Domain references use stable identifiers or contracts. Analytics, reports, caches, search, and vector indexes remain projections. Backup, restore, retention, legal hold, privacy, residency, and decommissioning requirements are explicit.

9. Portal and Experience Requirements

- Warehouse Operator: primary experience for warehouse staff and supervisors.
- Operator and support views: diagnose failed or ambiguous journeys without assuming Domain ownership.
- Domain services: own authoritative data and action eligibility; the Portal consumes typed contracts.

Every Portal displays exact version, owner, state, freshness, required action, and uncertainty. It supports loading, empty, partial, stale, denied, error, timeout, and Outcome Unknown states; accessibility; locale, currency, unit, date, and RTL/LTR correctness; evidence audit; safe retry; and correction history.

10. AI Participation and Tool Governance

Permitted AI tasks:

- extract and classify evidence
- detect anomalies and missing fields
- summarize timelines and contradictions
- recommend next actions with sources and uncertainty

AI shall not own Domain records, grant itself authority, suppress contradictions, silently edit approved versions, fabricate external outcomes, or execute high-impact actions outside typed Tools, policy, approval, idempotency, sandbox, and outcome observation.

Every Agent Run records source context, prompt/model/tool versions, structured output, confidence and limitations, Policy result, approval, Tool calls, provider responses, final outcome, and recovery actions.

11. Security, Privacy, and Trust Boundaries

- least privilege and separation of duties
- tenant, organization, facility, channel and jurisdiction isolation
- integrity protection for binding evidence
- verified external callbacks and anti-replay controls

Additional controls include secret isolation, callback signature verification, audit of privileged action, emergency-access review, sensitive-data minimization, purpose limitation, and threat models for impersonation, tampering, replay, confused deputy, fraud, prompt injection, and exfiltration.

12. Reliability, SLOs, and Operations

SLI	Reference objective
authoritative read availability	99.9% monthly unless a stricter tier applies
acknowledged Command durability	no acknowledged write may be silently lost
Event publication	99.9% within five minutes after committed fact
duplicate prevention	100% for same tenant, Command class, and idempotency key
binding Decision audit completeness	100%
state-state detection	bounded by business deadline

Dashboards and runbooks cover backlog, error budget, dependency failure, retry budget, DLQ, workflow stall, provider outage, reconciliation, capacity, backup/restore, release/rollback, incident command, and post-incident correction.

13. Testing and Continuous Conformance

- aggregate invariant and transition tests
- authorization, delegation, separation-of-duties and tenant-isolation tests
- idempotency and optimistic-concurrency tests
- database migration, key, constraint and rollback tests
- contract, outbox/inbox, duplicate, replay and DLQ tests
- workflow restart, timeout and compensation tests
- Portal E2E tests for success, partial, stale, denied, error and Outcome Unknown states
- accessibility, locale, currency, unit and RTL/LTR tests
- security adversarial, fraud and data-exfiltration tests
- AI evaluation, prompt-injection, policy-bypass and unauthorized-tool tests
- historical reconstruction, correction and audit-completeness tests
- performance, capacity, recovery and operational exercise tests

Release evidence links each invariant and control to the test, environment, input data, result, owner, and artifact proving it. Generated test counts never replace semantic coverage.

14. Repository Review Boundary

- This chapter is a repository-review specification. Exact executable implementation has not been inspected for every target behavior.
- Registered modules, catalog entries, README claims, frontend contracts, or plans are not proof of complete implementation.

Area	Classification
target aggregate, API, tables, state and workflow in this chapter	REFERENCE_ARCHITECTURE
registered module or catalog claim	DOCUMENTATION_ONLY_CLAIM until source inspection
uninspected integration	REQUIRES_REPOSITORY_REVIEW
behavior proven in another repository-grounded chapter	retain that chapter's evidence and classification
contradictory ownership or path claims	CONFLICT_REQUIRES_CANONICALIZATION

No statement upgrades implementation status merely because a file, directory, module name, frontend contract, database entry, plan, or report exists.

15. Worked Conformance Scenario

An authorized principal initiates a Command against an exact subject version. The service validates identity, tenant, mandate, Policy, Evidence, and idempotency. It records the state transition and outbox entry atomically. If an external dependency participates, timeout produces Outcome Unknown; reconciliation queries the source or waits for a verified callback instead of repeating the action blindly.

Portals show source, freshness, version, required action, and uncertainty. AI may extract, compare, summarize, detect anomalies, and recommend through typed Tools, but cannot own the subject or fabricate success. Later correction appends new facts, identifies affected projections and workflows, and preserves the historical Decision context.

16. Conformance Checklist

- ☐ stable identity and proposition ownership are explicit;
- ☐ authority and mandate are evaluated at action time;
- ☐ state, Recommendation, Decision, Intent, execution, and outcome remain distinct;
- ☐ Commands are typed, authorized, idempotent, and version guarded;
- ☐ Events describe completed facts;
- ☐ Evidence includes provenance, time, integrity, qualification, and correction;
- ☐ external outcomes retain their authority source;
- ☐ Portals show freshness and uncertainty;
- ☐ AI is bounded by typed Tools, Policy, approval, and outcome observation;
- ☐ security, tenant, facility, channel, and jurisdiction boundaries are enforced;
- ☐ Outcome Unknown and reconciliation exist where needed;
- ☐ corrections preserve history;
- ☐ tests prove invariants and recovery;
- ☐ implementation status is not upgraded without executable evidence.

17. Status Vocabulary

Status	Meaning
VERIFIED_IMPLEMENTED	Executable source and relevant behavior were inspected.
IMPLEMENTED_WITH_GAP	Executable behavior exists with a material governance or completeness gap.
PARTIAL_IMPLEMENTATION	Only part of the target capability is evidenced.
REFERENCE_ARCHITECTURE	Normative target behavior; no claim that it exists today.
PLANNED_NOT_IMPLEMENTED	Explicitly planned but not evidenced as executable.
DOCUMENTATION_ONLY_CLAIM	Documentation or client contract claims behavior without verified backend evidence.
CONFLICT_REQUIRES_CANONICALIZATION	Sources disagree and no final owner has been established.
REQUIRES_REPOSITORY_REVIEW	Necessary executable evidence has not yet been inspected.

Customer Portal — Portal Orientation and Information Architecture

Metadata	Value
Volume	4
Chapter ID	V04-P05-00
Subject	CustomerPortalPortal
Status	Generated First-Draft Architecture Skeleton - Domain-Specific Expansion Required
Content maturity	TEMPLATE_DERIVED_REFERENCE_SKELETON unless repository citations prove otherwise
Default implementation classification	REFERENCE_ARCHITECTURE / REQUIRES_REPOSITORY_REVIEW
Accountable owner	Portal Architecture / Customer Portal
Evidence rule	No implementation claim without inspected executable evidence
Repository	chinair88-prog/allinb2c

1. Executive Orientation

This chapter defines how GTOS shall **define personas, navigation, route ownership, domain dependencies and experience boundaries for buyer organizations and users, covering identity, demand, RFQ, quotation, PI, payment, PO, production, quality, shipping, inventory, finance.**

The specification separates reality, observations, knowledge, Decisions, Intent, execution, and outcomes. A component name, database row, UI label, AI answer, or workflow state does not acquire authority merely because it is visible or technically convenient.

Reality or external outcome

- ≠ Observation
- ≠ Claim
- ≠ derived Perspective
- ≠ Prediction
- ≠ Recommendation
- ≠ authorized Decision
- ≠ execution Intent

1.1 Accountable ownership

The accountable owner is **Portal Architecture / Customer Portal**. Supporting applications, shared infrastructure, integration adapters, analytics, and AI coordinate or present the capability but shall not silently own its authoritative propositions.

1.2 Scope

- create and identify the subject
- validate evidence and policy
- make authorized Decisions
- execute typed Commands
- publish completed-fact Events
- query current and historical perspectives
- correct and reconcile outcomes

1.3 Non-goals

- treating a registered Gradle module, catalog record, README, frontend route, migration plan, or generated report as proof of end-to-end implementation;
- direct cross-Domain database writes;
- generic status values that combine lifecycle, approval, provider, document, payment, dispute, and correction state;
- silent replacement of history;
- AI-created authority or fabricated external outcomes.

2. Ubiquitous Language and Subject Model

Subject	Required interpretation
CustomerPortalPortal	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit
CustomerPortalPortalVersion	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit
CustomerPortalPortalDecision	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit
CustomerPortalPortalEvidenceSet	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit
CustomerPortalPortalException	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit

Reference aggregate:

```
CustomerPortalPortal {
  subjectId
  tenantId
  organizationContext
  sourceIdentityRefs[]
  sourceVersionRefs[]
  lifecycleState
  relationshipRefs[]
  decisionRefs[]
  intentRefs[]
  evidenceSetRef
  knowledgeCutoff
  policyRefs[]
  authorityRef
  jurisdictionRefs[]
  createdAt
  effectiveAt
  updatedAt
  version
  correctionOf?
  correlationId
}
```

2.1 Core invariants

- Stable identity precedes relationship, state, and cross-system correlation.
- Effective time and recorded time remain distinct where business truth changes over time.
- Recommendation, Decision, Intent, execution, and outcome are separate concepts.
- No Portal, report, search index, cache, workflow, or AI Agent becomes a shadow owner of Domain truth.
- Binding submitted, approved, issued, accepted, or signed versions are immutable.
- Corrections append governed facts and preserve the original record.
- External authority and provider outcomes retain their source and qualification.
- Tenant and represented-principal context come from trusted authentication and mandate evaluation.
- Retried writes are idempotent and concurrency guarded.
- Outcome Unknown is explicit and reconciled before risky duplicate execution.

2.2 Required standards

- stable identifiers
- typed contracts
- immutable binding versions

- transactional outbox
- idempotent Commands
- explicit Outcome Unknown
- correction lineage
- machine-verifiable conformance

3. Actors, Roles, and Authority

- A conformant design distinguishes:
- the natural person acting;
 - the service or AI identity invoking a Tool;
 - the organization or principal represented;
 - the role or relationship granting context;
 - the mandate or delegation granting action authority;
 - the Policy and jurisdiction limiting the action;
 - the reviewer or approver responsible for a binding Decision.

Authority is evaluated at action time. Authentication alone does not grant business authority. Cached permissions and browser-supplied tenant headers are insufficient for high-impact actions.

4. Lifecycle and State Model

State	Semantics
PROPOSED	Distinct governed condition with entry, exit, timeout, correction and authority semantics
VALIDATION_PENDING	Distinct governed condition with entry, exit, timeout, correction and authority semantics
APPROVAL_PENDING	Distinct governed condition with entry, exit, timeout, correction and authority semantics
ACTIVE	Distinct governed condition with entry, exit, timeout, correction and authority semantics
SUSPENDED	Distinct governed condition with entry, exit, timeout, correction and authority semantics
CORRECTION_PENDING	Distinct governed condition with entry, exit, timeout, correction and authority semantics
RETIRED	Distinct governed condition with entry, exit, timeout, correction and authority semantics

```
stateDiagram-v2
    [*] --> PROPOSED
    PROPOSED --> VALIDATION_PENDING
    VALIDATION_PENDING --> APPROVAL_PENDING
    APPROVAL_PENDING --> ACTIVE
    ACTIVE --> SUSPENDED
    SUSPENDED --> CORRECTION_PENDING
    CORRECTION_PENDING --> RETIRED
```

The diagram is a primary reading path. Real implementations may add parallel review, amendment, appeal, timeout, suspension, partial completion, reconciliation, correction, and terminal failure without collapsing their meaning.

4.1 Transition rules

- transition through a typed, authorized Command;
- require exact expected version where concurrent change matters;
- record actor, represented principal, mandate, Policy, reason, and Evidence;
- use an idempotency key for retried writes;
- publish a completed-fact Event after durable state change;
- expose Outcome Unknown for unresolved external completion;
- preserve original and corrected states in historical reconstruction.

5. Decision, Evidence, and Knowledge Cutoff

Reference Decision:

```
Decision {
  decisionId
  decisionType
  subjectRef
  sourceVersionRefs[]
  knowledgeCutoff
  evidenceSetRef
  policyVersionRefs[]
  recommendationRefs[]
  principalId
  representedOrganizationId
  mandateRef
  rationale
  outcome
  decidedAt
  effectiveAt
  correctionOf?
}
```

Evidence records identify issuer or observer, subject, version, observed time, received time, effective interval, integrity, confidence, qualification, contradiction, correction, retention, residency, and access class. A recommendation may assist the Decision but cannot promote itself to the Decision.

6. Commands, Events, Queries, and Contracts

Reference Commands:

- CreateCustomerPortalPortal
- ValidateCustomerPortalPortal
- ApproveCustomerPortalPortal
- ActivateCustomerPortalPortal
- SuspendCustomerPortalPortal
- CorrectCustomerPortalPortal
- RetireCustomerPortalPortal

Reference Events:

- CustomerPortalPortalCreated
- CustomerPortalPortalValidated
- CustomerPortalPortalApproved
- CustomerPortalPortalActivated
- CustomerPortalPortalSuspended
- CustomerPortalPortalCorrected
- CustomerPortalPortalRetired

Reference queries:

- GetCustomerPortalPortal
- ListCustomerPortalPortalRecords
- GetCustomerPortalPortalTimeline
- GetCustomerPortalPortalEvidence
- GetCustomerPortalPortalDecisionPackage
- GetCustomerPortalPortalExceptions
- GetCustomerPortalPortalAuditTrail

Reference API surface:

```
POST /api/v1/customerportalportal/commands
GET  /api/v1/customerportalportal/{id}
GET  /api/v1/customerportalportal/{id}/timeline
GET  /api/v1/customerportalportal/{id}/evidence
GET  /api/v1/customerportalportal/{id}/decisions
POST /api/v1/customerportalportal/{id}/exceptions
POST /api/v1/customerportalportal/{id}/corrections
```

These endpoints are reference contracts, not claims that exact routes exist.

7. Workflow, Failure, and Compensation

flowchart TD

```
A[Validate identity version and authority] --> B[Collect required evidence]
B --> C{Policy and evidence gates pass?}
C -- No --> D[Open exception or request correction]
D --> B
C -- Yes --> E[Record Decision or execution Intent]
E --> F[Execute Domain command or external request]
F --> G{Outcome known?}
G -- Success --> H[Record fact and publish Event]
G -- Failure --> I[Record failure and compensation options]
G -- Unknown --> J[Enter Outcome Unknown]
J --> K[Query source or wait for verified callback]
K --> G
H --> L[Update projections and downstream workflow]
```

Representative failure modes:

- stale or wrong source version
- duplicate submission or replay
- external timeout after possible success
- contradictory source observations
- lost Event after committed state
- approval or mandate revoked during execution
- downstream action before a mandatory gate
- partial completion across multiple subjects
- evidence later retracted or corrected
- tenant, facility, channel or jurisdiction mismatch

Recovery shall query the authoritative source before duplicate execution, preserve partial success, use compensating Intent rather than destructive rewrite, publish corrections, quarantine high-impact ambiguity, and record affected downstream subjects.

8. Data and Persistence Architecture

Reference table families:

Table family	Purpose
customerportalportal_aggregate	authoritative subject
customerportalportal_version	immutable submitted, approved, issued, or signed versions
customerportalportal_relationship	governed relationships
customerportalportal_decision	binding Decisions and rationale
customerportalportal_evidence_link	provenance and evidence relationships
customerportalportal_event_outbox	transactional Event publication
customerportalportal_idempotency	duplicate-write protection
customerportalportal_exception	exception, claim, dispute, or hold
customerportalportal_correction	correction and supersession lineage
customerportalportal_audit	privileged action evidence

The owning service controls schema and migration. Cross-Domain references use stable identifiers or contracts. Analytics, reports, caches, search, and vector indexes remain projections. Backup, restore, retention, legal hold, privacy, residency, and decommissioning requirements are explicit.

9. Portal and Experience Requirements

- Customer Portal: primary experience for buyer organizations and users.
- Operator and support views: diagnose failed or ambiguous journeys without assuming Domain ownership.
- Domain services: own authoritative data and action eligibility; the Portal consumes typed contracts.

Every Portal displays exact version, owner, state, freshness, required action, and uncertainty. It supports loading, empty, partial, stale, denied, error, timeout, and Outcome Unknown states; accessibility; locale, currency, unit, date, and RTL/LTR correctness; evidence audit; safe retry; and correction history.

10. AI Participation and Tool Governance

Permitted AI tasks:

- extract and classify evidence
- detect anomalies and missing fields
- summarize timelines and contradictions
- recommend next actions with sources and uncertainty

AI shall not own Domain records, grant itself authority, suppress contradictions, silently edit approved versions, fabricate external outcomes, or execute high-impact actions outside typed Tools, policy, approval, idempotency, sandbox, and outcome observation.

Every Agent Run records source context, prompt/model/tool versions, structured output, confidence and limitations, Policy result, approval, Tool calls, provider responses, final outcome, and recovery actions.

11. Security, Privacy, and Trust Boundaries

- least privilege and separation of duties
- tenant, organization, facility, channel and jurisdiction isolation
- integrity protection for binding evidence
- verified external callbacks and anti-replay controls

Additional controls include secret isolation, callback signature verification, audit of privileged action, emergency-access review, sensitive-data minimization, purpose limitation, and threat models for impersonation, tampering, replay, confused deputy, fraud, prompt injection, and exfiltration.

12. Reliability, SLOs, and Operations

SLI	Reference objective
authoritative read availability	99.9% monthly unless a stricter tier applies
acknowledged Command durability	no acknowledged write may be silently lost
Event publication	99.9% within five minutes after committed fact
duplicate prevention	100% for same tenant, Command class, and idempotency key
binding Decision audit completeness	100%
state-state detection	bounded by business deadline

Dashboards and runbooks cover backlog, error budget, dependency failure, retry budget, DLQ, workflow stall, provider outage, reconciliation, capacity, backup/restore, release/rollback, incident command, and post-incident correction.

13. Testing and Continuous Conformance

- aggregate invariant and transition tests
- authorization, delegation, separation-of-duties and tenant-isolation tests
- idempotency and optimistic-concurrency tests
- database migration, key, constraint and rollback tests
- contract, outbox/inbox, duplicate, replay and DLQ tests
- workflow restart, timeout and compensation tests
- Portal E2E tests for success, partial, stale, denied, error and Outcome Unknown states
- accessibility, locale, currency, unit and RTL/LTR tests
- security adversarial, fraud and data-exfiltration tests
- AI evaluation, prompt-injection, policy-bypass and unauthorized-tool tests
- historical reconstruction, correction and audit-completeness tests
- performance, capacity, recovery and operational exercise tests

Release evidence links each invariant and control to the test, environment, input data, result, owner, and artifact proving it. Generated test counts never replace semantic coverage.

14. Repository Review Boundary

- This chapter is a repository-review specification. Exact executable implementation has not been inspected for every target behavior.
- Registered modules, catalog entries, README claims, frontend contracts, or plans are not proof of complete implementation.

Area	Classification
target aggregate, API, tables, state and workflow in this chapter	REFERENCE_ARCHITECTURE
registered module or catalog claim	DOCUMENTATION_ONLY_CLAIM until source inspection
uninspected integration	REQUIRES_REPOSITORY_REVIEW
behavior proven in another repository-grounded chapter	retain that chapter's evidence and classification
contradictory ownership or path claims	CONFLICT_REQUIRES_CANONICALIZATION

No statement upgrades implementation status merely because a file, directory, module name, frontend contract, database entry, plan, or report exists.

15. Worked Conformance Scenario

An authorized principal initiates a Command against an exact subject version. The service validates identity, tenant, mandate, Policy, Evidence, and idempotency. It records the state transition and outbox entry atomically. If an external dependency participates, timeout produces Outcome Unknown; reconciliation queries the source or waits for a verified callback instead of repeating the action blindly.

Portals show source, freshness, version, required action, and uncertainty. AI may extract, compare, summarize, detect anomalies, and recommend through typed Tools, but cannot own the subject or fabricate success. Later correction appends new facts, identifies affected projections and workflows, and preserves the historical Decision context.

16. Conformance Checklist

- ☐ stable identity and proposition ownership are explicit;
- ☐ authority and mandate are evaluated at action time;
- ☐ state, Recommendation, Decision, Intent, execution, and outcome remain distinct;
- ☐ Commands are typed, authorized, idempotent, and version guarded;
- ☐ Events describe completed facts;
- ☐ Evidence includes provenance, time, integrity, qualification, and correction;
- ☐ external outcomes retain their authority source;
- ☐ Portals show freshness and uncertainty;
- ☐ AI is bounded by typed Tools, Policy, approval, and outcome observation;
- ☐ security, tenant, facility, channel, and jurisdiction boundaries are enforced;
- ☐ Outcome Unknown and reconciliation exist where needed;
- ☐ corrections preserve history;
- ☐ tests prove invariants and recovery;
- ☐ implementation status is not upgraded without executable evidence.

17. Status Vocabulary

Status	Meaning
VERIFIED_IMPLEMENTED	Executable source and relevant behavior were inspected.
IMPLEMENTED_WITH_GAP	Executable behavior exists with a material governance or completeness gap.
PARTIAL_IMPLEMENTATION	Only part of the target capability is evidenced.
REFERENCE_ARCHITECTURE	Normative target behavior; no claim that it exists today.
PLANNED_NOT_IMPLEMENTED	Explicitly planned but not evidenced as executable.
DOCUMENTATION_ONLY_CLAIM	Documentation or client contract claims behavior without verified backend evidence.
CONFLICT_REQUIRES_CANONICALIZATION	Sources disagree and no final owner has been established.
REQUIRES_REPOSITORY_REVIEW	Necessary executable evidence has not yet been inspected.

Customer Portal — Routes, Pages, Components, and BFF Contracts

Metadata	Value
Volume	4
Chapter ID	V04-P05-01
Subject	CustomerPortalRouteRegistry
Status	Generated First-Draft Architecture Skeleton - Domain-Specific Expansion Required
Content maturity	TEMPLATE_DERIVED_REFERENCE_SKELETON unless repository citations prove otherwise
Default implementation classification	REFERENCE_ARCHITECTURE / REQUIRES_REPOSITORY_REVIEW
Accountable owner	Portal Architecture / Customer Portal
Evidence rule	No implementation claim without inspected executable evidence
Repository	chinair88-prog/allinb2c

1. Executive Orientation

This chapter defines how GTOS shall **inventory routes, layouts, pages, components, server/client boundaries, BFFs, APIs, realtime channels and ownership for buyer organizations and users, covering identity, demand, RFQ, quotation, PI, payment, PO, production, quality, shipping, inventory, finance.**

The specification separates reality, observations, knowledge, Decisions, Intent, execution, and outcomes. A component name, database row, UI label, AI answer, or workflow state does not acquire authority merely because it is visible or technically convenient.

Reality or external outcome

- ≠ Observation
- ≠ Claim
- ≠ derived Perspective
- ≠ Prediction
- ≠ Recommendation
- ≠ authorized Decision
- ≠ execution Intent

1.1 Accountable ownership

The accountable owner is **Portal Architecture / Customer Portal**. Supporting applications, shared infrastructure, integration adapters, analytics, and AI coordinate or present the capability but shall not silently own its authoritative propositions.

1.2 Scope

- create and identify the subject
- validate evidence and policy
- make authorized Decisions
- execute typed Commands
- publish completed-fact Events
- query current and historical perspectives
- correct and reconcile outcomes

1.3 Non-goals

- treating a registered Gradle module, catalog record, README, frontend route, migration plan, or generated report as proof of end-to-end implementation;
- direct cross-Domain database writes;
- generic status values that combine lifecycle, approval, provider, document, payment, dispute, and correction state;
- silent replacement of history;
- AI-created authority or fabricated external outcomes.

2. Ubiquitous Language and Subject Model

Subject	Required interpretation
CustomerPortalRouteRegistry	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit
CustomerPortalRouteRegistryVersion	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit
CustomerPortalRouteRegistryDecision	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit
CustomerPortalRouteRegistryEvidenceSet	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit
CustomerPortalRouteRegistryException	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit

Reference aggregate:

```
CustomerPortalRouteRegistry {
  subjectId
  tenantId
  organizationContext
  sourceIdentityRefs[]
  sourceVersionRefs[]
  lifecycleState
  relationshipRefs[]
  decisionRefs[]
  intentRefs[]
  evidenceSetRef
  knowledgeCutoff
  policyRefs[]
  authorityRef
  jurisdictionRefs[]
  createdAt
  effectiveAt
  updatedAt
  version
  correctionOf?
  correlationId
}
```

2.1 Core invariants

- Stable identity precedes relationship, state, and cross-system correlation.
- Effective time and recorded time remain distinct where business truth changes over time.
- Recommendation, Decision, Intent, execution, and outcome are separate concepts.
- No Portal, report, search index, cache, workflow, or AI Agent becomes a shadow owner of Domain truth.
- Binding submitted, approved, issued, accepted, or signed versions are immutable.
- Corrections append governed facts and preserve the original record.
- External authority and provider outcomes retain their source and qualification.
- Tenant and represented-principal context come from trusted authentication and mandate evaluation.
- Retried writes are idempotent and concurrency guarded.
- Outcome Unknown is explicit and reconciled before risky duplicate execution.

2.2 Required standards

- stable identifiers
- typed contracts
- immutable binding versions

- transactional outbox
- idempotent Commands
- explicit Outcome Unknown
- correction lineage
- machine-verifiable conformance

3. Actors, Roles, and Authority

- A conformant design distinguishes:
- the natural person acting;
 - the service or AI identity invoking a Tool;
 - the organization or principal represented;
 - the role or relationship granting context;
 - the mandate or delegation granting action authority;
 - the Policy and jurisdiction limiting the action;
 - the reviewer or approver responsible for a binding Decision.

Authority is evaluated at action time. Authentication alone does not grant business authority. Cached permissions and browser-supplied tenant headers are insufficient for high-impact actions.

4. Lifecycle and State Model

State	Semantics
PROPOSED	Distinct governed condition with entry, exit, timeout, correction and authority semantics
VALIDATION_PENDING	Distinct governed condition with entry, exit, timeout, correction and authority semantics
APPROVAL_PENDING	Distinct governed condition with entry, exit, timeout, correction and authority semantics
ACTIVE	Distinct governed condition with entry, exit, timeout, correction and authority semantics
SUSPENDED	Distinct governed condition with entry, exit, timeout, correction and authority semantics
CORRECTION_PENDING	Distinct governed condition with entry, exit, timeout, correction and authority semantics
RETIRED	Distinct governed condition with entry, exit, timeout, correction and authority semantics

```
stateDiagram-v2
    [*] --> PROPOSED
    PROPOSED --> VALIDATION_PENDING
    VALIDATION_PENDING --> APPROVAL_PENDING
    APPROVAL_PENDING --> ACTIVE
    ACTIVE --> SUSPENDED
    SUSPENDED --> CORRECTION_PENDING
    CORRECTION_PENDING --> RETIRED
```

The diagram is a primary reading path. Real implementations may add parallel review, amendment, appeal, timeout, suspension, partial completion, reconciliation, correction, and terminal failure without collapsing their meaning.

4.1 Transition rules

- transition through a typed, authorized Command;
- require exact expected version where concurrent change matters;
- record actor, represented principal, mandate, Policy, reason, and Evidence;
- use an idempotency key for retried writes;
- publish a completed-fact Event after durable state change;
- expose Outcome Unknown for unresolved external completion;
- preserve original and corrected states in historical reconstruction.

5. Decision, Evidence, and Knowledge Cutoff

Reference Decision:

```
Decision {
  decisionId
  decisionType
  subjectRef
  sourceVersionRefs[]
  knowledgeCutoff
  evidenceSetRef
  policyVersionRefs[]
  recommendationRefs[]
  principalId
  representedOrganizationId
  mandateRef
  rationale
  outcome
  decidedAt
  effectiveAt
  correctionOf?
}
```

Evidence records identify issuer or observer, subject, version, observed time, received time, effective interval, integrity, confidence, qualification, contradiction, correction, retention, residency, and access class. A recommendation may assist the Decision but cannot promote itself to the Decision.

6. Commands, Events, Queries, and Contracts

Reference Commands:

- CreateCustomerPortalRouteRegistry
- ValidateCustomerPortalRouteRegistry
- ApproveCustomerPortalRouteRegistry
- ActivateCustomerPortalRouteRegistry
- SuspendCustomerPortalRouteRegistry
- CorrectCustomerPortalRouteRegistry
- RetireCustomerPortalRouteRegistry

Reference Events:

- CustomerPortalRouteRegistryCreated
- CustomerPortalRouteRegistryValidated
- CustomerPortalRouteRegistryApproved
- CustomerPortalRouteRegistryActivated
- CustomerPortalRouteRegistrySuspended
- CustomerPortalRouteRegistryCorrected
- CustomerPortalRouteRegistryRetired

Reference queries:

- GetCustomerPortalRouteRegistry
- ListCustomerPortalRouteRegistryRecords
- GetCustomerPortalRouteRegistryTimeline
- GetCustomerPortalRouteRegistryEvidence
- GetCustomerPortalRouteRegistryDecisionPackage
- GetCustomerPortalRouteRegistryExceptions
- GetCustomerPortalRouteRegistryAuditTrail

Reference API surface:

```
POST /api/v1/customerportalrouteregistry/commands
GET  /api/v1/customerportalrouteregistry/{id}
GET  /api/v1/customerportalrouteregistry/{id}/timeline
GET  /api/v1/customerportalrouteregistry/{id}/evidence
GET  /api/v1/customerportalrouteregistry/{id}/decisions
POST /api/v1/customerportalrouteregistry/{id}/exceptions
POST /api/v1/customerportalrouteregistry/{id}/corrections
```

These endpoints are reference contracts, not claims that exact routes exist.

7. Workflow, Failure, and Compensation

flowchart TD

```
A[Validate identity version and authority] --> B[Collect required evidence]
B --> C{Policy and evidence gates pass?}
C -- No --> D[Open exception or request correction]
D --> B
C -- Yes --> E[Record Decision or execution Intent]
E --> F[Execute Domain command or external request]
F --> G{Outcome known?}
G -- Success --> H[Record fact and publish Event]
G -- Failure --> I[Record failure and compensation options]
G -- Unknown --> J[Enter Outcome Unknown]
J --> K[Query source or wait for verified callback]
K --> G
H --> L[Update projections and downstream workflow]
```

Representative failure modes:

- stale or wrong source version
- duplicate submission or replay
- external timeout after possible success
- contradictory source observations
- lost Event after committed state
- approval or mandate revoked during execution
- downstream action before a mandatory gate
- partial completion across multiple subjects
- evidence later retracted or corrected
- tenant, facility, channel or jurisdiction mismatch

Recovery shall query the authoritative source before duplicate execution, preserve partial success, use compensating Intent rather than destructive rewrite, publish corrections, quarantine high-impact ambiguity, and record affected downstream subjects.

8. Data and Persistence Architecture

Reference table families:

Table family	Purpose
customerportalrouterregistry_aggregate	authoritative subject
customerportalrouterregistry_version	immutable submitted, approved, issued, or signed versions
customerportalrouterregistry_relationship	governed relationships
customerportalrouterregistry_decision	binding Decisions and rationale
customerportalrouterregistry_evidence_link	provenance and evidence relationships
customerportalrouterregistry_event_outbox	transactional Event publication
customerportalrouterregistry_idempotency	duplicate-write protection
customerportalrouterregistry_exception	exception, claim, dispute, or hold
customerportalrouterregistry_correction	correction and supersession lineage
customerportalrouterregistry_audit	privileged action evidence

The owning service controls schema and migration. Cross-Domain references use stable identifiers or contracts. Analytics, reports, caches, search, and vector indexes remain projections. Backup, restore, retention, legal hold, privacy, residency, and decommissioning requirements are explicit.

9. Portal and Experience Requirements

- Customer Portal: primary experience for buyer organizations and users.
- Operator and support views: diagnose failed or ambiguous journeys without assuming Domain ownership.
- Domain services: own authoritative data and action eligibility; the Portal consumes typed contracts.

Every Portal displays exact version, owner, state, freshness, required action, and uncertainty. It supports loading, empty, partial, stale, denied, error, timeout, and Outcome Unknown states; accessibility; locale, currency, unit, date, and RTL/LTR correctness; evidence audit; safe retry; and correction history.

10. AI Participation and Tool Governance

Permitted AI tasks:

- extract and classify evidence
- detect anomalies and missing fields
- summarize timelines and contradictions
- recommend next actions with sources and uncertainty

AI shall not own Domain records, grant itself authority, suppress contradictions, silently edit approved versions, fabricate external outcomes, or execute high-impact actions outside typed Tools, policy, approval, idempotency, sandbox, and outcome observation.

Every Agent Run records source context, prompt/model/tool versions, structured output, confidence and limitations, Policy result, approval, Tool calls, provider responses, final outcome, and recovery actions.

11. Security, Privacy, and Trust Boundaries

- least privilege and separation of duties
- tenant, organization, facility, channel and jurisdiction isolation
- integrity protection for binding evidence
- verified external callbacks and anti-replay controls

Additional controls include secret isolation, callback signature verification, audit of privileged action, emergency-access review, sensitive-data minimization, purpose limitation, and threat models for impersonation, tampering, replay, confused deputy, fraud, prompt injection, and exfiltration.

12. Reliability, SLOs, and Operations

SLI	Reference objective
authoritative read availability	99.9% monthly unless a stricter tier applies
acknowledged Command durability	no acknowledged write may be silently lost
Event publication	99.9% within five minutes after committed fact
duplicate prevention	100% for same tenant, Command class, and idempotency key
binding Decision audit completeness	100%
state-state detection	bounded by business deadline

Dashboards and runbooks cover backlog, error budget, dependency failure, retry budget, DLQ, workflow stall, provider outage, reconciliation, capacity, backup/restore, release/rollback, incident command, and post-incident correction.

13. Testing and Continuous Conformance

- aggregate invariant and transition tests
- authorization, delegation, separation-of-duties and tenant-isolation tests
- idempotency and optimistic-concurrency tests
- database migration, key, constraint and rollback tests
- contract, outbox/inbox, duplicate, replay and DLQ tests
- workflow restart, timeout and compensation tests
- Portal E2E tests for success, partial, stale, denied, error and Outcome Unknown states
- accessibility, locale, currency, unit and RTL/LTR tests
- security adversarial, fraud and data-exfiltration tests
- AI evaluation, prompt-injection, policy-bypass and unauthorized-tool tests
- historical reconstruction, correction and audit-completeness tests
- performance, capacity, recovery and operational exercise tests

Release evidence links each invariant and control to the test, environment, input data, result, owner, and artifact proving it. Generated test counts never replace semantic coverage.

14. Repository Review Boundary

- This chapter is a repository-review specification. Exact executable implementation has not been inspected for every target behavior.
- Registered modules, catalog entries, README claims, frontend contracts, or plans are not proof of complete implementation.

Area	Classification
target aggregate, API, tables, state and workflow in this chapter	REFERENCE_ARCHITECTURE
registered module or catalog claim	DOCUMENTATION_ONLY_CLAIM until source inspection
uninspected integration	REQUIRES_REPOSITORY_REVIEW
behavior proven in another repository-grounded chapter	retain that chapter's evidence and classification
contradictory ownership or path claims	CONFLICT_REQUIRES_CANONICALIZATION

No statement upgrades implementation status merely because a file, directory, module name, frontend contract, database entry, plan, or report exists.

15. Worked Conformance Scenario

An authorized principal initiates a Command against an exact subject version. The service validates identity, tenant, mandate, Policy, Evidence, and idempotency. It records the state transition and outbox entry atomically. If an external dependency participates, timeout produces Outcome Unknown; reconciliation queries the source or waits for a verified callback instead of repeating the action blindly.

Portals show source, freshness, version, required action, and uncertainty. AI may extract, compare, summarize, detect anomalies, and recommend through typed Tools, but cannot own the subject or fabricate success. Later correction appends new facts, identifies affected projections and workflows, and preserves the historical Decision context.

16. Conformance Checklist

- ☐ stable identity and proposition ownership are explicit;
- ☐ authority and mandate are evaluated at action time;
- ☐ state, Recommendation, Decision, Intent, execution, and outcome remain distinct;
- ☐ Commands are typed, authorized, idempotent, and version guarded;
- ☐ Events describe completed facts;
- ☐ Evidence includes provenance, time, integrity, qualification, and correction;
- ☐ external outcomes retain their authority source;
- ☐ Portals show freshness and uncertainty;
- ☐ AI is bounded by typed Tools, Policy, approval, and outcome observation;
- ☐ security, tenant, facility, channel, and jurisdiction boundaries are enforced;
- ☐ Outcome Unknown and reconciliation exist where needed;
- ☐ corrections preserve history;
- ☐ tests prove invariants and recovery;
- ☐ implementation status is not upgraded without executable evidence.

17. Status Vocabulary

Status	Meaning
VERIFIED_IMPLEMENTED	Executable source and relevant behavior were inspected. Executable behavior exists with a material governance or completeness gap.
IMPLEMENTED_WITH_GAP	
PARTIAL_IMPLEMENTATION	Only part of the target capability is evidenced.
REFERENCE_ARCHITECTURE	Normative target behavior; no claim that it exists today.
PLANNED_NOT_IMPLEMENTED	Explicitly planned but not evidenced as executable.
DOCUMENTATION_ONLY_CLAIM	Documentation or client contract claims behavior without verified backend evidence.
CONFLICT_REQUIRES_CANONICALIZATION	Sources disagree and no final owner has been established.
REQUIRES_REPOSITORY_REVIEW	Necessary executable evidence has not yet been inspected.

Customer Portal — Identity, Session, Authorization, and Trust Boundaries

Metadata	Value
Volume	4
Chapter ID	V04-P05-02
Subject	CustomerPortalAccessModel
Status	Generated First-Draft Architecture Skeleton - Domain-Specific Expansion Required
Content maturity	TEMPLATE_DERIVED_REFERENCE_SKELETON unless repository citations prove otherwise
Default implementation classification	REFERENCE_ARCHITECTURE / REQUIRES_REPOSITORY_REVIEW
Accountable owner	Portal Architecture / Customer Portal
Evidence rule	No implementation claim without inspected executable evidence
Repository	chinair88-prog/allinb2c

1. Executive Orientation

This chapter defines how GTOS shall **govern login, session, role, relationship, tenant, facility, channel, delegation, impersonation and privileged action for buyer organizations and users, covering identity, demand, RFQ, quotation, PI, payment, PO, production, quality, shipping, inventory, finance.**

The specification separates reality, observations, knowledge, Decisions, Intent, execution, and outcomes. A component name, database row, UI label, AI answer, or workflow state does not acquire authority merely because it is visible or technically convenient.

Reality or external outcome
≠ Observation
≠ Claim
≠ derived Perspective
≠ Prediction
≠ Recommendation
≠ authorized Decision
≠ execution Intent

1.1 Accountable ownership

The accountable owner is **Portal Architecture / Customer Portal**. Supporting applications, shared infrastructure, integration adapters, analytics, and AI coordinate or present the capability but shall not silently own its authoritative propositions.

1.2 Scope

- create and identify the subject
- validate evidence and policy
- make authorized Decisions
- execute typed Commands
- publish completed-fact Events
- query current and historical perspectives
- correct and reconcile outcomes

1.3 Non-goals

- treating a registered Gradle module, catalog record, README, frontend route, migration plan, or generated report as proof of end-to-end implementation;
- direct cross-Domain database writes;
- generic status values that combine lifecycle, approval, provider, document, payment, dispute, and correction state;
- silent replacement of history;
- AI-created authority or fabricated external outcomes.

2. Ubiquitous Language and Subject Model

Subject	Required interpretation
CustomerPortalAccessModel	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit
CustomerPortalAccessModelVersion	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit
CustomerPortalAccessModelDecision	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit
CustomerPortalAccessModelEvidenceSet	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit
CustomerPortalAccessModelException	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit

Reference aggregate:

```
CustomerPortalAccessModel {  
  subjectId  
  tenantId  
  organizationContext  
  sourceIdentityRefs[]  
  sourceVersionRefs[]  
  lifecycleState  
  relationshipRefs[]  
  decisionRefs[]  
  intentRefs[]  
  evidenceSetRef  
  knowledgeCutoff  
  policyRefs[]  
  authorityRef  
  jurisdictionRefs[]  
  createdAt  
  effectiveAt  
  updatedAt  
  version  
  correctionOf?  
  correlationId  
}
```

2.1 Core invariants

- Stable identity precedes relationship, state, and cross-system correlation.
- Effective time and recorded time remain distinct where business truth changes over time.
- Recommendation, Decision, Intent, execution, and outcome are separate concepts.
- No Portal, report, search index, cache, workflow, or AI Agent becomes a shadow owner of Domain truth.
- Binding submitted, approved, issued, accepted, or signed versions are immutable.
- Corrections append governed facts and preserve the original record.
- External authority and provider outcomes retain their source and qualification.
- Tenant and represented-principal context come from trusted authentication and mandate evaluation.
- Retried writes are idempotent and concurrency guarded.
- Outcome Unknown is explicit and reconciled before risky duplicate execution.

2.2 Required standards

- stable identifiers
- typed contracts
- immutable binding versions

- transactional outbox
- idempotent Commands
- explicit Outcome Unknown
- correction lineage
- machine-verifiable conformance

3. Actors, Roles, and Authority

- A conformant design distinguishes:
- the natural person acting;
 - the service or AI identity invoking a Tool;
 - the organization or principal represented;
 - the role or relationship granting context;
 - the mandate or delegation granting action authority;
 - the Policy and jurisdiction limiting the action;
 - the reviewer or approver responsible for a binding Decision.

Authority is evaluated at action time. Authentication alone does not grant business authority. Cached permissions and browser-supplied tenant headers are insufficient for high-impact actions.

4. Lifecycle and State Model

State	Semantics
PROPOSED	Distinct governed condition with entry, exit, timeout, correction and authority semantics
VALIDATION_PENDING	Distinct governed condition with entry, exit, timeout, correction and authority semantics
APPROVAL_PENDING	Distinct governed condition with entry, exit, timeout, correction and authority semantics
ACTIVE	Distinct governed condition with entry, exit, timeout, correction and authority semantics
SUSPENDED	Distinct governed condition with entry, exit, timeout, correction and authority semantics
CORRECTION_PENDING	Distinct governed condition with entry, exit, timeout, correction and authority semantics
RETIRED	Distinct governed condition with entry, exit, timeout, correction and authority semantics

```
stateDiagram-v2
    [*] --> PROPOSED
    PROPOSED --> VALIDATION_PENDING
    VALIDATION_PENDING --> APPROVAL_PENDING
    APPROVAL_PENDING --> ACTIVE
    ACTIVE --> SUSPENDED
    SUSPENDED --> CORRECTION_PENDING
    CORRECTION_PENDING --> RETIRED
```

The diagram is a primary reading path. Real implementations may add parallel review, amendment, appeal, timeout, suspension, partial completion, reconciliation, correction, and terminal failure without collapsing their meaning.

4.1 Transition rules

- transition through a typed, authorized Command;
- require exact expected version where concurrent change matters;
- record actor, represented principal, mandate, Policy, reason, and Evidence;
- use an idempotency key for retried writes;
- publish a completed-fact Event after durable state change;
- expose Outcome Unknown for unresolved external completion;
- preserve original and corrected states in historical reconstruction.

5. Decision, Evidence, and Knowledge Cutoff

Reference Decision:

```
Decision {
  decisionId
  decisionType
  subjectRef
  sourceVersionRefs[]
  knowledgeCutoff
  evidenceSetRef
  policyVersionRefs[]
  recommendationRefs[]
  principalId
  representedOrganizationId
  mandateRef
  rationale
  outcome
  decidedAt
  effectiveAt
  correctionOf?
}
```

Evidence records identify issuer or observer, subject, version, observed time, received time, effective interval, integrity, confidence, qualification, contradiction, correction, retention, residency, and access class. A recommendation may assist the Decision but cannot promote itself to the Decision.

6. Commands, Events, Queries, and Contracts

Reference Commands:

- CreateCustomerPortalAccessModel
- ValidateCustomerPortalAccessModel
- ApproveCustomerPortalAccessModel
- ActivateCustomerPortalAccessModel
- SuspendCustomerPortalAccessModel
- CorrectCustomerPortalAccessModel
- RetireCustomerPortalAccessModel

Reference Events:

- CustomerPortalAccessModelCreated
- CustomerPortalAccessModelValidated
- CustomerPortalAccessModelApproved
- CustomerPortalAccessModelActivated
- CustomerPortalAccessModelSuspended
- CustomerPortalAccessModelCorrected
- CustomerPortalAccessModelRetired

Reference queries:

- GetCustomerPortalAccessModel
- ListCustomerPortalAccessModelRecords
- GetCustomerPortalAccessModelTimeline
- GetCustomerPortalAccessModelEvidence
- GetCustomerPortalAccessModelDecisionPackage
- GetCustomerPortalAccessModelExceptions
- GetCustomerPortalAccessModelAuditTrail

Reference API surface:

```
POST /api/v1/customerportalaccessmodel/commands
GET  /api/v1/customerportalaccessmodel/{id}
GET  /api/v1/customerportalaccessmodel/{id}/timeline
GET  /api/v1/customerportalaccessmodel/{id}/evidence
GET  /api/v1/customerportalaccessmodel/{id}/decisions
POST /api/v1/customerportalaccessmodel/{id}/exceptions
POST /api/v1/customerportalaccessmodel/{id}/corrections
```

These endpoints are reference contracts, not claims that exact routes exist.

7. Workflow, Failure, and Compensation

flowchart TD

```
A[Validate identity version and authority] --> B[Collect required evidence]
B --> C{Policy and evidence gates pass?}
C -- No --> D[Open exception or request correction]
D --> B
C -- Yes --> E[Record Decision or execution Intent]
E --> F[Execute Domain command or external request]
F --> G{Outcome known?}
G -- Success --> H[Record fact and publish Event]
G -- Failure --> I[Record failure and compensation options]
G -- Unknown --> J[Enter Outcome Unknown]
J --> K[Query source or wait for verified callback]
K --> G
H --> L[Update projections and downstream workflow]
```

Representative failure modes:

- stale or wrong source version
- duplicate submission or replay
- external timeout after possible success
- contradictory source observations
- lost Event after committed state
- approval or mandate revoked during execution
- downstream action before a mandatory gate
- partial completion across multiple subjects
- evidence later retracted or corrected
- tenant, facility, channel or jurisdiction mismatch

Recovery shall query the authoritative source before duplicate execution, preserve partial success, use compensating Intent rather than destructive rewrite, publish corrections, quarantine high-impact ambiguity, and record affected downstream subjects.

8. Data and Persistence Architecture

Reference table families:

Table family	Purpose
customerportalaccessmodel_aggregate	authoritative subject
customerportalaccessmodel_version	immutable submitted, approved, issued, or signed versions
customerportalaccessmodel_relationship	governed relationships
customerportalaccessmodel_decision	binding Decisions and rationale
customerportalaccessmodel_evidence_link	provenance and evidence relationships
customerportalaccessmodel_event_outbox	transactional Event publication
customerportalaccessmodel_idempotency	duplicate-write protection
customerportalaccessmodel_exception	exception, claim, dispute, or hold
customerportalaccessmodel_correction	correction and supersession lineage
customerportalaccessmodel_audit	privileged action evidence

The owning service controls schema and migration. Cross-Domain references use stable identifiers or contracts. Analytics, reports, caches, search, and vector indexes remain projections. Backup, restore, retention, legal hold, privacy, residency, and decommissioning requirements are explicit.

9. Portal and Experience Requirements

- Customer Portal: primary experience for buyer organizations and users.
- Operator and support views: diagnose failed or ambiguous journeys without assuming Domain ownership.
- Domain services: own authoritative data and action eligibility; the Portal consumes typed contracts.

Every Portal displays exact version, owner, state, freshness, required action, and uncertainty. It supports loading, empty, partial, stale, denied, error, timeout, and Outcome Unknown states; accessibility; locale, currency, unit, date, and RTL/LTR correctness; evidence audit; safe retry; and correction history.

10. AI Participation and Tool Governance

Permitted AI tasks:

- extract and classify evidence
- detect anomalies and missing fields
- summarize timelines and contradictions
- recommend next actions with sources and uncertainty

AI shall not own Domain records, grant itself authority, suppress contradictions, silently edit approved versions, fabricate external outcomes, or execute high-impact actions outside typed Tools, policy, approval, idempotency, sandbox, and outcome observation.

Every Agent Run records source context, prompt/model/tool versions, structured output, confidence and limitations, Policy result, approval, Tool calls, provider responses, final outcome, and recovery actions.

11. Security, Privacy, and Trust Boundaries

- least privilege and separation of duties
- tenant, organization, facility, channel and jurisdiction isolation
- integrity protection for binding evidence
- verified external callbacks and anti-replay controls

Additional controls include secret isolation, callback signature verification, audit of privileged action, emergency-access review, sensitive-data minimization, purpose limitation, and threat models for impersonation, tampering, replay, confused deputy, fraud, prompt injection, and exfiltration.

12. Reliability, SLOs, and Operations

SLI	Reference objective
authoritative read availability	99.9% monthly unless a stricter tier applies
acknowledged Command durability	no acknowledged write may be silently lost
Event publication	99.9% within five minutes after committed fact
duplicate prevention	100% for same tenant, Command class, and idempotency key
binding Decision audit completeness	100%
state-state detection	bounded by business deadline

Dashboards and runbooks cover backlog, error budget, dependency failure, retry budget, DLQ, workflow stall, provider outage, reconciliation, capacity, backup/restore, release/rollback, incident command, and post-incident correction.

13. Testing and Continuous Conformance

- aggregate invariant and transition tests
- authorization, delegation, separation-of-duties and tenant-isolation tests
- idempotency and optimistic-concurrency tests
- database migration, key, constraint and rollback tests
- contract, outbox/inbox, duplicate, replay and DLQ tests
- workflow restart, timeout and compensation tests
- Portal E2E tests for success, partial, stale, denied, error and Outcome Unknown states
- accessibility, locale, currency, unit and RTL/LTR tests
- security adversarial, fraud and data-exfiltration tests
- AI evaluation, prompt-injection, policy-bypass and unauthorized-tool tests
- historical reconstruction, correction and audit-completeness tests
- performance, capacity, recovery and operational exercise tests

Release evidence links each invariant and control to the test, environment, input data, result, owner, and artifact proving it. Generated test counts never replace semantic coverage.

14. Repository Review Boundary

- This chapter is a repository-review specification. Exact executable implementation has not been inspected for every target behavior.
- Registered modules, catalog entries, README claims, frontend contracts, or plans are not proof of complete implementation.

Area	Classification
target aggregate, API, tables, state and workflow in this chapter	REFERENCE_ARCHITECTURE
registered module or catalog claim	DOCUMENTATION_ONLY_CLAIM until source inspection
uninspected integration	REQUIRES_REPOSITORY_REVIEW
behavior proven in another repository-grounded chapter	retain that chapter's evidence and classification
contradictory ownership or path claims	CONFLICT_REQUIRES_CANONICALIZATION

No statement upgrades implementation status merely because a file, directory, module name, frontend contract, database entry, plan, or report exists.

15. Worked Conformance Scenario

An authorized principal initiates a Command against an exact subject version. The service validates identity, tenant, mandate, Policy, Evidence, and idempotency. It records the state transition and outbox entry atomically. If an external dependency participates, timeout produces Outcome Unknown; reconciliation queries the source or waits for a verified callback instead of repeating the action blindly.

Portals show source, freshness, version, required action, and uncertainty. AI may extract, compare, summarize, detect anomalies, and recommend through typed Tools, but cannot own the subject or fabricate success. Later correction appends new facts, identifies affected projections and workflows, and preserves the historical Decision context.

16. Conformance Checklist

- ☐ stable identity and proposition ownership are explicit;
- ☐ authority and mandate are evaluated at action time;
- ☐ state, Recommendation, Decision, Intent, execution, and outcome remain distinct;
- ☐ Commands are typed, authorized, idempotent, and version guarded;
- ☐ Events describe completed facts;
- ☐ Evidence includes provenance, time, integrity, qualification, and correction;
- ☐ external outcomes retain their authority source;
- ☐ Portals show freshness and uncertainty;
- ☐ AI is bounded by typed Tools, Policy, approval, and outcome observation;
- ☐ security, tenant, facility, channel, and jurisdiction boundaries are enforced;
- ☐ Outcome Unknown and reconciliation exist where needed;
- ☐ corrections preserve history;
- ☐ tests prove invariants and recovery;
- ☐ implementation status is not upgraded without executable evidence.

17. Status Vocabulary

Status	Meaning
VERIFIED_IMPLEMENTED	Executable source and relevant behavior were inspected. Executable behavior exists with a material governance or completeness gap.
IMPLEMENTED_WITH_GAP	
PARTIAL_IMPLEMENTATION	Only part of the target capability is evidenced.
REFERENCE_ARCHITECTURE	Normative target behavior; no claim that it exists today.
PLANNED_NOT_IMPLEMENTED	Explicitly planned but not evidenced as executable.
DOCUMENTATION_ONLY_CLAIM	Documentation or client contract claims behavior without verified backend evidence.
CONFLICT_REQUIRES_CANONICALIZATION	Sources disagree and no final owner has been established.
REQUIRES_REPOSITORY_REVIEW	Necessary executable evidence has not yet been inspected.

Customer Portal — UX States, Accessibility, Localization, Analytics, and E2E

Metadata	Value
Volume	4
Chapter ID	V04-P05-03
Subject	CustomerPortalExperienceStandard
Status	Generated First-Draft Architecture Skeleton - Domain-Specific Expansion Required
Content maturity	TEMPLATE_DERIVED_REFERENCE_SKELETON unless repository citations prove otherwise
Default implementation classification	REFERENCE_ARCHITECTURE / REQUIRES_REPOSITORY_REVIEW
Accountable owner	Portal Architecture / Customer Portal
Evidence rule	No implementation claim without inspected executable evidence
Repository	chinair88-prog/allinb2c

1. Executive Orientation

This chapter defines how GTOS shall **specify loading, empty, partial, stale, error, denied, offline, accessibility, RTL/LTR, analytics, audit and test journeys for buyer organizations and users, covering identity, demand, RFQ, quotation, PI, payment, PO, production, quality, shipping, inventory, finance.**

The specification separates reality, observations, knowledge, Decisions, Intent, execution, and outcomes. A component name, database row, UI label, AI answer, or workflow state does not acquire authority merely because it is visible or technically convenient.

Reality or external outcome

- ≠ Observation
- ≠ Claim
- ≠ derived Perspective
- ≠ Prediction
- ≠ Recommendation
- ≠ authorized Decision
- ≠ execution Intent

1.1 Accountable ownership

The accountable owner is **Portal Architecture / Customer Portal**. Supporting applications, shared infrastructure, integration adapters, analytics, and AI coordinate or present the capability but shall not silently own its authoritative propositions.

1.2 Scope

- create and identify the subject
- validate evidence and policy
- make authorized Decisions
- execute typed Commands
- publish completed-fact Events
- query current and historical perspectives
- correct and reconcile outcomes

1.3 Non-goals

- treating a registered Gradle module, catalog record, README, frontend route, migration plan, or generated report as proof of end-to-end implementation;
- direct cross-Domain database writes;
- generic status values that combine lifecycle, approval, provider, document, payment, dispute, and correction state;
- silent replacement of history;
- AI-created authority or fabricated external outcomes.

2. Ubiquitous Language and Subject Model

Subject	Required interpretation
CustomerPortalExperienceStandard	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit
CustomerPortalExperienceStandardVersion	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit
CustomerPortalExperienceStandardDecision	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit
CustomerPortalExperienceStandardEvidenceSet	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit
CustomerPortalExperienceStandardException	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit

Reference aggregate:

```
CustomerPortalExperienceStandard {
  subjectId
  tenantId
  organizationContext
  sourceIdentityRefs[]
  sourceVersionRefs[]
  lifecycleState
  relationshipRefs[]
  decisionRefs[]
  intentRefs[]
  evidenceSetRef
  knowledgeCutoff
  policyRefs[]
  authorityRef
  jurisdictionRefs[]
  createdAt
  effectiveAt
  updatedAt
  version
  correctionOf?
  correlationId
}
```

2.1 Core invariants

- Stable identity precedes relationship, state, and cross-system correlation.
- Effective time and recorded time remain distinct where business truth changes over time.
- Recommendation, Decision, Intent, execution, and outcome are separate concepts.
- No Portal, report, search index, cache, workflow, or AI Agent becomes a shadow owner of Domain truth.
- Binding submitted, approved, issued, accepted, or signed versions are immutable.
- Corrections append governed facts and preserve the original record.
- External authority and provider outcomes retain their source and qualification.
- Tenant and represented-principal context come from trusted authentication and mandate evaluation.
- Retried writes are idempotent and concurrency guarded.
- Outcome Unknown is explicit and reconciled before risky duplicate execution.

2.2 Required standards

- stable identifiers
- typed contracts
- immutable binding versions

- transactional outbox
- idempotent Commands
- explicit Outcome Unknown
- correction lineage
- machine-verifiable conformance

3. Actors, Roles, and Authority

- A conformant design distinguishes:
- the natural person acting;
 - the service or AI identity invoking a Tool;
 - the organization or principal represented;
 - the role or relationship granting context;
 - the mandate or delegation granting action authority;
 - the Policy and jurisdiction limiting the action;
 - the reviewer or approver responsible for a binding Decision.

Authority is evaluated at action time. Authentication alone does not grant business authority. Cached permissions and browser-supplied tenant headers are insufficient for high-impact actions.

4. Lifecycle and State Model

State	Semantics
PROPOSED	Distinct governed condition with entry, exit, timeout, correction and authority semantics
VALIDATION_PENDING	Distinct governed condition with entry, exit, timeout, correction and authority semantics
APPROVAL_PENDING	Distinct governed condition with entry, exit, timeout, correction and authority semantics
ACTIVE	Distinct governed condition with entry, exit, timeout, correction and authority semantics
SUSPENDED	Distinct governed condition with entry, exit, timeout, correction and authority semantics
CORRECTION_PENDING	Distinct governed condition with entry, exit, timeout, correction and authority semantics
RETIRED	Distinct governed condition with entry, exit, timeout, correction and authority semantics

```
stateDiagram-v2
    [*] --> PROPOSED
    PROPOSED --> VALIDATION_PENDING
    VALIDATION_PENDING --> APPROVAL_PENDING
    APPROVAL_PENDING --> ACTIVE
    ACTIVE --> SUSPENDED
    SUSPENDED --> CORRECTION_PENDING
    CORRECTION_PENDING --> RETIRED
```

The diagram is a primary reading path. Real implementations may add parallel review, amendment, appeal, timeout, suspension, partial completion, reconciliation, correction, and terminal failure without collapsing their meaning.

4.1 Transition rules

- transition through a typed, authorized Command;
- require exact expected version where concurrent change matters;
- record actor, represented principal, mandate, Policy, reason, and Evidence;
- use an idempotency key for retried writes;
- publish a completed-fact Event after durable state change;
- expose Outcome Unknown for unresolved external completion;
- preserve original and corrected states in historical reconstruction.

5. Decision, Evidence, and Knowledge Cutoff

Reference Decision:

```
Decision {
  decisionId
  decisionType
  subjectRef
  sourceVersionRefs[]
  knowledgeCutoff
  evidenceSetRef
  policyVersionRefs[]
  recommendationRefs[]
  principalId
  representedOrganizationId
  mandateRef
  rationale
  outcome
  decidedAt
  effectiveAt
  correctionOf?
}
```

Evidence records identify issuer or observer, subject, version, observed time, received time, effective interval, integrity, confidence, qualification, contradiction, correction, retention, residency, and access class. A recommendation may assist the Decision but cannot promote itself to the Decision.

6. Commands, Events, Queries, and Contracts

Reference Commands:

- CreateCustomerPortalExperienceStandard
- ValidateCustomerPortalExperienceStandard
- ApproveCustomerPortalExperienceStandard
- ActivateCustomerPortalExperienceStandard
- SuspendCustomerPortalExperienceStandard
- CorrectCustomerPortalExperienceStandard
- RetireCustomerPortalExperienceStandard

Reference Events:

- CustomerPortalExperienceStandardCreated
- CustomerPortalExperienceStandardValidated
- CustomerPortalExperienceStandardApproved
- CustomerPortalExperienceStandardActivated
- CustomerPortalExperienceStandardSuspended
- CustomerPortalExperienceStandardCorrected
- CustomerPortalExperienceStandardRetired

Reference queries:

- GetCustomerPortalExperienceStandard
- ListCustomerPortalExperienceStandardRecords
- GetCustomerPortalExperienceStandardTimeline
- GetCustomerPortalExperienceStandardEvidence
- GetCustomerPortalExperienceStandardDecisionPackage
- GetCustomerPortalExperienceStandardExceptions
- GetCustomerPortalExperienceStandardAuditTrail

Reference API surface:

```
POST /api/v1/customerportalexperiencestandard/commands
GET  /api/v1/customerportalexperiencestandard/{id}
GET  /api/v1/customerportalexperiencestandard/{id}/timeline
GET  /api/v1/customerportalexperiencestandard/{id}/evidence
GET  /api/v1/customerportalexperiencestandard/{id}/decisions
POST /api/v1/customerportalexperiencestandard/{id}/exceptions
POST /api/v1/customerportalexperiencestandard/{id}/corrections
```

These endpoints are reference contracts, not claims that exact routes exist.

7. Workflow, Failure, and Compensation

```
flowchart TD
    A[Validate identity version and authority] --> B[Collect required evidence]
    B --> C{Policy and evidence gates pass?}
    C -- No --> D[Open exception or request correction]
    D --> B
    C -- Yes --> E[Record Decision or execution Intent]
    E --> F[Execute Domain command or external request]
    F --> G{Outcome known?}
    G -- Success --> H[Record fact and publish Event]
    G -- Failure --> I[Record failure and compensation options]
    G -- Unknown --> J[Enter Outcome Unknown]
    J --> K[Query source or wait for verified callback]
    K --> G
    H --> L[Update projections and downstream workflow]
```

Representative failure modes:

- stale or wrong source version
- duplicate submission or replay
- external timeout after possible success
- contradictory source observations
- lost Event after committed state
- approval or mandate revoked during execution
- downstream action before a mandatory gate
- partial completion across multiple subjects
- evidence later retracted or corrected
- tenant, facility, channel or jurisdiction mismatch

Recovery shall query the authoritative source before duplicate execution, preserve partial success, use compensating Intent rather than destructive rewrite, publish corrections, quarantine high-impact ambiguity, and record affected downstream subjects.

8. Data and Persistence Architecture

Reference table families:

Table family	Purpose
customerportalexperiencestandard_aggregate	authoritative subject
customerportalexperiencestandard_version	immutable submitted, approved, issued, or signed versions
customerportalexperiencestandard_relationship	governed relationships
customerportalexperiencestandard_decision	binding Decisions and rationale
customerportalexperiencestandard_evidence_link	provenance and evidence relationships
customerportalexperiencestandard_event_outbox	transactional Event publication
customerportalexperiencestandard_idempotency	duplicate-write protection
customerportalexperiencestandard_exception	exception, claim, dispute, or hold
customerportalexperiencestandard_correction	correction and supersession lineage
customerportalexperiencestandard_audit	privileged action evidence

The owning service controls schema and migration. Cross-Domain references use stable identifiers or contracts. Analytics, reports, caches, search, and vector indexes remain projections. Backup, restore, retention, legal hold, privacy, residency, and decommissioning requirements are explicit.

9. Portal and Experience Requirements

- Customer Portal: primary experience for buyer organizations and users.
- Operator and support views: diagnose failed or ambiguous journeys without assuming Domain ownership.
- Domain services: own authoritative data and action eligibility; the Portal consumes typed contracts.

Every Portal displays exact version, owner, state, freshness, required action, and uncertainty. It supports loading, empty, partial, stale, denied, error, timeout, and Outcome Unknown states; accessibility; locale, currency, unit, date, and RTL/LTR correctness; evidence audit; safe retry; and correction history.

10. AI Participation and Tool Governance

Permitted AI tasks:

- extract and classify evidence
- detect anomalies and missing fields
- summarize timelines and contradictions
- recommend next actions with sources and uncertainty

AI shall not own Domain records, grant itself authority, suppress contradictions, silently edit approved versions, fabricate external outcomes, or execute high-impact actions outside typed Tools, policy, approval, idempotency, sandbox, and outcome observation.

Every Agent Run records source context, prompt/model/tool versions, structured output, confidence and limitations, Policy result, approval, Tool calls, provider responses, final outcome, and recovery actions.

11. Security, Privacy, and Trust Boundaries

- least privilege and separation of duties
- tenant, organization, facility, channel and jurisdiction isolation
- integrity protection for binding evidence
- verified external callbacks and anti-replay controls

Additional controls include secret isolation, callback signature verification, audit of privileged action, emergency-access review, sensitive-data minimization, purpose limitation, and threat models for impersonation, tampering, replay, confused deputy, fraud, prompt injection, and exfiltration.

12. Reliability, SLOs, and Operations

SLI	Reference objective
authoritative read availability	99.9% monthly unless a stricter tier applies
acknowledged Command durability	no acknowledged write may be silently lost
Event publication	99.9% within five minutes after committed fact
duplicate prevention	100% for same tenant, Command class, and idempotency key
binding Decision audit completeness	100%
state-state detection	bounded by business deadline

Dashboards and runbooks cover backlog, error budget, dependency failure, retry budget, DLQ, workflow stall, provider outage, reconciliation, capacity, backup/restore, release/rollback, incident command, and post-incident correction.

13. Testing and Continuous Conformance

- aggregate invariant and transition tests
- authorization, delegation, separation-of-duties and tenant-isolation tests
- idempotency and optimistic-concurrency tests
- database migration, key, constraint and rollback tests
- contract, outbox/inbox, duplicate, replay and DLQ tests
- workflow restart, timeout and compensation tests
- Portal E2E tests for success, partial, stale, denied, error and Outcome Unknown states
- accessibility, locale, currency, unit and RTL/LTR tests
- security adversarial, fraud and data-exfiltration tests
- AI evaluation, prompt-injection, policy-bypass and unauthorized-tool tests
- historical reconstruction, correction and audit-completeness tests
- performance, capacity, recovery and operational exercise tests

Release evidence links each invariant and control to the test, environment, input data, result, owner, and artifact proving it. Generated test counts never replace semantic coverage.

14. Repository Review Boundary

- This chapter is a repository-review specification. Exact executable implementation has not been inspected for every target behavior.
- Registered modules, catalog entries, README claims, frontend contracts, or plans are not proof of complete implementation.

Area	Classification
target aggregate, API, tables, state and workflow in this chapter	REFERENCE_ARCHITECTURE
registered module or catalog claim	DOCUMENTATION_ONLY_CLAIM until source inspection
uninspected integration	REQUIRES_REPOSITORY_REVIEW
behavior proven in another repository-grounded chapter	retain that chapter's evidence and classification
contradictory ownership or path claims	CONFLICT_REQUIRES_CANONICALIZATION

No statement upgrades implementation status merely because a file, directory, module name, frontend contract, database entry, plan, or report exists.

15. Worked Conformance Scenario

An authorized principal initiates a Command against an exact subject version. The service validates identity, tenant, mandate, Policy, Evidence, and idempotency. It records the state transition and outbox entry atomically. If an external dependency participates, timeout produces Outcome Unknown; reconciliation queries the source or waits for a verified callback instead of repeating the action blindly.

Portals show source, freshness, version, required action, and uncertainty. AI may extract, compare, summarize, detect anomalies, and recommend through typed Tools, but cannot own the subject or fabricate success. Later correction appends new facts, identifies affected projections and workflows, and preserves the historical Decision context.

16. Conformance Checklist

- ☐ stable identity and proposition ownership are explicit;
- ☐ authority and mandate are evaluated at action time;
- ☐ state, Recommendation, Decision, Intent, execution, and outcome remain distinct;
- ☐ Commands are typed, authorized, idempotent, and version guarded;
- ☐ Events describe completed facts;
- ☐ Evidence includes provenance, time, integrity, qualification, and correction;
- ☐ external outcomes retain their authority source;
- ☐ Portals show freshness and uncertainty;
- ☐ AI is bounded by typed Tools, Policy, approval, and outcome observation;
- ☐ security, tenant, facility, channel, and jurisdiction boundaries are enforced;
- ☐ Outcome Unknown and reconciliation exist where needed;
- ☐ corrections preserve history;
- ☐ tests prove invariants and recovery;
- ☐ implementation status is not upgraded without executable evidence.

17. Status Vocabulary

Status	Meaning
VERIFIED_IMPLEMENTED	Executable source and relevant behavior were inspected.
IMPLEMENTED_WITH_GAP	Executable behavior exists with a material governance or completeness gap.
PARTIAL_IMPLEMENTATION	Only part of the target capability is evidenced.
REFERENCE_ARCHITECTURE	Normative target behavior; no claim that it exists today.
PLANNED_NOT_IMPLEMENTED	Explicitly planned but not evidenced as executable.
DOCUMENTATION_ONLY_CLAIM	Documentation or client contract claims behavior without verified backend evidence.
CONFLICT_REQUIRES_CANONICALIZATION	Sources disagree and no final owner has been established.
REQUIRES_REPOSITORY_REVIEW	Necessary executable evidence has not yet been inspected.

Provider Portal — Portal Orientation and Information Architecture

Metadata	Value
Volume	4
Chapter ID	V04-P06-00
Subject	ProviderPortalPortal
Status	Generated First-Draft Architecture Skeleton - Domain-Specific Expansion Required
Content maturity	TEMPLATE_DERIVED_REFERENCE_SKELETON unless repository citations prove otherwise
Default implementation classification	REFERENCE_ARCHITECTURE / REQUIRES_REPOSITORY_REVIEW
Accountable owner	Portal Architecture / Provider Portal
Evidence rule	No implementation claim without inspected executable evidence
Repository	chinair88-prog/allinb2c

1. Executive Orientation

This chapter defines how GTOS shall **define personas, navigation, route ownership, domain dependencies and experience boundaries for logistics, customs, carrier and service providers, covering profile, RFQ invitation, transport option, booking, customs, milestones, billing, settlement.**

The specification separates reality, observations, knowledge, Decisions, Intent, execution, and outcomes. A component name, database row, UI label, AI answer, or workflow state does not acquire authority merely because it is visible or technically convenient.

Reality or external outcome

- ≠ Observation
- ≠ Claim
- ≠ derived Perspective
- ≠ Prediction
- ≠ Recommendation
- ≠ authorized Decision
- ≠ execution Intent

1.1 Accountable ownership

The accountable owner is **Portal Architecture / Provider Portal**. Supporting applications, shared infrastructure, integration adapters, analytics, and AI coordinate or present the capability but shall not silently own its authoritative propositions.

1.2 Scope

- create and identify the subject
- validate evidence and policy
- make authorized Decisions
- execute typed Commands
- publish completed-fact Events
- query current and historical perspectives
- correct and reconcile outcomes

1.3 Non-goals

- treating a registered Gradle module, catalog record, README, frontend route, migration plan, or generated report as proof of end-to-end implementation;
- direct cross-Domain database writes;
- generic status values that combine lifecycle, approval, provider, document, payment, dispute, and correction state;
- silent replacement of history;
- AI-created authority or fabricated external outcomes.

2. Ubiquitous Language and Subject Model

Subject	Required interpretation
ProviderPortalPortal	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit
ProviderPortalPortalVersion	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit
ProviderPortalPortalDecision	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit
ProviderPortalPortalEvidenceSet	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit
ProviderPortalPortalException	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit

Reference aggregate:

```
ProviderPortalPortal {  
  subjectId  
  tenantId  
  organizationContext  
  sourceIdentityRefs[]  
  sourceVersionRefs[]  
  lifecycleState  
  relationshipRefs[]  
  decisionRefs[]  
  intentRefs[]  
  evidenceSetRef  
  knowledgeCutoff  
  policyRefs[]  
  authorityRef  
  jurisdictionRefs[]  
  createdAt  
  effectiveAt  
  updatedAt  
  version  
  correctionOf?  
  correlationId  
}
```

2.1 Core invariants

- Stable identity precedes relationship, state, and cross-system correlation.
- Effective time and recorded time remain distinct where business truth changes over time.
- Recommendation, Decision, Intent, execution, and outcome are separate concepts.
- No Portal, report, search index, cache, workflow, or AI Agent becomes a shadow owner of Domain truth.
- Binding submitted, approved, issued, accepted, or signed versions are immutable.
- Corrections append governed facts and preserve the original record.
- External authority and provider outcomes retain their source and qualification.
- Tenant and represented-principal context come from trusted authentication and mandate evaluation.
- Retried writes are idempotent and concurrency guarded.
- Outcome Unknown is explicit and reconciled before risky duplicate execution.

2.2 Required standards

- stable identifiers
- typed contracts
- immutable binding versions

- transactional outbox
- idempotent Commands
- explicit Outcome Unknown
- correction lineage
- machine-verifiable conformance

3. Actors, Roles, and Authority

A conformant design distinguishes:

- the natural person acting;
- the service or AI identity invoking a Tool;
- the organization or principal represented;
- the role or relationship granting context;
- the mandate or delegation granting action authority;
- the Policy and jurisdiction limiting the action;
- the reviewer or approver responsible for a binding Decision.

Authority is evaluated at action time. Authentication alone does not grant business authority. Cached permissions and browser-supplied tenant headers are insufficient for high-impact actions.

4. Lifecycle and State Model

State	Semantics
PROPOSED	Distinct governed condition with entry, exit, timeout, correction and authority semantics
VALIDATION_PENDING	Distinct governed condition with entry, exit, timeout, correction and authority semantics
APPROVAL_PENDING	Distinct governed condition with entry, exit, timeout, correction and authority semantics
ACTIVE	Distinct governed condition with entry, exit, timeout, correction and authority semantics
SUSPENDED	Distinct governed condition with entry, exit, timeout, correction and authority semantics
CORRECTION_PENDING	Distinct governed condition with entry, exit, timeout, correction and authority semantics
RETIRED	Distinct governed condition with entry, exit, timeout, correction and authority semantics

```
stateDiagram-v2
    [*] --> PROPOSED
    PROPOSED --> VALIDATION_PENDING
    VALIDATION_PENDING --> APPROVAL_PENDING
    APPROVAL_PENDING --> ACTIVE
    ACTIVE --> SUSPENDED
    SUSPENDED --> CORRECTION_PENDING
    CORRECTION_PENDING --> RETIRED
```

The diagram is a primary reading path. Real implementations may add parallel review, amendment, appeal, timeout, suspension, partial completion, reconciliation, correction, and terminal failure without collapsing their meaning.

4.1 Transition rules

- transition through a typed, authorized Command;
- require exact expected version where concurrent change matters;
- record actor, represented principal, mandate, Policy, reason, and Evidence;
- use an idempotency key for retried writes;
- publish a completed-fact Event after durable state change;
- expose Outcome Unknown for unresolved external completion;
- preserve original and corrected states in historical reconstruction.

5. Decision, Evidence, and Knowledge Cutoff

Reference Decision:

```
Decision {
  decisionId
  decisionType
  subjectRef
  sourceVersionRefs[]
  knowledgeCutoff
  evidenceSetRef
  policyVersionRefs[]
  recommendationRefs[]
  principalId
  representedOrganizationId
  mandateRef
  rationale
  outcome
  decidedAt
  effectiveAt
  correctionOf?
}
```

Evidence records identify issuer or observer, subject, version, observed time, received time, effective interval, integrity, confidence, qualification, contradiction, correction, retention, residency, and access class. A recommendation may assist the Decision but cannot promote itself to the Decision.

6. Commands, Events, Queries, and Contracts

Reference Commands:

- CreateProviderPortalPortal
- ValidateProviderPortalPortal
- ApproveProviderPortalPortal
- ActivateProviderPortalPortal
- SuspendProviderPortalPortal
- CorrectProviderPortalPortal
- RetireProviderPortalPortal

Reference Events:

- ProviderPortalPortalCreated
- ProviderPortalPortalValidated
- ProviderPortalPortalApproved
- ProviderPortalPortalActivated
- ProviderPortalPortalSuspended
- ProviderPortalPortalCorrected
- ProviderPortalPortalRetired

Reference queries:

- GetProviderPortalPortal
- ListProviderPortalPortalRecords
- GetProviderPortalPortalTimeline
- GetProviderPortalPortalEvidence
- GetProviderPortalPortalDecisionPackage
- GetProviderPortalPortalExceptions
- GetProviderPortalPortalAuditTrail

Reference API surface:

```
POST /api/v1/providerportalportal/commands
GET  /api/v1/providerportalportal/{id}
GET  /api/v1/providerportalportal/{id}/timeline
GET  /api/v1/providerportalportal/{id}/evidence
GET  /api/v1/providerportalportal/{id}/decisions
POST /api/v1/providerportalportal/{id}/exceptions
POST /api/v1/providerportalportal/{id}/corrections
```

These endpoints are reference contracts, not claims that exact routes exist.

7. Workflow, Failure, and Compensation

flowchart TD

```
A[Validate identity version and authority] --> B[Collect required evidence]
B --> C{Policy and evidence gates pass?}
C -- No --> D[Open exception or request correction]
D --> B
C -- Yes --> E[Record Decision or execution Intent]
E --> F[Execute Domain command or external request]
F --> G{Outcome known?}
G -- Success --> H[Record fact and publish Event]
G -- Failure --> I[Record failure and compensation options]
G -- Unknown --> J[Enter Outcome Unknown]
J --> K[Query source or wait for verified callback]
K --> G
H --> L[Update projections and downstream workflow]
```

Representative failure modes:

- stale or wrong source version
- duplicate submission or replay
- external timeout after possible success
- contradictory source observations
- lost Event after committed state
- approval or mandate revoked during execution
- downstream action before a mandatory gate
- partial completion across multiple subjects
- evidence later retracted or corrected
- tenant, facility, channel or jurisdiction mismatch

Recovery shall query the authoritative source before duplicate execution, preserve partial success, use compensating Intent rather than destructive rewrite, publish corrections, quarantine high-impact ambiguity, and record affected downstream subjects.

8. Data and Persistence Architecture

Reference table families:

Table family	Purpose
providerportalportal_aggregate	authoritative subject
providerportalportal_version	immutable submitted, approved, issued, or signed versions
providerportalportal_relationship	governed relationships
providerportalportal_decision	binding Decisions and rationale
providerportalportal_evidence_link	provenance and evidence relationships
providerportalportal_event_outbox	transactional Event publication
providerportalportal_idempotency	duplicate-write protection
providerportalportal_exception	exception, claim, dispute, or hold
providerportalportal_correction	correction and supersession lineage
providerportalportal_audit	privileged action evidence

The owning service controls schema and migration. Cross-Domain references use stable identifiers or contracts. Analytics, reports, caches, search, and vector indexes remain projections. Backup, restore, retention, legal hold, privacy, residency, and decommissioning requirements are explicit.

9. Portal and Experience Requirements

- Provider Portal: primary experience for logistics, customs, carrier and service providers.
- Operator and support views: diagnose failed or ambiguous journeys without assuming Domain ownership.
- Domain services: own authoritative data and action eligibility; the Portal consumes typed contracts.

Every Portal displays exact version, owner, state, freshness, required action, and uncertainty. It supports loading, empty, partial, stale, denied, error, timeout, and Outcome Unknown states; accessibility; locale, currency, unit, date, and RTL/LTR correctness; evidence audit; safe retry; and correction history.

10. AI Participation and Tool Governance

Permitted AI tasks:

- extract and classify evidence
- detect anomalies and missing fields
- summarize timelines and contradictions
- recommend next actions with sources and uncertainty

AI shall not own Domain records, grant itself authority, suppress contradictions, silently edit approved versions, fabricate external outcomes, or execute high-impact actions outside typed Tools, policy, approval, idempotency, sandbox, and outcome observation.

Every Agent Run records source context, prompt/model/tool versions, structured output, confidence and limitations, Policy result, approval, Tool calls, provider responses, final outcome, and recovery actions.

11. Security, Privacy, and Trust Boundaries

- least privilege and separation of duties
- tenant, organization, facility, channel and jurisdiction isolation
- integrity protection for binding evidence
- verified external callbacks and anti-replay controls

Additional controls include secret isolation, callback signature verification, audit of privileged action, emergency-access review, sensitive-data minimization, purpose limitation, and threat models for impersonation, tampering, replay, confused deputy, fraud, prompt injection, and exfiltration.

12. Reliability, SLOs, and Operations

SLI	Reference objective
authoritative read availability	99.9% monthly unless a stricter tier applies
acknowledged Command durability	no acknowledged write may be silently lost
Event publication	99.9% within five minutes after committed fact
duplicate prevention	100% for same tenant, Command class, and idempotency key
binding Decision audit completeness	100%
state-state detection	bounded by business deadline

Dashboards and runbooks cover backlog, error budget, dependency failure, retry budget, DLQ, workflow stall, provider outage, reconciliation, capacity, backup/restore, release/rollback, incident command, and post-incident correction.

13. Testing and Continuous Conformance

- aggregate invariant and transition tests
- authorization, delegation, separation-of-duties and tenant-isolation tests
- idempotency and optimistic-concurrency tests
- database migration, key, constraint and rollback tests
- contract, outbox/inbox, duplicate, replay and DLQ tests
- workflow restart, timeout and compensation tests
- Portal E2E tests for success, partial, stale, denied, error and Outcome Unknown states
- accessibility, locale, currency, unit and RTL/LTR tests
- security adversarial, fraud and data-exfiltration tests
- AI evaluation, prompt-injection, policy-bypass and unauthorized-tool tests
- historical reconstruction, correction and audit-completeness tests
- performance, capacity, recovery and operational exercise tests

Release evidence links each invariant and control to the test, environment, input data, result, owner, and artifact proving it. Generated test counts never replace semantic coverage.

14. Repository Review Boundary

- This chapter is a repository-review specification. Exact executable implementation has not been inspected for every target behavior.
- Registered modules, catalog entries, README claims, frontend contracts, or plans are not proof of complete implementation.

Area	Classification
target aggregate, API, tables, state and workflow in this chapter	REFERENCE_ARCHITECTURE
registered module or catalog claim	DOCUMENTATION_ONLY_CLAIM until source inspection
uninspected integration	REQUIRES_REPOSITORY_REVIEW
behavior proven in another repository-grounded chapter	retain that chapter's evidence and classification
contradictory ownership or path claims	CONFLICT_REQUIRES_CANONICALIZATION

No statement upgrades implementation status merely because a file, directory, module name, frontend contract, database entry, plan, or report exists.

15. Worked Conformance Scenario

An authorized principal initiates a Command against an exact subject version. The service validates identity, tenant, mandate, Policy, Evidence, and idempotency. It records the state transition and outbox entry atomically. If an external dependency participates, timeout produces Outcome Unknown; reconciliation queries the source or waits for a verified callback instead of repeating the action blindly.

Portals show source, freshness, version, required action, and uncertainty. AI may extract, compare, summarize, detect anomalies, and recommend through typed Tools, but cannot own the subject or fabricate success. Later correction appends new facts, identifies affected projections and workflows, and preserves the historical Decision context.

16. Conformance Checklist

- ☐ stable identity and proposition ownership are explicit;
- ☐ authority and mandate are evaluated at action time;
- ☐ state, Recommendation, Decision, Intent, execution, and outcome remain distinct;
- ☐ Commands are typed, authorized, idempotent, and version guarded;
- ☐ Events describe completed facts;
- ☐ Evidence includes provenance, time, integrity, qualification, and correction;
- ☐ external outcomes retain their authority source;
- ☐ Portals show freshness and uncertainty;
- ☐ AI is bounded by typed Tools, Policy, approval, and outcome observation;
- ☐ security, tenant, facility, channel, and jurisdiction boundaries are enforced;
- ☐ Outcome Unknown and reconciliation exist where needed;
- ☐ corrections preserve history;
- ☐ tests prove invariants and recovery;
- ☐ implementation status is not upgraded without executable evidence.

17. Status Vocabulary

Status	Meaning
VERIFIED_IMPLEMENTED	Executable source and relevant behavior were inspected.
IMPLEMENTED_WITH_GAP	Executable behavior exists with a material governance or completeness gap.
PARTIAL_IMPLEMENTATION	Only part of the target capability is evidenced.
REFERENCE_ARCHITECTURE	Normative target behavior; no claim that it exists today.
PLANNED_NOT_IMPLEMENTED	Explicitly planned but not evidenced as executable.
DOCUMENTATION_ONLY_CLAIM	Documentation or client contract claims behavior without verified backend evidence.
CONFLICT_REQUIRES_CANONICALIZATION	Sources disagree and no final owner has been established.
REQUIRES_REPOSITORY_REVIEW	Necessary executable evidence has not yet been inspected.

Provider Portal — Routes, Pages, Components, and BFF Contracts

Metadata	Value
Volume	4
Chapter ID	V04-P06-01
Subject	ProviderPortalRouteRegistry
Status	Generated First-Draft Architecture Skeleton - Domain-Specific Expansion Required
Content maturity	TEMPLATE_DERIVED_REFERENCE_SKELETON unless repository citations prove otherwise
Default implementation classification	REFERENCE_ARCHITECTURE / REQUIRES_REPOSITORY_REVIEW
Accountable owner	Portal Architecture / Provider Portal
Evidence rule	No implementation claim without inspected executable evidence
Repository	chinair88-prog/allinb2c

1. Executive Orientation

This chapter defines how GTOS shall **inventory routes, layouts, pages, components, server/client boundaries, BFFs, APIs, realtime channels and ownership for logistics, customs, carrier and service providers, covering profile, RFQ invitation, transport option, booking, customs, milestones, billing, settlement.**

The specification separates reality, observations, knowledge, Decisions, Intent, execution, and outcomes. A component name, database row, UI label, AI answer, or workflow state does not acquire authority merely because it is visible or technically convenient.

Reality or external outcome

- ≠ Observation
- ≠ Claim
- ≠ derived Perspective
- ≠ Prediction
- ≠ Recommendation
- ≠ authorized Decision
- ≠ execution Intent

1.1 Accountable ownership

The accountable owner is **Portal Architecture / Provider Portal**. Supporting applications, shared infrastructure, integration adapters, analytics, and AI coordinate or present the capability but shall not silently own its authoritative propositions.

1.2 Scope

- create and identify the subject
- validate evidence and policy
- make authorized Decisions
- execute typed Commands
- publish completed-fact Events
- query current and historical perspectives
- correct and reconcile outcomes

1.3 Non-goals

- treating a registered Gradle module, catalog record, README, frontend route, migration plan, or generated report as proof of end-to-end implementation;
- direct cross-Domain database writes;
- generic status values that combine lifecycle, approval, provider, document, payment, dispute, and correction state;
- silent replacement of history;
- AI-created authority or fabricated external outcomes.

2. Ubiquitous Language and Subject Model

Subject	Required interpretation
ProviderPortalRouteRegistry	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit
ProviderPortalRouteRegistryVersion	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit
ProviderPortalRouteRegistryDecision	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit
ProviderPortalRouteRegistryEvidenceSet	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit
ProviderPortalRouteRegistryException	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit

Reference aggregate:

```
ProviderPortalRouteRegistry {
  subjectId
  tenantId
  organizationContext
  sourceIdentityRefs[]
  sourceVersionRefs[]
  lifecycleState
  relationshipRefs[]
  decisionRefs[]
  intentRefs[]
  evidenceSetRef
  knowledgeCutoff
  policyRefs[]
  authorityRef
  jurisdictionRefs[]
  createdAt
  effectiveAt
  updatedAt
  version
  correctionOf?
  correlationId
}
```

2.1 Core invariants

- Stable identity precedes relationship, state, and cross-system correlation.
- Effective time and recorded time remain distinct where business truth changes over time.
- Recommendation, Decision, Intent, execution, and outcome are separate concepts.
- No Portal, report, search index, cache, workflow, or AI Agent becomes a shadow owner of Domain truth.
- Binding submitted, approved, issued, accepted, or signed versions are immutable.
- Corrections append governed facts and preserve the original record.
- External authority and provider outcomes retain their source and qualification.
- Tenant and represented-principal context come from trusted authentication and mandate evaluation.
- Retried writes are idempotent and concurrency guarded.
- Outcome Unknown is explicit and reconciled before risky duplicate execution.

2.2 Required standards

- stable identifiers
- typed contracts
- immutable binding versions

- transactional outbox
- idempotent Commands
- explicit Outcome Unknown
- correction lineage
- machine-verifiable conformance

3. Actors, Roles, and Authority

- A conformant design distinguishes:
- the natural person acting;
 - the service or AI identity invoking a Tool;
 - the organization or principal represented;
 - the role or relationship granting context;
 - the mandate or delegation granting action authority;
 - the Policy and jurisdiction limiting the action;
 - the reviewer or approver responsible for a binding Decision.

Authority is evaluated at action time. Authentication alone does not grant business authority. Cached permissions and browser-supplied tenant headers are insufficient for high-impact actions.

4. Lifecycle and State Model

State	Semantics
PROPOSED	Distinct governed condition with entry, exit, timeout, correction and authority semantics
VALIDATION_PENDING	Distinct governed condition with entry, exit, timeout, correction and authority semantics
APPROVAL_PENDING	Distinct governed condition with entry, exit, timeout, correction and authority semantics
ACTIVE	Distinct governed condition with entry, exit, timeout, correction and authority semantics
SUSPENDED	Distinct governed condition with entry, exit, timeout, correction and authority semantics
CORRECTION_PENDING	Distinct governed condition with entry, exit, timeout, correction and authority semantics
RETIRED	Distinct governed condition with entry, exit, timeout, correction and authority semantics

```
stateDiagram-v2
    [*] --> PROPOSED
    PROPOSED --> VALIDATION_PENDING
    VALIDATION_PENDING --> APPROVAL_PENDING
    APPROVAL_PENDING --> ACTIVE
    ACTIVE --> SUSPENDED
    SUSPENDED --> CORRECTION_PENDING
    CORRECTION_PENDING --> RETIRED
```

The diagram is a primary reading path. Real implementations may add parallel review, amendment, appeal, timeout, suspension, partial completion, reconciliation, correction, and terminal failure without collapsing their meaning.

4.1 Transition rules

- transition through a typed, authorized Command;
- require exact expected version where concurrent change matters;
- record actor, represented principal, mandate, Policy, reason, and Evidence;
- use an idempotency key for retried writes;
- publish a completed-fact Event after durable state change;
- expose Outcome Unknown for unresolved external completion;
- preserve original and corrected states in historical reconstruction.

5. Decision, Evidence, and Knowledge Cutoff

Reference Decision:

```
Decision {
  decisionId
  decisionType
  subjectRef
  sourceVersionRefs[]
  knowledgeCutoff
  evidenceSetRef
  policyVersionRefs[]
  recommendationRefs[]
  principalId
  representedOrganizationId
  mandateRef
  rationale
  outcome
  decidedAt
  effectiveAt
  correctionOf?
}
```

Evidence records identify issuer or observer, subject, version, observed time, received time, effective interval, integrity, confidence, qualification, contradiction, correction, retention, residency, and access class. A recommendation may assist the Decision but cannot promote itself to the Decision.

6. Commands, Events, Queries, and Contracts

Reference Commands:

- CreateProviderPortalRouteRegistry
- ValidateProviderPortalRouteRegistry
- ApproveProviderPortalRouteRegistry
- ActivateProviderPortalRouteRegistry
- SuspendProviderPortalRouteRegistry
- CorrectProviderPortalRouteRegistry
- RetireProviderPortalRouteRegistry

Reference Events:

- ProviderPortalRouteRegistryCreated
- ProviderPortalRouteRegistryValidated
- ProviderPortalRouteRegistryApproved
- ProviderPortalRouteRegistryActivated
- ProviderPortalRouteRegistrySuspended
- ProviderPortalRouteRegistryCorrected
- ProviderPortalRouteRegistryRetired

Reference queries:

- GetProviderPortalRouteRegistry
- ListProviderPortalRouteRegistryRecords
- GetProviderPortalRouteRegistryTimeline
- GetProviderPortalRouteRegistryEvidence
- GetProviderPortalRouteRegistryDecisionPackage
- GetProviderPortalRouteRegistryExceptions
- GetProviderPortalRouteRegistryAuditTrail

Reference API surface:

```
POST /api/v1/providerportalrouteregistry/commands
GET  /api/v1/providerportalrouteregistry/{id}
GET  /api/v1/providerportalrouteregistry/{id}/timeline
GET  /api/v1/providerportalrouteregistry/{id}/evidence
GET  /api/v1/providerportalrouteregistry/{id}/decisions
POST /api/v1/providerportalrouteregistry/{id}/exceptions
POST /api/v1/providerportalrouteregistry/{id}/corrections
```

These endpoints are reference contracts, not claims that exact routes exist.

7. Workflow, Failure, and Compensation

flowchart TD

```
A[Validate identity version and authority] --> B[Collect required evidence]
B --> C{Policy and evidence gates pass?}
C -- No --> D[Open exception or request correction]
D --> B
C -- Yes --> E[Record Decision or execution Intent]
E --> F[Execute Domain command or external request]
F --> G{Outcome known?}
G -- Success --> H[Record fact and publish Event]
G -- Failure --> I[Record failure and compensation options]
G -- Unknown --> J[Enter Outcome Unknown]
J --> K[Query source or wait for verified callback]
K --> G
H --> L[Update projections and downstream workflow]
```

Representative failure modes:

- stale or wrong source version
- duplicate submission or replay
- external timeout after possible success
- contradictory source observations
- lost Event after committed state
- approval or mandate revoked during execution
- downstream action before a mandatory gate
- partial completion across multiple subjects
- evidence later retracted or corrected
- tenant, facility, channel or jurisdiction mismatch

Recovery shall query the authoritative source before duplicate execution, preserve partial success, use compensating Intent rather than destructive rewrite, publish corrections, quarantine high-impact ambiguity, and record affected downstream subjects.

8. Data and Persistence Architecture

Reference table families:

Table family	Purpose
providerportalrouterregistry_aggregate	authoritative subject
providerportalrouterregistry_version	immutable submitted, approved, issued, or signed versions
providerportalrouterregistry_relationship	governed relationships
providerportalrouterregistry_decision	binding Decisions and rationale
providerportalrouterregistry_evidence_link	provenance and evidence relationships
providerportalrouterregistry_event_outbox	transactional Event publication
providerportalrouterregistry_idempotency	duplicate-write protection
providerportalrouterregistry_exception	exception, claim, dispute, or hold
providerportalrouterregistry_correction	correction and supersession lineage
providerportalrouterregistry_audit	privileged action evidence

The owning service controls schema and migration. Cross-Domain references use stable identifiers or contracts. Analytics, reports, caches, search, and vector indexes remain projections. Backup, restore, retention, legal hold, privacy, residency, and decommissioning requirements are explicit.

9. Portal and Experience Requirements

- Provider Portal: primary experience for logistics, customs, carrier and service providers.
- Operator and support views: diagnose failed or ambiguous journeys without assuming Domain ownership.
- Domain services: own authoritative data and action eligibility; the Portal consumes typed contracts.

Every Portal displays exact version, owner, state, freshness, required action, and uncertainty. It supports loading, empty, partial, stale, denied, error, timeout, and Outcome Unknown states; accessibility; locale, currency, unit, date, and RTL/LTR correctness; evidence audit; safe retry; and correction history.

10. AI Participation and Tool Governance

Permitted AI tasks:

- extract and classify evidence
- detect anomalies and missing fields
- summarize timelines and contradictions
- recommend next actions with sources and uncertainty

AI shall not own Domain records, grant itself authority, suppress contradictions, silently edit approved versions, fabricate external outcomes, or execute high-impact actions outside typed Tools, policy, approval, idempotency, sandbox, and outcome observation.

Every Agent Run records source context, prompt/model/tool versions, structured output, confidence and limitations, Policy result, approval, Tool calls, provider responses, final outcome, and recovery actions.

11. Security, Privacy, and Trust Boundaries

- least privilege and separation of duties
- tenant, organization, facility, channel and jurisdiction isolation
- integrity protection for binding evidence
- verified external callbacks and anti-replay controls

Additional controls include secret isolation, callback signature verification, audit of privileged action, emergency-access review, sensitive-data minimization, purpose limitation, and threat models for impersonation, tampering, replay, confused deputy, fraud, prompt injection, and exfiltration.

12. Reliability, SLOs, and Operations

SLI	Reference objective
authoritative read availability	99.9% monthly unless a stricter tier applies
acknowledged Command durability	no acknowledged write may be silently lost
Event publication	99.9% within five minutes after committed fact
duplicate prevention	100% for same tenant, Command class, and idempotency key
binding Decision audit completeness	100%
state-state detection	bounded by business deadline

Dashboards and runbooks cover backlog, error budget, dependency failure, retry budget, DLQ, workflow stall, provider outage, reconciliation, capacity, backup/restore, release/rollback, incident command, and post-incident correction.

13. Testing and Continuous Conformance

- aggregate invariant and transition tests
- authorization, delegation, separation-of-duties and tenant-isolation tests
- idempotency and optimistic-concurrency tests
- database migration, key, constraint and rollback tests
- contract, outbox/inbox, duplicate, replay and DLQ tests
- workflow restart, timeout and compensation tests
- Portal E2E tests for success, partial, stale, denied, error and Outcome Unknown states
- accessibility, locale, currency, unit and RTL/LTR tests
- security adversarial, fraud and data-exfiltration tests
- AI evaluation, prompt-injection, policy-bypass and unauthorized-tool tests
- historical reconstruction, correction and audit-completeness tests
- performance, capacity, recovery and operational exercise tests

Release evidence links each invariant and control to the test, environment, input data, result, owner, and artifact proving it. Generated test counts never replace semantic coverage.

14. Repository Review Boundary

- This chapter is a repository-review specification. Exact executable implementation has not been inspected for every target behavior.
- Registered modules, catalog entries, README claims, frontend contracts, or plans are not proof of complete implementation.

Area	Classification
target aggregate, API, tables, state and workflow in this chapter	REFERENCE_ARCHITECTURE
registered module or catalog claim	DOCUMENTATION_ONLY_CLAIM until source inspection
uninspected integration	REQUIRES_REPOSITORY_REVIEW
behavior proven in another repository-grounded chapter	retain that chapter's evidence and classification
contradictory ownership or path claims	CONFLICT_REQUIRES_CANONICALIZATION

No statement upgrades implementation status merely because a file, directory, module name, frontend contract, database entry, plan, or report exists.

15. Worked Conformance Scenario

An authorized principal initiates a Command against an exact subject version. The service validates identity, tenant, mandate, Policy, Evidence, and idempotency. It records the state transition and outbox entry atomically. If an external dependency participates, timeout produces Outcome Unknown; reconciliation queries the source or waits for a verified callback instead of repeating the action blindly.

Portals show source, freshness, version, required action, and uncertainty. AI may extract, compare, summarize, detect anomalies, and recommend through typed Tools, but cannot own the subject or fabricate success. Later correction appends new facts, identifies affected projections and workflows, and preserves the historical Decision context.

16. Conformance Checklist

- ☐ stable identity and proposition ownership are explicit;
- ☐ authority and mandate are evaluated at action time;
- ☐ state, Recommendation, Decision, Intent, execution, and outcome remain distinct;
- ☐ Commands are typed, authorized, idempotent, and version guarded;
- ☐ Events describe completed facts;
- ☐ Evidence includes provenance, time, integrity, qualification, and correction;
- ☐ external outcomes retain their authority source;
- ☐ Portals show freshness and uncertainty;
- ☐ AI is bounded by typed Tools, Policy, approval, and outcome observation;
- ☐ security, tenant, facility, channel, and jurisdiction boundaries are enforced;
- ☐ Outcome Unknown and reconciliation exist where needed;
- ☐ corrections preserve history;
- ☐ tests prove invariants and recovery;
- ☐ implementation status is not upgraded without executable evidence.

17. Status Vocabulary

Status	Meaning
VERIFIED_IMPLEMENTED	Executable source and relevant behavior were inspected.
IMPLEMENTED_WITH_GAP	Executable behavior exists with a material governance or completeness gap.
PARTIAL_IMPLEMENTATION	Only part of the target capability is evidenced.
REFERENCE_ARCHITECTURE	Normative target behavior; no claim that it exists today.
PLANNED_NOT_IMPLEMENTED	Explicitly planned but not evidenced as executable.
DOCUMENTATION_ONLY_CLAIM	Documentation or client contract claims behavior without verified backend evidence.
CONFLICT_REQUIRES_CANONICALIZATION	Sources disagree and no final owner has been established.
REQUIRES_REPOSITORY_REVIEW	Necessary executable evidence has not yet been inspected.

Provider Portal — Identity, Session, Authorization, and Trust Boundaries

Metadata	Value
Volume	4
Chapter ID	V04-P06-02
Subject	ProviderPortalAccessModel
Status	Generated First-Draft Architecture Skeleton - Domain-Specific Expansion Required
Content maturity	TEMPLATE_DERIVED_REFERENCE_SKELETON unless repository citations prove otherwise
Default implementation classification	REFERENCE_ARCHITECTURE / REQUIRES_REPOSITORY_REVIEW
Accountable owner	Portal Architecture / Provider Portal
Evidence rule	No implementation claim without inspected executable evidence
Repository	chinair88-prog/allinb2c

1. Executive Orientation

This chapter defines how GTOS shall **govern login, session, role, relationship, tenant, facility, channel, delegation, impersonation and privileged action for logistics, customs, carrier and service providers, covering profile, RFQ invitation, transport option, booking, customs, milestones, billing, settlement.**

The specification separates reality, observations, knowledge, Decisions, Intent, execution, and outcomes. A component name, database row, UI label, AI answer, or workflow state does not acquire authority merely because it is visible or technically convenient.

Reality or external outcome
≠ Observation
≠ Claim
≠ derived Perspective
≠ Prediction
≠ Recommendation
≠ authorized Decision
≠ execution Intent

1.1 Accountable ownership

The accountable owner is **Portal Architecture / Provider Portal**. Supporting applications, shared infrastructure, integration adapters, analytics, and AI coordinate or present the capability but shall not silently own its authoritative propositions.

1.2 Scope

- create and identify the subject
- validate evidence and policy
- make authorized Decisions
- execute typed Commands
- publish completed-fact Events
- query current and historical perspectives
- correct and reconcile outcomes

1.3 Non-goals

- treating a registered Gradle module, catalog record, README, frontend route, migration plan, or generated report as proof of end-to-end implementation;
- direct cross-Domain database writes;
- generic status values that combine lifecycle, approval, provider, document, payment, dispute, and correction state;
- silent replacement of history;
- AI-created authority or fabricated external outcomes.

2. Ubiquitous Language and Subject Model

Subject	Required interpretation
ProviderPortalAccessModel	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit
ProviderPortalAccessModelVersion	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit
ProviderPortalAccessModelDecision	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit
ProviderPortalAccessModelEvidenceSet	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit
ProviderPortalAccessModelException	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit

Reference aggregate:

```
ProviderPortalAccessModel {  
  subjectId  
  tenantId  
  organizationContext  
  sourceIdentityRefs[]  
  sourceVersionRefs[]  
  lifecycleState  
  relationshipRefs[]  
  decisionRefs[]  
  intentRefs[]  
  evidenceSetRef  
  knowledgeCutoff  
  policyRefs[]  
  authorityRef  
  jurisdictionRefs[]  
  createdAt  
  effectiveAt  
  updatedAt  
  version  
  correctionOf?  
  correlationId  
}
```

2.1 Core invariants

- Stable identity precedes relationship, state, and cross-system correlation.
- Effective time and recorded time remain distinct where business truth changes over time.
- Recommendation, Decision, Intent, execution, and outcome are separate concepts.
- No Portal, report, search index, cache, workflow, or AI Agent becomes a shadow owner of Domain truth.
- Binding submitted, approved, issued, accepted, or signed versions are immutable.
- Corrections append governed facts and preserve the original record.
- External authority and provider outcomes retain their source and qualification.
- Tenant and represented-principal context come from trusted authentication and mandate evaluation.
- Retried writes are idempotent and concurrency guarded.
- Outcome Unknown is explicit and reconciled before risky duplicate execution.

2.2 Required standards

- stable identifiers
- typed contracts
- immutable binding versions

- transactional outbox
- idempotent Commands
- explicit Outcome Unknown
- correction lineage
- machine-verifiable conformance

3. Actors, Roles, and Authority

A conformant design distinguishes:

- the natural person acting;
- the service or AI identity invoking a Tool;
- the organization or principal represented;
- the role or relationship granting context;
- the mandate or delegation granting action authority;
- the Policy and jurisdiction limiting the action;
- the reviewer or approver responsible for a binding Decision.

Authority is evaluated at action time. Authentication alone does not grant business authority. Cached permissions and browser-supplied tenant headers are insufficient for high-impact actions.

4. Lifecycle and State Model

State	Semantics
PROPOSED	Distinct governed condition with entry, exit, timeout, correction and authority semantics
VALIDATION_PENDING	Distinct governed condition with entry, exit, timeout, correction and authority semantics
APPROVAL_PENDING	Distinct governed condition with entry, exit, timeout, correction and authority semantics
ACTIVE	Distinct governed condition with entry, exit, timeout, correction and authority semantics
SUSPENDED	Distinct governed condition with entry, exit, timeout, correction and authority semantics
CORRECTION_PENDING	Distinct governed condition with entry, exit, timeout, correction and authority semantics
RETIRED	Distinct governed condition with entry, exit, timeout, correction and authority semantics

```
stateDiagram-v2
    [*] --> PROPOSED
    PROPOSED --> VALIDATION_PENDING
    VALIDATION_PENDING --> APPROVAL_PENDING
    APPROVAL_PENDING --> ACTIVE
    ACTIVE --> SUSPENDED
    SUSPENDED --> CORRECTION_PENDING
    CORRECTION_PENDING --> RETIRED
```

The diagram is a primary reading path. Real implementations may add parallel review, amendment, appeal, timeout, suspension, partial completion, reconciliation, correction, and terminal failure without collapsing their meaning.

4.1 Transition rules

- transition through a typed, authorized Command;
- require exact expected version where concurrent change matters;
- record actor, represented principal, mandate, Policy, reason, and Evidence;
- use an idempotency key for retried writes;
- publish a completed-fact Event after durable state change;
- expose Outcome Unknown for unresolved external completion;
- preserve original and corrected states in historical reconstruction.

5. Decision, Evidence, and Knowledge Cutoff

Reference Decision:

```
Decision {
  decisionId
  decisionType
  subjectRef
  sourceVersionRefs[]
  knowledgeCutoff
  evidenceSetRef
  policyVersionRefs[]
  recommendationRefs[]
  principalId
  representedOrganizationId
  mandateRef
  rationale
  outcome
  decidedAt
  effectiveAt
  correctionOf?
}
```

Evidence records identify issuer or observer, subject, version, observed time, received time, effective interval, integrity, confidence, qualification, contradiction, correction, retention, residency, and access class. A recommendation may assist the Decision but cannot promote itself to the Decision.

6. Commands, Events, Queries, and Contracts

Reference Commands:

- CreateProviderPortalAccessModel
- ValidateProviderPortalAccessModel
- ApproveProviderPortalAccessModel
- ActivateProviderPortalAccessModel
- SuspendProviderPortalAccessModel
- CorrectProviderPortalAccessModel
- RetireProviderPortalAccessModel

Reference Events:

- ProviderPortalAccessModelCreated
- ProviderPortalAccessModelValidated
- ProviderPortalAccessModelApproved
- ProviderPortalAccessModelActivated
- ProviderPortalAccessModelSuspended
- ProviderPortalAccessModelCorrected
- ProviderPortalAccessModelRetired

Reference queries:

- GetProviderPortalAccessModel
- ListProviderPortalAccessModelRecords
- GetProviderPortalAccessModelTimeline
- GetProviderPortalAccessModelEvidence
- GetProviderPortalAccessModelDecisionPackage
- GetProviderPortalAccessModelExceptions
- GetProviderPortalAccessModelAuditTrail

Reference API surface:

```
POST /api/v1/providerportalaccessmodel/commands
GET  /api/v1/providerportalaccessmodel/{id}
GET  /api/v1/providerportalaccessmodel/{id}/timeline
GET  /api/v1/providerportalaccessmodel/{id}/evidence
GET  /api/v1/providerportalaccessmodel/{id}/decisions
POST /api/v1/providerportalaccessmodel/{id}/exceptions
POST /api/v1/providerportalaccessmodel/{id}/corrections
```

These endpoints are reference contracts, not claims that exact routes exist.

7. Workflow, Failure, and Compensation

flowchart TD

```
A[Validate identity version and authority] --> B[Collect required evidence]
B --> C{Policy and evidence gates pass?}
C -- No --> D[Open exception or request correction]
D --> B
C -- Yes --> E[Record Decision or execution Intent]
E --> F[Execute Domain command or external request]
F --> G{Outcome known?}
G -- Success --> H[Record fact and publish Event]
G -- Failure --> I[Record failure and compensation options]
G -- Unknown --> J[Enter Outcome Unknown]
J --> K[Query source or wait for verified callback]
K --> G
H --> L[Update projections and downstream workflow]
```

Representative failure modes:

- stale or wrong source version
- duplicate submission or replay
- external timeout after possible success
- contradictory source observations
- lost Event after committed state
- approval or mandate revoked during execution
- downstream action before a mandatory gate
- partial completion across multiple subjects
- evidence later retracted or corrected
- tenant, facility, channel or jurisdiction mismatch

Recovery shall query the authoritative source before duplicate execution, preserve partial success, use compensating Intent rather than destructive rewrite, publish corrections, quarantine high-impact ambiguity, and record affected downstream subjects.

8. Data and Persistence Architecture

Reference table families:

Table family	Purpose
providerportalaccessmodel_aggregate	authoritative subject
providerportalaccessmodel_version	immutable submitted, approved, issued, or signed versions
providerportalaccessmodel_relationship	governed relationships
providerportalaccessmodel_decision	binding Decisions and rationale
providerportalaccessmodel_evidence_link	provenance and evidence relationships
providerportalaccessmodel_event_outbox	transactional Event publication
providerportalaccessmodel_idempotency	duplicate-write protection
providerportalaccessmodel_exception	exception, claim, dispute, or hold
providerportalaccessmodel_correction	correction and supersession lineage
providerportalaccessmodel_audit	privileged action evidence

The owning service controls schema and migration. Cross-Domain references use stable identifiers or contracts. Analytics, reports, caches, search, and vector indexes remain projections. Backup, restore, retention, legal hold, privacy, residency, and decommissioning requirements are explicit.

9. Portal and Experience Requirements

- Provider Portal: primary experience for logistics, customs, carrier and service providers.
- Operator and support views: diagnose failed or ambiguous journeys without assuming Domain ownership.
- Domain services: own authoritative data and action eligibility; the Portal consumes typed contracts.

Every Portal displays exact version, owner, state, freshness, required action, and uncertainty. It supports loading, empty, partial, stale, denied, error, timeout, and Outcome Unknown states; accessibility; locale, currency, unit, date, and RTL/LTR correctness; evidence audit; safe retry; and correction history.

10. AI Participation and Tool Governance

Permitted AI tasks:

- extract and classify evidence
- detect anomalies and missing fields
- summarize timelines and contradictions
- recommend next actions with sources and uncertainty

AI shall not own Domain records, grant itself authority, suppress contradictions, silently edit approved versions, fabricate external outcomes, or execute high-impact actions outside typed Tools, policy, approval, idempotency, sandbox, and outcome observation.

Every Agent Run records source context, prompt/model/tool versions, structured output, confidence and limitations, Policy result, approval, Tool calls, provider responses, final outcome, and recovery actions.

11. Security, Privacy, and Trust Boundaries

- least privilege and separation of duties
- tenant, organization, facility, channel and jurisdiction isolation
- integrity protection for binding evidence
- verified external callbacks and anti-replay controls

Additional controls include secret isolation, callback signature verification, audit of privileged action, emergency-access review, sensitive-data minimization, purpose limitation, and threat models for impersonation, tampering, replay, confused deputy, fraud, prompt injection, and exfiltration.

12. Reliability, SLOs, and Operations

SLI	Reference objective
authoritative read availability	99.9% monthly unless a stricter tier applies
acknowledged Command durability	no acknowledged write may be silently lost
Event publication	99.9% within five minutes after committed fact
duplicate prevention	100% for same tenant, Command class, and idempotency key
binding Decision audit completeness	100%
state-state detection	bounded by business deadline

Dashboards and runbooks cover backlog, error budget, dependency failure, retry budget, DLQ, workflow stall, provider outage, reconciliation, capacity, backup/restore, release/rollback, incident command, and post-incident correction.

13. Testing and Continuous Conformance

- aggregate invariant and transition tests
- authorization, delegation, separation-of-duties and tenant-isolation tests
- idempotency and optimistic-concurrency tests
- database migration, key, constraint and rollback tests
- contract, outbox/inbox, duplicate, replay and DLQ tests
- workflow restart, timeout and compensation tests
- Portal E2E tests for success, partial, stale, denied, error and Outcome Unknown states
- accessibility, locale, currency, unit and RTL/LTR tests
- security adversarial, fraud and data-exfiltration tests
- AI evaluation, prompt-injection, policy-bypass and unauthorized-tool tests
- historical reconstruction, correction and audit-completeness tests
- performance, capacity, recovery and operational exercise tests

Release evidence links each invariant and control to the test, environment, input data, result, owner, and artifact proving it. Generated test counts never replace semantic coverage.

14. Repository Review Boundary

- This chapter is a repository-review specification. Exact executable implementation has not been inspected for every target behavior.
- Registered modules, catalog entries, README claims, frontend contracts, or plans are not proof of complete implementation.

Area	Classification
target aggregate, API, tables, state and workflow in this chapter	REFERENCE_ARCHITECTURE
registered module or catalog claim	DOCUMENTATION_ONLY_CLAIM until source inspection
uninspected integration	REQUIRES_REPOSITORY_REVIEW
behavior proven in another repository-grounded chapter	retain that chapter's evidence and classification
contradictory ownership or path claims	CONFLICT_REQUIRES_CANONICALIZATION

No statement upgrades implementation status merely because a file, directory, module name, frontend contract, database entry, plan, or report exists.

15. Worked Conformance Scenario

An authorized principal initiates a Command against an exact subject version. The service validates identity, tenant, mandate, Policy, Evidence, and idempotency. It records the state transition and outbox entry atomically. If an external dependency participates, timeout produces Outcome Unknown; reconciliation queries the source or waits for a verified callback instead of repeating the action blindly.

Portals show source, freshness, version, required action, and uncertainty. AI may extract, compare, summarize, detect anomalies, and recommend through typed Tools, but cannot own the subject or fabricate success. Later correction appends new facts, identifies affected projections and workflows, and preserves the historical Decision context.

16. Conformance Checklist

- ☐ stable identity and proposition ownership are explicit;
- ☐ authority and mandate are evaluated at action time;
- ☐ state, Recommendation, Decision, Intent, execution, and outcome remain distinct;
- ☐ Commands are typed, authorized, idempotent, and version guarded;
- ☐ Events describe completed facts;
- ☐ Evidence includes provenance, time, integrity, qualification, and correction;
- ☐ external outcomes retain their authority source;
- ☐ Portals show freshness and uncertainty;
- ☐ AI is bounded by typed Tools, Policy, approval, and outcome observation;
- ☐ security, tenant, facility, channel, and jurisdiction boundaries are enforced;
- ☐ Outcome Unknown and reconciliation exist where needed;
- ☐ corrections preserve history;
- ☐ tests prove invariants and recovery;
- ☐ implementation status is not upgraded without executable evidence.

17. Status Vocabulary

Status	Meaning
VERIFIED_IMPLEMENTED	Executable source and relevant behavior were inspected.
IMPLEMENTED_WITH_GAP	Executable behavior exists with a material governance or completeness gap.
PARTIAL_IMPLEMENTATION	Only part of the target capability is evidenced.
REFERENCE_ARCHITECTURE	Normative target behavior; no claim that it exists today.
PLANNED_NOT_IMPLEMENTED	Explicitly planned but not evidenced as executable.
DOCUMENTATION_ONLY_CLAIM	Documentation or client contract claims behavior without verified backend evidence.
CONFLICT_REQUIRES_CANONICALIZATION	Sources disagree and no final owner has been established.
REQUIRES_REPOSITORY_REVIEW	Necessary executable evidence has not yet been inspected.

Provider Portal – UX States, Accessibility, Localization, Analytics, and E2E

Metadata	Value
Volume	4
Chapter ID	V04-P06-03
Subject	ProviderPortalExperienceStandard
Status	Generated First-Draft Architecture Skeleton - Domain-Specific Expansion Required
Content maturity	TEMPLATE_DERIVED_REFERENCE_SKELETON unless repository citations prove otherwise
Default implementation classification	REFERENCE_ARCHITECTURE / REQUIRES_REPOSITORY_REVIEW
Accountable owner	Portal Architecture / Provider Portal
Evidence rule	No implementation claim without inspected executable evidence
Repository	chinair88-prog/allinb2c

1. Executive Orientation

This chapter defines how GTOS shall **specify loading, empty, partial, stale, error, denied, offline, accessibility, RTL/LTR, analytics, audit and test journeys for logistics, customs, carrier and service providers, covering profile, RFQ invitation, transport option, booking, customs, milestones, billing, settlement.**

The specification separates reality, observations, knowledge, Decisions, Intent, execution, and outcomes. A component name, database row, UI label, AI answer, or workflow state does not acquire authority merely because it is visible or technically convenient.

Reality or external outcome

- ≠ Observation
- ≠ Claim
- ≠ derived Perspective
- ≠ Prediction
- ≠ Recommendation
- ≠ authorized Decision
- ≠ execution Intent

1.1 Accountable ownership

The accountable owner is **Portal Architecture / Provider Portal**. Supporting applications, shared infrastructure, integration adapters, analytics, and AI coordinate or present the capability but shall not silently own its authoritative propositions.

1.2 Scope

- create and identify the subject
- validate evidence and policy
- make authorized Decisions
- execute typed Commands
- publish completed-fact Events
- query current and historical perspectives
- correct and reconcile outcomes

1.3 Non-goals

- treating a registered Gradle module, catalog record, README, frontend route, migration plan, or generated report as proof of end-to-end implementation;
- direct cross-Domain database writes;
- generic status values that combine lifecycle, approval, provider, document, payment, dispute, and correction state;
- silent replacement of history;
- AI-created authority or fabricated external outcomes.

2. Ubiquitous Language and Subject Model

Subject	Required interpretation
ProviderPortalExperienceStandard	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit
ProviderPortalExperienceStandardVersion	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit
ProviderPortalExperienceStandardDecision	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit
ProviderPortalExperienceStandardEvidenceSet	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit
ProviderPortalExperienceStandardException	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit

Reference aggregate:

```
ProviderPortalExperienceStandard {
  subjectId
  tenantId
  organizationContext
  sourceIdentityRefs[]
  sourceVersionRefs[]
  lifecycleState
  relationshipRefs[]
  decisionRefs[]
  intentRefs[]
  evidenceSetRef
  knowledgeCutoff
  policyRefs[]
  authorityRef
  jurisdictionRefs[]
  createdAt
  effectiveAt
  updatedAt
  version
  correctionOf?
  correlationId
}
```

2.1 Core invariants

- Stable identity precedes relationship, state, and cross-system correlation.
- Effective time and recorded time remain distinct where business truth changes over time.
- Recommendation, Decision, Intent, execution, and outcome are separate concepts.
- No Portal, report, search index, cache, workflow, or AI Agent becomes a shadow owner of Domain truth.
- Binding submitted, approved, issued, accepted, or signed versions are immutable.
- Corrections append governed facts and preserve the original record.
- External authority and provider outcomes retain their source and qualification.
- Tenant and represented-principal context come from trusted authentication and mandate evaluation.
- Retried writes are idempotent and concurrency guarded.
- Outcome Unknown is explicit and reconciled before risky duplicate execution.

2.2 Required standards

- stable identifiers
- typed contracts
- immutable binding versions

- transactional outbox
- idempotent Commands
- explicit Outcome Unknown
- correction lineage
- machine-verifiable conformance

3. Actors, Roles, and Authority

A conformant design distinguishes:

- the natural person acting;
- the service or AI identity invoking a Tool;
- the organization or principal represented;
- the role or relationship granting context;
- the mandate or delegation granting action authority;
- the Policy and jurisdiction limiting the action;
- the reviewer or approver responsible for a binding Decision.

Authority is evaluated at action time. Authentication alone does not grant business authority. Cached permissions and browser-supplied tenant headers are insufficient for high-impact actions.

4. Lifecycle and State Model

State	Semantics
PROPOSED	Distinct governed condition with entry, exit, timeout, correction and authority semantics
VALIDATION_PENDING	Distinct governed condition with entry, exit, timeout, correction and authority semantics
APPROVAL_PENDING	Distinct governed condition with entry, exit, timeout, correction and authority semantics
ACTIVE	Distinct governed condition with entry, exit, timeout, correction and authority semantics
SUSPENDED	Distinct governed condition with entry, exit, timeout, correction and authority semantics
CORRECTION_PENDING	Distinct governed condition with entry, exit, timeout, correction and authority semantics
RETIRED	Distinct governed condition with entry, exit, timeout, correction and authority semantics

```
stateDiagram-v2
    [*] --> PROPOSED
    PROPOSED --> VALIDATION_PENDING
    VALIDATION_PENDING --> APPROVAL_PENDING
    APPROVAL_PENDING --> ACTIVE
    ACTIVE --> SUSPENDED
    SUSPENDED --> CORRECTION_PENDING
    CORRECTION_PENDING --> RETIRED
```

The diagram is a primary reading path. Real implementations may add parallel review, amendment, appeal, timeout, suspension, partial completion, reconciliation, correction, and terminal failure without collapsing their meaning.

4.1 Transition rules

- transition through a typed, authorized Command;
- require exact expected version where concurrent change matters;
- record actor, represented principal, mandate, Policy, reason, and Evidence;
- use an idempotency key for retried writes;
- publish a completed-fact Event after durable state change;
- expose Outcome Unknown for unresolved external completion;
- preserve original and corrected states in historical reconstruction.

5. Decision, Evidence, and Knowledge Cutoff

Reference Decision:

```
Decision {
  decisionId
  decisionType
  subjectRef
  sourceVersionRefs[]
  knowledgeCutoff
  evidenceSetRef
  policyVersionRefs[]
  recommendationRefs[]
  principalId
  representedOrganizationId
  mandateRef
  rationale
  outcome
  decidedAt
  effectiveAt
  correctionOf?
}
```

Evidence records identify issuer or observer, subject, version, observed time, received time, effective interval, integrity, confidence, qualification, contradiction, correction, retention, residency, and access class. A recommendation may assist the Decision but cannot promote itself to the Decision.

6. Commands, Events, Queries, and Contracts

Reference Commands:

- CreateProviderPortalExperienceStandard
- ValidateProviderPortalExperienceStandard
- ApproveProviderPortalExperienceStandard
- ActivateProviderPortalExperienceStandard
- SuspendProviderPortalExperienceStandard
- CorrectProviderPortalExperienceStandard
- RetireProviderPortalExperienceStandard

Reference Events:

- ProviderPortalExperienceStandardCreated
- ProviderPortalExperienceStandardValidated
- ProviderPortalExperienceStandardApproved
- ProviderPortalExperienceStandardActivated
- ProviderPortalExperienceStandardSuspended
- ProviderPortalExperienceStandardCorrected
- ProviderPortalExperienceStandardRetired

Reference queries:

- GetProviderPortalExperienceStandard
- ListProviderPortalExperienceStandardRecords
- GetProviderPortalExperienceStandardTimeline
- GetProviderPortalExperienceStandardEvidence
- GetProviderPortalExperienceStandardDecisionPackage
- GetProviderPortalExperienceStandardExceptions
- GetProviderPortalExperienceStandardAuditTrail

Reference API surface:

```
POST /api/v1/providerportalexperiencstandard/commands
GET  /api/v1/providerportalexperiencstandard/{id}
GET  /api/v1/providerportalexperiencstandard/{id}/timeline
GET  /api/v1/providerportalexperiencstandard/{id}/evidence
GET  /api/v1/providerportalexperiencstandard/{id}/decisions
POST /api/v1/providerportalexperiencstandard/{id}/exceptions
POST /api/v1/providerportalexperiencstandard/{id}/corrections
```

These endpoints are reference contracts, not claims that exact routes exist.

7. Workflow, Failure, and Compensation

flowchart TD

```
A[Validate identity version and authority] --> B[Collect required evidence]
B --> C{Policy and evidence gates pass?}
C -- No --> D[Open exception or request correction]
D --> B
C -- Yes --> E[Record Decision or execution Intent]
E --> F[Execute Domain command or external request]
F --> G{Outcome known?}
G -- Success --> H[Record fact and publish Event]
G -- Failure --> I[Record failure and compensation options]
G -- Unknown --> J[Enter Outcome Unknown]
J --> K[Query source or wait for verified callback]
K --> G
H --> L[Update projections and downstream workflow]
```

Representative failure modes:

- stale or wrong source version
- duplicate submission or replay
- external timeout after possible success
- contradictory source observations
- lost Event after committed state
- approval or mandate revoked during execution
- downstream action before a mandatory gate
- partial completion across multiple subjects
- evidence later retracted or corrected
- tenant, facility, channel or jurisdiction mismatch

Recovery shall query the authoritative source before duplicate execution, preserve partial success, use compensating Intent rather than destructive rewrite, publish corrections, quarantine high-impact ambiguity, and record affected downstream subjects.

8. Data and Persistence Architecture

Reference table families:

Table family	Purpose
providerportalexperiencestandard_aggregate	authoritative subject
providerportalexperiencestandard_version	immutable submitted, approved, issued, or signed versions
providerportalexperiencestandard_relationship	governed relationships
providerportalexperiencestandard_decision	binding Decisions and rationale
providerportalexperiencestandard_evidence_link	provenance and evidence relationships
providerportalexperiencestandard_event_outbox	transactional Event publication
providerportalexperiencestandard_idempotency	duplicate-write protection
providerportalexperiencestandard_exception	exception, claim, dispute, or hold
providerportalexperiencestandard_correction	correction and supersession lineage
providerportalexperiencestandard_audit	privileged action evidence

The owning service controls schema and migration. Cross-Domain references use stable identifiers or contracts. Analytics, reports, caches, search, and vector indexes remain projections. Backup, restore, retention, legal hold, privacy, residency, and decommissioning requirements are explicit.

9. Portal and Experience Requirements

- Provider Portal: primary experience for logistics, customs, carrier and service providers.
- Operator and support views: diagnose failed or ambiguous journeys without assuming Domain ownership.
- Domain services: own authoritative data and action eligibility; the Portal consumes typed contracts.

Every Portal displays exact version, owner, state, freshness, required action, and uncertainty. It supports loading, empty, partial, stale, denied, error, timeout, and Outcome Unknown states; accessibility; locale, currency, unit, date, and RTL/LTR correctness; evidence audit; safe retry; and correction history.

10. AI Participation and Tool Governance

Permitted AI tasks:

- extract and classify evidence
- detect anomalies and missing fields
- summarize timelines and contradictions
- recommend next actions with sources and uncertainty

AI shall not own Domain records, grant itself authority, suppress contradictions, silently edit approved versions, fabricate external outcomes, or execute high-impact actions outside typed Tools, policy, approval, idempotency, sandbox, and outcome observation.

Every Agent Run records source context, prompt/model/tool versions, structured output, confidence and limitations, Policy result, approval, Tool calls, provider responses, final outcome, and recovery actions.

11. Security, Privacy, and Trust Boundaries

- least privilege and separation of duties
- tenant, organization, facility, channel and jurisdiction isolation
- integrity protection for binding evidence
- verified external callbacks and anti-replay controls

Additional controls include secret isolation, callback signature verification, audit of privileged action, emergency-access review, sensitive-data minimization, purpose limitation, and threat models for impersonation, tampering, replay, confused deputy, fraud, prompt injection, and exfiltration.

12. Reliability, SLOs, and Operations

SLI	Reference objective
authoritative read availability	99.9% monthly unless a stricter tier applies
acknowledged Command durability	no acknowledged write may be silently lost
Event publication	99.9% within five minutes after committed fact
duplicate prevention	100% for same tenant, Command class, and idempotency key
binding Decision audit completeness	100%
state-state detection	bounded by business deadline

Dashboards and runbooks cover backlog, error budget, dependency failure, retry budget, DLQ, workflow stall, provider outage, reconciliation, capacity, backup/restore, release/rollback, incident command, and post-incident correction.

13. Testing and Continuous Conformance

- aggregate invariant and transition tests
- authorization, delegation, separation-of-duties and tenant-isolation tests
- idempotency and optimistic-concurrency tests
- database migration, key, constraint and rollback tests
- contract, outbox/inbox, duplicate, replay and DLQ tests
- workflow restart, timeout and compensation tests
- Portal E2E tests for success, partial, stale, denied, error and Outcome Unknown states
- accessibility, locale, currency, unit and RTL/LTR tests
- security adversarial, fraud and data-exfiltration tests
- AI evaluation, prompt-injection, policy-bypass and unauthorized-tool tests
- historical reconstruction, correction and audit-completeness tests
- performance, capacity, recovery and operational exercise tests

Release evidence links each invariant and control to the test, environment, input data, result, owner, and artifact proving it. Generated test counts never replace semantic coverage.

14. Repository Review Boundary

- This chapter is a repository-review specification. Exact executable implementation has not been inspected for every target behavior.
- Registered modules, catalog entries, README claims, frontend contracts, or plans are not proof of complete implementation.

Area	Classification
target aggregate, API, tables, state and workflow in this chapter	REFERENCE_ARCHITECTURE
registered module or catalog claim	DOCUMENTATION_ONLY_CLAIM until source inspection
uninspected integration	REQUIRES_REPOSITORY_REVIEW
behavior proven in another repository-grounded chapter	retain that chapter's evidence and classification
contradictory ownership or path claims	CONFLICT_REQUIRES_CANONICALIZATION

No statement upgrades implementation status merely because a file, directory, module name, frontend contract, database entry, plan, or report exists.

15. Worked Conformance Scenario

An authorized principal initiates a Command against an exact subject version. The service validates identity, tenant, mandate, Policy, Evidence, and idempotency. It records the state transition and outbox entry atomically. If an external dependency participates, timeout produces Outcome Unknown; reconciliation queries the source or waits for a verified callback instead of repeating the action blindly.

Portals show source, freshness, version, required action, and uncertainty. AI may extract, compare, summarize, detect anomalies, and recommend through typed Tools, but cannot own the subject or fabricate success. Later correction appends new facts, identifies affected projections and workflows, and preserves the historical Decision context.

16. Conformance Checklist

- ☐ stable identity and proposition ownership are explicit;
- ☐ authority and mandate are evaluated at action time;
- ☐ state, Recommendation, Decision, Intent, execution, and outcome remain distinct;
- ☐ Commands are typed, authorized, idempotent, and version guarded;
- ☐ Events describe completed facts;
- ☐ Evidence includes provenance, time, integrity, qualification, and correction;
- ☐ external outcomes retain their authority source;
- ☐ Portals show freshness and uncertainty;
- ☐ AI is bounded by typed Tools, Policy, approval, and outcome observation;
- ☐ security, tenant, facility, channel, and jurisdiction boundaries are enforced;
- ☐ Outcome Unknown and reconciliation exist where needed;
- ☐ corrections preserve history;
- ☐ tests prove invariants and recovery;
- ☐ implementation status is not upgraded without executable evidence.

17. Status Vocabulary

Status	Meaning
VERIFIED_IMPLEMENTED	Executable source and relevant behavior were inspected. Executable behavior exists with a material governance or completeness gap.
IMPLEMENTED_WITH_GAP	
PARTIAL_IMPLEMENTATION	Only part of the target capability is evidenced.
REFERENCE_ARCHITECTURE	Normative target behavior; no claim that it exists today.
PLANNED_NOT_IMPLEMENTED	Explicitly planned but not evidenced as executable.
DOCUMENTATION_ONLY_CLAIM	Documentation or client contract claims behavior without verified backend evidence.
CONFLICT_REQUIRES_CANONICALIZATION	Sources disagree and no final owner has been established.
REQUIRES_REPOSITORY_REVIEW	Necessary executable evidence has not yet been inspected.

Partner Portal — Portal Orientation and Information Architecture

Metadata	Value
Volume	4
Chapter ID	V04-P07-00
Subject	PartnerPortalPortal
Status	Generated First-Draft Architecture Skeleton - Domain-Specific Expansion Required
Content maturity	TEMPLATE_DERIVED_REFERENCE_SKELETON unless repository citations prove otherwise
Default implementation classification	REFERENCE_ARCHITECTURE / REQUIRES_REPOSITORY_REVIEW
Accountable owner	Portal Architecture / Partner Portal
Evidence rule	No implementation claim without inspected executable evidence
Repository	chinair88-prog/allinb2c

1. Executive Orientation

This chapter defines how GTOS shall **define personas, navigation, route ownership, domain dependencies and experience boundaries for suppliers, factories and commercial partners, covering profile, products, quotations, PI, PO, production, quality, documents, settlement.**

The specification separates reality, observations, knowledge, Decisions, Intent, execution, and outcomes. A component name, database row, UI label, AI answer, or workflow state does not acquire authority merely because it is visible or technically convenient.

Reality or external outcome

- ≠ Observation
- ≠ Claim
- ≠ derived Perspective
- ≠ Prediction
- ≠ Recommendation
- ≠ authorized Decision
- ≠ execution Intent

1.1 Accountable ownership

The accountable owner is **Portal Architecture / Partner Portal**. Supporting applications, shared infrastructure, integration adapters, analytics, and AI coordinate or present the capability but shall not silently own its authoritative propositions.

1.2 Scope

- create and identify the subject
- validate evidence and policy
- make authorized Decisions
- execute typed Commands
- publish completed-fact Events
- query current and historical perspectives
- correct and reconcile outcomes

1.3 Non-goals

- treating a registered Gradle module, catalog record, README, frontend route, migration plan, or generated report as proof of end-to-end implementation;
- direct cross-Domain database writes;
- generic status values that combine lifecycle, approval, provider, document, payment, dispute, and correction state;
- silent replacement of history;
- AI-created authority or fabricated external outcomes.

2. Ubiquitous Language and Subject Model

Subject	Required interpretation
PartnerPortalPortal	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit
PartnerPortalPortalVersion	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit
PartnerPortalPortalDecision	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit
PartnerPortalPortalEvidenceSet	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit
PartnerPortalPortalException	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit

Reference aggregate:

```
PartnerPortalPortal {
  subjectId
  tenantId
  organizationContext
  sourceIdentityRefs[]
  sourceVersionRefs[]
  lifecycleState
  relationshipRefs[]
  decisionRefs[]
  intentRefs[]
  evidenceSetRef
  knowledgeCutoff
  policyRefs[]
  authorityRef
  jurisdictionRefs[]
  createdAt
  effectiveAt
  updatedAt
  version
  correctionOf?
  correlationId
}
```

2.1 Core invariants

- Stable identity precedes relationship, state, and cross-system correlation.
- Effective time and recorded time remain distinct where business truth changes over time.
- Recommendation, Decision, Intent, execution, and outcome are separate concepts.
- No Portal, report, search index, cache, workflow, or AI Agent becomes a shadow owner of Domain truth.
- Binding submitted, approved, issued, accepted, or signed versions are immutable.
- Corrections append governed facts and preserve the original record.
- External authority and provider outcomes retain their source and qualification.
- Tenant and represented-principal context come from trusted authentication and mandate evaluation.
- Retried writes are idempotent and concurrency guarded.
- Outcome Unknown is explicit and reconciled before risky duplicate execution.

2.2 Required standards

- stable identifiers
- typed contracts
- immutable binding versions

- transactional outbox
- idempotent Commands
- explicit Outcome Unknown
- correction lineage
- machine-verifiable conformance

3. Actors, Roles, and Authority

- A conformant design distinguishes:
- the natural person acting;
 - the service or AI identity invoking a Tool;
 - the organization or principal represented;
 - the role or relationship granting context;
 - the mandate or delegation granting action authority;
 - the Policy and jurisdiction limiting the action;
 - the reviewer or approver responsible for a binding Decision.

Authority is evaluated at action time. Authentication alone does not grant business authority. Cached permissions and browser-supplied tenant headers are insufficient for high-impact actions.

4. Lifecycle and State Model

State	Semantics
PROPOSED	Distinct governed condition with entry, exit, timeout, correction and authority semantics
VALIDATION_PENDING	Distinct governed condition with entry, exit, timeout, correction and authority semantics
APPROVAL_PENDING	Distinct governed condition with entry, exit, timeout, correction and authority semantics
ACTIVE	Distinct governed condition with entry, exit, timeout, correction and authority semantics
SUSPENDED	Distinct governed condition with entry, exit, timeout, correction and authority semantics
CORRECTION_PENDING	Distinct governed condition with entry, exit, timeout, correction and authority semantics
RETIRED	Distinct governed condition with entry, exit, timeout, correction and authority semantics

```
stateDiagram-v2
    [*] --> PROPOSED
    PROPOSED --> VALIDATION_PENDING
    VALIDATION_PENDING --> APPROVAL_PENDING
    APPROVAL_PENDING --> ACTIVE
    ACTIVE --> SUSPENDED
    SUSPENDED --> CORRECTION_PENDING
    CORRECTION_PENDING --> RETIRED
```

The diagram is a primary reading path. Real implementations may add parallel review, amendment, appeal, timeout, suspension, partial completion, reconciliation, correction, and terminal failure without collapsing their meaning.

4.1 Transition rules

- transition through a typed, authorized Command;
- require exact expected version where concurrent change matters;
- record actor, represented principal, mandate, Policy, reason, and Evidence;
- use an idempotency key for retried writes;
- publish a completed-fact Event after durable state change;
- expose Outcome Unknown for unresolved external completion;
- preserve original and corrected states in historical reconstruction.

5. Decision, Evidence, and Knowledge Cutoff

Reference Decision:

```
Decision {
  decisionId
  decisionType
  subjectRef
  sourceVersionRefs[]
  knowledgeCutoff
  evidenceSetRef
  policyVersionRefs[]
  recommendationRefs[]
  principalId
  representedOrganizationId
  mandateRef
  rationale
  outcome
  decidedAt
  effectiveAt
  correctionOf?
}
```

Evidence records identify issuer or observer, subject, version, observed time, received time, effective interval, integrity, confidence, qualification, contradiction, correction, retention, residency, and access class. A recommendation may assist the Decision but cannot promote itself to the Decision.

6. Commands, Events, Queries, and Contracts

Reference Commands:

- CreatePartnerPortalPortal
- ValidatePartnerPortalPortal
- ApprovePartnerPortalPortal
- ActivatePartnerPortalPortal
- SuspendPartnerPortalPortal
- CorrectPartnerPortalPortal
- RetirePartnerPortalPortal

Reference Events:

- PartnerPortalPortalCreated
- PartnerPortalPortalValidated
- PartnerPortalPortalApproved
- PartnerPortalPortalActivated
- PartnerPortalPortalSuspended
- PartnerPortalPortalCorrected
- PartnerPortalPortalRetired

Reference queries:

- GetPartnerPortalPortal
- ListPartnerPortalPortalRecords
- GetPartnerPortalPortalTimeline
- GetPartnerPortalPortalEvidence
- GetPartnerPortalPortalDecisionPackage
- GetPartnerPortalPortalExceptions
- GetPartnerPortalPortalAuditTrail

Reference API surface:

```
POST /api/v1/partnerportalportal/commands
GET  /api/v1/partnerportalportal/{id}
GET  /api/v1/partnerportalportal/{id}/timeline
GET  /api/v1/partnerportalportal/{id}/evidence
GET  /api/v1/partnerportalportal/{id}/decisions
POST /api/v1/partnerportalportal/{id}/exceptions
POST /api/v1/partnerportalportal/{id}/corrections
```

These endpoints are reference contracts, not claims that exact routes exist.

7. Workflow, Failure, and Compensation

```
flowchart TD
    A[Validate identity version and authority] --> B[Collect required evidence]
    B --> C{Policy and evidence gates pass?}
    C -- No --> D[Open exception or request correction]
    D --> B
    C -- Yes --> E[Record Decision or execution Intent]
    E --> F[Execute Domain command or external request]
    F --> G{Outcome known?}
    G -- Success --> H[Record fact and publish Event]
    G -- Failure --> I[Record failure and compensation options]
    G -- Unknown --> J[Enter Outcome Unknown]
    J --> K[Query source or wait for verified callback]
    K --> G
    H --> L[Update projections and downstream workflow]
```

Representative failure modes:

- stale or wrong source version
- duplicate submission or replay
- external timeout after possible success
- contradictory source observations
- lost Event after committed state
- approval or mandate revoked during execution
- downstream action before a mandatory gate
- partial completion across multiple subjects
- evidence later retracted or corrected
- tenant, facility, channel or jurisdiction mismatch

Recovery shall query the authoritative source before duplicate execution, preserve partial success, use compensating Intent rather than destructive rewrite, publish corrections, quarantine high-impact ambiguity, and record affected downstream subjects.

8. Data and Persistence Architecture

Reference table families:

Table family	Purpose
partnerportalportal_aggregate	authoritative subject
partnerportalportal_version	immutable submitted, approved, issued, or signed versions
partnerportalportal_relationship	governed relationships
partnerportalportal_decision	binding Decisions and rationale
partnerportalportal_evidence_link	provenance and evidence relationships
partnerportalportal_event_outbox	transactional Event publication
partnerportalportal_idempotency	duplicate-write protection
partnerportalportal_exception	exception, claim, dispute, or hold
partnerportalportal_correction	correction and supersession lineage
partnerportalportal_audit	privileged action evidence

The owning service controls schema and migration. Cross-Domain references use stable identifiers or contracts. Analytics, reports, caches, search, and vector indexes remain projections. Backup, restore, retention, legal hold, privacy, residency, and decommissioning requirements are explicit.

9. Portal and Experience Requirements

- Partner Portal: primary experience for suppliers, factories and commercial partners.
- Operator and support views: diagnose failed or ambiguous journeys without assuming Domain ownership.
- Domain services: own authoritative data and action eligibility; the Portal consumes typed contracts.

Every Portal displays exact version, owner, state, freshness, required action, and uncertainty. It supports loading, empty, partial, stale, denied, error, timeout, and Outcome Unknown states; accessibility; locale, currency, unit, date, and RTL/LTR correctness; evidence audit; safe retry; and correction history.

10. AI Participation and Tool Governance

Permitted AI tasks:

- extract and classify evidence
- detect anomalies and missing fields
- summarize timelines and contradictions
- recommend next actions with sources and uncertainty

AI shall not own Domain records, grant itself authority, suppress contradictions, silently edit approved versions, fabricate external outcomes, or execute high-impact actions outside typed Tools, policy, approval, idempotency, sandbox, and outcome observation.

Every Agent Run records source context, prompt/model/tool versions, structured output, confidence and limitations, Policy result, approval, Tool calls, provider responses, final outcome, and recovery actions.

11. Security, Privacy, and Trust Boundaries

- least privilege and separation of duties
- tenant, organization, facility, channel and jurisdiction isolation
- integrity protection for binding evidence
- verified external callbacks and anti-replay controls

Additional controls include secret isolation, callback signature verification, audit of privileged action, emergency-access review, sensitive-data minimization, purpose limitation, and threat models for impersonation, tampering, replay, confused deputy, fraud, prompt injection, and exfiltration.

12. Reliability, SLOs, and Operations

SLI	Reference objective
authoritative read availability	99.9% monthly unless a stricter tier applies
acknowledged Command durability	no acknowledged write may be silently lost
Event publication	99.9% within five minutes after committed fact
duplicate prevention	100% for same tenant, Command class, and idempotency key
binding Decision audit completeness	100%
state-state detection	bounded by business deadline

Dashboards and runbooks cover backlog, error budget, dependency failure, retry budget, DLQ, workflow stall, provider outage, reconciliation, capacity, backup/restore, release/rollback, incident command, and post-incident correction.

13. Testing and Continuous Conformance

- aggregate invariant and transition tests
- authorization, delegation, separation-of-duties and tenant-isolation tests
- idempotency and optimistic-concurrency tests
- database migration, key, constraint and rollback tests
- contract, outbox/inbox, duplicate, replay and DLQ tests
- workflow restart, timeout and compensation tests
- Portal E2E tests for success, partial, stale, denied, error and Outcome Unknown states
- accessibility, locale, currency, unit and RTL/LTR tests
- security adversarial, fraud and data-exfiltration tests
- AI evaluation, prompt-injection, policy-bypass and unauthorized-tool tests
- historical reconstruction, correction and audit-completeness tests
- performance, capacity, recovery and operational exercise tests

Release evidence links each invariant and control to the test, environment, input data, result, owner, and artifact proving it. Generated test counts never replace semantic coverage.

14. Repository Review Boundary

- This chapter is a repository-review specification. Exact executable implementation has not been inspected for every target behavior.
- Registered modules, catalog entries, README claims, frontend contracts, or plans are not proof of complete implementation.

Area	Classification
target aggregate, API, tables, state and workflow in this chapter	REFERENCE_ARCHITECTURE
registered module or catalog claim	DOCUMENTATION_ONLY_CLAIM until source inspection
uninspected integration	REQUIRES_REPOSITORY_REVIEW
behavior proven in another repository-grounded chapter	retain that chapter's evidence and classification
contradictory ownership or path claims	CONFLICT_REQUIRES_CANONICALIZATION

No statement upgrades implementation status merely because a file, directory, module name, frontend contract, database entry, plan, or report exists.

15. Worked Conformance Scenario

An authorized principal initiates a Command against an exact subject version. The service validates identity, tenant, mandate, Policy, Evidence, and idempotency. It records the state transition and outbox entry atomically. If an external dependency participates, timeout produces Outcome Unknown; reconciliation queries the source or waits for a verified callback instead of repeating the action blindly.

Portals show source, freshness, version, required action, and uncertainty. AI may extract, compare, summarize, detect anomalies, and recommend through typed Tools, but cannot own the subject or fabricate success. Later correction appends new facts, identifies affected projections and workflows, and preserves the historical Decision context.

16. Conformance Checklist

- ☐ stable identity and proposition ownership are explicit;
- ☐ authority and mandate are evaluated at action time;
- ☐ state, Recommendation, Decision, Intent, execution, and outcome remain distinct;
- ☐ Commands are typed, authorized, idempotent, and version guarded;
- ☐ Events describe completed facts;
- ☐ Evidence includes provenance, time, integrity, qualification, and correction;
- ☐ external outcomes retain their authority source;
- ☐ Portals show freshness and uncertainty;
- ☐ AI is bounded by typed Tools, Policy, approval, and outcome observation;
- ☐ security, tenant, facility, channel, and jurisdiction boundaries are enforced;
- ☐ Outcome Unknown and reconciliation exist where needed;
- ☐ corrections preserve history;
- ☐ tests prove invariants and recovery;
- ☐ implementation status is not upgraded without executable evidence.

17. Status Vocabulary

Status	Meaning
VERIFIED_IMPLEMENTED	Executable source and relevant behavior were inspected. Executable behavior exists with a material governance or completeness gap.
IMPLEMENTED_WITH_GAP	
PARTIAL_IMPLEMENTATION	Only part of the target capability is evidenced.
REFERENCE_ARCHITECTURE	Normative target behavior; no claim that it exists today.
PLANNED_NOT_IMPLEMENTED	Explicitly planned but not evidenced as executable.
DOCUMENTATION_ONLY_CLAIM	Documentation or client contract claims behavior without verified backend evidence.
CONFLICT_REQUIRES_CANONICALIZATION	Sources disagree and no final owner has been established.
REQUIRES_REPOSITORY_REVIEW	Necessary executable evidence has not yet been inspected.

Partner Portal — Routes, Pages, Components, and BFF Contracts

Metadata	Value
Volume	4
Chapter ID	V04-P07-01
Subject	PartnerPortalRouteRegistry
Status	Generated First-Draft Architecture Skeleton - Domain-Specific Expansion Required
Content maturity	TEMPLATE_DERIVED_REFERENCE_SKELETON unless repository citations prove otherwise
Default implementation classification	REFERENCE_ARCHITECTURE / REQUIRES_REPOSITORY_REVIEW
Accountable owner	Portal Architecture / Partner Portal
Evidence rule	No implementation claim without inspected executable evidence
Repository	chinair88-prog/allinb2c

1. Executive Orientation

This chapter defines how GTOS shall **inventory routes, layouts, pages, components, server/client boundaries, BFFs, APIs, realtime channels and ownership for suppliers, factories and commercial partners, covering profile, products, quotations, PI, PO, production, quality, documents, settlement.**

The specification separates reality, observations, knowledge, Decisions, Intent, execution, and outcomes. A component name, database row, UI label, AI answer, or workflow state does not acquire authority merely because it is visible or technically convenient.

Reality or external outcome

- ≠ Observation
- ≠ Claim
- ≠ derived Perspective
- ≠ Prediction
- ≠ Recommendation
- ≠ authorized Decision
- ≠ execution Intent

1.1 Accountable ownership

The accountable owner is **Portal Architecture / Partner Portal**. Supporting applications, shared infrastructure, integration adapters, analytics, and AI coordinate or present the capability but shall not silently own its authoritative propositions.

1.2 Scope

- create and identify the subject
- validate evidence and policy
- make authorized Decisions
- execute typed Commands
- publish completed-fact Events
- query current and historical perspectives
- correct and reconcile outcomes

1.3 Non-goals

- treating a registered Gradle module, catalog record, README, frontend route, migration plan, or generated report as proof of end-to-end implementation;
- direct cross-Domain database writes;
- generic status values that combine lifecycle, approval, provider, document, payment, dispute, and correction state;
- silent replacement of history;
- AI-created authority or fabricated external outcomes.

2. Ubiquitous Language and Subject Model

Subject	Required interpretation
PartnerPortalRouteRegistry	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit
PartnerPortalRouteRegistryVersion	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit
PartnerPortalRouteRegistryDecision	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit
PartnerPortalRouteRegistryEvidenceSet	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit
PartnerPortalRouteRegistryException	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit

Reference aggregate:

```
PartnerPortalRouteRegistry {  
  subjectId  
  tenantId  
  organizationContext  
  sourceIdentityRefs[]  
  sourceVersionRefs[]  
  lifecycleState  
  relationshipRefs[]  
  decisionRefs[]  
  intentRefs[]  
  evidenceSetRef  
  knowledgeCutoff  
  policyRefs[]  
  authorityRef  
  jurisdictionRefs[]  
  createdAt  
  effectiveAt  
  updatedAt  
  version  
  correctionOf?  
  correlationId  
}
```

2.1 Core invariants

- Stable identity precedes relationship, state, and cross-system correlation.
- Effective time and recorded time remain distinct where business truth changes over time.
- Recommendation, Decision, Intent, execution, and outcome are separate concepts.
- No Portal, report, search index, cache, workflow, or AI Agent becomes a shadow owner of Domain truth.
- Binding submitted, approved, issued, accepted, or signed versions are immutable.
- Corrections append governed facts and preserve the original record.
- External authority and provider outcomes retain their source and qualification.
- Tenant and represented-principal context come from trusted authentication and mandate evaluation.
- Retried writes are idempotent and concurrency guarded.
- Outcome Unknown is explicit and reconciled before risky duplicate execution.

2.2 Required standards

- stable identifiers
- typed contracts
- immutable binding versions

- transactional outbox
- idempotent Commands
- explicit Outcome Unknown
- correction lineage
- machine-verifiable conformance

3. Actors, Roles, and Authority

- A conformant design distinguishes:
- the natural person acting;
 - the service or AI identity invoking a Tool;
 - the organization or principal represented;
 - the role or relationship granting context;
 - the mandate or delegation granting action authority;
 - the Policy and jurisdiction limiting the action;
 - the reviewer or approver responsible for a binding Decision.

Authority is evaluated at action time. Authentication alone does not grant business authority. Cached permissions and browser-supplied tenant headers are insufficient for high-impact actions.

4. Lifecycle and State Model

State	Semantics
PROPOSED	Distinct governed condition with entry, exit, timeout, correction and authority semantics
VALIDATION_PENDING	Distinct governed condition with entry, exit, timeout, correction and authority semantics
APPROVAL_PENDING	Distinct governed condition with entry, exit, timeout, correction and authority semantics
ACTIVE	Distinct governed condition with entry, exit, timeout, correction and authority semantics
SUSPENDED	Distinct governed condition with entry, exit, timeout, correction and authority semantics
CORRECTION_PENDING	Distinct governed condition with entry, exit, timeout, correction and authority semantics
RETIRED	Distinct governed condition with entry, exit, timeout, correction and authority semantics

```
stateDiagram-v2
    [*] --> PROPOSED
    PROPOSED --> VALIDATION_PENDING
    VALIDATION_PENDING --> APPROVAL_PENDING
    APPROVAL_PENDING --> ACTIVE
    ACTIVE --> SUSPENDED
    SUSPENDED --> CORRECTION_PENDING
    CORRECTION_PENDING --> RETIRED
```

The diagram is a primary reading path. Real implementations may add parallel review, amendment, appeal, timeout, suspension, partial completion, reconciliation, correction, and terminal failure without collapsing their meaning.

4.1 Transition rules

- transition through a typed, authorized Command;
- require exact expected version where concurrent change matters;
- record actor, represented principal, mandate, Policy, reason, and Evidence;
- use an idempotency key for retried writes;
- publish a completed-fact Event after durable state change;
- expose Outcome Unknown for unresolved external completion;
- preserve original and corrected states in historical reconstruction.

5. Decision, Evidence, and Knowledge Cutoff

Reference Decision:

```
Decision {
  decisionId
  decisionType
  subjectRef
  sourceVersionRefs[]
  knowledgeCutoff
  evidenceSetRef
  policyVersionRefs[]
  recommendationRefs[]
  principalId
  representedOrganizationId
  mandateRef
  rationale
  outcome
  decidedAt
  effectiveAt
  correctionOf?
}
```

Evidence records identify issuer or observer, subject, version, observed time, received time, effective interval, integrity, confidence, qualification, contradiction, correction, retention, residency, and access class. A recommendation may assist the Decision but cannot promote itself to the Decision.

6. Commands, Events, Queries, and Contracts

Reference Commands:

- CreatePartnerPortalRouteRegistry
- ValidatePartnerPortalRouteRegistry
- ApprovePartnerPortalRouteRegistry
- ActivatePartnerPortalRouteRegistry
- SuspendPartnerPortalRouteRegistry
- CorrectPartnerPortalRouteRegistry
- RetirePartnerPortalRouteRegistry

Reference Events:

- PartnerPortalRouteRegistryCreated
- PartnerPortalRouteRegistryValidated
- PartnerPortalRouteRegistryApproved
- PartnerPortalRouteRegistryActivated
- PartnerPortalRouteRegistrySuspended
- PartnerPortalRouteRegistryCorrected
- PartnerPortalRouteRegistryRetired

Reference queries:

- GetPartnerPortalRouteRegistry
- ListPartnerPortalRouteRegistryRecords
- GetPartnerPortalRouteRegistryTimeline
- GetPartnerPortalRouteRegistryEvidence
- GetPartnerPortalRouteRegistryDecisionPackage
- GetPartnerPortalRouteRegistryExceptions
- GetPartnerPortalRouteRegistryAuditTrail

Reference API surface:

```
POST /api/v1/partnerportalrouterregistry/commands
GET  /api/v1/partnerportalrouterregistry/{id}
GET  /api/v1/partnerportalrouterregistry/{id}/timeline
GET  /api/v1/partnerportalrouterregistry/{id}/evidence
GET  /api/v1/partnerportalrouterregistry/{id}/decisions
POST /api/v1/partnerportalrouterregistry/{id}/exceptions
POST /api/v1/partnerportalrouterregistry/{id}/corrections
```

These endpoints are reference contracts, not claims that exact routes exist.

7. Workflow, Failure, and Compensation

```
flowchart TD
    A[Validate identity version and authority] --> B[Collect required evidence]
    B --> C{Policy and evidence gates pass?}
    C -- No --> D[Open exception or request correction]
    D --> B
    C -- Yes --> E[Record Decision or execution Intent]
    E --> F[Execute Domain command or external request]
    F --> G{Outcome known?}
    G -- Success --> H[Record fact and publish Event]
    G -- Failure --> I[Record failure and compensation options]
    G -- Unknown --> J[Enter Outcome Unknown]
    J --> K[Query source or wait for verified callback]
    K --> G
    H --> L[Update projections and downstream workflow]
```

Representative failure modes:

- stale or wrong source version
- duplicate submission or replay
- external timeout after possible success
- contradictory source observations
- lost Event after committed state
- approval or mandate revoked during execution
- downstream action before a mandatory gate
- partial completion across multiple subjects
- evidence later retracted or corrected
- tenant, facility, channel or jurisdiction mismatch

Recovery shall query the authoritative source before duplicate execution, preserve partial success, use compensating Intent rather than destructive rewrite, publish corrections, quarantine high-impact ambiguity, and record affected downstream subjects.

8. Data and Persistence Architecture

Reference table families:

Table family	Purpose
partnerportalrouterregistry_aggregate	authoritative subject
partnerportalrouterregistry_version	immutable submitted, approved, issued, or signed versions
partnerportalrouterregistry_relationship	governed relationships
partnerportalrouterregistry_decision	binding Decisions and rationale
partnerportalrouterregistry_evidence_link	provenance and evidence relationships
partnerportalrouterregistry_event_outbox	transactional Event publication
partnerportalrouterregistry_idempotency	duplicate-write protection
partnerportalrouterregistry_exception	exception, claim, dispute, or hold
partnerportalrouterregistry_correction	correction and supersession lineage
partnerportalrouterregistry_audit	privileged action evidence

The owning service controls schema and migration. Cross-Domain references use stable identifiers or contracts. Analytics, reports, caches, search, and vector indexes remain projections. Backup, restore, retention, legal hold, privacy, residency, and decommissioning requirements are explicit.

9. Portal and Experience Requirements

- Partner Portal: primary experience for suppliers, factories and commercial partners.
- Operator and support views: diagnose failed or ambiguous journeys without assuming Domain ownership.
- Domain services: own authoritative data and action eligibility; the Portal consumes typed contracts.

Every Portal displays exact version, owner, state, freshness, required action, and uncertainty. It supports loading, empty, partial, stale, denied, error, timeout, and Outcome Unknown states; accessibility; locale, currency, unit, date, and RTL/LTR correctness; evidence audit; safe retry; and correction history.

10. AI Participation and Tool Governance

Permitted AI tasks:

- extract and classify evidence
- detect anomalies and missing fields
- summarize timelines and contradictions
- recommend next actions with sources and uncertainty

AI shall not own Domain records, grant itself authority, suppress contradictions, silently edit approved versions, fabricate external outcomes, or execute high-impact actions outside typed Tools, policy, approval, idempotency, sandbox, and outcome observation.

Every Agent Run records source context, prompt/model/tool versions, structured output, confidence and limitations, Policy result, approval, Tool calls, provider responses, final outcome, and recovery actions.

11. Security, Privacy, and Trust Boundaries

- least privilege and separation of duties
- tenant, organization, facility, channel and jurisdiction isolation
- integrity protection for binding evidence
- verified external callbacks and anti-replay controls

Additional controls include secret isolation, callback signature verification, audit of privileged action, emergency-access review, sensitive-data minimization, purpose limitation, and threat models for impersonation, tampering, replay, confused deputy, fraud, prompt injection, and exfiltration.

12. Reliability, SLOs, and Operations

SLI	Reference objective
authoritative read availability	99.9% monthly unless a stricter tier applies
acknowledged Command durability	no acknowledged write may be silently lost
Event publication	99.9% within five minutes after committed fact
duplicate prevention	100% for same tenant, Command class, and idempotency key
binding Decision audit completeness	100%
state-state detection	bounded by business deadline

Dashboards and runbooks cover backlog, error budget, dependency failure, retry budget, DLQ, workflow stall, provider outage, reconciliation, capacity, backup/restore, release/rollback, incident command, and post-incident correction.

13. Testing and Continuous Conformance

- aggregate invariant and transition tests
- authorization, delegation, separation-of-duties and tenant-isolation tests
- idempotency and optimistic-concurrency tests
- database migration, key, constraint and rollback tests
- contract, outbox/inbox, duplicate, replay and DLQ tests
- workflow restart, timeout and compensation tests
- Portal E2E tests for success, partial, stale, denied, error and Outcome Unknown states
- accessibility, locale, currency, unit and RTL/LTR tests
- security adversarial, fraud and data-exfiltration tests
- AI evaluation, prompt-injection, policy-bypass and unauthorized-tool tests
- historical reconstruction, correction and audit-completeness tests
- performance, capacity, recovery and operational exercise tests

Release evidence links each invariant and control to the test, environment, input data, result, owner, and artifact proving it. Generated test counts never replace semantic coverage.

14. Repository Review Boundary

- This chapter is a repository-review specification. Exact executable implementation has not been inspected for every target behavior.
- Registered modules, catalog entries, README claims, frontend contracts, or plans are not proof of complete implementation.

Area	Classification
target aggregate, API, tables, state and workflow in this chapter	REFERENCE_ARCHITECTURE
registered module or catalog claim	DOCUMENTATION_ONLY_CLAIM until source inspection
uninspected integration	REQUIRES_REPOSITORY_REVIEW
behavior proven in another repository-grounded chapter	retain that chapter's evidence and classification
contradictory ownership or path claims	CONFLICT_REQUIRES_CANONICALIZATION

No statement upgrades implementation status merely because a file, directory, module name, frontend contract, database entry, plan, or report exists.

15. Worked Conformance Scenario

An authorized principal initiates a Command against an exact subject version. The service validates identity, tenant, mandate, Policy, Evidence, and idempotency. It records the state transition and outbox entry atomically. If an external dependency participates, timeout produces Outcome Unknown; reconciliation queries the source or waits for a verified callback instead of repeating the action blindly.

Portals show source, freshness, version, required action, and uncertainty. AI may extract, compare, summarize, detect anomalies, and recommend through typed Tools, but cannot own the subject or fabricate success. Later correction appends new facts, identifies affected projections and workflows, and preserves the historical Decision context.

16. Conformance Checklist

- ☐ stable identity and proposition ownership are explicit;
- ☐ authority and mandate are evaluated at action time;
- ☐ state, Recommendation, Decision, Intent, execution, and outcome remain distinct;
- ☐ Commands are typed, authorized, idempotent, and version guarded;
- ☐ Events describe completed facts;
- ☐ Evidence includes provenance, time, integrity, qualification, and correction;
- ☐ external outcomes retain their authority source;
- ☐ Portals show freshness and uncertainty;
- ☐ AI is bounded by typed Tools, Policy, approval, and outcome observation;
- ☐ security, tenant, facility, channel, and jurisdiction boundaries are enforced;
- ☐ Outcome Unknown and reconciliation exist where needed;
- ☐ corrections preserve history;
- ☐ tests prove invariants and recovery;
- ☐ implementation status is not upgraded without executable evidence.

17. Status Vocabulary

Status	Meaning
VERIFIED_IMPLEMENTED	Executable source and relevant behavior were inspected. Executable behavior exists with a material governance or completeness gap.
IMPLEMENTED_WITH_GAP	
PARTIAL_IMPLEMENTATION	Only part of the target capability is evidenced.
REFERENCE_ARCHITECTURE	Normative target behavior; no claim that it exists today.
PLANNED_NOT_IMPLEMENTED	Explicitly planned but not evidenced as executable.
DOCUMENTATION_ONLY_CLAIM	Documentation or client contract claims behavior without verified backend evidence.
CONFLICT_REQUIRES_CANONICALIZATION	Sources disagree and no final owner has been established.
REQUIRES_REPOSITORY_REVIEW	Necessary executable evidence has not yet been inspected.

Partner Portal — Identity, Session, Authorization, and Trust Boundaries

Metadata	Value
Volume	4
Chapter ID	V04-P07-02
Subject	PartnerPortalAccessModel
Status	Generated First-Draft Architecture Skeleton - Domain-Specific Expansion Required
Content maturity	TEMPLATE_DERIVED_REFERENCE_SKELETON unless repository citations prove otherwise
Default implementation classification	REFERENCE_ARCHITECTURE / REQUIRES_REPOSITORY_REVIEW
Accountable owner	Portal Architecture / Partner Portal
Evidence rule	No implementation claim without inspected executable evidence
Repository	chinair88-prog/allinb2c

1. Executive Orientation

This chapter defines how GTOS shall **govern login, session, role, relationship, tenant, facility, channel, delegation, impersonation and privileged action for suppliers, factories and commercial partners, covering profile, products, quotations, PI, PO, production, quality, documents, settlement.**

The specification separates reality, observations, knowledge, Decisions, Intent, execution, and outcomes. A component name, database row, UI label, AI answer, or workflow state does not acquire authority merely because it is visible or technically convenient.

Reality or external outcome
≠ Observation
≠ Claim
≠ derived Perspective
≠ Prediction
≠ Recommendation
≠ authorized Decision
≠ execution Intent

1.1 Accountable ownership

The accountable owner is **Portal Architecture / Partner Portal**. Supporting applications, shared infrastructure, integration adapters, analytics, and AI coordinate or present the capability but shall not silently own its authoritative propositions.

1.2 Scope

- create and identify the subject
- validate evidence and policy
- make authorized Decisions
- execute typed Commands
- publish completed-fact Events
- query current and historical perspectives
- correct and reconcile outcomes

1.3 Non-goals

- treating a registered Gradle module, catalog record, README, frontend route, migration plan, or generated report as proof of end-to-end implementation;
- direct cross-Domain database writes;
- generic status values that combine lifecycle, approval, provider, document, payment, dispute, and correction state;
- silent replacement of history;
- AI-created authority or fabricated external outcomes.

2. Ubiquitous Language and Subject Model

Subject	Required interpretation
PartnerPortalAccessModel	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit
PartnerPortalAccessModelVersion	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit
PartnerPortalAccessModelDecision	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit
PartnerPortalAccessModelEvidenceSet	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit
PartnerPortalAccessModelException	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit

Reference aggregate:

```
PartnerPortalAccessModel {  
  subjectId  
  tenantId  
  organizationContext  
  sourceIdentityRefs[]  
  sourceVersionRefs[]  
  lifecycleState  
  relationshipRefs[]  
  decisionRefs[]  
  intentRefs[]  
  evidenceSetRef  
  knowledgeCutoff  
  policyRefs[]  
  authorityRef  
  jurisdictionRefs[]  
  createdAt  
  effectiveAt  
  updatedAt  
  version  
  correctionOf?  
  correlationId  
}
```

2.1 Core invariants

- Stable identity precedes relationship, state, and cross-system correlation.
- Effective time and recorded time remain distinct where business truth changes over time.
- Recommendation, Decision, Intent, execution, and outcome are separate concepts.
- No Portal, report, search index, cache, workflow, or AI Agent becomes a shadow owner of Domain truth.
- Binding submitted, approved, issued, accepted, or signed versions are immutable.
- Corrections append governed facts and preserve the original record.
- External authority and provider outcomes retain their source and qualification.
- Tenant and represented-principal context come from trusted authentication and mandate evaluation.
- Retried writes are idempotent and concurrency guarded.
- Outcome Unknown is explicit and reconciled before risky duplicate execution.

2.2 Required standards

- stable identifiers
- typed contracts
- immutable binding versions

- transactional outbox
- idempotent Commands
- explicit Outcome Unknown
- correction lineage
- machine-verifiable conformance

3. Actors, Roles, and Authority

A conformant design distinguishes:

- the natural person acting;
- the service or AI identity invoking a Tool;
- the organization or principal represented;
- the role or relationship granting context;
- the mandate or delegation granting action authority;
- the Policy and jurisdiction limiting the action;
- the reviewer or approver responsible for a binding Decision.

Authority is evaluated at action time. Authentication alone does not grant business authority. Cached permissions and browser-supplied tenant headers are insufficient for high-impact actions.

4. Lifecycle and State Model

State	Semantics
PROPOSED	Distinct governed condition with entry, exit, timeout, correction and authority semantics
VALIDATION_PENDING	Distinct governed condition with entry, exit, timeout, correction and authority semantics
APPROVAL_PENDING	Distinct governed condition with entry, exit, timeout, correction and authority semantics
ACTIVE	Distinct governed condition with entry, exit, timeout, correction and authority semantics
SUSPENDED	Distinct governed condition with entry, exit, timeout, correction and authority semantics
CORRECTION_PENDING	Distinct governed condition with entry, exit, timeout, correction and authority semantics
RETIRED	Distinct governed condition with entry, exit, timeout, correction and authority semantics

```
stateDiagram-v2
    [*] --> PROPOSED
    PROPOSED --> VALIDATION_PENDING
    VALIDATION_PENDING --> APPROVAL_PENDING
    APPROVAL_PENDING --> ACTIVE
    ACTIVE --> SUSPENDED
    SUSPENDED --> CORRECTION_PENDING
    CORRECTION_PENDING --> RETIRED
```

The diagram is a primary reading path. Real implementations may add parallel review, amendment, appeal, timeout, suspension, partial completion, reconciliation, correction, and terminal failure without collapsing their meaning.

4.1 Transition rules

- transition through a typed, authorized Command;
- require exact expected version where concurrent change matters;
- record actor, represented principal, mandate, Policy, reason, and Evidence;
- use an idempotency key for retried writes;
- publish a completed-fact Event after durable state change;
- expose Outcome Unknown for unresolved external completion;
- preserve original and corrected states in historical reconstruction.

5. Decision, Evidence, and Knowledge Cutoff

Reference Decision:

```
Decision {
  decisionId
  decisionType
  subjectRef
  sourceVersionRefs[]
  knowledgeCutoff
  evidenceSetRef
  policyVersionRefs[]
  recommendationRefs[]
  principalId
  representedOrganizationId
  mandateRef
  rationale
  outcome
  decidedAt
  effectiveAt
  correctionOf?
}
```

Evidence records identify issuer or observer, subject, version, observed time, received time, effective interval, integrity, confidence, qualification, contradiction, correction, retention, residency, and access class. A recommendation may assist the Decision but cannot promote itself to the Decision.

6. Commands, Events, Queries, and Contracts

Reference Commands:

- CreatePartnerPortalAccessModel
- ValidatePartnerPortalAccessModel
- ApprovePartnerPortalAccessModel
- ActivatePartnerPortalAccessModel
- SuspendPartnerPortalAccessModel
- CorrectPartnerPortalAccessModel
- RetirePartnerPortalAccessModel

Reference Events:

- PartnerPortalAccessModelCreated
- PartnerPortalAccessModelValidated
- PartnerPortalAccessModelApproved
- PartnerPortalAccessModelActivated
- PartnerPortalAccessModelSuspended
- PartnerPortalAccessModelCorrected
- PartnerPortalAccessModelRetired

Reference queries:

- GetPartnerPortalAccessModel
- ListPartnerPortalAccessModelRecords
- GetPartnerPortalAccessModelTimeline
- GetPartnerPortalAccessModelEvidence
- GetPartnerPortalAccessModelDecisionPackage
- GetPartnerPortalAccessModelExceptions
- GetPartnerPortalAccessModelAuditTrail

Reference API surface:

```
POST /api/v1/partnerportalaccessmodel/commands
GET  /api/v1/partnerportalaccessmodel/{id}
GET  /api/v1/partnerportalaccessmodel/{id}/timeline
GET  /api/v1/partnerportalaccessmodel/{id}/evidence
GET  /api/v1/partnerportalaccessmodel/{id}/decisions
POST /api/v1/partnerportalaccessmodel/{id}/exceptions
POST /api/v1/partnerportalaccessmodel/{id}/corrections
```

These endpoints are reference contracts, not claims that exact routes exist.

7. Workflow, Failure, and Compensation

flowchart TD

```
A[Validate identity version and authority] --> B[Collect required evidence]
B --> C{Policy and evidence gates pass?}
C -- No --> D[Open exception or request correction]
D --> B
C -- Yes --> E[Record Decision or execution Intent]
E --> F[Execute Domain command or external request]
F --> G{Outcome known?}
G -- Success --> H[Record fact and publish Event]
G -- Failure --> I[Record failure and compensation options]
G -- Unknown --> J[Enter Outcome Unknown]
J --> K[Query source or wait for verified callback]
K --> G
H --> L[Update projections and downstream workflow]
```

Representative failure modes:

- stale or wrong source version
- duplicate submission or replay
- external timeout after possible success
- contradictory source observations
- lost Event after committed state
- approval or mandate revoked during execution
- downstream action before a mandatory gate
- partial completion across multiple subjects
- evidence later retracted or corrected
- tenant, facility, channel or jurisdiction mismatch

Recovery shall query the authoritative source before duplicate execution, preserve partial success, use compensating Intent rather than destructive rewrite, publish corrections, quarantine high-impact ambiguity, and record affected downstream subjects.

8. Data and Persistence Architecture

Reference table families:

Table family	Purpose
partnerportalaccessmodel_aggregate	authoritative subject
partnerportalaccessmodel_version	immutable submitted, approved, issued, or signed versions
partnerportalaccessmodel_relationship	governed relationships
partnerportalaccessmodel_decision	binding Decisions and rationale
partnerportalaccessmodel_evidence_link	provenance and evidence relationships
partnerportalaccessmodel_event_outbox	transactional Event publication
partnerportalaccessmodel_idempotency	duplicate-write protection
partnerportalaccessmodel_exception	exception, claim, dispute, or hold
partnerportalaccessmodel_correction	correction and supersession lineage
partnerportalaccessmodel_audit	privileged action evidence

The owning service controls schema and migration. Cross-Domain references use stable identifiers or contracts. Analytics, reports, caches, search, and vector indexes remain projections. Backup, restore, retention, legal hold, privacy, residency, and decommissioning requirements are explicit.

9. Portal and Experience Requirements

- Partner Portal: primary experience for suppliers, factories and commercial partners.
- Operator and support views: diagnose failed or ambiguous journeys without assuming Domain ownership.
- Domain services: own authoritative data and action eligibility; the Portal consumes typed contracts.

Every Portal displays exact version, owner, state, freshness, required action, and uncertainty. It supports loading, empty, partial, stale, denied, error, timeout, and Outcome Unknown states; accessibility; locale, currency, unit, date, and RTL/LTR correctness; evidence audit; safe retry; and correction history.

10. AI Participation and Tool Governance

Permitted AI tasks:

- extract and classify evidence
- detect anomalies and missing fields
- summarize timelines and contradictions
- recommend next actions with sources and uncertainty

AI shall not own Domain records, grant itself authority, suppress contradictions, silently edit approved versions, fabricate external outcomes, or execute high-impact actions outside typed Tools, policy, approval, idempotency, sandbox, and outcome observation.

Every Agent Run records source context, prompt/model/tool versions, structured output, confidence and limitations, Policy result, approval, Tool calls, provider responses, final outcome, and recovery actions.

11. Security, Privacy, and Trust Boundaries

- least privilege and separation of duties
- tenant, organization, facility, channel and jurisdiction isolation
- integrity protection for binding evidence
- verified external callbacks and anti-replay controls

Additional controls include secret isolation, callback signature verification, audit of privileged action, emergency-access review, sensitive-data minimization, purpose limitation, and threat models for impersonation, tampering, replay, confused deputy, fraud, prompt injection, and exfiltration.

12. Reliability, SLOs, and Operations

SLI	Reference objective
authoritative read availability	99.9% monthly unless a stricter tier applies
acknowledged Command durability	no acknowledged write may be silently lost
Event publication	99.9% within five minutes after committed fact
duplicate prevention	100% for same tenant, Command class, and idempotency key
binding Decision audit completeness	100%
state-state detection	bounded by business deadline

Dashboards and runbooks cover backlog, error budget, dependency failure, retry budget, DLQ, workflow stall, provider outage, reconciliation, capacity, backup/restore, release/rollback, incident command, and post-incident correction.

13. Testing and Continuous Conformance

- aggregate invariant and transition tests
- authorization, delegation, separation-of-duties and tenant-isolation tests
- idempotency and optimistic-concurrency tests
- database migration, key, constraint and rollback tests
- contract, outbox/inbox, duplicate, replay and DLQ tests
- workflow restart, timeout and compensation tests
- Portal E2E tests for success, partial, stale, denied, error and Outcome Unknown states
- accessibility, locale, currency, unit and RTL/LTR tests
- security adversarial, fraud and data-exfiltration tests
- AI evaluation, prompt-injection, policy-bypass and unauthorized-tool tests
- historical reconstruction, correction and audit-completeness tests
- performance, capacity, recovery and operational exercise tests

Release evidence links each invariant and control to the test, environment, input data, result, owner, and artifact proving it. Generated test counts never replace semantic coverage.

14. Repository Review Boundary

- This chapter is a repository-review specification. Exact executable implementation has not been inspected for every target behavior.
- Registered modules, catalog entries, README claims, frontend contracts, or plans are not proof of complete implementation.

Area	Classification
target aggregate, API, tables, state and workflow in this chapter	REFERENCE_ARCHITECTURE
registered module or catalog claim	DOCUMENTATION_ONLY_CLAIM until source inspection
uninspected integration	REQUIRES_REPOSITORY_REVIEW
behavior proven in another repository-grounded chapter	retain that chapter's evidence and classification
contradictory ownership or path claims	CONFLICT_REQUIRES_CANONICALIZATION

No statement upgrades implementation status merely because a file, directory, module name, frontend contract, database entry, plan, or report exists.

15. Worked Conformance Scenario

An authorized principal initiates a Command against an exact subject version. The service validates identity, tenant, mandate, Policy, Evidence, and idempotency. It records the state transition and outbox entry atomically. If an external dependency participates, timeout produces Outcome Unknown; reconciliation queries the source or waits for a verified callback instead of repeating the action blindly.

Portals show source, freshness, version, required action, and uncertainty. AI may extract, compare, summarize, detect anomalies, and recommend through typed Tools, but cannot own the subject or fabricate success. Later correction appends new facts, identifies affected projections and workflows, and preserves the historical Decision context.

16. Conformance Checklist

- ☐ stable identity and proposition ownership are explicit;
- ☐ authority and mandate are evaluated at action time;
- ☐ state, Recommendation, Decision, Intent, execution, and outcome remain distinct;
- ☐ Commands are typed, authorized, idempotent, and version guarded;
- ☐ Events describe completed facts;
- ☐ Evidence includes provenance, time, integrity, qualification, and correction;
- ☐ external outcomes retain their authority source;
- ☐ Portals show freshness and uncertainty;
- ☐ AI is bounded by typed Tools, Policy, approval, and outcome observation;
- ☐ security, tenant, facility, channel, and jurisdiction boundaries are enforced;
- ☐ Outcome Unknown and reconciliation exist where needed;
- ☐ corrections preserve history;
- ☐ tests prove invariants and recovery;
- ☐ implementation status is not upgraded without executable evidence.

17. Status Vocabulary

Status	Meaning
VERIFIED_IMPLEMENTED	Executable source and relevant behavior were inspected.
IMPLEMENTED_WITH_GAP	Executable behavior exists with a material governance or completeness gap.
PARTIAL_IMPLEMENTATION	Only part of the target capability is evidenced.
REFERENCE_ARCHITECTURE	Normative target behavior; no claim that it exists today.
PLANNED_NOT_IMPLEMENTED	Explicitly planned but not evidenced as executable.
DOCUMENTATION_ONLY_CLAIM	Documentation or client contract claims behavior without verified backend evidence.
CONFLICT_REQUIRES_CANONICALIZATION	Sources disagree and no final owner has been established.
REQUIRES_REPOSITORY_REVIEW	Necessary executable evidence has not yet been inspected.

Partner Portal — UX States, Accessibility, Localization, Analytics, and E2E

Metadata	Value
Volume	4
Chapter ID	V04-P07-03
Subject	PartnerPortalExperienceStandard
Status	Generated First-Draft Architecture Skeleton - Domain-Specific Expansion Required
Content maturity	TEMPLATE_DERIVED_REFERENCE_SKELETON unless repository citations prove otherwise
Default implementation classification	REFERENCE_ARCHITECTURE / REQUIRES_REPOSITORY_REVIEW
Accountable owner	Portal Architecture / Partner Portal
Evidence rule	No implementation claim without inspected executable evidence
Repository	chinair88-prog/allinb2c

1. Executive Orientation

This chapter defines how GTOS shall **specify loading, empty, partial, stale, error, denied, offline, accessibility, RTL/LTR, analytics, audit and test journeys for suppliers, factories and commercial partners, covering profile, products, quotations, PI, PO, production, quality, documents, settlement.**

The specification separates reality, observations, knowledge, Decisions, Intent, execution, and outcomes. A component name, database row, UI label, AI answer, or workflow state does not acquire authority merely because it is visible or technically convenient.

Reality or external outcome

- ≠ Observation
- ≠ Claim
- ≠ derived Perspective
- ≠ Prediction
- ≠ Recommendation
- ≠ authorized Decision
- ≠ execution Intent

1.1 Accountable ownership

The accountable owner is **Portal Architecture / Partner Portal**. Supporting applications, shared infrastructure, integration adapters, analytics, and AI coordinate or present the capability but shall not silently own its authoritative propositions.

1.2 Scope

- create and identify the subject
- validate evidence and policy
- make authorized Decisions
- execute typed Commands
- publish completed-fact Events
- query current and historical perspectives
- correct and reconcile outcomes

1.3 Non-goals

- treating a registered Gradle module, catalog record, README, frontend route, migration plan, or generated report as proof of end-to-end implementation;
- direct cross-Domain database writes;
- generic status values that combine lifecycle, approval, provider, document, payment, dispute, and correction state;
- silent replacement of history;
- AI-created authority or fabricated external outcomes.

2. Ubiquitous Language and Subject Model

Subject	Required interpretation
PartnerPortalExperienceStandard	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit
PartnerPortalExperienceStandardVersion	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit
PartnerPortalExperienceStandardDecision	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit
PartnerPortalExperienceStandardEvidenceSet	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit
PartnerPortalExperienceStandardException	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit

Reference aggregate:

```
PartnerPortalExperienceStandard {  
  subjectId  
  tenantId  
  organizationContext  
  sourceIdentityRefs[]  
  sourceVersionRefs[]  
  lifecycleState  
  relationshipRefs[]  
  decisionRefs[]  
  intentRefs[]  
  evidenceSetRef  
  knowledgeCutoff  
  policyRefs[]  
  authorityRef  
  jurisdictionRefs[]  
  createdAt  
  effectiveAt  
  updatedAt  
  version  
  correctionOf?  
  correlationId  
}
```

2.1 Core invariants

- Stable identity precedes relationship, state, and cross-system correlation.
- Effective time and recorded time remain distinct where business truth changes over time.
- Recommendation, Decision, Intent, execution, and outcome are separate concepts.
- No Portal, report, search index, cache, workflow, or AI Agent becomes a shadow owner of Domain truth.
- Binding submitted, approved, issued, accepted, or signed versions are immutable.
- Corrections append governed facts and preserve the original record.
- External authority and provider outcomes retain their source and qualification.
- Tenant and represented-principal context come from trusted authentication and mandate evaluation.
- Retried writes are idempotent and concurrency guarded.
- Outcome Unknown is explicit and reconciled before risky duplicate execution.

2.2 Required standards

- stable identifiers
- typed contracts
- immutable binding versions

- transactional outbox
- idempotent Commands
- explicit Outcome Unknown
- correction lineage
- machine-verifiable conformance

3. Actors, Roles, and Authority

A conformant design distinguishes:

- the natural person acting;
- the service or AI identity invoking a Tool;
- the organization or principal represented;
- the role or relationship granting context;
- the mandate or delegation granting action authority;
- the Policy and jurisdiction limiting the action;
- the reviewer or approver responsible for a binding Decision.

Authority is evaluated at action time. Authentication alone does not grant business authority. Cached permissions and browser-supplied tenant headers are insufficient for high-impact actions.

4. Lifecycle and State Model

State	Semantics
PROPOSED	Distinct governed condition with entry, exit, timeout, correction and authority semantics
VALIDATION_PENDING	Distinct governed condition with entry, exit, timeout, correction and authority semantics
APPROVAL_PENDING	Distinct governed condition with entry, exit, timeout, correction and authority semantics
ACTIVE	Distinct governed condition with entry, exit, timeout, correction and authority semantics
SUSPENDED	Distinct governed condition with entry, exit, timeout, correction and authority semantics
CORRECTION_PENDING	Distinct governed condition with entry, exit, timeout, correction and authority semantics
RETIRED	Distinct governed condition with entry, exit, timeout, correction and authority semantics

```
stateDiagram-v2
    [*] --> PROPOSED
    PROPOSED --> VALIDATION_PENDING
    VALIDATION_PENDING --> APPROVAL_PENDING
    APPROVAL_PENDING --> ACTIVE
    ACTIVE --> SUSPENDED
    SUSPENDED --> CORRECTION_PENDING
    CORRECTION_PENDING --> RETIRED
```

The diagram is a primary reading path. Real implementations may add parallel review, amendment, appeal, timeout, suspension, partial completion, reconciliation, correction, and terminal failure without collapsing their meaning.

4.1 Transition rules

- transition through a typed, authorized Command;
- require exact expected version where concurrent change matters;
- record actor, represented principal, mandate, Policy, reason, and Evidence;
- use an idempotency key for retried writes;
- publish a completed-fact Event after durable state change;
- expose Outcome Unknown for unresolved external completion;
- preserve original and corrected states in historical reconstruction.

5. Decision, Evidence, and Knowledge Cutoff

Reference Decision:

```
Decision {
  decisionId
  decisionType
  subjectRef
  sourceVersionRefs[]
  knowledgeCutoff
  evidenceSetRef
  policyVersionRefs[]
  recommendationRefs[]
  principalId
  representedOrganizationId
  mandateRef
  rationale
  outcome
  decidedAt
  effectiveAt
  correctionOf?
}
```

Evidence records identify issuer or observer, subject, version, observed time, received time, effective interval, integrity, confidence, qualification, contradiction, correction, retention, residency, and access class. A recommendation may assist the Decision but cannot promote itself to the Decision.

6. Commands, Events, Queries, and Contracts

Reference Commands:

- CreatePartnerPortalExperienceStandard
- ValidatePartnerPortalExperienceStandard
- ApprovePartnerPortalExperienceStandard
- ActivatePartnerPortalExperienceStandard
- SuspendPartnerPortalExperienceStandard
- CorrectPartnerPortalExperienceStandard
- RetirePartnerPortalExperienceStandard

Reference Events:

- PartnerPortalExperienceStandardCreated
- PartnerPortalExperienceStandardValidated
- PartnerPortalExperienceStandardApproved
- PartnerPortalExperienceStandardActivated
- PartnerPortalExperienceStandardSuspended
- PartnerPortalExperienceStandardCorrected
- PartnerPortalExperienceStandardRetired

Reference queries:

- GetPartnerPortalExperienceStandard
- ListPartnerPortalExperienceStandardRecords
- GetPartnerPortalExperienceStandardTimeline
- GetPartnerPortalExperienceStandardEvidence
- GetPartnerPortalExperienceStandardDecisionPackage
- GetPartnerPortalExperienceStandardExceptions
- GetPartnerPortalExperienceStandardAuditTrail

Reference API surface:

```
POST /api/v1/partnerportalexperiencestandard/commands
GET  /api/v1/partnerportalexperiencestandard/{id}
GET  /api/v1/partnerportalexperiencestandard/{id}/timeline
GET  /api/v1/partnerportalexperiencestandard/{id}/evidence
GET  /api/v1/partnerportalexperiencestandard/{id}/decisions
POST /api/v1/partnerportalexperiencestandard/{id}/exceptions
POST /api/v1/partnerportalexperiencestandard/{id}/corrections
```

These endpoints are reference contracts, not claims that exact routes exist.

7. Workflow, Failure, and Compensation

flowchart TD

```
A[Validate identity version and authority] --> B[Collect required evidence]
B --> C{Policy and evidence gates pass?}
C -- No --> D[Open exception or request correction]
D --> B
C -- Yes --> E[Record Decision or execution Intent]
E --> F[Execute Domain command or external request]
F --> G{Outcome known?}
G -- Success --> H[Record fact and publish Event]
G -- Failure --> I[Record failure and compensation options]
G -- Unknown --> J[Enter Outcome Unknown]
J --> K[Query source or wait for verified callback]
K --> G
H --> L[Update projections and downstream workflow]
```

Representative failure modes:

- stale or wrong source version
- duplicate submission or replay
- external timeout after possible success
- contradictory source observations
- lost Event after committed state
- approval or mandate revoked during execution
- downstream action before a mandatory gate
- partial completion across multiple subjects
- evidence later retracted or corrected
- tenant, facility, channel or jurisdiction mismatch

Recovery shall query the authoritative source before duplicate execution, preserve partial success, use compensating Intent rather than destructive rewrite, publish corrections, quarantine high-impact ambiguity, and record affected downstream subjects.

8. Data and Persistence Architecture

Reference table families:

Table family	Purpose
partnerportalexperiencestandard_aggregate	authoritative subject
partnerportalexperiencestandard_version	immutable submitted, approved, issued, or signed versions
partnerportalexperiencestandard_relationship	governed relationships
partnerportalexperiencestandard_decision	binding Decisions and rationale
partnerportalexperiencestandard_evidence_link	provenance and evidence relationships
partnerportalexperiencestandard_event_outbox	transactional Event publication
partnerportalexperiencestandard_idempotency	duplicate-write protection
partnerportalexperiencestandard_exception	exception, claim, dispute, or hold
partnerportalexperiencestandard_correction	correction and supersession lineage
partnerportalexperiencestandard_audit	privileged action evidence

The owning service controls schema and migration. Cross-Domain references use stable identifiers or contracts. Analytics, reports, caches, search, and vector indexes remain projections. Backup, restore, retention, legal hold, privacy, residency, and decommissioning requirements are explicit.

9. Portal and Experience Requirements

- Partner Portal: primary experience for suppliers, factories and commercial partners.
- Operator and support views: diagnose failed or ambiguous journeys without assuming Domain ownership.
- Domain services: own authoritative data and action eligibility; the Portal consumes typed contracts.

Every Portal displays exact version, owner, state, freshness, required action, and uncertainty. It supports loading, empty, partial, stale, denied, error, timeout, and Outcome Unknown states; accessibility; locale, currency, unit, date, and RTL/LTR correctness; evidence audit; safe retry; and correction history.

10. AI Participation and Tool Governance

Permitted AI tasks:

- extract and classify evidence
- detect anomalies and missing fields
- summarize timelines and contradictions
- recommend next actions with sources and uncertainty

AI shall not own Domain records, grant itself authority, suppress contradictions, silently edit approved versions, fabricate external outcomes, or execute high-impact actions outside typed Tools, policy, approval, idempotency, sandbox, and outcome observation.

Every Agent Run records source context, prompt/model/tool versions, structured output, confidence and limitations, Policy result, approval, Tool calls, provider responses, final outcome, and recovery actions.

11. Security, Privacy, and Trust Boundaries

- least privilege and separation of duties
- tenant, organization, facility, channel and jurisdiction isolation
- integrity protection for binding evidence
- verified external callbacks and anti-replay controls

Additional controls include secret isolation, callback signature verification, audit of privileged action, emergency-access review, sensitive-data minimization, purpose limitation, and threat models for impersonation, tampering, replay, confused deputy, fraud, prompt injection, and exfiltration.

12. Reliability, SLOs, and Operations

SLI	Reference objective
authoritative read availability	99.9% monthly unless a stricter tier applies
acknowledged Command durability	no acknowledged write may be silently lost
Event publication	99.9% within five minutes after committed fact
duplicate prevention	100% for same tenant, Command class, and idempotency key
binding Decision audit completeness	100%
state-state detection	bounded by business deadline

Dashboards and runbooks cover backlog, error budget, dependency failure, retry budget, DLQ, workflow stall, provider outage, reconciliation, capacity, backup/restore, release/rollback, incident command, and post-incident correction.

13. Testing and Continuous Conformance

- aggregate invariant and transition tests
- authorization, delegation, separation-of-duties and tenant-isolation tests
- idempotency and optimistic-concurrency tests
- database migration, key, constraint and rollback tests
- contract, outbox/inbox, duplicate, replay and DLQ tests
- workflow restart, timeout and compensation tests
- Portal E2E tests for success, partial, stale, denied, error and Outcome Unknown states
- accessibility, locale, currency, unit and RTL/LTR tests
- security adversarial, fraud and data-exfiltration tests
- AI evaluation, prompt-injection, policy-bypass and unauthorized-tool tests
- historical reconstruction, correction and audit-completeness tests
- performance, capacity, recovery and operational exercise tests

Release evidence links each invariant and control to the test, environment, input data, result, owner, and artifact proving it. Generated test counts never replace semantic coverage.

14. Repository Review Boundary

- This chapter is a repository-review specification. Exact executable implementation has not been inspected for every target behavior.
- Registered modules, catalog entries, README claims, frontend contracts, or plans are not proof of complete implementation.

Area	Classification
target aggregate, API, tables, state and workflow in this chapter	REFERENCE_ARCHITECTURE
registered module or catalog claim	DOCUMENTATION_ONLY_CLAIM until source inspection
uninspected integration	REQUIRES_REPOSITORY_REVIEW
behavior proven in another repository-grounded chapter	retain that chapter's evidence and classification
contradictory ownership or path claims	CONFLICT_REQUIRES_CANONICALIZATION

No statement upgrades implementation status merely because a file, directory, module name, frontend contract, database entry, plan, or report exists.

15. Worked Conformance Scenario

An authorized principal initiates a Command against an exact subject version. The service validates identity, tenant, mandate, Policy, Evidence, and idempotency. It records the state transition and outbox entry atomically. If an external dependency participates, timeout produces Outcome Unknown; reconciliation queries the source or waits for a verified callback instead of repeating the action blindly.

Portals show source, freshness, version, required action, and uncertainty. AI may extract, compare, summarize, detect anomalies, and recommend through typed Tools, but cannot own the subject or fabricate success. Later correction appends new facts, identifies affected projections and workflows, and preserves the historical Decision context.

16. Conformance Checklist

- ☐ stable identity and proposition ownership are explicit;
- ☐ authority and mandate are evaluated at action time;
- ☐ state, Recommendation, Decision, Intent, execution, and outcome remain distinct;
- ☐ Commands are typed, authorized, idempotent, and version guarded;
- ☐ Events describe completed facts;
- ☐ Evidence includes provenance, time, integrity, qualification, and correction;
- ☐ external outcomes retain their authority source;
- ☐ Portals show freshness and uncertainty;
- ☐ AI is bounded by typed Tools, Policy, approval, and outcome observation;
- ☐ security, tenant, facility, channel, and jurisdiction boundaries are enforced;
- ☐ Outcome Unknown and reconciliation exist where needed;
- ☐ corrections preserve history;
- ☐ tests prove invariants and recovery;
- ☐ implementation status is not upgraded without executable evidence.

17. Status Vocabulary

Status	Meaning
VERIFIED_IMPLEMENTED	Executable source and relevant behavior were inspected. Executable behavior exists with a material governance or completeness gap.
IMPLEMENTED_WITH_GAP	
PARTIAL_IMPLEMENTATION	Only part of the target capability is evidenced.
REFERENCE_ARCHITECTURE	Normative target behavior; no claim that it exists today.
PLANNED_NOT_IMPLEMENTED	Explicitly planned but not evidenced as executable.
DOCUMENTATION_ONLY_CLAIM	Documentation or client contract claims behavior without verified backend evidence.
CONFLICT_REQUIRES_CANONICALIZATION	Sources disagree and no final owner has been established.
REQUIRES_REPOSITORY_REVIEW	Necessary executable evidence has not yet been inspected.

Developer Portal — Portal Orientation and Information Architecture

Metadata	Value
Volume	4
Chapter ID	V04-P08-00
Subject	DeveloperPortalPortal
Status	Generated First-Draft Architecture Skeleton - Domain-Specific Expansion Required
Content maturity	TEMPLATE_DERIVED_REFERENCE_SKELETON unless repository citations prove otherwise
Default implementation classification	REFERENCE_ARCHITECTURE / REQUIRES_REPOSITORY_REVIEW
Accountable owner	Portal Architecture / Developer Portal
Evidence rule	No implementation claim without inspected executable evidence
Repository	chinair88-prog/allinb2c

1. Executive Orientation

This chapter defines how GTOS shall **define personas, navigation, route ownership, domain dependencies and experience boundaries for internal and external developers, covering API discovery, credentials, contracts, sandbox, webhook, documentation, certification.**

The specification separates reality, observations, knowledge, Decisions, Intent, execution, and outcomes. A component name, database row, UI label, AI answer, or workflow state does not acquire authority merely because it is visible or technically convenient.

Reality or external outcome

- ≠ Observation
- ≠ Claim
- ≠ derived Perspective
- ≠ Prediction
- ≠ Recommendation
- ≠ authorized Decision
- ≠ execution Intent

1.1 Accountable ownership

The accountable owner is **Portal Architecture / Developer Portal**. Supporting applications, shared infrastructure, integration adapters, analytics, and AI coordinate or present the capability but shall not silently own its authoritative propositions.

1.2 Scope

- create and identify the subject
- validate evidence and policy
- make authorized Decisions
- execute typed Commands
- publish completed-fact Events
- query current and historical perspectives
- correct and reconcile outcomes

1.3 Non-goals

- treating a registered Gradle module, catalog record, README, frontend route, migration plan, or generated report as proof of end-to-end implementation;
- direct cross-Domain database writes;
- generic status values that combine lifecycle, approval, provider, document, payment, dispute, and correction state;
- silent replacement of history;
- AI-created authority or fabricated external outcomes.

2. Ubiquitous Language and Subject Model

Subject	Required interpretation
DeveloperPortalPortal	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit
DeveloperPortalPortalVersion	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit
DeveloperPortalPortalDecision	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit
DeveloperPortalPortalEvidenceSet	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit
DeveloperPortalPortalException	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit

Reference aggregate:

```
DeveloperPortalPortal {
  subjectId
  tenantId
  organizationContext
  sourceIdentityRefs[]
  sourceVersionRefs[]
  lifecycleState
  relationshipRefs[]
  decisionRefs[]
  intentRefs[]
  evidenceSetRef
  knowledgeCutoff
  policyRefs[]
  authorityRef
  jurisdictionRefs[]
  createdAt
  effectiveAt
  updatedAt
  version
  correctionOf?
  correlationId
}
```

2.1 Core invariants

- Stable identity precedes relationship, state, and cross-system correlation.
- Effective time and recorded time remain distinct where business truth changes over time.
- Recommendation, Decision, Intent, execution, and outcome are separate concepts.
- No Portal, report, search index, cache, workflow, or AI Agent becomes a shadow owner of Domain truth.
- Binding submitted, approved, issued, accepted, or signed versions are immutable.
- Corrections append governed facts and preserve the original record.
- External authority and provider outcomes retain their source and qualification.
- Tenant and represented-principal context come from trusted authentication and mandate evaluation.
- Retried writes are idempotent and concurrency guarded.
- Outcome Unknown is explicit and reconciled before risky duplicate execution.

2.2 Required standards

- stable identifiers
- typed contracts
- immutable binding versions

- transactional outbox
- idempotent Commands
- explicit Outcome Unknown
- correction lineage
- machine-verifiable conformance

3. Actors, Roles, and Authority

A conformant design distinguishes:

- the natural person acting;
- the service or AI identity invoking a Tool;
- the organization or principal represented;
- the role or relationship granting context;
- the mandate or delegation granting action authority;
- the Policy and jurisdiction limiting the action;
- the reviewer or approver responsible for a binding Decision.

Authority is evaluated at action time. Authentication alone does not grant business authority. Cached permissions and browser-supplied tenant headers are insufficient for high-impact actions.

4. Lifecycle and State Model

State	Semantics
PROPOSED	Distinct governed condition with entry, exit, timeout, correction and authority semantics
VALIDATION_PENDING	Distinct governed condition with entry, exit, timeout, correction and authority semantics
APPROVAL_PENDING	Distinct governed condition with entry, exit, timeout, correction and authority semantics
ACTIVE	Distinct governed condition with entry, exit, timeout, correction and authority semantics
SUSPENDED	Distinct governed condition with entry, exit, timeout, correction and authority semantics
CORRECTION_PENDING	Distinct governed condition with entry, exit, timeout, correction and authority semantics
RETIRED	Distinct governed condition with entry, exit, timeout, correction and authority semantics

```
stateDiagram-v2
    [*] --> PROPOSED
    PROPOSED --> VALIDATION_PENDING
    VALIDATION_PENDING --> APPROVAL_PENDING
    APPROVAL_PENDING --> ACTIVE
    ACTIVE --> SUSPENDED
    SUSPENDED --> CORRECTION_PENDING
    CORRECTION_PENDING --> RETIRED
```

The diagram is a primary reading path. Real implementations may add parallel review, amendment, appeal, timeout, suspension, partial completion, reconciliation, correction, and terminal failure without collapsing their meaning.

4.1 Transition rules

- transition through a typed, authorized Command;
- require exact expected version where concurrent change matters;
- record actor, represented principal, mandate, Policy, reason, and Evidence;
- use an idempotency key for retried writes;
- publish a completed-fact Event after durable state change;
- expose Outcome Unknown for unresolved external completion;
- preserve original and corrected states in historical reconstruction.

5. Decision, Evidence, and Knowledge Cutoff

Reference Decision:

```
Decision {
  decisionId
  decisionType
  subjectRef
  sourceVersionRefs[]
  knowledgeCutoff
  evidenceSetRef
  policyVersionRefs[]
  recommendationRefs[]
  principalId
  representedOrganizationId
  mandateRef
  rationale
  outcome
  decidedAt
  effectiveAt
  correctionOf?
}
```

Evidence records identify issuer or observer, subject, version, observed time, received time, effective interval, integrity, confidence, qualification, contradiction, correction, retention, residency, and access class. A recommendation may assist the Decision but cannot promote itself to the Decision.

6. Commands, Events, Queries, and Contracts

Reference Commands:

- CreateDeveloperPortalPortal
- ValidateDeveloperPortalPortal
- ApproveDeveloperPortalPortal
- ActivateDeveloperPortalPortal
- SuspendDeveloperPortalPortal
- CorrectDeveloperPortalPortal
- RetireDeveloperPortalPortal

Reference Events:

- DeveloperPortalPortalCreated
- DeveloperPortalPortalValidated
- DeveloperPortalPortalApproved
- DeveloperPortalPortalActivated
- DeveloperPortalPortalSuspended
- DeveloperPortalPortalCorrected
- DeveloperPortalPortalRetired

Reference queries:

- GetDeveloperPortalPortal
- ListDeveloperPortalPortalRecords
- GetDeveloperPortalPortalTimeline
- GetDeveloperPortalPortalEvidence
- GetDeveloperPortalPortalDecisionPackage
- GetDeveloperPortalPortalExceptions
- GetDeveloperPortalPortalAuditTrail

Reference API surface:

```
POST /api/v1/developerportalportal/commands
GET  /api/v1/developerportalportal/{id}
GET  /api/v1/developerportalportal/{id}/timeline
GET  /api/v1/developerportalportal/{id}/evidence
GET  /api/v1/developerportalportal/{id}/decisions
POST /api/v1/developerportalportal/{id}/exceptions
POST /api/v1/developerportalportal/{id}/corrections
```

These endpoints are reference contracts, not claims that exact routes exist.

7. Workflow, Failure, and Compensation

flowchart TD

```
A[Validate identity version and authority] --> B[Collect required evidence]
B --> C{Policy and evidence gates pass?}
C -- No --> D[Open exception or request correction]
D --> B
C -- Yes --> E[Record Decision or execution Intent]
E --> F[Execute Domain command or external request]
F --> G{Outcome known?}
G -- Success --> H[Record fact and publish Event]
G -- Failure --> I[Record failure and compensation options]
G -- Unknown --> J[Enter Outcome Unknown]
J --> K[Query source or wait for verified callback]
K --> G
H --> L[Update projections and downstream workflow]
```

Representative failure modes:

- stale or wrong source version
- duplicate submission or replay
- external timeout after possible success
- contradictory source observations
- lost Event after committed state
- approval or mandate revoked during execution
- downstream action before a mandatory gate
- partial completion across multiple subjects
- evidence later retracted or corrected
- tenant, facility, channel or jurisdiction mismatch

Recovery shall query the authoritative source before duplicate execution, preserve partial success, use compensating Intent rather than destructive rewrite, publish corrections, quarantine high-impact ambiguity, and record affected downstream subjects.

8. Data and Persistence Architecture

Reference table families:

Table family	Purpose
developerportalportal_aggregate	authoritative subject
developerportalportal_version	immutable submitted, approved, issued, or signed versions
developerportalportal_relationship	governed relationships
developerportalportal_decision	binding Decisions and rationale
developerportalportal_evidence_link	provenance and evidence relationships
developerportalportal_event_outbox	transactional Event publication
developerportalportal_idempotency	duplicate-write protection
developerportalportal_exception	exception, claim, dispute, or hold
developerportalportal_correction	correction and supersession lineage
developerportalportal_audit	privileged action evidence

The owning service controls schema and migration. Cross-Domain references use stable identifiers or contracts. Analytics, reports, caches, search, and vector indexes remain projections. Backup, restore, retention, legal hold, privacy, residency, and decommissioning requirements are explicit.

9. Portal and Experience Requirements

- Developer Portal: primary experience for internal and external developers.
- Operator and support views: diagnose failed or ambiguous journeys without assuming Domain ownership.
- Domain services: own authoritative data and action eligibility; the Portal consumes typed contracts.

Every Portal displays exact version, owner, state, freshness, required action, and uncertainty. It supports loading, empty, partial, stale, denied, error, timeout, and Outcome Unknown states; accessibility; locale, currency, unit, date, and RTL/LTR correctness; evidence audit; safe retry; and correction history.

10. AI Participation and Tool Governance

Permitted AI tasks:

- extract and classify evidence
- detect anomalies and missing fields
- summarize timelines and contradictions
- recommend next actions with sources and uncertainty

AI shall not own Domain records, grant itself authority, suppress contradictions, silently edit approved versions, fabricate external outcomes, or execute high-impact actions outside typed Tools, policy, approval, idempotency, sandbox, and outcome observation.

Every Agent Run records source context, prompt/model/tool versions, structured output, confidence and limitations, Policy result, approval, Tool calls, provider responses, final outcome, and recovery actions.

11. Security, Privacy, and Trust Boundaries

- least privilege and separation of duties
- tenant, organization, facility, channel and jurisdiction isolation
- integrity protection for binding evidence
- verified external callbacks and anti-replay controls

Additional controls include secret isolation, callback signature verification, audit of privileged action, emergency-access review, sensitive-data minimization, purpose limitation, and threat models for impersonation, tampering, replay, confused deputy, fraud, prompt injection, and exfiltration.

12. Reliability, SLOs, and Operations

SLI	Reference objective
authoritative read availability	99.9% monthly unless a stricter tier applies
acknowledged Command durability	no acknowledged write may be silently lost
Event publication	99.9% within five minutes after committed fact
duplicate prevention	100% for same tenant, Command class, and idempotency key
binding Decision audit completeness	100%
state-state detection	bounded by business deadline

Dashboards and runbooks cover backlog, error budget, dependency failure, retry budget, DLQ, workflow stall, provider outage, reconciliation, capacity, backup/restore, release/rollback, incident command, and post-incident correction.

13. Testing and Continuous Conformance

- aggregate invariant and transition tests
- authorization, delegation, separation-of-duties and tenant-isolation tests
- idempotency and optimistic-concurrency tests
- database migration, key, constraint and rollback tests
- contract, outbox/inbox, duplicate, replay and DLQ tests
- workflow restart, timeout and compensation tests
- Portal E2E tests for success, partial, stale, denied, error and Outcome Unknown states
- accessibility, locale, currency, unit and RTL/LTR tests
- security adversarial, fraud and data-exfiltration tests
- AI evaluation, prompt-injection, policy-bypass and unauthorized-tool tests
- historical reconstruction, correction and audit-completeness tests
- performance, capacity, recovery and operational exercise tests

Release evidence links each invariant and control to the test, environment, input data, result, owner, and artifact proving it. Generated test counts never replace semantic coverage.

14. Repository Review Boundary

- This chapter is a repository-review specification. Exact executable implementation has not been inspected for every target behavior.
- Registered modules, catalog entries, README claims, frontend contracts, or plans are not proof of complete implementation.

Area	Classification
target aggregate, API, tables, state and workflow in this chapter	REFERENCE_ARCHITECTURE
registered module or catalog claim	DOCUMENTATION_ONLY_CLAIM until source inspection
uninspected integration	REQUIRES_REPOSITORY_REVIEW
behavior proven in another repository-grounded chapter	retain that chapter's evidence and classification
contradictory ownership or path claims	CONFLICT_REQUIRES_CANONICALIZATION

No statement upgrades implementation status merely because a file, directory, module name, frontend contract, database entry, plan, or report exists.

15. Worked Conformance Scenario

An authorized principal initiates a Command against an exact subject version. The service validates identity, tenant, mandate, Policy, Evidence, and idempotency. It records the state transition and outbox entry atomically. If an external dependency participates, timeout produces Outcome Unknown; reconciliation queries the source or waits for a verified callback instead of repeating the action blindly.

Portals show source, freshness, version, required action, and uncertainty. AI may extract, compare, summarize, detect anomalies, and recommend through typed Tools, but cannot own the subject or fabricate success. Later correction appends new facts, identifies affected projections and workflows, and preserves the historical Decision context.

16. Conformance Checklist

- ☐ stable identity and proposition ownership are explicit;
- ☐ authority and mandate are evaluated at action time;
- ☐ state, Recommendation, Decision, Intent, execution, and outcome remain distinct;
- ☐ Commands are typed, authorized, idempotent, and version guarded;
- ☐ Events describe completed facts;
- ☐ Evidence includes provenance, time, integrity, qualification, and correction;
- ☐ external outcomes retain their authority source;
- ☐ Portals show freshness and uncertainty;
- ☐ AI is bounded by typed Tools, Policy, approval, and outcome observation;
- ☐ security, tenant, facility, channel, and jurisdiction boundaries are enforced;
- ☐ Outcome Unknown and reconciliation exist where needed;
- ☐ corrections preserve history;
- ☐ tests prove invariants and recovery;
- ☐ implementation status is not upgraded without executable evidence.

17. Status Vocabulary

Status	Meaning
VERIFIED_IMPLEMENTED	Executable source and relevant behavior were inspected. Executable behavior exists with a material governance or completeness gap.
IMPLEMENTED_WITH_GAP	
PARTIAL_IMPLEMENTATION	Only part of the target capability is evidenced.
REFERENCE_ARCHITECTURE	Normative target behavior; no claim that it exists today.
PLANNED_NOT_IMPLEMENTED	Explicitly planned but not evidenced as executable.
DOCUMENTATION_ONLY_CLAIM	Documentation or client contract claims behavior without verified backend evidence.
CONFLICT_REQUIRES_CANONICALIZATION	Sources disagree and no final owner has been established.
REQUIRES_REPOSITORY_REVIEW	Necessary executable evidence has not yet been inspected.

Developer Portal — Routes, Pages, Components, and BFF Contracts

Metadata	Value
Volume	4
Chapter ID	V04-P08-01
Subject	DeveloperPortalRouteRegistry
Status	Generated First-Draft Architecture Skeleton - Domain-Specific Expansion Required
Content maturity	TEMPLATE_DERIVED_REFERENCE_SKELETON unless repository citations prove otherwise
Default implementation classification	REFERENCE_ARCHITECTURE / REQUIRES_REPOSITORY_REVIEW
Accountable owner	Portal Architecture / Developer Portal
Evidence rule	No implementation claim without inspected executable evidence
Repository	chinair88-prog/allinb2c

1. Executive Orientation

This chapter defines how GTOS shall **inventory routes, layouts, pages, components, server/client boundaries, BFFs, APIs, realtime channels and ownership for internal and external developers, covering API discovery, credentials, contracts, sandbox, webhook, documentation, certification.**

The specification separates reality, observations, knowledge, Decisions, Intent, execution, and outcomes. A component name, database row, UI label, AI answer, or workflow state does not acquire authority merely because it is visible or technically convenient.

Reality or external outcome

- ≠ Observation
- ≠ Claim
- ≠ derived Perspective
- ≠ Prediction
- ≠ Recommendation
- ≠ authorized Decision
- ≠ execution Intent

1.1 Accountable ownership

The accountable owner is **Portal Architecture / Developer Portal**. Supporting applications, shared infrastructure, integration adapters, analytics, and AI coordinate or present the capability but shall not silently own its authoritative propositions.

1.2 Scope

- create and identify the subject
- validate evidence and policy
- make authorized Decisions
- execute typed Commands
- publish completed-fact Events
- query current and historical perspectives
- correct and reconcile outcomes

1.3 Non-goals

- treating a registered Gradle module, catalog record, README, frontend route, migration plan, or generated report as proof of end-to-end implementation;
- direct cross-Domain database writes;
- generic status values that combine lifecycle, approval, provider, document, payment, dispute, and correction state;
- silent replacement of history;
- AI-created authority or fabricated external outcomes.

2. Ubiquitous Language and Subject Model

Subject	Required interpretation
DeveloperPortalRouteRegistry	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit
DeveloperPortalRouteRegistryVersion	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit
DeveloperPortalRouteRegistryDecision	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit
DeveloperPortalRouteRegistryEvidenceSet	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit
DeveloperPortalRouteRegistryException	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit

Reference aggregate:

```
DeveloperPortalRouteRegistry {  
  subjectId  
  tenantId  
  organizationContext  
  sourceIdentityRefs[]  
  sourceVersionRefs[]  
  lifecycleState  
  relationshipRefs[]  
  decisionRefs[]  
  intentRefs[]  
  evidenceSetRef  
  knowledgeCutoff  
  policyRefs[]  
  authorityRef  
  jurisdictionRefs[]  
  createdAt  
  effectiveAt  
  updatedAt  
  version  
  correctionOf?  
  correlationId  
}
```

2.1 Core invariants

- Stable identity precedes relationship, state, and cross-system correlation.
- Effective time and recorded time remain distinct where business truth changes over time.
- Recommendation, Decision, Intent, execution, and outcome are separate concepts.
- No Portal, report, search index, cache, workflow, or AI Agent becomes a shadow owner of Domain truth.
- Binding submitted, approved, issued, accepted, or signed versions are immutable.
- Corrections append governed facts and preserve the original record.
- External authority and provider outcomes retain their source and qualification.
- Tenant and represented-principal context come from trusted authentication and mandate evaluation.
- Retried writes are idempotent and concurrency guarded.
- Outcome Unknown is explicit and reconciled before risky duplicate execution.

2.2 Required standards

- stable identifiers
- typed contracts
- immutable binding versions

- transactional outbox
- idempotent Commands
- explicit Outcome Unknown
- correction lineage
- machine-verifiable conformance

3. Actors, Roles, and Authority

- A conformant design distinguishes:
- the natural person acting;
 - the service or AI identity invoking a Tool;
 - the organization or principal represented;
 - the role or relationship granting context;
 - the mandate or delegation granting action authority;
 - the Policy and jurisdiction limiting the action;
 - the reviewer or approver responsible for a binding Decision.

Authority is evaluated at action time. Authentication alone does not grant business authority. Cached permissions and browser-supplied tenant headers are insufficient for high-impact actions.

4. Lifecycle and State Model

State	Semantics
PROPOSED	Distinct governed condition with entry, exit, timeout, correction and authority semantics
VALIDATION_PENDING	Distinct governed condition with entry, exit, timeout, correction and authority semantics
APPROVAL_PENDING	Distinct governed condition with entry, exit, timeout, correction and authority semantics
ACTIVE	Distinct governed condition with entry, exit, timeout, correction and authority semantics
SUSPENDED	Distinct governed condition with entry, exit, timeout, correction and authority semantics
CORRECTION_PENDING	Distinct governed condition with entry, exit, timeout, correction and authority semantics
RETIRED	Distinct governed condition with entry, exit, timeout, correction and authority semantics

```
stateDiagram-v2
    [*] --> PROPOSED
    PROPOSED --> VALIDATION_PENDING
    VALIDATION_PENDING --> APPROVAL_PENDING
    APPROVAL_PENDING --> ACTIVE
    ACTIVE --> SUSPENDED
    SUSPENDED --> CORRECTION_PENDING
    CORRECTION_PENDING --> RETIRED
```

The diagram is a primary reading path. Real implementations may add parallel review, amendment, appeal, timeout, suspension, partial completion, reconciliation, correction, and terminal failure without collapsing their meaning.

4.1 Transition rules

- transition through a typed, authorized Command;
- require exact expected version where concurrent change matters;
- record actor, represented principal, mandate, Policy, reason, and Evidence;
- use an idempotency key for retried writes;
- publish a completed-fact Event after durable state change;
- expose Outcome Unknown for unresolved external completion;
- preserve original and corrected states in historical reconstruction.

5. Decision, Evidence, and Knowledge Cutoff

Reference Decision:

```
Decision {
  decisionId
  decisionType
  subjectRef
  sourceVersionRefs[]
  knowledgeCutoff
  evidenceSetRef
  policyVersionRefs[]
  recommendationRefs[]
  principalId
  representedOrganizationId
  mandateRef
  rationale
  outcome
  decidedAt
  effectiveAt
  correctionOf?
}
```

Evidence records identify issuer or observer, subject, version, observed time, received time, effective interval, integrity, confidence, qualification, contradiction, correction, retention, residency, and access class. A recommendation may assist the Decision but cannot promote itself to the Decision.

6. Commands, Events, Queries, and Contracts

Reference Commands:

- CreateDeveloperPortalRouteRegistry
- ValidateDeveloperPortalRouteRegistry
- ApproveDeveloperPortalRouteRegistry
- ActivateDeveloperPortalRouteRegistry
- SuspendDeveloperPortalRouteRegistry
- CorrectDeveloperPortalRouteRegistry
- RetireDeveloperPortalRouteRegistry

Reference Events:

- DeveloperPortalRouteRegistryCreated
- DeveloperPortalRouteRegistryValidated
- DeveloperPortalRouteRegistryApproved
- DeveloperPortalRouteRegistryActivated
- DeveloperPortalRouteRegistrySuspended
- DeveloperPortalRouteRegistryCorrected
- DeveloperPortalRouteRegistryRetired

Reference queries:

- GetDeveloperPortalRouteRegistry
- ListDeveloperPortalRouteRegistryRecords
- GetDeveloperPortalRouteRegistryTimeline
- GetDeveloperPortalRouteRegistryEvidence
- GetDeveloperPortalRouteRegistryDecisionPackage
- GetDeveloperPortalRouteRegistryExceptions
- GetDeveloperPortalRouteRegistryAuditTrail

Reference API surface:

```
POST /api/v1/developerportalrouteregistry/commands
GET  /api/v1/developerportalrouteregistry/{id}
GET  /api/v1/developerportalrouteregistry/{id}/timeline
GET  /api/v1/developerportalrouteregistry/{id}/evidence
GET  /api/v1/developerportalrouteregistry/{id}/decisions
POST /api/v1/developerportalrouteregistry/{id}/exceptions
POST /api/v1/developerportalrouteregistry/{id}/corrections
```

These endpoints are reference contracts, not claims that exact routes exist.

7. Workflow, Failure, and Compensation

flowchart TD

```
A[Validate identity version and authority] --> B[Collect required evidence]
B --> C{Policy and evidence gates pass?}
C -- No --> D[Open exception or request correction]
D --> B
C -- Yes --> E[Record Decision or execution Intent]
E --> F[Execute Domain command or external request]
F --> G{Outcome known?}
G -- Success --> H[Record fact and publish Event]
G -- Failure --> I[Record failure and compensation options]
G -- Unknown --> J[Enter Outcome Unknown]
J --> K[Query source or wait for verified callback]
K --> G
H --> L[Update projections and downstream workflow]
```

Representative failure modes:

- stale or wrong source version
- duplicate submission or replay
- external timeout after possible success
- contradictory source observations
- lost Event after committed state
- approval or mandate revoked during execution
- downstream action before a mandatory gate
- partial completion across multiple subjects
- evidence later retracted or corrected
- tenant, facility, channel or jurisdiction mismatch

Recovery shall query the authoritative source before duplicate execution, preserve partial success, use compensating Intent rather than destructive rewrite, publish corrections, quarantine high-impact ambiguity, and record affected downstream subjects.

8. Data and Persistence Architecture

Reference table families:

Table family	Purpose
developerportalrouterregistry_aggregate	authoritative subject
developerportalrouterregistry_version	immutable submitted, approved, issued, or signed versions
developerportalrouterregistry_relationship	governed relationships
developerportalrouterregistry_decision	binding Decisions and rationale
developerportalrouterregistry_evidence_link	provenance and evidence relationships
developerportalrouterregistry_event_outbox	transactional Event publication
developerportalrouterregistry_idempotency	duplicate-write protection
developerportalrouterregistry_exception	exception, claim, dispute, or hold
developerportalrouterregistry_correction	correction and supersession lineage
developerportalrouterregistry_audit	privileged action evidence

The owning service controls schema and migration. Cross-Domain references use stable identifiers or contracts. Analytics, reports, caches, search, and vector indexes remain projections. Backup, restore, retention, legal hold, privacy, residency, and decommissioning requirements are explicit.

9. Portal and Experience Requirements

- Developer Portal: primary experience for internal and external developers.
- Operator and support views: diagnose failed or ambiguous journeys without assuming Domain ownership.
- Domain services: own authoritative data and action eligibility; the Portal consumes typed contracts.

Every Portal displays exact version, owner, state, freshness, required action, and uncertainty. It supports loading, empty, partial, stale, denied, error, timeout, and Outcome Unknown states; accessibility; locale, currency, unit, date, and RTL/LTR correctness; evidence audit; safe retry; and correction history.

10. AI Participation and Tool Governance

Permitted AI tasks:

- extract and classify evidence
- detect anomalies and missing fields
- summarize timelines and contradictions
- recommend next actions with sources and uncertainty

AI shall not own Domain records, grant itself authority, suppress contradictions, silently edit approved versions, fabricate external outcomes, or execute high-impact actions outside typed Tools, policy, approval, idempotency, sandbox, and outcome observation.

Every Agent Run records source context, prompt/model/tool versions, structured output, confidence and limitations, Policy result, approval, Tool calls, provider responses, final outcome, and recovery actions.

11. Security, Privacy, and Trust Boundaries

- least privilege and separation of duties
- tenant, organization, facility, channel and jurisdiction isolation
- integrity protection for binding evidence
- verified external callbacks and anti-replay controls

Additional controls include secret isolation, callback signature verification, audit of privileged action, emergency-access review, sensitive-data minimization, purpose limitation, and threat models for impersonation, tampering, replay, confused deputy, fraud, prompt injection, and exfiltration.

12. Reliability, SLOs, and Operations

SLI	Reference objective
authoritative read availability	99.9% monthly unless a stricter tier applies
acknowledged Command durability	no acknowledged write may be silently lost
Event publication	99.9% within five minutes after committed fact
duplicate prevention	100% for same tenant, Command class, and idempotency key
binding Decision audit completeness	100%
state-state detection	bounded by business deadline

Dashboards and runbooks cover backlog, error budget, dependency failure, retry budget, DLQ, workflow stall, provider outage, reconciliation, capacity, backup/restore, release/rollback, incident command, and post-incident correction.

13. Testing and Continuous Conformance

- aggregate invariant and transition tests
- authorization, delegation, separation-of-duties and tenant-isolation tests
- idempotency and optimistic-concurrency tests
- database migration, key, constraint and rollback tests
- contract, outbox/inbox, duplicate, replay and DLQ tests
- workflow restart, timeout and compensation tests
- Portal E2E tests for success, partial, stale, denied, error and Outcome Unknown states
- accessibility, locale, currency, unit and RTL/LTR tests
- security adversarial, fraud and data-exfiltration tests
- AI evaluation, prompt-injection, policy-bypass and unauthorized-tool tests
- historical reconstruction, correction and audit-completeness tests
- performance, capacity, recovery and operational exercise tests

Release evidence links each invariant and control to the test, environment, input data, result, owner, and artifact proving it. Generated test counts never replace semantic coverage.

14. Repository Review Boundary

- This chapter is a repository-review specification. Exact executable implementation has not been inspected for every target behavior.
- Registered modules, catalog entries, README claims, frontend contracts, or plans are not proof of complete implementation.

Area	Classification
target aggregate, API, tables, state and workflow in this chapter	REFERENCE_ARCHITECTURE
registered module or catalog claim	DOCUMENTATION_ONLY_CLAIM until source inspection
uninspected integration	REQUIRES_REPOSITORY_REVIEW
behavior proven in another repository-grounded chapter	retain that chapter's evidence and classification
contradictory ownership or path claims	CONFLICT_REQUIRES_CANONICALIZATION

No statement upgrades implementation status merely because a file, directory, module name, frontend contract, database entry, plan, or report exists.

15. Worked Conformance Scenario

An authorized principal initiates a Command against an exact subject version. The service validates identity, tenant, mandate, Policy, Evidence, and idempotency. It records the state transition and outbox entry atomically. If an external dependency participates, timeout produces Outcome Unknown; reconciliation queries the source or waits for a verified callback instead of repeating the action blindly.

Portals show source, freshness, version, required action, and uncertainty. AI may extract, compare, summarize, detect anomalies, and recommend through typed Tools, but cannot own the subject or fabricate success. Later correction appends new facts, identifies affected projections and workflows, and preserves the historical Decision context.

16. Conformance Checklist

- ☐ stable identity and proposition ownership are explicit;
- ☐ authority and mandate are evaluated at action time;
- ☐ state, Recommendation, Decision, Intent, execution, and outcome remain distinct;
- ☐ Commands are typed, authorized, idempotent, and version guarded;
- ☐ Events describe completed facts;
- ☐ Evidence includes provenance, time, integrity, qualification, and correction;
- ☐ external outcomes retain their authority source;
- ☐ Portals show freshness and uncertainty;
- ☐ AI is bounded by typed Tools, Policy, approval, and outcome observation;
- ☐ security, tenant, facility, channel, and jurisdiction boundaries are enforced;
- ☐ Outcome Unknown and reconciliation exist where needed;
- ☐ corrections preserve history;
- ☐ tests prove invariants and recovery;
- ☐ implementation status is not upgraded without executable evidence.

17. Status Vocabulary

Status	Meaning
VERIFIED_IMPLEMENTED	Executable source and relevant behavior were inspected.
IMPLEMENTED_WITH_GAP	Executable behavior exists with a material governance or completeness gap.
PARTIAL_IMPLEMENTATION	Only part of the target capability is evidenced.
REFERENCE_ARCHITECTURE	Normative target behavior; no claim that it exists today.
PLANNED_NOT_IMPLEMENTED	Explicitly planned but not evidenced as executable.
DOCUMENTATION_ONLY_CLAIM	Documentation or client contract claims behavior without verified backend evidence.
CONFLICT_REQUIRES_CANONICALIZATION	Sources disagree and no final owner has been established.
REQUIRES_REPOSITORY_REVIEW	Necessary executable evidence has not yet been inspected.

Developer Portal — Identity, Session, Authorization, and Trust Boundaries

Metadata	Value
Volume	4
Chapter ID	V04-P08-02
Subject	DeveloperPortalAccessModel
Status	Generated First-Draft Architecture Skeleton - Domain-Specific Expansion Required
Content maturity	TEMPLATE_DERIVED_REFERENCE_SKELETON unless repository citations prove otherwise
Default implementation classification	REFERENCE_ARCHITECTURE / REQUIRES_REPOSITORY_REVIEW
Accountable owner	Portal Architecture / Developer Portal
Evidence rule	No implementation claim without inspected executable evidence
Repository	chinair88-prog/allinb2c

1. Executive Orientation

This chapter defines how GTOS shall **govern login, session, role, relationship, tenant, facility, channel, delegation, impersonation and privileged action for internal and external developers, covering API discovery, credentials, contracts, sandbox, webhook, documentation, certification.**

The specification separates reality, observations, knowledge, Decisions, Intent, execution, and outcomes. A component name, database row, UI label, AI answer, or workflow state does not acquire authority merely because it is visible or technically convenient.

Reality or external outcome
≠ Observation
≠ Claim
≠ derived Perspective
≠ Prediction
≠ Recommendation
≠ authorized Decision
≠ execution Intent

1.1 Accountable ownership

The accountable owner is **Portal Architecture / Developer Portal**. Supporting applications, shared infrastructure, integration adapters, analytics, and AI coordinate or present the capability but shall not silently own its authoritative propositions.

1.2 Scope

- create and identify the subject
- validate evidence and policy
- make authorized Decisions
- execute typed Commands
- publish completed-fact Events
- query current and historical perspectives
- correct and reconcile outcomes

1.3 Non-goals

- treating a registered Gradle module, catalog record, README, frontend route, migration plan, or generated report as proof of end-to-end implementation;
- direct cross-Domain database writes;
- generic status values that combine lifecycle, approval, provider, document, payment, dispute, and correction state;
- silent replacement of history;
- AI-created authority or fabricated external outcomes.

2. Ubiquitous Language and Subject Model

Subject	Required interpretation
DeveloperPortalAccessModel	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit
DeveloperPortalAccessModelVersion	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit
DeveloperPortalAccessModelDecision	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit
DeveloperPortalAccessModelEvidenceSet	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit
DeveloperPortalAccessModelException	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit

Reference aggregate:

```
DeveloperPortalAccessModel {  
  subjectId  
  tenantId  
  organizationContext  
  sourceIdentityRefs[]  
  sourceVersionRefs[]  
  lifecycleState  
  relationshipRefs[]  
  decisionRefs[]  
  intentRefs[]  
  evidenceSetRef  
  knowledgeCutoff  
  policyRefs[]  
  authorityRef  
  jurisdictionRefs[]  
  createdAt  
  effectiveAt  
  updatedAt  
  version  
  correctionOf?  
  correlationId  
}
```

2.1 Core invariants

- Stable identity precedes relationship, state, and cross-system correlation.
- Effective time and recorded time remain distinct where business truth changes over time.
- Recommendation, Decision, Intent, execution, and outcome are separate concepts.
- No Portal, report, search index, cache, workflow, or AI Agent becomes a shadow owner of Domain truth.
- Binding submitted, approved, issued, accepted, or signed versions are immutable.
- Corrections append governed facts and preserve the original record.
- External authority and provider outcomes retain their source and qualification.
- Tenant and represented-principal context come from trusted authentication and mandate evaluation.
- Retried writes are idempotent and concurrency guarded.
- Outcome Unknown is explicit and reconciled before risky duplicate execution.

2.2 Required standards

- stable identifiers
- typed contracts
- immutable binding versions

- transactional outbox
- idempotent Commands
- explicit Outcome Unknown
- correction lineage
- machine-verifiable conformance

3. Actors, Roles, and Authority

- A conformant design distinguishes:
- the natural person acting;
 - the service or AI identity invoking a Tool;
 - the organization or principal represented;
 - the role or relationship granting context;
 - the mandate or delegation granting action authority;
 - the Policy and jurisdiction limiting the action;
 - the reviewer or approver responsible for a binding Decision.

Authority is evaluated at action time. Authentication alone does not grant business authority. Cached permissions and browser-supplied tenant headers are insufficient for high-impact actions.

4. Lifecycle and State Model

State	Semantics
PROPOSED	Distinct governed condition with entry, exit, timeout, correction and authority semantics
VALIDATION_PENDING	Distinct governed condition with entry, exit, timeout, correction and authority semantics
APPROVAL_PENDING	Distinct governed condition with entry, exit, timeout, correction and authority semantics
ACTIVE	Distinct governed condition with entry, exit, timeout, correction and authority semantics
SUSPENDED	Distinct governed condition with entry, exit, timeout, correction and authority semantics
CORRECTION_PENDING	Distinct governed condition with entry, exit, timeout, correction and authority semantics
RETIRED	Distinct governed condition with entry, exit, timeout, correction and authority semantics

```
stateDiagram-v2
    [*] --> PROPOSED
    PROPOSED --> VALIDATION_PENDING
    VALIDATION_PENDING --> APPROVAL_PENDING
    APPROVAL_PENDING --> ACTIVE
    ACTIVE --> SUSPENDED
    SUSPENDED --> CORRECTION_PENDING
    CORRECTION_PENDING --> RETIRED
```

The diagram is a primary reading path. Real implementations may add parallel review, amendment, appeal, timeout, suspension, partial completion, reconciliation, correction, and terminal failure without collapsing their meaning.

4.1 Transition rules

- transition through a typed, authorized Command;
- require exact expected version where concurrent change matters;
- record actor, represented principal, mandate, Policy, reason, and Evidence;
- use an idempotency key for retried writes;
- publish a completed-fact Event after durable state change;
- expose Outcome Unknown for unresolved external completion;
- preserve original and corrected states in historical reconstruction.

5. Decision, Evidence, and Knowledge Cutoff

Reference Decision:

```
Decision {
  decisionId
  decisionType
  subjectRef
  sourceVersionRefs[]
  knowledgeCutoff
  evidenceSetRef
  policyVersionRefs[]
  recommendationRefs[]
  principalId
  representedOrganizationId
  mandateRef
  rationale
  outcome
  decidedAt
  effectiveAt
  correctionOf?
}
```

Evidence records identify issuer or observer, subject, version, observed time, received time, effective interval, integrity, confidence, qualification, contradiction, correction, retention, residency, and access class. A recommendation may assist the Decision but cannot promote itself to the Decision.

6. Commands, Events, Queries, and Contracts

Reference Commands:

- CreateDeveloperPortalAccessModel
- ValidateDeveloperPortalAccessModel
- ApproveDeveloperPortalAccessModel
- ActivateDeveloperPortalAccessModel
- SuspendDeveloperPortalAccessModel
- CorrectDeveloperPortalAccessModel
- RetireDeveloperPortalAccessModel

Reference Events:

- DeveloperPortalAccessModelCreated
- DeveloperPortalAccessModelValidated
- DeveloperPortalAccessModelApproved
- DeveloperPortalAccessModelActivated
- DeveloperPortalAccessModelSuspended
- DeveloperPortalAccessModelCorrected
- DeveloperPortalAccessModelRetired

Reference queries:

- GetDeveloperPortalAccessModel
- ListDeveloperPortalAccessModelRecords
- GetDeveloperPortalAccessModelTimeline
- GetDeveloperPortalAccessModelEvidence
- GetDeveloperPortalAccessModelDecisionPackage
- GetDeveloperPortalAccessModelExceptions
- GetDeveloperPortalAccessModelAuditTrail

Reference API surface:

```
POST /api/v1/developerportalaccessmodel/commands
GET  /api/v1/developerportalaccessmodel/{id}
GET  /api/v1/developerportalaccessmodel/{id}/timeline
GET  /api/v1/developerportalaccessmodel/{id}/evidence
GET  /api/v1/developerportalaccessmodel/{id}/decisions
POST /api/v1/developerportalaccessmodel/{id}/exceptions
POST /api/v1/developerportalaccessmodel/{id}/corrections
```

These endpoints are reference contracts, not claims that exact routes exist.

7. Workflow, Failure, and Compensation

flowchart TD

```
A[Validate identity version and authority] --> B[Collect required evidence]
B --> C{Policy and evidence gates pass?}
C -- No --> D[Open exception or request correction]
D --> B
C -- Yes --> E[Record Decision or execution Intent]
E --> F[Execute Domain command or external request]
F --> G{Outcome known?}
G -- Success --> H[Record fact and publish Event]
G -- Failure --> I[Record failure and compensation options]
G -- Unknown --> J[Enter Outcome Unknown]
J --> K[Query source or wait for verified callback]
K --> G
H --> L[Update projections and downstream workflow]
```

Representative failure modes:

- stale or wrong source version
- duplicate submission or replay
- external timeout after possible success
- contradictory source observations
- lost Event after committed state
- approval or mandate revoked during execution
- downstream action before a mandatory gate
- partial completion across multiple subjects
- evidence later retracted or corrected
- tenant, facility, channel or jurisdiction mismatch

Recovery shall query the authoritative source before duplicate execution, preserve partial success, use compensating Intent rather than destructive rewrite, publish corrections, quarantine high-impact ambiguity, and record affected downstream subjects.

8. Data and Persistence Architecture

Reference table families:

Table family	Purpose
developerportalaccessmodel_aggregate	authoritative subject
developerportalaccessmodel_version	immutable submitted, approved, issued, or signed versions
developerportalaccessmodel_relationship	governed relationships
developerportalaccessmodel_decision	binding Decisions and rationale
developerportalaccessmodel_evidence_link	provenance and evidence relationships
developerportalaccessmodel_event_outbox	transactional Event publication
developerportalaccessmodel_idempotency	duplicate-write protection
developerportalaccessmodel_exception	exception, claim, dispute, or hold
developerportalaccessmodel_correction	correction and supersession lineage
developerportalaccessmodel_audit	privileged action evidence

The owning service controls schema and migration. Cross-Domain references use stable identifiers or contracts. Analytics, reports, caches, search, and vector indexes remain projections. Backup, restore, retention, legal hold, privacy, residency, and decommissioning requirements are explicit.

9. Portal and Experience Requirements

- Developer Portal: primary experience for internal and external developers.
- Operator and support views: diagnose failed or ambiguous journeys without assuming Domain ownership.
- Domain services: own authoritative data and action eligibility; the Portal consumes typed contracts.

Every Portal displays exact version, owner, state, freshness, required action, and uncertainty. It supports loading, empty, partial, stale, denied, error, timeout, and Outcome Unknown states; accessibility; locale, currency, unit, date, and RTL/LTR correctness; evidence audit; safe retry; and correction history.

10. AI Participation and Tool Governance

Permitted AI tasks:

- extract and classify evidence
- detect anomalies and missing fields
- summarize timelines and contradictions
- recommend next actions with sources and uncertainty

AI shall not own Domain records, grant itself authority, suppress contradictions, silently edit approved versions, fabricate external outcomes, or execute high-impact actions outside typed Tools, policy, approval, idempotency, sandbox, and outcome observation.

Every Agent Run records source context, prompt/model/tool versions, structured output, confidence and limitations, Policy result, approval, Tool calls, provider responses, final outcome, and recovery actions.

11. Security, Privacy, and Trust Boundaries

- least privilege and separation of duties
- tenant, organization, facility, channel and jurisdiction isolation
- integrity protection for binding evidence
- verified external callbacks and anti-replay controls

Additional controls include secret isolation, callback signature verification, audit of privileged action, emergency-access review, sensitive-data minimization, purpose limitation, and threat models for impersonation, tampering, replay, confused deputy, fraud, prompt injection, and exfiltration.

12. Reliability, SLOs, and Operations

SLI	Reference objective
authoritative read availability	99.9% monthly unless a stricter tier applies
acknowledged Command durability	no acknowledged write may be silently lost
Event publication	99.9% within five minutes after committed fact
duplicate prevention	100% for same tenant, Command class, and idempotency key
binding Decision audit completeness	100%
state-state detection	bounded by business deadline

Dashboards and runbooks cover backlog, error budget, dependency failure, retry budget, DLQ, workflow stall, provider outage, reconciliation, capacity, backup/restore, release/rollback, incident command, and post-incident correction.

13. Testing and Continuous Conformance

- aggregate invariant and transition tests
- authorization, delegation, separation-of-duties and tenant-isolation tests
- idempotency and optimistic-concurrency tests
- database migration, key, constraint and rollback tests
- contract, outbox/inbox, duplicate, replay and DLQ tests
- workflow restart, timeout and compensation tests
- Portal E2E tests for success, partial, stale, denied, error and Outcome Unknown states
- accessibility, locale, currency, unit and RTL/LTR tests
- security adversarial, fraud and data-exfiltration tests
- AI evaluation, prompt-injection, policy-bypass and unauthorized-tool tests
- historical reconstruction, correction and audit-completeness tests
- performance, capacity, recovery and operational exercise tests

Release evidence links each invariant and control to the test, environment, input data, result, owner, and artifact proving it. Generated test counts never replace semantic coverage.

14. Repository Review Boundary

- This chapter is a repository-review specification. Exact executable implementation has not been inspected for every target behavior.
- Registered modules, catalog entries, README claims, frontend contracts, or plans are not proof of complete implementation.

Area	Classification
target aggregate, API, tables, state and workflow in this chapter	REFERENCE_ARCHITECTURE
registered module or catalog claim	DOCUMENTATION_ONLY_CLAIM until source inspection
uninspected integration	REQUIRES_REPOSITORY_REVIEW
behavior proven in another repository-grounded chapter	retain that chapter's evidence and classification
contradictory ownership or path claims	CONFLICT_REQUIRES_CANONICALIZATION

No statement upgrades implementation status merely because a file, directory, module name, frontend contract, database entry, plan, or report exists.

15. Worked Conformance Scenario

An authorized principal initiates a Command against an exact subject version. The service validates identity, tenant, mandate, Policy, Evidence, and idempotency. It records the state transition and outbox entry atomically. If an external dependency participates, timeout produces Outcome Unknown; reconciliation queries the source or waits for a verified callback instead of repeating the action blindly.

Portals show source, freshness, version, required action, and uncertainty. AI may extract, compare, summarize, detect anomalies, and recommend through typed Tools, but cannot own the subject or fabricate success. Later correction appends new facts, identifies affected projections and workflows, and preserves the historical Decision context.

16. Conformance Checklist

- ☐ stable identity and proposition ownership are explicit;
- ☐ authority and mandate are evaluated at action time;
- ☐ state, Recommendation, Decision, Intent, execution, and outcome remain distinct;
- ☐ Commands are typed, authorized, idempotent, and version guarded;
- ☐ Events describe completed facts;
- ☐ Evidence includes provenance, time, integrity, qualification, and correction;
- ☐ external outcomes retain their authority source;
- ☐ Portals show freshness and uncertainty;
- ☐ AI is bounded by typed Tools, Policy, approval, and outcome observation;
- ☐ security, tenant, facility, channel, and jurisdiction boundaries are enforced;
- ☐ Outcome Unknown and reconciliation exist where needed;
- ☐ corrections preserve history;
- ☐ tests prove invariants and recovery;
- ☐ implementation status is not upgraded without executable evidence.

17. Status Vocabulary

Status	Meaning
VERIFIED_IMPLEMENTED	Executable source and relevant behavior were inspected.
IMPLEMENTED_WITH_GAP	Executable behavior exists with a material governance or completeness gap.
PARTIAL_IMPLEMENTATION	Only part of the target capability is evidenced.
REFERENCE_ARCHITECTURE	Normative target behavior; no claim that it exists today.
PLANNED_NOT_IMPLEMENTED	Explicitly planned but not evidenced as executable.
DOCUMENTATION_ONLY_CLAIM	Documentation or client contract claims behavior without verified backend evidence.
CONFLICT_REQUIRES_CANONICALIZATION	Sources disagree and no final owner has been established.
REQUIRES_REPOSITORY_REVIEW	Necessary executable evidence has not yet been inspected.

Developer Portal — UX States, Accessibility, Localization, Analytics, and E2E

Metadata	Value
Volume	4
Chapter ID	V04-P08-03
Subject	DeveloperPortalExperienceStandard
Status	Generated First-Draft Architecture Skeleton - Domain-Specific Expansion Required
Content maturity	TEMPLATE_DERIVED_REFERENCE_SKELETON unless repository citations prove otherwise
Default implementation classification	REFERENCE_ARCHITECTURE / REQUIRES_REPOSITORY_REVIEW
Accountable owner	Portal Architecture / Developer Portal
Evidence rule	No implementation claim without inspected executable evidence
Repository	chinair88-prog/allinb2c

1. Executive Orientation

This chapter defines how GTOS shall **specify loading, empty, partial, stale, error, denied, offline, accessibility, RTL/LTR, analytics, audit and test journeys for internal and external developers, covering API discovery, credentials, contracts, sandbox, webhook, documentation, certification.**

The specification separates reality, observations, knowledge, Decisions, Intent, execution, and outcomes. A component name, database row, UI label, AI answer, or workflow state does not acquire authority merely because it is visible or technically convenient.

Reality or external outcome

- ≠ Observation
- ≠ Claim
- ≠ derived Perspective
- ≠ Prediction
- ≠ Recommendation
- ≠ authorized Decision
- ≠ execution Intent

1.1 Accountable ownership

The accountable owner is **Portal Architecture / Developer Portal**. Supporting applications, shared infrastructure, integration adapters, analytics, and AI coordinate or present the capability but shall not silently own its authoritative propositions.

1.2 Scope

- create and identify the subject
- validate evidence and policy
- make authorized Decisions
- execute typed Commands
- publish completed-fact Events
- query current and historical perspectives
- correct and reconcile outcomes

1.3 Non-goals

- treating a registered Gradle module, catalog record, README, frontend route, migration plan, or generated report as proof of end-to-end implementation;
- direct cross-Domain database writes;
- generic status values that combine lifecycle, approval, provider, document, payment, dispute, and correction state;
- silent replacement of history;
- AI-created authority or fabricated external outcomes.

2. Ubiquitous Language and Subject Model

Subject	Required interpretation
DeveloperPortalExperienceStandard	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit
DeveloperPortalExperienceStandardVersion	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit
DeveloperPortalExperienceStandardDecision	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit
DeveloperPortalExperienceStandardEvidenceSet	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit
DeveloperPortalExperienceStandardException	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit

Reference aggregate:

```
DeveloperPortalExperienceStandard {  
  subjectId  
  tenantId  
  organizationContext  
  sourceIdentityRefs[]  
  sourceVersionRefs[]  
  lifecycleState  
  relationshipRefs[]  
  decisionRefs[]  
  intentRefs[]  
  evidenceSetRef  
  knowledgeCutoff  
  policyRefs[]  
  authorityRef  
  jurisdictionRefs[]  
  createdAt  
  effectiveAt  
  updatedAt  
  version  
  correctionOf?  
  correlationId  
}
```

2.1 Core invariants

- Stable identity precedes relationship, state, and cross-system correlation.
- Effective time and recorded time remain distinct where business truth changes over time.
- Recommendation, Decision, Intent, execution, and outcome are separate concepts.
- No Portal, report, search index, cache, workflow, or AI Agent becomes a shadow owner of Domain truth.
- Binding submitted, approved, issued, accepted, or signed versions are immutable.
- Corrections append governed facts and preserve the original record.
- External authority and provider outcomes retain their source and qualification.
- Tenant and represented-principal context come from trusted authentication and mandate evaluation.
- Retried writes are idempotent and concurrency guarded.
- Outcome Unknown is explicit and reconciled before risky duplicate execution.

2.2 Required standards

- stable identifiers
- typed contracts
- immutable binding versions

- transactional outbox
- idempotent Commands
- explicit Outcome Unknown
- correction lineage
- machine-verifiable conformance

3. Actors, Roles, and Authority

A conformant design distinguishes:

- the natural person acting;
- the service or AI identity invoking a Tool;
- the organization or principal represented;
- the role or relationship granting context;
- the mandate or delegation granting action authority;
- the Policy and jurisdiction limiting the action;
- the reviewer or approver responsible for a binding Decision.

Authority is evaluated at action time. Authentication alone does not grant business authority. Cached permissions and browser-supplied tenant headers are insufficient for high-impact actions.

4. Lifecycle and State Model

State	Semantics
PROPOSED	Distinct governed condition with entry, exit, timeout, correction and authority semantics
VALIDATION_PENDING	Distinct governed condition with entry, exit, timeout, correction and authority semantics
APPROVAL_PENDING	Distinct governed condition with entry, exit, timeout, correction and authority semantics
ACTIVE	Distinct governed condition with entry, exit, timeout, correction and authority semantics
SUSPENDED	Distinct governed condition with entry, exit, timeout, correction and authority semantics
CORRECTION_PENDING	Distinct governed condition with entry, exit, timeout, correction and authority semantics
RETIRED	Distinct governed condition with entry, exit, timeout, correction and authority semantics

```
stateDiagram-v2
    [*] --> PROPOSED
    PROPOSED --> VALIDATION_PENDING
    VALIDATION_PENDING --> APPROVAL_PENDING
    APPROVAL_PENDING --> ACTIVE
    ACTIVE --> SUSPENDED
    SUSPENDED --> CORRECTION_PENDING
    CORRECTION_PENDING --> RETIRED
```

The diagram is a primary reading path. Real implementations may add parallel review, amendment, appeal, timeout, suspension, partial completion, reconciliation, correction, and terminal failure without collapsing their meaning.

4.1 Transition rules

- transition through a typed, authorized Command;
- require exact expected version where concurrent change matters;
- record actor, represented principal, mandate, Policy, reason, and Evidence;
- use an idempotency key for retried writes;
- publish a completed-fact Event after durable state change;
- expose Outcome Unknown for unresolved external completion;
- preserve original and corrected states in historical reconstruction.

5. Decision, Evidence, and Knowledge Cutoff

Reference Decision:

```
Decision {
  decisionId
  decisionType
  subjectRef
  sourceVersionRefs[]
  knowledgeCutoff
  evidenceSetRef
  policyVersionRefs[]
  recommendationRefs[]
  principalId
  representedOrganizationId
  mandateRef
  rationale
  outcome
  decidedAt
  effectiveAt
  correctionOf?
}
```

Evidence records identify issuer or observer, subject, version, observed time, received time, effective interval, integrity, confidence, qualification, contradiction, correction, retention, residency, and access class. A recommendation may assist the Decision but cannot promote itself to the Decision.

6. Commands, Events, Queries, and Contracts

Reference Commands:

- CreateDeveloperPortalExperienceStandard
- ValidateDeveloperPortalExperienceStandard
- ApproveDeveloperPortalExperienceStandard
- ActivateDeveloperPortalExperienceStandard
- SuspendDeveloperPortalExperienceStandard
- CorrectDeveloperPortalExperienceStandard
- RetireDeveloperPortalExperienceStandard

Reference Events:

- DeveloperPortalExperienceStandardCreated
- DeveloperPortalExperienceStandardValidated
- DeveloperPortalExperienceStandardApproved
- DeveloperPortalExperienceStandardActivated
- DeveloperPortalExperienceStandardSuspended
- DeveloperPortalExperienceStandardCorrected
- DeveloperPortalExperienceStandardRetired

Reference queries:

- GetDeveloperPortalExperienceStandard
- ListDeveloperPortalExperienceStandardRecords
- GetDeveloperPortalExperienceStandardTimeline
- GetDeveloperPortalExperienceStandardEvidence
- GetDeveloperPortalExperienceStandardDecisionPackage
- GetDeveloperPortalExperienceStandardExceptions
- GetDeveloperPortalExperienceStandardAuditTrail

Reference API surface:

```
POST /api/v1/developerportalexperiencstandard/commands
GET  /api/v1/developerportalexperiencstandard/{id}
GET  /api/v1/developerportalexperiencstandard/{id}/timeline
GET  /api/v1/developerportalexperiencstandard/{id}/evidence
GET  /api/v1/developerportalexperiencstandard/{id}/decisions
POST /api/v1/developerportalexperiencstandard/{id}/exceptions
POST /api/v1/developerportalexperiencstandard/{id}/corrections
```

These endpoints are reference contracts, not claims that exact routes exist.

7. Workflow, Failure, and Compensation

flowchart TD

```
A[Validate identity version and authority] --> B[Collect required evidence]
B --> C{Policy and evidence gates pass?}
C -- No --> D[Open exception or request correction]
D --> B
C -- Yes --> E[Record Decision or execution Intent]
E --> F[Execute Domain command or external request]
F --> G{Outcome known?}
G -- Success --> H[Record fact and publish Event]
G -- Failure --> I[Record failure and compensation options]
G -- Unknown --> J[Enter Outcome Unknown]
J --> K[Query source or wait for verified callback]
K --> G
H --> L[Update projections and downstream workflow]
```

Representative failure modes:

- stale or wrong source version
- duplicate submission or replay
- external timeout after possible success
- contradictory source observations
- lost Event after committed state
- approval or mandate revoked during execution
- downstream action before a mandatory gate
- partial completion across multiple subjects
- evidence later retracted or corrected
- tenant, facility, channel or jurisdiction mismatch

Recovery shall query the authoritative source before duplicate execution, preserve partial success, use compensating Intent rather than destructive rewrite, publish corrections, quarantine high-impact ambiguity, and record affected downstream subjects.

8. Data and Persistence Architecture

Reference table families:

Table family	Purpose
developerportalexperiencestandard_aggregate	authoritative subject
developerportalexperiencestandard_version	immutable submitted, approved, issued, or signed versions
developerportalexperiencestandard_relationship	governed relationships
developerportalexperiencestandard_decision	binding Decisions and rationale
developerportalexperiencestandard_evidence_link	provenance and evidence relationships
developerportalexperiencestandard_event_outbox	transactional Event publication
developerportalexperiencestandard_idempotency	duplicate-write protection
developerportalexperiencestandard_exception	exception, claim, dispute, or hold
developerportalexperiencestandard_correction	correction and supersession lineage
developerportalexperiencestandard_audit	privileged action evidence

The owning service controls schema and migration. Cross-Domain references use stable identifiers or contracts. Analytics, reports, caches, search, and vector indexes remain projections. Backup, restore, retention, legal hold, privacy, residency, and decommissioning requirements are explicit.

9. Portal and Experience Requirements

- Developer Portal: primary experience for internal and external developers.
- Operator and support views: diagnose failed or ambiguous journeys without assuming Domain ownership.
- Domain services: own authoritative data and action eligibility; the Portal consumes typed contracts.

Every Portal displays exact version, owner, state, freshness, required action, and uncertainty. It supports loading, empty, partial, stale, denied, error, timeout, and Outcome Unknown states; accessibility; locale, currency, unit, date, and RTL/LTR correctness; evidence audit; safe retry; and correction history.

10. AI Participation and Tool Governance

Permitted AI tasks:

- extract and classify evidence
- detect anomalies and missing fields
- summarize timelines and contradictions
- recommend next actions with sources and uncertainty

AI shall not own Domain records, grant itself authority, suppress contradictions, silently edit approved versions, fabricate external outcomes, or execute high-impact actions outside typed Tools, policy, approval, idempotency, sandbox, and outcome observation.

Every Agent Run records source context, prompt/model/tool versions, structured output, confidence and limitations, Policy result, approval, Tool calls, provider responses, final outcome, and recovery actions.

11. Security, Privacy, and Trust Boundaries

- least privilege and separation of duties
- tenant, organization, facility, channel and jurisdiction isolation
- integrity protection for binding evidence
- verified external callbacks and anti-replay controls

Additional controls include secret isolation, callback signature verification, audit of privileged action, emergency-access review, sensitive-data minimization, purpose limitation, and threat models for impersonation, tampering, replay, confused deputy, fraud, prompt injection, and exfiltration.

12. Reliability, SLOs, and Operations

SLI	Reference objective
authoritative read availability	99.9% monthly unless a stricter tier applies
acknowledged Command durability	no acknowledged write may be silently lost
Event publication	99.9% within five minutes after committed fact
duplicate prevention	100% for same tenant, Command class, and idempotency key
binding Decision audit completeness	100%
state-state detection	bounded by business deadline

Dashboards and runbooks cover backlog, error budget, dependency failure, retry budget, DLQ, workflow stall, provider outage, reconciliation, capacity, backup/restore, release/rollback, incident command, and post-incident correction.

13. Testing and Continuous Conformance

- aggregate invariant and transition tests
- authorization, delegation, separation-of-duties and tenant-isolation tests
- idempotency and optimistic-concurrency tests
- database migration, key, constraint and rollback tests
- contract, outbox/inbox, duplicate, replay and DLQ tests
- workflow restart, timeout and compensation tests
- Portal E2E tests for success, partial, stale, denied, error and Outcome Unknown states
- accessibility, locale, currency, unit and RTL/LTR tests
- security adversarial, fraud and data-exfiltration tests
- AI evaluation, prompt-injection, policy-bypass and unauthorized-tool tests
- historical reconstruction, correction and audit-completeness tests
- performance, capacity, recovery and operational exercise tests

Release evidence links each invariant and control to the test, environment, input data, result, owner, and artifact proving it. Generated test counts never replace semantic coverage.

14. Repository Review Boundary

- This chapter is a repository-review specification. Exact executable implementation has not been inspected for every target behavior.
- Registered modules, catalog entries, README claims, frontend contracts, or plans are not proof of complete implementation.

Area	Classification
target aggregate, API, tables, state and workflow in this chapter	REFERENCE_ARCHITECTURE
registered module or catalog claim	DOCUMENTATION_ONLY_CLAIM until source inspection
uninspected integration	REQUIRES_REPOSITORY_REVIEW
behavior proven in another repository-grounded chapter	retain that chapter's evidence and classification
contradictory ownership or path claims	CONFLICT_REQUIRES_CANONICALIZATION

No statement upgrades implementation status merely because a file, directory, module name, frontend contract, database entry, plan, or report exists.

15. Worked Conformance Scenario

An authorized principal initiates a Command against an exact subject version. The service validates identity, tenant, mandate, Policy, Evidence, and idempotency. It records the state transition and outbox entry atomically. If an external dependency participates, timeout produces Outcome Unknown; reconciliation queries the source or waits for a verified callback instead of repeating the action blindly.

Portals show source, freshness, version, required action, and uncertainty. AI may extract, compare, summarize, detect anomalies, and recommend through typed Tools, but cannot own the subject or fabricate success. Later correction appends new facts, identifies affected projections and workflows, and preserves the historical Decision context.

16. Conformance Checklist

- ☐ stable identity and proposition ownership are explicit;
- ☐ authority and mandate are evaluated at action time;
- ☐ state, Recommendation, Decision, Intent, execution, and outcome remain distinct;
- ☐ Commands are typed, authorized, idempotent, and version guarded;
- ☐ Events describe completed facts;
- ☐ Evidence includes provenance, time, integrity, qualification, and correction;
- ☐ external outcomes retain their authority source;
- ☐ Portals show freshness and uncertainty;
- ☐ AI is bounded by typed Tools, Policy, approval, and outcome observation;
- ☐ security, tenant, facility, channel, and jurisdiction boundaries are enforced;
- ☐ Outcome Unknown and reconciliation exist where needed;
- ☐ corrections preserve history;
- ☐ tests prove invariants and recovery;
- ☐ implementation status is not upgraded without executable evidence.

17. Status Vocabulary

Status	Meaning
VERIFIED_IMPLEMENTED	Executable source and relevant behavior were inspected. Executable behavior exists with a material governance or completeness gap.
IMPLEMENTED_WITH_GAP	
PARTIAL_IMPLEMENTATION	Only part of the target capability is evidenced.
REFERENCE_ARCHITECTURE	Normative target behavior; no claim that it exists today.
PLANNED_NOT_IMPLEMENTED	Explicitly planned but not evidenced as executable.
DOCUMENTATION_ONLY_CLAIM	Documentation or client contract claims behavior without verified backend evidence.
CONFLICT_REQUIRES_CANONICALIZATION	Sources disagree and no final owner has been established.
REQUIRES_REPOSITORY_REVIEW	Necessary executable evidence has not yet been inspected.

WhatsApp Admin — Portal Orientation and Information Architecture

Metadata	Value
Volume	4
Chapter ID	V04-P09-00
Subject	WhatsAppAdminPortal
Status	Generated First-Draft Architecture Skeleton - Domain-Specific Expansion Required
Content maturity	TEMPLATE_DERIVED_REFERENCE_SKELETON unless repository citations prove otherwise
Default implementation classification	REFERENCE_ARCHITECTURE / REQUIRES_REPOSITORY_REVIEW
Accountable owner	Portal Architecture / WhatsApp Admin
Evidence rule	No implementation claim without inspected executable evidence
Repository	chinair88-prog/allinb2c

1. Executive Orientation

This chapter defines how GTOS shall **define personas, navigation, route ownership, domain dependencies and experience boundaries for channel operators and support managers, covering templates, consent, conversation routing, provider state, human handoff, audit.**

The specification separates reality, observations, knowledge, Decisions, Intent, execution, and outcomes. A component name, database row, UI label, AI answer, or workflow state does not acquire authority merely because it is visible or technically convenient.

Reality or external outcome

- ≠ Observation
- ≠ Claim
- ≠ derived Perspective
- ≠ Prediction
- ≠ Recommendation
- ≠ authorized Decision
- ≠ execution Intent

1.1 Accountable ownership

The accountable owner is **Portal Architecture / WhatsApp Admin**. Supporting applications, shared infrastructure, integration adapters, analytics, and AI coordinate or present the capability but shall not silently own its authoritative propositions.

1.2 Scope

- create and identify the subject
- validate evidence and policy
- make authorized Decisions
- execute typed Commands
- publish completed-fact Events
- query current and historical perspectives
- correct and reconcile outcomes

1.3 Non-goals

- treating a registered Gradle module, catalog record, README, frontend route, migration plan, or generated report as proof of end-to-end implementation;
- direct cross-Domain database writes;
- generic status values that combine lifecycle, approval, provider, document, payment, dispute, and correction state;
- silent replacement of history;
- AI-created authority or fabricated external outcomes.

2. Ubiquitous Language and Subject Model

Subject	Required interpretation
WhatsAppAdminPortal	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit
WhatsAppAdminPortalVersion	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit
WhatsAppAdminPortalDecision	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit
WhatsAppAdminPortalEvidenceSet	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit
WhatsAppAdminPortalException	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit

Reference aggregate:

```
WhatsAppAdminPortal {  
  subjectId  
  tenantId  
  organizationContext  
  sourceIdentityRefs[]  
  sourceVersionRefs[]  
  lifecycleState  
  relationshipRefs[]  
  decisionRefs[]  
  intentRefs[]  
  evidenceSetRef  
  knowledgeCutoff  
  policyRefs[]  
  authorityRef  
  jurisdictionRefs[]  
  createdAt  
  effectiveAt  
  updatedAt  
  version  
  correctionOf?  
  correlationId  
}
```

2.1 Core invariants

- Stable identity precedes relationship, state, and cross-system correlation.
- Effective time and recorded time remain distinct where business truth changes over time.
- Recommendation, Decision, Intent, execution, and outcome are separate concepts.
- No Portal, report, search index, cache, workflow, or AI Agent becomes a shadow owner of Domain truth.
- Binding submitted, approved, issued, accepted, or signed versions are immutable.
- Corrections append governed facts and preserve the original record.
- External authority and provider outcomes retain their source and qualification.
- Tenant and represented-principal context come from trusted authentication and mandate evaluation.
- Retried writes are idempotent and concurrency guarded.
- Outcome Unknown is explicit and reconciled before risky duplicate execution.

2.2 Required standards

- stable identifiers
- typed contracts
- immutable binding versions

- transactional outbox
- idempotent Commands
- explicit Outcome Unknown
- correction lineage
- machine-verifiable conformance

3. Actors, Roles, and Authority

A conformant design distinguishes:

- the natural person acting;
- the service or AI identity invoking a Tool;
- the organization or principal represented;
- the role or relationship granting context;
- the mandate or delegation granting action authority;
- the Policy and jurisdiction limiting the action;
- the reviewer or approver responsible for a binding Decision.

Authority is evaluated at action time. Authentication alone does not grant business authority. Cached permissions and browser-supplied tenant headers are insufficient for high-impact actions.

4. Lifecycle and State Model

State	Semantics
PROPOSED	Distinct governed condition with entry, exit, timeout, correction and authority semantics
VALIDATION_PENDING	Distinct governed condition with entry, exit, timeout, correction and authority semantics
APPROVAL_PENDING	Distinct governed condition with entry, exit, timeout, correction and authority semantics
ACTIVE	Distinct governed condition with entry, exit, timeout, correction and authority semantics
SUSPENDED	Distinct governed condition with entry, exit, timeout, correction and authority semantics
CORRECTION_PENDING	Distinct governed condition with entry, exit, timeout, correction and authority semantics
RETIRED	Distinct governed condition with entry, exit, timeout, correction and authority semantics

```
stateDiagram-v2
    [*] --> PROPOSED
    PROPOSED --> VALIDATION_PENDING
    VALIDATION_PENDING --> APPROVAL_PENDING
    APPROVAL_PENDING --> ACTIVE
    ACTIVE --> SUSPENDED
    SUSPENDED --> CORRECTION_PENDING
    CORRECTION_PENDING --> RETIRED
```

The diagram is a primary reading path. Real implementations may add parallel review, amendment, appeal, timeout, suspension, partial completion, reconciliation, correction, and terminal failure without collapsing their meaning.

4.1 Transition rules

- transition through a typed, authorized Command;
- require exact expected version where concurrent change matters;
- record actor, represented principal, mandate, Policy, reason, and Evidence;
- use an idempotency key for retried writes;
- publish a completed-fact Event after durable state change;
- expose Outcome Unknown for unresolved external completion;
- preserve original and corrected states in historical reconstruction.

5. Decision, Evidence, and Knowledge Cutoff

Reference Decision:

```
Decision {
  decisionId
  decisionType
  subjectRef
  sourceVersionRefs[]
  knowledgeCutoff
  evidenceSetRef
  policyVersionRefs[]
  recommendationRefs[]
  principalId
  representedOrganizationId
  mandateRef
  rationale
  outcome
  decidedAt
  effectiveAt
  correctionOf?
}
```

Evidence records identify issuer or observer, subject, version, observed time, received time, effective interval, integrity, confidence, qualification, contradiction, correction, retention, residency, and access class. A recommendation may assist the Decision but cannot promote itself to the Decision.

6. Commands, Events, Queries, and Contracts

Reference Commands:

- CreateWhatsAppAdminPortal
- ValidateWhatsAppAdminPortal
- ApproveWhatsAppAdminPortal
- ActivateWhatsAppAdminPortal
- SuspendWhatsAppAdminPortal
- CorrectWhatsAppAdminPortal
- RetireWhatsAppAdminPortal

Reference Events:

- WhatsAppAdminPortalCreated
- WhatsAppAdminPortalValidated
- WhatsAppAdminPortalApproved
- WhatsAppAdminPortalActivated
- WhatsAppAdminPortalSuspended
- WhatsAppAdminPortalCorrected
- WhatsAppAdminPortalRetired

Reference queries:

- GetWhatsAppAdminPortal
- ListWhatsAppAdminPortalRecords
- GetWhatsAppAdminPortalTimeline
- GetWhatsAppAdminPortalEvidence
- GetWhatsAppAdminPortalDecisionPackage
- GetWhatsAppAdminPortalExceptions
- GetWhatsAppAdminPortalAuditTrail

Reference API surface:

```
POST /api/v1/whatsappadminportal/commands
GET  /api/v1/whatsappadminportal/{id}
GET  /api/v1/whatsappadminportal/{id}/timeline
GET  /api/v1/whatsappadminportal/{id}/evidence
GET  /api/v1/whatsappadminportal/{id}/decisions
POST /api/v1/whatsappadminportal/{id}/exceptions
POST /api/v1/whatsappadminportal/{id}/corrections
```

These endpoints are reference contracts, not claims that exact routes exist.

7. Workflow, Failure, and Compensation

flowchart TD

```
A[Validate identity version and authority] --> B[Collect required evidence]
B --> C{Policy and evidence gates pass?}
C -- No --> D[Open exception or request correction]
D --> B
C -- Yes --> E[Record Decision or execution Intent]
E --> F[Execute Domain command or external request]
F --> G{Outcome known?}
G -- Success --> H[Record fact and publish Event]
G -- Failure --> I[Record failure and compensation options]
G -- Unknown --> J[Enter Outcome Unknown]
J --> K[Query source or wait for verified callback]
K --> G
H --> L[Update projections and downstream workflow]
```

Representative failure modes:

- stale or wrong source version
- duplicate submission or replay
- external timeout after possible success
- contradictory source observations
- lost Event after committed state
- approval or mandate revoked during execution
- downstream action before a mandatory gate
- partial completion across multiple subjects
- evidence later retracted or corrected
- tenant, facility, channel or jurisdiction mismatch

Recovery shall query the authoritative source before duplicate execution, preserve partial success, use compensating Intent rather than destructive rewrite, publish corrections, quarantine high-impact ambiguity, and record affected downstream subjects.

8. Data and Persistence Architecture

Reference table families:

Table family	Purpose
whatsappadminportal_aggregate	authoritative subject
whatsappadminportal_version	immutable submitted, approved, issued, or signed versions
whatsappadminportal_relationship	governed relationships
whatsappadminportal_decision	binding Decisions and rationale
whatsappadminportal_evidence_link	provenance and evidence relationships
whatsappadminportal_event_outbox	transactional Event publication
whatsappadminportal_idempotency	duplicate-write protection
whatsappadminportal_exception	exception, claim, dispute, or hold
whatsappadminportal_correction	correction and supersession lineage
whatsappadminportal_audit	privileged action evidence

The owning service controls schema and migration. Cross-Domain references use stable identifiers or contracts. Analytics, reports, caches, search, and vector indexes remain projections. Backup, restore, retention, legal hold, privacy, residency, and decommissioning requirements are explicit.

9. Portal and Experience Requirements

- WhatsApp Admin: primary experience for channel operators and support managers.
- Operator and support views: diagnose failed or ambiguous journeys without assuming Domain ownership.
- Domain services: own authoritative data and action eligibility; the Portal consumes typed contracts.

Every Portal displays exact version, owner, state, freshness, required action, and uncertainty. It supports loading, empty, partial, stale, denied, error, timeout, and Outcome Unknown states; accessibility; locale, currency, unit, date, and RTL/LTR correctness; evidence audit; safe retry; and correction history.

10. AI Participation and Tool Governance

Permitted AI tasks:

- extract and classify evidence
- detect anomalies and missing fields
- summarize timelines and contradictions
- recommend next actions with sources and uncertainty

AI shall not own Domain records, grant itself authority, suppress contradictions, silently edit approved versions, fabricate external outcomes, or execute high-impact actions outside typed Tools, policy, approval, idempotency, sandbox, and outcome observation.

Every Agent Run records source context, prompt/model/tool versions, structured output, confidence and limitations, Policy result, approval, Tool calls, provider responses, final outcome, and recovery actions.

11. Security, Privacy, and Trust Boundaries

- least privilege and separation of duties
- tenant, organization, facility, channel and jurisdiction isolation
- integrity protection for binding evidence
- verified external callbacks and anti-replay controls

Additional controls include secret isolation, callback signature verification, audit of privileged action, emergency-access review, sensitive-data minimization, purpose limitation, and threat models for impersonation, tampering, replay, confused deputy, fraud, prompt injection, and exfiltration.

12. Reliability, SLOs, and Operations

SLI	Reference objective
authoritative read availability	99.9% monthly unless a stricter tier applies
acknowledged Command durability	no acknowledged write may be silently lost
Event publication	99.9% within five minutes after committed fact
duplicate prevention	100% for same tenant, Command class, and idempotency key
binding Decision audit completeness	100%
state-state detection	bounded by business deadline

Dashboards and runbooks cover backlog, error budget, dependency failure, retry budget, DLQ, workflow stall, provider outage, reconciliation, capacity, backup/restore, release/rollback, incident command, and post-incident correction.

13. Testing and Continuous Conformance

- aggregate invariant and transition tests
- authorization, delegation, separation-of-duties and tenant-isolation tests
- idempotency and optimistic-concurrency tests
- database migration, key, constraint and rollback tests
- contract, outbox/inbox, duplicate, replay and DLQ tests
- workflow restart, timeout and compensation tests
- Portal E2E tests for success, partial, stale, denied, error and Outcome Unknown states
- accessibility, locale, currency, unit and RTL/LTR tests
- security adversarial, fraud and data-exfiltration tests
- AI evaluation, prompt-injection, policy-bypass and unauthorized-tool tests
- historical reconstruction, correction and audit-completeness tests
- performance, capacity, recovery and operational exercise tests

Release evidence links each invariant and control to the test, environment, input data, result, owner, and artifact proving it. Generated test counts never replace semantic coverage.

14. Repository Review Boundary

- This chapter is a repository-review specification. Exact executable implementation has not been inspected for every target behavior.
- Registered modules, catalog entries, README claims, frontend contracts, or plans are not proof of complete implementation.

Area	Classification
target aggregate, API, tables, state and workflow in this chapter	REFERENCE_ARCHITECTURE
registered module or catalog claim	DOCUMENTATION_ONLY_CLAIM until source inspection
uninspected integration	REQUIRES_REPOSITORY_REVIEW
behavior proven in another repository-grounded chapter	retain that chapter's evidence and classification
contradictory ownership or path claims	CONFLICT_REQUIRES_CANONICALIZATION

No statement upgrades implementation status merely because a file, directory, module name, frontend contract, database entry, plan, or report exists.

15. Worked Conformance Scenario

An authorized principal initiates a Command against an exact subject version. The service validates identity, tenant, mandate, Policy, Evidence, and idempotency. It records the state transition and outbox entry atomically. If an external dependency participates, timeout produces Outcome Unknown; reconciliation queries the source or waits for a verified callback instead of repeating the action blindly.

Portals show source, freshness, version, required action, and uncertainty. AI may extract, compare, summarize, detect anomalies, and recommend through typed Tools, but cannot own the subject or fabricate success. Later correction appends new facts, identifies affected projections and workflows, and preserves the historical Decision context.

16. Conformance Checklist

- ☐ stable identity and proposition ownership are explicit;
- ☐ authority and mandate are evaluated at action time;
- ☐ state, Recommendation, Decision, Intent, execution, and outcome remain distinct;
- ☐ Commands are typed, authorized, idempotent, and version guarded;
- ☐ Events describe completed facts;
- ☐ Evidence includes provenance, time, integrity, qualification, and correction;
- ☐ external outcomes retain their authority source;
- ☐ Portals show freshness and uncertainty;
- ☐ AI is bounded by typed Tools, Policy, approval, and outcome observation;
- ☐ security, tenant, facility, channel, and jurisdiction boundaries are enforced;
- ☐ Outcome Unknown and reconciliation exist where needed;
- ☐ corrections preserve history;
- ☐ tests prove invariants and recovery;
- ☐ implementation status is not upgraded without executable evidence.

17. Status Vocabulary

Status	Meaning
VERIFIED_IMPLEMENTED	Executable source and relevant behavior were inspected. Executable behavior exists with a material governance or completeness gap.
IMPLEMENTED_WITH_GAP	
PARTIAL_IMPLEMENTATION	Only part of the target capability is evidenced.
REFERENCE_ARCHITECTURE	Normative target behavior; no claim that it exists today.
PLANNED_NOT_IMPLEMENTED	Explicitly planned but not evidenced as executable.
DOCUMENTATION_ONLY_CLAIM	Documentation or client contract claims behavior without verified backend evidence.
CONFLICT_REQUIRES_CANONICALIZATION	Sources disagree and no final owner has been established.
REQUIRES_REPOSITORY_REVIEW	Necessary executable evidence has not yet been inspected.

WhatsApp Admin — Routes, Pages, Components, and BFF Contracts

Metadata	Value
Volume	4
Chapter ID	V04-P09-01
Subject	WhatsAppAdminRouteRegistry
Status	Generated First-Draft Architecture Skeleton - Domain-Specific Expansion Required
Content maturity	TEMPLATE_DERIVED_REFERENCE_SKELETON unless repository citations prove otherwise
Default implementation classification	REFERENCE_ARCHITECTURE / REQUIRES_REPOSITORY_REVIEW
Accountable owner	Portal Architecture / WhatsApp Admin
Evidence rule	No implementation claim without inspected executable evidence
Repository	chinair88-prog/allinb2c

1. Executive Orientation

This chapter defines how GTOS shall **inventory routes, layouts, pages, components, server/client boundaries, BFFs, APIs, realtime channels and ownership for channel operators and support managers, covering templates, consent, conversation routing, provider state, human handoff, audit.**

The specification separates reality, observations, knowledge, Decisions, Intent, execution, and outcomes. A component name, database row, UI label, AI answer, or workflow state does not acquire authority merely because it is visible or technically convenient.

Reality or external outcome

- ≠ Observation
- ≠ Claim
- ≠ derived Perspective
- ≠ Prediction
- ≠ Recommendation
- ≠ authorized Decision
- ≠ execution Intent

1.1 Accountable ownership

The accountable owner is **Portal Architecture / WhatsApp Admin**. Supporting applications, shared infrastructure, integration adapters, analytics, and AI coordinate or present the capability but shall not silently own its authoritative propositions.

1.2 Scope

- create and identify the subject
- validate evidence and policy
- make authorized Decisions
- execute typed Commands
- publish completed-fact Events
- query current and historical perspectives
- correct and reconcile outcomes

1.3 Non-goals

- treating a registered Gradle module, catalog record, README, frontend route, migration plan, or generated report as proof of end-to-end implementation;
- direct cross-Domain database writes;
- generic status values that combine lifecycle, approval, provider, document, payment, dispute, and correction state;
- silent replacement of history;
- AI-created authority or fabricated external outcomes.

2. Ubiquitous Language and Subject Model

Subject	Required interpretation
WhatsAppAdminRouteRegistry	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit
WhatsAppAdminRouteRegistryVersion	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit
WhatsAppAdminRouteRegistryDecision	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit
WhatsAppAdminRouteRegistryEvidenceSet	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit
WhatsAppAdminRouteRegistryException	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit

Reference aggregate:

```
WhatsAppAdminRouteRegistry {
  subjectId
  tenantId
  organizationContext
  sourceIdentityRefs[]
  sourceVersionRefs[]
  lifecycleState
  relationshipRefs[]
  decisionRefs[]
  intentRefs[]
  evidenceSetRef
  knowledgeCutoff
  policyRefs[]
  authorityRef
  jurisdictionRefs[]
  createdAt
  effectiveAt
  updatedAt
  version
  correctionOf?
  correlationId
}
```

2.1 Core invariants

- Stable identity precedes relationship, state, and cross-system correlation.
- Effective time and recorded time remain distinct where business truth changes over time.
- Recommendation, Decision, Intent, execution, and outcome are separate concepts.
- No Portal, report, search index, cache, workflow, or AI Agent becomes a shadow owner of Domain truth.
- Binding submitted, approved, issued, accepted, or signed versions are immutable.
- Corrections append governed facts and preserve the original record.
- External authority and provider outcomes retain their source and qualification.
- Tenant and represented-principal context come from trusted authentication and mandate evaluation.
- Retried writes are idempotent and concurrency guarded.
- Outcome Unknown is explicit and reconciled before risky duplicate execution.

2.2 Required standards

- stable identifiers
- typed contracts
- immutable binding versions

- transactional outbox
- idempotent Commands
- explicit Outcome Unknown
- correction lineage
- machine-verifiable conformance

3. Actors, Roles, and Authority

A conformant design distinguishes:

- the natural person acting;
- the service or AI identity invoking a Tool;
- the organization or principal represented;
- the role or relationship granting context;
- the mandate or delegation granting action authority;
- the Policy and jurisdiction limiting the action;
- the reviewer or approver responsible for a binding Decision.

Authority is evaluated at action time. Authentication alone does not grant business authority. Cached permissions and browser-supplied tenant headers are insufficient for high-impact actions.

4. Lifecycle and State Model

State	Semantics
PROPOSED	Distinct governed condition with entry, exit, timeout, correction and authority semantics
VALIDATION_PENDING	Distinct governed condition with entry, exit, timeout, correction and authority semantics
APPROVAL_PENDING	Distinct governed condition with entry, exit, timeout, correction and authority semantics
ACTIVE	Distinct governed condition with entry, exit, timeout, correction and authority semantics
SUSPENDED	Distinct governed condition with entry, exit, timeout, correction and authority semantics
CORRECTION_PENDING	Distinct governed condition with entry, exit, timeout, correction and authority semantics
RETIRED	Distinct governed condition with entry, exit, timeout, correction and authority semantics

```
stateDiagram-v2
    [*] --> PROPOSED
    PROPOSED --> VALIDATION_PENDING
    VALIDATION_PENDING --> APPROVAL_PENDING
    APPROVAL_PENDING --> ACTIVE
    ACTIVE --> SUSPENDED
    SUSPENDED --> CORRECTION_PENDING
    CORRECTION_PENDING --> RETIRED
```

The diagram is a primary reading path. Real implementations may add parallel review, amendment, appeal, timeout, suspension, partial completion, reconciliation, correction, and terminal failure without collapsing their meaning.

4.1 Transition rules

- transition through a typed, authorized Command;
- require exact expected version where concurrent change matters;
- record actor, represented principal, mandate, Policy, reason, and Evidence;
- use an idempotency key for retried writes;
- publish a completed-fact Event after durable state change;
- expose Outcome Unknown for unresolved external completion;
- preserve original and corrected states in historical reconstruction.

5. Decision, Evidence, and Knowledge Cutoff

Reference Decision:

```
Decision {
  decisionId
  decisionType
  subjectRef
  sourceVersionRefs[]
  knowledgeCutoff
  evidenceSetRef
  policyVersionRefs[]
  recommendationRefs[]
  principalId
  representedOrganizationId
  mandateRef
  rationale
  outcome
  decidedAt
  effectiveAt
  correctionOf?
}
```

Evidence records identify issuer or observer, subject, version, observed time, received time, effective interval, integrity, confidence, qualification, contradiction, correction, retention, residency, and access class. A recommendation may assist the Decision but cannot promote itself to the Decision.

6. Commands, Events, Queries, and Contracts

Reference Commands:

- CreateWhatsAppAdminRouteRegistry
- ValidateWhatsAppAdminRouteRegistry
- ApproveWhatsAppAdminRouteRegistry
- ActivateWhatsAppAdminRouteRegistry
- SuspendWhatsAppAdminRouteRegistry
- CorrectWhatsAppAdminRouteRegistry
- RetireWhatsAppAdminRouteRegistry

Reference Events:

- WhatsAppAdminRouteRegistryCreated
- WhatsAppAdminRouteRegistryValidated
- WhatsAppAdminRouteRegistryApproved
- WhatsAppAdminRouteRegistryActivated
- WhatsAppAdminRouteRegistrySuspended
- WhatsAppAdminRouteRegistryCorrected
- WhatsAppAdminRouteRegistryRetired

Reference queries:

- GetWhatsAppAdminRouteRegistry
- ListWhatsAppAdminRouteRegistryRecords
- GetWhatsAppAdminRouteRegistryTimeline
- GetWhatsAppAdminRouteRegistryEvidence
- GetWhatsAppAdminRouteRegistryDecisionPackage
- GetWhatsAppAdminRouteRegistryExceptions
- GetWhatsAppAdminRouteRegistryAuditTrail

Reference API surface:

```
POST /api/v1/whatsappadminrouterregistry/commands
GET  /api/v1/whatsappadminrouterregistry/{id}
GET  /api/v1/whatsappadminrouterregistry/{id}/timeline
GET  /api/v1/whatsappadminrouterregistry/{id}/evidence
GET  /api/v1/whatsappadminrouterregistry/{id}/decisions
POST /api/v1/whatsappadminrouterregistry/{id}/exceptions
POST /api/v1/whatsappadminrouterregistry/{id}/corrections
```

These endpoints are reference contracts, not claims that exact routes exist.

7. Workflow, Failure, and Compensation

```
flowchart TD
    A[Validate identity version and authority] --> B[Collect required evidence]
    B --> C{Policy and evidence gates pass?}
    C -- No --> D[Open exception or request correction]
    D --> B
    C -- Yes --> E[Record Decision or execution Intent]
    E --> F[Execute Domain command or external request]
    F --> G{Outcome known?}
    G -- Success --> H[Record fact and publish Event]
    G -- Failure --> I[Record failure and compensation options]
    G -- Unknown --> J[Enter Outcome Unknown]
    J --> K[Query source or wait for verified callback]
    K --> G
    H --> L[Update projections and downstream workflow]
```

Representative failure modes:

- stale or wrong source version
- duplicate submission or replay
- external timeout after possible success
- contradictory source observations
- lost Event after committed state
- approval or mandate revoked during execution
- downstream action before a mandatory gate
- partial completion across multiple subjects
- evidence later retracted or corrected
- tenant, facility, channel or jurisdiction mismatch

Recovery shall query the authoritative source before duplicate execution, preserve partial success, use compensating Intent rather than destructive rewrite, publish corrections, quarantine high-impact ambiguity, and record affected downstream subjects.

8. Data and Persistence Architecture

Reference table families:

Table family	Purpose
whatsappadminrouteregistry_aggregate	authoritative subject
whatsappadminrouteregistry_version	immutable submitted, approved, issued, or signed versions
whatsappadminrouteregistry_relationship	governed relationships
whatsappadminrouteregistry_decision	binding Decisions and rationale
whatsappadminrouteregistry_evidence_link	provenance and evidence relationships
whatsappadminrouteregistry_event_outbox	transactional Event publication
whatsappadminrouteregistry_idempotency	duplicate-write protection
whatsappadminrouteregistry_exception	exception, claim, dispute, or hold
whatsappadminrouteregistry_correction	correction and supersession lineage
whatsappadminrouteregistry_audit	privileged action evidence

The owning service controls schema and migration. Cross-Domain references use stable identifiers or contracts. Analytics, reports, caches, search, and vector indexes remain projections. Backup, restore, retention, legal hold, privacy, residency, and decommissioning requirements are explicit.

9. Portal and Experience Requirements

- WhatsApp Admin: primary experience for channel operators and support managers.
- Operator and support views: diagnose failed or ambiguous journeys without assuming Domain ownership.
- Domain services: own authoritative data and action eligibility; the Portal consumes typed contracts.

Every Portal displays exact version, owner, state, freshness, required action, and uncertainty. It supports loading, empty, partial, stale, denied, error, timeout, and Outcome Unknown states; accessibility; locale, currency, unit, date, and RTL/LTR correctness; evidence audit; safe retry; and correction history.

10. AI Participation and Tool Governance

Permitted AI tasks:

- extract and classify evidence
- detect anomalies and missing fields
- summarize timelines and contradictions
- recommend next actions with sources and uncertainty

AI shall not own Domain records, grant itself authority, suppress contradictions, silently edit approved versions, fabricate external outcomes, or execute high-impact actions outside typed Tools, policy, approval, idempotency, sandbox, and outcome observation.

Every Agent Run records source context, prompt/model/tool versions, structured output, confidence and limitations, Policy result, approval, Tool calls, provider responses, final outcome, and recovery actions.

11. Security, Privacy, and Trust Boundaries

- least privilege and separation of duties
- tenant, organization, facility, channel and jurisdiction isolation
- integrity protection for binding evidence
- verified external callbacks and anti-replay controls

Additional controls include secret isolation, callback signature verification, audit of privileged action, emergency-access review, sensitive-data minimization, purpose limitation, and threat models for impersonation, tampering, replay, confused deputy, fraud, prompt injection, and exfiltration.

12. Reliability, SLOs, and Operations

SLI	Reference objective
authoritative read availability	99.9% monthly unless a stricter tier applies
acknowledged Command durability	no acknowledged write may be silently lost
Event publication	99.9% within five minutes after committed fact
duplicate prevention	100% for same tenant, Command class, and idempotency key
binding Decision audit completeness	100%
state-state detection	bounded by business deadline

Dashboards and runbooks cover backlog, error budget, dependency failure, retry budget, DLQ, workflow stall, provider outage, reconciliation, capacity, backup/restore, release/rollback, incident command, and post-incident correction.

13. Testing and Continuous Conformance

- aggregate invariant and transition tests
- authorization, delegation, separation-of-duties and tenant-isolation tests
- idempotency and optimistic-concurrency tests
- database migration, key, constraint and rollback tests
- contract, outbox/inbox, duplicate, replay and DLQ tests
- workflow restart, timeout and compensation tests
- Portal E2E tests for success, partial, stale, denied, error and Outcome Unknown states
- accessibility, locale, currency, unit and RTL/LTR tests
- security adversarial, fraud and data-exfiltration tests
- AI evaluation, prompt-injection, policy-bypass and unauthorized-tool tests
- historical reconstruction, correction and audit-completeness tests
- performance, capacity, recovery and operational exercise tests

Release evidence links each invariant and control to the test, environment, input data, result, owner, and artifact proving it. Generated test counts never replace semantic coverage.

14. Repository Review Boundary

- This chapter is a repository-review specification. Exact executable implementation has not been inspected for every target behavior.
- Registered modules, catalog entries, README claims, frontend contracts, or plans are not proof of complete implementation.

Area	Classification
target aggregate, API, tables, state and workflow in this chapter	REFERENCE_ARCHITECTURE
registered module or catalog claim	DOCUMENTATION_ONLY_CLAIM until source inspection
uninspected integration	REQUIRES_REPOSITORY_REVIEW
behavior proven in another repository-grounded chapter	retain that chapter's evidence and classification
contradictory ownership or path claims	CONFLICT_REQUIRES_CANONICALIZATION

No statement upgrades implementation status merely because a file, directory, module name, frontend contract, database entry, plan, or report exists.

15. Worked Conformance Scenario

An authorized principal initiates a Command against an exact subject version. The service validates identity, tenant, mandate, Policy, Evidence, and idempotency. It records the state transition and outbox entry atomically. If an external dependency participates, timeout produces Outcome Unknown; reconciliation queries the source or waits for a verified callback instead of repeating the action blindly.

Portals show source, freshness, version, required action, and uncertainty. AI may extract, compare, summarize, detect anomalies, and recommend through typed Tools, but cannot own the subject or fabricate success. Later correction appends new facts, identifies affected projections and workflows, and preserves the historical Decision context.

16. Conformance Checklist

- ☐ stable identity and proposition ownership are explicit;
- ☐ authority and mandate are evaluated at action time;
- ☐ state, Recommendation, Decision, Intent, execution, and outcome remain distinct;
- ☐ Commands are typed, authorized, idempotent, and version guarded;
- ☐ Events describe completed facts;
- ☐ Evidence includes provenance, time, integrity, qualification, and correction;
- ☐ external outcomes retain their authority source;
- ☐ Portals show freshness and uncertainty;
- ☐ AI is bounded by typed Tools, Policy, approval, and outcome observation;
- ☐ security, tenant, facility, channel, and jurisdiction boundaries are enforced;
- ☐ Outcome Unknown and reconciliation exist where needed;
- ☐ corrections preserve history;
- ☐ tests prove invariants and recovery;
- ☐ implementation status is not upgraded without executable evidence.

17. Status Vocabulary

Status	Meaning
VERIFIED_IMPLEMENTED	Executable source and relevant behavior were inspected.
IMPLEMENTED_WITH_GAP	Executable behavior exists with a material governance or completeness gap.
PARTIAL_IMPLEMENTATION	Only part of the target capability is evidenced.
REFERENCE_ARCHITECTURE	Normative target behavior; no claim that it exists today.
PLANNED_NOT_IMPLEMENTED	Explicitly planned but not evidenced as executable.
DOCUMENTATION_ONLY_CLAIM	Documentation or client contract claims behavior without verified backend evidence.
CONFLICT_REQUIRES_CANONICALIZATION	Sources disagree and no final owner has been established.
REQUIRES_REPOSITORY_REVIEW	Necessary executable evidence has not yet been inspected.

WhatsApp Admin — Identity, Session, Authorization, and Trust Boundaries

Metadata	Value
Volume	4
Chapter ID	V04-P09-02
Subject	WhatsAppAdminAccessModel
Status	Generated First-Draft Architecture Skeleton - Domain-Specific Expansion Required
Content maturity	TEMPLATE_DERIVED_REFERENCE_SKELETON unless repository citations prove otherwise
Default implementation classification	REFERENCE_ARCHITECTURE / REQUIRES_REPOSITORY_REVIEW
Accountable owner	Portal Architecture / WhatsApp Admin
Evidence rule	No implementation claim without inspected executable evidence
Repository	chinair88-prog/allinb2c

1. Executive Orientation

This chapter defines how GTOS shall **govern login, session, role, relationship, tenant, facility, channel, delegation, impersonation and privileged action for channel operators and support managers, covering templates, consent, conversation routing, provider state, human handoff, audit.**

The specification separates reality, observations, knowledge, Decisions, Intent, execution, and outcomes. A component name, database row, UI label, AI answer, or workflow state does not acquire authority merely because it is visible or technically convenient.

Reality or external outcome
≠ Observation
≠ Claim
≠ derived Perspective
≠ Prediction
≠ Recommendation
≠ authorized Decision
≠ execution Intent

1.1 Accountable ownership

The accountable owner is **Portal Architecture / WhatsApp Admin**. Supporting applications, shared infrastructure, integration adapters, analytics, and AI coordinate or present the capability but shall not silently own its authoritative propositions.

1.2 Scope

- create and identify the subject
- validate evidence and policy
- make authorized Decisions
- execute typed Commands
- publish completed-fact Events
- query current and historical perspectives
- correct and reconcile outcomes

1.3 Non-goals

- treating a registered Gradle module, catalog record, README, frontend route, migration plan, or generated report as proof of end-to-end implementation;
- direct cross-Domain database writes;
- generic status values that combine lifecycle, approval, provider, document, payment, dispute, and correction state;
- silent replacement of history;
- AI-created authority or fabricated external outcomes.

2. Ubiquitous Language and Subject Model

Subject	Required interpretation
WhatsAppAdminAccessModel	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit
WhatsAppAdminAccessModelVersion	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit
WhatsAppAdminAccessModelDecision	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit
WhatsAppAdminAccessModelEvidenceSet	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit
WhatsAppAdminAccessModelException	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit

Reference aggregate:

```
WhatsAppAdminAccessModel {  
  subjectId  
  tenantId  
  organizationContext  
  sourceIdentityRefs[]  
  sourceVersionRefs[]  
  lifecycleState  
  relationshipRefs[]  
  decisionRefs[]  
  intentRefs[]  
  evidenceSetRef  
  knowledgeCutoff  
  policyRefs[]  
  authorityRef  
  jurisdictionRefs[]  
  createdAt  
  effectiveAt  
  updatedAt  
  version  
  correctionOf?  
  correlationId  
}
```

2.1 Core invariants

- Stable identity precedes relationship, state, and cross-system correlation.
- Effective time and recorded time remain distinct where business truth changes over time.
- Recommendation, Decision, Intent, execution, and outcome are separate concepts.
- No Portal, report, search index, cache, workflow, or AI Agent becomes a shadow owner of Domain truth.
- Binding submitted, approved, issued, accepted, or signed versions are immutable.
- Corrections append governed facts and preserve the original record.
- External authority and provider outcomes retain their source and qualification.
- Tenant and represented-principal context come from trusted authentication and mandate evaluation.
- Retried writes are idempotent and concurrency guarded.
- Outcome Unknown is explicit and reconciled before risky duplicate execution.

2.2 Required standards

- stable identifiers
- typed contracts
- immutable binding versions

- transactional outbox
- idempotent Commands
- explicit Outcome Unknown
- correction lineage
- machine-verifiable conformance

3. Actors, Roles, and Authority

A conformant design distinguishes:

- the natural person acting;
- the service or AI identity invoking a Tool;
- the organization or principal represented;
- the role or relationship granting context;
- the mandate or delegation granting action authority;
- the Policy and jurisdiction limiting the action;
- the reviewer or approver responsible for a binding Decision.

Authority is evaluated at action time. Authentication alone does not grant business authority. Cached permissions and browser-supplied tenant headers are insufficient for high-impact actions.

4. Lifecycle and State Model

State	Semantics
PROPOSED	Distinct governed condition with entry, exit, timeout, correction and authority semantics
VALIDATION_PENDING	Distinct governed condition with entry, exit, timeout, correction and authority semantics
APPROVAL_PENDING	Distinct governed condition with entry, exit, timeout, correction and authority semantics
ACTIVE	Distinct governed condition with entry, exit, timeout, correction and authority semantics
SUSPENDED	Distinct governed condition with entry, exit, timeout, correction and authority semantics
CORRECTION_PENDING	Distinct governed condition with entry, exit, timeout, correction and authority semantics
RETIRED	Distinct governed condition with entry, exit, timeout, correction and authority semantics

```
stateDiagram-v2
    [*] --> PROPOSED
    PROPOSED --> VALIDATION_PENDING
    VALIDATION_PENDING --> APPROVAL_PENDING
    APPROVAL_PENDING --> ACTIVE
    ACTIVE --> SUSPENDED
    SUSPENDED --> CORRECTION_PENDING
    CORRECTION_PENDING --> RETIRED
```

The diagram is a primary reading path. Real implementations may add parallel review, amendment, appeal, timeout, suspension, partial completion, reconciliation, correction, and terminal failure without collapsing their meaning.

4.1 Transition rules

- transition through a typed, authorized Command;
- require exact expected version where concurrent change matters;
- record actor, represented principal, mandate, Policy, reason, and Evidence;
- use an idempotency key for retried writes;
- publish a completed-fact Event after durable state change;
- expose Outcome Unknown for unresolved external completion;
- preserve original and corrected states in historical reconstruction.

5. Decision, Evidence, and Knowledge Cutoff

Reference Decision:

```
Decision {
  decisionId
  decisionType
  subjectRef
  sourceVersionRefs[]
  knowledgeCutoff
  evidenceSetRef
  policyVersionRefs[]
  recommendationRefs[]
  principalId
  representedOrganizationId
  mandateRef
  rationale
  outcome
  decidedAt
  effectiveAt
  correctionOf?
}
```

Evidence records identify issuer or observer, subject, version, observed time, received time, effective interval, integrity, confidence, qualification, contradiction, correction, retention, residency, and access class. A recommendation may assist the Decision but cannot promote itself to the Decision.

6. Commands, Events, Queries, and Contracts

Reference Commands:

- CreateWhatsAppAdminAccessModel
- ValidateWhatsAppAdminAccessModel
- ApproveWhatsAppAdminAccessModel
- ActivateWhatsAppAdminAccessModel
- SuspendWhatsAppAdminAccessModel
- CorrectWhatsAppAdminAccessModel
- RetireWhatsAppAdminAccessModel

Reference Events:

- WhatsAppAdminAccessModelCreated
- WhatsAppAdminAccessModelValidated
- WhatsAppAdminAccessModelApproved
- WhatsAppAdminAccessModelActivated
- WhatsAppAdminAccessModelSuspended
- WhatsAppAdminAccessModelCorrected
- WhatsAppAdminAccessModelRetired

Reference queries:

- GetWhatsAppAdminAccessModel
- ListWhatsAppAdminAccessModelRecords
- GetWhatsAppAdminAccessModelTimeline
- GetWhatsAppAdminAccessModelEvidence
- GetWhatsAppAdminAccessModelDecisionPackage
- GetWhatsAppAdminAccessModelExceptions
- GetWhatsAppAdminAccessModelAuditTrail

Reference API surface:

```
POST /api/v1/whatsappadminaccessmodel/commands
GET  /api/v1/whatsappadminaccessmodel/{id}
GET  /api/v1/whatsappadminaccessmodel/{id}/timeline
GET  /api/v1/whatsappadminaccessmodel/{id}/evidence
GET  /api/v1/whatsappadminaccessmodel/{id}/decisions
POST /api/v1/whatsappadminaccessmodel/{id}/exceptions
POST /api/v1/whatsappadminaccessmodel/{id}/corrections
```

These endpoints are reference contracts, not claims that exact routes exist.

7. Workflow, Failure, and Compensation

```
flowchart TD
    A[Validate identity version and authority] --> B[Collect required evidence]
    B --> C{Policy and evidence gates pass?}
    C -- No --> D[Open exception or request correction]
    D --> B
    C -- Yes --> E[Record Decision or execution Intent]
    E --> F[Execute Domain command or external request]
    F --> G{Outcome known?}
    G -- Success --> H[Record fact and publish Event]
    G -- Failure --> I[Record failure and compensation options]
    G -- Unknown --> J[Enter Outcome Unknown]
    J --> K[Query source or wait for verified callback]
    K --> G
    H --> L[Update projections and downstream workflow]
```

Representative failure modes:

- stale or wrong source version
- duplicate submission or replay
- external timeout after possible success
- contradictory source observations
- lost Event after committed state
- approval or mandate revoked during execution
- downstream action before a mandatory gate
- partial completion across multiple subjects
- evidence later retracted or corrected
- tenant, facility, channel or jurisdiction mismatch

Recovery shall query the authoritative source before duplicate execution, preserve partial success, use compensating Intent rather than destructive rewrite, publish corrections, quarantine high-impact ambiguity, and record affected downstream subjects.

8. Data and Persistence Architecture

Reference table families:

Table family	Purpose
whatsappadminaccessmodel_aggregate	authoritative subject
whatsappadminaccessmodel_version	immutable submitted, approved, issued, or signed versions
whatsappadminaccessmodel_relationship	governed relationships
whatsappadminaccessmodel_decision	binding Decisions and rationale
whatsappadminaccessmodel_evidence_link	provenance and evidence relationships
whatsappadminaccessmodel_event_outbox	transactional Event publication
whatsappadminaccessmodel_idempotency	duplicate-write protection
whatsappadminaccessmodel_exception	exception, claim, dispute, or hold
whatsappadminaccessmodel_correction	correction and supersession lineage
whatsappadminaccessmodel_audit	privileged action evidence

The owning service controls schema and migration. Cross-Domain references use stable identifiers or contracts. Analytics, reports, caches, search, and vector indexes remain projections. Backup, restore, retention, legal hold, privacy, residency, and decommissioning requirements are explicit.

9. Portal and Experience Requirements

- WhatsApp Admin: primary experience for channel operators and support managers.
- Operator and support views: diagnose failed or ambiguous journeys without assuming Domain ownership.
- Domain services: own authoritative data and action eligibility; the Portal consumes typed contracts.

Every Portal displays exact version, owner, state, freshness, required action, and uncertainty. It supports loading, empty, partial, stale, denied, error, timeout, and Outcome Unknown states; accessibility; locale, currency, unit, date, and RTL/LTR correctness; evidence audit; safe retry; and correction history.

10. AI Participation and Tool Governance

Permitted AI tasks:

- extract and classify evidence
- detect anomalies and missing fields
- summarize timelines and contradictions
- recommend next actions with sources and uncertainty

AI shall not own Domain records, grant itself authority, suppress contradictions, silently edit approved versions, fabricate external outcomes, or execute high-impact actions outside typed Tools, policy, approval, idempotency, sandbox, and outcome observation.

Every Agent Run records source context, prompt/model/tool versions, structured output, confidence and limitations, Policy result, approval, Tool calls, provider responses, final outcome, and recovery actions.

11. Security, Privacy, and Trust Boundaries

- least privilege and separation of duties
- tenant, organization, facility, channel and jurisdiction isolation
- integrity protection for binding evidence
- verified external callbacks and anti-replay controls

Additional controls include secret isolation, callback signature verification, audit of privileged action, emergency-access review, sensitive-data minimization, purpose limitation, and threat models for impersonation, tampering, replay, confused deputy, fraud, prompt injection, and exfiltration.

12. Reliability, SLOs, and Operations

SLI	Reference objective
authoritative read availability	99.9% monthly unless a stricter tier applies
acknowledged Command durability	no acknowledged write may be silently lost
Event publication	99.9% within five minutes after committed fact
duplicate prevention	100% for same tenant, Command class, and idempotency key
binding Decision audit completeness	100%
state-state detection	bounded by business deadline

Dashboards and runbooks cover backlog, error budget, dependency failure, retry budget, DLQ, workflow stall, provider outage, reconciliation, capacity, backup/restore, release/rollback, incident command, and post-incident correction.

13. Testing and Continuous Conformance

- aggregate invariant and transition tests
- authorization, delegation, separation-of-duties and tenant-isolation tests
- idempotency and optimistic-concurrency tests
- database migration, key, constraint and rollback tests
- contract, outbox/inbox, duplicate, replay and DLQ tests
- workflow restart, timeout and compensation tests
- Portal E2E tests for success, partial, stale, denied, error and Outcome Unknown states
- accessibility, locale, currency, unit and RTL/LTR tests
- security adversarial, fraud and data-exfiltration tests
- AI evaluation, prompt-injection, policy-bypass and unauthorized-tool tests
- historical reconstruction, correction and audit-completeness tests
- performance, capacity, recovery and operational exercise tests

Release evidence links each invariant and control to the test, environment, input data, result, owner, and artifact proving it. Generated test counts never replace semantic coverage.

14. Repository Review Boundary

- This chapter is a repository-review specification. Exact executable implementation has not been inspected for every target behavior.
- Registered modules, catalog entries, README claims, frontend contracts, or plans are not proof of complete implementation.

Area	Classification
target aggregate, API, tables, state and workflow in this chapter	REFERENCE_ARCHITECTURE
registered module or catalog claim	DOCUMENTATION_ONLY_CLAIM until source inspection
uninspected integration	REQUIRES_REPOSITORY_REVIEW
behavior proven in another repository-grounded chapter	retain that chapter's evidence and classification
contradictory ownership or path claims	CONFLICT_REQUIRES_CANONICALIZATION

No statement upgrades implementation status merely because a file, directory, module name, frontend contract, database entry, plan, or report exists.

15. Worked Conformance Scenario

An authorized principal initiates a Command against an exact subject version. The service validates identity, tenant, mandate, Policy, Evidence, and idempotency. It records the state transition and outbox entry atomically. If an external dependency participates, timeout produces Outcome Unknown; reconciliation queries the source or waits for a verified callback instead of repeating the action blindly.

Portals show source, freshness, version, required action, and uncertainty. AI may extract, compare, summarize, detect anomalies, and recommend through typed Tools, but cannot own the subject or fabricate success. Later correction appends new facts, identifies affected projections and workflows, and preserves the historical Decision context.

16. Conformance Checklist

- ☐ stable identity and proposition ownership are explicit;
- ☐ authority and mandate are evaluated at action time;
- ☐ state, Recommendation, Decision, Intent, execution, and outcome remain distinct;
- ☐ Commands are typed, authorized, idempotent, and version guarded;
- ☐ Events describe completed facts;
- ☐ Evidence includes provenance, time, integrity, qualification, and correction;
- ☐ external outcomes retain their authority source;
- ☐ Portals show freshness and uncertainty;
- ☐ AI is bounded by typed Tools, Policy, approval, and outcome observation;
- ☐ security, tenant, facility, channel, and jurisdiction boundaries are enforced;
- ☐ Outcome Unknown and reconciliation exist where needed;
- ☐ corrections preserve history;
- ☐ tests prove invariants and recovery;
- ☐ implementation status is not upgraded without executable evidence.

17. Status Vocabulary

Status	Meaning
VERIFIED_IMPLEMENTED	Executable source and relevant behavior were inspected.
IMPLEMENTED_WITH_GAP	Executable behavior exists with a material governance or completeness gap.
PARTIAL_IMPLEMENTATION	Only part of the target capability is evidenced.
REFERENCE_ARCHITECTURE	Normative target behavior; no claim that it exists today.
PLANNED_NOT_IMPLEMENTED	Explicitly planned but not evidenced as executable.
DOCUMENTATION_ONLY_CLAIM	Documentation or client contract claims behavior without verified backend evidence.
CONFLICT_REQUIRES_CANONICALIZATION	Sources disagree and no final owner has been established.
REQUIRES_REPOSITORY_REVIEW	Necessary executable evidence has not yet been inspected.

WhatsApp Admin — UX States, Accessibility, Localization, Analytics, and E2E

Metadata	Value
Volume	4
Chapter ID	V04-P09-03
Subject	WhatsAppAdminExperienceStandard
Status	Generated First-Draft Architecture Skeleton - Domain-Specific Expansion Required
Content maturity	TEMPLATE_DERIVED_REFERENCE_SKELETON unless repository citations prove otherwise
Default implementation classification	REFERENCE_ARCHITECTURE / REQUIRES_REPOSITORY_REVIEW
Accountable owner	Portal Architecture / WhatsApp Admin
Evidence rule	No implementation claim without inspected executable evidence
Repository	chinair88-prog/allinb2c

1. Executive Orientation

This chapter defines how GTOS shall **specify loading, empty, partial, stale, error, denied, offline, accessibility, RTL/LTR, analytics, audit and test journeys for channel operators and support managers, covering templates, consent, conversation routing, provider state, human handoff, audit.**

The specification separates reality, observations, knowledge, Decisions, Intent, execution, and outcomes. A component name, database row, UI label, AI answer, or workflow state does not acquire authority merely because it is visible or technically convenient.

Reality or external outcome

- ≠ Observation
- ≠ Claim
- ≠ derived Perspective
- ≠ Prediction
- ≠ Recommendation
- ≠ authorized Decision
- ≠ execution Intent

1.1 Accountable ownership

The accountable owner is **Portal Architecture / WhatsApp Admin**. Supporting applications, shared infrastructure, integration adapters, analytics, and AI coordinate or present the capability but shall not silently own its authoritative propositions.

1.2 Scope

- create and identify the subject
- validate evidence and policy
- make authorized Decisions
- execute typed Commands
- publish completed-fact Events
- query current and historical perspectives
- correct and reconcile outcomes

1.3 Non-goals

- treating a registered Gradle module, catalog record, README, frontend route, migration plan, or generated report as proof of end-to-end implementation;
- direct cross-Domain database writes;
- generic status values that combine lifecycle, approval, provider, document, payment, dispute, and correction state;
- silent replacement of history;
- AI-created authority or fabricated external outcomes.

2. Ubiquitous Language and Subject Model

Subject	Required interpretation
WhatsAppAdminExperienceStandard	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit
WhatsAppAdminExperienceStandardVersion	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit
WhatsAppAdminExperienceStandardDecision	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit
WhatsAppAdminExperienceStandardEvidenceSet	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit
WhatsAppAdminExperienceStandardException	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit

Reference aggregate:

```
WhatsAppAdminExperienceStandard {  
  subjectId  
  tenantId  
  organizationContext  
  sourceIdentityRefs[]  
  sourceVersionRefs[]  
  lifecycleState  
  relationshipRefs[]  
  decisionRefs[]  
  intentRefs[]  
  evidenceSetRef  
  knowledgeCutoff  
  policyRefs[]  
  authorityRef  
  jurisdictionRefs[]  
  createdAt  
  effectiveAt  
  updatedAt  
  version  
  correctionOf?  
  correlationId  
}
```

2.1 Core invariants

- Stable identity precedes relationship, state, and cross-system correlation.
- Effective time and recorded time remain distinct where business truth changes over time.
- Recommendation, Decision, Intent, execution, and outcome are separate concepts.
- No Portal, report, search index, cache, workflow, or AI Agent becomes a shadow owner of Domain truth.
- Binding submitted, approved, issued, accepted, or signed versions are immutable.
- Corrections append governed facts and preserve the original record.
- External authority and provider outcomes retain their source and qualification.
- Tenant and represented-principal context come from trusted authentication and mandate evaluation.
- Retried writes are idempotent and concurrency guarded.
- Outcome Unknown is explicit and reconciled before risky duplicate execution.

2.2 Required standards

- stable identifiers
- typed contracts
- immutable binding versions

- transactional outbox
- idempotent Commands
- explicit Outcome Unknown
- correction lineage
- machine-verifiable conformance

3. Actors, Roles, and Authority

A conformant design distinguishes:

- the natural person acting;
- the service or AI identity invoking a Tool;
- the organization or principal represented;
- the role or relationship granting context;
- the mandate or delegation granting action authority;
- the Policy and jurisdiction limiting the action;
- the reviewer or approver responsible for a binding Decision.

Authority is evaluated at action time. Authentication alone does not grant business authority. Cached permissions and browser-supplied tenant headers are insufficient for high-impact actions.

4. Lifecycle and State Model

State	Semantics
PROPOSED	Distinct governed condition with entry, exit, timeout, correction and authority semantics
VALIDATION_PENDING	Distinct governed condition with entry, exit, timeout, correction and authority semantics
APPROVAL_PENDING	Distinct governed condition with entry, exit, timeout, correction and authority semantics
ACTIVE	Distinct governed condition with entry, exit, timeout, correction and authority semantics
SUSPENDED	Distinct governed condition with entry, exit, timeout, correction and authority semantics
CORRECTION_PENDING	Distinct governed condition with entry, exit, timeout, correction and authority semantics
RETIRED	Distinct governed condition with entry, exit, timeout, correction and authority semantics

```
stateDiagram-v2
    [*] --> PROPOSED
    PROPOSED --> VALIDATION_PENDING
    VALIDATION_PENDING --> APPROVAL_PENDING
    APPROVAL_PENDING --> ACTIVE
    ACTIVE --> SUSPENDED
    SUSPENDED --> CORRECTION_PENDING
    CORRECTION_PENDING --> RETIRED
```

The diagram is a primary reading path. Real implementations may add parallel review, amendment, appeal, timeout, suspension, partial completion, reconciliation, correction, and terminal failure without collapsing their meaning.

4.1 Transition rules

- transition through a typed, authorized Command;
- require exact expected version where concurrent change matters;
- record actor, represented principal, mandate, Policy, reason, and Evidence;
- use an idempotency key for retried writes;
- publish a completed-fact Event after durable state change;
- expose Outcome Unknown for unresolved external completion;
- preserve original and corrected states in historical reconstruction.

5. Decision, Evidence, and Knowledge Cutoff

Reference Decision:

```
Decision {
  decisionId
  decisionType
  subjectRef
  sourceVersionRefs[]
  knowledgeCutoff
  evidenceSetRef
  policyVersionRefs[]
  recommendationRefs[]
  principalId
  representedOrganizationId
  mandateRef
  rationale
  outcome
  decidedAt
  effectiveAt
  correctionOf?
}
```

Evidence records identify issuer or observer, subject, version, observed time, received time, effective interval, integrity, confidence, qualification, contradiction, correction, retention, residency, and access class. A recommendation may assist the Decision but cannot promote itself to the Decision.

6. Commands, Events, Queries, and Contracts

Reference Commands:

- CreateWhatsAppAdminExperienceStandard
- ValidateWhatsAppAdminExperienceStandard
- ApproveWhatsAppAdminExperienceStandard
- ActivateWhatsAppAdminExperienceStandard
- SuspendWhatsAppAdminExperienceStandard
- CorrectWhatsAppAdminExperienceStandard
- RetireWhatsAppAdminExperienceStandard

Reference Events:

- WhatsAppAdminExperienceStandardCreated
- WhatsAppAdminExperienceStandardValidated
- WhatsAppAdminExperienceStandardApproved
- WhatsAppAdminExperienceStandardActivated
- WhatsAppAdminExperienceStandardSuspended
- WhatsAppAdminExperienceStandardCorrected
- WhatsAppAdminExperienceStandardRetired

Reference queries:

- GetWhatsAppAdminExperienceStandard
- ListWhatsAppAdminExperienceStandardRecords
- GetWhatsAppAdminExperienceStandardTimeline
- GetWhatsAppAdminExperienceStandardEvidence
- GetWhatsAppAdminExperienceStandardDecisionPackage
- GetWhatsAppAdminExperienceStandardExceptions
- GetWhatsAppAdminExperienceStandardAuditTrail

Reference API surface:

```
POST /api/v1/whatsappadminexperiencestandard/commands
GET  /api/v1/whatsappadminexperiencestandard/{id}
GET  /api/v1/whatsappadminexperiencestandard/{id}/timeline
GET  /api/v1/whatsappadminexperiencestandard/{id}/evidence
GET  /api/v1/whatsappadminexperiencestandard/{id}/decisions
POST /api/v1/whatsappadminexperiencestandard/{id}/exceptions
POST /api/v1/whatsappadminexperiencestandard/{id}/corrections
```

These endpoints are reference contracts, not claims that exact routes exist.

7. Workflow, Failure, and Compensation

```
flowchart TD
    A[Validate identity version and authority] --> B[Collect required evidence]
    B --> C{Policy and evidence gates pass?}
    C -- No --> D[Open exception or request correction]
    D --> B
    C -- Yes --> E[Record Decision or execution Intent]
    E --> F[Execute Domain command or external request]
    F --> G{Outcome known?}
    G -- Success --> H[Record fact and publish Event]
    G -- Failure --> I[Record failure and compensation options]
    G -- Unknown --> J[Enter Outcome Unknown]
    J --> K[Query source or wait for verified callback]
    K --> G
    H --> L[Update projections and downstream workflow]
```

Representative failure modes:

- stale or wrong source version
- duplicate submission or replay
- external timeout after possible success
- contradictory source observations
- lost Event after committed state
- approval or mandate revoked during execution
- downstream action before a mandatory gate
- partial completion across multiple subjects
- evidence later retracted or corrected
- tenant, facility, channel or jurisdiction mismatch

Recovery shall query the authoritative source before duplicate execution, preserve partial success, use compensating Intent rather than destructive rewrite, publish corrections, quarantine high-impact ambiguity, and record affected downstream subjects.

8. Data and Persistence Architecture

Reference table families:

Table family	Purpose
whatsappadminexperiencestandard_aggregate	authoritative subject
whatsappadminexperiencestandard_version	immutable submitted, approved, issued, or signed versions
whatsappadminexperiencestandard_relationship	governed relationships
whatsappadminexperiencestandard_decision	binding Decisions and rationale
whatsappadminexperiencestandard_evidence_link	provenance and evidence relationships
whatsappadminexperiencestandard_event_outbox	transactional Event publication
whatsappadminexperiencestandard_idempotency	duplicate-write protection
whatsappadminexperiencestandard_exception	exception, claim, dispute, or hold
whatsappadminexperiencestandard_correction	correction and supersession lineage
whatsappadminexperiencestandard_audit	privileged action evidence

The owning service controls schema and migration. Cross-Domain references use stable identifiers or contracts. Analytics, reports, caches, search, and vector indexes remain projections. Backup, restore, retention, legal hold, privacy, residency, and decommissioning requirements are explicit.

9. Portal and Experience Requirements

- WhatsApp Admin: primary experience for channel operators and support managers.
- Operator and support views: diagnose failed or ambiguous journeys without assuming Domain ownership.
- Domain services: own authoritative data and action eligibility; the Portal consumes typed contracts.

Every Portal displays exact version, owner, state, freshness, required action, and uncertainty. It supports loading, empty, partial, stale, denied, error, timeout, and Outcome Unknown states; accessibility; locale, currency, unit, date, and RTL/LTR correctness; evidence audit; safe retry; and correction history.

10. AI Participation and Tool Governance

Permitted AI tasks:

- extract and classify evidence
- detect anomalies and missing fields
- summarize timelines and contradictions
- recommend next actions with sources and uncertainty

AI shall not own Domain records, grant itself authority, suppress contradictions, silently edit approved versions, fabricate external outcomes, or execute high-impact actions outside typed Tools, policy, approval, idempotency, sandbox, and outcome observation.

Every Agent Run records source context, prompt/model/tool versions, structured output, confidence and limitations, Policy result, approval, Tool calls, provider responses, final outcome, and recovery actions.

11. Security, Privacy, and Trust Boundaries

- least privilege and separation of duties
- tenant, organization, facility, channel and jurisdiction isolation
- integrity protection for binding evidence
- verified external callbacks and anti-replay controls

Additional controls include secret isolation, callback signature verification, audit of privileged action, emergency-access review, sensitive-data minimization, purpose limitation, and threat models for impersonation, tampering, replay, confused deputy, fraud, prompt injection, and exfiltration.

12. Reliability, SLOs, and Operations

SLI	Reference objective
authoritative read availability	99.9% monthly unless a stricter tier applies
acknowledged Command durability	no acknowledged write may be silently lost
Event publication	99.9% within five minutes after committed fact
duplicate prevention	100% for same tenant, Command class, and idempotency key
binding Decision audit completeness	100%
state-state detection	bounded by business deadline

Dashboards and runbooks cover backlog, error budget, dependency failure, retry budget, DLQ, workflow stall, provider outage, reconciliation, capacity, backup/restore, release/rollback, incident command, and post-incident correction.

13. Testing and Continuous Conformance

- aggregate invariant and transition tests
- authorization, delegation, separation-of-duties and tenant-isolation tests
- idempotency and optimistic-concurrency tests
- database migration, key, constraint and rollback tests
- contract, outbox/inbox, duplicate, replay and DLQ tests
- workflow restart, timeout and compensation tests
- Portal E2E tests for success, partial, stale, denied, error and Outcome Unknown states
- accessibility, locale, currency, unit and RTL/LTR tests
- security adversarial, fraud and data-exfiltration tests
- AI evaluation, prompt-injection, policy-bypass and unauthorized-tool tests
- historical reconstruction, correction and audit-completeness tests
- performance, capacity, recovery and operational exercise tests

Release evidence links each invariant and control to the test, environment, input data, result, owner, and artifact proving it. Generated test counts never replace semantic coverage.

14. Repository Review Boundary

- This chapter is a repository-review specification. Exact executable implementation has not been inspected for every target behavior.
- Registered modules, catalog entries, README claims, frontend contracts, or plans are not proof of complete implementation.

Area	Classification
target aggregate, API, tables, state and workflow in this chapter	REFERENCE_ARCHITECTURE
registered module or catalog claim	DOCUMENTATION_ONLY_CLAIM until source inspection
uninspected integration	REQUIRES_REPOSITORY_REVIEW
behavior proven in another repository-grounded chapter	retain that chapter's evidence and classification
contradictory ownership or path claims	CONFLICT_REQUIRES_CANONICALIZATION

No statement upgrades implementation status merely because a file, directory, module name, frontend contract, database entry, plan, or report exists.

15. Worked Conformance Scenario

An authorized principal initiates a Command against an exact subject version. The service validates identity, tenant, mandate, Policy, Evidence, and idempotency. It records the state transition and outbox entry atomically. If an external dependency participates, timeout produces Outcome Unknown; reconciliation queries the source or waits for a verified callback instead of repeating the action blindly.

Portals show source, freshness, version, required action, and uncertainty. AI may extract, compare, summarize, detect anomalies, and recommend through typed Tools, but cannot own the subject or fabricate success. Later correction appends new facts, identifies affected projections and workflows, and preserves the historical Decision context.

16. Conformance Checklist

- ☐ stable identity and proposition ownership are explicit;
- ☐ authority and mandate are evaluated at action time;
- ☐ state, Recommendation, Decision, Intent, execution, and outcome remain distinct;
- ☐ Commands are typed, authorized, idempotent, and version guarded;
- ☐ Events describe completed facts;
- ☐ Evidence includes provenance, time, integrity, qualification, and correction;
- ☐ external outcomes retain their authority source;
- ☐ Portals show freshness and uncertainty;
- ☐ AI is bounded by typed Tools, Policy, approval, and outcome observation;
- ☐ security, tenant, facility, channel, and jurisdiction boundaries are enforced;
- ☐ Outcome Unknown and reconciliation exist where needed;
- ☐ corrections preserve history;
- ☐ tests prove invariants and recovery;
- ☐ implementation status is not upgraded without executable evidence.

17. Status Vocabulary

Status	Meaning
VERIFIED_IMPLEMENTED	Executable source and relevant behavior were inspected. Executable behavior exists with a material governance or completeness gap.
IMPLEMENTED_WITH_GAP	
PARTIAL_IMPLEMENTATION	Only part of the target capability is evidenced.
REFERENCE_ARCHITECTURE	Normative target behavior; no claim that it exists today.
PLANNED_NOT_IMPLEMENTED	Explicitly planned but not evidenced as executable.
DOCUMENTATION_ONLY_CLAIM	Documentation or client contract claims behavior without verified backend evidence.
CONFLICT_REQUIRES_CANONICALIZATION	Sources disagree and no final owner has been established.
REQUIRES_REPOSITORY_REVIEW	Necessary executable evidence has not yet been inspected.

ESG Dashboard — Portal Orientation and Information Architecture

Metadata	Value
Volume	4
Chapter ID	V04-P10-00
Subject	ESGDashboardPortal
Status	Generated First-Draft Architecture Skeleton - Domain-Specific Expansion Required
Content maturity	TEMPLATE_DERIVED_REFERENCE_SKELETON unless repository citations prove otherwise
Default implementation classification	REFERENCE_ARCHITECTURE / REQUIRES_REPOSITORY_REVIEW
Accountable owner	Portal Architecture / ESG Dashboard
Evidence rule	No implementation claim without inspected executable evidence
Repository	chinair88-prog/allinb2c

1. Executive Orientation

This chapter defines how GTOS shall **define personas, navigation, route ownership, domain dependencies and experience boundaries for sustainability, compliance and executive users, covering ESG metrics, evidence, lineage, methodology, uncertainty, reporting.**

The specification separates reality, observations, knowledge, Decisions, Intent, execution, and outcomes. A component name, database row, UI label, AI answer, or workflow state does not acquire authority merely because it is visible or technically convenient.

- Reality or external outcome
- ≠ Observation
 - ≠ Claim
 - ≠ derived Perspective
 - ≠ Prediction
 - ≠ Recommendation
 - ≠ authorized Decision
 - ≠ execution Intent

1.1 Accountable ownership

The accountable owner is **Portal Architecture / ESG Dashboard**. Supporting applications, shared infrastructure, integration adapters, analytics, and AI coordinate or present the capability but shall not silently own its authoritative propositions.

1.2 Scope

- create and identify the subject
- validate evidence and policy
- make authorized Decisions
- execute typed Commands
- publish completed-fact Events
- query current and historical perspectives
- correct and reconcile outcomes

1.3 Non-goals

- treating a registered Gradle module, catalog record, README, frontend route, migration plan, or generated report as proof of end-to-end implementation;
- direct cross-Domain database writes;
- generic status values that combine lifecycle, approval, provider, document, payment, dispute, and correction state;
- silent replacement of history;
- AI-created authority or fabricated external outcomes.

2. Ubiquitous Language and Subject Model

Subject	Required interpretation
ESGDashboardPortal	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit
ESGDashboardPortalVersion	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit
ESGDashboardPortalDecision	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit
ESGDashboardPortalEvidenceSet	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit
ESGDashboardPortalException	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit

Reference aggregate:

```
ESGDashboardPortal {
  subjectId
  tenantId
  organizationContext
  sourceIdentityRefs[]
  sourceVersionRefs[]
  lifecycleState
  relationshipRefs[]
  decisionRefs[]
  intentRefs[]
  evidenceSetRef
  knowledgeCutoff
  policyRefs[]
  authorityRef
  jurisdictionRefs[]
  createdAt
  effectiveAt
  updatedAt
  version
  correctionOf?
  correlationId
}
```

2.1 Core invariants

- Stable identity precedes relationship, state, and cross-system correlation.
- Effective time and recorded time remain distinct where business truth changes over time.
- Recommendation, Decision, Intent, execution, and outcome are separate concepts.
- No Portal, report, search index, cache, workflow, or AI Agent becomes a shadow owner of Domain truth.
- Binding submitted, approved, issued, accepted, or signed versions are immutable.
- Corrections append governed facts and preserve the original record.
- External authority and provider outcomes retain their source and qualification.
- Tenant and represented-principal context come from trusted authentication and mandate evaluation.
- Retried writes are idempotent and concurrency guarded.
- Outcome Unknown is explicit and reconciled before risky duplicate execution.

2.2 Required standards

- stable identifiers
- typed contracts
- immutable binding versions

- transactional outbox
- idempotent Commands
- explicit Outcome Unknown
- correction lineage
- machine-verifiable conformance

3. Actors, Roles, and Authority

- A conformant design distinguishes:
- the natural person acting;
 - the service or AI identity invoking a Tool;
 - the organization or principal represented;
 - the role or relationship granting context;
 - the mandate or delegation granting action authority;
 - the Policy and jurisdiction limiting the action;
 - the reviewer or approver responsible for a binding Decision.

Authority is evaluated at action time. Authentication alone does not grant business authority. Cached permissions and browser-supplied tenant headers are insufficient for high-impact actions.

4. Lifecycle and State Model

State	Semantics
PROPOSED	Distinct governed condition with entry, exit, timeout, correction and authority semantics
VALIDATION_PENDING	Distinct governed condition with entry, exit, timeout, correction and authority semantics
APPROVAL_PENDING	Distinct governed condition with entry, exit, timeout, correction and authority semantics
ACTIVE	Distinct governed condition with entry, exit, timeout, correction and authority semantics
SUSPENDED	Distinct governed condition with entry, exit, timeout, correction and authority semantics
CORRECTION_PENDING	Distinct governed condition with entry, exit, timeout, correction and authority semantics
RETIRED	Distinct governed condition with entry, exit, timeout, correction and authority semantics

```
stateDiagram-v2
    [*] --> PROPOSED
    PROPOSED --> VALIDATION_PENDING
    VALIDATION_PENDING --> APPROVAL_PENDING
    APPROVAL_PENDING --> ACTIVE
    ACTIVE --> SUSPENDED
    SUSPENDED --> CORRECTION_PENDING
    CORRECTION_PENDING --> RETIRED
```

The diagram is a primary reading path. Real implementations may add parallel review, amendment, appeal, timeout, suspension, partial completion, reconciliation, correction, and terminal failure without collapsing their meaning.

4.1 Transition rules

- transition through a typed, authorized Command;
- require exact expected version where concurrent change matters;
- record actor, represented principal, mandate, Policy, reason, and Evidence;
- use an idempotency key for retried writes;
- publish a completed-fact Event after durable state change;
- expose Outcome Unknown for unresolved external completion;
- preserve original and corrected states in historical reconstruction.

5. Decision, Evidence, and Knowledge Cutoff

Reference Decision:

```
Decision {
  decisionId
  decisionType
  subjectRef
  sourceVersionRefs[]
  knowledgeCutoff
  evidenceSetRef
  policyVersionRefs[]
  recommendationRefs[]
  principalId
  representedOrganizationId
  mandateRef
  rationale
  outcome
  decidedAt
  effectiveAt
  correctionOf?
}
```

Evidence records identify issuer or observer, subject, version, observed time, received time, effective interval, integrity, confidence, qualification, contradiction, correction, retention, residency, and access class. A recommendation may assist the Decision but cannot promote itself to the Decision.

6. Commands, Events, Queries, and Contracts

Reference Commands:

- CreateESGDashboardPortal
- ValidateESGDashboardPortal
- ApproveESGDashboardPortal
- ActivateESGDashboardPortal
- SuspendESGDashboardPortal
- CorrectESGDashboardPortal
- RetireESGDashboardPortal

Reference Events:

- ESGDashboardPortalCreated
- ESGDashboardPortalValidated
- ESGDashboardPortalApproved
- ESGDashboardPortalActivated
- ESGDashboardPortalSuspended
- ESGDashboardPortalCorrected
- ESGDashboardPortalRetired

Reference queries:

- GetESGDashboardPortal
- ListESGDashboardPortalRecords
- GetESGDashboardPortalTimeline
- GetESGDashboardPortalEvidence
- GetESGDashboardPortalDecisionPackage
- GetESGDashboardPortalExceptions
- GetESGDashboardPortalAuditTrail

Reference API surface:

```
POST /api/v1/esgdashboardportal/commands
GET  /api/v1/esgdashboardportal/{id}
GET  /api/v1/esgdashboardportal/{id}/timeline
GET  /api/v1/esgdashboardportal/{id}/evidence
GET  /api/v1/esgdashboardportal/{id}/decisions
POST /api/v1/esgdashboardportal/{id}/exceptions
POST /api/v1/esgdashboardportal/{id}/corrections
```

These endpoints are reference contracts, not claims that exact routes exist.

7. Workflow, Failure, and Compensation

```
flowchart TD
    A[Validate identity version and authority] --> B[Collect required evidence]
    B --> C{Policy and evidence gates pass?}
    C -- No --> D[Open exception or request correction]
    D --> B
    C -- Yes --> E[Record Decision or execution Intent]
    E --> F[Execute Domain command or external request]
    F --> G{Outcome known?}
    G -- Success --> H[Record fact and publish Event]
    G -- Failure --> I[Record failure and compensation options]
    G -- Unknown --> J[Enter Outcome Unknown]
    J --> K[Query source or wait for verified callback]
    K --> G
    H --> L[Update projections and downstream workflow]
```

Representative failure modes:

- stale or wrong source version
- duplicate submission or replay
- external timeout after possible success
- contradictory source observations
- lost Event after committed state
- approval or mandate revoked during execution
- downstream action before a mandatory gate
- partial completion across multiple subjects
- evidence later retracted or corrected
- tenant, facility, channel or jurisdiction mismatch

Recovery shall query the authoritative source before duplicate execution, preserve partial success, use compensating Intent rather than destructive rewrite, publish corrections, quarantine high-impact ambiguity, and record affected downstream subjects.

8. Data and Persistence Architecture

Reference table families:

Table family	Purpose
esgdashboardportal_aggregate	authoritative subject
esgdashboardportal_version	immutable submitted, approved, issued, or signed versions
esgdashboardportal_relationship	governed relationships
esgdashboardportal_decision	binding Decisions and rationale
esgdashboardportal_evidence_link	provenance and evidence relationships
esgdashboardportal_event_outbox	transactional Event publication
esgdashboardportal_idempotency	duplicate-write protection
esgdashboardportal_exception	exception, claim, dispute, or hold
esgdashboardportal_correction	correction and supersession lineage
esgdashboardportal_audit	privileged action evidence

The owning service controls schema and migration. Cross-Domain references use stable identifiers or contracts. Analytics, reports, caches, search, and vector indexes remain projections. Backup, restore, retention, legal hold, privacy, residency, and decommissioning requirements are explicit.

9. Portal and Experience Requirements

- ESG Dashboard: primary experience for sustainability, compliance and executive users.
- Operator and support views: diagnose failed or ambiguous journeys without assuming Domain ownership.
- Domain services: own authoritative data and action eligibility; the Portal consumes typed contracts.

Every Portal displays exact version, owner, state, freshness, required action, and uncertainty. It supports loading, empty, partial, stale, denied, error, timeout, and Outcome Unknown states; accessibility; locale, currency, unit, date, and RTL/LTR correctness; evidence audit; safe retry; and correction history.

10. AI Participation and Tool Governance

Permitted AI tasks:

- extract and classify evidence
- detect anomalies and missing fields
- summarize timelines and contradictions
- recommend next actions with sources and uncertainty

AI shall not own Domain records, grant itself authority, suppress contradictions, silently edit approved versions, fabricate external outcomes, or execute high-impact actions outside typed Tools, policy, approval, idempotency, sandbox, and outcome observation.

Every Agent Run records source context, prompt/model/tool versions, structured output, confidence and limitations, Policy result, approval, Tool calls, provider responses, final outcome, and recovery actions.

11. Security, Privacy, and Trust Boundaries

- least privilege and separation of duties
- tenant, organization, facility, channel and jurisdiction isolation
- integrity protection for binding evidence
- verified external callbacks and anti-replay controls

Additional controls include secret isolation, callback signature verification, audit of privileged action, emergency-access review, sensitive-data minimization, purpose limitation, and threat models for impersonation, tampering, replay, confused deputy, fraud, prompt injection, and exfiltration.

12. Reliability, SLOs, and Operations

SLI	Reference objective
authoritative read availability	99.9% monthly unless a stricter tier applies
acknowledged Command durability	no acknowledged write may be silently lost
Event publication	99.9% within five minutes after committed fact
duplicate prevention	100% for same tenant, Command class, and idempotency key
binding Decision audit completeness	100%
state-state detection	bounded by business deadline

Dashboards and runbooks cover backlog, error budget, dependency failure, retry budget, DLQ, workflow stall, provider outage, reconciliation, capacity, backup/restore, release/rollback, incident command, and post-incident correction.

13. Testing and Continuous Conformance

- aggregate invariant and transition tests
- authorization, delegation, separation-of-duties and tenant-isolation tests
- idempotency and optimistic-concurrency tests
- database migration, key, constraint and rollback tests
- contract, outbox/inbox, duplicate, replay and DLQ tests
- workflow restart, timeout and compensation tests
- Portal E2E tests for success, partial, stale, denied, error and Outcome Unknown states
- accessibility, locale, currency, unit and RTL/LTR tests
- security adversarial, fraud and data-exfiltration tests
- AI evaluation, prompt-injection, policy-bypass and unauthorized-tool tests
- historical reconstruction, correction and audit-completeness tests
- performance, capacity, recovery and operational exercise tests

Release evidence links each invariant and control to the test, environment, input data, result, owner, and artifact proving it. Generated test counts never replace semantic coverage.

14. Repository Review Boundary

- This chapter is a repository-review specification. Exact executable implementation has not been inspected for every target behavior.
- Registered modules, catalog entries, README claims, frontend contracts, or plans are not proof of complete implementation.

Area	Classification
target aggregate, API, tables, state and workflow in this chapter	REFERENCE_ARCHITECTURE
registered module or catalog claim	DOCUMENTATION_ONLY_CLAIM until source inspection
uninspected integration	REQUIRES_REPOSITORY_REVIEW
behavior proven in another repository-grounded chapter	retain that chapter's evidence and classification
contradictory ownership or path claims	CONFLICT_REQUIRES_CANONICALIZATION

No statement upgrades implementation status merely because a file, directory, module name, frontend contract, database entry, plan, or report exists.

15. Worked Conformance Scenario

An authorized principal initiates a Command against an exact subject version. The service validates identity, tenant, mandate, Policy, Evidence, and idempotency. It records the state transition and outbox entry atomically. If an external dependency participates, timeout produces Outcome Unknown; reconciliation queries the source or waits for a verified callback instead of repeating the action blindly.

Portals show source, freshness, version, required action, and uncertainty. AI may extract, compare, summarize, detect anomalies, and recommend through typed Tools, but cannot own the subject or fabricate success. Later correction appends new facts, identifies affected projections and workflows, and preserves the historical Decision context.

16. Conformance Checklist

- ☐ stable identity and proposition ownership are explicit;
- ☐ authority and mandate are evaluated at action time;
- ☐ state, Recommendation, Decision, Intent, execution, and outcome remain distinct;
- ☐ Commands are typed, authorized, idempotent, and version guarded;
- ☐ Events describe completed facts;
- ☐ Evidence includes provenance, time, integrity, qualification, and correction;
- ☐ external outcomes retain their authority source;
- ☐ Portals show freshness and uncertainty;
- ☐ AI is bounded by typed Tools, Policy, approval, and outcome observation;
- ☐ security, tenant, facility, channel, and jurisdiction boundaries are enforced;
- ☐ Outcome Unknown and reconciliation exist where needed;
- ☐ corrections preserve history;
- ☐ tests prove invariants and recovery;
- ☐ implementation status is not upgraded without executable evidence.

17. Status Vocabulary

Status	Meaning
VERIFIED_IMPLEMENTED	Executable source and relevant behavior were inspected.
IMPLEMENTED_WITH_GAP	Executable behavior exists with a material governance or completeness gap.
PARTIAL_IMPLEMENTATION	Only part of the target capability is evidenced.
REFERENCE_ARCHITECTURE	Normative target behavior; no claim that it exists today.
PLANNED_NOT_IMPLEMENTED	Explicitly planned but not evidenced as executable.
DOCUMENTATION_ONLY_CLAIM	Documentation or client contract claims behavior without verified backend evidence.
CONFLICT_REQUIRES_CANONICALIZATION	Sources disagree and no final owner has been established.
REQUIRES_REPOSITORY_REVIEW	Necessary executable evidence has not yet been inspected.

ESG Dashboard — Routes, Pages, Components, and BFF Contracts

Metadata	Value
Volume	4
Chapter ID	V04-P10-01
Subject	ESGDashboardRouteRegistry
Status	Generated First-Draft Architecture Skeleton - Domain-Specific Expansion Required
Content maturity	TEMPLATE_DERIVED_REFERENCE_SKELETON unless repository citations prove otherwise
Default implementation classification	REFERENCE_ARCHITECTURE / REQUIRES_REPOSITORY_REVIEW
Accountable owner	Portal Architecture / ESG Dashboard
Evidence rule	No implementation claim without inspected executable evidence
Repository	chinair88-prog/allinb2c

1. Executive Orientation

This chapter defines how GTOS shall **inventory routes, layouts, pages, components, server/client boundaries, BFFs, APIs, realtime channels and ownership for sustainability, compliance and executive users, covering ESG metrics, evidence, lineage, methodology, uncertainty, reporting.**

The specification separates reality, observations, knowledge, Decisions, Intent, execution, and outcomes. A component name, database row, UI label, AI answer, or workflow state does not acquire authority merely because it is visible or technically convenient.

- Reality or external outcome
- ≠ Observation
 - ≠ Claim
 - ≠ derived Perspective
 - ≠ Prediction
 - ≠ Recommendation
 - ≠ authorized Decision
 - ≠ execution Intent

1.1 Accountable ownership

The accountable owner is **Portal Architecture / ESG Dashboard**. Supporting applications, shared infrastructure, integration adapters, analytics, and AI coordinate or present the capability but shall not silently own its authoritative propositions.

1.2 Scope

- create and identify the subject
- validate evidence and policy
- make authorized Decisions
- execute typed Commands
- publish completed-fact Events
- query current and historical perspectives
- correct and reconcile outcomes

1.3 Non-goals

- treating a registered Gradle module, catalog record, README, frontend route, migration plan, or generated report as proof of end-to-end implementation;
- direct cross-Domain database writes;
- generic status values that combine lifecycle, approval, provider, document, payment, dispute, and correction state;
- silent replacement of history;
- AI-created authority or fabricated external outcomes.

2. Ubiquitous Language and Subject Model

Subject	Required interpretation
ESGDashboardRouteRegistry	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit
ESGDashboardRouteRegistryVersion	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit
ESGDashboardRouteRegistryDecision	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit
ESGDashboardRouteRegistryEvidenceSet	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit
ESGDashboardRouteRegistryException	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit

Reference aggregate:

```
ESGDashboardRouteRegistry {
  subjectId
  tenantId
  organizationContext
  sourceIdentityRefs[]
  sourceVersionRefs[]
  lifecycleState
  relationshipRefs[]
  decisionRefs[]
  intentRefs[]
  evidenceSetRef
  knowledgeCutoff
  policyRefs[]
  authorityRef
  jurisdictionRefs[]
  createdAt
  effectiveAt
  updatedAt
  version
  correctionOf?
  correlationId
}
```

2.1 Core invariants

- Stable identity precedes relationship, state, and cross-system correlation.
- Effective time and recorded time remain distinct where business truth changes over time.
- Recommendation, Decision, Intent, execution, and outcome are separate concepts.
- No Portal, report, search index, cache, workflow, or AI Agent becomes a shadow owner of Domain truth.
- Binding submitted, approved, issued, accepted, or signed versions are immutable.
- Corrections append governed facts and preserve the original record.
- External authority and provider outcomes retain their source and qualification.
- Tenant and represented-principal context come from trusted authentication and mandate evaluation.
- Retried writes are idempotent and concurrency guarded.
- Outcome Unknown is explicit and reconciled before risky duplicate execution.

2.2 Required standards

- stable identifiers
- typed contracts
- immutable binding versions

- transactional outbox
- idempotent Commands
- explicit Outcome Unknown
- correction lineage
- machine-verifiable conformance

3. Actors, Roles, and Authority

- A conformant design distinguishes:
- the natural person acting;
 - the service or AI identity invoking a Tool;
 - the organization or principal represented;
 - the role or relationship granting context;
 - the mandate or delegation granting action authority;
 - the Policy and jurisdiction limiting the action;
 - the reviewer or approver responsible for a binding Decision.

Authority is evaluated at action time. Authentication alone does not grant business authority. Cached permissions and browser-supplied tenant headers are insufficient for high-impact actions.

4. Lifecycle and State Model

State	Semantics
PROPOSED	Distinct governed condition with entry, exit, timeout, correction and authority semantics
VALIDATION_PENDING	Distinct governed condition with entry, exit, timeout, correction and authority semantics
APPROVAL_PENDING	Distinct governed condition with entry, exit, timeout, correction and authority semantics
ACTIVE	Distinct governed condition with entry, exit, timeout, correction and authority semantics
SUSPENDED	Distinct governed condition with entry, exit, timeout, correction and authority semantics
CORRECTION_PENDING	Distinct governed condition with entry, exit, timeout, correction and authority semantics
RETIRED	Distinct governed condition with entry, exit, timeout, correction and authority semantics

```
stateDiagram-v2
    [*] --> PROPOSED
    PROPOSED --> VALIDATION_PENDING
    VALIDATION_PENDING --> APPROVAL_PENDING
    APPROVAL_PENDING --> ACTIVE
    ACTIVE --> SUSPENDED
    SUSPENDED --> CORRECTION_PENDING
    CORRECTION_PENDING --> RETIRED
```

The diagram is a primary reading path. Real implementations may add parallel review, amendment, appeal, timeout, suspension, partial completion, reconciliation, correction, and terminal failure without collapsing their meaning.

4.1 Transition rules

- transition through a typed, authorized Command;
- require exact expected version where concurrent change matters;
- record actor, represented principal, mandate, Policy, reason, and Evidence;
- use an idempotency key for retried writes;
- publish a completed-fact Event after durable state change;
- expose Outcome Unknown for unresolved external completion;
- preserve original and corrected states in historical reconstruction.

5. Decision, Evidence, and Knowledge Cutoff

Reference Decision:

```
Decision {
  decisionId
  decisionType
  subjectRef
  sourceVersionRefs[]
  knowledgeCutoff
  evidenceSetRef
  policyVersionRefs[]
  recommendationRefs[]
  principalId
  representedOrganizationId
  mandateRef
  rationale
  outcome
  decidedAt
  effectiveAt
  correctionOf?
}
```

Evidence records identify issuer or observer, subject, version, observed time, received time, effective interval, integrity, confidence, qualification, contradiction, correction, retention, residency, and access class. A recommendation may assist the Decision but cannot promote itself to the Decision.

6. Commands, Events, Queries, and Contracts

Reference Commands:

- CreateESGDashboardRouteRegistry
- ValidateESGDashboardRouteRegistry
- ApproveESGDashboardRouteRegistry
- ActivateESGDashboardRouteRegistry
- SuspendESGDashboardRouteRegistry
- CorrectESGDashboardRouteRegistry
- RetireESGDashboardRouteRegistry

Reference Events:

- ESGDashboardRouteRegistryCreated
- ESGDashboardRouteRegistryValidated
- ESGDashboardRouteRegistryApproved
- ESGDashboardRouteRegistryActivated
- ESGDashboardRouteRegistrySuspended
- ESGDashboardRouteRegistryCorrected
- ESGDashboardRouteRegistryRetired

Reference queries:

- GetESGDashboardRouteRegistry
- ListESGDashboardRouteRegistryRecords
- GetESGDashboardRouteRegistryTimeline
- GetESGDashboardRouteRegistryEvidence
- GetESGDashboardRouteRegistryDecisionPackage
- GetESGDashboardRouteRegistryExceptions
- GetESGDashboardRouteRegistryAuditTrail

Reference API surface:

```
POST /api/v1/esgdashboardrouterregistry/commands
GET  /api/v1/esgdashboardrouterregistry/{id}
GET  /api/v1/esgdashboardrouterregistry/{id}/timeline
GET  /api/v1/esgdashboardrouterregistry/{id}/evidence
GET  /api/v1/esgdashboardrouterregistry/{id}/decisions
POST /api/v1/esgdashboardrouterregistry/{id}/exceptions
POST /api/v1/esgdashboardrouterregistry/{id}/corrections
```

These endpoints are reference contracts, not claims that exact routes exist.

7. Workflow, Failure, and Compensation

```
flowchart TD
    A[Validate identity version and authority] --> B[Collect required evidence]
    B --> C{Policy and evidence gates pass?}
    C -- No --> D[Open exception or request correction]
    D --> B
    C -- Yes --> E[Record Decision or execution Intent]
    E --> F[Execute Domain command or external request]
    F --> G{Outcome known?}
    G -- Success --> H[Record fact and publish Event]
    G -- Failure --> I[Record failure and compensation options]
    G -- Unknown --> J[Enter Outcome Unknown]
    J --> K[Query source or wait for verified callback]
    K --> G
    H --> L[Update projections and downstream workflow]
```

Representative failure modes:

- stale or wrong source version
- duplicate submission or replay
- external timeout after possible success
- contradictory source observations
- lost Event after committed state
- approval or mandate revoked during execution
- downstream action before a mandatory gate
- partial completion across multiple subjects
- evidence later retracted or corrected
- tenant, facility, channel or jurisdiction mismatch

Recovery shall query the authoritative source before duplicate execution, preserve partial success, use compensating Intent rather than destructive rewrite, publish corrections, quarantine high-impact ambiguity, and record affected downstream subjects.

8. Data and Persistence Architecture

Reference table families:

Table family	Purpose
esgdashboardrouterregistry_aggregate	authoritative subject
esgdashboardrouterregistry_version	immutable submitted, approved, issued, or signed versions
esgdashboardrouterregistry_relationship	governed relationships
esgdashboardrouterregistry_decision	binding Decisions and rationale
esgdashboardrouterregistry_evidence_link	provenance and evidence relationships
esgdashboardrouterregistry_event_outbox	transactional Event publication
esgdashboardrouterregistry_idempotency	duplicate-write protection
esgdashboardrouterregistry_exception	exception, claim, dispute, or hold
esgdashboardrouterregistry_correction	correction and supersession lineage
esgdashboardrouterregistry_audit	privileged action evidence

The owning service controls schema and migration. Cross-Domain references use stable identifiers or contracts. Analytics, reports, caches, search, and vector indexes remain projections. Backup, restore, retention, legal hold, privacy, residency, and decommissioning requirements are explicit.

9. Portal and Experience Requirements

- ESG Dashboard: primary experience for sustainability, compliance and executive users.
- Operator and support views: diagnose failed or ambiguous journeys without assuming Domain ownership.
- Domain services: own authoritative data and action eligibility; the Portal consumes typed contracts.

Every Portal displays exact version, owner, state, freshness, required action, and uncertainty. It supports loading, empty, partial, stale, denied, error, timeout, and Outcome Unknown states; accessibility; locale, currency, unit, date, and RTL/LTR correctness; evidence audit; safe retry; and correction history.

10. AI Participation and Tool Governance

Permitted AI tasks:

- extract and classify evidence
- detect anomalies and missing fields
- summarize timelines and contradictions
- recommend next actions with sources and uncertainty

AI shall not own Domain records, grant itself authority, suppress contradictions, silently edit approved versions, fabricate external outcomes, or execute high-impact actions outside typed Tools, policy, approval, idempotency, sandbox, and outcome observation.

Every Agent Run records source context, prompt/model/tool versions, structured output, confidence and limitations, Policy result, approval, Tool calls, provider responses, final outcome, and recovery actions.

11. Security, Privacy, and Trust Boundaries

- least privilege and separation of duties
- tenant, organization, facility, channel and jurisdiction isolation
- integrity protection for binding evidence
- verified external callbacks and anti-replay controls

Additional controls include secret isolation, callback signature verification, audit of privileged action, emergency-access review, sensitive-data minimization, purpose limitation, and threat models for impersonation, tampering, replay, confused deputy, fraud, prompt injection, and exfiltration.

12. Reliability, SLOs, and Operations

SLI	Reference objective
authoritative read availability	99.9% monthly unless a stricter tier applies
acknowledged Command durability	no acknowledged write may be silently lost
Event publication	99.9% within five minutes after committed fact
duplicate prevention	100% for same tenant, Command class, and idempotency key
binding Decision audit completeness	100%
state-state detection	bounded by business deadline

Dashboards and runbooks cover backlog, error budget, dependency failure, retry budget, DLQ, workflow stall, provider outage, reconciliation, capacity, backup/restore, release/rollback, incident command, and post-incident correction.

13. Testing and Continuous Conformance

- aggregate invariant and transition tests
- authorization, delegation, separation-of-duties and tenant-isolation tests
- idempotency and optimistic-concurrency tests
- database migration, key, constraint and rollback tests
- contract, outbox/inbox, duplicate, replay and DLQ tests
- workflow restart, timeout and compensation tests
- Portal E2E tests for success, partial, stale, denied, error and Outcome Unknown states
- accessibility, locale, currency, unit and RTL/LTR tests
- security adversarial, fraud and data-exfiltration tests
- AI evaluation, prompt-injection, policy-bypass and unauthorized-tool tests
- historical reconstruction, correction and audit-completeness tests
- performance, capacity, recovery and operational exercise tests

Release evidence links each invariant and control to the test, environment, input data, result, owner, and artifact proving it. Generated test counts never replace semantic coverage.

14. Repository Review Boundary

- This chapter is a repository-review specification. Exact executable implementation has not been inspected for every target behavior.
- Registered modules, catalog entries, README claims, frontend contracts, or plans are not proof of complete implementation.

Area	Classification
target aggregate, API, tables, state and workflow in this chapter	REFERENCE_ARCHITECTURE
registered module or catalog claim	DOCUMENTATION_ONLY_CLAIM until source inspection
uninspected integration	REQUIRES_REPOSITORY_REVIEW
behavior proven in another repository-grounded chapter	retain that chapter's evidence and classification
contradictory ownership or path claims	CONFLICT_REQUIRES_CANONICALIZATION

No statement upgrades implementation status merely because a file, directory, module name, frontend contract, database entry, plan, or report exists.

15. Worked Conformance Scenario

An authorized principal initiates a Command against an exact subject version. The service validates identity, tenant, mandate, Policy, Evidence, and idempotency. It records the state transition and outbox entry atomically. If an external dependency participates, timeout produces Outcome Unknown; reconciliation queries the source or waits for a verified callback instead of repeating the action blindly.

Portals show source, freshness, version, required action, and uncertainty. AI may extract, compare, summarize, detect anomalies, and recommend through typed Tools, but cannot own the subject or fabricate success. Later correction appends new facts, identifies affected projections and workflows, and preserves the historical Decision context.

16. Conformance Checklist

- ☐ stable identity and proposition ownership are explicit;
- ☐ authority and mandate are evaluated at action time;
- ☐ state, Recommendation, Decision, Intent, execution, and outcome remain distinct;
- ☐ Commands are typed, authorized, idempotent, and version guarded;
- ☐ Events describe completed facts;
- ☐ Evidence includes provenance, time, integrity, qualification, and correction;
- ☐ external outcomes retain their authority source;
- ☐ Portals show freshness and uncertainty;
- ☐ AI is bounded by typed Tools, Policy, approval, and outcome observation;
- ☐ security, tenant, facility, channel, and jurisdiction boundaries are enforced;
- ☐ Outcome Unknown and reconciliation exist where needed;
- ☐ corrections preserve history;
- ☐ tests prove invariants and recovery;
- ☐ implementation status is not upgraded without executable evidence.

17. Status Vocabulary

Status	Meaning
VERIFIED_IMPLEMENTED	Executable source and relevant behavior were inspected. Executable behavior exists with a material governance or completeness gap.
IMPLEMENTED_WITH_GAP	
PARTIAL_IMPLEMENTATION	Only part of the target capability is evidenced.
REFERENCE_ARCHITECTURE	Normative target behavior; no claim that it exists today.
PLANNED_NOT_IMPLEMENTED	Explicitly planned but not evidenced as executable.
DOCUMENTATION_ONLY_CLAIM	Documentation or client contract claims behavior without verified backend evidence.
CONFLICT_REQUIRES_CANONICALIZATION	Sources disagree and no final owner has been established.
REQUIRES_REPOSITORY_REVIEW	Necessary executable evidence has not yet been inspected.

ESG Dashboard — Identity, Session, Authorization, and Trust Boundaries

Metadata	Value
Volume	4
Chapter ID	V04-P10-02
Subject	ESGDashboardAccessModel
Status	Generated First-Draft Architecture Skeleton - Domain-Specific Expansion Required
Content maturity	TEMPLATE_DERIVED_REFERENCE_SKELETON unless repository citations prove otherwise
Default implementation classification	REFERENCE_ARCHITECTURE / REQUIRES_REPOSITORY_REVIEW
Accountable owner	Portal Architecture / ESG Dashboard
Evidence rule	No implementation claim without inspected executable evidence
Repository	chinair88-prog/allinb2c

1. Executive Orientation

This chapter defines how GTOS shall **govern login, session, role, relationship, tenant, facility, channel, delegation, impersonation and privileged action for sustainability, compliance and executive users, covering ESG metrics, evidence, lineage, methodology, uncertainty, reporting.**

The specification separates reality, observations, knowledge, Decisions, Intent, execution, and outcomes. A component name, database row, UI label, AI answer, or workflow state does not acquire authority merely because it is visible or technically convenient.

Reality or external outcome
≠ Observation
≠ Claim
≠ derived Perspective
≠ Prediction
≠ Recommendation
≠ authorized Decision
≠ execution Intent

1.1 Accountable ownership

The accountable owner is **Portal Architecture / ESG Dashboard**. Supporting applications, shared infrastructure, integration adapters, analytics, and AI coordinate or present the capability but shall not silently own its authoritative propositions.

1.2 Scope

- create and identify the subject
- validate evidence and policy
- make authorized Decisions
- execute typed Commands
- publish completed-fact Events
- query current and historical perspectives
- correct and reconcile outcomes

1.3 Non-goals

- treating a registered Gradle module, catalog record, README, frontend route, migration plan, or generated report as proof of end-to-end implementation;
- direct cross-Domain database writes;
- generic status values that combine lifecycle, approval, provider, document, payment, dispute, and correction state;
- silent replacement of history;
- AI-created authority or fabricated external outcomes.

2. Ubiquitous Language and Subject Model

Subject	Required interpretation
ESGDashboardAccessModel	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit
ESGDashboardAccessModelVersion	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit
ESGDashboardAccessModelDecision	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit
ESGDashboardAccessModelEvidenceSet	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit
ESGDashboardAccessModelException	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit

Reference aggregate:

```
ESGDashboardAccessModel {
  subjectId
  tenantId
  organizationContext
  sourceIdentityRefs[]
  sourceVersionRefs[]
  lifecycleState
  relationshipRefs[]
  decisionRefs[]
  intentRefs[]
  evidenceSetRef
  knowledgeCutoff
  policyRefs[]
  authorityRef
  jurisdictionRefs[]
  createdAt
  effectiveAt
  updatedAt
  version
  correctionOf?
  correlationId
}
```

2.1 Core invariants

- Stable identity precedes relationship, state, and cross-system correlation.
- Effective time and recorded time remain distinct where business truth changes over time.
- Recommendation, Decision, Intent, execution, and outcome are separate concepts.
- No Portal, report, search index, cache, workflow, or AI Agent becomes a shadow owner of Domain truth.
- Binding submitted, approved, issued, accepted, or signed versions are immutable.
- Corrections append governed facts and preserve the original record.
- External authority and provider outcomes retain their source and qualification.
- Tenant and represented-principal context come from trusted authentication and mandate evaluation.
- Retried writes are idempotent and concurrency guarded.
- Outcome Unknown is explicit and reconciled before risky duplicate execution.

2.2 Required standards

- stable identifiers
- typed contracts
- immutable binding versions

- transactional outbox
- idempotent Commands
- explicit Outcome Unknown
- correction lineage
- machine-verifiable conformance

3. Actors, Roles, and Authority

A conformant design distinguishes:

- the natural person acting;
- the service or AI identity invoking a Tool;
- the organization or principal represented;
- the role or relationship granting context;
- the mandate or delegation granting action authority;
- the Policy and jurisdiction limiting the action;
- the reviewer or approver responsible for a binding Decision.

Authority is evaluated at action time. Authentication alone does not grant business authority. Cached permissions and browser-supplied tenant headers are insufficient for high-impact actions.

4. Lifecycle and State Model

State	Semantics
PROPOSED	Distinct governed condition with entry, exit, timeout, correction and authority semantics
VALIDATION_PENDING	Distinct governed condition with entry, exit, timeout, correction and authority semantics
APPROVAL_PENDING	Distinct governed condition with entry, exit, timeout, correction and authority semantics
ACTIVE	Distinct governed condition with entry, exit, timeout, correction and authority semantics
SUSPENDED	Distinct governed condition with entry, exit, timeout, correction and authority semantics
CORRECTION_PENDING	Distinct governed condition with entry, exit, timeout, correction and authority semantics
RETIRED	Distinct governed condition with entry, exit, timeout, correction and authority semantics

```
stateDiagram-v2
    [*] --> PROPOSED
    PROPOSED --> VALIDATION_PENDING
    VALIDATION_PENDING --> APPROVAL_PENDING
    APPROVAL_PENDING --> ACTIVE
    ACTIVE --> SUSPENDED
    SUSPENDED --> CORRECTION_PENDING
    CORRECTION_PENDING --> RETIRED
```

The diagram is a primary reading path. Real implementations may add parallel review, amendment, appeal, timeout, suspension, partial completion, reconciliation, correction, and terminal failure without collapsing their meaning.

4.1 Transition rules

- transition through a typed, authorized Command;
- require exact expected version where concurrent change matters;
- record actor, represented principal, mandate, Policy, reason, and Evidence;
- use an idempotency key for retried writes;
- publish a completed-fact Event after durable state change;
- expose Outcome Unknown for unresolved external completion;
- preserve original and corrected states in historical reconstruction.

5. Decision, Evidence, and Knowledge Cutoff

Reference Decision:

```
Decision {
  decisionId
  decisionType
  subjectRef
  sourceVersionRefs[]
  knowledgeCutoff
  evidenceSetRef
  policyVersionRefs[]
  recommendationRefs[]
  principalId
  representedOrganizationId
  mandateRef
  rationale
  outcome
  decidedAt
  effectiveAt
  correctionOf?
}
```

Evidence records identify issuer or observer, subject, version, observed time, received time, effective interval, integrity, confidence, qualification, contradiction, correction, retention, residency, and access class. A recommendation may assist the Decision but cannot promote itself to the Decision.

6. Commands, Events, Queries, and Contracts

Reference Commands:

- CreateESGDashboardAccessModel
- ValidateESGDashboardAccessModel
- ApproveESGDashboardAccessModel
- ActivateESGDashboardAccessModel
- SuspendESGDashboardAccessModel
- CorrectESGDashboardAccessModel
- RetireESGDashboardAccessModel

Reference Events:

- ESGDashboardAccessModelCreated
- ESGDashboardAccessModelValidated
- ESGDashboardAccessModelApproved
- ESGDashboardAccessModelActivated
- ESGDashboardAccessModelSuspended
- ESGDashboardAccessModelCorrected
- ESGDashboardAccessModelRetired

Reference queries:

- GetESGDashboardAccessModel
- ListESGDashboardAccessModelRecords
- GetESGDashboardAccessModelTimeline
- GetESGDashboardAccessModelEvidence
- GetESGDashboardAccessModelDecisionPackage
- GetESGDashboardAccessModelExceptions
- GetESGDashboardAccessModelAuditTrail

Reference API surface:

```
POST /api/v1/esgdashboardaccessmodel/commands
GET  /api/v1/esgdashboardaccessmodel/{id}
GET  /api/v1/esgdashboardaccessmodel/{id}/timeline
GET  /api/v1/esgdashboardaccessmodel/{id}/evidence
GET  /api/v1/esgdashboardaccessmodel/{id}/decisions
POST /api/v1/esgdashboardaccessmodel/{id}/exceptions
POST /api/v1/esgdashboardaccessmodel/{id}/corrections
```

These endpoints are reference contracts, not claims that exact routes exist.

7. Workflow, Failure, and Compensation

flowchart TD

```
A[Validate identity version and authority] --> B[Collect required evidence]
B --> C{Policy and evidence gates pass?}
C -- No --> D[Open exception or request correction]
D --> B
C -- Yes --> E[Record Decision or execution Intent]
E --> F[Execute Domain command or external request]
F --> G{Outcome known?}
G -- Success --> H[Record fact and publish Event]
G -- Failure --> I[Record failure and compensation options]
G -- Unknown --> J[Enter Outcome Unknown]
J --> K[Query source or wait for verified callback]
K --> G
H --> L[Update projections and downstream workflow]
```

Representative failure modes:

- stale or wrong source version
- duplicate submission or replay
- external timeout after possible success
- contradictory source observations
- lost Event after committed state
- approval or mandate revoked during execution
- downstream action before a mandatory gate
- partial completion across multiple subjects
- evidence later retracted or corrected
- tenant, facility, channel or jurisdiction mismatch

Recovery shall query the authoritative source before duplicate execution, preserve partial success, use compensating Intent rather than destructive rewrite, publish corrections, quarantine high-impact ambiguity, and record affected downstream subjects.

8. Data and Persistence Architecture

Reference table families:

Table family	Purpose
esgdashboardaccessmodel_aggregate	authoritative subject
esgdashboardaccessmodel_version	immutable submitted, approved, issued, or signed versions
esgdashboardaccessmodel_relationship	governed relationships
esgdashboardaccessmodel_decision	binding Decisions and rationale
esgdashboardaccessmodel_evidence_link	provenance and evidence relationships
esgdashboardaccessmodel_event_outbox	transactional Event publication
esgdashboardaccessmodel_idempotency	duplicate-write protection
esgdashboardaccessmodel_exception	exception, claim, dispute, or hold
esgdashboardaccessmodel_correction	correction and supersession lineage
esgdashboardaccessmodel_audit	privileged action evidence

The owning service controls schema and migration. Cross-Domain references use stable identifiers or contracts. Analytics, reports, caches, search, and vector indexes remain projections. Backup, restore, retention, legal hold, privacy, residency, and decommissioning requirements are explicit.

9. Portal and Experience Requirements

- ESG Dashboard: primary experience for sustainability, compliance and executive users.
- Operator and support views: diagnose failed or ambiguous journeys without assuming Domain ownership.
- Domain services: own authoritative data and action eligibility; the Portal consumes typed contracts.

Every Portal displays exact version, owner, state, freshness, required action, and uncertainty. It supports loading, empty, partial, stale, denied, error, timeout, and Outcome Unknown states; accessibility; locale, currency, unit, date, and RTL/LTR correctness; evidence audit; safe retry; and correction history.

10. AI Participation and Tool Governance

Permitted AI tasks:

- extract and classify evidence
- detect anomalies and missing fields
- summarize timelines and contradictions
- recommend next actions with sources and uncertainty

AI shall not own Domain records, grant itself authority, suppress contradictions, silently edit approved versions, fabricate external outcomes, or execute high-impact actions outside typed Tools, policy, approval, idempotency, sandbox, and outcome observation.

Every Agent Run records source context, prompt/model/tool versions, structured output, confidence and limitations, Policy result, approval, Tool calls, provider responses, final outcome, and recovery actions.

11. Security, Privacy, and Trust Boundaries

- least privilege and separation of duties
- tenant, organization, facility, channel and jurisdiction isolation
- integrity protection for binding evidence
- verified external callbacks and anti-replay controls

Additional controls include secret isolation, callback signature verification, audit of privileged action, emergency-access review, sensitive-data minimization, purpose limitation, and threat models for impersonation, tampering, replay, confused deputy, fraud, prompt injection, and exfiltration.

12. Reliability, SLOs, and Operations

SLI	Reference objective
authoritative read availability	99.9% monthly unless a stricter tier applies
acknowledged Command durability	no acknowledged write may be silently lost
Event publication	99.9% within five minutes after committed fact
duplicate prevention	100% for same tenant, Command class, and idempotency key
binding Decision audit completeness	100%
state-state detection	bounded by business deadline

Dashboards and runbooks cover backlog, error budget, dependency failure, retry budget, DLQ, workflow stall, provider outage, reconciliation, capacity, backup/restore, release/rollback, incident command, and post-incident correction.

13. Testing and Continuous Conformance

- aggregate invariant and transition tests
- authorization, delegation, separation-of-duties and tenant-isolation tests
- idempotency and optimistic-concurrency tests
- database migration, key, constraint and rollback tests
- contract, outbox/inbox, duplicate, replay and DLQ tests
- workflow restart, timeout and compensation tests
- Portal E2E tests for success, partial, stale, denied, error and Outcome Unknown states
- accessibility, locale, currency, unit and RTL/LTR tests
- security adversarial, fraud and data-exfiltration tests
- AI evaluation, prompt-injection, policy-bypass and unauthorized-tool tests
- historical reconstruction, correction and audit-completeness tests
- performance, capacity, recovery and operational exercise tests

Release evidence links each invariant and control to the test, environment, input data, result, owner, and artifact proving it. Generated test counts never replace semantic coverage.

14. Repository Review Boundary

- This chapter is a repository-review specification. Exact executable implementation has not been inspected for every target behavior.
- Registered modules, catalog entries, README claims, frontend contracts, or plans are not proof of complete implementation.

Area	Classification
target aggregate, API, tables, state and workflow in this chapter	REFERENCE_ARCHITECTURE
registered module or catalog claim	DOCUMENTATION_ONLY_CLAIM until source inspection
uninspected integration	REQUIRES_REPOSITORY_REVIEW
behavior proven in another repository-grounded chapter	retain that chapter's evidence and classification
contradictory ownership or path claims	CONFLICT_REQUIRES_CANONICALIZATION

No statement upgrades implementation status merely because a file, directory, module name, frontend contract, database entry, plan, or report exists.

15. Worked Conformance Scenario

An authorized principal initiates a Command against an exact subject version. The service validates identity, tenant, mandate, Policy, Evidence, and idempotency. It records the state transition and outbox entry atomically. If an external dependency participates, timeout produces Outcome Unknown; reconciliation queries the source or waits for a verified callback instead of repeating the action blindly.

Portals show source, freshness, version, required action, and uncertainty. AI may extract, compare, summarize, detect anomalies, and recommend through typed Tools, but cannot own the subject or fabricate success. Later correction appends new facts, identifies affected projections and workflows, and preserves the historical Decision context.

16. Conformance Checklist

- ☐ stable identity and proposition ownership are explicit;
- ☐ authority and mandate are evaluated at action time;
- ☐ state, Recommendation, Decision, Intent, execution, and outcome remain distinct;
- ☐ Commands are typed, authorized, idempotent, and version guarded;
- ☐ Events describe completed facts;
- ☐ Evidence includes provenance, time, integrity, qualification, and correction;
- ☐ external outcomes retain their authority source;
- ☐ Portals show freshness and uncertainty;
- ☐ AI is bounded by typed Tools, Policy, approval, and outcome observation;
- ☐ security, tenant, facility, channel, and jurisdiction boundaries are enforced;
- ☐ Outcome Unknown and reconciliation exist where needed;
- ☐ corrections preserve history;
- ☐ tests prove invariants and recovery;
- ☐ implementation status is not upgraded without executable evidence.

17. Status Vocabulary

Status	Meaning
VERIFIED_IMPLEMENTED	Executable source and relevant behavior were inspected. Executable behavior exists with a material governance or completeness gap.
IMPLEMENTED_WITH_GAP	
PARTIAL_IMPLEMENTATION	Only part of the target capability is evidenced.
REFERENCE_ARCHITECTURE	Normative target behavior; no claim that it exists today.
PLANNED_NOT_IMPLEMENTED	Explicitly planned but not evidenced as executable.
DOCUMENTATION_ONLY_CLAIM	Documentation or client contract claims behavior without verified backend evidence.
CONFLICT_REQUIRES_CANONICALIZATION	Sources disagree and no final owner has been established.
REQUIRES_REPOSITORY_REVIEW	Necessary executable evidence has not yet been inspected.

ESG Dashboard — UX States, Accessibility, Localization, Analytics, and E2E

Metadata	Value
Volume	4
Chapter ID	V04-P10-03
Subject	ESGDashboardExperienceStandard
Status	Generated First-Draft Architecture Skeleton - Domain-Specific Expansion Required
Content maturity	TEMPLATE_DERIVED_REFERENCE_SKELETON unless repository citations prove otherwise
Default implementation classification	REFERENCE_ARCHITECTURE / REQUIRES_REPOSITORY_REVIEW
Accountable owner	Portal Architecture / ESG Dashboard
Evidence rule	No implementation claim without inspected executable evidence
Repository	chinair88-prog/allinb2c

1. Executive Orientation

This chapter defines how GTOS shall **specify loading, empty, partial, stale, error, denied, offline, accessibility, RTL/LTR, analytics, audit and test journeys for sustainability, compliance and executive users, covering ESG metrics, evidence, lineage, methodology, uncertainty, reporting.**

The specification separates reality, observations, knowledge, Decisions, Intent, execution, and outcomes. A component name, database row, UI label, AI answer, or workflow state does not acquire authority merely because it is visible or technically convenient.

Reality or external outcome

- ≠ Observation
- ≠ Claim
- ≠ derived Perspective
- ≠ Prediction
- ≠ Recommendation
- ≠ authorized Decision
- ≠ execution Intent

1.1 Accountable ownership

The accountable owner is **Portal Architecture / ESG Dashboard**. Supporting applications, shared infrastructure, integration adapters, analytics, and AI coordinate or present the capability but shall not silently own its authoritative propositions.

1.2 Scope

- create and identify the subject
- validate evidence and policy
- make authorized Decisions
- execute typed Commands
- publish completed-fact Events
- query current and historical perspectives
- correct and reconcile outcomes

1.3 Non-goals

- treating a registered Gradle module, catalog record, README, frontend route, migration plan, or generated report as proof of end-to-end implementation;
- direct cross-Domain database writes;
- generic status values that combine lifecycle, approval, provider, document, payment, dispute, and correction state;
- silent replacement of history;
- AI-created authority or fabricated external outcomes.

2. Ubiquitous Language and Subject Model

Subject	Required interpretation
ESGDashboardExperienceStandard	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit
ESGDashboardExperienceStandardVersion	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit
ESGDashboardExperienceStandardDecision	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit
ESGDashboardExperienceStandardEvidenceSet	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit
ESGDashboardExperienceStandardException	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit

Reference aggregate:

```
ESGDashboardExperienceStandard {
  subjectId
  tenantId
  organizationContext
  sourceIdentityRefs[]
  sourceVersionRefs[]
  lifecycleState
  relationshipRefs[]
  decisionRefs[]
  intentRefs[]
  evidenceSetRef
  knowledgeCutoff
  policyRefs[]
  authorityRef
  jurisdictionRefs[]
  createdAt
  effectiveAt
  updatedAt
  version
  correctionOf?
  correlationId
}
```

2.1 Core invariants

- Stable identity precedes relationship, state, and cross-system correlation.
- Effective time and recorded time remain distinct where business truth changes over time.
- Recommendation, Decision, Intent, execution, and outcome are separate concepts.
- No Portal, report, search index, cache, workflow, or AI Agent becomes a shadow owner of Domain truth.
- Binding submitted, approved, issued, accepted, or signed versions are immutable.
- Corrections append governed facts and preserve the original record.
- External authority and provider outcomes retain their source and qualification.
- Tenant and represented-principal context come from trusted authentication and mandate evaluation.
- Retried writes are idempotent and concurrency guarded.
- Outcome Unknown is explicit and reconciled before risky duplicate execution.

2.2 Required standards

- stable identifiers
- typed contracts
- immutable binding versions

- transactional outbox
- idempotent Commands
- explicit Outcome Unknown
- correction lineage
- machine-verifiable conformance

3. Actors, Roles, and Authority

A conformant design distinguishes:

- the natural person acting;
- the service or AI identity invoking a Tool;
- the organization or principal represented;
- the role or relationship granting context;
- the mandate or delegation granting action authority;
- the Policy and jurisdiction limiting the action;
- the reviewer or approver responsible for a binding Decision.

Authority is evaluated at action time. Authentication alone does not grant business authority. Cached permissions and browser-supplied tenant headers are insufficient for high-impact actions.

4. Lifecycle and State Model

State	Semantics
PROPOSED	Distinct governed condition with entry, exit, timeout, correction and authority semantics
VALIDATION_PENDING	Distinct governed condition with entry, exit, timeout, correction and authority semantics
APPROVAL_PENDING	Distinct governed condition with entry, exit, timeout, correction and authority semantics
ACTIVE	Distinct governed condition with entry, exit, timeout, correction and authority semantics
SUSPENDED	Distinct governed condition with entry, exit, timeout, correction and authority semantics
CORRECTION_PENDING	Distinct governed condition with entry, exit, timeout, correction and authority semantics
RETIRED	Distinct governed condition with entry, exit, timeout, correction and authority semantics

```
stateDiagram-v2
    [*] --> PROPOSED
    PROPOSED --> VALIDATION_PENDING
    VALIDATION_PENDING --> APPROVAL_PENDING
    APPROVAL_PENDING --> ACTIVE
    ACTIVE --> SUSPENDED
    SUSPENDED --> CORRECTION_PENDING
    CORRECTION_PENDING --> RETIRED
```

The diagram is a primary reading path. Real implementations may add parallel review, amendment, appeal, timeout, suspension, partial completion, reconciliation, correction, and terminal failure without collapsing their meaning.

4.1 Transition rules

- transition through a typed, authorized Command;
- require exact expected version where concurrent change matters;
- record actor, represented principal, mandate, Policy, reason, and Evidence;
- use an idempotency key for retried writes;
- publish a completed-fact Event after durable state change;
- expose Outcome Unknown for unresolved external completion;
- preserve original and corrected states in historical reconstruction.

5. Decision, Evidence, and Knowledge Cutoff

Reference Decision:

```
Decision {
  decisionId
  decisionType
  subjectRef
  sourceVersionRefs[]
  knowledgeCutoff
  evidenceSetRef
  policyVersionRefs[]
  recommendationRefs[]
  principalId
  representedOrganizationId
  mandateRef
  rationale
  outcome
  decidedAt
  effectiveAt
  correctionOf?
}
```

Evidence records identify issuer or observer, subject, version, observed time, received time, effective interval, integrity, confidence, qualification, contradiction, correction, retention, residency, and access class. A recommendation may assist the Decision but cannot promote itself to the Decision.

6. Commands, Events, Queries, and Contracts

Reference Commands:

- CreateESGDashboardExperienceStandard
- ValidateESGDashboardExperienceStandard
- ApproveESGDashboardExperienceStandard
- ActivateESGDashboardExperienceStandard
- SuspendESGDashboardExperienceStandard
- CorrectESGDashboardExperienceStandard
- RetireESGDashboardExperienceStandard

Reference Events:

- ESGDashboardExperienceStandardCreated
- ESGDashboardExperienceStandardValidated
- ESGDashboardExperienceStandardApproved
- ESGDashboardExperienceStandardActivated
- ESGDashboardExperienceStandardSuspended
- ESGDashboardExperienceStandardCorrected
- ESGDashboardExperienceStandardRetired

Reference queries:

- GetESGDashboardExperienceStandard
- ListESGDashboardExperienceStandardRecords
- GetESGDashboardExperienceStandardTimeline
- GetESGDashboardExperienceStandardEvidence
- GetESGDashboardExperienceStandardDecisionPackage
- GetESGDashboardExperienceStandardExceptions
- GetESGDashboardExperienceStandardAuditTrail

Reference API surface:

```
POST /api/v1/esgdashboardexperiencestandard/commands
GET  /api/v1/esgdashboardexperiencestandard/{id}
GET  /api/v1/esgdashboardexperiencestandard/{id}/timeline
GET  /api/v1/esgdashboardexperiencestandard/{id}/evidence
GET  /api/v1/esgdashboardexperiencestandard/{id}/decisions
POST /api/v1/esgdashboardexperiencestandard/{id}/exceptions
POST /api/v1/esgdashboardexperiencestandard/{id}/corrections
```

These endpoints are reference contracts, not claims that exact routes exist.

7. Workflow, Failure, and Compensation

```
flowchart TD
    A[Validate identity version and authority] --> B[Collect required evidence]
    B --> C{Policy and evidence gates pass?}
    C -- No --> D[Open exception or request correction]
    D --> B
    C -- Yes --> E[Record Decision or execution Intent]
    E --> F[Execute Domain command or external request]
    F --> G{Outcome known?}
    G -- Success --> H[Record fact and publish Event]
    G -- Failure --> I[Record failure and compensation options]
    G -- Unknown --> J[Enter Outcome Unknown]
    J --> K[Query source or wait for verified callback]
    K --> G
    H --> L[Update projections and downstream workflow]
```

Representative failure modes:

- stale or wrong source version
- duplicate submission or replay
- external timeout after possible success
- contradictory source observations
- lost Event after committed state
- approval or mandate revoked during execution
- downstream action before a mandatory gate
- partial completion across multiple subjects
- evidence later retracted or corrected
- tenant, facility, channel or jurisdiction mismatch

Recovery shall query the authoritative source before duplicate execution, preserve partial success, use compensating Intent rather than destructive rewrite, publish corrections, quarantine high-impact ambiguity, and record affected downstream subjects.

8. Data and Persistence Architecture

Reference table families:

Table family	Purpose
esgdashboardexperiencestandard_aggregate	authoritative subject
esgdashboardexperiencestandard_version	immutable submitted, approved, issued, or signed versions
esgdashboardexperiencestandard_relationship	governed relationships
esgdashboardexperiencestandard_decision	binding Decisions and rationale
esgdashboardexperiencestandard_evidence_link	provenance and evidence relationships
esgdashboardexperiencestandard_event_outbox	transactional Event publication
esgdashboardexperiencestandard_idempotency	duplicate-write protection
esgdashboardexperiencestandard_exception	exception, claim, dispute, or hold
esgdashboardexperiencestandard_correction	correction and supersession lineage
esgdashboardexperiencestandard_audit	privileged action evidence

The owning service controls schema and migration. Cross-Domain references use stable identifiers or contracts. Analytics, reports, caches, search, and vector indexes remain projections. Backup, restore, retention, legal hold, privacy, residency, and decommissioning requirements are explicit.

9. Portal and Experience Requirements

- ESG Dashboard: primary experience for sustainability, compliance and executive users.
- Operator and support views: diagnose failed or ambiguous journeys without assuming Domain ownership.
- Domain services: own authoritative data and action eligibility; the Portal consumes typed contracts.

Every Portal displays exact version, owner, state, freshness, required action, and uncertainty. It supports loading, empty, partial, stale, denied, error, timeout, and Outcome Unknown states; accessibility; locale, currency, unit, date, and RTL/LTR correctness; evidence audit; safe retry; and correction history.

10. AI Participation and Tool Governance

Permitted AI tasks:

- extract and classify evidence
- detect anomalies and missing fields
- summarize timelines and contradictions
- recommend next actions with sources and uncertainty

AI shall not own Domain records, grant itself authority, suppress contradictions, silently edit approved versions, fabricate external outcomes, or execute high-impact actions outside typed Tools, policy, approval, idempotency, sandbox, and outcome observation.

Every Agent Run records source context, prompt/model/tool versions, structured output, confidence and limitations, Policy result, approval, Tool calls, provider responses, final outcome, and recovery actions.

11. Security, Privacy, and Trust Boundaries

- least privilege and separation of duties
- tenant, organization, facility, channel and jurisdiction isolation
- integrity protection for binding evidence
- verified external callbacks and anti-replay controls

Additional controls include secret isolation, callback signature verification, audit of privileged action, emergency-access review, sensitive-data minimization, purpose limitation, and threat models for impersonation, tampering, replay, confused deputy, fraud, prompt injection, and exfiltration.

12. Reliability, SLOs, and Operations

SLI	Reference objective
authoritative read availability	99.9% monthly unless a stricter tier applies
acknowledged Command durability	no acknowledged write may be silently lost
Event publication	99.9% within five minutes after committed fact
duplicate prevention	100% for same tenant, Command class, and idempotency key
binding Decision audit completeness	100%
state-state detection	bounded by business deadline

Dashboards and runbooks cover backlog, error budget, dependency failure, retry budget, DLQ, workflow stall, provider outage, reconciliation, capacity, backup/restore, release/rollback, incident command, and post-incident correction.

13. Testing and Continuous Conformance

- aggregate invariant and transition tests
- authorization, delegation, separation-of-duties and tenant-isolation tests
- idempotency and optimistic-concurrency tests
- database migration, key, constraint and rollback tests
- contract, outbox/inbox, duplicate, replay and DLQ tests
- workflow restart, timeout and compensation tests
- Portal E2E tests for success, partial, stale, denied, error and Outcome Unknown states
- accessibility, locale, currency, unit and RTL/LTR tests
- security adversarial, fraud and data-exfiltration tests
- AI evaluation, prompt-injection, policy-bypass and unauthorized-tool tests
- historical reconstruction, correction and audit-completeness tests
- performance, capacity, recovery and operational exercise tests

Release evidence links each invariant and control to the test, environment, input data, result, owner, and artifact proving it. Generated test counts never replace semantic coverage.

14. Repository Review Boundary

- This chapter is a repository-review specification. Exact executable implementation has not been inspected for every target behavior.
- Registered modules, catalog entries, README claims, frontend contracts, or plans are not proof of complete implementation.

Area	Classification
target aggregate, API, tables, state and workflow in this chapter	REFERENCE_ARCHITECTURE
registered module or catalog claim	DOCUMENTATION_ONLY_CLAIM until source inspection
uninspected integration	REQUIRES_REPOSITORY_REVIEW
behavior proven in another repository-grounded chapter	retain that chapter's evidence and classification
contradictory ownership or path claims	CONFLICT_REQUIRES_CANONICALIZATION

No statement upgrades implementation status merely because a file, directory, module name, frontend contract, database entry, plan, or report exists.

15. Worked Conformance Scenario

An authorized principal initiates a Command against an exact subject version. The service validates identity, tenant, mandate, Policy, Evidence, and idempotency. It records the state transition and outbox entry atomically. If an external dependency participates, timeout produces Outcome Unknown; reconciliation queries the source or waits for a verified callback instead of repeating the action blindly.

Portals show source, freshness, version, required action, and uncertainty. AI may extract, compare, summarize, detect anomalies, and recommend through typed Tools, but cannot own the subject or fabricate success. Later correction appends new facts, identifies affected projections and workflows, and preserves the historical Decision context.

16. Conformance Checklist

- ☐ stable identity and proposition ownership are explicit;
- ☐ authority and mandate are evaluated at action time;
- ☐ state, Recommendation, Decision, Intent, execution, and outcome remain distinct;
- ☐ Commands are typed, authorized, idempotent, and version guarded;
- ☐ Events describe completed facts;
- ☐ Evidence includes provenance, time, integrity, qualification, and correction;
- ☐ external outcomes retain their authority source;
- ☐ Portals show freshness and uncertainty;
- ☐ AI is bounded by typed Tools, Policy, approval, and outcome observation;
- ☐ security, tenant, facility, channel, and jurisdiction boundaries are enforced;
- ☐ Outcome Unknown and reconciliation exist where needed;
- ☐ corrections preserve history;
- ☐ tests prove invariants and recovery;
- ☐ implementation status is not upgraded without executable evidence.

17. Status Vocabulary

Status	Meaning
VERIFIED_IMPLEMENTED	Executable source and relevant behavior were inspected. Executable behavior exists with a material governance or completeness gap.
IMPLEMENTED_WITH_GAP	
PARTIAL_IMPLEMENTATION	Only part of the target capability is evidenced.
REFERENCE_ARCHITECTURE	Normative target behavior; no claim that it exists today.
PLANNED_NOT_IMPLEMENTED	Explicitly planned but not evidenced as executable.
DOCUMENTATION_ONLY_CLAIM	Documentation or client contract claims behavior without verified backend evidence.
CONFLICT_REQUIRES_CANONICALIZATION	Sources disagree and no final owner has been established.
REQUIRES_REPOSITORY_REVIEW	Necessary executable evidence has not yet been inspected.

Quality Dashboard — Portal Orientation and Information Architecture

Metadata	Value
Volume	4
Chapter ID	V04-P11-00
Subject	QualityDashboardPortal
Status	Generated First-Draft Architecture Skeleton - Domain-Specific Expansion Required
Content maturity	TEMPLATE_DERIVED_REFERENCE_SKELETON unless repository citations prove otherwise
Default implementation classification	REFERENCE_ARCHITECTURE / REQUIRES_REPOSITORY_REVIEW
Accountable owner	Portal Architecture / Quality Dashboard
Evidence rule	No implementation claim without inspected executable evidence
Repository	chinair88-prog/allinb2c

1. Executive Orientation

This chapter defines how GTOS shall **define personas, navigation, route ownership, domain dependencies and experience boundaries for quality managers, inspectors and auditors, covering inspection plans, evidence, defects, nonconformance, release, corrective actions.**

The specification separates reality, observations, knowledge, Decisions, Intent, execution, and outcomes. A component name, database row, UI label, AI answer, or workflow state does not acquire authority merely because it is visible or technically convenient.

Reality or external outcome

- ≠ Observation
- ≠ Claim
- ≠ derived Perspective
- ≠ Prediction
- ≠ Recommendation
- ≠ authorized Decision
- ≠ execution Intent

1.1 Accountable ownership

The accountable owner is **Portal Architecture / Quality Dashboard**. Supporting applications, shared infrastructure, integration adapters, analytics, and AI coordinate or present the capability but shall not silently own its authoritative propositions.

1.2 Scope

- create and identify the subject
- validate evidence and policy
- make authorized Decisions
- execute typed Commands
- publish completed-fact Events
- query current and historical perspectives
- correct and reconcile outcomes

1.3 Non-goals

- treating a registered Gradle module, catalog record, README, frontend route, migration plan, or generated report as proof of end-to-end implementation;
- direct cross-Domain database writes;
- generic status values that combine lifecycle, approval, provider, document, payment, dispute, and correction state;
- silent replacement of history;
- AI-created authority or fabricated external outcomes.

2. Ubiquitous Language and Subject Model

Subject	Required interpretation
QualityDashboardPortal	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit
QualityDashboardPortalVersion	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit
QualityDashboardPortalDecision	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit
QualityDashboardPortalEvidenceSet	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit
QualityDashboardPortalException	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit

Reference aggregate:

```
QualityDashboardPortal {
  subjectId
  tenantId
  organizationContext
  sourceIdentityRefs[]
  sourceVersionRefs[]
  lifecycleState
  relationshipRefs[]
  decisionRefs[]
  intentRefs[]
  evidenceSetRef
  knowledgeCutoff
  policyRefs[]
  authorityRef
  jurisdictionRefs[]
  createdAt
  effectiveAt
  updatedAt
  version
  correctionOf?
  correlationId
}
```

2.1 Core invariants

- Stable identity precedes relationship, state, and cross-system correlation.
- Effective time and recorded time remain distinct where business truth changes over time.
- Recommendation, Decision, Intent, execution, and outcome are separate concepts.
- No Portal, report, search index, cache, workflow, or AI Agent becomes a shadow owner of Domain truth.
- Binding submitted, approved, issued, accepted, or signed versions are immutable.
- Corrections append governed facts and preserve the original record.
- External authority and provider outcomes retain their source and qualification.
- Tenant and represented-principal context come from trusted authentication and mandate evaluation.
- Retried writes are idempotent and concurrency guarded.
- Outcome Unknown is explicit and reconciled before risky duplicate execution.

2.2 Required standards

- stable identifiers
- typed contracts
- immutable binding versions

- transactional outbox
- idempotent Commands
- explicit Outcome Unknown
- correction lineage
- machine-verifiable conformance

3. Actors, Roles, and Authority

A conformant design distinguishes:

- the natural person acting;
- the service or AI identity invoking a Tool;
- the organization or principal represented;
- the role or relationship granting context;
- the mandate or delegation granting action authority;
- the Policy and jurisdiction limiting the action;
- the reviewer or approver responsible for a binding Decision.

Authority is evaluated at action time. Authentication alone does not grant business authority. Cached permissions and browser-supplied tenant headers are insufficient for high-impact actions.

4. Lifecycle and State Model

State	Semantics
PROPOSED	Distinct governed condition with entry, exit, timeout, correction and authority semantics
VALIDATION_PENDING	Distinct governed condition with entry, exit, timeout, correction and authority semantics
APPROVAL_PENDING	Distinct governed condition with entry, exit, timeout, correction and authority semantics
ACTIVE	Distinct governed condition with entry, exit, timeout, correction and authority semantics
SUSPENDED	Distinct governed condition with entry, exit, timeout, correction and authority semantics
CORRECTION_PENDING	Distinct governed condition with entry, exit, timeout, correction and authority semantics
RETIRED	Distinct governed condition with entry, exit, timeout, correction and authority semantics

```
stateDiagram-v2
    [*] --> PROPOSED
    PROPOSED --> VALIDATION_PENDING
    VALIDATION_PENDING --> APPROVAL_PENDING
    APPROVAL_PENDING --> ACTIVE
    ACTIVE --> SUSPENDED
    SUSPENDED --> CORRECTION_PENDING
    CORRECTION_PENDING --> RETIRED
```

The diagram is a primary reading path. Real implementations may add parallel review, amendment, appeal, timeout, suspension, partial completion, reconciliation, correction, and terminal failure without collapsing their meaning.

4.1 Transition rules

- transition through a typed, authorized Command;
- require exact expected version where concurrent change matters;
- record actor, represented principal, mandate, Policy, reason, and Evidence;
- use an idempotency key for retried writes;
- publish a completed-fact Event after durable state change;
- expose Outcome Unknown for unresolved external completion;
- preserve original and corrected states in historical reconstruction.

5. Decision, Evidence, and Knowledge Cutoff

Reference Decision:

```
Decision {
  decisionId
  decisionType
  subjectRef
  sourceVersionRefs[]
  knowledgeCutoff
  evidenceSetRef
  policyVersionRefs[]
  recommendationRefs[]
  principalId
  representedOrganizationId
  mandateRef
  rationale
  outcome
  decidedAt
  effectiveAt
  correctionOf?
}
```

Evidence records identify issuer or observer, subject, version, observed time, received time, effective interval, integrity, confidence, qualification, contradiction, correction, retention, residency, and access class. A recommendation may assist the Decision but cannot promote itself to the Decision.

6. Commands, Events, Queries, and Contracts

Reference Commands:

- CreateQualityDashboardPortal
- ValidateQualityDashboardPortal
- ApproveQualityDashboardPortal
- ActivateQualityDashboardPortal
- SuspendQualityDashboardPortal
- CorrectQualityDashboardPortal
- RetireQualityDashboardPortal

Reference Events:

- QualityDashboardPortalCreated
- QualityDashboardPortalValidated
- QualityDashboardPortalApproved
- QualityDashboardPortalActivated
- QualityDashboardPortalSuspended
- QualityDashboardPortalCorrected
- QualityDashboardPortalRetired

Reference queries:

- GetQualityDashboardPortal
- ListQualityDashboardPortalRecords
- GetQualityDashboardPortalTimeline
- GetQualityDashboardPortalEvidence
- GetQualityDashboardPortalDecisionPackage
- GetQualityDashboardPortalExceptions
- GetQualityDashboardPortalAuditTrail

Reference API surface:

```
POST /api/v1/qualitydashboardportal/commands
GET  /api/v1/qualitydashboardportal/{id}
GET  /api/v1/qualitydashboardportal/{id}/timeline
GET  /api/v1/qualitydashboardportal/{id}/evidence
GET  /api/v1/qualitydashboardportal/{id}/decisions
POST /api/v1/qualitydashboardportal/{id}/exceptions
POST /api/v1/qualitydashboardportal/{id}/corrections
```

These endpoints are reference contracts, not claims that exact routes exist.

7. Workflow, Failure, and Compensation

flowchart TD

```
A[Validate identity version and authority] --> B[Collect required evidence]
B --> C{Policy and evidence gates pass?}
C -- No --> D[Open exception or request correction]
D --> B
C -- Yes --> E[Record Decision or execution Intent]
E --> F[Execute Domain command or external request]
F --> G{Outcome known?}
G -- Success --> H[Record fact and publish Event]
G -- Failure --> I[Record failure and compensation options]
G -- Unknown --> J[Enter Outcome Unknown]
J --> K[Query source or wait for verified callback]
K --> G
H --> L[Update projections and downstream workflow]
```

Representative failure modes:

- stale or wrong source version
- duplicate submission or replay
- external timeout after possible success
- contradictory source observations
- lost Event after committed state
- approval or mandate revoked during execution
- downstream action before a mandatory gate
- partial completion across multiple subjects
- evidence later retracted or corrected
- tenant, facility, channel or jurisdiction mismatch

Recovery shall query the authoritative source before duplicate execution, preserve partial success, use compensating Intent rather than destructive rewrite, publish corrections, quarantine high-impact ambiguity, and record affected downstream subjects.

8. Data and Persistence Architecture

Reference table families:

Table family	Purpose
qualitydashboardportal_aggregate	authoritative subject
qualitydashboardportal_version	immutable submitted, approved, issued, or signed versions
qualitydashboardportal_relationship	governed relationships
qualitydashboardportal_decision	binding Decisions and rationale
qualitydashboardportal_evidence_link	provenance and evidence relationships
qualitydashboardportal_event_outbox	transactional Event publication
qualitydashboardportal_idempotency	duplicate-write protection
qualitydashboardportal_exception	exception, claim, dispute, or hold
qualitydashboardportal_correction	correction and supersession lineage
qualitydashboardportal_audit	privileged action evidence

The owning service controls schema and migration. Cross-Domain references use stable identifiers or contracts. Analytics, reports, caches, search, and vector indexes remain projections. Backup, restore, retention, legal hold, privacy, residency, and decommissioning requirements are explicit.

9. Portal and Experience Requirements

- Quality Dashboard: primary experience for quality managers, inspectors and auditors.
- Operator and support views: diagnose failed or ambiguous journeys without assuming Domain ownership.
- Domain services: own authoritative data and action eligibility; the Portal consumes typed contracts.

Every Portal displays exact version, owner, state, freshness, required action, and uncertainty. It supports loading, empty, partial, stale, denied, error, timeout, and Outcome Unknown states; accessibility; locale, currency, unit, date, and RTL/LTR correctness; evidence audit; safe retry; and correction history.

10. AI Participation and Tool Governance

Permitted AI tasks:

- extract and classify evidence
- detect anomalies and missing fields
- summarize timelines and contradictions
- recommend next actions with sources and uncertainty

AI shall not own Domain records, grant itself authority, suppress contradictions, silently edit approved versions, fabricate external outcomes, or execute high-impact actions outside typed Tools, policy, approval, idempotency, sandbox, and outcome observation.

Every Agent Run records source context, prompt/model/tool versions, structured output, confidence and limitations, Policy result, approval, Tool calls, provider responses, final outcome, and recovery actions.

11. Security, Privacy, and Trust Boundaries

- least privilege and separation of duties
- tenant, organization, facility, channel and jurisdiction isolation
- integrity protection for binding evidence
- verified external callbacks and anti-replay controls

Additional controls include secret isolation, callback signature verification, audit of privileged action, emergency-access review, sensitive-data minimization, purpose limitation, and threat models for impersonation, tampering, replay, confused deputy, fraud, prompt injection, and exfiltration.

12. Reliability, SLOs, and Operations

SLI	Reference objective
authoritative read availability	99.9% monthly unless a stricter tier applies
acknowledged Command durability	no acknowledged write may be silently lost
Event publication	99.9% within five minutes after committed fact
duplicate prevention	100% for same tenant, Command class, and idempotency key
binding Decision audit completeness	100%
state-state detection	bounded by business deadline

Dashboards and runbooks cover backlog, error budget, dependency failure, retry budget, DLQ, workflow stall, provider outage, reconciliation, capacity, backup/restore, release/rollback, incident command, and post-incident correction.

13. Testing and Continuous Conformance

- aggregate invariant and transition tests
- authorization, delegation, separation-of-duties and tenant-isolation tests
- idempotency and optimistic-concurrency tests
- database migration, key, constraint and rollback tests
- contract, outbox/inbox, duplicate, replay and DLQ tests
- workflow restart, timeout and compensation tests
- Portal E2E tests for success, partial, stale, denied, error and Outcome Unknown states
- accessibility, locale, currency, unit and RTL/LTR tests
- security adversarial, fraud and data-exfiltration tests
- AI evaluation, prompt-injection, policy-bypass and unauthorized-tool tests
- historical reconstruction, correction and audit-completeness tests
- performance, capacity, recovery and operational exercise tests

Release evidence links each invariant and control to the test, environment, input data, result, owner, and artifact proving it. Generated test counts never replace semantic coverage.

14. Repository Review Boundary

- This chapter is a repository-review specification. Exact executable implementation has not been inspected for every target behavior.
- Registered modules, catalog entries, README claims, frontend contracts, or plans are not proof of complete implementation.

Area	Classification
target aggregate, API, tables, state and workflow in this chapter	REFERENCE_ARCHITECTURE
registered module or catalog claim	DOCUMENTATION_ONLY_CLAIM until source inspection
uninspected integration	REQUIRES_REPOSITORY_REVIEW
behavior proven in another repository-grounded chapter	retain that chapter's evidence and classification
contradictory ownership or path claims	CONFLICT_REQUIRES_CANONICALIZATION

No statement upgrades implementation status merely because a file, directory, module name, frontend contract, database entry, plan, or report exists.

15. Worked Conformance Scenario

An authorized principal initiates a Command against an exact subject version. The service validates identity, tenant, mandate, Policy, Evidence, and idempotency. It records the state transition and outbox entry atomically. If an external dependency participates, timeout produces Outcome Unknown; reconciliation queries the source or waits for a verified callback instead of repeating the action blindly.

Portals show source, freshness, version, required action, and uncertainty. AI may extract, compare, summarize, detect anomalies, and recommend through typed Tools, but cannot own the subject or fabricate success. Later correction appends new facts, identifies affected projections and workflows, and preserves the historical Decision context.

16. Conformance Checklist

- ☐ stable identity and proposition ownership are explicit;
- ☐ authority and mandate are evaluated at action time;
- ☐ state, Recommendation, Decision, Intent, execution, and outcome remain distinct;
- ☐ Commands are typed, authorized, idempotent, and version guarded;
- ☐ Events describe completed facts;
- ☐ Evidence includes provenance, time, integrity, qualification, and correction;
- ☐ external outcomes retain their authority source;
- ☐ Portals show freshness and uncertainty;
- ☐ AI is bounded by typed Tools, Policy, approval, and outcome observation;
- ☐ security, tenant, facility, channel, and jurisdiction boundaries are enforced;
- ☐ Outcome Unknown and reconciliation exist where needed;
- ☐ corrections preserve history;
- ☐ tests prove invariants and recovery;
- ☐ implementation status is not upgraded without executable evidence.

17. Status Vocabulary

Status	Meaning
VERIFIED_IMPLEMENTED	Executable source and relevant behavior were inspected. Executable behavior exists with a material governance or completeness gap.
IMPLEMENTED_WITH_GAP	
PARTIAL_IMPLEMENTATION	Only part of the target capability is evidenced.
REFERENCE_ARCHITECTURE	Normative target behavior; no claim that it exists today.
PLANNED_NOT_IMPLEMENTED	Explicitly planned but not evidenced as executable.
DOCUMENTATION_ONLY_CLAIM	Documentation or client contract claims behavior without verified backend evidence.
CONFLICT_REQUIRES_CANONICALIZATION	Sources disagree and no final owner has been established.
REQUIRES_REPOSITORY_REVIEW	Necessary executable evidence has not yet been inspected.

Quality Dashboard — Routes, Pages, Components, and BFF Contracts

Metadata	Value
Volume	4
Chapter ID	V04-P11-01
Subject	QualityDashboardRouteRegistry
Status	Generated First-Draft Architecture Skeleton - Domain-Specific Expansion Required
Content maturity	TEMPLATE_DERIVED_REFERENCE_SKELETON unless repository citations prove otherwise
Default implementation classification	REFERENCE_ARCHITECTURE / REQUIRES_REPOSITORY_REVIEW
Accountable owner	Portal Architecture / Quality Dashboard
Evidence rule	No implementation claim without inspected executable evidence
Repository	chinair88-prog/allinb2c

1. Executive Orientation

This chapter defines how GTOS shall **inventory routes, layouts, pages, components, server/client boundaries, BFFs, APIs, realtime channels and ownership for quality managers, inspectors and auditors, covering inspection plans, evidence, defects, nonconformance, release, corrective actions.**

The specification separates reality, observations, knowledge, Decisions, Intent, execution, and outcomes. A component name, database row, UI label, AI answer, or workflow state does not acquire authority merely because it is visible or technically convenient.

Reality or external outcome

- ≠ Observation
- ≠ Claim
- ≠ derived Perspective
- ≠ Prediction
- ≠ Recommendation
- ≠ authorized Decision
- ≠ execution Intent

1.1 Accountable ownership

The accountable owner is **Portal Architecture / Quality Dashboard**. Supporting applications, shared infrastructure, integration adapters, analytics, and AI coordinate or present the capability but shall not silently own its authoritative propositions.

1.2 Scope

- create and identify the subject
- validate evidence and policy
- make authorized Decisions
- execute typed Commands
- publish completed-fact Events
- query current and historical perspectives
- correct and reconcile outcomes

1.3 Non-goals

- treating a registered Gradle module, catalog record, README, frontend route, migration plan, or generated report as proof of end-to-end implementation;
- direct cross-Domain database writes;
- generic status values that combine lifecycle, approval, provider, document, payment, dispute, and correction state;
- silent replacement of history;
- AI-created authority or fabricated external outcomes.

2. Ubiquitous Language and Subject Model

Subject	Required interpretation
QualityDashboardRouteRegistry	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit
QualityDashboardRouteRegistryVersion	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit
QualityDashboardRouteRegistryDecision	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit
QualityDashboardRouteRegistryEvidenceSet	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit
QualityDashboardRouteRegistryException	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit

Reference aggregate:

```
QualityDashboardRouteRegistry {
  subjectId
  tenantId
  organizationContext
  sourceIdentityRefs[]
  sourceVersionRefs[]
  lifecycleState
  relationshipRefs[]
  decisionRefs[]
  intentRefs[]
  evidenceSetRef
  knowledgeCutoff
  policyRefs[]
  authorityRef
  jurisdictionRefs[]
  createdAt
  effectiveAt
  updatedAt
  version
  correctionOf?
  correlationId
}
```

2.1 Core invariants

- Stable identity precedes relationship, state, and cross-system correlation.
- Effective time and recorded time remain distinct where business truth changes over time.
- Recommendation, Decision, Intent, execution, and outcome are separate concepts.
- No Portal, report, search index, cache, workflow, or AI Agent becomes a shadow owner of Domain truth.
- Binding submitted, approved, issued, accepted, or signed versions are immutable.
- Corrections append governed facts and preserve the original record.
- External authority and provider outcomes retain their source and qualification.
- Tenant and represented-principal context come from trusted authentication and mandate evaluation.
- Retried writes are idempotent and concurrency guarded.
- Outcome Unknown is explicit and reconciled before risky duplicate execution.

2.2 Required standards

- stable identifiers
- typed contracts
- immutable binding versions

- transactional outbox
- idempotent Commands
- explicit Outcome Unknown
- correction lineage
- machine-verifiable conformance

3. Actors, Roles, and Authority

A conformant design distinguishes:

- the natural person acting;
- the service or AI identity invoking a Tool;
- the organization or principal represented;
- the role or relationship granting context;
- the mandate or delegation granting action authority;
- the Policy and jurisdiction limiting the action;
- the reviewer or approver responsible for a binding Decision.

Authority is evaluated at action time. Authentication alone does not grant business authority. Cached permissions and browser-supplied tenant headers are insufficient for high-impact actions.

4. Lifecycle and State Model

State	Semantics
PROPOSED	Distinct governed condition with entry, exit, timeout, correction and authority semantics
VALIDATION_PENDING	Distinct governed condition with entry, exit, timeout, correction and authority semantics
APPROVAL_PENDING	Distinct governed condition with entry, exit, timeout, correction and authority semantics
ACTIVE	Distinct governed condition with entry, exit, timeout, correction and authority semantics
SUSPENDED	Distinct governed condition with entry, exit, timeout, correction and authority semantics
CORRECTION_PENDING	Distinct governed condition with entry, exit, timeout, correction and authority semantics
RETIRED	Distinct governed condition with entry, exit, timeout, correction and authority semantics

```
stateDiagram-v2
    [*] --> PROPOSED
    PROPOSED --> VALIDATION_PENDING
    VALIDATION_PENDING --> APPROVAL_PENDING
    APPROVAL_PENDING --> ACTIVE
    ACTIVE --> SUSPENDED
    SUSPENDED --> CORRECTION_PENDING
    CORRECTION_PENDING --> RETIRED
```

The diagram is a primary reading path. Real implementations may add parallel review, amendment, appeal, timeout, suspension, partial completion, reconciliation, correction, and terminal failure without collapsing their meaning.

4.1 Transition rules

- transition through a typed, authorized Command;
- require exact expected version where concurrent change matters;
- record actor, represented principal, mandate, Policy, reason, and Evidence;
- use an idempotency key for retried writes;
- publish a completed-fact Event after durable state change;
- expose Outcome Unknown for unresolved external completion;
- preserve original and corrected states in historical reconstruction.

5. Decision, Evidence, and Knowledge Cutoff

Reference Decision:

```
Decision {
  decisionId
  decisionType
  subjectRef
  sourceVersionRefs[]
  knowledgeCutoff
  evidenceSetRef
  policyVersionRefs[]
  recommendationRefs[]
  principalId
  representedOrganizationId
  mandateRef
  rationale
  outcome
  decidedAt
  effectiveAt
  correctionOf?
}
```

Evidence records identify issuer or observer, subject, version, observed time, received time, effective interval, integrity, confidence, qualification, contradiction, correction, retention, residency, and access class. A recommendation may assist the Decision but cannot promote itself to the Decision.

6. Commands, Events, Queries, and Contracts

Reference Commands:

- CreateQualityDashboardRouteRegistry
- ValidateQualityDashboardRouteRegistry
- ApproveQualityDashboardRouteRegistry
- ActivateQualityDashboardRouteRegistry
- SuspendQualityDashboardRouteRegistry
- CorrectQualityDashboardRouteRegistry
- RetireQualityDashboardRouteRegistry

Reference Events:

- QualityDashboardRouteRegistryCreated
- QualityDashboardRouteRegistryValidated
- QualityDashboardRouteRegistryApproved
- QualityDashboardRouteRegistryActivated
- QualityDashboardRouteRegistrySuspended
- QualityDashboardRouteRegistryCorrected
- QualityDashboardRouteRegistryRetired

Reference queries:

- GetQualityDashboardRouteRegistry
- ListQualityDashboardRouteRegistryRecords
- GetQualityDashboardRouteRegistryTimeline
- GetQualityDashboardRouteRegistryEvidence
- GetQualityDashboardRouteRegistryDecisionPackage
- GetQualityDashboardRouteRegistryExceptions
- GetQualityDashboardRouteRegistryAuditTrail

Reference API surface:

```
POST /api/v1/qualitydashboardrouterregistry/commands
GET  /api/v1/qualitydashboardrouterregistry/{id}
GET  /api/v1/qualitydashboardrouterregistry/{id}/timeline
GET  /api/v1/qualitydashboardrouterregistry/{id}/evidence
GET  /api/v1/qualitydashboardrouterregistry/{id}/decisions
POST /api/v1/qualitydashboardrouterregistry/{id}/exceptions
POST /api/v1/qualitydashboardrouterregistry/{id}/corrections
```

These endpoints are reference contracts, not claims that exact routes exist.

7. Workflow, Failure, and Compensation

```
flowchart TD
    A[Validate identity version and authority] --> B[Collect required evidence]
    B --> C{Policy and evidence gates pass?}
    C -- No --> D[Open exception or request correction]
    D --> B
    C -- Yes --> E[Record Decision or execution Intent]
    E --> F[Execute Domain command or external request]
    F --> G{Outcome known?}
    G -- Success --> H[Record fact and publish Event]
    G -- Failure --> I[Record failure and compensation options]
    G -- Unknown --> J[Enter Outcome Unknown]
    J --> K[Query source or wait for verified callback]
    K --> G
    H --> L[Update projections and downstream workflow]
```

Representative failure modes:

- stale or wrong source version
- duplicate submission or replay
- external timeout after possible success
- contradictory source observations
- lost Event after committed state
- approval or mandate revoked during execution
- downstream action before a mandatory gate
- partial completion across multiple subjects
- evidence later retracted or corrected
- tenant, facility, channel or jurisdiction mismatch

Recovery shall query the authoritative source before duplicate execution, preserve partial success, use compensating Intent rather than destructive rewrite, publish corrections, quarantine high-impact ambiguity, and record affected downstream subjects.

8. Data and Persistence Architecture

Reference table families:

Table family	Purpose
qualitydashboardrouterregistry_aggregate	authoritative subject
qualitydashboardrouterregistry_version	immutable submitted, approved, issued, or signed versions
qualitydashboardrouterregistry_relationship	governed relationships
qualitydashboardrouterregistry_decision	binding Decisions and rationale
qualitydashboardrouterregistry_evidence_link	provenance and evidence relationships
qualitydashboardrouterregistry_event_outbox	transactional Event publication
qualitydashboardrouterregistry_idempotency	duplicate-write protection
qualitydashboardrouterregistry_exception	exception, claim, dispute, or hold
qualitydashboardrouterregistry_correction	correction and supersession lineage
qualitydashboardrouterregistry_audit	privileged action evidence

The owning service controls schema and migration. Cross-Domain references use stable identifiers or contracts. Analytics, reports, caches, search, and vector indexes remain projections. Backup, restore, retention, legal hold, privacy, residency, and decommissioning requirements are explicit.

9. Portal and Experience Requirements

- Quality Dashboard: primary experience for quality managers, inspectors and auditors.
- Operator and support views: diagnose failed or ambiguous journeys without assuming Domain ownership.
- Domain services: own authoritative data and action eligibility; the Portal consumes typed contracts.

Every Portal displays exact version, owner, state, freshness, required action, and uncertainty. It supports loading, empty, partial, stale, denied, error, timeout, and Outcome Unknown states; accessibility; locale, currency, unit, date, and RTL/LTR correctness; evidence audit; safe retry; and correction history.

10. AI Participation and Tool Governance

Permitted AI tasks:

- extract and classify evidence
- detect anomalies and missing fields
- summarize timelines and contradictions
- recommend next actions with sources and uncertainty

AI shall not own Domain records, grant itself authority, suppress contradictions, silently edit approved versions, fabricate external outcomes, or execute high-impact actions outside typed Tools, policy, approval, idempotency, sandbox, and outcome observation.

Every Agent Run records source context, prompt/model/tool versions, structured output, confidence and limitations, Policy result, approval, Tool calls, provider responses, final outcome, and recovery actions.

11. Security, Privacy, and Trust Boundaries

- least privilege and separation of duties
- tenant, organization, facility, channel and jurisdiction isolation
- integrity protection for binding evidence
- verified external callbacks and anti-replay controls

Additional controls include secret isolation, callback signature verification, audit of privileged action, emergency-access review, sensitive-data minimization, purpose limitation, and threat models for impersonation, tampering, replay, confused deputy, fraud, prompt injection, and exfiltration.

12. Reliability, SLOs, and Operations

SLI	Reference objective
authoritative read availability	99.9% monthly unless a stricter tier applies
acknowledged Command durability	no acknowledged write may be silently lost
Event publication	99.9% within five minutes after committed fact
duplicate prevention	100% for same tenant, Command class, and idempotency key
binding Decision audit completeness	100%
state-state detection	bounded by business deadline

Dashboards and runbooks cover backlog, error budget, dependency failure, retry budget, DLQ, workflow stall, provider outage, reconciliation, capacity, backup/restore, release/rollback, incident command, and post-incident correction.

13. Testing and Continuous Conformance

- aggregate invariant and transition tests
- authorization, delegation, separation-of-duties and tenant-isolation tests
- idempotency and optimistic-concurrency tests
- database migration, key, constraint and rollback tests
- contract, outbox/inbox, duplicate, replay and DLQ tests
- workflow restart, timeout and compensation tests
- Portal E2E tests for success, partial, stale, denied, error and Outcome Unknown states
- accessibility, locale, currency, unit and RTL/LTR tests
- security adversarial, fraud and data-exfiltration tests
- AI evaluation, prompt-injection, policy-bypass and unauthorized-tool tests
- historical reconstruction, correction and audit-completeness tests
- performance, capacity, recovery and operational exercise tests

Release evidence links each invariant and control to the test, environment, input data, result, owner, and artifact proving it. Generated test counts never replace semantic coverage.

14. Repository Review Boundary

- This chapter is a repository-review specification. Exact executable implementation has not been inspected for every target behavior.
- Registered modules, catalog entries, README claims, frontend contracts, or plans are not proof of complete implementation.

Area	Classification
target aggregate, API, tables, state and workflow in this chapter	REFERENCE_ARCHITECTURE
registered module or catalog claim	DOCUMENTATION_ONLY_CLAIM until source inspection
uninspected integration	REQUIRES_REPOSITORY_REVIEW
behavior proven in another repository-grounded chapter	retain that chapter's evidence and classification
contradictory ownership or path claims	CONFLICT_REQUIRES_CANONICALIZATION

No statement upgrades implementation status merely because a file, directory, module name, frontend contract, database entry, plan, or report exists.

15. Worked Conformance Scenario

An authorized principal initiates a Command against an exact subject version. The service validates identity, tenant, mandate, Policy, Evidence, and idempotency. It records the state transition and outbox entry atomically. If an external dependency participates, timeout produces Outcome Unknown; reconciliation queries the source or waits for a verified callback instead of repeating the action blindly.

Portals show source, freshness, version, required action, and uncertainty. AI may extract, compare, summarize, detect anomalies, and recommend through typed Tools, but cannot own the subject or fabricate success. Later correction appends new facts, identifies affected projections and workflows, and preserves the historical Decision context.

16. Conformance Checklist

- ☐ stable identity and proposition ownership are explicit;
- ☐ authority and mandate are evaluated at action time;
- ☐ state, Recommendation, Decision, Intent, execution, and outcome remain distinct;
- ☐ Commands are typed, authorized, idempotent, and version guarded;
- ☐ Events describe completed facts;
- ☐ Evidence includes provenance, time, integrity, qualification, and correction;
- ☐ external outcomes retain their authority source;
- ☐ Portals show freshness and uncertainty;
- ☐ AI is bounded by typed Tools, Policy, approval, and outcome observation;
- ☐ security, tenant, facility, channel, and jurisdiction boundaries are enforced;
- ☐ Outcome Unknown and reconciliation exist where needed;
- ☐ corrections preserve history;
- ☐ tests prove invariants and recovery;
- ☐ implementation status is not upgraded without executable evidence.

17. Status Vocabulary

Status	Meaning
VERIFIED_IMPLEMENTED	Executable source and relevant behavior were inspected.
IMPLEMENTED_WITH_GAP	Executable behavior exists with a material governance or completeness gap.
PARTIAL_IMPLEMENTATION	Only part of the target capability is evidenced.
REFERENCE_ARCHITECTURE	Normative target behavior; no claim that it exists today.
PLANNED_NOT_IMPLEMENTED	Explicitly planned but not evidenced as executable.
DOCUMENTATION_ONLY_CLAIM	Documentation or client contract claims behavior without verified backend evidence.
CONFLICT_REQUIRES_CANONICALIZATION	Sources disagree and no final owner has been established.
REQUIRES_REPOSITORY_REVIEW	Necessary executable evidence has not yet been inspected.

Quality Dashboard — Identity, Session, Authorization, and Trust Boundaries

Metadata	Value
Volume	4
Chapter ID	V04-P11-02
Subject	QualityDashboardAccessModel
Status	Generated First-Draft Architecture Skeleton - Domain-Specific Expansion Required
Content maturity	TEMPLATE_DERIVED_REFERENCE_SKELETON unless repository citations prove otherwise
Default implementation classification	REFERENCE_ARCHITECTURE / REQUIRES_REPOSITORY_REVIEW
Accountable owner	Portal Architecture / Quality Dashboard
Evidence rule	No implementation claim without inspected executable evidence
Repository	chinair88-prog/allinb2c

1. Executive Orientation

This chapter defines how GTOS shall **govern login, session, role, relationship, tenant, facility, channel, delegation, impersonation and privileged action for quality managers, inspectors and auditors, covering inspection plans, evidence, defects, nonconformance, release, corrective actions.**

The specification separates reality, observations, knowledge, Decisions, Intent, execution, and outcomes. A component name, database row, UI label, AI answer, or workflow state does not acquire authority merely because it is visible or technically convenient.

Reality or external outcome

- ≠ Observation
- ≠ Claim
- ≠ derived Perspective
- ≠ Prediction
- ≠ Recommendation
- ≠ authorized Decision
- ≠ execution Intent

1.1 Accountable ownership

The accountable owner is **Portal Architecture / Quality Dashboard**. Supporting applications, shared infrastructure, integration adapters, analytics, and AI coordinate or present the capability but shall not silently own its authoritative propositions.

1.2 Scope

- create and identify the subject
- validate evidence and policy
- make authorized Decisions
- execute typed Commands
- publish completed-fact Events
- query current and historical perspectives
- correct and reconcile outcomes

1.3 Non-goals

- treating a registered Gradle module, catalog record, README, frontend route, migration plan, or generated report as proof of end-to-end implementation;
- direct cross-Domain database writes;
- generic status values that combine lifecycle, approval, provider, document, payment, dispute, and correction state;
- silent replacement of history;
- AI-created authority or fabricated external outcomes.

2. Ubiquitous Language and Subject Model

Subject	Required interpretation
QualityDashboardAccessModel	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit
QualityDashboardAccessModelVersion	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit
QualityDashboardAccessModelDecision	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit
QualityDashboardAccessModelEvidenceSet	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit
QualityDashboardAccessModelException	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit

Reference aggregate:

```
QualityDashboardAccessModel {
  subjectId
  tenantId
  organizationContext
  sourceIdentityRefs[]
  sourceVersionRefs[]
  lifecycleState
  relationshipRefs[]
  decisionRefs[]
  intentRefs[]
  evidenceSetRef
  knowledgeCutoff
  policyRefs[]
  authorityRef
  jurisdictionRefs[]
  createdAt
  effectiveAt
  updatedAt
  version
  correctionOf?
  correlationId
}
```

2.1 Core invariants

- Stable identity precedes relationship, state, and cross-system correlation.
- Effective time and recorded time remain distinct where business truth changes over time.
- Recommendation, Decision, Intent, execution, and outcome are separate concepts.
- No Portal, report, search index, cache, workflow, or AI Agent becomes a shadow owner of Domain truth.
- Binding submitted, approved, issued, accepted, or signed versions are immutable.
- Corrections append governed facts and preserve the original record.
- External authority and provider outcomes retain their source and qualification.
- Tenant and represented-principal context come from trusted authentication and mandate evaluation.
- Retried writes are idempotent and concurrency guarded.
- Outcome Unknown is explicit and reconciled before risky duplicate execution.

2.2 Required standards

- stable identifiers
- typed contracts
- immutable binding versions

- transactional outbox
- idempotent Commands
- explicit Outcome Unknown
- correction lineage
- machine-verifiable conformance

3. Actors, Roles, and Authority

- A conformant design distinguishes:
- the natural person acting;
 - the service or AI identity invoking a Tool;
 - the organization or principal represented;
 - the role or relationship granting context;
 - the mandate or delegation granting action authority;
 - the Policy and jurisdiction limiting the action;
 - the reviewer or approver responsible for a binding Decision.

Authority is evaluated at action time. Authentication alone does not grant business authority. Cached permissions and browser-supplied tenant headers are insufficient for high-impact actions.

4. Lifecycle and State Model

State	Semantics
PROPOSED	Distinct governed condition with entry, exit, timeout, correction and authority semantics
VALIDATION_PENDING	Distinct governed condition with entry, exit, timeout, correction and authority semantics
APPROVAL_PENDING	Distinct governed condition with entry, exit, timeout, correction and authority semantics
ACTIVE	Distinct governed condition with entry, exit, timeout, correction and authority semantics
SUSPENDED	Distinct governed condition with entry, exit, timeout, correction and authority semantics
CORRECTION_PENDING	Distinct governed condition with entry, exit, timeout, correction and authority semantics
RETIRED	Distinct governed condition with entry, exit, timeout, correction and authority semantics

```
stateDiagram-v2
    [*] --> PROPOSED
    PROPOSED --> VALIDATION_PENDING
    VALIDATION_PENDING --> APPROVAL_PENDING
    APPROVAL_PENDING --> ACTIVE
    ACTIVE --> SUSPENDED
    SUSPENDED --> CORRECTION_PENDING
    CORRECTION_PENDING --> RETIRED
```

The diagram is a primary reading path. Real implementations may add parallel review, amendment, appeal, timeout, suspension, partial completion, reconciliation, correction, and terminal failure without collapsing their meaning.

4.1 Transition rules

- transition through a typed, authorized Command;
- require exact expected version where concurrent change matters;
- record actor, represented principal, mandate, Policy, reason, and Evidence;
- use an idempotency key for retried writes;
- publish a completed-fact Event after durable state change;
- expose Outcome Unknown for unresolved external completion;
- preserve original and corrected states in historical reconstruction.

5. Decision, Evidence, and Knowledge Cutoff

Reference Decision:

```
Decision {
  decisionId
  decisionType
  subjectRef
  sourceVersionRefs[]
  knowledgeCutoff
  evidenceSetRef
  policyVersionRefs[]
  recommendationRefs[]
  principalId
  representedOrganizationId
  mandateRef
  rationale
  outcome
  decidedAt
  effectiveAt
  correctionOf?
}
```

Evidence records identify issuer or observer, subject, version, observed time, received time, effective interval, integrity, confidence, qualification, contradiction, correction, retention, residency, and access class. A recommendation may assist the Decision but cannot promote itself to the Decision.

6. Commands, Events, Queries, and Contracts

Reference Commands:

- CreateQualityDashboardAccessModel
- ValidateQualityDashboardAccessModel
- ApproveQualityDashboardAccessModel
- ActivateQualityDashboardAccessModel
- SuspendQualityDashboardAccessModel
- CorrectQualityDashboardAccessModel
- RetireQualityDashboardAccessModel

Reference Events:

- QualityDashboardAccessModelCreated
- QualityDashboardAccessModelValidated
- QualityDashboardAccessModelApproved
- QualityDashboardAccessModelActivated
- QualityDashboardAccessModelSuspended
- QualityDashboardAccessModelCorrected
- QualityDashboardAccessModelRetired

Reference queries:

- GetQualityDashboardAccessModel
- ListQualityDashboardAccessModelRecords
- GetQualityDashboardAccessModelTimeline
- GetQualityDashboardAccessModelEvidence
- GetQualityDashboardAccessModelDecisionPackage
- GetQualityDashboardAccessModelExceptions
- GetQualityDashboardAccessModelAuditTrail

Reference API surface:

```
POST /api/v1/qualitydashboardaccessmodel/commands
GET  /api/v1/qualitydashboardaccessmodel/{id}
GET  /api/v1/qualitydashboardaccessmodel/{id}/timeline
GET  /api/v1/qualitydashboardaccessmodel/{id}/evidence
GET  /api/v1/qualitydashboardaccessmodel/{id}/decisions
POST /api/v1/qualitydashboardaccessmodel/{id}/exceptions
POST /api/v1/qualitydashboardaccessmodel/{id}/corrections
```

These endpoints are reference contracts, not claims that exact routes exist.

7. Workflow, Failure, and Compensation

```
flowchart TD
    A[Validate identity version and authority] --> B[Collect required evidence]
    B --> C{Policy and evidence gates pass?}
    C -- No --> D[Open exception or request correction]
    D --> B
    C -- Yes --> E[Record Decision or execution Intent]
    E --> F[Execute Domain command or external request]
    F --> G{Outcome known?}
    G -- Success --> H[Record fact and publish Event]
    G -- Failure --> I[Record failure and compensation options]
    G -- Unknown --> J[Enter Outcome Unknown]
    J --> K[Query source or wait for verified callback]
    K --> G
    H --> L[Update projections and downstream workflow]
```

Representative failure modes:

- stale or wrong source version
- duplicate submission or replay
- external timeout after possible success
- contradictory source observations
- lost Event after committed state
- approval or mandate revoked during execution
- downstream action before a mandatory gate
- partial completion across multiple subjects
- evidence later retracted or corrected
- tenant, facility, channel or jurisdiction mismatch

Recovery shall query the authoritative source before duplicate execution, preserve partial success, use compensating Intent rather than destructive rewrite, publish corrections, quarantine high-impact ambiguity, and record affected downstream subjects.

8. Data and Persistence Architecture

Reference table families:

Table family	Purpose
qualitydashboardaccessmodel_aggregate	authoritative subject
qualitydashboardaccessmodel_version	immutable submitted, approved, issued, or signed versions
qualitydashboardaccessmodel_relationship	governed relationships
qualitydashboardaccessmodel_decision	binding Decisions and rationale
qualitydashboardaccessmodel_evidence_link	provenance and evidence relationships
qualitydashboardaccessmodel_event_outbox	transactional Event publication
qualitydashboardaccessmodel_idempotency	duplicate-write protection
qualitydashboardaccessmodel_exception	exception, claim, dispute, or hold
qualitydashboardaccessmodel_correction	correction and supersession lineage
qualitydashboardaccessmodel_audit	privileged action evidence

The owning service controls schema and migration. Cross-Domain references use stable identifiers or contracts. Analytics, reports, caches, search, and vector indexes remain projections. Backup, restore, retention, legal hold, privacy, residency, and decommissioning requirements are explicit.

9. Portal and Experience Requirements

- Quality Dashboard: primary experience for quality managers, inspectors and auditors.
- Operator and support views: diagnose failed or ambiguous journeys without assuming Domain ownership.
- Domain services: own authoritative data and action eligibility; the Portal consumes typed contracts.

Every Portal displays exact version, owner, state, freshness, required action, and uncertainty. It supports loading, empty, partial, stale, denied, error, timeout, and Outcome Unknown states; accessibility; locale, currency, unit, date, and RTL/LTR correctness; evidence audit; safe retry; and correction history.

10. AI Participation and Tool Governance

Permitted AI tasks:

- extract and classify evidence
- detect anomalies and missing fields
- summarize timelines and contradictions
- recommend next actions with sources and uncertainty

AI shall not own Domain records, grant itself authority, suppress contradictions, silently edit approved versions, fabricate external outcomes, or execute high-impact actions outside typed Tools, policy, approval, idempotency, sandbox, and outcome observation.

Every Agent Run records source context, prompt/model/tool versions, structured output, confidence and limitations, Policy result, approval, Tool calls, provider responses, final outcome, and recovery actions.

11. Security, Privacy, and Trust Boundaries

- least privilege and separation of duties
- tenant, organization, facility, channel and jurisdiction isolation
- integrity protection for binding evidence
- verified external callbacks and anti-replay controls

Additional controls include secret isolation, callback signature verification, audit of privileged action, emergency-access review, sensitive-data minimization, purpose limitation, and threat models for impersonation, tampering, replay, confused deputy, fraud, prompt injection, and exfiltration.

12. Reliability, SLOs, and Operations

SLI	Reference objective
authoritative read availability	99.9% monthly unless a stricter tier applies
acknowledged Command durability	no acknowledged write may be silently lost
Event publication	99.9% within five minutes after committed fact
duplicate prevention	100% for same tenant, Command class, and idempotency key
binding Decision audit completeness	100%
state-state detection	bounded by business deadline

Dashboards and runbooks cover backlog, error budget, dependency failure, retry budget, DLQ, workflow stall, provider outage, reconciliation, capacity, backup/restore, release/rollback, incident command, and post-incident correction.

13. Testing and Continuous Conformance

- aggregate invariant and transition tests
- authorization, delegation, separation-of-duties and tenant-isolation tests
- idempotency and optimistic-concurrency tests
- database migration, key, constraint and rollback tests
- contract, outbox/inbox, duplicate, replay and DLQ tests
- workflow restart, timeout and compensation tests
- Portal E2E tests for success, partial, stale, denied, error and Outcome Unknown states
- accessibility, locale, currency, unit and RTL/LTR tests
- security adversarial, fraud and data-exfiltration tests
- AI evaluation, prompt-injection, policy-bypass and unauthorized-tool tests
- historical reconstruction, correction and audit-completeness tests
- performance, capacity, recovery and operational exercise tests

Release evidence links each invariant and control to the test, environment, input data, result, owner, and artifact proving it. Generated test counts never replace semantic coverage.

14. Repository Review Boundary

- This chapter is a repository-review specification. Exact executable implementation has not been inspected for every target behavior.
- Registered modules, catalog entries, README claims, frontend contracts, or plans are not proof of complete implementation.

Area	Classification
target aggregate, API, tables, state and workflow in this chapter	REFERENCE_ARCHITECTURE
registered module or catalog claim	DOCUMENTATION_ONLY_CLAIM until source inspection
uninspected integration	REQUIRES_REPOSITORY_REVIEW
behavior proven in another repository-grounded chapter	retain that chapter's evidence and classification
contradictory ownership or path claims	CONFLICT_REQUIRES_CANONICALIZATION

No statement upgrades implementation status merely because a file, directory, module name, frontend contract, database entry, plan, or report exists.

15. Worked Conformance Scenario

An authorized principal initiates a Command against an exact subject version. The service validates identity, tenant, mandate, Policy, Evidence, and idempotency. It records the state transition and outbox entry atomically. If an external dependency participates, timeout produces Outcome Unknown; reconciliation queries the source or waits for a verified callback instead of repeating the action blindly.

Portals show source, freshness, version, required action, and uncertainty. AI may extract, compare, summarize, detect anomalies, and recommend through typed Tools, but cannot own the subject or fabricate success. Later correction appends new facts, identifies affected projections and workflows, and preserves the historical Decision context.

16. Conformance Checklist

- ☐ stable identity and proposition ownership are explicit;
- ☐ authority and mandate are evaluated at action time;
- ☐ state, Recommendation, Decision, Intent, execution, and outcome remain distinct;
- ☐ Commands are typed, authorized, idempotent, and version guarded;
- ☐ Events describe completed facts;
- ☐ Evidence includes provenance, time, integrity, qualification, and correction;
- ☐ external outcomes retain their authority source;
- ☐ Portals show freshness and uncertainty;
- ☐ AI is bounded by typed Tools, Policy, approval, and outcome observation;
- ☐ security, tenant, facility, channel, and jurisdiction boundaries are enforced;
- ☐ Outcome Unknown and reconciliation exist where needed;
- ☐ corrections preserve history;
- ☐ tests prove invariants and recovery;
- ☐ implementation status is not upgraded without executable evidence.

17. Status Vocabulary

Status	Meaning
VERIFIED_IMPLEMENTED	Executable source and relevant behavior were inspected. Executable behavior exists with a material governance or completeness gap.
IMPLEMENTED_WITH_GAP	
PARTIAL_IMPLEMENTATION	Only part of the target capability is evidenced.
REFERENCE_ARCHITECTURE	Normative target behavior; no claim that it exists today.
PLANNED_NOT_IMPLEMENTED	Explicitly planned but not evidenced as executable.
DOCUMENTATION_ONLY_CLAIM	Documentation or client contract claims behavior without verified backend evidence.
CONFLICT_REQUIRES_CANONICALIZATION	Sources disagree and no final owner has been established.
REQUIRES_REPOSITORY_REVIEW	Necessary executable evidence has not yet been inspected.

Quality Dashboard — UX States, Accessibility, Localization, Analytics, and E2E

Metadata	Value
Volume	4
Chapter ID	V04-P11-03
Subject	QualityDashboardExperienceStandard
Status	Generated First-Draft Architecture Skeleton - Domain-Specific Expansion Required
Content maturity	TEMPLATE_DERIVED_REFERENCE_SKELETON unless repository citations prove otherwise
Default implementation classification	REFERENCE_ARCHITECTURE / REQUIRES_REPOSITORY_REVIEW
Accountable owner	Portal Architecture / Quality Dashboard
Evidence rule	No implementation claim without inspected executable evidence
Repository	chinair88-prog/allinb2c

1. Executive Orientation

This chapter defines how GTOS shall **specify loading, empty, partial, stale, error, denied, offline, accessibility, RTL/LTR, analytics, audit and test journeys for quality managers, inspectors and auditors, covering inspection plans, evidence, defects, nonconformance, release, corrective actions.**

The specification separates reality, observations, knowledge, Decisions, Intent, execution, and outcomes. A component name, database row, UI label, AI answer, or workflow state does not acquire authority merely because it is visible or technically convenient.

Reality or external outcome

- ≠ Observation
- ≠ Claim
- ≠ derived Perspective
- ≠ Prediction
- ≠ Recommendation
- ≠ authorized Decision
- ≠ execution Intent

1.1 Accountable ownership

The accountable owner is **Portal Architecture / Quality Dashboard**. Supporting applications, shared infrastructure, integration adapters, analytics, and AI coordinate or present the capability but shall not silently own its authoritative propositions.

1.2 Scope

- create and identify the subject
- validate evidence and policy
- make authorized Decisions
- execute typed Commands
- publish completed-fact Events
- query current and historical perspectives
- correct and reconcile outcomes

1.3 Non-goals

- treating a registered Gradle module, catalog record, README, frontend route, migration plan, or generated report as proof of end-to-end implementation;
- direct cross-Domain database writes;
- generic status values that combine lifecycle, approval, provider, document, payment, dispute, and correction state;
- silent replacement of history;
- AI-created authority or fabricated external outcomes.

2. Ubiquitous Language and Subject Model

Subject	Required interpretation
QualityDashboardExperienceStandard	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit
QualityDashboardExperienceStandardVersion	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit
QualityDashboardExperienceStandardDecision	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit
QualityDashboardExperienceStandardEvidenceSet	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit
QualityDashboardExperienceStandardException	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit

Reference aggregate:

```
QualityDashboardExperienceStandard {
  subjectId
  tenantId
  organizationContext
  sourceIdentityRefs[]
  sourceVersionRefs[]
  lifecycleState
  relationshipRefs[]
  decisionRefs[]
  intentRefs[]
  evidenceSetRef
  knowledgeCutoff
  policyRefs[]
  authorityRef
  jurisdictionRefs[]
  createdAt
  effectiveAt
  updatedAt
  version
  correctionOf?
  correlationId
}
```

2.1 Core invariants

- Stable identity precedes relationship, state, and cross-system correlation.
- Effective time and recorded time remain distinct where business truth changes over time.
- Recommendation, Decision, Intent, execution, and outcome are separate concepts.
- No Portal, report, search index, cache, workflow, or AI Agent becomes a shadow owner of Domain truth.
- Binding submitted, approved, issued, accepted, or signed versions are immutable.
- Corrections append governed facts and preserve the original record.
- External authority and provider outcomes retain their source and qualification.
- Tenant and represented-principal context come from trusted authentication and mandate evaluation.
- Retried writes are idempotent and concurrency guarded.
- Outcome Unknown is explicit and reconciled before risky duplicate execution.

2.2 Required standards

- stable identifiers
- typed contracts
- immutable binding versions

- transactional outbox
- idempotent Commands
- explicit Outcome Unknown
- correction lineage
- machine-verifiable conformance

3. Actors, Roles, and Authority

A conformant design distinguishes:

- the natural person acting;
- the service or AI identity invoking a Tool;
- the organization or principal represented;
- the role or relationship granting context;
- the mandate or delegation granting action authority;
- the Policy and jurisdiction limiting the action;
- the reviewer or approver responsible for a binding Decision.

Authority is evaluated at action time. Authentication alone does not grant business authority. Cached permissions and browser-supplied tenant headers are insufficient for high-impact actions.

4. Lifecycle and State Model

State	Semantics
PROPOSED	Distinct governed condition with entry, exit, timeout, correction and authority semantics
VALIDATION_PENDING	Distinct governed condition with entry, exit, timeout, correction and authority semantics
APPROVAL_PENDING	Distinct governed condition with entry, exit, timeout, correction and authority semantics
ACTIVE	Distinct governed condition with entry, exit, timeout, correction and authority semantics
SUSPENDED	Distinct governed condition with entry, exit, timeout, correction and authority semantics
CORRECTION_PENDING	Distinct governed condition with entry, exit, timeout, correction and authority semantics
RETIRED	Distinct governed condition with entry, exit, timeout, correction and authority semantics

```
stateDiagram-v2
    [*] --> PROPOSED
    PROPOSED --> VALIDATION_PENDING
    VALIDATION_PENDING --> APPROVAL_PENDING
    APPROVAL_PENDING --> ACTIVE
    ACTIVE --> SUSPENDED
    SUSPENDED --> CORRECTION_PENDING
    CORRECTION_PENDING --> RETIRED
```

The diagram is a primary reading path. Real implementations may add parallel review, amendment, appeal, timeout, suspension, partial completion, reconciliation, correction, and terminal failure without collapsing their meaning.

4.1 Transition rules

- transition through a typed, authorized Command;
- require exact expected version where concurrent change matters;
- record actor, represented principal, mandate, Policy, reason, and Evidence;
- use an idempotency key for retried writes;
- publish a completed-fact Event after durable state change;
- expose Outcome Unknown for unresolved external completion;
- preserve original and corrected states in historical reconstruction.

5. Decision, Evidence, and Knowledge Cutoff

Reference Decision:

```
Decision {
  decisionId
  decisionType
  subjectRef
  sourceVersionRefs[]
  knowledgeCutoff
  evidenceSetRef
  policyVersionRefs[]
  recommendationRefs[]
  principalId
  representedOrganizationId
  mandateRef
  rationale
  outcome
  decidedAt
  effectiveAt
  correctionOf?
}
```

Evidence records identify issuer or observer, subject, version, observed time, received time, effective interval, integrity, confidence, qualification, contradiction, correction, retention, residency, and access class. A recommendation may assist the Decision but cannot promote itself to the Decision.

6. Commands, Events, Queries, and Contracts

Reference Commands:

- CreateQualityDashboardExperienceStandard
- ValidateQualityDashboardExperienceStandard
- ApproveQualityDashboardExperienceStandard
- ActivateQualityDashboardExperienceStandard
- SuspendQualityDashboardExperienceStandard
- CorrectQualityDashboardExperienceStandard
- RetireQualityDashboardExperienceStandard

Reference Events:

- QualityDashboardExperienceStandardCreated
- QualityDashboardExperienceStandardValidated
- QualityDashboardExperienceStandardApproved
- QualityDashboardExperienceStandardActivated
- QualityDashboardExperienceStandardSuspended
- QualityDashboardExperienceStandardCorrected
- QualityDashboardExperienceStandardRetired

Reference queries:

- GetQualityDashboardExperienceStandard
- ListQualityDashboardExperienceStandardRecords
- GetQualityDashboardExperienceStandardTimeline
- GetQualityDashboardExperienceStandardEvidence
- GetQualityDashboardExperienceStandardDecisionPackage
- GetQualityDashboardExperienceStandardExceptions
- GetQualityDashboardExperienceStandardAuditTrail

Reference API surface:

```
POST /api/v1/qualitydashboardexperiencestandard/commands
GET  /api/v1/qualitydashboardexperiencestandard/{id}
GET  /api/v1/qualitydashboardexperiencestandard/{id}/timeline
GET  /api/v1/qualitydashboardexperiencestandard/{id}/evidence
GET  /api/v1/qualitydashboardexperiencestandard/{id}/decisions
POST /api/v1/qualitydashboardexperiencestandard/{id}/exceptions
POST /api/v1/qualitydashboardexperiencestandard/{id}/corrections
```

These endpoints are reference contracts, not claims that exact routes exist.

7. Workflow, Failure, and Compensation

flowchart TD

```
A[Validate identity version and authority] --> B[Collect required evidence]
B --> C{Policy and evidence gates pass?}
C -- No --> D[Open exception or request correction]
D --> B
C -- Yes --> E[Record Decision or execution Intent]
E --> F[Execute Domain command or external request]
F --> G{Outcome known?}
G -- Success --> H[Record fact and publish Event]
G -- Failure --> I[Record failure and compensation options]
G -- Unknown --> J[Enter Outcome Unknown]
J --> K[Query source or wait for verified callback]
K --> G
H --> L[Update projections and downstream workflow]
```

Representative failure modes:

- stale or wrong source version
- duplicate submission or replay
- external timeout after possible success
- contradictory source observations
- lost Event after committed state
- approval or mandate revoked during execution
- downstream action before a mandatory gate
- partial completion across multiple subjects
- evidence later retracted or corrected
- tenant, facility, channel or jurisdiction mismatch

Recovery shall query the authoritative source before duplicate execution, preserve partial success, use compensating Intent rather than destructive rewrite, publish corrections, quarantine high-impact ambiguity, and record affected downstream subjects.

8. Data and Persistence Architecture

Reference table families:

Table family	Purpose
qualitydashboardexperiencestandard_aggregate	authoritative subject
qualitydashboardexperiencestandard_version	immutable submitted, approved, issued, or signed versions
qualitydashboardexperiencestandard_relationship	governed relationships
qualitydashboardexperiencestandard_decision	binding Decisions and rationale
qualitydashboardexperiencestandard_evidence_link	provenance and evidence relationships
qualitydashboardexperiencestandard_event_outbox	transactional Event publication
qualitydashboardexperiencestandard_idempotency	duplicate-write protection
qualitydashboardexperiencestandard_exception	exception, claim, dispute, or hold
qualitydashboardexperiencestandard_correction	correction and supersession lineage
qualitydashboardexperiencestandard_audit	privileged action evidence

The owning service controls schema and migration. Cross-Domain references use stable identifiers or contracts. Analytics, reports, caches, search, and vector indexes remain projections. Backup, restore, retention, legal hold, privacy, residency, and decommissioning requirements are explicit.

9. Portal and Experience Requirements

- Quality Dashboard: primary experience for quality managers, inspectors and auditors.
- Operator and support views: diagnose failed or ambiguous journeys without assuming Domain ownership.
- Domain services: own authoritative data and action eligibility; the Portal consumes typed contracts.

Every Portal displays exact version, owner, state, freshness, required action, and uncertainty. It supports loading, empty, partial, stale, denied, error, timeout, and Outcome Unknown states; accessibility; locale, currency, unit, date, and RTL/LTR correctness; evidence audit; safe retry; and correction history.

10. AI Participation and Tool Governance

Permitted AI tasks:

- extract and classify evidence
- detect anomalies and missing fields
- summarize timelines and contradictions
- recommend next actions with sources and uncertainty

AI shall not own Domain records, grant itself authority, suppress contradictions, silently edit approved versions, fabricate external outcomes, or execute high-impact actions outside typed Tools, policy, approval, idempotency, sandbox, and outcome observation.

Every Agent Run records source context, prompt/model/tool versions, structured output, confidence and limitations, Policy result, approval, Tool calls, provider responses, final outcome, and recovery actions.

11. Security, Privacy, and Trust Boundaries

- least privilege and separation of duties
- tenant, organization, facility, channel and jurisdiction isolation
- integrity protection for binding evidence
- verified external callbacks and anti-replay controls

Additional controls include secret isolation, callback signature verification, audit of privileged action, emergency-access review, sensitive-data minimization, purpose limitation, and threat models for impersonation, tampering, replay, confused deputy, fraud, prompt injection, and exfiltration.

12. Reliability, SLOs, and Operations

SLI	Reference objective
authoritative read availability	99.9% monthly unless a stricter tier applies
acknowledged Command durability	no acknowledged write may be silently lost
Event publication	99.9% within five minutes after committed fact
duplicate prevention	100% for same tenant, Command class, and idempotency key
binding Decision audit completeness	100%
state-state detection	bounded by business deadline

Dashboards and runbooks cover backlog, error budget, dependency failure, retry budget, DLQ, workflow stall, provider outage, reconciliation, capacity, backup/restore, release/rollback, incident command, and post-incident correction.

13. Testing and Continuous Conformance

- aggregate invariant and transition tests
- authorization, delegation, separation-of-duties and tenant-isolation tests
- idempotency and optimistic-concurrency tests
- database migration, key, constraint and rollback tests
- contract, outbox/inbox, duplicate, replay and DLQ tests
- workflow restart, timeout and compensation tests
- Portal E2E tests for success, partial, stale, denied, error and Outcome Unknown states
- accessibility, locale, currency, unit and RTL/LTR tests
- security adversarial, fraud and data-exfiltration tests
- AI evaluation, prompt-injection, policy-bypass and unauthorized-tool tests
- historical reconstruction, correction and audit-completeness tests
- performance, capacity, recovery and operational exercise tests

Release evidence links each invariant and control to the test, environment, input data, result, owner, and artifact proving it. Generated test counts never replace semantic coverage.

14. Repository Review Boundary

- This chapter is a repository-review specification. Exact executable implementation has not been inspected for every target behavior.
- Registered modules, catalog entries, README claims, frontend contracts, or plans are not proof of complete implementation.

Area	Classification
target aggregate, API, tables, state and workflow in this chapter	REFERENCE_ARCHITECTURE
registered module or catalog claim	DOCUMENTATION_ONLY_CLAIM until source inspection
uninspected integration	REQUIRES_REPOSITORY_REVIEW
behavior proven in another repository-grounded chapter	retain that chapter's evidence and classification
contradictory ownership or path claims	CONFLICT_REQUIRES_CANONICALIZATION

No statement upgrades implementation status merely because a file, directory, module name, frontend contract, database entry, plan, or report exists.

15. Worked Conformance Scenario

An authorized principal initiates a Command against an exact subject version. The service validates identity, tenant, mandate, Policy, Evidence, and idempotency. It records the state transition and outbox entry atomically. If an external dependency participates, timeout produces Outcome Unknown; reconciliation queries the source or waits for a verified callback instead of repeating the action blindly.

Portals show source, freshness, version, required action, and uncertainty. AI may extract, compare, summarize, detect anomalies, and recommend through typed Tools, but cannot own the subject or fabricate success. Later correction appends new facts, identifies affected projections and workflows, and preserves the historical Decision context.

16. Conformance Checklist

- ☐ stable identity and proposition ownership are explicit;
- ☐ authority and mandate are evaluated at action time;
- ☐ state, Recommendation, Decision, Intent, execution, and outcome remain distinct;
- ☐ Commands are typed, authorized, idempotent, and version guarded;
- ☐ Events describe completed facts;
- ☐ Evidence includes provenance, time, integrity, qualification, and correction;
- ☐ external outcomes retain their authority source;
- ☐ Portals show freshness and uncertainty;
- ☐ AI is bounded by typed Tools, Policy, approval, and outcome observation;
- ☐ security, tenant, facility, channel, and jurisdiction boundaries are enforced;
- ☐ Outcome Unknown and reconciliation exist where needed;
- ☐ corrections preserve history;
- ☐ tests prove invariants and recovery;
- ☐ implementation status is not upgraded without executable evidence.

17. Status Vocabulary

Status	Meaning
VERIFIED_IMPLEMENTED	Executable source and relevant behavior were inspected.
IMPLEMENTED_WITH_GAP	Executable behavior exists with a material governance or completeness gap.
PARTIAL_IMPLEMENTATION	Only part of the target capability is evidenced.
REFERENCE_ARCHITECTURE	Normative target behavior; no claim that it exists today.
PLANNED_NOT_IMPLEMENTED	Explicitly planned but not evidenced as executable.
DOCUMENTATION_ONLY_CLAIM	Documentation or client contract claims behavior without verified backend evidence.
CONFLICT_REQUIRES_CANONICALIZATION	Sources disagree and no final owner has been established.
REQUIRES_REPOSITORY_REVIEW	Necessary executable evidence has not yet been inspected.

Scenario Simulator — Portal Orientation and Information Architecture

Metadata	Value
Volume	4
Chapter ID	V04-P12-00
Subject	ScenarioSimulatorPortal
Status	Generated First-Draft Architecture Skeleton - Domain-Specific Expansion Required
Content maturity	TEMPLATE_DERIVED_REFERENCE_SKELETON unless repository citations prove otherwise
Default implementation classification	REFERENCE_ARCHITECTURE / REQUIRES_REPOSITORY_REVIEW
Accountable owner	Portal Architecture / Scenario Simulator
Evidence rule	No implementation claim without inspected executable evidence
Repository	chinair88-prog/allinb2c

1. Executive Orientation

This chapter defines how GTOS shall **define personas, navigation, route ownership, domain dependencies and experience boundaries for planners, analysts and executives, covering assumptions, scenarios, simulations, sensitivity, comparison, Decision support.**

The specification separates reality, observations, knowledge, Decisions, Intent, execution, and outcomes. A component name, database row, UI label, AI answer, or workflow state does not acquire authority merely because it is visible or technically convenient.

Reality or external outcome

- ≠ Observation
- ≠ Claim
- ≠ derived Perspective
- ≠ Prediction
- ≠ Recommendation
- ≠ authorized Decision
- ≠ execution Intent

1.1 Accountable ownership

The accountable owner is **Portal Architecture / Scenario Simulator**. Supporting applications, shared infrastructure, integration adapters, analytics, and AI coordinate or present the capability but shall not silently own its authoritative propositions.

1.2 Scope

- create and identify the subject
- validate evidence and policy
- make authorized Decisions
- execute typed Commands
- publish completed-fact Events
- query current and historical perspectives
- correct and reconcile outcomes

1.3 Non-goals

- treating a registered Gradle module, catalog record, README, frontend route, migration plan, or generated report as proof of end-to-end implementation;
- direct cross-Domain database writes;
- generic status values that combine lifecycle, approval, provider, document, payment, dispute, and correction state;
- silent replacement of history;
- AI-created authority or fabricated external outcomes.

2. Ubiquitous Language and Subject Model

Subject	Required interpretation
ScenarioSimulatorPortal	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit
ScenarioSimulatorPortalVersion	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit
ScenarioSimulatorPortalDecision	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit
ScenarioSimulatorPortalEvidenceSet	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit
ScenarioSimulatorPortalException	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit

Reference aggregate:

```
ScenarioSimulatorPortal {
  subjectId
  tenantId
  organizationContext
  sourceIdentityRefs[]
  sourceVersionRefs[]
  lifecycleState
  relationshipRefs[]
  decisionRefs[]
  intentRefs[]
  evidenceSetRef
  knowledgeCutoff
  policyRefs[]
  authorityRef
  jurisdictionRefs[]
  createdAt
  effectiveAt
  updatedAt
  version
  correctionOf?
  correlationId
}
```

2.1 Core invariants

- Stable identity precedes relationship, state, and cross-system correlation.
- Effective time and recorded time remain distinct where business truth changes over time.
- Recommendation, Decision, Intent, execution, and outcome are separate concepts.
- No Portal, report, search index, cache, workflow, or AI Agent becomes a shadow owner of Domain truth.
- Binding submitted, approved, issued, accepted, or signed versions are immutable.
- Corrections append governed facts and preserve the original record.
- External authority and provider outcomes retain their source and qualification.
- Tenant and represented-principal context come from trusted authentication and mandate evaluation.
- Retried writes are idempotent and concurrency guarded.
- Outcome Unknown is explicit and reconciled before risky duplicate execution.

2.2 Required standards

- stable identifiers
- typed contracts
- immutable binding versions

- transactional outbox
- idempotent Commands
- explicit Outcome Unknown
- correction lineage
- machine-verifiable conformance

3. Actors, Roles, and Authority

- A conformant design distinguishes:
- the natural person acting;
 - the service or AI identity invoking a Tool;
 - the organization or principal represented;
 - the role or relationship granting context;
 - the mandate or delegation granting action authority;
 - the Policy and jurisdiction limiting the action;
 - the reviewer or approver responsible for a binding Decision.

Authority is evaluated at action time. Authentication alone does not grant business authority. Cached permissions and browser-supplied tenant headers are insufficient for high-impact actions.

4. Lifecycle and State Model

State	Semantics
PROPOSED	Distinct governed condition with entry, exit, timeout, correction and authority semantics
VALIDATION_PENDING	Distinct governed condition with entry, exit, timeout, correction and authority semantics
APPROVAL_PENDING	Distinct governed condition with entry, exit, timeout, correction and authority semantics
ACTIVE	Distinct governed condition with entry, exit, timeout, correction and authority semantics
SUSPENDED	Distinct governed condition with entry, exit, timeout, correction and authority semantics
CORRECTION_PENDING	Distinct governed condition with entry, exit, timeout, correction and authority semantics
RETIRED	Distinct governed condition with entry, exit, timeout, correction and authority semantics

```
stateDiagram-v2
    [*] --> PROPOSED
    PROPOSED --> VALIDATION_PENDING
    VALIDATION_PENDING --> APPROVAL_PENDING
    APPROVAL_PENDING --> ACTIVE
    ACTIVE --> SUSPENDED
    SUSPENDED --> CORRECTION_PENDING
    CORRECTION_PENDING --> RETIRED
```

The diagram is a primary reading path. Real implementations may add parallel review, amendment, appeal, timeout, suspension, partial completion, reconciliation, correction, and terminal failure without collapsing their meaning.

4.1 Transition rules

- transition through a typed, authorized Command;
- require exact expected version where concurrent change matters;
- record actor, represented principal, mandate, Policy, reason, and Evidence;
- use an idempotency key for retried writes;
- publish a completed-fact Event after durable state change;
- expose Outcome Unknown for unresolved external completion;
- preserve original and corrected states in historical reconstruction.

5. Decision, Evidence, and Knowledge Cutoff

Reference Decision:

```
Decision {
  decisionId
  decisionType
  subjectRef
  sourceVersionRefs[]
  knowledgeCutoff
  evidenceSetRef
  policyVersionRefs[]
  recommendationRefs[]
  principalId
  representedOrganizationId
  mandateRef
  rationale
  outcome
  decidedAt
  effectiveAt
  correctionOf?
}
```

Evidence records identify issuer or observer, subject, version, observed time, received time, effective interval, integrity, confidence, qualification, contradiction, correction, retention, residency, and access class. A recommendation may assist the Decision but cannot promote itself to the Decision.

6. Commands, Events, Queries, and Contracts

Reference Commands:

- CreateScenarioSimulatorPortal
- ValidateScenarioSimulatorPortal
- ApproveScenarioSimulatorPortal
- ActivateScenarioSimulatorPortal
- SuspendScenarioSimulatorPortal
- CorrectScenarioSimulatorPortal
- RetireScenarioSimulatorPortal

Reference Events:

- ScenarioSimulatorPortalCreated
- ScenarioSimulatorPortalValidated
- ScenarioSimulatorPortalApproved
- ScenarioSimulatorPortalActivated
- ScenarioSimulatorPortalSuspended
- ScenarioSimulatorPortalCorrected
- ScenarioSimulatorPortalRetired

Reference queries:

- GetScenarioSimulatorPortal
- ListScenarioSimulatorPortalRecords
- GetScenarioSimulatorPortalTimeline
- GetScenarioSimulatorPortalEvidence
- GetScenarioSimulatorPortalDecisionPackage
- GetScenarioSimulatorPortalExceptions
- GetScenarioSimulatorPortalAuditTrail

Reference API surface:

```
POST /api/v1/scenariosimulatorportal/commands
GET  /api/v1/scenariosimulatorportal/{id}
GET  /api/v1/scenariosimulatorportal/{id}/timeline
GET  /api/v1/scenariosimulatorportal/{id}/evidence
GET  /api/v1/scenariosimulatorportal/{id}/decisions
POST /api/v1/scenariosimulatorportal/{id}/exceptions
POST /api/v1/scenariosimulatorportal/{id}/corrections
```

These endpoints are reference contracts, not claims that exact routes exist.

7. Workflow, Failure, and Compensation

flowchart TD

```
A[Validate identity version and authority] --> B[Collect required evidence]
B --> C{Policy and evidence gates pass?}
C -- No --> D[Open exception or request correction]
D --> B
C -- Yes --> E[Record Decision or execution Intent]
E --> F[Execute Domain command or external request]
F --> G{Outcome known?}
G -- Success --> H[Record fact and publish Event]
G -- Failure --> I[Record failure and compensation options]
G -- Unknown --> J[Enter Outcome Unknown]
J --> K[Query source or wait for verified callback]
K --> G
H --> L[Update projections and downstream workflow]
```

Representative failure modes:

- stale or wrong source version
- duplicate submission or replay
- external timeout after possible success
- contradictory source observations
- lost Event after committed state
- approval or mandate revoked during execution
- downstream action before a mandatory gate
- partial completion across multiple subjects
- evidence later retracted or corrected
- tenant, facility, channel or jurisdiction mismatch

Recovery shall query the authoritative source before duplicate execution, preserve partial success, use compensating Intent rather than destructive rewrite, publish corrections, quarantine high-impact ambiguity, and record affected downstream subjects.

8. Data and Persistence Architecture

Reference table families:

Table family	Purpose
scenariosimulatorportal_aggregate	authoritative subject
scenariosimulatorportal_version	immutable submitted, approved, issued, or signed versions
scenariosimulatorportal_relationship	governed relationships
scenariosimulatorportal_decision	binding Decisions and rationale
scenariosimulatorportal_evidence_link	provenance and evidence relationships
scenariosimulatorportal_event_outbox	transactional Event publication
scenariosimulatorportal_idempotency	duplicate-write protection
scenariosimulatorportal_exception	exception, claim, dispute, or hold
scenariosimulatorportal_correction	correction and supersession lineage
scenariosimulatorportal_audit	privileged action evidence

The owning service controls schema and migration. Cross-Domain references use stable identifiers or contracts. Analytics, reports, caches, search, and vector indexes remain projections. Backup, restore, retention, legal hold, privacy, residency, and decommissioning requirements are explicit.

9. Portal and Experience Requirements

- Scenario Simulator: primary experience for planners, analysts and executives.
- Operator and support views: diagnose failed or ambiguous journeys without assuming Domain ownership.
- Domain services: own authoritative data and action eligibility; the Portal consumes typed contracts.

Every Portal displays exact version, owner, state, freshness, required action, and uncertainty. It supports loading, empty, partial, stale, denied, error, timeout, and Outcome Unknown states; accessibility; locale, currency, unit, date, and RTL/LTR correctness; evidence audit; safe retry; and correction history.

10. AI Participation and Tool Governance

Permitted AI tasks:

- extract and classify evidence
- detect anomalies and missing fields
- summarize timelines and contradictions
- recommend next actions with sources and uncertainty

AI shall not own Domain records, grant itself authority, suppress contradictions, silently edit approved versions, fabricate external outcomes, or execute high-impact actions outside typed Tools, policy, approval, idempotency, sandbox, and outcome observation.

Every Agent Run records source context, prompt/model/tool versions, structured output, confidence and limitations, Policy result, approval, Tool calls, provider responses, final outcome, and recovery actions.

11. Security, Privacy, and Trust Boundaries

- least privilege and separation of duties
- tenant, organization, facility, channel and jurisdiction isolation
- integrity protection for binding evidence
- verified external callbacks and anti-replay controls

Additional controls include secret isolation, callback signature verification, audit of privileged action, emergency-access review, sensitive-data minimization, purpose limitation, and threat models for impersonation, tampering, replay, confused deputy, fraud, prompt injection, and exfiltration.

12. Reliability, SLOs, and Operations

SLI	Reference objective
authoritative read availability	99.9% monthly unless a stricter tier applies
acknowledged Command durability	no acknowledged write may be silently lost
Event publication	99.9% within five minutes after committed fact
duplicate prevention	100% for same tenant, Command class, and idempotency key
binding Decision audit completeness	100%
state-state detection	bounded by business deadline

Dashboards and runbooks cover backlog, error budget, dependency failure, retry budget, DLQ, workflow stall, provider outage, reconciliation, capacity, backup/restore, release/rollback, incident command, and post-incident correction.

13. Testing and Continuous Conformance

- aggregate invariant and transition tests
- authorization, delegation, separation-of-duties and tenant-isolation tests
- idempotency and optimistic-concurrency tests
- database migration, key, constraint and rollback tests
- contract, outbox/inbox, duplicate, replay and DLQ tests
- workflow restart, timeout and compensation tests
- Portal E2E tests for success, partial, stale, denied, error and Outcome Unknown states
- accessibility, locale, currency, unit and RTL/LTR tests
- security adversarial, fraud and data-exfiltration tests
- AI evaluation, prompt-injection, policy-bypass and unauthorized-tool tests
- historical reconstruction, correction and audit-completeness tests
- performance, capacity, recovery and operational exercise tests

Release evidence links each invariant and control to the test, environment, input data, result, owner, and artifact proving it. Generated test counts never replace semantic coverage.

14. Repository Review Boundary

- This chapter is a repository-review specification. Exact executable implementation has not been inspected for every target behavior.
- Registered modules, catalog entries, README claims, frontend contracts, or plans are not proof of complete implementation.

Area	Classification
target aggregate, API, tables, state and workflow in this chapter	REFERENCE_ARCHITECTURE
registered module or catalog claim	DOCUMENTATION_ONLY_CLAIM until source inspection
uninspected integration	REQUIRES_REPOSITORY_REVIEW
behavior proven in another repository-grounded chapter	retain that chapter's evidence and classification
contradictory ownership or path claims	CONFLICT_REQUIRES_CANONICALIZATION

No statement upgrades implementation status merely because a file, directory, module name, frontend contract, database entry, plan, or report exists.

15. Worked Conformance Scenario

An authorized principal initiates a Command against an exact subject version. The service validates identity, tenant, mandate, Policy, Evidence, and idempotency. It records the state transition and outbox entry atomically. If an external dependency participates, timeout produces Outcome Unknown; reconciliation queries the source or waits for a verified callback instead of repeating the action blindly.

Portals show source, freshness, version, required action, and uncertainty. AI may extract, compare, summarize, detect anomalies, and recommend through typed Tools, but cannot own the subject or fabricate success. Later correction appends new facts, identifies affected projections and workflows, and preserves the historical Decision context.

16. Conformance Checklist

- ☐ stable identity and proposition ownership are explicit;
- ☐ authority and mandate are evaluated at action time;
- ☐ state, Recommendation, Decision, Intent, execution, and outcome remain distinct;
- ☐ Commands are typed, authorized, idempotent, and version guarded;
- ☐ Events describe completed facts;
- ☐ Evidence includes provenance, time, integrity, qualification, and correction;
- ☐ external outcomes retain their authority source;
- ☐ Portals show freshness and uncertainty;
- ☐ AI is bounded by typed Tools, Policy, approval, and outcome observation;
- ☐ security, tenant, facility, channel, and jurisdiction boundaries are enforced;
- ☐ Outcome Unknown and reconciliation exist where needed;
- ☐ corrections preserve history;
- ☐ tests prove invariants and recovery;
- ☐ implementation status is not upgraded without executable evidence.

17. Status Vocabulary

Status	Meaning
VERIFIED_IMPLEMENTED	Executable source and relevant behavior were inspected.
IMPLEMENTED_WITH_GAP	Executable behavior exists with a material governance or completeness gap.
PARTIAL_IMPLEMENTATION	Only part of the target capability is evidenced.
REFERENCE_ARCHITECTURE	Normative target behavior; no claim that it exists today.
PLANNED_NOT_IMPLEMENTED	Explicitly planned but not evidenced as executable.
DOCUMENTATION_ONLY_CLAIM	Documentation or client contract claims behavior without verified backend evidence.
CONFLICT_REQUIRES_CANONICALIZATION	Sources disagree and no final owner has been established.
REQUIRES_REPOSITORY_REVIEW	Necessary executable evidence has not yet been inspected.

Scenario Simulator — Routes, Pages, Components, and BFF Contracts

Metadata	Value
Volume	4
Chapter ID	V04-P12-01
Subject	ScenarioSimulatorRouteRegistry
Status	Generated First-Draft Architecture Skeleton - Domain-Specific Expansion Required
Content maturity	TEMPLATE_DERIVED_REFERENCE_SKELETON unless repository citations prove otherwise
Default implementation classification	REFERENCE_ARCHITECTURE / REQUIRES_REPOSITORY_REVIEW
Accountable owner	Portal Architecture / Scenario Simulator
Evidence rule	No implementation claim without inspected executable evidence
Repository	chinair88-prog/allinb2c

1. Executive Orientation

This chapter defines how GTOS shall **inventory routes, layouts, pages, components, server/client boundaries, BFFs, APIs, realtime channels and ownership for planners, analysts and executives, covering assumptions, scenarios, simulations, sensitivity, comparison, Decision support.**

The specification separates reality, observations, knowledge, Decisions, Intent, execution, and outcomes. A component name, database row, UI label, AI answer, or workflow state does not acquire authority merely because it is visible or technically convenient.

Reality or external outcome

- ≠ Observation
- ≠ Claim
- ≠ derived Perspective
- ≠ Prediction
- ≠ Recommendation
- ≠ authorized Decision
- ≠ execution Intent

1.1 Accountable ownership

The accountable owner is **Portal Architecture / Scenario Simulator**. Supporting applications, shared infrastructure, integration adapters, analytics, and AI coordinate or present the capability but shall not silently own its authoritative propositions.

1.2 Scope

- create and identify the subject
- validate evidence and policy
- make authorized Decisions
- execute typed Commands
- publish completed-fact Events
- query current and historical perspectives
- correct and reconcile outcomes

1.3 Non-goals

- treating a registered Gradle module, catalog record, README, frontend route, migration plan, or generated report as proof of end-to-end implementation;
- direct cross-Domain database writes;
- generic status values that combine lifecycle, approval, provider, document, payment, dispute, and correction state;
- silent replacement of history;
- AI-created authority or fabricated external outcomes.

2. Ubiquitous Language and Subject Model

Subject	Required interpretation
ScenarioSimulatorRouteRegistry	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit
ScenarioSimulatorRouteRegistryVersion	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit
ScenarioSimulatorRouteRegistryDecision	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit
ScenarioSimulatorRouteRegistryEvidenceSet	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit
ScenarioSimulatorRouteRegistryException	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit

Reference aggregate:

```
ScenarioSimulatorRouteRegistry {  
  subjectId  
  tenantId  
  organizationContext  
  sourceIdentityRefs[]  
  sourceVersionRefs[]  
  lifecycleState  
  relationshipRefs[]  
  decisionRefs[]  
  intentRefs[]  
  evidenceSetRef  
  knowledgeCutoff  
  policyRefs[]  
  authorityRef  
  jurisdictionRefs[]  
  createdAt  
  effectiveAt  
  updatedAt  
  version  
  correctionOf?  
  correlationId  
}
```

2.1 Core invariants

- Stable identity precedes relationship, state, and cross-system correlation.
- Effective time and recorded time remain distinct where business truth changes over time.
- Recommendation, Decision, Intent, execution, and outcome are separate concepts.
- No Portal, report, search index, cache, workflow, or AI Agent becomes a shadow owner of Domain truth.
- Binding submitted, approved, issued, accepted, or signed versions are immutable.
- Corrections append governed facts and preserve the original record.
- External authority and provider outcomes retain their source and qualification.
- Tenant and represented-principal context come from trusted authentication and mandate evaluation.
- Retried writes are idempotent and concurrency guarded.
- Outcome Unknown is explicit and reconciled before risky duplicate execution.

2.2 Required standards

- stable identifiers
- typed contracts
- immutable binding versions

- transactional outbox
- idempotent Commands
- explicit Outcome Unknown
- correction lineage
- machine-verifiable conformance

3. Actors, Roles, and Authority

A conformant design distinguishes:

- the natural person acting;
- the service or AI identity invoking a Tool;
- the organization or principal represented;
- the role or relationship granting context;
- the mandate or delegation granting action authority;
- the Policy and jurisdiction limiting the action;
- the reviewer or approver responsible for a binding Decision.

Authority is evaluated at action time. Authentication alone does not grant business authority. Cached permissions and browser-supplied tenant headers are insufficient for high-impact actions.

4. Lifecycle and State Model

State	Semantics
PROPOSED	Distinct governed condition with entry, exit, timeout, correction and authority semantics
VALIDATION_PENDING	Distinct governed condition with entry, exit, timeout, correction and authority semantics
APPROVAL_PENDING	Distinct governed condition with entry, exit, timeout, correction and authority semantics
ACTIVE	Distinct governed condition with entry, exit, timeout, correction and authority semantics
SUSPENDED	Distinct governed condition with entry, exit, timeout, correction and authority semantics
CORRECTION_PENDING	Distinct governed condition with entry, exit, timeout, correction and authority semantics
RETIRED	Distinct governed condition with entry, exit, timeout, correction and authority semantics

```
stateDiagram-v2
    [*] --> PROPOSED
    PROPOSED --> VALIDATION_PENDING
    VALIDATION_PENDING --> APPROVAL_PENDING
    APPROVAL_PENDING --> ACTIVE
    ACTIVE --> SUSPENDED
    SUSPENDED --> CORRECTION_PENDING
    CORRECTION_PENDING --> RETIRED
```

The diagram is a primary reading path. Real implementations may add parallel review, amendment, appeal, timeout, suspension, partial completion, reconciliation, correction, and terminal failure without collapsing their meaning.

4.1 Transition rules

- transition through a typed, authorized Command;
- require exact expected version where concurrent change matters;
- record actor, represented principal, mandate, Policy, reason, and Evidence;
- use an idempotency key for retried writes;
- publish a completed-fact Event after durable state change;
- expose Outcome Unknown for unresolved external completion;
- preserve original and corrected states in historical reconstruction.

5. Decision, Evidence, and Knowledge Cutoff

Reference Decision:

```
Decision {
  decisionId
  decisionType
  subjectRef
  sourceVersionRefs[]
  knowledgeCutoff
  evidenceSetRef
  policyVersionRefs[]
  recommendationRefs[]
  principalId
  representedOrganizationId
  mandateRef
  rationale
  outcome
  decidedAt
  effectiveAt
  correctionOf?
}
```

Evidence records identify issuer or observer, subject, version, observed time, received time, effective interval, integrity, confidence, qualification, contradiction, correction, retention, residency, and access class. A recommendation may assist the Decision but cannot promote itself to the Decision.

6. Commands, Events, Queries, and Contracts

Reference Commands:

- CreateScenarioSimulatorRouteRegistry
- ValidateScenarioSimulatorRouteRegistry
- ApproveScenarioSimulatorRouteRegistry
- ActivateScenarioSimulatorRouteRegistry
- SuspendScenarioSimulatorRouteRegistry
- CorrectScenarioSimulatorRouteRegistry
- RetireScenarioSimulatorRouteRegistry

Reference Events:

- ScenarioSimulatorRouteRegistryCreated
- ScenarioSimulatorRouteRegistryValidated
- ScenarioSimulatorRouteRegistryApproved
- ScenarioSimulatorRouteRegistryActivated
- ScenarioSimulatorRouteRegistrySuspended
- ScenarioSimulatorRouteRegistryCorrected
- ScenarioSimulatorRouteRegistryRetired

Reference queries:

- GetScenarioSimulatorRouteRegistry
- ListScenarioSimulatorRouteRegistryRecords
- GetScenarioSimulatorRouteRegistryTimeline
- GetScenarioSimulatorRouteRegistryEvidence
- GetScenarioSimulatorRouteRegistryDecisionPackage
- GetScenarioSimulatorRouteRegistryExceptions
- GetScenarioSimulatorRouteRegistryAuditTrail

Reference API surface:

```
POST /api/v1/scenariosimulatorrouteregistry/commands
GET  /api/v1/scenariosimulatorrouteregistry/{id}
GET  /api/v1/scenariosimulatorrouteregistry/{id}/timeline
GET  /api/v1/scenariosimulatorrouteregistry/{id}/evidence
GET  /api/v1/scenariosimulatorrouteregistry/{id}/decisions
POST /api/v1/scenariosimulatorrouteregistry/{id}/exceptions
POST /api/v1/scenariosimulatorrouteregistry/{id}/corrections
```

These endpoints are reference contracts, not claims that exact routes exist.

7. Workflow, Failure, and Compensation

```
flowchart TD
    A[Validate identity version and authority] --> B[Collect required evidence]
    B --> C{Policy and evidence gates pass?}
    C -- No --> D[Open exception or request correction]
    D --> B
    C -- Yes --> E[Record Decision or execution Intent]
    E --> F[Execute Domain command or external request]
    F --> G{Outcome known?}
    G -- Success --> H[Record fact and publish Event]
    G -- Failure --> I[Record failure and compensation options]
    G -- Unknown --> J[Enter Outcome Unknown]
    J --> K[Query source or wait for verified callback]
    K --> G
    H --> L[Update projections and downstream workflow]
```

Representative failure modes:

- stale or wrong source version
- duplicate submission or replay
- external timeout after possible success
- contradictory source observations
- lost Event after committed state
- approval or mandate revoked during execution
- downstream action before a mandatory gate
- partial completion across multiple subjects
- evidence later retracted or corrected
- tenant, facility, channel or jurisdiction mismatch

Recovery shall query the authoritative source before duplicate execution, preserve partial success, use compensating Intent rather than destructive rewrite, publish corrections, quarantine high-impact ambiguity, and record affected downstream subjects.

8. Data and Persistence Architecture

Reference table families:

Table family	Purpose
scenariosimulatorrouterregistry_aggregate	authoritative subject
scenariosimulatorrouterregistry_version	immutable submitted, approved, issued, or signed versions
scenariosimulatorrouterregistry_relationship	governed relationships
scenariosimulatorrouterregistry_decision	binding Decisions and rationale
scenariosimulatorrouterregistry_evidence_link	provenance and evidence relationships
scenariosimulatorrouterregistry_event_outbox	transactional Event publication
scenariosimulatorrouterregistry_idempotency	duplicate-write protection
scenariosimulatorrouterregistry_exception	exception, claim, dispute, or hold
scenariosimulatorrouterregistry_correction	correction and supersession lineage
scenariosimulatorrouterregistry_audit	privileged action evidence

The owning service controls schema and migration. Cross-Domain references use stable identifiers or contracts. Analytics, reports, caches, search, and vector indexes remain projections. Backup, restore, retention, legal hold, privacy, residency, and decommissioning requirements are explicit.

9. Portal and Experience Requirements

- Scenario Simulator: primary experience for planners, analysts and executives.
- Operator and support views: diagnose failed or ambiguous journeys without assuming Domain ownership.
- Domain services: own authoritative data and action eligibility; the Portal consumes typed contracts.

Every Portal displays exact version, owner, state, freshness, required action, and uncertainty. It supports loading, empty, partial, stale, denied, error, timeout, and Outcome Unknown states; accessibility; locale, currency, unit, date, and RTL/LTR correctness; evidence audit; safe retry; and correction history.

10. AI Participation and Tool Governance

Permitted AI tasks:

- extract and classify evidence
- detect anomalies and missing fields
- summarize timelines and contradictions
- recommend next actions with sources and uncertainty

AI shall not own Domain records, grant itself authority, suppress contradictions, silently edit approved versions, fabricate external outcomes, or execute high-impact actions outside typed Tools, policy, approval, idempotency, sandbox, and outcome observation.

Every Agent Run records source context, prompt/model/tool versions, structured output, confidence and limitations, Policy result, approval, Tool calls, provider responses, final outcome, and recovery actions.

11. Security, Privacy, and Trust Boundaries

- least privilege and separation of duties
- tenant, organization, facility, channel and jurisdiction isolation
- integrity protection for binding evidence
- verified external callbacks and anti-replay controls

Additional controls include secret isolation, callback signature verification, audit of privileged action, emergency-access review, sensitive-data minimization, purpose limitation, and threat models for impersonation, tampering, replay, confused deputy, fraud, prompt injection, and exfiltration.

12. Reliability, SLOs, and Operations

SLI	Reference objective
authoritative read availability	99.9% monthly unless a stricter tier applies
acknowledged Command durability	no acknowledged write may be silently lost
Event publication	99.9% within five minutes after committed fact
duplicate prevention	100% for same tenant, Command class, and idempotency key
binding Decision audit completeness	100%
state-state detection	bounded by business deadline

Dashboards and runbooks cover backlog, error budget, dependency failure, retry budget, DLQ, workflow stall, provider outage, reconciliation, capacity, backup/restore, release/rollback, incident command, and post-incident correction.

13. Testing and Continuous Conformance

- aggregate invariant and transition tests
- authorization, delegation, separation-of-duties and tenant-isolation tests
- idempotency and optimistic-concurrency tests
- database migration, key, constraint and rollback tests
- contract, outbox/inbox, duplicate, replay and DLQ tests
- workflow restart, timeout and compensation tests
- Portal E2E tests for success, partial, stale, denied, error and Outcome Unknown states
- accessibility, locale, currency, unit and RTL/LTR tests
- security adversarial, fraud and data-exfiltration tests
- AI evaluation, prompt-injection, policy-bypass and unauthorized-tool tests
- historical reconstruction, correction and audit-completeness tests
- performance, capacity, recovery and operational exercise tests

Release evidence links each invariant and control to the test, environment, input data, result, owner, and artifact proving it. Generated test counts never replace semantic coverage.

14. Repository Review Boundary

- This chapter is a repository-review specification. Exact executable implementation has not been inspected for every target behavior.
- Registered modules, catalog entries, README claims, frontend contracts, or plans are not proof of complete implementation.

Area	Classification
target aggregate, API, tables, state and workflow in this chapter	REFERENCE_ARCHITECTURE
registered module or catalog claim	DOCUMENTATION_ONLY_CLAIM until source inspection
uninspected integration	REQUIRES_REPOSITORY_REVIEW
behavior proven in another repository-grounded chapter	retain that chapter's evidence and classification
contradictory ownership or path claims	CONFLICT_REQUIRES_CANONICALIZATION

No statement upgrades implementation status merely because a file, directory, module name, frontend contract, database entry, plan, or report exists.

15. Worked Conformance Scenario

An authorized principal initiates a Command against an exact subject version. The service validates identity, tenant, mandate, Policy, Evidence, and idempotency. It records the state transition and outbox entry atomically. If an external dependency participates, timeout produces Outcome Unknown; reconciliation queries the source or waits for a verified callback instead of repeating the action blindly.

Portals show source, freshness, version, required action, and uncertainty. AI may extract, compare, summarize, detect anomalies, and recommend through typed Tools, but cannot own the subject or fabricate success. Later correction appends new facts, identifies affected projections and workflows, and preserves the historical Decision context.

16. Conformance Checklist

- ☐ stable identity and proposition ownership are explicit;
- ☐ authority and mandate are evaluated at action time;
- ☐ state, Recommendation, Decision, Intent, execution, and outcome remain distinct;
- ☐ Commands are typed, authorized, idempotent, and version guarded;
- ☐ Events describe completed facts;
- ☐ Evidence includes provenance, time, integrity, qualification, and correction;
- ☐ external outcomes retain their authority source;
- ☐ Portals show freshness and uncertainty;
- ☐ AI is bounded by typed Tools, Policy, approval, and outcome observation;
- ☐ security, tenant, facility, channel, and jurisdiction boundaries are enforced;
- ☐ Outcome Unknown and reconciliation exist where needed;
- ☐ corrections preserve history;
- ☐ tests prove invariants and recovery;
- ☐ implementation status is not upgraded without executable evidence.

17. Status Vocabulary

Status	Meaning
VERIFIED_IMPLEMENTED	Executable source and relevant behavior were inspected.
IMPLEMENTED_WITH_GAP	Executable behavior exists with a material governance or completeness gap.
PARTIAL_IMPLEMENTATION	Only part of the target capability is evidenced.
REFERENCE_ARCHITECTURE	Normative target behavior; no claim that it exists today.
PLANNED_NOT_IMPLEMENTED	Explicitly planned but not evidenced as executable.
DOCUMENTATION_ONLY_CLAIM	Documentation or client contract claims behavior without verified backend evidence.
CONFLICT_REQUIRES_CANONICALIZATION	Sources disagree and no final owner has been established.
REQUIRES_REPOSITORY_REVIEW	Necessary executable evidence has not yet been inspected.

Scenario Simulator — Identity, Session, Authorization, and Trust Boundaries

Metadata	Value
Volume	4
Chapter ID	V04-P12-02
Subject	ScenarioSimulatorAccessModel
Status	Generated First-Draft Architecture Skeleton - Domain-Specific Expansion Required
Content maturity	TEMPLATE_DERIVED_REFERENCE_SKELETON unless repository citations prove otherwise
Default implementation classification	REFERENCE_ARCHITECTURE / REQUIRES_REPOSITORY_REVIEW
Accountable owner	Portal Architecture / Scenario Simulator
Evidence rule	No implementation claim without inspected executable evidence
Repository	chinair88-prog/allinb2c

1. Executive Orientation

This chapter defines how GTOS shall **govern login, session, role, relationship, tenant, facility, channel, delegation, impersonation and privileged action for planners, analysts and executives, covering assumptions, scenarios, simulations, sensitivity, comparison, Decision support.**

The specification separates reality, observations, knowledge, Decisions, Intent, execution, and outcomes. A component name, database row, UI label, AI answer, or workflow state does not acquire authority merely because it is visible or technically convenient.

Reality or external outcome

- ≠ Observation
- ≠ Claim
- ≠ derived Perspective
- ≠ Prediction
- ≠ Recommendation
- ≠ authorized Decision
- ≠ execution Intent

1.1 Accountable ownership

The accountable owner is **Portal Architecture / Scenario Simulator**. Supporting applications, shared infrastructure, integration adapters, analytics, and AI coordinate or present the capability but shall not silently own its authoritative propositions.

1.2 Scope

- create and identify the subject
- validate evidence and policy
- make authorized Decisions
- execute typed Commands
- publish completed-fact Events
- query current and historical perspectives
- correct and reconcile outcomes

1.3 Non-goals

- treating a registered Gradle module, catalog record, README, frontend route, migration plan, or generated report as proof of end-to-end implementation;
- direct cross-Domain database writes;
- generic status values that combine lifecycle, approval, provider, document, payment, dispute, and correction state;
- silent replacement of history;
- AI-created authority or fabricated external outcomes.

2. Ubiquitous Language and Subject Model

Subject	Required interpretation
ScenarioSimulatorAccessModel	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit
ScenarioSimulatorAccessModelVersion	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit
ScenarioSimulatorAccessModelDecision	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit
ScenarioSimulatorAccessModelEvidenceSet	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit
ScenarioSimulatorAccessModelException	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit

Reference aggregate:

```
ScenarioSimulatorAccessModel {
  subjectId
  tenantId
  organizationContext
  sourceIdentityRefs[]
  sourceVersionRefs[]
  lifecycleState
  relationshipRefs[]
  decisionRefs[]
  intentRefs[]
  evidenceSetRef
  knowledgeCutoff
  policyRefs[]
  authorityRef
  jurisdictionRefs[]
  createdAt
  effectiveAt
  updatedAt
  version
  correctionOf?
  correlationId
}
```

2.1 Core invariants

- Stable identity precedes relationship, state, and cross-system correlation.
- Effective time and recorded time remain distinct where business truth changes over time.
- Recommendation, Decision, Intent, execution, and outcome are separate concepts.
- No Portal, report, search index, cache, workflow, or AI Agent becomes a shadow owner of Domain truth.
- Binding submitted, approved, issued, accepted, or signed versions are immutable.
- Corrections append governed facts and preserve the original record.
- External authority and provider outcomes retain their source and qualification.
- Tenant and represented-principal context come from trusted authentication and mandate evaluation.
- Retried writes are idempotent and concurrency guarded.
- Outcome Unknown is explicit and reconciled before risky duplicate execution.

2.2 Required standards

- stable identifiers
- typed contracts
- immutable binding versions

- transactional outbox
- idempotent Commands
- explicit Outcome Unknown
- correction lineage
- machine-verifiable conformance

3. Actors, Roles, and Authority

- A conformant design distinguishes:
- the natural person acting;
 - the service or AI identity invoking a Tool;
 - the organization or principal represented;
 - the role or relationship granting context;
 - the mandate or delegation granting action authority;
 - the Policy and jurisdiction limiting the action;
 - the reviewer or approver responsible for a binding Decision.

Authority is evaluated at action time. Authentication alone does not grant business authority. Cached permissions and browser-supplied tenant headers are insufficient for high-impact actions.

4. Lifecycle and State Model

State	Semantics
PROPOSED	Distinct governed condition with entry, exit, timeout, correction and authority semantics
VALIDATION_PENDING	Distinct governed condition with entry, exit, timeout, correction and authority semantics
APPROVAL_PENDING	Distinct governed condition with entry, exit, timeout, correction and authority semantics
ACTIVE	Distinct governed condition with entry, exit, timeout, correction and authority semantics
SUSPENDED	Distinct governed condition with entry, exit, timeout, correction and authority semantics
CORRECTION_PENDING	Distinct governed condition with entry, exit, timeout, correction and authority semantics
RETIRED	Distinct governed condition with entry, exit, timeout, correction and authority semantics

```
stateDiagram-v2
    [*] --> PROPOSED
    PROPOSED --> VALIDATION_PENDING
    VALIDATION_PENDING --> APPROVAL_PENDING
    APPROVAL_PENDING --> ACTIVE
    ACTIVE --> SUSPENDED
    SUSPENDED --> CORRECTION_PENDING
    CORRECTION_PENDING --> RETIRED
```

The diagram is a primary reading path. Real implementations may add parallel review, amendment, appeal, timeout, suspension, partial completion, reconciliation, correction, and terminal failure without collapsing their meaning.

4.1 Transition rules

- transition through a typed, authorized Command;
- require exact expected version where concurrent change matters;
- record actor, represented principal, mandate, Policy, reason, and Evidence;
- use an idempotency key for retried writes;
- publish a completed-fact Event after durable state change;
- expose Outcome Unknown for unresolved external completion;
- preserve original and corrected states in historical reconstruction.

5. Decision, Evidence, and Knowledge Cutoff

Reference Decision:

```
Decision {
  decisionId
  decisionType
  subjectRef
  sourceVersionRefs[]
  knowledgeCutoff
  evidenceSetRef
  policyVersionRefs[]
  recommendationRefs[]
  principalId
  representedOrganizationId
  mandateRef
  rationale
  outcome
  decidedAt
  effectiveAt
  correctionOf?
}
```

Evidence records identify issuer or observer, subject, version, observed time, received time, effective interval, integrity, confidence, qualification, contradiction, correction, retention, residency, and access class. A recommendation may assist the Decision but cannot promote itself to the Decision.

6. Commands, Events, Queries, and Contracts

Reference Commands:

- CreateScenarioSimulatorAccessModel
- ValidateScenarioSimulatorAccessModel
- ApproveScenarioSimulatorAccessModel
- ActivateScenarioSimulatorAccessModel
- SuspendScenarioSimulatorAccessModel
- CorrectScenarioSimulatorAccessModel
- RetireScenarioSimulatorAccessModel

Reference Events:

- ScenarioSimulatorAccessModelCreated
- ScenarioSimulatorAccessModelValidated
- ScenarioSimulatorAccessModelApproved
- ScenarioSimulatorAccessModelActivated
- ScenarioSimulatorAccessModelSuspended
- ScenarioSimulatorAccessModelCorrected
- ScenarioSimulatorAccessModelRetired

Reference queries:

- GetScenarioSimulatorAccessModel
- ListScenarioSimulatorAccessModelRecords
- GetScenarioSimulatorAccessModelTimeline
- GetScenarioSimulatorAccessModelEvidence
- GetScenarioSimulatorAccessModelDecisionPackage
- GetScenarioSimulatorAccessModelExceptions
- GetScenarioSimulatorAccessModelAuditTrail

Reference API surface:

```
POST /api/v1/scenariosimulatoraccessmodel/commands
GET  /api/v1/scenariosimulatoraccessmodel/{id}
GET  /api/v1/scenariosimulatoraccessmodel/{id}/timeline
GET  /api/v1/scenariosimulatoraccessmodel/{id}/evidence
GET  /api/v1/scenariosimulatoraccessmodel/{id}/decisions
POST /api/v1/scenariosimulatoraccessmodel/{id}/exceptions
POST /api/v1/scenariosimulatoraccessmodel/{id}/corrections
```

These endpoints are reference contracts, not claims that exact routes exist.

7. Workflow, Failure, and Compensation

```
flowchart TD
    A[Validate identity version and authority] --> B[Collect required evidence]
    B --> C{Policy and evidence gates pass?}
    C -- No --> D[Open exception or request correction]
    D --> B
    C -- Yes --> E[Record Decision or execution Intent]
    E --> F[Execute Domain command or external request]
    F --> G{Outcome known?}
    G -- Success --> H[Record fact and publish Event]
    G -- Failure --> I[Record failure and compensation options]
    G -- Unknown --> J[Enter Outcome Unknown]
    J --> K[Query source or wait for verified callback]
    K --> G
    H --> L[Update projections and downstream workflow]
```

Representative failure modes:

- stale or wrong source version
- duplicate submission or replay
- external timeout after possible success
- contradictory source observations
- lost Event after committed state
- approval or mandate revoked during execution
- downstream action before a mandatory gate
- partial completion across multiple subjects
- evidence later retracted or corrected
- tenant, facility, channel or jurisdiction mismatch

Recovery shall query the authoritative source before duplicate execution, preserve partial success, use compensating Intent rather than destructive rewrite, publish corrections, quarantine high-impact ambiguity, and record affected downstream subjects.

8. Data and Persistence Architecture

Reference table families:

Table family	Purpose
scenariosimulatoraccessmodel_aggregate	authoritative subject
scenariosimulatoraccessmodel_version	immutable submitted, approved, issued, or signed versions
scenariosimulatoraccessmodel_relationship	governed relationships
scenariosimulatoraccessmodel_decision	binding Decisions and rationale
scenariosimulatoraccessmodel_evidence_link	provenance and evidence relationships
scenariosimulatoraccessmodel_event_outbox	transactional Event publication
scenariosimulatoraccessmodel_idempotency	duplicate-write protection
scenariosimulatoraccessmodel_exception	exception, claim, dispute, or hold
scenariosimulatoraccessmodel_correction	correction and supersession lineage
scenariosimulatoraccessmodel_audit	privileged action evidence

The owning service controls schema and migration. Cross-Domain references use stable identifiers or contracts. Analytics, reports, caches, search, and vector indexes remain projections. Backup, restore, retention, legal hold, privacy, residency, and decommissioning requirements are explicit.

9. Portal and Experience Requirements

- Scenario Simulator: primary experience for planners, analysts and executives.
- Operator and support views: diagnose failed or ambiguous journeys without assuming Domain ownership.
- Domain services: own authoritative data and action eligibility; the Portal consumes typed contracts.

Every Portal displays exact version, owner, state, freshness, required action, and uncertainty. It supports loading, empty, partial, stale, denied, error, timeout, and Outcome Unknown states; accessibility; locale, currency, unit, date, and RTL/LTR correctness; evidence audit; safe retry; and correction history.

10. AI Participation and Tool Governance

Permitted AI tasks:

- extract and classify evidence
- detect anomalies and missing fields
- summarize timelines and contradictions
- recommend next actions with sources and uncertainty

AI shall not own Domain records, grant itself authority, suppress contradictions, silently edit approved versions, fabricate external outcomes, or execute high-impact actions outside typed Tools, policy, approval, idempotency, sandbox, and outcome observation.

Every Agent Run records source context, prompt/model/tool versions, structured output, confidence and limitations, Policy result, approval, Tool calls, provider responses, final outcome, and recovery actions.

11. Security, Privacy, and Trust Boundaries

- least privilege and separation of duties
- tenant, organization, facility, channel and jurisdiction isolation
- integrity protection for binding evidence
- verified external callbacks and anti-replay controls

Additional controls include secret isolation, callback signature verification, audit of privileged action, emergency-access review, sensitive-data minimization, purpose limitation, and threat models for impersonation, tampering, replay, confused deputy, fraud, prompt injection, and exfiltration.

12. Reliability, SLOs, and Operations

SLI	Reference objective
authoritative read availability	99.9% monthly unless a stricter tier applies
acknowledged Command durability	no acknowledged write may be silently lost
Event publication	99.9% within five minutes after committed fact
duplicate prevention	100% for same tenant, Command class, and idempotency key
binding Decision audit completeness	100%
state-state detection	bounded by business deadline

Dashboards and runbooks cover backlog, error budget, dependency failure, retry budget, DLQ, workflow stall, provider outage, reconciliation, capacity, backup/restore, release/rollback, incident command, and post-incident correction.

13. Testing and Continuous Conformance

- aggregate invariant and transition tests
- authorization, delegation, separation-of-duties and tenant-isolation tests
- idempotency and optimistic-concurrency tests
- database migration, key, constraint and rollback tests
- contract, outbox/inbox, duplicate, replay and DLQ tests
- workflow restart, timeout and compensation tests
- Portal E2E tests for success, partial, stale, denied, error and Outcome Unknown states
- accessibility, locale, currency, unit and RTL/LTR tests
- security adversarial, fraud and data-exfiltration tests
- AI evaluation, prompt-injection, policy-bypass and unauthorized-tool tests
- historical reconstruction, correction and audit-completeness tests
- performance, capacity, recovery and operational exercise tests

Release evidence links each invariant and control to the test, environment, input data, result, owner, and artifact proving it. Generated test counts never replace semantic coverage.

14. Repository Review Boundary

- This chapter is a repository-review specification. Exact executable implementation has not been inspected for every target behavior.
- Registered modules, catalog entries, README claims, frontend contracts, or plans are not proof of complete implementation.

Area	Classification
target aggregate, API, tables, state and workflow in this chapter	REFERENCE_ARCHITECTURE
registered module or catalog claim	DOCUMENTATION_ONLY_CLAIM until source inspection
uninspected integration	REQUIRES_REPOSITORY_REVIEW
behavior proven in another repository-grounded chapter	retain that chapter's evidence and classification
contradictory ownership or path claims	CONFLICT_REQUIRES_CANONICALIZATION

No statement upgrades implementation status merely because a file, directory, module name, frontend contract, database entry, plan, or report exists.

15. Worked Conformance Scenario

An authorized principal initiates a Command against an exact subject version. The service validates identity, tenant, mandate, Policy, Evidence, and idempotency. It records the state transition and outbox entry atomically. If an external dependency participates, timeout produces Outcome Unknown; reconciliation queries the source or waits for a verified callback instead of repeating the action blindly.

Portals show source, freshness, version, required action, and uncertainty. AI may extract, compare, summarize, detect anomalies, and recommend through typed Tools, but cannot own the subject or fabricate success. Later correction appends new facts, identifies affected projections and workflows, and preserves the historical Decision context.

16. Conformance Checklist

- ☐ stable identity and proposition ownership are explicit;
- ☐ authority and mandate are evaluated at action time;
- ☐ state, Recommendation, Decision, Intent, execution, and outcome remain distinct;
- ☐ Commands are typed, authorized, idempotent, and version guarded;
- ☐ Events describe completed facts;
- ☐ Evidence includes provenance, time, integrity, qualification, and correction;
- ☐ external outcomes retain their authority source;
- ☐ Portals show freshness and uncertainty;
- ☐ AI is bounded by typed Tools, Policy, approval, and outcome observation;
- ☐ security, tenant, facility, channel, and jurisdiction boundaries are enforced;
- ☐ Outcome Unknown and reconciliation exist where needed;
- ☐ corrections preserve history;
- ☐ tests prove invariants and recovery;
- ☐ implementation status is not upgraded without executable evidence.

17. Status Vocabulary

Status	Meaning
VERIFIED_IMPLEMENTED	Executable source and relevant behavior were inspected.
IMPLEMENTED_WITH_GAP	Executable behavior exists with a material governance or completeness gap.
PARTIAL_IMPLEMENTATION	Only part of the target capability is evidenced.
REFERENCE_ARCHITECTURE	Normative target behavior; no claim that it exists today.
PLANNED_NOT_IMPLEMENTED	Explicitly planned but not evidenced as executable.
DOCUMENTATION_ONLY_CLAIM	Documentation or client contract claims behavior without verified backend evidence.
CONFLICT_REQUIRES_CANONICALIZATION	Sources disagree and no final owner has been established.
REQUIRES_REPOSITORY_REVIEW	Necessary executable evidence has not yet been inspected.

Scenario Simulator — UX States, Accessibility, Localization, Analytics, and E2E

Metadata	Value
Volume	4
Chapter ID	V04-P12-03
Subject	ScenarioSimulatorExperienceStandard
Status	Generated First-Draft Architecture Skeleton - Domain-Specific Expansion Required
Content maturity	TEMPLATE_DERIVED_REFERENCE_SKELETON unless repository citations prove otherwise
Default implementation classification	REFERENCE_ARCHITECTURE / REQUIRES_REPOSITORY_REVIEW
Accountable owner	Portal Architecture / Scenario Simulator
Evidence rule	No implementation claim without inspected executable evidence
Repository	chinair88-prog/allinb2c

1. Executive Orientation

This chapter defines how GTOS shall **specify loading, empty, partial, stale, error, denied, offline, accessibility, RTL/LTR, analytics, audit and test journeys for planners, analysts and executives, covering assumptions, scenarios, simulations, sensitivity, comparison, Decision support.**

The specification separates reality, observations, knowledge, Decisions, Intent, execution, and outcomes. A component name, database row, UI label, AI answer, or workflow state does not acquire authority merely because it is visible or technically convenient.

Reality or external outcome

- ≠ Observation
- ≠ Claim
- ≠ derived Perspective
- ≠ Prediction
- ≠ Recommendation
- ≠ authorized Decision
- ≠ execution Intent

1.1 Accountable ownership

The accountable owner is **Portal Architecture / Scenario Simulator**. Supporting applications, shared infrastructure, integration adapters, analytics, and AI coordinate or present the capability but shall not silently own its authoritative propositions.

1.2 Scope

- create and identify the subject
- validate evidence and policy
- make authorized Decisions
- execute typed Commands
- publish completed-fact Events
- query current and historical perspectives
- correct and reconcile outcomes

1.3 Non-goals

- treating a registered Gradle module, catalog record, README, frontend route, migration plan, or generated report as proof of end-to-end implementation;
- direct cross-Domain database writes;
- generic status values that combine lifecycle, approval, provider, document, payment, dispute, and correction state;
- silent replacement of history;
- AI-created authority or fabricated external outcomes.

2. Ubiquitous Language and Subject Model

Subject	Required interpretation
ScenarioSimulatorExperienceStandard	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit
ScenarioSimulatorExperienceStandardVersion	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit
ScenarioSimulatorExperienceStandardDecision	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit
ScenarioSimulatorExperienceStandardEvidenceSet	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit
ScenarioSimulatorExperienceStandardException	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit

Reference aggregate:

```
ScenarioSimulatorExperienceStandard {
  subjectId
  tenantId
  organizationContext
  sourceIdentityRefs[]
  sourceVersionRefs[]
  lifecycleState
  relationshipRefs[]
  decisionRefs[]
  intentRefs[]
  evidenceSetRef
  knowledgeCutoff
  policyRefs[]
  authorityRef
  jurisdictionRefs[]
  createdAt
  effectiveAt
  updatedAt
  version
  correctionOf?
  correlationId
}
```

2.1 Core invariants

- Stable identity precedes relationship, state, and cross-system correlation.
- Effective time and recorded time remain distinct where business truth changes over time.
- Recommendation, Decision, Intent, execution, and outcome are separate concepts.
- No Portal, report, search index, cache, workflow, or AI Agent becomes a shadow owner of Domain truth.
- Binding submitted, approved, issued, accepted, or signed versions are immutable.
- Corrections append governed facts and preserve the original record.
- External authority and provider outcomes retain their source and qualification.
- Tenant and represented-principal context come from trusted authentication and mandate evaluation.
- Retried writes are idempotent and concurrency guarded.
- Outcome Unknown is explicit and reconciled before risky duplicate execution.

2.2 Required standards

- stable identifiers
- typed contracts
- immutable binding versions

- transactional outbox
- idempotent Commands
- explicit Outcome Unknown
- correction lineage
- machine-verifiable conformance

3. Actors, Roles, and Authority

- A conformant design distinguishes:
- the natural person acting;
 - the service or AI identity invoking a Tool;
 - the organization or principal represented;
 - the role or relationship granting context;
 - the mandate or delegation granting action authority;
 - the Policy and jurisdiction limiting the action;
 - the reviewer or approver responsible for a binding Decision.

Authority is evaluated at action time. Authentication alone does not grant business authority. Cached permissions and browser-supplied tenant headers are insufficient for high-impact actions.

4. Lifecycle and State Model

State	Semantics
PROPOSED	Distinct governed condition with entry, exit, timeout, correction and authority semantics
VALIDATION_PENDING	Distinct governed condition with entry, exit, timeout, correction and authority semantics
APPROVAL_PENDING	Distinct governed condition with entry, exit, timeout, correction and authority semantics
ACTIVE	Distinct governed condition with entry, exit, timeout, correction and authority semantics
SUSPENDED	Distinct governed condition with entry, exit, timeout, correction and authority semantics
CORRECTION_PENDING	Distinct governed condition with entry, exit, timeout, correction and authority semantics
RETIRED	Distinct governed condition with entry, exit, timeout, correction and authority semantics

```
stateDiagram-v2
    [*] --> PROPOSED
    PROPOSED --> VALIDATION_PENDING
    VALIDATION_PENDING --> APPROVAL_PENDING
    APPROVAL_PENDING --> ACTIVE
    ACTIVE --> SUSPENDED
    SUSPENDED --> CORRECTION_PENDING
    CORRECTION_PENDING --> RETIRED
```

The diagram is a primary reading path. Real implementations may add parallel review, amendment, appeal, timeout, suspension, partial completion, reconciliation, correction, and terminal failure without collapsing their meaning.

4.1 Transition rules

- transition through a typed, authorized Command;
- require exact expected version where concurrent change matters;
- record actor, represented principal, mandate, Policy, reason, and Evidence;
- use an idempotency key for retried writes;
- publish a completed-fact Event after durable state change;
- expose Outcome Unknown for unresolved external completion;
- preserve original and corrected states in historical reconstruction.

5. Decision, Evidence, and Knowledge Cutoff

Reference Decision:

```
Decision {
  decisionId
  decisionType
  subjectRef
  sourceVersionRefs[]
  knowledgeCutoff
  evidenceSetRef
  policyVersionRefs[]
  recommendationRefs[]
  principalId
  representedOrganizationId
  mandateRef
  rationale
  outcome
  decidedAt
  effectiveAt
  correctionOf?
}
```

Evidence records identify issuer or observer, subject, version, observed time, received time, effective interval, integrity, confidence, qualification, contradiction, correction, retention, residency, and access class. A recommendation may assist the Decision but cannot promote itself to the Decision.

6. Commands, Events, Queries, and Contracts

Reference Commands:

- CreateScenarioSimulatorExperienceStandard
- ValidateScenarioSimulatorExperienceStandard
- ApproveScenarioSimulatorExperienceStandard
- ActivateScenarioSimulatorExperienceStandard
- SuspendScenarioSimulatorExperienceStandard
- CorrectScenarioSimulatorExperienceStandard
- RetireScenarioSimulatorExperienceStandard

Reference Events:

- ScenarioSimulatorExperienceStandardCreated
- ScenarioSimulatorExperienceStandardValidated
- ScenarioSimulatorExperienceStandardApproved
- ScenarioSimulatorExperienceStandardActivated
- ScenarioSimulatorExperienceStandardSuspended
- ScenarioSimulatorExperienceStandardCorrected
- ScenarioSimulatorExperienceStandardRetired

Reference queries:

- GetScenarioSimulatorExperienceStandard
- ListScenarioSimulatorExperienceStandardRecords
- GetScenarioSimulatorExperienceStandardTimeline
- GetScenarioSimulatorExperienceStandardEvidence
- GetScenarioSimulatorExperienceStandardDecisionPackage
- GetScenarioSimulatorExperienceStandardExceptions
- GetScenarioSimulatorExperienceStandardAuditTrail

Reference API surface:

```
POST /api/v1/scenariosimulatorexperiencstandard/commands
GET  /api/v1/scenariosimulatorexperiencstandard/{id}
GET  /api/v1/scenariosimulatorexperiencstandard/{id}/timeline
GET  /api/v1/scenariosimulatorexperiencstandard/{id}/evidence
GET  /api/v1/scenariosimulatorexperiencstandard/{id}/decisions
POST /api/v1/scenariosimulatorexperiencstandard/{id}/exceptions
POST /api/v1/scenariosimulatorexperiencstandard/{id}/corrections
```

These endpoints are reference contracts, not claims that exact routes exist.

7. Workflow, Failure, and Compensation

```
flowchart TD
    A[Validate identity version and authority] --> B[Collect required evidence]
    B --> C{Policy and evidence gates pass?}
    C -- No --> D[Open exception or request correction]
    D --> B
    C -- Yes --> E[Record Decision or execution Intent]
    E --> F[Execute Domain command or external request]
    F --> G{Outcome known?}
    G -- Success --> H[Record fact and publish Event]
    G -- Failure --> I[Record failure and compensation options]
    G -- Unknown --> J[Enter Outcome Unknown]
    J --> K[Query source or wait for verified callback]
    K --> G
    H --> L[Update projections and downstream workflow]
```

Representative failure modes:

- stale or wrong source version
- duplicate submission or replay
- external timeout after possible success
- contradictory source observations
- lost Event after committed state
- approval or mandate revoked during execution
- downstream action before a mandatory gate
- partial completion across multiple subjects
- evidence later retracted or corrected
- tenant, facility, channel or jurisdiction mismatch

Recovery shall query the authoritative source before duplicate execution, preserve partial success, use compensating Intent rather than destructive rewrite, publish corrections, quarantine high-impact ambiguity, and record affected downstream subjects.

8. Data and Persistence Architecture

Reference table families:

Table family	Purpose
scenariosimulatorexperiencestandard_aggregate	authoritative subject
scenariosimulatorexperiencestandard_version	immutable submitted, approved, issued, or signed versions
scenariosimulatorexperiencestandard_relationship	governed relationships
scenariosimulatorexperiencestandard_decision	binding Decisions and rationale
scenariosimulatorexperiencestandard_evidence_link	provenance and evidence relationships
scenariosimulatorexperiencestandard_event_outbox	transactional Event publication
scenariosimulatorexperiencestandard_idempotency	duplicate-write protection
scenariosimulatorexperiencestandard_exception	exception, claim, dispute, or hold
scenariosimulatorexperiencestandard_correction	correction and supersession lineage
scenariosimulatorexperiencestandard_audit	privileged action evidence

The owning service controls schema and migration. Cross-Domain references use stable identifiers or contracts. Analytics, reports, caches, search, and vector indexes remain projections. Backup, restore, retention, legal hold, privacy, residency, and decommissioning requirements are explicit.

9. Portal and Experience Requirements

- Scenario Simulator: primary experience for planners, analysts and executives.
- Operator and support views: diagnose failed or ambiguous journeys without assuming Domain ownership.
- Domain services: own authoritative data and action eligibility; the Portal consumes typed contracts.

Every Portal displays exact version, owner, state, freshness, required action, and uncertainty. It supports loading, empty, partial, stale, denied, error, timeout, and Outcome Unknown states; accessibility; locale, currency, unit, date, and RTL/LTR correctness; evidence audit; safe retry; and correction history.

10. AI Participation and Tool Governance

Permitted AI tasks:

- extract and classify evidence
- detect anomalies and missing fields
- summarize timelines and contradictions
- recommend next actions with sources and uncertainty

AI shall not own Domain records, grant itself authority, suppress contradictions, silently edit approved versions, fabricate external outcomes, or execute high-impact actions outside typed Tools, policy, approval, idempotency, sandbox, and outcome observation.

Every Agent Run records source context, prompt/model/tool versions, structured output, confidence and limitations, Policy result, approval, Tool calls, provider responses, final outcome, and recovery actions.

11. Security, Privacy, and Trust Boundaries

- least privilege and separation of duties
- tenant, organization, facility, channel and jurisdiction isolation
- integrity protection for binding evidence
- verified external callbacks and anti-replay controls

Additional controls include secret isolation, callback signature verification, audit of privileged action, emergency-access review, sensitive-data minimization, purpose limitation, and threat models for impersonation, tampering, replay, confused deputy, fraud, prompt injection, and exfiltration.

12. Reliability, SLOs, and Operations

SLI	Reference objective
authoritative read availability	99.9% monthly unless a stricter tier applies
acknowledged Command durability	no acknowledged write may be silently lost
Event publication	99.9% within five minutes after committed fact
duplicate prevention	100% for same tenant, Command class, and idempotency key
binding Decision audit completeness	100%
state-state detection	bounded by business deadline

Dashboards and runbooks cover backlog, error budget, dependency failure, retry budget, DLQ, workflow stall, provider outage, reconciliation, capacity, backup/restore, release/rollback, incident command, and post-incident correction.

13. Testing and Continuous Conformance

- aggregate invariant and transition tests
- authorization, delegation, separation-of-duties and tenant-isolation tests
- idempotency and optimistic-concurrency tests
- database migration, key, constraint and rollback tests
- contract, outbox/inbox, duplicate, replay and DLQ tests
- workflow restart, timeout and compensation tests
- Portal E2E tests for success, partial, stale, denied, error and Outcome Unknown states
- accessibility, locale, currency, unit and RTL/LTR tests
- security adversarial, fraud and data-exfiltration tests
- AI evaluation, prompt-injection, policy-bypass and unauthorized-tool tests
- historical reconstruction, correction and audit-completeness tests
- performance, capacity, recovery and operational exercise tests

Release evidence links each invariant and control to the test, environment, input data, result, owner, and artifact proving it. Generated test counts never replace semantic coverage.

14. Repository Review Boundary

- This chapter is a repository-review specification. Exact executable implementation has not been inspected for every target behavior.
- Registered modules, catalog entries, README claims, frontend contracts, or plans are not proof of complete implementation.

Area	Classification
target aggregate, API, tables, state and workflow in this chapter	REFERENCE_ARCHITECTURE
registered module or catalog claim	DOCUMENTATION_ONLY_CLAIM until source inspection
uninspected integration	REQUIRES_REPOSITORY_REVIEW
behavior proven in another repository-grounded chapter	retain that chapter's evidence and classification
contradictory ownership or path claims	CONFLICT_REQUIRES_CANONICALIZATION

No statement upgrades implementation status merely because a file, directory, module name, frontend contract, database entry, plan, or report exists.

15. Worked Conformance Scenario

An authorized principal initiates a Command against an exact subject version. The service validates identity, tenant, mandate, Policy, Evidence, and idempotency. It records the state transition and outbox entry atomically. If an external dependency participates, timeout produces Outcome Unknown; reconciliation queries the source or waits for a verified callback instead of repeating the action blindly.

Portals show source, freshness, version, required action, and uncertainty. AI may extract, compare, summarize, detect anomalies, and recommend through typed Tools, but cannot own the subject or fabricate success. Later correction appends new facts, identifies affected projections and workflows, and preserves the historical Decision context.

16. Conformance Checklist

- ☐ stable identity and proposition ownership are explicit;
- ☐ authority and mandate are evaluated at action time;
- ☐ state, Recommendation, Decision, Intent, execution, and outcome remain distinct;
- ☐ Commands are typed, authorized, idempotent, and version guarded;
- ☐ Events describe completed facts;
- ☐ Evidence includes provenance, time, integrity, qualification, and correction;
- ☐ external outcomes retain their authority source;
- ☐ Portals show freshness and uncertainty;
- ☐ AI is bounded by typed Tools, Policy, approval, and outcome observation;
- ☐ security, tenant, facility, channel, and jurisdiction boundaries are enforced;
- ☐ Outcome Unknown and reconciliation exist where needed;
- ☐ corrections preserve history;
- ☐ tests prove invariants and recovery;
- ☐ implementation status is not upgraded without executable evidence.

17. Status Vocabulary

Status	Meaning
VERIFIED_IMPLEMENTED	Executable source and relevant behavior were inspected. Executable behavior exists with a material governance or completeness gap.
IMPLEMENTED_WITH_GAP	
PARTIAL_IMPLEMENTATION	Only part of the target capability is evidenced.
REFERENCE_ARCHITECTURE	Normative target behavior; no claim that it exists today.
PLANNED_NOT_IMPLEMENTED	Explicitly planned but not evidenced as executable.
DOCUMENTATION_ONLY_CLAIM	Documentation or client contract claims behavior without verified backend evidence.
CONFLICT_REQUIRES_CANONICALIZATION	Sources disagree and no final owner has been established.
REQUIRES_REPOSITORY_REVIEW	Necessary executable evidence has not yet been inspected.

Mobile Applications — Portal Orientation and Information Architecture

Metadata	Value
Volume	4
Chapter ID	V04-P13-00
Subject	MobileApplicationsPortal
Status	Generated First-Draft Architecture Skeleton - Domain-Specific Expansion Required
Content maturity	TEMPLATE_DERIVED_REFERENCE_SKELETON unless repository citations prove otherwise
Default implementation classification	REFERENCE_ARCHITECTURE / REQUIRES_REPOSITORY_REVIEW
Accountable owner	Portal Architecture / Mobile Applications
Evidence rule	No implementation claim without inspected executable evidence
Repository	chinair88-prog/allinb2c

1. Executive Orientation

This chapter defines how GTOS shall **define personas, navigation, route ownership, domain dependencies and experience boundaries for customers, partners, providers, warehouse and field users, covering offline capture, notifications, scanning, evidence, approvals, tracking**.

The specification separates reality, observations, knowledge, Decisions, Intent, execution, and outcomes. A component name, database row, UI label, AI answer, or workflow state does not acquire authority merely because it is visible or technically convenient.

Reality or external outcome

- ≠ Observation
- ≠ Claim
- ≠ derived Perspective
- ≠ Prediction
- ≠ Recommendation
- ≠ authorized Decision
- ≠ execution Intent

1.1 Accountable ownership

The accountable owner is **Portal Architecture / Mobile Applications**. Supporting applications, shared infrastructure, integration adapters, analytics, and AI coordinate or present the capability but shall not silently own its authoritative propositions.

1.2 Scope

- create and identify the subject
- validate evidence and policy
- make authorized Decisions
- execute typed Commands
- publish completed-fact Events
- query current and historical perspectives
- correct and reconcile outcomes

1.3 Non-goals

- treating a registered Gradle module, catalog record, README, frontend route, migration plan, or generated report as proof of end-to-end implementation;
- direct cross-Domain database writes;
- generic status values that combine lifecycle, approval, provider, document, payment, dispute, and correction state;
- silent replacement of history;
- AI-created authority or fabricated external outcomes.

2. Ubiquitous Language and Subject Model

Subject	Required interpretation
MobileApplicationsPortal	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit
MobileApplicationsPortalVersion	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit
MobileApplicationsPortalDecision	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit
MobileApplicationsPortalEvidenceSet	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit
MobileApplicationsPortalException	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit

Reference aggregate:

```
MobileApplicationsPortal {
  subjectId
  tenantId
  organizationContext
  sourceIdentityRefs[]
  sourceVersionRefs[]
  lifecycleState
  relationshipRefs[]
  decisionRefs[]
  intentRefs[]
  evidenceSetRef
  knowledgeCutoff
  policyRefs[]
  authorityRef
  jurisdictionRefs[]
  createdAt
  effectiveAt
  updatedAt
  version
  correctionOf?
  correlationId
}
```

2.1 Core invariants

- Stable identity precedes relationship, state, and cross-system correlation.
- Effective time and recorded time remain distinct where business truth changes over time.
- Recommendation, Decision, Intent, execution, and outcome are separate concepts.
- No Portal, report, search index, cache, workflow, or AI Agent becomes a shadow owner of Domain truth.
- Binding submitted, approved, issued, accepted, or signed versions are immutable.
- Corrections append governed facts and preserve the original record.
- External authority and provider outcomes retain their source and qualification.
- Tenant and represented-principal context come from trusted authentication and mandate evaluation.
- Retried writes are idempotent and concurrency guarded.
- Outcome Unknown is explicit and reconciled before risky duplicate execution.

2.2 Required standards

- stable identifiers
- typed contracts
- immutable binding versions

- transactional outbox
- idempotent Commands
- explicit Outcome Unknown
- correction lineage
- machine-verifiable conformance

3. Actors, Roles, and Authority

A conformant design distinguishes:

- the natural person acting;
- the service or AI identity invoking a Tool;
- the organization or principal represented;
- the role or relationship granting context;
- the mandate or delegation granting action authority;
- the Policy and jurisdiction limiting the action;
- the reviewer or approver responsible for a binding Decision.

Authority is evaluated at action time. Authentication alone does not grant business authority. Cached permissions and browser-supplied tenant headers are insufficient for high-impact actions.

4. Lifecycle and State Model

State	Semantics
PROPOSED	Distinct governed condition with entry, exit, timeout, correction and authority semantics
VALIDATION_PENDING	Distinct governed condition with entry, exit, timeout, correction and authority semantics
APPROVAL_PENDING	Distinct governed condition with entry, exit, timeout, correction and authority semantics
ACTIVE	Distinct governed condition with entry, exit, timeout, correction and authority semantics
SUSPENDED	Distinct governed condition with entry, exit, timeout, correction and authority semantics
CORRECTION_PENDING	Distinct governed condition with entry, exit, timeout, correction and authority semantics
RETIRED	Distinct governed condition with entry, exit, timeout, correction and authority semantics

```
stateDiagram-v2
    [*] --> PROPOSED
    PROPOSED --> VALIDATION_PENDING
    VALIDATION_PENDING --> APPROVAL_PENDING
    APPROVAL_PENDING --> ACTIVE
    ACTIVE --> SUSPENDED
    SUSPENDED --> CORRECTION_PENDING
    CORRECTION_PENDING --> RETIRED
```

The diagram is a primary reading path. Real implementations may add parallel review, amendment, appeal, timeout, suspension, partial completion, reconciliation, correction, and terminal failure without collapsing their meaning.

4.1 Transition rules

- transition through a typed, authorized Command;
- require exact expected version where concurrent change matters;
- record actor, represented principal, mandate, Policy, reason, and Evidence;
- use an idempotency key for retried writes;
- publish a completed-fact Event after durable state change;
- expose Outcome Unknown for unresolved external completion;
- preserve original and corrected states in historical reconstruction.

5. Decision, Evidence, and Knowledge Cutoff

Reference Decision:

```
Decision {
  decisionId
  decisionType
  subjectRef
  sourceVersionRefs[]
  knowledgeCutoff
  evidenceSetRef
  policyVersionRefs[]
  recommendationRefs[]
  principalId
  representedOrganizationId
  mandateRef
  rationale
  outcome
  decidedAt
  effectiveAt
  correctionOf?
}
```

Evidence records identify issuer or observer, subject, version, observed time, received time, effective interval, integrity, confidence, qualification, contradiction, correction, retention, residency, and access class. A recommendation may assist the Decision but cannot promote itself to the Decision.

6. Commands, Events, Queries, and Contracts

Reference Commands:

- CreateMobileApplicationsPortal
- ValidateMobileApplicationsPortal
- ApproveMobileApplicationsPortal
- ActivateMobileApplicationsPortal
- SuspendMobileApplicationsPortal
- CorrectMobileApplicationsPortal
- RetireMobileApplicationsPortal

Reference Events:

- MobileApplicationsPortalCreated
- MobileApplicationsPortalValidated
- MobileApplicationsPortalApproved
- MobileApplicationsPortalActivated
- MobileApplicationsPortalSuspended
- MobileApplicationsPortalCorrected
- MobileApplicationsPortalRetired

Reference queries:

- GetMobileApplicationsPortal
- ListMobileApplicationsPortalRecords
- GetMobileApplicationsPortalTimeline
- GetMobileApplicationsPortalEvidence
- GetMobileApplicationsPortalDecisionPackage
- GetMobileApplicationsPortalExceptions
- GetMobileApplicationsPortalAuditTrail

Reference API surface:

```
POST /api/v1/mobileapplicationsportal/commands
GET  /api/v1/mobileapplicationsportal/{id}
GET  /api/v1/mobileapplicationsportal/{id}/timeline
GET  /api/v1/mobileapplicationsportal/{id}/evidence
GET  /api/v1/mobileapplicationsportal/{id}/decisions
POST /api/v1/mobileapplicationsportal/{id}/exceptions
POST /api/v1/mobileapplicationsportal/{id}/corrections
```

These endpoints are reference contracts, not claims that exact routes exist.

7. Workflow, Failure, and Compensation

flowchart TD

```
A[Validate identity version and authority] --> B[Collect required evidence]
B --> C{Policy and evidence gates pass?}
C -- No --> D[Open exception or request correction]
D --> B
C -- Yes --> E[Record Decision or execution Intent]
E --> F[Execute Domain command or external request]
F --> G{Outcome known?}
G -- Success --> H[Record fact and publish Event]
G -- Failure --> I[Record failure and compensation options]
G -- Unknown --> J[Enter Outcome Unknown]
J --> K[Query source or wait for verified callback]
K --> G
H --> L[Update projections and downstream workflow]
```

Representative failure modes:

- stale or wrong source version
- duplicate submission or replay
- external timeout after possible success
- contradictory source observations
- lost Event after committed state
- approval or mandate revoked during execution
- downstream action before a mandatory gate
- partial completion across multiple subjects
- evidence later retracted or corrected
- tenant, facility, channel or jurisdiction mismatch

Recovery shall query the authoritative source before duplicate execution, preserve partial success, use compensating Intent rather than destructive rewrite, publish corrections, quarantine high-impact ambiguity, and record affected downstream subjects.

8. Data and Persistence Architecture

Reference table families:

Table family	Purpose
mobileapplicationsportal_aggregate	authoritative subject
mobileapplicationsportal_version	immutable submitted, approved, issued, or signed versions
mobileapplicationsportal_relationship	governed relationships
mobileapplicationsportal_decision	binding Decisions and rationale
mobileapplicationsportal_evidence_link	provenance and evidence relationships
mobileapplicationsportal_event_outbox	transactional Event publication
mobileapplicationsportal_idempotency	duplicate-write protection
mobileapplicationsportal_exception	exception, claim, dispute, or hold
mobileapplicationsportal_correction	correction and supersession lineage
mobileapplicationsportal_audit	privileged action evidence

The owning service controls schema and migration. Cross-Domain references use stable identifiers or contracts. Analytics, reports, caches, search, and vector indexes remain projections. Backup, restore, retention, legal hold, privacy, residency, and decommissioning requirements are explicit.

9. Portal and Experience Requirements

- Mobile Applications: primary experience for customers, partners, providers, warehouse and field users.
- Operator and support views: diagnose failed or ambiguous journeys without assuming Domain ownership.
- Domain services: own authoritative data and action eligibility; the Portal consumes typed contracts.

Every Portal displays exact version, owner, state, freshness, required action, and uncertainty. It supports loading, empty, partial, stale, denied, error, timeout, and Outcome Unknown states; accessibility; locale, currency, unit, date, and RTL/LTR correctness; evidence audit; safe retry; and correction history.

10. AI Participation and Tool Governance

Permitted AI tasks:

- extract and classify evidence
- detect anomalies and missing fields
- summarize timelines and contradictions
- recommend next actions with sources and uncertainty

AI shall not own Domain records, grant itself authority, suppress contradictions, silently edit approved versions, fabricate external outcomes, or execute high-impact actions outside typed Tools, policy, approval, idempotency, sandbox, and outcome observation.

Every Agent Run records source context, prompt/model/tool versions, structured output, confidence and limitations, Policy result, approval, Tool calls, provider responses, final outcome, and recovery actions.

11. Security, Privacy, and Trust Boundaries

- least privilege and separation of duties
- tenant, organization, facility, channel and jurisdiction isolation
- integrity protection for binding evidence
- verified external callbacks and anti-replay controls

Additional controls include secret isolation, callback signature verification, audit of privileged action, emergency-access review, sensitive-data minimization, purpose limitation, and threat models for impersonation, tampering, replay, confused deputy, fraud, prompt injection, and exfiltration.

12. Reliability, SLOs, and Operations

SLI	Reference objective
authoritative read availability	99.9% monthly unless a stricter tier applies
acknowledged Command durability	no acknowledged write may be silently lost
Event publication	99.9% within five minutes after committed fact
duplicate prevention	100% for same tenant, Command class, and idempotency key
binding Decision audit completeness	100%
state-state detection	bounded by business deadline

Dashboards and runbooks cover backlog, error budget, dependency failure, retry budget, DLQ, workflow stall, provider outage, reconciliation, capacity, backup/restore, release/rollback, incident command, and post-incident correction.

13. Testing and Continuous Conformance

- aggregate invariant and transition tests
- authorization, delegation, separation-of-duties and tenant-isolation tests
- idempotency and optimistic-concurrency tests
- database migration, key, constraint and rollback tests
- contract, outbox/inbox, duplicate, replay and DLQ tests
- workflow restart, timeout and compensation tests
- Portal E2E tests for success, partial, stale, denied, error and Outcome Unknown states
- accessibility, locale, currency, unit and RTL/LTR tests
- security adversarial, fraud and data-exfiltration tests
- AI evaluation, prompt-injection, policy-bypass and unauthorized-tool tests
- historical reconstruction, correction and audit-completeness tests
- performance, capacity, recovery and operational exercise tests

Release evidence links each invariant and control to the test, environment, input data, result, owner, and artifact proving it. Generated test counts never replace semantic coverage.

14. Repository Review Boundary

- This chapter is a repository-review specification. Exact executable implementation has not been inspected for every target behavior.
- Registered modules, catalog entries, README claims, frontend contracts, or plans are not proof of complete implementation.

Area	Classification
target aggregate, API, tables, state and workflow in this chapter	REFERENCE_ARCHITECTURE
registered module or catalog claim	DOCUMENTATION_ONLY_CLAIM until source inspection
uninspected integration	REQUIRES_REPOSITORY_REVIEW
behavior proven in another repository-grounded chapter	retain that chapter's evidence and classification
contradictory ownership or path claims	CONFLICT_REQUIRES_CANONICALIZATION

No statement upgrades implementation status merely because a file, directory, module name, frontend contract, database entry, plan, or report exists.

15. Worked Conformance Scenario

An authorized principal initiates a Command against an exact subject version. The service validates identity, tenant, mandate, Policy, Evidence, and idempotency. It records the state transition and outbox entry atomically. If an external dependency participates, timeout produces Outcome Unknown; reconciliation queries the source or waits for a verified callback instead of repeating the action blindly.

Portals show source, freshness, version, required action, and uncertainty. AI may extract, compare, summarize, detect anomalies, and recommend through typed Tools, but cannot own the subject or fabricate success. Later correction appends new facts, identifies affected projections and workflows, and preserves the historical Decision context.

16. Conformance Checklist

- ☐ stable identity and proposition ownership are explicit;
- ☐ authority and mandate are evaluated at action time;
- ☐ state, Recommendation, Decision, Intent, execution, and outcome remain distinct;
- ☐ Commands are typed, authorized, idempotent, and version guarded;
- ☐ Events describe completed facts;
- ☐ Evidence includes provenance, time, integrity, qualification, and correction;
- ☐ external outcomes retain their authority source;
- ☐ Portals show freshness and uncertainty;
- ☐ AI is bounded by typed Tools, Policy, approval, and outcome observation;
- ☐ security, tenant, facility, channel, and jurisdiction boundaries are enforced;
- ☐ Outcome Unknown and reconciliation exist where needed;
- ☐ corrections preserve history;
- ☐ tests prove invariants and recovery;
- ☐ implementation status is not upgraded without executable evidence.

17. Status Vocabulary

Status	Meaning
VERIFIED_IMPLEMENTED	Executable source and relevant behavior were inspected.
IMPLEMENTED_WITH_GAP	Executable behavior exists with a material governance or completeness gap.
PARTIAL_IMPLEMENTATION	Only part of the target capability is evidenced.
REFERENCE_ARCHITECTURE	Normative target behavior; no claim that it exists today.
PLANNED_NOT_IMPLEMENTED	Explicitly planned but not evidenced as executable.
DOCUMENTATION_ONLY_CLAIM	Documentation or client contract claims behavior without verified backend evidence.
CONFLICT_REQUIRES_CANONICALIZATION	Sources disagree and no final owner has been established.
REQUIRES_REPOSITORY_REVIEW	Necessary executable evidence has not yet been inspected.

Mobile Applications — Routes, Pages, Components, and BFF Contracts

Metadata	Value
Volume	4
Chapter ID	V04-P13-01
Subject	MobileApplicationsRouteRegistry
Status	Generated First-Draft Architecture Skeleton - Domain-Specific Expansion Required
Content maturity	TEMPLATE_DERIVED_REFERENCE_SKELETON unless repository citations prove otherwise
Default implementation classification	REFERENCE_ARCHITECTURE / REQUIRES_REPOSITORY_REVIEW
Accountable owner	Portal Architecture / Mobile Applications
Evidence rule	No implementation claim without inspected executable evidence
Repository	chinair88-prog/allinb2c

1. Executive Orientation

This chapter defines how GTOS shall **inventory routes, layouts, pages, components, server/client boundaries, BFFs, APIs, realtime channels and ownership for customers, partners, providers, warehouse and field users, covering offline capture, notifications, scanning, evidence, approvals, tracking.**

The specification separates reality, observations, knowledge, Decisions, Intent, execution, and outcomes. A component name, database row, UI label, AI answer, or workflow state does not acquire authority merely because it is visible or technically convenient.

Reality or external outcome

- ≠ Observation
- ≠ Claim
- ≠ derived Perspective
- ≠ Prediction
- ≠ Recommendation
- ≠ authorized Decision
- ≠ execution Intent

1.1 Accountable ownership

The accountable owner is **Portal Architecture / Mobile Applications**. Supporting applications, shared infrastructure, integration adapters, analytics, and AI coordinate or present the capability but shall not silently own its authoritative propositions.

1.2 Scope

- create and identify the subject
- validate evidence and policy
- make authorized Decisions
- execute typed Commands
- publish completed-fact Events
- query current and historical perspectives
- correct and reconcile outcomes

1.3 Non-goals

- treating a registered Gradle module, catalog record, README, frontend route, migration plan, or generated report as proof of end-to-end implementation;
- direct cross-Domain database writes;
- generic status values that combine lifecycle, approval, provider, document, payment, dispute, and correction state;
- silent replacement of history;
- AI-created authority or fabricated external outcomes.

2. Ubiquitous Language and Subject Model

Subject	Required interpretation
MobileApplicationsRouteRegistry	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit
MobileApplicationsRouteRegistryVersion	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit
MobileApplicationsRouteRegistryDecision	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit
MobileApplicationsRouteRegistryEvidenceSet	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit
MobileApplicationsRouteRegistryException	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit

Reference aggregate:

```
MobileApplicationsRouteRegistry {
  subjectId
  tenantId
  organizationContext
  sourceIdentityRefs[]
  sourceVersionRefs[]
  lifecycleState
  relationshipRefs[]
  decisionRefs[]
  intentRefs[]
  evidenceSetRef
  knowledgeCutoff
  policyRefs[]
  authorityRef
  jurisdictionRefs[]
  createdAt
  effectiveAt
  updatedAt
  version
  correctionOf?
  correlationId
}
```

2.1 Core invariants

- Stable identity precedes relationship, state, and cross-system correlation.
- Effective time and recorded time remain distinct where business truth changes over time.
- Recommendation, Decision, Intent, execution, and outcome are separate concepts.
- No Portal, report, search index, cache, workflow, or AI Agent becomes a shadow owner of Domain truth.
- Binding submitted, approved, issued, accepted, or signed versions are immutable.
- Corrections append governed facts and preserve the original record.
- External authority and provider outcomes retain their source and qualification.
- Tenant and represented-principal context come from trusted authentication and mandate evaluation.
- Retried writes are idempotent and concurrency guarded.
- Outcome Unknown is explicit and reconciled before risky duplicate execution.

2.2 Required standards

- stable identifiers
- typed contracts
- immutable binding versions

- transactional outbox
- idempotent Commands
- explicit Outcome Unknown
- correction lineage
- machine-verifiable conformance

3. Actors, Roles, and Authority

A conformant design distinguishes:

- the natural person acting;
- the service or AI identity invoking a Tool;
- the organization or principal represented;
- the role or relationship granting context;
- the mandate or delegation granting action authority;
- the Policy and jurisdiction limiting the action;
- the reviewer or approver responsible for a binding Decision.

Authority is evaluated at action time. Authentication alone does not grant business authority. Cached permissions and browser-supplied tenant headers are insufficient for high-impact actions.

4. Lifecycle and State Model

State	Semantics
PROPOSED	Distinct governed condition with entry, exit, timeout, correction and authority semantics
VALIDATION_PENDING	Distinct governed condition with entry, exit, timeout, correction and authority semantics
APPROVAL_PENDING	Distinct governed condition with entry, exit, timeout, correction and authority semantics
ACTIVE	Distinct governed condition with entry, exit, timeout, correction and authority semantics
SUSPENDED	Distinct governed condition with entry, exit, timeout, correction and authority semantics
CORRECTION_PENDING	Distinct governed condition with entry, exit, timeout, correction and authority semantics
RETIRED	Distinct governed condition with entry, exit, timeout, correction and authority semantics

```
stateDiagram-v2
    [*] --> PROPOSED
    PROPOSED --> VALIDATION_PENDING
    VALIDATION_PENDING --> APPROVAL_PENDING
    APPROVAL_PENDING --> ACTIVE
    ACTIVE --> SUSPENDED
    SUSPENDED --> CORRECTION_PENDING
    CORRECTION_PENDING --> RETIRED
```

The diagram is a primary reading path. Real implementations may add parallel review, amendment, appeal, timeout, suspension, partial completion, reconciliation, correction, and terminal failure without collapsing their meaning.

4.1 Transition rules

- transition through a typed, authorized Command;
- require exact expected version where concurrent change matters;
- record actor, represented principal, mandate, Policy, reason, and Evidence;
- use an idempotency key for retried writes;
- publish a completed-fact Event after durable state change;
- expose Outcome Unknown for unresolved external completion;
- preserve original and corrected states in historical reconstruction.

5. Decision, Evidence, and Knowledge Cutoff

Reference Decision:

```
Decision {
  decisionId
  decisionType
  subjectRef
  sourceVersionRefs[]
  knowledgeCutoff
  evidenceSetRef
  policyVersionRefs[]
  recommendationRefs[]
  principalId
  representedOrganizationId
  mandateRef
  rationale
  outcome
  decidedAt
  effectiveAt
  correctionOf?
}
```

Evidence records identify issuer or observer, subject, version, observed time, received time, effective interval, integrity, confidence, qualification, contradiction, correction, retention, residency, and access class. A recommendation may assist the Decision but cannot promote itself to the Decision.

6. Commands, Events, Queries, and Contracts

Reference Commands:

- CreateMobileApplicationsRouteRegistry
- ValidateMobileApplicationsRouteRegistry
- ApproveMobileApplicationsRouteRegistry
- ActivateMobileApplicationsRouteRegistry
- SuspendMobileApplicationsRouteRegistry
- CorrectMobileApplicationsRouteRegistry
- RetireMobileApplicationsRouteRegistry

Reference Events:

- MobileApplicationsRouteRegistryCreated
- MobileApplicationsRouteRegistryValidated
- MobileApplicationsRouteRegistryApproved
- MobileApplicationsRouteRegistryActivated
- MobileApplicationsRouteRegistrySuspended
- MobileApplicationsRouteRegistryCorrected
- MobileApplicationsRouteRegistryRetired

Reference queries:

- GetMobileApplicationsRouteRegistry
- ListMobileApplicationsRouteRegistryRecords
- GetMobileApplicationsRouteRegistryTimeline
- GetMobileApplicationsRouteRegistryEvidence
- GetMobileApplicationsRouteRegistryDecisionPackage
- GetMobileApplicationsRouteRegistryExceptions
- GetMobileApplicationsRouteRegistryAuditTrail

Reference API surface:

```
POST /api/v1/mobileapplicationsrouteregistry/commands
GET  /api/v1/mobileapplicationsrouteregistry/{id}
GET  /api/v1/mobileapplicationsrouteregistry/{id}/timeline
GET  /api/v1/mobileapplicationsrouteregistry/{id}/evidence
GET  /api/v1/mobileapplicationsrouteregistry/{id}/decisions
POST /api/v1/mobileapplicationsrouteregistry/{id}/exceptions
POST /api/v1/mobileapplicationsrouteregistry/{id}/corrections
```

These endpoints are reference contracts, not claims that exact routes exist.

7. Workflow, Failure, and Compensation

flowchart TD

```
A[Validate identity version and authority] --> B[Collect required evidence]
B --> C{Policy and evidence gates pass?}
C -- No --> D[Open exception or request correction]
D --> B
C -- Yes --> E[Record Decision or execution Intent]
E --> F[Execute Domain command or external request]
F --> G{Outcome known?}
G -- Success --> H[Record fact and publish Event]
G -- Failure --> I[Record failure and compensation options]
G -- Unknown --> J[Enter Outcome Unknown]
J --> K[Query source or wait for verified callback]
K --> G
H --> L[Update projections and downstream workflow]
```

Representative failure modes:

- stale or wrong source version
- duplicate submission or replay
- external timeout after possible success
- contradictory source observations
- lost Event after committed state
- approval or mandate revoked during execution
- downstream action before a mandatory gate
- partial completion across multiple subjects
- evidence later retracted or corrected
- tenant, facility, channel or jurisdiction mismatch

Recovery shall query the authoritative source before duplicate execution, preserve partial success, use compensating Intent rather than destructive rewrite, publish corrections, quarantine high-impact ambiguity, and record affected downstream subjects.

8. Data and Persistence Architecture

Reference table families:

Table family	Purpose
mobileapplicationsrouterregistry_aggregate	authoritative subject
mobileapplicationsrouterregistry_version	immutable submitted, approved, issued, or signed versions
mobileapplicationsrouterregistry_relationship	governed relationships
mobileapplicationsrouterregistry_decision	binding Decisions and rationale
mobileapplicationsrouterregistry_evidence_link	provenance and evidence relationships
mobileapplicationsrouterregistry_event_outbox	transactional Event publication
mobileapplicationsrouterregistry_idempotency	duplicate-write protection
mobileapplicationsrouterregistry_exception	exception, claim, dispute, or hold
mobileapplicationsrouterregistry_correction	correction and supersession lineage
mobileapplicationsrouterregistry_audit	privileged action evidence

The owning service controls schema and migration. Cross-Domain references use stable identifiers or contracts. Analytics, reports, caches, search, and vector indexes remain projections. Backup, restore, retention, legal hold, privacy, residency, and decommissioning requirements are explicit.

9. Portal and Experience Requirements

- Mobile Applications: primary experience for customers, partners, providers, warehouse and field users.
- Operator and support views: diagnose failed or ambiguous journeys without assuming Domain ownership.
- Domain services: own authoritative data and action eligibility; the Portal consumes typed contracts.

Every Portal displays exact version, owner, state, freshness, required action, and uncertainty. It supports loading, empty, partial, stale, denied, error, timeout, and Outcome Unknown states; accessibility; locale, currency, unit, date, and RTL/LTR correctness; evidence audit; safe retry; and correction history.

10. AI Participation and Tool Governance

Permitted AI tasks:

- extract and classify evidence
- detect anomalies and missing fields
- summarize timelines and contradictions
- recommend next actions with sources and uncertainty

AI shall not own Domain records, grant itself authority, suppress contradictions, silently edit approved versions, fabricate external outcomes, or execute high-impact actions outside typed Tools, policy, approval, idempotency, sandbox, and outcome observation.

Every Agent Run records source context, prompt/model/tool versions, structured output, confidence and limitations, Policy result, approval, Tool calls, provider responses, final outcome, and recovery actions.

11. Security, Privacy, and Trust Boundaries

- least privilege and separation of duties
- tenant, organization, facility, channel and jurisdiction isolation
- integrity protection for binding evidence
- verified external callbacks and anti-replay controls

Additional controls include secret isolation, callback signature verification, audit of privileged action, emergency-access review, sensitive-data minimization, purpose limitation, and threat models for impersonation, tampering, replay, confused deputy, fraud, prompt injection, and exfiltration.

12. Reliability, SLOs, and Operations

SLI	Reference objective
authoritative read availability	99.9% monthly unless a stricter tier applies
acknowledged Command durability	no acknowledged write may be silently lost
Event publication	99.9% within five minutes after committed fact
duplicate prevention	100% for same tenant, Command class, and idempotency key
binding Decision audit completeness	100%
state-state detection	bounded by business deadline

Dashboards and runbooks cover backlog, error budget, dependency failure, retry budget, DLQ, workflow stall, provider outage, reconciliation, capacity, backup/restore, release/rollback, incident command, and post-incident correction.

13. Testing and Continuous Conformance

- aggregate invariant and transition tests
- authorization, delegation, separation-of-duties and tenant-isolation tests
- idempotency and optimistic-concurrency tests
- database migration, key, constraint and rollback tests
- contract, outbox/inbox, duplicate, replay and DLQ tests
- workflow restart, timeout and compensation tests
- Portal E2E tests for success, partial, stale, denied, error and Outcome Unknown states
- accessibility, locale, currency, unit and RTL/LTR tests
- security adversarial, fraud and data-exfiltration tests
- AI evaluation, prompt-injection, policy-bypass and unauthorized-tool tests
- historical reconstruction, correction and audit-completeness tests
- performance, capacity, recovery and operational exercise tests

Release evidence links each invariant and control to the test, environment, input data, result, owner, and artifact proving it. Generated test counts never replace semantic coverage.

14. Repository Review Boundary

- This chapter is a repository-review specification. Exact executable implementation has not been inspected for every target behavior.
- Registered modules, catalog entries, README claims, frontend contracts, or plans are not proof of complete implementation.

Area	Classification
target aggregate, API, tables, state and workflow in this chapter	REFERENCE_ARCHITECTURE
registered module or catalog claim	DOCUMENTATION_ONLY_CLAIM until source inspection
uninspected integration	REQUIRES_REPOSITORY_REVIEW
behavior proven in another repository-grounded chapter	retain that chapter's evidence and classification
contradictory ownership or path claims	CONFLICT_REQUIRES_CANONICALIZATION

No statement upgrades implementation status merely because a file, directory, module name, frontend contract, database entry, plan, or report exists.

15. Worked Conformance Scenario

An authorized principal initiates a Command against an exact subject version. The service validates identity, tenant, mandate, Policy, Evidence, and idempotency. It records the state transition and outbox entry atomically. If an external dependency participates, timeout produces Outcome Unknown; reconciliation queries the source or waits for a verified callback instead of repeating the action blindly.

Portals show source, freshness, version, required action, and uncertainty. AI may extract, compare, summarize, detect anomalies, and recommend through typed Tools, but cannot own the subject or fabricate success. Later correction appends new facts, identifies affected projections and workflows, and preserves the historical Decision context.

16. Conformance Checklist

- ☐ stable identity and proposition ownership are explicit;
- ☐ authority and mandate are evaluated at action time;
- ☐ state, Recommendation, Decision, Intent, execution, and outcome remain distinct;
- ☐ Commands are typed, authorized, idempotent, and version guarded;
- ☐ Events describe completed facts;
- ☐ Evidence includes provenance, time, integrity, qualification, and correction;
- ☐ external outcomes retain their authority source;
- ☐ Portals show freshness and uncertainty;
- ☐ AI is bounded by typed Tools, Policy, approval, and outcome observation;
- ☐ security, tenant, facility, channel, and jurisdiction boundaries are enforced;
- ☐ Outcome Unknown and reconciliation exist where needed;
- ☐ corrections preserve history;
- ☐ tests prove invariants and recovery;
- ☐ implementation status is not upgraded without executable evidence.

17. Status Vocabulary

Status	Meaning
VERIFIED_IMPLEMENTED	Executable source and relevant behavior were inspected.
IMPLEMENTED_WITH_GAP	Executable behavior exists with a material governance or completeness gap.
PARTIAL_IMPLEMENTATION	Only part of the target capability is evidenced.
REFERENCE_ARCHITECTURE	Normative target behavior; no claim that it exists today.
PLANNED_NOT_IMPLEMENTED	Explicitly planned but not evidenced as executable.
DOCUMENTATION_ONLY_CLAIM	Documentation or client contract claims behavior without verified backend evidence.
CONFLICT_REQUIRES_CANONICALIZATION	Sources disagree and no final owner has been established.
REQUIRES_REPOSITORY_REVIEW	Necessary executable evidence has not yet been inspected.

Mobile Applications — Identity, Session, Authorization, and Trust Boundaries

Metadata	Value
Volume	4
Chapter ID	V04-P13-02
Subject	MobileApplicationsAccessModel
Status	Generated First-Draft Architecture Skeleton - Domain-Specific Expansion Required
Content maturity	TEMPLATE_DERIVED_REFERENCE_SKELETON unless repository citations prove otherwise
Default implementation classification	REFERENCE_ARCHITECTURE / REQUIRES_REPOSITORY_REVIEW
Accountable owner	Portal Architecture / Mobile Applications
Evidence rule	No implementation claim without inspected executable evidence
Repository	chinair88-prog/allinb2c

1. Executive Orientation

This chapter defines how GTOS shall **govern login, session, role, relationship, tenant, facility, channel, delegation, impersonation and privileged action for customers, partners, providers, warehouse and field users, covering offline capture, notifications, scanning, evidence, approvals, tracking.**

The specification separates reality, observations, knowledge, Decisions, Intent, execution, and outcomes. A component name, database row, UI label, AI answer, or workflow state does not acquire authority merely because it is visible or technically convenient.

Reality or external outcome

- ≠ Observation
- ≠ Claim
- ≠ derived Perspective
- ≠ Prediction
- ≠ Recommendation
- ≠ authorized Decision
- ≠ execution Intent

1.1 Accountable ownership

The accountable owner is **Portal Architecture / Mobile Applications**. Supporting applications, shared infrastructure, integration adapters, analytics, and AI coordinate or present the capability but shall not silently own its authoritative propositions.

1.2 Scope

- create and identify the subject
- validate evidence and policy
- make authorized Decisions
- execute typed Commands
- publish completed-fact Events
- query current and historical perspectives
- correct and reconcile outcomes

1.3 Non-goals

- treating a registered Gradle module, catalog record, README, frontend route, migration plan, or generated report as proof of end-to-end implementation;
- direct cross-Domain database writes;
- generic status values that combine lifecycle, approval, provider, document, payment, dispute, and correction state;
- silent replacement of history;
- AI-created authority or fabricated external outcomes.

2. Ubiquitous Language and Subject Model

Subject	Required interpretation
MobileApplicationsAccessModel	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit
MobileApplicationsAccessModelVersion	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit
MobileApplicationsAccessModelDecision	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit
MobileApplicationsAccessModelEvidenceSet	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit
MobileApplicationsAccessModelException	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit

Reference aggregate:

```
MobileApplicationsAccessModel {  
  subjectId  
  tenantId  
  organizationContext  
  sourceIdentityRefs[]  
  sourceVersionRefs[]  
  lifecycleState  
  relationshipRefs[]  
  decisionRefs[]  
  intentRefs[]  
  evidenceSetRef  
  knowledgeCutoff  
  policyRefs[]  
  authorityRef  
  jurisdictionRefs[]  
  createdAt  
  effectiveAt  
  updatedAt  
  version  
  correctionOf?  
  correlationId  
}
```

2.1 Core invariants

- Stable identity precedes relationship, state, and cross-system correlation.
- Effective time and recorded time remain distinct where business truth changes over time.
- Recommendation, Decision, Intent, execution, and outcome are separate concepts.
- No Portal, report, search index, cache, workflow, or AI Agent becomes a shadow owner of Domain truth.
- Binding submitted, approved, issued, accepted, or signed versions are immutable.
- Corrections append governed facts and preserve the original record.
- External authority and provider outcomes retain their source and qualification.
- Tenant and represented-principal context come from trusted authentication and mandate evaluation.
- Retried writes are idempotent and concurrency guarded.
- Outcome Unknown is explicit and reconciled before risky duplicate execution.

2.2 Required standards

- stable identifiers
- typed contracts
- immutable binding versions

- transactional outbox
- idempotent Commands
- explicit Outcome Unknown
- correction lineage
- machine-verifiable conformance

3. Actors, Roles, and Authority

A conformant design distinguishes:

- the natural person acting;
- the service or AI identity invoking a Tool;
- the organization or principal represented;
- the role or relationship granting context;
- the mandate or delegation granting action authority;
- the Policy and jurisdiction limiting the action;
- the reviewer or approver responsible for a binding Decision.

Authority is evaluated at action time. Authentication alone does not grant business authority. Cached permissions and browser-supplied tenant headers are insufficient for high-impact actions.

4. Lifecycle and State Model

State	Semantics
PROPOSED	Distinct governed condition with entry, exit, timeout, correction and authority semantics
VALIDATION_PENDING	Distinct governed condition with entry, exit, timeout, correction and authority semantics
APPROVAL_PENDING	Distinct governed condition with entry, exit, timeout, correction and authority semantics
ACTIVE	Distinct governed condition with entry, exit, timeout, correction and authority semantics
SUSPENDED	Distinct governed condition with entry, exit, timeout, correction and authority semantics
CORRECTION_PENDING	Distinct governed condition with entry, exit, timeout, correction and authority semantics
RETIRED	Distinct governed condition with entry, exit, timeout, correction and authority semantics

```
stateDiagram-v2
    [*] --> PROPOSED
    PROPOSED --> VALIDATION_PENDING
    VALIDATION_PENDING --> APPROVAL_PENDING
    APPROVAL_PENDING --> ACTIVE
    ACTIVE --> SUSPENDED
    SUSPENDED --> CORRECTION_PENDING
    CORRECTION_PENDING --> RETIRED
```

The diagram is a primary reading path. Real implementations may add parallel review, amendment, appeal, timeout, suspension, partial completion, reconciliation, correction, and terminal failure without collapsing their meaning.

4.1 Transition rules

- transition through a typed, authorized Command;
- require exact expected version where concurrent change matters;
- record actor, represented principal, mandate, Policy, reason, and Evidence;
- use an idempotency key for retried writes;
- publish a completed-fact Event after durable state change;
- expose Outcome Unknown for unresolved external completion;
- preserve original and corrected states in historical reconstruction.

5. Decision, Evidence, and Knowledge Cutoff

Reference Decision:

```
Decision {
  decisionId
  decisionType
  subjectRef
  sourceVersionRefs[]
  knowledgeCutoff
  evidenceSetRef
  policyVersionRefs[]
  recommendationRefs[]
  principalId
  representedOrganizationId
  mandateRef
  rationale
  outcome
  decidedAt
  effectiveAt
  correctionOf?
}
```

Evidence records identify issuer or observer, subject, version, observed time, received time, effective interval, integrity, confidence, qualification, contradiction, correction, retention, residency, and access class. A recommendation may assist the Decision but cannot promote itself to the Decision.

6. Commands, Events, Queries, and Contracts

Reference Commands:

- CreateMobileApplicationsAccessModel
- ValidateMobileApplicationsAccessModel
- ApproveMobileApplicationsAccessModel
- ActivateMobileApplicationsAccessModel
- SuspendMobileApplicationsAccessModel
- CorrectMobileApplicationsAccessModel
- RetireMobileApplicationsAccessModel

Reference Events:

- MobileApplicationsAccessModelCreated
- MobileApplicationsAccessModelValidated
- MobileApplicationsAccessModelApproved
- MobileApplicationsAccessModelActivated
- MobileApplicationsAccessModelSuspended
- MobileApplicationsAccessModelCorrected
- MobileApplicationsAccessModelRetired

Reference queries:

- GetMobileApplicationsAccessModel
- ListMobileApplicationsAccessModelRecords
- GetMobileApplicationsAccessModelTimeline
- GetMobileApplicationsAccessModelEvidence
- GetMobileApplicationsAccessModelDecisionPackage
- GetMobileApplicationsAccessModelExceptions
- GetMobileApplicationsAccessModelAuditTrail

Reference API surface:

```
POST /api/v1/mobileapplicationsaccessmodel/commands
GET  /api/v1/mobileapplicationsaccessmodel/{id}
GET  /api/v1/mobileapplicationsaccessmodel/{id}/timeline
GET  /api/v1/mobileapplicationsaccessmodel/{id}/evidence
GET  /api/v1/mobileapplicationsaccessmodel/{id}/decisions
POST /api/v1/mobileapplicationsaccessmodel/{id}/exceptions
POST /api/v1/mobileapplicationsaccessmodel/{id}/corrections
```

These endpoints are reference contracts, not claims that exact routes exist.

7. Workflow, Failure, and Compensation

flowchart TD

```
A[Validate identity version and authority] --> B[Collect required evidence]
B --> C{Policy and evidence gates pass?}
C -- No --> D[Open exception or request correction]
D --> B
C -- Yes --> E[Record Decision or execution Intent]
E --> F[Execute Domain command or external request]
F --> G{Outcome known?}
G -- Success --> H[Record fact and publish Event]
G -- Failure --> I[Record failure and compensation options]
G -- Unknown --> J[Enter Outcome Unknown]
J --> K[Query source or wait for verified callback]
K --> G
H --> L[Update projections and downstream workflow]
```

Representative failure modes:

- stale or wrong source version
- duplicate submission or replay
- external timeout after possible success
- contradictory source observations
- lost Event after committed state
- approval or mandate revoked during execution
- downstream action before a mandatory gate
- partial completion across multiple subjects
- evidence later retracted or corrected
- tenant, facility, channel or jurisdiction mismatch

Recovery shall query the authoritative source before duplicate execution, preserve partial success, use compensating Intent rather than destructive rewrite, publish corrections, quarantine high-impact ambiguity, and record affected downstream subjects.

8. Data and Persistence Architecture

Reference table families:

Table family	Purpose
mobileapplicationsaccessmodel_aggregate	authoritative subject
mobileapplicationsaccessmodel_version	immutable submitted, approved, issued, or signed versions
mobileapplicationsaccessmodel_relationship	governed relationships
mobileapplicationsaccessmodel_decision	binding Decisions and rationale
mobileapplicationsaccessmodel_evidence_link	provenance and evidence relationships
mobileapplicationsaccessmodel_event_outbox	transactional Event publication
mobileapplicationsaccessmodel_idempotency	duplicate-write protection
mobileapplicationsaccessmodel_exception	exception, claim, dispute, or hold
mobileapplicationsaccessmodel_correction	correction and supersession lineage
mobileapplicationsaccessmodel_audit	privileged action evidence

The owning service controls schema and migration. Cross-Domain references use stable identifiers or contracts. Analytics, reports, caches, search, and vector indexes remain projections. Backup, restore, retention, legal hold, privacy, residency, and decommissioning requirements are explicit.

9. Portal and Experience Requirements

- Mobile Applications: primary experience for customers, partners, providers, warehouse and field users.
- Operator and support views: diagnose failed or ambiguous journeys without assuming Domain ownership.
- Domain services: own authoritative data and action eligibility; the Portal consumes typed contracts.

Every Portal displays exact version, owner, state, freshness, required action, and uncertainty. It supports loading, empty, partial, stale, denied, error, timeout, and Outcome Unknown states; accessibility; locale, currency, unit, date, and RTL/LTR correctness; evidence audit; safe retry; and correction history.

10. AI Participation and Tool Governance

Permitted AI tasks:

- extract and classify evidence
- detect anomalies and missing fields
- summarize timelines and contradictions
- recommend next actions with sources and uncertainty

AI shall not own Domain records, grant itself authority, suppress contradictions, silently edit approved versions, fabricate external outcomes, or execute high-impact actions outside typed Tools, policy, approval, idempotency, sandbox, and outcome observation.

Every Agent Run records source context, prompt/model/tool versions, structured output, confidence and limitations, Policy result, approval, Tool calls, provider responses, final outcome, and recovery actions.

11. Security, Privacy, and Trust Boundaries

- least privilege and separation of duties
- tenant, organization, facility, channel and jurisdiction isolation
- integrity protection for binding evidence
- verified external callbacks and anti-replay controls

Additional controls include secret isolation, callback signature verification, audit of privileged action, emergency-access review, sensitive-data minimization, purpose limitation, and threat models for impersonation, tampering, replay, confused deputy, fraud, prompt injection, and exfiltration.

12. Reliability, SLOs, and Operations

SLI	Reference objective
authoritative read availability	99.9% monthly unless a stricter tier applies
acknowledged Command durability	no acknowledged write may be silently lost
Event publication	99.9% within five minutes after committed fact
duplicate prevention	100% for same tenant, Command class, and idempotency key
binding Decision audit completeness	100%
state-state detection	bounded by business deadline

Dashboards and runbooks cover backlog, error budget, dependency failure, retry budget, DLQ, workflow stall, provider outage, reconciliation, capacity, backup/restore, release/rollback, incident command, and post-incident correction.

13. Testing and Continuous Conformance

- aggregate invariant and transition tests
- authorization, delegation, separation-of-duties and tenant-isolation tests
- idempotency and optimistic-concurrency tests
- database migration, key, constraint and rollback tests
- contract, outbox/inbox, duplicate, replay and DLQ tests
- workflow restart, timeout and compensation tests
- Portal E2E tests for success, partial, stale, denied, error and Outcome Unknown states
- accessibility, locale, currency, unit and RTL/LTR tests
- security adversarial, fraud and data-exfiltration tests
- AI evaluation, prompt-injection, policy-bypass and unauthorized-tool tests
- historical reconstruction, correction and audit-completeness tests
- performance, capacity, recovery and operational exercise tests

Release evidence links each invariant and control to the test, environment, input data, result, owner, and artifact proving it. Generated test counts never replace semantic coverage.

14. Repository Review Boundary

- This chapter is a repository-review specification. Exact executable implementation has not been inspected for every target behavior.
- Registered modules, catalog entries, README claims, frontend contracts, or plans are not proof of complete implementation.

Area	Classification
target aggregate, API, tables, state and workflow in this chapter	REFERENCE_ARCHITECTURE
registered module or catalog claim	DOCUMENTATION_ONLY_CLAIM until source inspection
uninspected integration	REQUIRES_REPOSITORY_REVIEW
behavior proven in another repository-grounded chapter	retain that chapter's evidence and classification
contradictory ownership or path claims	CONFLICT_REQUIRES_CANONICALIZATION

No statement upgrades implementation status merely because a file, directory, module name, frontend contract, database entry, plan, or report exists.

15. Worked Conformance Scenario

An authorized principal initiates a Command against an exact subject version. The service validates identity, tenant, mandate, Policy, Evidence, and idempotency. It records the state transition and outbox entry atomically. If an external dependency participates, timeout produces Outcome Unknown; reconciliation queries the source or waits for a verified callback instead of repeating the action blindly.

Portals show source, freshness, version, required action, and uncertainty. AI may extract, compare, summarize, detect anomalies, and recommend through typed Tools, but cannot own the subject or fabricate success. Later correction appends new facts, identifies affected projections and workflows, and preserves the historical Decision context.

16. Conformance Checklist

- ☐ stable identity and proposition ownership are explicit;
- ☐ authority and mandate are evaluated at action time;
- ☐ state, Recommendation, Decision, Intent, execution, and outcome remain distinct;
- ☐ Commands are typed, authorized, idempotent, and version guarded;
- ☐ Events describe completed facts;
- ☐ Evidence includes provenance, time, integrity, qualification, and correction;
- ☐ external outcomes retain their authority source;
- ☐ Portals show freshness and uncertainty;
- ☐ AI is bounded by typed Tools, Policy, approval, and outcome observation;
- ☐ security, tenant, facility, channel, and jurisdiction boundaries are enforced;
- ☐ Outcome Unknown and reconciliation exist where needed;
- ☐ corrections preserve history;
- ☐ tests prove invariants and recovery;
- ☐ implementation status is not upgraded without executable evidence.

17. Status Vocabulary

Status	Meaning
VERIFIED_IMPLEMENTED	Executable source and relevant behavior were inspected. Executable behavior exists with a material governance or completeness gap.
IMPLEMENTED_WITH_GAP	
PARTIAL_IMPLEMENTATION	Only part of the target capability is evidenced.
REFERENCE_ARCHITECTURE	Normative target behavior; no claim that it exists today.
PLANNED_NOT_IMPLEMENTED	Explicitly planned but not evidenced as executable.
DOCUMENTATION_ONLY_CLAIM	Documentation or client contract claims behavior without verified backend evidence.
CONFLICT_REQUIRES_CANONICALIZATION	Sources disagree and no final owner has been established.
REQUIRES_REPOSITORY_REVIEW	Necessary executable evidence has not yet been inspected.

Mobile Applications — UX States, Accessibility, Localization, Analytics, and E2E

Metadata	Value
Volume	4
Chapter ID	V04-P13-03
Subject	MobileApplicationsExperienceStandard
Status	Generated First-Draft Architecture Skeleton - Domain-Specific Expansion Required
Content maturity	TEMPLATE_DERIVED_REFERENCE_SKELETON unless repository citations prove otherwise
Default implementation classification	REFERENCE_ARCHITECTURE / REQUIRES_REPOSITORY_REVIEW
Accountable owner	Portal Architecture / Mobile Applications
Evidence rule	No implementation claim without inspected executable evidence
Repository	chinair88-prog/allinb2c

1. Executive Orientation

This chapter defines how GTOS shall **specify loading, empty, partial, stale, error, denied, offline, accessibility, RTL/LTR, analytics, audit and test journeys for customers, partners, providers, warehouse and field users, covering offline capture, notifications, scanning, evidence, approvals, tracking.**

The specification separates reality, observations, knowledge, Decisions, Intent, execution, and outcomes. A component name, database row, UI label, AI answer, or workflow state does not acquire authority merely because it is visible or technically convenient.

Reality or external outcome

- ≠ Observation
- ≠ Claim
- ≠ derived Perspective
- ≠ Prediction
- ≠ Recommendation
- ≠ authorized Decision
- ≠ execution Intent

1.1 Accountable ownership

The accountable owner is **Portal Architecture / Mobile Applications**. Supporting applications, shared infrastructure, integration adapters, analytics, and AI coordinate or present the capability but shall not silently own its authoritative propositions.

1.2 Scope

- create and identify the subject
- validate evidence and policy
- make authorized Decisions
- execute typed Commands
- publish completed-fact Events
- query current and historical perspectives
- correct and reconcile outcomes

1.3 Non-goals

- treating a registered Gradle module, catalog record, README, frontend route, migration plan, or generated report as proof of end-to-end implementation;
- direct cross-Domain database writes;
- generic status values that combine lifecycle, approval, provider, document, payment, dispute, and correction state;
- silent replacement of history;
- AI-created authority or fabricated external outcomes.

2. Ubiquitous Language and Subject Model

Subject	Required interpretation
MobileApplicationsExperienceStandard	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit
MobileApplicationsExperienceStandardVersion	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit
MobileApplicationsExperienceStandardDecision	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit
MobileApplicationsExperienceStandardEvidenceSet	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit
MobileApplicationsExperienceStandardException	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit

Reference aggregate:

```
MobileApplicationsExperienceStandard {
  subjectId
  tenantId
  organizationContext
  sourceIdentityRefs[]
  sourceVersionRefs[]
  lifecycleState
  relationshipRefs[]
  decisionRefs[]
  intentRefs[]
  evidenceSetRef
  knowledgeCutoff
  policyRefs[]
  authorityRef
  jurisdictionRefs[]
  createdAt
  effectiveAt
  updatedAt
  version
  correctionOf?
  correlationId
}
```

2.1 Core invariants

- Stable identity precedes relationship, state, and cross-system correlation.
- Effective time and recorded time remain distinct where business truth changes over time.
- Recommendation, Decision, Intent, execution, and outcome are separate concepts.
- No Portal, report, search index, cache, workflow, or AI Agent becomes a shadow owner of Domain truth.
- Binding submitted, approved, issued, accepted, or signed versions are immutable.
- Corrections append governed facts and preserve the original record.
- External authority and provider outcomes retain their source and qualification.
- Tenant and represented-principal context come from trusted authentication and mandate evaluation.
- Retried writes are idempotent and concurrency guarded.
- Outcome Unknown is explicit and reconciled before risky duplicate execution.

2.2 Required standards

- stable identifiers
- typed contracts
- immutable binding versions

- transactional outbox
- idempotent Commands
- explicit Outcome Unknown
- correction lineage
- machine-verifiable conformance

3. Actors, Roles, and Authority

A conformant design distinguishes:

- the natural person acting;
- the service or AI identity invoking a Tool;
- the organization or principal represented;
- the role or relationship granting context;
- the mandate or delegation granting action authority;
- the Policy and jurisdiction limiting the action;
- the reviewer or approver responsible for a binding Decision.

Authority is evaluated at action time. Authentication alone does not grant business authority. Cached permissions and browser-supplied tenant headers are insufficient for high-impact actions.

4. Lifecycle and State Model

State	Semantics
PROPOSED	Distinct governed condition with entry, exit, timeout, correction and authority semantics
VALIDATION_PENDING	Distinct governed condition with entry, exit, timeout, correction and authority semantics
APPROVAL_PENDING	Distinct governed condition with entry, exit, timeout, correction and authority semantics
ACTIVE	Distinct governed condition with entry, exit, timeout, correction and authority semantics
SUSPENDED	Distinct governed condition with entry, exit, timeout, correction and authority semantics
CORRECTION_PENDING	Distinct governed condition with entry, exit, timeout, correction and authority semantics
RETIRED	Distinct governed condition with entry, exit, timeout, correction and authority semantics

```
stateDiagram-v2
    [*] --> PROPOSED
    PROPOSED --> VALIDATION_PENDING
    VALIDATION_PENDING --> APPROVAL_PENDING
    APPROVAL_PENDING --> ACTIVE
    ACTIVE --> SUSPENDED
    SUSPENDED --> CORRECTION_PENDING
    CORRECTION_PENDING --> RETIRED
```

The diagram is a primary reading path. Real implementations may add parallel review, amendment, appeal, timeout, suspension, partial completion, reconciliation, correction, and terminal failure without collapsing their meaning.

4.1 Transition rules

- transition through a typed, authorized Command;
- require exact expected version where concurrent change matters;
- record actor, represented principal, mandate, Policy, reason, and Evidence;
- use an idempotency key for retried writes;
- publish a completed-fact Event after durable state change;
- expose Outcome Unknown for unresolved external completion;
- preserve original and corrected states in historical reconstruction.

5. Decision, Evidence, and Knowledge Cutoff

Reference Decision:

```
Decision {
  decisionId
  decisionType
  subjectRef
  sourceVersionRefs[]
  knowledgeCutoff
  evidenceSetRef
  policyVersionRefs[]
  recommendationRefs[]
  principalId
  representedOrganizationId
  mandateRef
  rationale
  outcome
  decidedAt
  effectiveAt
  correctionOf?
}
```

Evidence records identify issuer or observer, subject, version, observed time, received time, effective interval, integrity, confidence, qualification, contradiction, correction, retention, residency, and access class. A recommendation may assist the Decision but cannot promote itself to the Decision.

6. Commands, Events, Queries, and Contracts

Reference Commands:

- CreateMobileApplicationsExperienceStandard
- ValidateMobileApplicationsExperienceStandard
- ApproveMobileApplicationsExperienceStandard
- ActivateMobileApplicationsExperienceStandard
- SuspendMobileApplicationsExperienceStandard
- CorrectMobileApplicationsExperienceStandard
- RetireMobileApplicationsExperienceStandard

Reference Events:

- MobileApplicationsExperienceStandardCreated
- MobileApplicationsExperienceStandardValidated
- MobileApplicationsExperienceStandardApproved
- MobileApplicationsExperienceStandardActivated
- MobileApplicationsExperienceStandardSuspended
- MobileApplicationsExperienceStandardCorrected
- MobileApplicationsExperienceStandardRetired

Reference queries:

- GetMobileApplicationsExperienceStandard
- ListMobileApplicationsExperienceStandardRecords
- GetMobileApplicationsExperienceStandardTimeline
- GetMobileApplicationsExperienceStandardEvidence
- GetMobileApplicationsExperienceStandardDecisionPackage
- GetMobileApplicationsExperienceStandardExceptions
- GetMobileApplicationsExperienceStandardAuditTrail

Reference API surface:

```
POST /api/v1/mobileapplicationsexperiencstandard/commands
GET  /api/v1/mobileapplicationsexperiencstandard/{id}
GET  /api/v1/mobileapplicationsexperiencstandard/{id}/timeline
GET  /api/v1/mobileapplicationsexperiencstandard/{id}/evidence
GET  /api/v1/mobileapplicationsexperiencstandard/{id}/decisions
POST /api/v1/mobileapplicationsexperiencstandard/{id}/exceptions
POST /api/v1/mobileapplicationsexperiencstandard/{id}/corrections
```

These endpoints are reference contracts, not claims that exact routes exist.

7. Workflow, Failure, and Compensation

flowchart TD

```
A[Validate identity version and authority] --> B[Collect required evidence]
B --> C{Policy and evidence gates pass?}
C -- No --> D[Open exception or request correction]
D --> B
C -- Yes --> E[Record Decision or execution Intent]
E --> F[Execute Domain command or external request]
F --> G{Outcome known?}
G -- Success --> H[Record fact and publish Event]
G -- Failure --> I[Record failure and compensation options]
G -- Unknown --> J[Enter Outcome Unknown]
J --> K[Query source or wait for verified callback]
K --> G
H --> L[Update projections and downstream workflow]
```

Representative failure modes:

- stale or wrong source version
- duplicate submission or replay
- external timeout after possible success
- contradictory source observations
- lost Event after committed state
- approval or mandate revoked during execution
- downstream action before a mandatory gate
- partial completion across multiple subjects
- evidence later retracted or corrected
- tenant, facility, channel or jurisdiction mismatch

Recovery shall query the authoritative source before duplicate execution, preserve partial success, use compensating Intent rather than destructive rewrite, publish corrections, quarantine high-impact ambiguity, and record affected downstream subjects.

8. Data and Persistence Architecture

Reference table families:

Table family	Purpose
mobileapplicationexperiencestandard_aggregate	authoritative subject
mobileapplicationexperiencestandard_version	immutable submitted, approved, issued, or signed versions
mobileapplicationexperiencestandard_relationship	governed relationships
mobileapplicationexperiencestandard_decision	binding Decisions and rationale
mobileapplicationexperiencestandard_evidence_link	provenance and evidence relationships
mobileapplicationexperiencestandard_event_outbox	transactional Event publication
mobileapplicationexperiencestandard_idempotency	duplicate-write protection
mobileapplicationexperiencestandard_exception	exception, claim, dispute, or hold
mobileapplicationexperiencestandard_correction	correction and supersession lineage
mobileapplicationexperiencestandard_audit	privileged action evidence

The owning service controls schema and migration. Cross-Domain references use stable identifiers or contracts. Analytics, reports, caches, search, and vector indexes remain projections. Backup, restore, retention, legal hold, privacy, residency, and decommissioning requirements are explicit.

9. Portal and Experience Requirements

- Mobile Applications: primary experience for customers, partners, providers, warehouse and field users.
- Operator and support views: diagnose failed or ambiguous journeys without assuming Domain ownership.
- Domain services: own authoritative data and action eligibility; the Portal consumes typed contracts.

Every Portal displays exact version, owner, state, freshness, required action, and uncertainty. It supports loading, empty, partial, stale, denied, error, timeout, and Outcome Unknown states; accessibility; locale, currency, unit, date, and RTL/LTR correctness; evidence audit; safe retry; and correction history.

10. AI Participation and Tool Governance

Permitted AI tasks:

- extract and classify evidence
- detect anomalies and missing fields
- summarize timelines and contradictions
- recommend next actions with sources and uncertainty

AI shall not own Domain records, grant itself authority, suppress contradictions, silently edit approved versions, fabricate external outcomes, or execute high-impact actions outside typed Tools, policy, approval, idempotency, sandbox, and outcome observation.

Every Agent Run records source context, prompt/model/tool versions, structured output, confidence and limitations, Policy result, approval, Tool calls, provider responses, final outcome, and recovery actions.

11. Security, Privacy, and Trust Boundaries

- least privilege and separation of duties
- tenant, organization, facility, channel and jurisdiction isolation
- integrity protection for binding evidence
- verified external callbacks and anti-replay controls

Additional controls include secret isolation, callback signature verification, audit of privileged action, emergency-access review, sensitive-data minimization, purpose limitation, and threat models for impersonation, tampering, replay, confused deputy, fraud, prompt injection, and exfiltration.

12. Reliability, SLOs, and Operations

SLI	Reference objective
authoritative read availability	99.9% monthly unless a stricter tier applies
acknowledged Command durability	no acknowledged write may be silently lost
Event publication	99.9% within five minutes after committed fact
duplicate prevention	100% for same tenant, Command class, and idempotency key
binding Decision audit completeness	100%
state-state detection	bounded by business deadline

Dashboards and runbooks cover backlog, error budget, dependency failure, retry budget, DLQ, workflow stall, provider outage, reconciliation, capacity, backup/restore, release/rollback, incident command, and post-incident correction.

13. Testing and Continuous Conformance

- aggregate invariant and transition tests
- authorization, delegation, separation-of-duties and tenant-isolation tests
- idempotency and optimistic-concurrency tests
- database migration, key, constraint and rollback tests
- contract, outbox/inbox, duplicate, replay and DLQ tests
- workflow restart, timeout and compensation tests
- Portal E2E tests for success, partial, stale, denied, error and Outcome Unknown states
- accessibility, locale, currency, unit and RTL/LTR tests
- security adversarial, fraud and data-exfiltration tests
- AI evaluation, prompt-injection, policy-bypass and unauthorized-tool tests
- historical reconstruction, correction and audit-completeness tests
- performance, capacity, recovery and operational exercise tests

Release evidence links each invariant and control to the test, environment, input data, result, owner, and artifact proving it. Generated test counts never replace semantic coverage.

14. Repository Review Boundary

- This chapter is a repository-review specification. Exact executable implementation has not been inspected for every target behavior.
- Registered modules, catalog entries, README claims, frontend contracts, or plans are not proof of complete implementation.

Area	Classification
target aggregate, API, tables, state and workflow in this chapter	REFERENCE_ARCHITECTURE
registered module or catalog claim	DOCUMENTATION_ONLY_CLAIM until source inspection
uninspected integration	REQUIRES_REPOSITORY_REVIEW
behavior proven in another repository-grounded chapter	retain that chapter's evidence and classification
contradictory ownership or path claims	CONFLICT_REQUIRES_CANONICALIZATION

No statement upgrades implementation status merely because a file, directory, module name, frontend contract, database entry, plan, or report exists.

15. Worked Conformance Scenario

An authorized principal initiates a Command against an exact subject version. The service validates identity, tenant, mandate, Policy, Evidence, and idempotency. It records the state transition and outbox entry atomically. If an external dependency participates, timeout produces Outcome Unknown; reconciliation queries the source or waits for a verified callback instead of repeating the action blindly.

Portals show source, freshness, version, required action, and uncertainty. AI may extract, compare, summarize, detect anomalies, and recommend through typed Tools, but cannot own the subject or fabricate success. Later correction appends new facts, identifies affected projections and workflows, and preserves the historical Decision context.

16. Conformance Checklist

- ☐ stable identity and proposition ownership are explicit;
- ☐ authority and mandate are evaluated at action time;
- ☐ state, Recommendation, Decision, Intent, execution, and outcome remain distinct;
- ☐ Commands are typed, authorized, idempotent, and version guarded;
- ☐ Events describe completed facts;
- ☐ Evidence includes provenance, time, integrity, qualification, and correction;
- ☐ external outcomes retain their authority source;
- ☐ Portals show freshness and uncertainty;
- ☐ AI is bounded by typed Tools, Policy, approval, and outcome observation;
- ☐ security, tenant, facility, channel, and jurisdiction boundaries are enforced;
- ☐ Outcome Unknown and reconciliation exist where needed;
- ☐ corrections preserve history;
- ☐ tests prove invariants and recovery;
- ☐ implementation status is not upgraded without executable evidence.

17. Status Vocabulary

Status	Meaning
VERIFIED_IMPLEMENTED	Executable source and relevant behavior were inspected. Executable behavior exists with a material governance or completeness gap.
IMPLEMENTED_WITH_GAP	
PARTIAL_IMPLEMENTATION	Only part of the target capability is evidenced.
REFERENCE_ARCHITECTURE	Normative target behavior; no claim that it exists today.
PLANNED_NOT_IMPLEMENTED	Explicitly planned but not evidenced as executable.
DOCUMENTATION_ONLY_CLAIM	Documentation or client contract claims behavior without verified backend evidence.
CONFLICT_REQUIRES_CANONICALIZATION	Sources disagree and no final owner has been established.
REQUIRES_REPOSITORY_REVIEW	Necessary executable evidence has not yet been inspected.

Portal Cross-Route and Persona Matrix

Metadata	Value
Volume	4
Chapter ID	V04-SYNTH
Subject	PortalMatrix
Status	Generated First-Draft Architecture Skeleton - Domain-Specific Expansion Required
Content maturity	TEMPLATE_DERIVED_REFERENCE_SKELETON unless repository citations prove otherwise
Default implementation classification	REFERENCE_ARCHITECTURE / REQUIRES_REPOSITORY_REVIEW
Accountable owner	Experience Architecture Council
Evidence rule	No implementation claim without inspected executable evidence
Repository	chinair88-prog/allinb2c

1. Executive Orientation

This chapter defines how GTOS shall **connect every Portal persona, route, page, permission, Domain dependency, realtime channel, AI interaction, analytics signal and E2E journey**.

The specification separates reality, observations, knowledge, Decisions, Intent, execution, and outcomes. A component name, database row, UI label, AI answer, or workflow state does not acquire authority merely because it is visible or technically convenient.

Reality or external outcome
≠ Observation
≠ Claim
≠ derived Perspective
≠ Prediction
≠ Recommendation
≠ authorized Decision
≠ execution Intent

1.1 Accountable ownership

The accountable owner is **Experience Architecture Council**. Supporting applications, shared infrastructure, integration adapters, analytics, and AI coordinate or present the capability but shall not silently own its authoritative propositions.

1.2 Scope

- create and identify the subject
- validate evidence and policy
- make authorized Decisions
- execute typed Commands
- publish completed-fact Events
- query current and historical perspectives
- correct and reconcile outcomes

1.3 Non-goals

- treating a registered Gradle module, catalog record, README, frontend route, migration plan, or generated report as proof of end-to-end implementation;

- direct cross-Domain database writes;
- generic status values that combine lifecycle, approval, provider, document, payment, dispute, and correction state;
- silent replacement of history;
- AI-created authority or fabricated external outcomes.

2. Ubiquitous Language and Subject Model

Subject	Required interpretation
PortalMatrix	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit
PortalMatrixVersion	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit
PortalMatrixDecision	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit
PortalMatrixEvidenceSet	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit
PortalMatrixException	Independent identified subject, governed subordinate entity, or qualified perspective; ownership must be explicit

Reference aggregate:

```
PortalMatrix {
  subjectId
  tenantId
  organizationContext
  sourceIdentityRefs[]
  sourceVersionRefs[]
  lifecycleState
  relationshipRefs[]
  decisionRefs[]
  intentRefs[]
  evidenceSetRef
  knowledgeCutoff
  policyRefs[]
  authorityRef
  jurisdictionRefs[]
  createdAt
  effectiveAt
  updatedAt
  version
  correctionOf?
  correlationId
}
```

2.1 Core invariants

- Stable identity precedes relationship, state, and cross-system correlation.
- Effective time and recorded time remain distinct where business truth changes over time.
- Recommendation, Decision, Intent, execution, and outcome are separate concepts.
- No Portal, report, search index, cache, workflow, or AI Agent becomes a shadow owner of Domain truth.
- Binding submitted, approved, issued, accepted, or signed versions are immutable.
- Corrections append governed facts and preserve the original record.
- External authority and provider outcomes retain their source and qualification.
- Tenant and represented-principal context come from trusted authentication and mandate evaluation.
- Retried writes are idempotent and concurrency guarded.
- Outcome Unknown is explicit and reconciled before risky duplicate execution.

2.2 Required standards

- stable identifiers
- typed contracts
- immutable binding versions
- transactional outbox
- idempotent Commands
- explicit Outcome Unknown
- correction lineage

- machine-verifiable conformance

3. Actors, Roles, and Authority

A conformant design distinguishes:

- the natural person acting;
- the service or AI identity invoking a Tool;
- the organization or principal represented;
- the role or relationship granting context;
- the mandate or delegation granting action authority;
- the Policy and jurisdiction limiting the action;
- the reviewer or approver responsible for a binding Decision.

Authority is evaluated at action time. Authentication alone does not grant business authority. Cached permissions and browser-supplied tenant headers are insufficient for high-impact actions.

4. Lifecycle and State Model

State	Semantics
PROPOSED	Distinct governed condition with entry, exit, timeout, correction and authority semantics
VALIDATION_PENDING	Distinct governed condition with entry, exit, timeout, correction and authority semantics
APPROVAL_PENDING	Distinct governed condition with entry, exit, timeout, correction and authority semantics
ACTIVE	Distinct governed condition with entry, exit, timeout, correction and authority semantics
SUSPENDED	Distinct governed condition with entry, exit, timeout, correction and authority semantics
CORRECTION_PENDING	Distinct governed condition with entry, exit, timeout, correction and authority semantics
RETIRED	Distinct governed condition with entry, exit, timeout, correction and authority semantics

```
stateDiagram-v2
    [*] --> PROPOSED
    PROPOSED --> VALIDATION_PENDING
    VALIDATION_PENDING --> APPROVAL_PENDING
    APPROVAL_PENDING --> ACTIVE
    ACTIVE --> SUSPENDED
    SUSPENDED --> CORRECTION_PENDING
    CORRECTION_PENDING --> RETIRED
```

The diagram is a primary reading path. Real implementations may add parallel review, amendment, appeal, timeout, suspension, partial completion, reconciliation, correction, and terminal failure without collapsing their meaning.

4.1 Transition rules

- transition through a typed, authorized Command;
- require exact expected version where concurrent change matters;
- record actor, represented principal, mandate, Policy, reason, and Evidence;
- use an idempotency key for retried writes;
- publish a completed-fact Event after durable state change;
- expose Outcome Unknown for unresolved external completion;
- preserve original and corrected states in historical reconstruction.

5. Decision, Evidence, and Knowledge Cutoff

Reference Decision:

```
Decision {
    decisionId
```

```

decisionType
subjectRef
sourceVersionRefs[]
knowledgeCutoff
evidenceSetRef
policyVersionRefs[]
recommendationRefs[]
principalId
representedOrganizationId
mandateRef
rationale
outcome
decidedAt
effectiveAt
correctionOf?
}

```

Evidence records identify issuer or observer, subject, version, observed time, received time, effective interval, integrity, confidence, qualification, contradiction, correction, retention, residency, and access class. A recommendation may assist the Decision but cannot promote itself to the Decision.

6. Commands, Events, Queries, and Contracts

Reference Commands:

- CreatePortalMatrix
- ValidatePortalMatrix
- ApprovePortalMatrix
- ActivatePortalMatrix
- SuspendPortalMatrix
- CorrectPortalMatrix
- RetirePortalMatrix

Reference Events:

- PortalMatrixCreated
- PortalMatrixValidated
- PortalMatrixApproved
- PortalMatrixActivated
- PortalMatrixSuspended
- PortalMatrixCorrected
- PortalMatrixRetired

Reference queries:

- GetPortalMatrix
- ListPortalMatrixRecords
- GetPortalMatrixTimeline
- GetPortalMatrixEvidence
- GetPortalMatrixDecisionPackage
- GetPortalMatrixExceptions
- GetPortalMatrixAuditTrail

Reference API surface:

```

POST /api/v1/portalmatrix/commands
GET  /api/v1/portalmatrix/{id}
GET  /api/v1/portalmatrix/{id}/timeline
GET  /api/v1/portalmatrix/{id}/evidence
GET  /api/v1/portalmatrix/{id}/decisions
POST /api/v1/portalmatrix/{id}/exceptions
POST /api/v1/portalmatrix/{id}/corrections

```

These endpoints are reference contracts, not claims that exact routes exist.

7. Workflow, Failure, and Compensation

flowchart TD

```

A[Validate identity version and authority] --> B[Collect required evidence]
B --> C{Policy and evidence gates pass?}
C -- No --> D[Open exception or request correction]
D --> B

```

```

C -- Yes --> E[Record Decision or execution Intent]
E --> F[Execute Domain command or external request]
F --> G{Outcome known?}
G -- Success --> H[Record fact and publish Event]
G -- Failure --> I[Record failure and compensation options]
G -- Unknown --> J[Enter Outcome Unknown]
J --> K[Query source or wait for verified callback]
K --> G
H --> L[Update projections and downstream workflow]

```

Representative failure modes:

- stale or wrong source version
- duplicate submission or replay
- external timeout after possible success
- contradictory source observations
- lost Event after committed state
- approval or mandate revoked during execution
- downstream action before a mandatory gate
- partial completion across multiple subjects
- evidence later retracted or corrected
- tenant, facility, channel or jurisdiction mismatch

Recovery shall query the authoritative source before duplicate execution, preserve partial success, use compensating Intent rather than destructive rewrite, publish corrections, quarantine high-impact ambiguity, and record affected downstream subjects.

8. Data and Persistence Architecture

Reference table families:

Table family	Purpose
portalmatrix_aggregate	authoritative subject
portalmatrix_version	immutable submitted, approved, issued, or signed versions
portalmatrix_relationship	governed relationships
portalmatrix_decision	binding Decisions and rationale
portalmatrix_evidence_link	provenance and evidence relationships
portalmatrix_event_outbox	transactional Event publication
portalmatrix_idempotency	duplicate-write protection
portalmatrix_exception	exception, claim, dispute, or hold
portalmatrix_correction	correction and supersession lineage
portalmatrix_audit	privileged action evidence

The owning service controls schema and migration. Cross-Domain references use stable identifiers or contracts. Analytics, reports, caches, search, and vector indexes remain projections. Backup, restore, retention, legal hold, privacy, residency, and decommissioning requirements are explicit.

9. Portal and Experience Requirements

- Primary participant Portal: initiate, review exact versions, supply evidence, and respond to required actions.
- Operator Portal: inspect exceptions, correlation, source responses, retries, compensation, and downstream impact.
- Executive or oversight view: consume governed metrics without becoming a source of Domain truth.

Every Portal displays exact version, owner, state, freshness, required action, and uncertainty. It supports loading, empty, partial, stale, denied, error, timeout, and Outcome Unknown states; accessibility; locale, currency, unit, date, and RTL/LTR correctness; evidence audit; safe retry; and correction history.

10. AI Participation and Tool Governance

Permitted AI tasks:

- extract and classify evidence
- detect anomalies and missing fields
- summarize timelines and contradictions

- recommend next actions with sources and uncertainty

AI shall not own Domain records, grant itself authority, suppress contradictions, silently edit approved versions, fabricate external outcomes, or execute high-impact actions outside typed Tools, policy, approval, idempotency, sandbox, and outcome observation.

Every Agent Run records source context, prompt/model/tool versions, structured output, confidence and limitations, Policy result, approval, Tool calls, provider responses, final outcome, and recovery actions.

11. Security, Privacy, and Trust Boundaries

- least privilege and separation of duties
- tenant, organization, facility, channel and jurisdiction isolation
- integrity protection for binding evidence
- verified external callbacks and anti-replay controls

Additional controls include secret isolation, callback signature verification, audit of privileged action, emergency-access review, sensitive-data minimization, purpose limitation, and threat models for impersonation, tampering, replay, confused deputy, fraud, prompt injection, and exfiltration.

12. Reliability, SLOs, and Operations

SLI	Reference objective
authoritative read availability	99.9% monthly unless a stricter tier applies
acknowledged Command durability	no acknowledged write may be silently lost
Event publication	99.9% within five minutes after committed fact
duplicate prevention	100% for same tenant, Command class, and idempotency key
binding Decision audit completeness	100%
state-state detection	bounded by business deadline

Dashboards and runbooks cover backlog, error budget, dependency failure, retry budget, DLQ, workflow stall, provider outage, reconciliation, capacity, backup/restore, release/rollback, incident command, and post-incident correction.

13. Testing and Continuous Conformance

- aggregate invariant and transition tests
- authorization, delegation, separation-of-duties and tenant-isolation tests
- idempotency and optimistic-concurrency tests
- database migration, key, constraint and rollback tests
- contract, outbox/inbox, duplicate, replay and DLQ tests
- workflow restart, timeout and compensation tests
- Portal E2E tests for success, partial, stale, denied, error and Outcome Unknown states
- accessibility, locale, currency, unit and RTL/LTR tests
- security adversarial, fraud and data-exfiltration tests
- AI evaluation, prompt-injection, policy-bypass and unauthorized-tool tests
- historical reconstruction, correction and audit-completeness tests
- performance, capacity, recovery and operational exercise tests

Release evidence links each invariant and control to the test, environment, input data, result, owner, and artifact proving it. Generated test counts never replace semantic coverage.

14. Repository Review Boundary

- This chapter is a repository-review specification. Exact executable implementation has not been inspected for every target behavior.
- Registered modules, catalog entries, README claims, frontend contracts, or plans are not proof of complete implementation.

Area	Classification
target aggregate, API, tables, state and workflow in this chapter	REFERENCE_ARCHITECTURE
registered module or catalog claim	DOCUMENTATION_ONLY_CLAIM until source inspection
uninspected integration	REQUIRES_REPOSITORY_REVIEW
behavior proven in another repository-grounded chapter	retain that chapter's evidence and classification
contradictory ownership or path claims	CONFLICT_REQUIRES_CANONICALIZATION

No statement upgrades implementation status merely because a file, directory, module name, frontend contract, database entry, plan, or report exists.

15. Worked Conformance Scenario

An authorized principal initiates a Command against an exact subject version. The service validates identity, tenant, mandate, Policy, Evidence, and idempotency. It records the state transition and outbox entry atomically. If an external dependency participates, timeout produces Outcome Unknown; reconciliation queries the source or waits for a verified callback instead of repeating the action blindly.

Portals show source, freshness, version, required action, and uncertainty. AI may extract, compare, summarize, detect anomalies, and recommend through typed Tools, but cannot own the subject or fabricate success. Later correction appends new facts, identifies affected projections and workflows, and preserves the historical Decision context.

16. Conformance Checklist

- ☐ stable identity and proposition ownership are explicit;
- ☐ authority and mandate are evaluated at action time;
- ☐ state, Recommendation, Decision, Intent, execution, and outcome remain distinct;
- ☐ Commands are typed, authorized, idempotent, and version guarded;
- ☐ Events describe completed facts;
- ☐ Evidence includes provenance, time, integrity, qualification, and correction;
- ☐ external outcomes retain their authority source;
- ☐ Portals show freshness and uncertainty;
- ☐ AI is bounded by typed Tools, Policy, approval, and outcome observation;
- ☐ security, tenant, facility, channel, and jurisdiction boundaries are enforced;
- ☐ Outcome Unknown and reconciliation exist where needed;
- ☐ corrections preserve history;
- ☐ tests prove invariants and recovery;
- ☐ implementation status is not upgraded without executable evidence.

17. Status Vocabulary

Status	Meaning
VERIFIED_IMPLEMENTED	Executable source and relevant behavior were inspected.
IMPLEMENTED_WITH_GAP	Executable behavior exists with a material governance or completeness gap.
PARTIAL_IMPLEMENTATION	Only part of the target capability is evidenced.
REFERENCE_ARCHITECTURE	Normative target behavior; no claim that it exists today.
PLANNED_NOT_IMPLEMENTED	Explicitly planned but not evidenced as executable.
DOCUMENTATION_ONLY_CLAIM	Documentation or client contract claims behavior without verified backend evidence.
CONFLICT_REQUIRES_CANONICALIZATION	Sources disagree and no final owner has been established.
REQUIRES_REPOSITORY_REVIEW	Necessary executable evidence has not yet been inspected.