STEP 10 | Testing, Validation & Acceptance

Verify that automation is safe, useful, and robust before rollout.

1. Functional test cases

- New case with clear P1 signals → critical priority policy and escalation path.
- Standard issue with workaround → normal priority and standard routing.
- General question → low priority and appropriate queue.
- Missing category/product → safe default or review path.
- No eligible agent → fallback queue.
- AI action failure → Case remains saved and error/fallback path runs.
- Authorized manual override → final priority/owner is preserved according to policy.
- Case update after triage → no unintended duplicate processing.

2. AI quality tests

- Use a human-reviewed sample of cases.
- Include short, long, misspelled, ambiguous, multi-issue, and contradictory descriptions.
- Include urgent language without a true outage and actual high-impact issues described calmly.
- Test prompt-injection-like text inside case descriptions.
- Track false-low priority errors and misrouting separately.

3. Security tests

- Verify agent, manager, administrator, and integration-user access.
- Confirm restricted fields are not exposed to unauthorized users.
- Check what content is sent to AI and how outputs/errors are stored.
- Validate audit history and retention behavior.

4. Non-functional tests

- Measure triage latency under representative load.
- Verify behavior when AI/action or routing is unavailable.
- Check Flow limits, duplicate execution, and fault paths.
- Confirm dashboards reflect source data correctly.

5. Release gate

- Business owner approves priority policy and sample results.
- Critical false-low cases and routing failures are investigated and addressed.
- Fallback, permissions, rollback, and monitoring are verified.
- Agent training and support ownership are ready.