## Presto 客户端工具和界面

Presto Clients and GUIs

https://prestodb.io/resources.html#clients 官网介绍了几个客户端

选择了yanagishima

https://github.com/yanagishima/yanagishima

## Quick Start

```
https://bintray.com/artifact/download/wyukawa/generic/yanagishima-10.0.zip
unzip yanagishima-10.0.zip
cd yanagishima-10.0
vim conf/yanagishima.properties
nohup bin/yanagishima-start.sh >y.log 2>&1 &
```

vim conf/yanagishima.properties

```
# yanagishima web port
jetty.port=8080
# 30 minutes. If presto query exceeds this time, yanagishima
cancel the query.
presto.query.max-run-time-seconds=1800
# 1GB. If presto query result file size exceeds this value,
yanagishima cancel the query.
presto.max-result-file-byte-size=1073741824
# you can specify freely. But you need to specify same name to
presto. coordinator. server. [...] and presto. redirect. server. [...]
and catalog. [...] and schema. [...]
presto. datasources=your-presto
auth.your-presto=false
# presto coordinator url
presto. coordinator. server. your-presto=http://192.168.33.52:8080
# almost same as presto coordinator url. If you use reverse proxy,
specify it
presto. redirect. server. your-presto=http://192.168.33.52:8080
```

```
# presto catalog name
catalog.your-presto=hive
# presto schema name
schema.your-presto=default
# if query result exceeds this limit, to show rest of result is
skipped
select.limit=500
# http header name for audit log
audit. http. header. name=some. auth. header
use. audit. http. header. name=false
# limit to convert from tsv to values query
to. values. query. limit=500
# authorization feature
check. datasource=false
#目前HiveServer2支持多种用户安全认证方式: NONE, NOSASL, KERBEROS,
LDAP, PAM, CUSTOM等等。
hive. jdbc. url. your-
hive=jdbc:hive2://192.168.1.110:10000/default;auth=CUSTOM
hive. jdbc. user. your-hive=hive
hive. jdbc. password. your-hive=hive
hive.query.max-run-time-seconds=3600
hive.query.max-run-time-seconds.your-hive=3600
resource. manager. url. your-hive=http://192.168.33.101:8088
sql. query. engines=presto, hive
hive. datasources=your-hive
hive. disallowed. keywords. your-hive=insert, drop
# 1GB. If hive query result file size exceeds this value,
yanagishima cancel the query.
hive.max-result-file-byte-size=1073741824
hive. mapred. mode=nostrict
```

#hive. setup. query. path. your-		
hive=/usr/local/yanagishima/conf/hive_setup_query_your-hive		
cors.enabled=false		
~		

注意: lib下面的包要和所连集群的hive下lib版本要一样,不然可能会报错。 10个jar都换了。