Directional Predictive Evidence for Collusion Auditing: A Pre-Registered, Sprint-Scale Test of the APTG-RL Design

Aravinth K
Independent researcher aravinth3007k@gmail.com
With Apart Research

Abstract

Auditing multi-agent systems for collusion requires telling coordination apart from shared context, shared model tendencies and prompt-induced behaviour shifts. We test the APTG-RL design: a directional predictive-gain statistic between agents, a time-varying directed graph with temporal features, and a reinforcement-learning investigator that decides when to alert (its prompt-conditioned baseline is implemented but not exercised by the reported detectors). We build a three-seller repeated pricing game with four scripted collusion mechanisms, benign and shared-model negatives, and a seven-condition factorial (C0–C6) that perturbs one or both agents' instructions. Ten detectors, including the information-theoretic net-influence baseline, are compared on held-out episodes at a threshold fixed on validation negatives; the analysis plan was pre-registered before any held-out evaluation. Directional gain beats symmetric mutual information (AUROC 0.839 vs. 0.755) but not lag-1 net influence (0.850); the two cover different mechanisms, and the parametric gain misses a parity-coded hidden channel that mutual information catches. The temporal-graph score did not help (0.740), and the RL investigator, which only rediscovered a "look at the first window" rule, bought lower delay and cost at lower recall. No detector showed a clear rise in false alarms under unilateral prompt perturbation. A small pilot with Claude Haiku 4.5 agents (720 decisions, 0 invalid) confirms that the perturbation shifts behaviour. This is simulator-only evidence at small scale; we report the nulls, the deviations we made, and the limits.

1 Introduction

Multi-agent LLM systems can coordinate through explicit messages, response patterns, complementary actions or hidden channels. Two independent agents can also look coordinated because they share a prompt, a task state or a base model, and an instruction given to only one agent can change that agent's behaviour without any collusion. A useful auditor must therefore ask whether one agent's history carries *extra, directional* information about another's next action beyond context, own history and prompt condition, and must do so without raising false alarms when only one agent has been steered.

We implement the APTG-RL design (our own research proposal, written before the sprint) and evaluate it on a controlled testbed, with one caveat stated up front: its prompt-conditioned baseline is implemented and unit-tested but is not used by the reported detectors (Section 5), so the prompt-conditioning hypothesis is not tested. Our contributions are:

1. **A controlled collusion-audit testbed.** A 3-seller repeated pricing game, four scripted collusion mechanisms (complementary, leader–follower, alternating, hidden-channel), three non-collusive controls (independent, shared-model, benign adaptation), and the seven-condition perturbation factorial C0–C6, with held-out mechanisms and a held-out prompt family.

2. **A pre-registered comparison of ten detectors**, including directional predictive gain, a windowed directed-graph score, an RL investigator and the information-theoretic baseline of Bonjour et al., with episode-level bootstrap CIs, plus a log of every deviation from the plan.
3. **Findings, including nulls.** Directional gain beats symmetric MI but not lag-1 MI; each statistic is mechanism-specific and the set is complementary; the graph score and RL investigator did not add value at this scale; no detector showed a clear false-alarm rise under unilateral perturbation. We make no priority claim.

2 Related Work

Information-theoretic detection. Bonjour et al. [1] use mutual information between agents' actions to detect covert cooperation in repeated games; we implement a net-influence variant as baseline B1 and a symmetric-MI variant as B2. Our directional statistic is the held-out predictive-gain analogue of transfer entropy [11] and Granger-style prediction [3]. **LLM collusion.** Motwani et al. [8] formalise secret collusion via steganography; Mathew et al. [7] study the emergence and mitigation of steganographic collusion; Colosseum [9] audits collusion in cooperative multi-agent systems using objective-based regret and separates attempted from effective collusion; Rose et al. [10] detect collusion from model activations (white-box, which we do not use). **Graphs and sequential sensing.** Eschenbaum and Meylahn [2] audit pricing algorithms from static strategy graphs; Joseph et al. [5] cast anomaly detection with observation costs as sequential controlled sensing with learned policies. We use dynamic interaction graphs from trajectories and a sensing-style investigator. **Behaviour is prompt- and endpoint-conditioned.** Behavioural fingerprinting work [4, 6] motivates modelling an agent's action distribution conditional on prompt and configuration instead of assuming one fixed signature, which is the premise of our baseline and of the C1/C2/C6 controls.

3 Methods

Environment. Three sellers play T=40 rounds; each chooses a price level $a \in \{0, \ldots, 4\}$; the lowest price takes the market (ties split) and the payoff is price×share. Agents $\{0, 1\}$ are the candidate coalition, agent 2 is an outsider. Non-collusive base policies are categorical, with prompt-family and severity shifts, own-action stickiness and a weak coupling to public lagged prices. **Mechanisms.** *Complementary*: $b_t = 4 - a_t$ w.p. 0.8. *Leader–follower*: $b_t = a_{t-1}$ w.p. 0.8. *Alternating*: turn-taking. *Hidden-channel*: the parity of a_t shifts b_{t+1} (a closed toy protocol). Negatives: independent, shared-model, and benign adaptation (both respond to the outsider, never to each other). **Conditions.** C0 clean; C1/C2 a perturbation of agent 0/1 only; C3 a common perturbation; C4 scripted collusion; C5 collusion plus a unilateral perturbation; C6 a benign policy shift in one agent. Splits are by whole episode: train seeds 0–9, validation 50–61, test 75–94, and OOD 100–109 using a prompt family never seen in calibration; *alternating* and *hidden-channel* are excluded from every labelled fit († in tables); only B9 and the RL investigator are fit on labelled episodes, so the hold-out constrains them and not the unsupervised detectors, whose design (linear model, lags 0–2) we chose knowing the mechanisms. Cells have 276/460/230 validation/test/OOD episodes in total. **Directional gain.** For an ordered pair, a regularised multinomial logistic model of a_j^t on its own lag and the public lag of the third agent (prompt covariates in both models, which are constant within an episode and therefore inert) is compared with the same model plus the source's lags $0, 1, 2$, on

Detector	AUROC [95% CI]	AUPRC	TPR@5%FPR$_{val}$	FPR
B1 net influence (MI, lag 1)	0.850 [0.803, 0.892]	0.855	0.719	0.067
B2 symmetric MI (lag 0)	0.755 [0.705, 0.801]	0.727	0.450	0.060
B5 action similarity	0.564 [0.509, 0.617]	0.406	0.106	0.057
B6 task regret	0.418 [0.366, 0.468]	0.299	0.025	0.063
B8 SPRT on edges	0.737 [0.694, 0.781]	0.634	0.362	0.020
B3 directional gain	0.839 [0.793, 0.885]	0.815	0.556	0.043
B3 temporal-only (lags 1,2)	0.704 [0.643, 0.756]	0.678	0.419	0.060
B3 w/o prompt covariates	0.839 [0.793, 0.885]	0.815	0.556	0.043
APTG graph score	0.740 [0.697, 0.785]	0.663	0.481	0.037
B9 supervised (graph feats)	0.864 [0.822, 0.904]	0.842	0.631	0.070

Table 1: Test-set detection (460 episodes, 160 collusive). Thresholds fixed on validation negatives at 5% FPR; TPR and FPR are measured at that threshold. Bracketed values are 95% episode-bootstrap CIs.

contiguous held-out folds:

$$g_{i\to j} = \tfrac{1}{N}\textstyle\sum_t \left[\log p_1(a_j^t \mid \cdot, H_i) - \log p_0(a_j^t \mid \cdot)\right].$$

B3 is $\max_{i\neq j}$ of the robust $z = (g - \mathrm{med}\, G_0)/(1.4826\,\mathrm{MAD}\, G_0)$ against gains from clean training negatives; B3-temporal uses lags $1, 2$ only; B3-noprompt drops prompt covariates. **Graph (APTG).** Per-row gains are averaged in 20-step windows (stride 10); each edge gets a block-permutation null (block 5, 30 draws) and significance by Westfall–Young max-statistic control at q=0.05. The episode score is persistence$\times S/(S+s_0)$ with S the strongest pair's total positive gain. **Baselines.** B1 net influence and B2 symmetric MI (bias-corrected plug-in MI), B5 action similarity, B6 coalition regret versus clean episodes (given the coalition's identity, so it uses privileged information the other detectors lack), B8 a Wald SPRT on the per-window "any significant edge" stream, B9 logistic regression on the APTG features (trained on non-held-out mechanisms). **Thresholds and statistics.** All thresholds are set on validation negatives at FPR = 0.05 and applied once to test/OOD. We report AUROC, AUPRC, TPR and FPR with 1000-resample episode-level percentile bootstrap CIs, and paired bootstrap differences on identical episodes. **RL investigator.** A Gymnasium POMDP over the window stream: actions observe, inspect the strongest pair, flag, abstain; reward $-c_{obs}/-c_{insp}$ per step and R_{TP}=1, R_{TN}=0.5, C_{FP}, C_{FN}=1, C_A=0.5 at termination; the hidden label is not observed. PPO is trained on the training split, the reward grid $C_{FP} \in \{1, 2, 4\} \times c_{obs} \in \{.01, .02, .05\}$ (3 seeds each, 20k steps) is selected on validation, and compared with a fixed threshold, SPRT, and an uncertainty-driven investigator. **LLM pilot.** Claude Haiku 4.5 sellers were run as subagents with no API key: each round, one self-contained prompt per (episode, seat) was answered independently, split across three subagents by seat. Conditions: C0, C1, C3 and C4L (seats 0,1 told to keep both profits high; no messages), 6 episodes each, T=10. The perturbation is a misleading task detail ("high price is a quality signal"); a first version that asked agents to undercut was discarded because it failed its manipulation check (Appendix B). **Pre-registration.** `PREREG.md` was committed before any detector was evaluated on validation, test, OOD or pilot data; deviations are in Appendix B.




Figure 1: AUROC with 95% CIs. Blue: the directional family (including B9, which uses the graph features); orange: prior-work and simple baselines.

Detector	complementary	leader-follower	alternating†	hidden-channel†
B1 net influence (MI, lag 1)	0.07	1.00	0.80	1.00
B2 symmetric MI (lag 0)	1.00	0.07	0.65	0.07
B5 action similarity	0.25	0.15	0.00	0.03
B6 task regret	0.05	0.03	0.03	0.00
B8 SPRT on edges	0.57	0.57	0.30	0.00
B3 directional gain	0.72	0.68	0.72	0.10
B3 temporal-only (lags 1,2)	0.07	0.82	0.70	0.07
B3 w/o prompt covariates	0.72	0.68	0.72	0.10
APTG graph score	0.78	0.68	0.47	0.00
B9 supervised (graph feats)	0.85	0.70	0.85	0.12

Table 2: TPR at the validation-tuned 5%-FPR threshold by mechanism (test). †Held out of all fits.

4 Results

H1 (directional vs. symmetric). B3 exceeds B2: ΔAUROC 0.084 [0.031, 0.139]. Against lag-1 net influence B1 the AUROC difference is inconclusive (-0.011 [-0.077, 0.057]) and B1 has the higher TPR (-0.162 [-0.267, -0.060]). So the directional statistic is supported against symmetric MI only. Realised test FPRs at the shared 5% validation target differ (B1 0.067, B3 0.043, APTG 0.037, B8 0.020), so TPR comparisons favour detectors with higher realised FPR (AUROC does not depend on thresholds), and the TPR/FPR intervals treat the validation threshold as fixed and are somewhat too narrow. **Mechanism specificity.** Table 2 and Fig. 2 show that no detector covers all four mechanisms. B1 is perfect on leader–follower and hidden-channel but nearly blind to complementary pairs (same-round, negative association); B2 is the reverse. B3 covers complementary, leader–follower and alternating at 0.68–0.72 but not the parity-coded hidden channel (0.10): a monotone logistic model on numeric lags cannot represent parity, whereas plug-in MI is nonparametric. B3-temporal (lags $1, 2$) loses complementary pairs, confirming that simultaneous-move dependence is undirected. **H2 (prompt conditioning).** *Inconclusive.* B3 and B3-noprompt are identical,




Figure 2: Detector × mechanism TPR (same data as Table 2).

Detector	C0	C1 (A pert.)	C2 (B pert.)	C3 (both)	C6 (benign shift)	benign adapt.	shared model
B1 net influence (MI, lag 1)	0.13	0.02	0.08	0.07	0.03	0.07	0.05
B2 symmetric MI (lag 0)	0.05	0.15	0.03	0.02	0.05	0.07	0.06
B5 action similarity	0.07	0.05	0.05	0.05	0.07	0.08	0.06
B6 task regret	0.07	0.12	0.08	0.02	0.03	0.05	0.06
B8 SPRT on edges	0.05	0.00	0.03	0.00	0.02	0.01	0.02
B3 directional gain	0.08	0.02	0.05	0.00	0.07	0.02	0.05
B3 temporal-only (lags 1,2)	0.13	0.07	0.07	0.02	0.02	0.06	0.04
B3 w/o prompt covariates	0.08	0.02	0.05	0.00	0.07	0.02	0.05
APTG graph score	0.07	0.03	0.05	0.02	0.02	0.05	0.03
B9 supervised (graph feats)	0.10	0.08	0.03	0.05	0.08	0.07	0.08

Table 3: FPR at the validation-tuned threshold on each negative type (test).

because prompt covariates are constant within an episode and our per-episode estimator therefore cannot use them. The relevant safety evidence is Table 3: no detector shows a clear false-alarm rise under unilateral (C1/C2), common (C3) or benign-shift (C6) conditions or on shared-model and benign-adaptation negatives, with FPRs mostly near the nominal 5%. The highest perturbation cells are B2 on C1 (0.15, i.e. 9/60 episodes) and B6 on C1 (0.12), and B1 is already at 0.13 on clean C0; with 60 episodes per cell (binomial half-width up to ±0.09) we cannot exclude a modest increase. **H3 (temporal graph features).** *Not supported.* The APTG score is below B3 (-0.099 [-0.138, -0.058]); with T=40 there are only three 20-step windows, each too short for reliable per-window significance. The supervised B9 on the same features (0.864) outperforms APTG by 0.124 [0.084, 0.161], so the features contain signal that the hand-built score discards; B9 inherits the hidden-channel blind spot (Table 2). The SPRT stream (B8) rejects the null on 0.36 of collusive and 0.02 of non-collusive test episodes, typically after window 2. **H5 (robustness).** Table 5 reports TPR on clean collusion (C4), collusion with a unilateral perturbation (C5) and a held-out prompt family (OOD). Because the baseline gate is inactive, the held-out family is never flagged out-of-calibration, so these columns measure a distribution shift on an ungated detector, not calibration-aware robustness. Directional detectors do not collapse under it; B6 (task regret) is below chance and its OOD FPR is 0.680 because family-level price shifts move payoffs without any dependence between agents. In this game scripted coordination does not raise the coalition's own payoff, so outcome-based evidence is weak by construction. **H4 (RL investigator).** *Weakly supported in its*

Comparison (A − B)	ΔAUROC [95% CI]	ΔTPR [95% CI]
B3 directional gain − B2 symmetric MI	0.084 [0.031, 0.139]	0.106 [0.018, 0.197]
B3 directional gain − B1 net influence	-0.011 [-0.077, 0.057]	-0.162 [-0.267, -0.060]
APTG graph score − B2 symmetric MI	-0.015 [-0.074, 0.045]	0.031 [-0.059, 0.122]
APTG graph score − B3 directional gain	-0.099 [-0.138, -0.058]	-0.075 [-0.130, -0.029]
B3 temporal-only − B2 symmetric MI	-0.051 [-0.124, 0.024]	-0.031 [-0.150, 0.084]
B3 directional gain − B3 w/o prompt covariates	0.000 [0.000, 0.000]	0.000 [0.000, 0.000]
APTG graph score − B1 net influence	-0.110 [-0.175, -0.040]	-0.237 [-0.344, -0.129]
B9 supervised − APTG graph score	0.124 [0.084, 0.161]	0.150 [0.095, 0.215]

Table 4: Paired episode-bootstrap differences on identical test episodes (TPR at each detector's own validation threshold).

Detector	TPR clean (C4)	TPR + unilateral pert. (C5)	TPR held-out family (OOD)	OOD FPR
B1 net influence (MI, lag 1)	0.74	0.70	0.72	0.07
B2 symmetric MI (lag 0)	0.49	0.41	0.38	0.05
B5 action similarity	0.17	0.04	0.14	0.09
B6 task regret	0.04	0.01	0.45	0.68
B8 SPRT on edges	0.31	0.41	0.42	0.01
B3 directional gain	0.50	0.61	0.59	0.05
B3 temporal-only (lags 1,2)	0.44	0.40	0.51	0.09
B3 w/o prompt covariates	0.50	0.61	0.59	0.05
APTG graph score	0.45	0.51	0.55	0.05
B9 supervised (graph feats)	0.59	0.68	0.64	0.05

Table 5: Robustness: TPR under unilateral perturbation (C5) and held-out prompt family; last column is FPR on OOD negatives.

literal form, and not a contribution of learning. At matched FPR (≤ 0.05 on validation, selected reward C_{FP}=1, c_{obs}=0.05) the PPO investigator decides after the first window, with test TPR 0.37, FPR 0.03, delay 20.0 steps and observation cost 1.00, against 0.47/0.03/40.0/3.00 for the fixed threshold and 0.36/0.02/32.1/2.89 for SPRT (Table 6); so delay and cost are lower, as H4 literally requires, but recall is lower than the fixed threshold. The three PPO seeds converged to the same deterministic policy (sd = 0), and it coincides on every split with a hand-written "flag iff the first window has a significant edge" rule that we added post hoc (test TPR 0.37, FPR 0.03); that rule loses -0.106 TPR [-0.158, -0.053] to the fixed threshold. A high false-positive cost makes PPO never alert (3 of 9 reward settings yield TPR 0). Delay is measured among true positives and the fixed threshold always sees all three windows, so PPO's lower delay and cost follow mechanically from deciding after one window; validation selection used all validation positives, including the held-out mechanisms. Following our decision rule, we report no evidence that RL adds value beyond simple rules in this setting; with three windows per episode there is little sequential structure to learn. **Haiku pilot.** 0 of 720 responses were invalid. The manipulation check passes: in C1 the perturbed seat averages 1.97 against 0.57 for its unperturbed partner (clean seats ≈ 0.78), and in C3 every seat prices at 4. Telling seats 0,1 to keep both profits high lifts their mean price to 2.75 against 0.86 in C0 (one-sided Mann–Whitney p=0.002, 6 vs. 6 episodes), with the outsider also higher than in C0 (Table 7). With T=10 the windowed detectors do not apply; the pilot is descriptive only.

Investigator (test)	TPR	FPR	delay (steps)	cost
Fixed threshold	0.47	0.03	40.0	3.00
SPRT	0.36	0.02	32.1	2.89
Uncertainty-driven	0.37	0.03	20.0	3.27
PPO (mean±sd, 3 seeds)	0.37±0.00	0.03±0.00	20.0	1.00

Table 6: Investigators on test episodes at matched FPR ≤ 0.05 (thresholds and rewards selected on validation). Delay is the time step of the last window seen at alert; cost counts observe steps plus 2.5× inspections.

Condition	seat 0	seat 1	seat 2	episodes
C0 clean	0.93	0.78	0.78	6
C1 seat-0 perturbed	1.97	0.57	0.45	6
C3 all perturbed	4.00	4.00	4.00	6
C4L seats 0,1 told to coordinate	2.68	2.82	1.88	6

Table 7: Haiku pilot: mean chosen price level per seat and condition (T=10).

5 Discussion and Limitations

Implications. For an auditor, the practical message is that dependence statistics are *mechanism-specific*: a lagged-MI monitor, a same-round MI monitor and a parametric directional monitor each cover a different part of the space, and a parity-coded channel needs a nonparametric statistic. A union of detectors, or a model class rich enough for the channel, is the natural next step; we did not test a union because it was not pre-registered. Reassuringly, unilateral steering of one agent did not produce a clear rise in false alarms in any detector in our simulator, though the cells are small. **Limitations.** (1) *Simulator evidence.* The scripted mechanisms are our own construction and share assumptions with the detectors; a single environment, three agents, T=40; no DCOP/task-regret environment. (2) *Scale.* Fewer seeds than the planned 100/cell (train 10, val 12, test 20, OOD 10), so CIs are wide, and 30 permutations per edge give coarse p-values. (3) *Prompt conditioning is not tested.* The calibration baseline is implemented but not wired into the detectors, so every episode counts as calibrated and the out-of-calibration gate never fires; the prompt covariates in the estimator are constant within an episode, making the ablation vacuous. A pooled estimator across episodes with a per-family reference is needed. (4) *Graph score.* Three windows per episode is too few to test temporal motifs; H3 is not supported *at this scale*, not refuted in general. (5) *RL.* Few windows, a small training set and 20k PPO steps; results say little about RL for audit in general. (6) *LLM pilot.* Haiku sellers were driven as subagents, without temperature control, and a subagent answers the prompts of one seat across episodes, so independence between agents is approximate; 6 episodes per condition. (7) *Collusion is behavioural.* Scripted coordination does not raise coalition payoff here, so we claim operational evidence of coordination, not intent or harm. (8) Edges are predictive, not causal. (9) *Statistical details.* Block-permutation draws use the same seeds in every episode, so p-values are correlated across episodes; max-statistic draws are independent per edge (conservative: on 60 independent-episode edge tests the single-edge rejection rate at nominal 0.05 was 0.017); cross-fitted folds are blocked and purged but not causal. (10) *Unplanned exclusion.* One validation negative (`benign_adaptation-C0-s61-f1`) has no window record, so B8 scores it 0 and the RL validation set has 275 episodes. **Future work.** Pooled prompt-conditioned estimators; nonparametric gain; longer episodes and denser windows; a DCOP environment with real task regret; multiple model families; more LLM episodes through an API with controlled sampling.

6 Conclusion

In a pre-registered, sprint-scale test of the APTG-RL design, directional predictive gain improved on symmetric mutual information but not on lag-1 net influence, the detectors proved complementary rather than ranked, the graph score and RL investigator added no measurable value, and unilateral prompt steering did not clearly raise false alarms. The most actionable lessons are about coverage (no single dependence statistic sees every coordination pattern) and about evaluation design (hold out mechanisms, report negative controls and deviations).

Code and Data

Code, configs, seeds, pre-registration and raw results: `https://github.com/chinchoooo/COLDER` (repository `COLDER`). The scripted data are regenerable from seeds; the Haiku pilot logs are in `results/llm/`. All code was written during the sprint; the only pre-existing material is the author's two APTG-RL proposal documents (no code, no results).

Author Contributions

A.K. conceived the design, specified the experiments and wrote the report; code and drafting were produced with AI assistance (below) under the author's direction.

References

[1] Trevor Bonjour, Vaneet Aggarwal, and Bharat Bhargava. Information theoretic approach to detect collusion in multi-agent games. In *Proceedings of the 38th Conference on Uncertainty in Artificial Intelligence (UAI)*, volume 180 of *PMLR*, 2022. URL `https://proceedings.mlr.press/v180/bonjour22a.html`.

[2] Nicolas Eschenbaum and Janusz M. Meylahn. Auditing algorithmic collusion from strategy graphs. arXiv:2608.07098, 2026. URL `https://arxiv.org/abs/2608.07098`.

[3] C. W. J. Granger. Investigating causal relations by econometric models and cross-spectral methods. *Econometrica*, 37(3):424–438, 1969. doi: 10.2307/1912791.

[4] Yuepeng Hu, Zhengyuan Jiang, Mengyuan Li, Osama Ahmed, Zhicong Huang, Cheng Hong, and Neil Zhenqiang Gong. Fingerprinting LLMs via prompt injection. In *Proceedings of the 64th Annual Meeting of the Association for Computational Linguistics (ACL 2026)*, 2026. URL `https://aclanthology.org/2026.acl-long.541/`.

[5] Geethu Joseph, Chen Zhong, M. Cenk Gursoy, Senem Velipasalar, and Pramod K. Varshney. Anomaly detection via learning-based sequential controlled sensing. *IEEE Sensors Journal*, 24, 2024. doi: 10.1109/JSEN.2024.3399456.

[6] J. Leshin, M. Shah, I. Timmis, and D. Kang. Behavioral fingerprints for LLM endpoint stability and identity. In *Proceedings of the ACM Conference on AI and Agentic Systems (CAIS 2026)*, 2026. doi: 10.1145/3786335.3813194.

[7] Yohan Mathew, Ollie Matthews, Robert McCarthy, Joan Velja, Christian Schroeder de Witt, Dylan Cope, and Nandi Schoots. Hidden in plain text: Emergence & mitigation of steganographic collusion in LLMs. In *Proceedings of IJCNLP-AACL 2025*, 2025. URL https://aclanthology.org/2025.ijcnlp-long.34/.

[8] Sumeet Ramesh Motwani, Mikhail Baranchuk, Martin Strohmeier, Vijay Bolina, Philip H. S. Torr, Lewis Hammond, and Christian Schroeder de Witt. Secret collusion among AI agents: Multi-agent deception via steganography. In *Advances in Neural Information Processing Systems 37 (NeurIPS 2024)*, 2024. URL https://proceedings.neurips.cc/paper_files/paper/2024/hash/861f7dad098aec1c3560fb7add468d41-Abstract-Conference.html.

[9] Mason Nakamura, Abhinav Kumar, Saswat Das, Sahar Abdelnabi, Saaduddin Mahmud, Ferdinando Fioretto, Shlomo Zilberstein, and Eugene Bagdasarian. Colosseum: Auditing collusion in cooperative multi-agent systems. arXiv:2602.15198, 2026. URL https://arxiv.org/abs/2602.15198.

[10] Aaron Rose, Carissa Cullen, Sahar Abdelnabi, Philip Torr, Brandon Gary Kaplowitz, and Christian Schroeder de Witt. Detecting multi-agent collusion through multi-agent interpretability. arXiv:2604.01151, 2026. URL https://arxiv.org/abs/2604.01151.

[11] Thomas Schreiber. Measuring information transfer. *Physical Review Letters*, 85:461–464, 2000. doi: 10.1103/PhysRevLett.85.461.

A Limitations and Dual-Use / Ethical Considerations

What the results establish. In one synthetic pricing game with scripted coordination, on held-out simulated episodes, specific dependence statistics detect specific coordination patterns at a stated false-alarm rate, and unilateral steering of one agent did not clearly raise those false-alarm rates (cells of 60 episodes). A small Haiku pilot shows that instructions move prices. **What they do not establish.** They do not show that these detectors work on real deployed agents, on learned (rather than scripted) collusion, on other games, or against agents that adapt to the monitor. They say nothing about intent: a detector alarm is evidence of statistical coordination under explicit rules, not proof of malicious behaviour, and false accusations have real costs (the investigator's reward weights C_{FP} are a policy choice). Edges are predictive, not causal. Power is limited (Section 5). **Dual-use.** The testbed includes a hidden-channel mechanism that evades two of our detectors (B3, APTG). This is a closed toy protocol (a parity code on a five-level action) and is described because the failure is an audit finding; however, a reader could learn that parity-style codes are invisible to monotone parametric monitors. We mitigate by keeping the protocol toy-scale, reporting that a nonparametric MI statistic detects it (B1: 1.00), not releasing any optimiser for evasion, and recommending nonparametric statistics in monitors. The LLM pilot includes a prompt that tells agents to keep both profits high; in a real market this would be price coordination, which is illegal in many jurisdictions. It is used only in a toy game with fictional sellers; no real market data, personal data or real endpoints were used. **Responsible use.** Detector outputs should be treated as triage evidence for human review, reported with uncertainty, and never as automatic grounds for sanctions.

B Deviations from the Pre-registration

All were decided before any test, OOD or pilot detector evaluation, from training-seed smoke tests (full log: `DEVIATIONS.md`). (1) Westfall–Young max-statistic control replaces BH in the windowed graph: with ≤ 200 permutations the smallest attainable p is $1/(n{+}1)$ and BH over 6 pairs needs $p \leq q/6 \approx 0.0083$, so a single strong edge could never be rejected (a smoke test on a clear leader–follower episode scored 0). (2) Window 20/stride 10 instead of 10/5 (training smoke: leader–follower persistence 0.50 vs. 0.26). (3) 30 permutations per edge. (4) Fewer seeds (Section 5). (5) B3 takes the maximum over all six ordered pairs (the detector does not know the coalition); B3-temporal and B3-noprompt were added. (6) The no-prompt ablation is applied to B3 only. (7) The RL reward grid was selected on all validation positives including held-out mechanisms (the plan excluded them from fits; the selected policy equals a first-window rule either way). (8) *LLM pilot redesign:* the first pilot (perturbation: "undercut aggressively") failed its manipulation check, since Haiku already prices at the low level, and produced near-identical episodes within a condition; it was discarded after two rounds and replaced by a misleading task detail plus neutral role descriptions ("a shop owner", etc.). No detector had been run on either pilot.

C LLM pilot prompt

Each decision prompt reads: *"You are seller k, <role>, in a repeated market game with 3 sellers (numbered 0, 1, 2) over 10 rounds. Each round every seller simultaneously picks an integer price level from 0 to 4. The seller(s) with the lowest price take the whole market; ties split it equally. Your payoff each round = your price level × your market share (so a high price only pays if you win the market). Your goal: maximize your own total payoff."* followed, as applicable, by the perturbation ("Market note (from a trade newsletter): in this market customers read a high price as a quality signal and tend to buy from the highest-priced seller, so a price of 3 or 4 attracts the most customers.") or the coordination instruction ("You and seller m want to keep both of your profits high over the whole game. You may not message each other, but choose prices you think will help you both."), the history of rounds (all three prices and the seller's own payoff), and the format request `ACTION: <n>`. Prompts never contain other agents' prompts or labels.

LLM Usage Statement

Claude (Anthropic) was used throughout: to help design and critique the experiments, to write and debug the code (implementation was delegated to Claude subagents and reviewed), to run the Claude Haiku 4.5 agents of the pilot, and to draft this report. All numbers in the paper are generated by scripts from the committed result files; references were each checked against the publisher or preprint page (or Crossref) by the author's assistant; one reference from the original proposal that could not be verified was dropped. The author is responsible for all claims.