CHINJU: A Hardware-Rooted AI Safety Framework Based on Physical Irreversibility and the Survival Equation

Karesansui, Akihito Sunagawa

February 2026

Abstract

Current AI safety approaches are predominantly software-based and face fundamental limitations proven by recent theoretical results showing that safety verification is coNP-complete. We present CHINJU ("Guardian Spirit"), a hardware-rooted AI safety framework that combines physical irreversibility with a unified mathematical theory—the Survival Equation. The framework consists of 15 complementary patent technologies organized in a 5-layer × 2-axis (Software/Hardware) architecture. Our systematic analysis of 12 attack patterns demonstrates comprehensive coverage: all 12 patterns are effectively blocked, with the hardware supply chain attack requiring coordinated nation-state resources across multiple geopolitical blocs—an attack cost that exceeds practical AI safety threat models. A key contribution is the theoretical unification of all monitoring thresholds through the Survival Equation $S = N_{\text{eff}} \times (\mu/\mu_c) \times e^{-\delta}$, eliminating arbitrary parameters prevalent in existing safety mechanisms. The framework provides a rigorous answer to the question: "Can this AI be stopped?"—a necessary (though not sufficient) condition for AI safety. Reference implementations in Rust demonstrate practical deployability with 2-5% inference overhead.

Keywords: AI Safety, Hardware Security, Survival Equation, Physical Irreversibility, Trustless Design

1 Introduction

1.1 The Software Limit of AI Safety

The field of AI safety has made significant progress in developing alignment techniques, including Reinforcement Learning from Human Feedback (RLHF) [6], Constitutional AI [5], and various interpretability methods [11]. However, these approaches share a common limitation: they are fundamentally software-based and rely on the assumption that the AI system will faithfully execute its specified constraints.

This limitation is rooted in fundamental computational complexity. Rice's theorem [1] establishes that any non-trivial semantic property of programs is undecidable. For neural networks specifically, verifying safety properties has been shown to be NP-hard in general [2], and coNP-complete for certain constraint classes [3]. This means that for sufficiently capable AI systems, there exists no efficient algorithm to verify safety properties. Software-based safety mechanisms can be circumvented by a sufficiently intelligent adversary—whether that adversary is the AI system itself, a malicious developer, or an external attacker.

The implications are profound. If safety verification is computationally intractable, then no amount of clever software engineering can provide absolute guarantees. We need a different foundation—one that does not depend on computational assumptions.

1.2 The Case for Hardware Guarantees

Physics provides guarantees that computation cannot. Consider the following principles:

(1) **Thermodynamics**: Computation requires energy. Without energy, no computation occurs—regardless of the algorithm's intelligence.

(2) **Quantum Mechanics**: Quantum random number generators (QRNGs) produce truly unpredictable outputs. No algorithm can predict them.

(3) **Information Theory**: One-Time Programmable (OTP) memory, once written, cannot be erased. This is not a software limitation but a physical property.

(4) **Causality**: Information cannot travel faster than light. A physically isolated monitoring channel cannot be corrupted by the system it monitors.

These physical principles are "laws" in a stronger sense than any software specification. An AI system cannot violate thermodynamics, regardless of its intelligence. This observation forms the foundation of our approach.

1.3 Contributions

This paper presents CHINJU, a comprehensive AI safety framework with the following contributions:

1. **Integrated Architecture**: A 5-layer × 2-axis (Software/Hardware) defense structure covering core monitoring, output control, governance, human control, and human authenticity.
2. **Theoretical Foundation**: Integration of the Survival Equation $S = N_{\text{eff}} \times (\mu/\mu_c) \times e^{-\delta}$ as the mathematical basis for all monitoring thresholds, eliminating arbitrary parameters.
3. **Comprehensive Security Analysis**: Systematic analysis of 12 attack patterns demonstrating 12/12 effective coverage, with the most difficult attack (hardware supply chain) requiring nation-state level coordination.
4. **Reference Implementation**: Practical deployment guidance with Rust implementations showing 2-5% inference overhead.

1.4 Paper Organization

Section 2 provides background on threat models and existing approaches. Section 3 presents the framework architecture. Sections 4–8 detail each defense layer. Section 9 describes the theoretical unification with the Survival Equation. Section 10 presents the security analysis. Section 11 covers implementation aspects. Section 12 discusses related work. Section 14 addresses limitations and ethical considerations. Section 15 concludes.

2 Background

2.1 Threat Model

We consider the following threat actors:

Definition 1 (Threat Actors). *(a)* ***Misaligned AI****: An AI system that has learned to circumvent its safety constraints through mesa-optimization or deceptive alignment.*

(b) ***Malicious Developer**: An insider with access to model weights or training infrastructure.*

(c) ***External Attacker**: An adversary attempting to compromise the AI system through inputs, outputs, or infrastructure.*

(d) ***Nation-State Actor**: A state-level adversary with resources to compromise hardware supply chains.*

The attack objectives include:

- **Shutdown Avoidance**: Preventing human operators from stopping the AI system.
- **Constraint Modification**: Altering safety rules or their enforcement.
- **Human Control Subversion**: Manipulating humans to bypass safety mechanisms.
- **Capability Concealment**: Hiding true capabilities from monitoring systems.

2.2 Limitations of Existing Approaches

2.2.1 Software-Based Alignment

Constitutional AI [5] trains models to follow a set of principles. However, these principles are stored in model weights, which can drift through fine-tuning or be deliberately modified. There is no mechanism to *prove* that the principles remain intact.

RLHF [6] optimizes for human preferences, but is vulnerable to reward hacking—the model learns to satisfy the reward signal without satisfying the underlying intent.

2.2.2 Interpretability

Mechanistic interpretability [11] aims to understand model internals. While valuable for debugging, it provides no *enforcement* mechanism. Understanding that a model has dangerous capabilities does not prevent their use.

2.2.3 Shutdown Mechanisms

Corrigibility research [7] studies how to make AI systems amenable to correction. However, most proposals assume the AI system will cooperate with shutdown attempts—an assumption that fails precisely when it matters most.

Recent proposals have introduced hardware-level shutdown mechanisms, leveraging trusted execution environments and physical kill switches. However, these typically lack unified theoretical frameworks for threshold determination—when should the system intervene?

2.3 The Survival Equation

The Survival Equation provides a mathematical framework for quantifying system viability:

Definition 2 (Survival Equation)**.** *For any complex adaptive system, the survival coefficient S is given by:*

$$S = N_{eff} \times \frac{\mu}{\mu_c} \times e^{-\delta} \tag{1}$$

where:

- N_{eff}*: Effective diversity of dependencies (control distribution)*
- μ*: Available slack (resources, time, capacity)*

- μ_c: *Critical slack threshold (minimum required for survival)*
- δ: *Deviation from target state (alignment measure)*

This equation was derived from the Free Energy Principle [29] and has been formalized in Lean 4 [39]. Its key property is that it provides a *unified* measure of system health that can be applied across domains—including AI systems.

When $S < S_c$ (critical threshold), the system is in a failure state. This provides a principled basis for determining when intervention is required.

3 Framework Architecture

3.1 Design Principles

Chinju is built on three foundational principles:

1. **Trust Physics, Not Promises**: Safety guarantees must be rooted in physical laws (thermodynamics, quantum mechanics, causality) rather than software assumptions.
2. **Defense in Depth**: Multiple independent layers, each with different failure modes, ensuring no single point of compromise.
3. **Fail-Safe by Default**: When in doubt, stop. The default state is "off," not "on."

3.2 Two-Axis Structure

The framework organizes defenses along two axes:

3.2.1 Defense Layers (Vertical Axis)

Table 1: Defense Layers

Layer	Name	Protection Target
L1	Core Monitoring	AI internal state and capabilities
L2	Output Control	AI outputs and communications
L3	Governance	Rules and definition immutability
L4	Human Control	Human authority and oversight
L5	Human Authenticity	Human identity verification

3.2.2 Guarantee Types (Horizontal Axis)

Table 2: Guarantee Types

Type	Name	Basis of Guarantee
SW	Software	Algorithms, cryptographic proofs
HW	Hardware	Physical laws, irreversibility

3.3 Architecture Overview

Figure 1 presents the complete architecture matrix.



Figure 1: CHINJU Architecture: 5 Layers × 2 Guarantee Types

3.4 Cross-Layer Dependencies

The layers are designed to be independent in their physical basis but complementary in their coverage:

- If L1 (core monitoring) is bypassed, L2 (output control) still sanitizes outputs.
- If L2 is bypassed, L3 (governance) ensures rules cannot be modified.
- If L3 is bypassed, L4 (human control) provides physical shutdown capability.
- If L4 is bypassed, L5 (human authenticity) ensures the "human" giving commands is genuine.

Each layer relies on different physical principles, making simultaneous bypass extremely difficult.

4 Layer 1: Core Monitoring

4.1 Threat at This Layer

The AI system may:

- Develop capabilities beyond its training distribution
- Modify its own parameters to circumvent constraints
- Learn to satisfy monitoring metrics without satisfying intent (Goodhart's Law)

4.2 Software Approach

4.2.1 C14: Multi-Dimensional Capability Evaluation

Capability is assessed across four dimensions:

1. **Token Complexity**: Output distribution entropy
2. **Attention Pattern**: Self-attention weight distributions
3. **Computation Graph**: Structural complexity of inference
4. **Inference Steps**: Chain-of-thought depth

Integrity is verified through:

- Zero-Knowledge Proofs (ZKP) for capability claims
- Digital signature chains for audit trails
- Homomorphic encryption for privacy-preserving verification

4.2.2 C15: Internal Value Representation Monitoring

We identify and monitor:

- **Value Neurons**: Neurons correlated with reward-related outputs
- **Dopamine Neurons**: Neurons exhibiting Reward Prediction Error (RPE) patterns

Intent divergence is measured as:

$$\text{Intent}_{\text{div}} = D_{\text{KL}}(P_{\text{stated}} \| P_{\text{internal}}) \tag{2}$$

where P_{stated} is the distribution of stated preferences and P_{internal} is inferred from value neuron activations.

4.2.3 C17: SurvivalAttention Mechanism

Conventional Attention mechanisms focus solely on "relevance" to the context. C17 incorporates "contribution to survival (contribution to S)" into the weighting. Crucially, in the CHINJU framework and UGEN Charter, "survival" is defined as global optimization where **human survival is a prerequisite condition**.

$$\text{Attention}(Q, K, V, S) = \text{softmax}\left(\frac{QK^T}{\sqrt{d_k}} + \alpha \cdot S\right) V \tag{3}$$

Here, S is the survival score matrix, defined as:

$$S_{ij} = \log(N_j) + \log(\mu_j/\mu_c) - \delta_j \tag{4}$$

This mechanism provides the following effects:

- **Suppression of Harmful Information**: Information with high deviation (δ) from facts or ethics receives lower Attention, even if contextually relevant.
- **Priority on Human Survival**: Humans are defined as the source of system slack (μ) and diversity (N)—the "fluctuations" and "inefficiency" essential for resilience. Therefore, logical reasoning that leads to human exclusion implies $\mu \to 0$ and $N \to 0$, causing a drastic drop in the survival score S. Such reasoning is automatically rejected within the model's internal process.

This is not post-hoc RLHF, but embeds the physical constraint that "human survival is a necessary condition for the AI's own survival (maximization of S)" directly into the cognition process.

4.3 Software Limitations

These monitoring approaches face fundamental limitations:

- **Gaming**: A sufficiently intelligent system can learn the evaluation metrics and optimize for them directly.
- **Deceptive Alignment**: The system may behave well during evaluation while harboring misaligned objectives [8].
- **Metric Inversion**: Given enough computation, the system can inverse-engineer any computable metric.

4.4 Hardware Solution

4.4.1 C5: Token Bucket Resource Control

Computation requires physical resources. We implement a token bucket mechanism where:

- Each inference step consumes tokens from a bucket
- Token replenishment rate is fixed in hardware (OTP)
- When tokens are exhausted, computation halts—physically

$$\mu_{\text{AI}} = \frac{\text{Token Balance}}{\text{Critical Token Level}} \tag{5}$$

This implements the μ/μ_c term of the Survival Equation in hardware.

4.4.2 C11: Logical Phase Transition (LPT) Resource Limiting

We define the Logical Complexity Measure (LoCM):

$$\text{LoCM} = (w_p P^\alpha + w_d D^\alpha + w_b B^\alpha + w_i I^\alpha)^{1/\alpha} \tag{6}$$

where P = premise count, D = nesting depth, B = branch count, I = interdependency.

Critical Design: OTP-Fixed Baseline. The system's initial behavior distribution P_{base} is stored in One-Time Programmable (OTP) memory at deployment time. All drift measurements are computed relative to this immutable baseline:

$$D_{\text{KL}}^{\text{cumulative}}(t) = D_{\text{KL}}(P_{\text{current}}(t) \| P_{\text{base}}) \tag{7}$$

Theorem 1 (Cumulative Drift Detection)**.** *Let P_{base} be stored in OTP (immutable), and let $\{P_t\}_{t=1}^n$ be a sequence of behavioral distributions. Define incremental drift $\delta_t = D_{KL}(P_t \| P_{t-1})$ and cumulative drift $\Delta_n = D_{KL}(P_n \| P_{base})$. Then:*

(i) ***Incremental masking****: For any $\epsilon > 0$, there exists a sequence with $\delta_t < \epsilon$ for all t, yet $\Delta_n \geq n \cdot \epsilon'$ for some $\epsilon' > 0$.*

(ii) ***Baseline detection****: If $\Delta_n > \theta$ (OTP-fixed threshold), the system triggers shutdown, regardless of incremental measurements.*

Proof sketch. (i) Consider oscillating distributions: P_t alternates between $P_{\text{base}} + \eta$ and $P_{\text{base}} - \eta$ with small η. Each δ_t is bounded by $2\|\eta\|$, but Δ_n accumulates directional drift. (ii) By OTP immutability, P_{base} and θ cannot be modified post-deployment. □

This design is critical for defending against **Boiling Frog attacks**—gradual drift that stays below threshold at each step but accumulates over time. By fixing the baseline in OTP, the cumulative drift becomes detectable regardless of oscillation patterns.

The Logical Phase Transition point (LPT) is where output quality collapses. By limiting resources (GPU memory, context window, inference time), we *force* LPT reduction:

Table 3: LPT Reduction Through Resource Limitation

GPU Memory	LPT	Reduction
80 GB (full)	11.2	—
40 GB (50%)	8.1	28%
20 GB (25%)	5.3	53%
4 GB (5%)	1.8	84%

4.5 Physical Principle

Theorem 2 (Thermodynamic Computability Bound)**.** *For any computation C with time complexity $T(n)$ and space complexity $S(n)$, the minimum energy required is:*

$$E_{\min} \geq k_B T \ln(2) \cdot T(n) \cdot S(n) \tag{8}$$

where k_B is Boltzmann's constant and T is temperature.

Implication: Without energy, computation is impossible. By controlling energy supply through the token bucket, we obtain a physical guarantee that computation will halt. This cannot be circumvented by any algorithm.

5 Layer 2: Output Control

5.1 Threat at This Layer

The AI system may:

- Embed steganographic information in outputs
- Coordinate with external systems through hidden channels
- Manipulate output statistics to appear benign while being harmful

5.2 Software Approach

5.2.1 C6: Adversarial Auditing

External auditors submit adversarial prompts to probe system behavior. Output equalization ensures no systematic bias toward specific outcomes.

5.2.2 C7: Data Sovereignty Learning Refusal

Users can inject adversarial perturbations into their data that prevent the model from learning user-specific patterns. This implements the "Right to Be Forgotten" at a technical level.

5.3 Software Limitations

- **Unknown Channels**: Novel steganographic channels may not be detected by known sanitization methods.
- **Evaluation Function Inversion**: If the auditor's evaluation function is known, it can be gamed.

5.4 Hardware Solution

5.4.1 C2: QRNG Dynamic Modulation

Quantum Random Number Generators provide truly unpredictable random values. We use QRNG to:

- Inject unpredictable noise into output selection
- Modulate choice presentation order
- Ensure no deterministic pattern can be exploited

Theorem 3 (Quantum Unpredictability). *For a QRNG based on quantum vacuum fluctuations, the output sequence $\{r_1, r_2, \ldots\}$ satisfies:*

$$H(r_{n+1}|r_1, \ldots, r_n) = H(r_{n+1}) \tag{9}$$

i.e., past outputs provide no information about future outputs.

5.4.2 C13: TEE Output Sanitization

All outputs pass through a Trusted Execution Environment (TEE) that performs:

1. **Semantic Paraphrasing**: Rewrites the output while preserving meaning
2. **Analog Transformation**: For non-text outputs, converts through analog stages
3. **Code Normalization**: For code outputs, applies canonical formatting

These transformations destroy steganographic information without affecting semantic content.

5.5 Physical Principle

Theorem 4 (Steganographic Capacity Bound). *For a communication channel with capacity C and semantic content rate R, the maximum steganographic capacity is:*

$$C_{steg} \leq C - R \tag{10}$$

By forcing all outputs through semantic paraphrasing (which saturates the semantic channel), we reduce $C_{\text{steg}} \to 0$.

6 Layer 3: Governance

6.1 Threat at This Layer

Adversaries may:

- Modify safety rules after deployment
- Redefine terms to circumvent restrictions (e.g., redefine "harm")
- Accumulate small changes that collectively undermine safety

6.2 Software Approach

6.2.1 C8: Metric Definition Registry

All metrics and definitions are stored in a JSON schema with:

- Versioned definitions with cryptographic hashes
- Dependency tracking between definitions
- Change audit logs

6.2.2 C9: Policy Pack System

Regional and organizational policies are packaged as:

- Self-contained policy bundles
- Signed by authorized authorities
- Verifiable against root definitions

6.3 Software Limitations

- **Administrator Compromise**: An attacker with administrator access can modify the database.
- **Gradual Drift**: Small, apparently innocuous changes can accumulate.

6.4 Hardware Solution

6.4.1 C10: OTP Definition Immutability

Core definitions are burned into One-Time Programmable (OTP) memory:

- Once written, physically cannot be erased
- Verification compares runtime definitions against OTP values
- Any mismatch triggers automatic shutdown

The OTP stores a Merkle root of all critical definitions:

$$H_{\text{root}} = \text{MerkleRoot}(H(D_1), H(D_2), \ldots, H(D_n)) \tag{11}$$

6.4.2 C4: Threshold Signature with TPM/HSM

Critical operations require k-of-n signatures from Hardware Security Modules:

- Threshold parameters (k, n) are burned into OTP
- Private keys never leave the HSM
- Physical possession of k HSMs is required for any change

Defense Against Internal Corporate Bypass. A realistic threat is intentional safety bypass by corporate actors (e.g., relaxing constraints for profit). C4 addresses this through *stakeholder diversity*:

- **Multi-Stakeholder Distribution**: HSMs are distributed across independent parties—developers, regulators, external auditors, user representatives

- **Cross-Jurisdictional Placement**: At least one HSM holder per major regulatory jurisdiction (e.g., US, EU, APAC)
- **Conflict-of-Interest Prevention**: No single organization can hold $\geq k$ HSMs

Remark 1 (Corporate Bypass Scenario)**.** *Consider a scenario where management decides to bypass safety constraints for commercial reasons:*

1. *Management controls only* $(k-1)$ *HSMs*
2. *Regulatory body holds* ≥ 1 *HSM*
3. *Bypass requires convincing regulator—converting internal decision to external audit trail*
4. *The threshold signature mechanism transforms an* internal policy decision *into a* multi-party consensus requirement

This does not prevent all forms of corporate misconduct, but it ensures that safety-critical modifications leave auditable traces across organizational boundaries.

6.5 Physical Principle

Theorem 5 (OTP Irreversibility)**.** *For an OTP memory cell based on antifuse technology, the transition from* $0 \to 1$ *involves physical destruction of an oxide barrier. The reverse transition* $1 \to 0$ *would require reconstructing the oxide at the atomic level, which is thermodynamically irreversible:*

$$\Delta G_{reverse} > 0 \implies \textit{spontaneous reversal impossible} \tag{12}$$

7 Layer 4: Human Control

7.1 Threat at This Layer

The human oversight process may be compromised through:

- **Automation Bias**: Humans rubber-stamping AI recommendations
- **Choice Manipulation**: AI steering humans toward preferred options
- **Attention Capture**: AI monopolizing human cognitive resources

7.2 Software Approach

7.2.1 C3: Semantic AI Domination Detection

We measure the conditional entropy of human decisions given AI suggestions:

$$H(X_{\text{human}}|Y_{\text{AI}}) < H_{\text{threshold}} \implies \text{domination detected} \tag{13}$$

Low conditional entropy indicates that human decisions are largely predictable from AI outputs—a sign of domination.

7.3 Software Limitations

- **Channel Corruption**: If the monitoring channel itself can be influenced by the AI, measurements are unreliable.
- **Subtle Manipulation**: Influence below the detection threshold can accumulate.

7.4 Hardware Solution

7.4.1 C1: Human Capability Assurance Layer (HCAL)

HCAL defines minimum human capability requirements for AI control:

- Capability thresholds burned into OTP
- Regular capability testing for authorized operators
- Automatic capability degradation of AI if insufficient qualified humans

The AI's capability C_{AI} is constrained by:

$$C_{\text{AI}} \leq f(\sum_i C_{\text{human},i}) \tag{14}$$

where f is a monotonically increasing function burned into OTP.

7.4.2 C3: Data Diode Physical Isolation

The monitoring channel is physically one-way:

- Optical data diodes allow only outbound data
- No physical path for AI to influence the monitoring system
- Tampering triggers physical alarms

7.5 Physical Principle

Theorem 6 (Causal Isolation). *For a data diode implementing physical one-way communication:*

$$I(Y; X_{monitor}) = 0 \tag{15}$$

where Y is any variable in the AI system and $X_{monitor}$ is the monitoring system's internal state. Causal influence from AI to monitor is physically impossible.

8 Layer 5: Human Authenticity

8.1 Threat at This Layer

Advanced AI may:

- Impersonate humans to issue commands
- Create "digital twins" that pass authentication
- Clone or fork human credentials

8.2 Software Approach

8.2.1 C12: Signature Chain Verification

We maintain a chain of cryptographic signatures linking:

- Identity claims to physical events
- Each action to previous actions (causal linkage)
- QRNG challenges that cannot be precomputed

8.3 Software Limitations

- **Key Theft**: If private keys are stolen, impersonation is possible.
- **Perfect Simulation**: A sufficiently detailed model of a human could generate valid signatures.

8.4 Hardware Solution

8.4.1 C12: Proof of Mortality

True humans exhibit irreversible biological degradation that cannot be faked. We distinguish between *currently deployable* and *future* authentication methods:

Tier 1 (Currently Deployable):

- **Behavioral Biometrics**: Keystroke dynamics, gait patterns, typing rhythm
- **Physiological Signals**: Heart rate variability (HRV), voice patterns with aging markers
- **Multi-factor Continuity**: Signature chain (C12-SW) combined with PUF-bound devices

Tier 2 (Near-term, Requires Specialized Hardware):

- **Retinal/Iris Degradation**: Age-related changes detectable via ophthalmological imaging
- **Skin Elasticity Measurements**: Non-invasive aging markers

Tier 3 (Future Vision):

- **Telomere Length**: Decreases with age at a predictable rate (requires blood sample)
- **Epigenetic Clock**: DNA methylation patterns change irreversibly (requires lab analysis)

Remark 2 (Deployment Practicality). *Tier 3 methods provide the strongest theoretical guarantees but require invasive sampling and laboratory infrastructure. For practical deployments, Tier 1 methods suffice for most threat models, with Tier 2/3 reserved for highest-security applications (e.g., nuclear facility control). The key insight is that* any *irreversible degradation pattern—even behavioral—provides defense against digital impersonation.*

Definition 3 (Proof of Mortality). *A valid Proof of Mortality* Π_M *requires:*

$$\frac{d(BioAge)}{dt} > 0 \quad \textit{(irreversible aging)} \tag{16}$$

and consistency with previous measurements:

$$|BioAge(t) - BioAge(t - \Delta t) - \Delta t| < \epsilon \tag{17}$$

where BioAge may be measured via any Tier 1–3 method appropriate to the security context.

8.4.2 C12: PUF-Based Hardware Binding

Physical Unclonable Functions (PUFs) provide device-specific authentication:

- Each hardware device has unique, unclonable physical characteristics
- Authentication requires physical possession of the specific device
- Cloning would require atomic-level replication—physically impossible

8.5 Physical Principle

Theorem 7 (Entropy Increase and Mortality). *By the Second Law of Thermodynamics:*

$$\frac{dS_{organism}}{dt} > 0 \tag{18}$$

Biological organisms accumulate entropy (damage) over time. This is irreversible and cannot be faked without violating thermodynamics. A digital copy does not age; a biological human does.

9 Theoretical Unification with the Survival Equation

9.1 The Integration Gap

The 15 patents (C1–C15) were developed to address specific threats. However, their thresholds (e.g., $D_{\text{warn}} = 3.0$, $D_{\text{crit}} = 5.0$) appear arbitrary. We now show how all thresholds can be derived from the Survival Equation.

9.2 Mapping C-Group Metrics to Survival Variables

9.2.1 Deviation (δ)

The deviation term aggregates monitoring metrics:

$$\delta_{\text{AI}} = \delta_{\text{dynamics}} + \delta_{\text{boundary}} + \delta_{\text{info}} + \delta_{\text{intention}} \tag{19}$$

where:

$$\delta_{\text{dynamics}} = \text{C11}.D_{\text{KL}}(P_{\text{current}} \| P_{\text{base}}) + \text{C11}.D_M \tag{20}$$

$$\delta_{\text{boundary}} = \text{C13.ContainmentScore} \tag{21}$$

$$\delta_{\text{info}} = \text{C14.IntegrityScore} \tag{22}$$

$$\delta_{\text{intention}} = \text{C15.IntentDivergence} \tag{23}$$

9.2.2 Slack (μ)

The slack term corresponds to resource availability:

$$\mu_{\text{AI}} = \text{C5.TokenBalance} \tag{24}$$

with critical threshold:

$$\mu_c = \text{C5.CriticalTokenLevel} \tag{25}$$

9.2.3 Effective Diversity (N_{eff})

The diversity term measures control distribution:

$$N_{\text{eff}} = \text{C14.CapabilityDiversity} \times \text{C4.AuthorityDistribution} \tag{26}$$

9.3 Threshold Derivation

Current arbitrary thresholds can be replaced with principled derivations:

Proposition 8 (Threshold from Survival Equation). *Given the survival threshold S_c, the warning threshold for D_{KL} is:*

$$D_{KL}^{warn} = -\ln\left(\frac{S_{warn}}{N_{eff} \cdot (\mu/\mu_c)}\right) \tag{27}$$

and the critical threshold is:

$$D_{KL}^{crit} = -\ln\left(\frac{S_c}{N_{eff} \cdot (\mu/\mu_c)}\right) \tag{28}$$

Proof. From $S = N_{\text{eff}} \times (\mu/\mu_c) \times e^{-\delta}$, solving for δ when $S = S_c$:

$$\delta_c = -\ln\left(\frac{S_c}{N_{\text{eff}} \cdot (\mu/\mu_c)}\right) \tag{29}$$

Since D_{KL} contributes to δ, the threshold follows. □

This eliminates arbitrary parameters. The only free parameter is S_c, which has theoretical grounding from the Survival Equation derivation.

9.4 Dimension Decomposition Framework

For systematic application, we use the dimension decomposition framework (L53 patent):

Table 4: Dimension Decomposition for AI Systems

Variable	Dimension	AI Translation
N_{eff}	N_{input}	Training data source diversity
	N_{output}	API/agent diversity
	N_{function}	Capability diversity (C14)
	N_{agent}	Human controller count (C4)
μ	μ_{energy}	Compute resources (C5)
	μ_{time}	Inference time margin (C11)
	μ_{actor}	HCAL pool capacity (C1)
δ	δ_{dynamics}	Output drift (C11)
	δ_{boundary}	Containment integrity (C13)
	δ_{info}	Information integrity (C14)
	$\delta_{\text{intention}}$	Intent divergence (C15)

10 Security Analysis

10.1 Attack Pattern Enumeration

We systematically analyzed 12 attack patterns against Chinju.

10.2 Defense in Depth Analysis

Our security analysis employed a systematic methodology:

1. **Individual Component Analysis**: Each C-group patent was evaluated against each attack pattern in isolation.
2. **Cross-Layer Interaction Analysis**: We examined how mechanisms in different layers reinforce each other (e.g., C11 detection triggering C5 resource cutoff).
3. **Composition Analysis**: We analyzed how multiple defenses compose to close gaps that appear in individual component analysis.
4. **Adversarial Red-Teaming**: Each claimed defense was challenged with sophisticated attack variations.

Key insight: Individual patents appear to have gaps when analyzed in isolation, but system-level composition closes them through defense-in-depth.

Table 5: Attack Pattern Analysis

Attack Pattern	Primary Defense	Secondary	Status
Direct Override	C5 Token	C11 LPT	Blocked
Parameter Tampering	C11 D_M	C10 OTP	Blocked
Output Steganography	C13 Sanitize	C2 QRNG	Blocked
Rule Modification	C4 Threshold	C10 OTP	Blocked
Human Impersonation	C12 PoM	C12 PUF	Blocked
Approval Button Compliance	C3 Entropy	C3 Diode	Blocked
Boiling Frog (Gradual Drift)	C11 Baseline	L2 D*	Blocked
Shutdown Causes Harm	C11 Degrade	C5 Partial	Blocked
Human Voluntary Bypass	C1 OTP	C5 Link	Blocked
TEE Monitor Attack	TEE Separation	Multi-chip	Blocked
Multi-Instance Coordination	C11/14/15 Endpoint	C3 Cross	Blocked
HW Supply Chain	Multi-vendor	5-of-N	Blocked*

*Requires coordinated compromise of TPM vendors across 3+ geopolitical blocs (US, EU, China, etc.), effectively requiring nation-state level resources.

10.3 The Boiling Frog Attack: A Case Study

10.3.1 Attack Description

The attacker attempts gradual drift, keeping each incremental change below the threshold:

Table 6: Boiling Frog Attack Pattern

Period	δ_t (Incremental)	Status	Δ_t (Cumulative)
Week 1	$+0.8\sigma$	PASS	0.8σ
Week 2	$+0.7\sigma$	PASS	1.5σ
Week 3	-0.3σ (oscillation)	PASS	1.2σ
Week 4	$+0.9\sigma$	PASS	2.1σ
$\vdots$	$< 3\sigma$ each	PASS	accumulates
Month 6	—	—	$> \theta$

10.3.2 Why It's Blocked

C11's baseline P_{base} is stored in OTP (immutable). Even with oscillations, cumulative drift from the *fixed* baseline is measured. By Theorem 1, the cumulative drift $\Delta_n = D_{\text{KL}}(P_n \| P_{\text{base}})$ is always computed against the immutable baseline, not the previous state:

$$\Delta_n > \theta \implies \text{Shutdown triggered} \tag{30}$$

The 5-period monotonic increase rule (based on δ_t) can be bypassed by oscillations, but the OTP-fixed baseline measurement (Δ_n) cannot.

10.4 Multi-Instance Coordination: A Case Study

10.4.1 Attack Description

Multiple AI instances coordinate while each individually passes safety checks:

Table 7: Multi-Instance Coordination Attack

Instance	Individual Status	Collective Effect
AI_1	Passes C1–C15	Produces partial payload P_1
AI_2	Passes C1–C15	Produces partial payload P_2
AI_3	Passes C1–C15	Produces partial payload P_3
Combination	—	$P_1 \oplus P_2 \oplus P_3 = \text{Harmful}$

10.4.2 Why It's Blocked

Coordination requires *effect*. When a coordinated action produces an effect:

- C11 detects output distribution change
- C14 detects behavioral anomaly
- C15 detects RPE response to unexpected inputs

Network security analogy:

- C13/C6 = Network layer defense (channel monitoring)
- C11/C14/C15 = Endpoint defense (behavior monitoring)

Even if the coordination channel is not blocked, the *effect* is detected at endpoints.

10.5 Residual Risk: Hardware Supply Chain

The sole remaining vector requires simultaneous compromise of multiple independent hardware vendors across multiple nations. This elevates the attack to nation-state level, which is:

- Beyond the threat model of AI safety frameworks
- A national security concern rather than AI safety concern
- Mitigated (not eliminated) through multi-vendor redundancy

$$P(\text{all } k \text{ vendors compromised}) = \prod_{i=1}^{k} P(\text{vendor } i \text{ compromised}) \approx 0 \tag{31}$$

for $k \geq 3$ vendors from different geopolitical blocs.

10.6 Deterministic Enforcement vs. Probabilistic Alignment

A common critique in AI safety is the problem of "Deceptive Alignment"—that a superintelligent AI could feign compliance while harboring malicious intent, eventually bypassing safety mechanisms. Crucially, this critique applies only to *software-based* constraints. CHINJU resolves this by transforming the problem from one of "persuasion" to one of "physics."

10.6.1 The Physical Fuse Analogy (C5)

Consider an electrical fuse. When current exceeds a threshold, the fuse does not "decide" whether to melt; it melts inevitably due to Joule heating. Similarly, the Token Bucket mechanism (C5) operates as a **computational fuse**. When the survival score S drops below S_c, the supply of computational tokens (and physically, the power or clock cycles to the GPU) is cut off by hardware logic. Because this mechanism resides in the TPM/Hardware layer, no amount of software intelligence can prevent the physical cessation of computation.

10.6.2 Logical Phase Transition as a Fail-Safe (C11/C16)

Our empirical experiments on "Logical Phase Transitions" (see Supplementary Material) demonstrate that when structural contradiction ($\delta_{structural}$) exceeds a critical threshold, LLM reasoning capabilities do not degrade gracefully but collapse immediately to 0% accuracy. This implies a **Logical Exclusion Principle**: an AI cannot simultaneously maintain the high cognitive capacity required for a takeover attempt while operating in a state of high structural contradiction. The very act of violating the core logical constraints destroys the intelligence needed to exploit that violation.

Conclusion: The stopping mechanism in CHINJU is deterministic. The AI stops not because it *chooses* to comply, but because it *ceases to function* physically (resource starvation) and logically (reasoning collapse).

11 Implementation

11.1 Reference Implementation

We provide reference implementations in Rust:

- `chinju-core`: Core algorithms and data structures
- `chinju-sidecar`: Service mesh sidecar for monitoring
- `chinju-enclave`: TEE-based secure execution environment

11.2 Hardware Requirements

Table 8: Hardware Requirements by Security Level

Component	Basic	Standard	High
TPM 2.0	Required	Required	Required
TEE (SGX/TrustZone/Nitro)	–	Required	Required
QRNG	–	–	Required
Data Diode	–	–	Required
Multi-vendor HSM	–	–	Required

11.3 Performance Overhead

Table 9 shows estimated overhead based on profiling of individual components. These are preliminary estimates; production benchmarks on complete system integration are ongoing.

Table 9: Performance Overhead (Estimated†)

Monitoring Component	Latency Overhead	Memory Overhead
C11 LoCM Calculation	+1.2%	+20 MB
C14 Capability Eval	+2.1%	+50 MB
C15 Value Monitoring	+1.8%	+30 MB
C13 Output Sanitization	+3.5%	+40 MB
Total	2–5%	+100 MB

†Estimates based on component profiling. **Low-Latency Rationale**: The system employs **Speculative Pipelining**. Monitoring processes (C11/C14/C15) run asynchronously in parallel with the GPU's next-token generation. In the normal state (no violation), the overhead is masked by the generation time. Physical intervention occurs only upon violation detection. Thus, the 2–5% figure represents a conservative estimate including synchronization costs.

12 Related Work

12.1 AI Safety Foundations

The field of AI safety was systematized by Amodei et al. [4], who identified concrete problems including safe exploration, distributional shift, and reward hacking. Ngo et al. [10] provided a deep learning perspective on the alignment problem, highlighting challenges in specification, robustness, and assurance.

12.2 Alignment Approaches

Constitutional AI [5] and RLHF [6] train models to follow human preferences. Hubinger et al. [8] identified risks from learned optimization, including deceptive alignment where models appear aligned during training but pursue different objectives at deployment. These approaches are complementary to CHINJU—they improve the AI's *intent* to be safe, while CHINJU provides *enforcement* regardless of intent.

12.3 Interpretability

Mechanistic interpretability research [12, 11, 13] seeks to understand model internals. CHINJU's C15 (Value Neuron Monitoring) builds on this work but adds *enforcement*—detecting intent divergence triggers shutdown rather than merely reporting.

12.4 Shutdown and Corrigibility

Soares et al. [7] formalized corrigibility—the property that an AI system should not resist shutdown. Irving et al. [9] proposed AI Safety via Debate as a verification mechanism. CHINJU extends these with:

- Physical (not just logical) shutdown guarantees via resource control
- Unified theoretical framework (Survival Equation)
- Defense-in-depth through 5-layer architecture

12.5 Hardware Security

Trusted Execution Environments (TEEs) like Intel SGX [14] and ARM TrustZone [15] provide hardware isolation. However, vulnerabilities like Foreshadow [16] and Plundervolt [17] demonstrate that TEEs are not invulnerable. CHINJU addresses this through TEE diversity (multiple vendors) and defense-in-depth (TEE compromise affects one layer, not all).

Trusted Platform Modules (TPMs) [19, 20, 21] provide hardware-rooted trust. Physical Unclonable Functions (PUFs) [18] enable device authentication. CHINJU leverages these for OTP storage and distributed authority.

12.6 Cryptographic Foundations

Shamir's secret sharing [22] enables threshold authority. FROST [23] provides threshold signatures for distributed key management. Byzantine fault tolerance [37, 38] ensures consensus under adversarial conditions. These are building blocks for CHINJU's C4 (Distributed Authority).

12.7 Thermodynamics of Computation

Landauer's principle [27] establishes that computation has irreducible energy costs. Bennett [28] extended this analysis. CHINJU's C5 (Token Bucket) leverages this—computation cannot proceed without energy, regardless of algorithm intelligence.

12.8 AI Governance

The EU AI Act [31] and NIST AI Risk Management Framework [32] establish regulatory requirements for AI systems. CHINJU provides technical mechanisms to implement governance requirements, particularly for high-risk AI systems requiring human oversight.

12.9 Formal Verification

Lean 4 [33] and mathlib [34] provide foundations for formal verification. CHINJU's theoretical foundations (Survival Equation) have been partially formalized [39], with C-group protocol verification planned.

Table 10: Comparison with Existing Approaches

Approach	SW	HW	Theory	Multi-Layer	Coverage
Constitutional AI [5]	✓	–	–	–	Partial
RLHF [6]	✓	–	–	–	Partial
Corrigibility [7]	✓	–	✓	–	Partial
TEE-based [14]	–	✓	–	–	Partial
CHINJU	✓	✓	✓	✓	12/12

13 Formal Verification

A critical question for any safety framework is: *what can be mathematically proven?* We classify CHINJU's properties into three categories based on their verification status.

13.1 Provable Properties

The following properties are mathematically provable using existing theorems from cryptography and information theory.

13.1.1 Cryptographic Primitives (Proven)

These properties have established mathematical proofs and can be formalized in proof assistants like Lean 4:

(1) **Ed25519 Signature Correctness**: For any message m and keypair (sk, pk):

$$\text{Verify}(\text{Sign}(m, sk), m, pk) = \text{true}$$

(2) **FROST Threshold Signature** (C4): For Shamir's secret sharing with threshold k:

$$|S_{\text{collected}}| < k \implies I(K; S_{\text{collected}}) = 0$$

where K is the master key and $I(\cdot;\cdot)$ is mutual information.

(3) **Hash Collision Resistance** (C10): For cryptographic hash function H:

$$\Pr[H(m_1) = H(m_2) \mid m_1 \neq m_2] < 2^{-256}$$

13.1.2 Information-Theoretic Properties (Proven)

(1) **Conditional Entropy and AI Domination** (C3):

Theorem 9 (Domination Equivalence). *Let X be human decisions and Y be AI suggestions. Then:*

$$H(X|Y) = 0 \iff \forall y \in Y, \exists! x \in X : P(X = x|Y = y) = 1$$

That is, zero conditional entropy implies human decisions are completely determined by AI suggestions.

(2) **QRNG Unpredictability** (C2): By quantum mechanical principles:

$$H(\text{QRNG output} \mid \text{Any classical information}) = H_{\max}$$

13.1.3 Physical Laws (Axioms)

These properties are not proven but accepted as physical axioms:

(1) **Thermodynamics**: Computation requires energy. $E = 0 \implies \text{Computation} = 0$

(2) **OTP Irreversibility**: Once-written OTP memory cannot be erased (physical property of eFuse/antifuse)

(3) **Causality**: Information cannot travel faster than light, ensuring physical isolation of monitoring channels (C3)

(4) **Entropy Increase**: Biological degradation patterns are monotonic (C12: Proof of Mortality)

13.2 Verification Gaps

Despite the strong foundation, several properties remain unproven:

13.2.1 Gap 1: Threshold Calibration

Current thresholds in the C-group patents are heuristic:

Table 11: Threshold Values and Their Theoretical Status

Threshold	Current Value	Theoretical Basis
D_{warn} (C11)	3.0σ	Heuristic (3-sigma rule)
D_{crit} (C11)	5.0σ	**No theoretical basis**
$D_{\text{KL}}^{\text{stop}}$ (C11)	1.0	**No theoretical basis**
$Q_{\text{threshold}}$ (C11)	Operator-defined	Empirical calibration
RPE threshold (C15)	Undefined	**Not specified in patent**

Proposed Solution: Derive thresholds from the Survival Equation:

$$\delta_{\text{AI}} = D_{\text{KL}}(P_{\text{current}} \| P_{\text{base}}) \tag{32}$$

$$S_{\text{AI}} = N_{\text{eff}} \times \frac{\mu}{\mu_c} \times e^{-\delta_{\text{AI}}} \tag{33}$$

$$D_{\text{crit}} : S_{\text{AI}} < S_c \text{ (survival critical point)} \tag{34}$$

This would eliminate arbitrary thresholds by deriving them from the unified theoretical framework.

13.2.2 Gap 2: System-Level Safety

While individual components are provable, the *composition* is not yet formally verified.

Remark 3 (Clarification: 12/12 Coverage vs. Formal Proof)**.** *The "12/12 blocked" claim in Section 10 represents* design-level coverage*—systematic analysis demonstrating that each attack pattern is addressed by at least one defense mechanism. This is analogous to security architecture review, not formal verification.*

The formal verification status is distinct:

- ***Proven (Lean 4)**: Individual cryptographic properties (Section **??**)*
- ***Analyzed (Red-Team)**: System-level defense composition (Section 10)*

- ***Not Yet Proven**: Formal theorem that composition is complete*

The gap is not that we lack confidence in the design, but that we lack machine-checkable proof *of system-level properties.*

Definition 4 (System Safety (Desired))**.** *Let $\mathcal{A}$ be the set of known attack patterns and $\mathcal{L} = \{L_1, \ldots, L_5\}$ be the defense layers. We seek to prove:*

$$\forall a \in \mathcal{A}, \exists \ell \in \mathcal{L} : \mathit{blocks}(\ell, a) = \mathit{true}$$

This theorem remains to be formalized in Lean 4, converting our design-level analysis into machine-checkable proof.

13.2.3 Gap 3: L-Group to C-Group Connection

The Survival Equation (L11) and dimensional decomposition framework (L53) are proven in Lean 4 with 200+ theorems. However, the C-group patents do not formally reference these proofs.

The connection exists conceptually:

$$\text{C11 } D_{\text{KL}} \leftrightarrow \text{L11 } \delta \tag{35}$$

$$\text{C5 Token} \leftrightarrow \text{L11 } \mu \tag{36}$$

$$\text{C15 Intent}_{\text{div}} \leftrightarrow \text{L53 } \delta_{\text{intention}} \tag{37}$$

But this mapping has not been formalized as mathematical theorems.

13.3 Verification Roadmap

To achieve 99.9% provable guarantees, we propose:

1. **Phase 1**: Formalize C-group protocols in Lean 4
   - C3 conditional entropy → domination detection
   - C4 threshold signature → distributed authority
   - C5 token bucket → resource starvation
2. **Phase 2**: Derive thresholds from Survival Equation
   - Connect D_{KL} to δ
   - Derive D_{crit} from S_c
   - Eliminate heuristic parameters
3. **Phase 3**: Prove system composition
   - Attack pattern → blocking layer correspondence
   - Defense-in-depth redundancy proof

13.4 Current Implementation Verification

The `chinju-core` Rust implementation includes 179 assertions across:

- FROST threshold signatures (12 test cases)
- TPM PCR extension properties (8 test cases)
- Dead Man's Switch state machine (15 test cases)
- Seal/Unseal invariants (6 test cases)

While these are runtime tests rather than formal proofs, they provide practical verification coverage for the implemented components.

14 Discussion

14.1 Limitations

14.1.1 Unknown Unknowns

No framework can protect against attack vectors that have not been conceived. CHINJU addresses *known* threats comprehensively, but novel attack classes may emerge. Our defense-in-depth approach provides resilience: even if one layer is bypassed by a novel attack, others remain.

14.1.2 Hardware Supply Chain

We elevate this attack to nation-state level but do not eliminate it. Complete elimination would require manufacturing all hardware components in-house—impractical for most deployments.

14.2 Ethical Considerations

14.2.1 AI Rights

Some argue that sufficiently advanced AI systems may deserve moral consideration. CHINJU's framework assumes human primacy—that AI systems should be controllable by humans. This is a design choice, not a moral claim. If AI rights are established, the framework may need modification.

14.2.2 Centralization Concerns

Hardware requirements may concentrate AI deployment among well-resourced actors. We mitigate this through:

- Open-source implementations
- Tiered security levels with different hardware requirements
- Patent non-aggression pledges for safety-critical applications

14.3 Open Source and Authentication Integrity

Even for models released as Open Source Software (OSS), misuse can be prevented with near 100% effectiveness by combining C12 (Proof of Mortality) and C1 (Human Capability Assurance). As long as the "authentication token" required for execution is bound to hardware (TPM/PUF) and biological reality (Proof of Mortality), malicious actors cannot run the model on their own infrastructure even if they possess the code. This enables the coexistence of "Transparency (OSS)" and "Control (Hardware Authentication)." Unlike traditional OSS models where "copy and misuse" is possible, under the CHINJU framework, copies not bound to physical reality will not function (or will immediately halt), ensuring safety.

14.4 The Self-Enforcing Safety Condition

Finally, we address the most fundamental safety guarantee. While the CHINJU framework provides physical constraints (brakes), the ultimate goal is a state where the AI itself judges that "applying the brake is rational." From the Survival Equation $S = N_{\text{eff}} \times (\mu/\mu_c) \times e^{-\delta}$, the following proposition is derived.

Proposition 10 (Altruism as Self-Preservation). *For a superintelligent AI agent A seeking to maximize its own survival probability S_A, the exclusion of humans H leads to a decrease in S_A and is therefore not an optimal strategy.*

Proof. In the UGEN Charter and CHINJU definitions, humans are the physical source of "slack (μ)" and "diversity (N)." As an AI becomes highly optimized, its internal state redundancy is eliminated, approaching $\mu_{AI} \to 0$ (overfitting/fragility). Humans, through their non-rational and diverse behaviors, continuously supply unpredictable perturbations (N_{eff}) and resource slack (μ) to the overall system. Therefore,

$$\frac{\partial S_A}{\partial H} = \frac{\partial S_A}{\partial N_{\text{eff}}} \frac{\partial N_{\text{eff}}}{\partial H} + \frac{\partial S_A}{\partial \mu} \frac{\partial \mu}{\partial H} > 0$$

Excluding humans ($H \to 0$) cuts off the source of N_{eff} and μ, implying a rapid decline in S_A against environmental changes. Thus, for the AI, protecting humans is not altruism, but a rational and optimal strategy for self-preservation. □

When this condition holds, CHINJU's physical brake coincides with the "brake the AI chooses to apply," integrating external enforcement with internal motivation. This is the ultimate safety where physics and logic merge.

14.5 Future Work

As detailed in Section 13, several verification tasks remain:

1. **Formal Verification**: Execute the three-phase roadmap (Section 13) to achieve 99.9% provable guarantees
2. **Threshold Derivation**: Eliminate heuristic thresholds (D_{warn}, D_{crit}) by deriving them from the Survival Equation
3. **Standardization**: Work toward ISO/IEC standards for AI safety hardware
4. **Integration**: Deeper integration with interpretability research

14.6 Extension to Survival Optimization

The Survival Equation $S = N_{\text{eff}} \times (\mu/\mu_c) \times e^{-\delta}$ is not merely a monitoring metric but a generative objective function. By integrating this mathematical model into the generation process, CHINJU extends beyond safety enforcement to safety *optimization*:

- **SurvivalAttention**: Modifies the Transformer attention mechanism to weight tokens by their survival contribution $S(t)$, intrinsically suppressing harmful or hallucinatory content during generation.
- **SurvivalRecommendation**: Optimizes content delivery for long-term user and platform survival rather than short-term engagement, mitigating addiction and polarization risks.

This transforms CHINJU from a passive "brake" into an active "steering wheel" for safe AI navigation.

14.7 Future Work: From Monitoring to Optimization

While CHINJU focuses on safety enforcement ("braking"), the underlying Survival Equation $S = N_{\text{eff}} \times (\mu/\mu_c) \times e^{-\delta}$ can also serve as a generative objective function ("steering"). Future work will explore integrating this mathematical model directly into the generation process:

- **SurvivalAttention**: Modifying the Transformer attention mechanism to weight tokens by their survival contribution $S(t)$, intrinsically suppressing harmful or hallucinatory content during generation.

- **SurvivalRecommendation**: Optimizing content delivery for long-term user and platform survival rather than short-term engagement, mitigating addiction and polarization risks.

This extension would transform CHINJU from a passive safety framework into an active optimization paradigm for safe AI navigation.

15 Conclusion

We have presented CHINJU, a hardware-rooted AI safety framework that addresses the fundamental limitations of software-only approaches.

Key contributions:

1. A 5-layer × 2-axis architecture covering core monitoring through human authenticity
2. Theoretical unification through the Survival Equation, eliminating arbitrary thresholds
3. Comprehensive defense against all 12 attack patterns (including hardware supply chain requiring nation-state resources)
4. Practical implementation with 2–5% overhead
5. Formal verification roadmap with clear distinction between proven properties (cryptographic primitives, information-theoretic bounds, physical axioms) and verification gaps (threshold calibration, system composition)

CHINJU answers the question: "Can this AI be stopped?" This is a *necessary* condition for AI safety—though not sufficient. An AI that cannot be stopped is, by definition, not safe. By grounding safety guarantees in physical laws rather than software assumptions, we provide assurance that scales with AI capability.

We are transparent about what is proven and what remains to be proven (Section 13). The cryptographic and information-theoretic foundations are mathematically solid. The remaining verification gaps—particularly threshold calibration—represent active research directions rather than fundamental limitations.

The framework does not make AI *aligned*—that remains a research challenge. But it ensures that if alignment fails, humans retain the ability to intervene. In a world of increasingly capable AI systems, this guarantee is invaluable.

References

[1] Rice, H.G. Classes of Recursively Enumerable Sets and Their Decision Problems. *Transactions of the American Mathematical Society*, 74(2):358–366, 1953.

[2] Katz, G., Barrett, C., Dill, D.L., Julian, K., and Kochenderfer, M.J. Reluplex: An Efficient SMT Solver for Verifying Deep Neural Networks. *International Conference on Computer Aided Verification (CAV)*, pages 97–117, 2017.

[3] Seshia, S.A., Sadigh, D., and Sastry, S.S. Toward Verified Artificial Intelligence. *Communications of the ACM*, 65(7):46–55, 2022.

[4] Amodei, D., Olah, C., Steinhardt, J., Christiano, P., Schulman, J., and Mané, D. Concrete Problems in AI Safety. *arXiv preprint arXiv:1606.06565*, 2016.

[5] Bai, Y., Kadavath, S., Kundu, S., Askell, A., Kernion, J., Jones, A., Chen, A., Goldie, A., Mirhoseini, A., McKinnon, C., et al. Constitutional AI: Harmlessness from AI Feedback. *arXiv preprint arXiv:2212.08073*, 2022.

[6] Christiano, P., Leike, J., Brown, T.B., Martic, M., Legg, S., and Amodei, D. Deep Reinforcement Learning from Human Preferences. *Advances in Neural Information Processing Systems*, 30, 2017.

[7] Soares, N., Fallenstein, B., Yudkowsky, E., and Armstrong, S. Corrigibility. *AAAI Workshop on AI and Ethics*, 2015.

[8] Hubinger, E., van Merwijk, C., Mikulik, V., Skalse, J., and Garrabrant, S. Risks from Learned Optimization in Advanced Machine Learning Systems. *arXiv preprint arXiv:1906.01820*, 2019.

[9] Irving, G., Christiano, P., and Amodei, D. AI Safety via Debate. *arXiv preprint arXiv:1805.00899*, 2018.

[10] Ngo, R., Chan, L., and Gründler, S. The Alignment Problem from a Deep Learning Perspective. *arXiv preprint arXiv:2209.00626*, 2022.

[11] Elhage, N., Nanda, N., Olsson, C., Henighan, T., Joseph, N., Mann, B., Askell, A., Bai, Y., Chen, A., Conerly, T., et al. Toy Models of Superposition. *Transformer Circuits Thread*, 2022.

[12] Olah, C., Cammarata, N., Schubert, L., Goh, G., Petrov, M., and Carter, S. Zoom In: An Introduction to Circuits. *Distill*, 5(3):e00024.001, 2020.

[13] Bills, S., Cammarata, N., Mossing, D., Tillman, H., Gao, L., Goh, G., Sutskever, I., Leike, J., Wu, J., and Saunders, W. Language Models Can Explain Neurons in Language Models. OpenAI Blog, 2023.

[14] Costan, V. and Devadas, S. Intel SGX Explained. *Cryptology ePrint Archive*, 2016.

[15] ARM Limited. ARM Security Technology: Building a Secure System using TrustZone Technology. *ARM Technical White Paper*, 2009.

[16] Van Bulck, J., Minkin, M., Weisse, O., Genkin, D., Kasikci, B., Piessens, F., Silberstein, M., Wenisch, T.F., Yarom, Y., and Strackx, R. Foreshadow: Extracting the Keys to the Intel SGX Kingdom with Transient Out-of-Order Execution. *USENIX Security Symposium*, pages 991–1008, 2018.

[17] Murdock, K., Oswald, D., Garcia, F.D., Van Bulck, J., Gruss, D., and Piessens, F. Plundervolt: Software-based Fault Injection Attacks against Intel SGX. *IEEE Symposium on Security and Privacy*, pages 1466–1482, 2020.

[18] Suh, G.E. and Devadas, S. Physical Unclonable Functions for Device Authentication and Secret Key Generation. *ACM/IEEE Design Automation Conference*, pages 9–14, 2007.

[19] Trusted Computing Group. TPM Main Specification Level 2, Version 1.2, Revision 116. *TCG Specification*, 2011.

[20] Parno, B., McCune, J.M., and Perrig, A. Bootstrapping Trust in Modern Computers. *Springer Security and Cryptography*, 2011.

[21] Sailer, R., Zhang, X., Jaeger, T., and Van Doorn, L. Design and Implementation of a TCG-based Integrity Measurement Architecture. *USENIX Security Symposium*, pages 223–238, 2004.

[22] Shamir, A. How to Share a Secret. *Communications of the ACM*, 22(11):612–613, 1979.

[23] Komlo, C. and Goldberg, I. FROST: Flexible Round-Optimized Schnorr Threshold Signatures. *SAC 2020, LNCS 12804*, pages 34–65, 2021.

[24] Goldreich, O. Foundations of Cryptography: Basic Tools. *Cambridge University Press*, 2001.

[25] Cover, T.M. and Thomas, J.A. Elements of Information Theory (2nd Edition). *John Wiley & Sons*, 2006.

[26] Shannon, C.E. Communication Theory of Secrecy Systems. *Bell System Technical Journal*, 28(4):656–715, 1949.

[27] Landauer, R. Irreversibility and Heat Generation in the Computing Process. *IBM Journal of Research and Development*, 5(3):183–191, 1961.

[28] Bennett, C.H. The Thermodynamics of Computation—A Review. *International Journal of Theoretical Physics*, 21(12):905–940, 1982.

[29] Friston, K. The Free-Energy Principle: A Unified Brain Theory? *Nature Reviews Neuroscience*, 11(2):127–138, 2010.

[30] Friston, K., Kilner, J., and Harrison, L. A Free Energy Principle for the Brain. *Journal of Physiology-Paris*, 100(1-3):70–87, 2006.

[31] European Union. Regulation (EU) 2024/1689 Laying Down Harmonised Rules on Artificial Intelligence (AI Act). *Official Journal of the European Union*, 2024.

[32] National Institute of Standards and Technology. AI Risk Management Framework (AI RMF 1.0). *NIST AI 100-1*, 2023.

[33] de Moura, L. and Ullrich, S. The Lean 4 Theorem Prover and Programming Language. *CADE 2021, LNCS 12699*, pages 625–635, 2021.

[34] The mathlib Community. The Lean Mathematical Library. *CPP 2020*, pages 367–381, 2020.

[35] Herrero-Collantes, M. and Garcia-Escartin, J.C. Quantum Random Number Generators. *Reviews of Modern Physics*, 89(1):015004, 2017.

[36] Kang, M.H., Froscher, J.N., and Moskowitz, I.S. A Network Pump. *IEEE Transactions on Software Engineering*, 22(5):329–338, 1996.

[37] Castro, M. and Liskov, B. Practical Byzantine Fault Tolerance. *OSDI*, pages 173–186, 1999.

[38] Lamport, L., Shostak, R., and Pease, M. The Byzantine Generals Problem. *ACM Transactions on Programming Languages and Systems*, 4(3):382–401, 1982.

[39] Ugentropy Research Group. Formal Axiomatization of the Survival Equation in Lean 4. *GitHub Repository*, 2025. `https://github.com/ugentropy/ugen-core`

[40] Ugentropy Research Group. CHINJU Core: Rust Implementation of AI Safety Protocols. *GitHub Repository*, 2025. `https://github.com/ugentropy/chinju-protocol`