





Properties 390-420: 3D Transforms, Gradient Masks, and Row Rules











Properties added after baseline 389 · CSS Transforms, Masking, and Gap Rules · font-family "Liberation Sans"








PROPS-390-TO-420

Audit of CSS properties and features implemented after baseline 389. Rows cover WebKit 3D prefix aliases, multi-axis 3D transform functions, gradient and image-set masks, and row/universal gap rules. Each row features an imperative specification and a live visual Effect demo.

#	Property	What it should do	Effect (live)
1	`-webkit-backface-visibility` legacy-vendor-alias · CSS Transforms · Chrome yes Chrome supported	Maps to `backface-visibility`. When rotated 180deg about Y with `hidden`, the back side of the element is not painted.	vis hidden visible shows flipped red card; hidden culls card
2	`-webkit-perspective` legacy-vendor-alias · CSS Transforms · Chrome yes Chrome supported	Maps to `perspective`. Establishes a 3D perspective projection distance for child elements rotated in 3D.	flat 3d flat (orthographic) vs 180px perspective camera
3	`-webkit-perspective-origin` legacy-vendor-alias · CSS Transforms · Chrome yes Chrome supported	Maps to `perspective-origin`. Controls the center vanishing point for 3D perspective projection.	left right vanishing point left (10%) vs right (90%)
4	`-webkit-transform-style` legacy-vendor-alias · CSS Transforms · Chrome yes Chrome supported	Maps to `transform-style`. `preserve-3d` preserves shared 3D space across nested elements without 2D flattening.	flat p3d flat intermediate vs preserve-3d shared space
5	`translate3d()` 3D transform function · CSS Transforms · Chrome yes Chrome supported	Translates an element in 3D along X, Y, and Z axes. Under perspective, positive Z brings the element closer to the viewer.	z:0 z:60 Z=0 baseline vs Z=60px foreshortened closer
6	`scale3d()` 3D transform function · CSS Transforms · Chrome yes Chrome supported	Applies 3D scaling factors (sx, sy, sz) across width, height, and depth dimensions.	1x 1.3/ 0.75
7	`translate (3-value)` independent transform longhand · CSS Transforms · Chrome yes Chrome supported	Accepts three values `x y z` to independently position an element in 3D without invoking `transform`.	10 4 40
8	`scale (3-value)` independent transform longhand · CSS Transforms · Chrome yes Chrome supported	Accepts three values `sx sy sz` to scale along width, height, and depth axes independently.	base scal ed
9	`rotate (axis vector)` independent transform longhand · CSS Transforms · Chrome yes Chrome supported	Accepts 4 tokens `x y z angle` (e.g. `rotate: 1 1 0 45deg`) to rotate around an arbitrary 3D vector.	1 1 0 45°

#	Property	What it should do	Effect (live)
10	`mask-image (linear-gradient)` longhand · CSS Masking · Chrome yes Chrome supported	Accepts `linear-gradient(...)` to smoothly feather or fade element painting into transparency.	linear fade
11	`mask-image (repeating-linear-gradient)` longhand · CSS Masking · Chrome yes Chrome supported	Accepts `repeating-linear-gradient(...)` to mask an element with repeating stripes or venetian-blind patterns.	striped mask
12	`mask-image (image-set)` longhand · CSS Masking · Chrome yes Chrome supported	Accepts `image-set(...)` candidate lists in mask layers, resolving the standard 1x candidate.	image-set
13	`mask (gradient shorthand)` shorthand · CSS Masking · Chrome yes Chrome supported	Parses gradient sources directly in the shorthand while resetting mask-border properties.	shorthand mask
14	`row-rule` shorthand · CSS Gap Rules · Chrome experimental Chrome experimental	Shorthand setting width, style, and color for rule divider lines painted in grid or flex row gaps.	
15	`row-rule-color` longhand · CSS Gap Rules · Chrome experimental Chrome experimental	Specifies the color of row rule divider lines painted between grid and flex rows.	
16	`row-rule-style` longhand · CSS Gap Rules · Chrome experimental Chrome experimental	Specifies the stroke style of row rules (`solid`, `dashed`, `dotted`, `double`).	
17	`row-rule-width` longhand · CSS Gap Rules · Chrome experimental Chrome experimental	Specifies the thickness of rule lines painted inside row gaps.	
18	`row-rule-visibility-items` longhand · CSS Gap Rules · Chrome experimental Chrome experimental	Controls whether row rules paint strictly between items (`between`) or also at outer boundaries (`all`, `around`).	 between vs all items
19	`row-rule-inset-start` longhand · CSS Gap Rules · Chrome experimental Chrome experimental	Insets the start (inline start / left) of the row rule divider line from the container margin.	 line indented 24px from left
20	`row-rule-inset-end` longhand · CSS Gap Rules · Chrome experimental Chrome experimental	Insets the end (inline end / right) of the row rule divider line so it stops before the right boundary.	 line stops 24px before right edge

#	Property	What it should do	Effect (live)
21	`row-rule-inset-cap` shorthand · CSS Gap Rules · Chrome experimental Chrome experimental	Shorthand setting equal start and end insets for rule lines at outer cap edges.	 16px cap inset on both ends
22	`row-rule-inset-cap-start` longhand · CSS Gap Rules · Chrome experimental Chrome experimental	Sets the inline-start cap inset specifically for row rule lines.	
23	`row-rule-inset-cap-end` longhand · CSS Gap Rules · Chrome experimental Chrome experimental	Sets the inline-end cap inset specifically for row rule lines.	
24	`row-rule-break` longhand (partial) · CSS Gap Rules · Chrome experimental Partial support	Configures break behavior (e.g. `intersection`) where row rules intersect crossing column gaps.	 break across column gap
25	`row-rule-inset` shorthand / longhand (partial) · CSS Gap Rules · Chrome experimental Partial support	Sets start and end insets simultaneously for row rules.	
26	`row-rule-inset-junction` shorthand (partial) · CSS Gap Rules · Chrome experimental Partial support	Sets insets around intersection junctions where row and column rules cross.	
27	`row-rule-inset-junction-start` longhand (partial) · CSS Gap Rules · Chrome experimental Partial support	Sets start gap offset around intersection junctions along row rules.	
28	`row-rule-inset-junction-end` longhand (partial) · CSS Gap Rules · Chrome experimental Partial support	Sets end gap offset around intersection junctions along row rules.	
29	`rule` shorthand · CSS Gap Rules · Chrome experimental Chrome experimental	Universal shorthand setting width, style, and color across both column rules and row rules simultaneously.	
30	`rule-color` shorthand / longhand · CSS Gap Rules · Chrome experimental Chrome experimental	Sets the color for all gap divider lines across both row and column directions.	
31	`rule-style` shorthand / longhand · CSS Gap Rules · Chrome experimental Chrome experimental	Sets the stroke style (`dashed`, `dotted`, `solid`) across both row and column gap rules.	

#	Property	What it should do	Effect (live)
32	`rule-width` shorthand / longhand · CSS Gap Rules · Chrome experimental Chrome experimental	Sets the line thickness for all gap rules in the container.	
33	`rule-visibility-items` shorthand / longhand · CSS Gap Rules · Chrome experimental Chrome experimental	Controls visibility of rules between items or around all perimeter edges.	
34	`rule-inset-start` shorthand / longhand · CSS Gap Rules · Chrome experimental Chrome experimental	Sets start insets across both row rules and column rules simultaneously.	
35	`rule-inset-end` shorthand / longhand · CSS Gap Rules · Chrome experimental Chrome experimental	Sets end insets across both row rules and column rules simultaneously.	
36	`rule-inset-cap` shorthand · CSS Gap Rules · Chrome experimental Chrome experimental	Sets symmetric cap insets for all gap rules in both row and column directions.	
37	`rule-overlap` longhand · CSS Gap Rules · Chrome experimental Chrome experimental	Determines how row and column rules overlap and composite when crossing at grid junctions.	
38	`rule-break` shorthand (partial) · CSS Gap Rules · Chrome experimental Partial support	Sets break modes for both row rules and column rules at gap intersections.	
39	`rule-inset` shorthand (partial) · CSS Gap Rules · Chrome experimental Partial support	Sets universal insets across start and end of all rules.	
40	`rule-inset-junction` shorthand (partial) · CSS Gap Rules · Chrome experimental Partial support	Sets junction insets across all rule intersections in both directions.	

Source: blinkless CSS catalog audit (post-389 additions) · Pattern: fixture-60/61/62/64 · Properties 390-420+ (40 demonstrated rows) · Needle: PROPS-390-TO-420 · font-family "Liberation Sans"