











Fixture 66: Anchor Positioning (one-canvas subset)


CSS Anchor Positioning one-canvas subset · absolute and fixed targets place against an in-scope anchor · font-family "Liberation Sans"

ANCHOR-POSITIONING

Audit of the eight anchor positioning properties plus `@position-try`. Each row states the contract and shows a live Effect demo with a real anchor and an absolutely positioned tip. The blinkless engine moves the tip against the anchor; engines without anchor support keep the ordinary absolute offsets. Scroll hiding is out of scope: `anchor-visible` matches `anchor-valid` on this canvas.

#	Property	What it should do	Effect (live)
1	`anchor-name` longhand · CSS Anchor Positioning · Chrome yes Chrome supported	Stores `none` or one or more dashed idents. Two boxes can carry different names and `none` clears the list. Invalid keeps the previous value.	 Tip names --a, so it sits above the left anchor. The --b anchor stays put.
2	`anchor-scope: all` longhand · CSS Anchor Positioning · Chrome yes Chrome supported	`all` hides every name on that element from descendants outside it. A target outside the scope behaves as if the anchor were missing.	 Tip is outside the scope, so it keeps its left/top offsets instead of moving.
3	`anchor-scope: list` longhand · CSS Anchor Positioning · Chrome yes Chrome supported	A name list hides only those names. Other names on the same element stay visible. Lookup only, no containing block.	 --hidden is scoped out, --shown still moves the tip above the anchor.
4	`position-anchor` longhand · CSS Anchor Positioning · Chrome yes Chrome supported	Names one dashed ident. Unknown names keep the earlier valid value. An out-of-scope name behaves like a missing name.	 Tip sits below the menu anchor, start-edge aligned. Anchor does not move.
5	`position-anchor: auto (single)` longhand · CSS Anchor Positioning · Chrome yes Chrome supported	`auto` uses the anchor only when exactly one in-scope name exists. One anchor plus `auto` moves the tip.	 Exactly one name in scope, so auto resolves to it and the tip goes above.

#	Property	What it should do	Effect (live)
6	`position-anchor: auto (ambiguous)` longhand · CSS Anchor Positioning · Chrome yes Chrome supported	With several in-scope names, `auto` does not guess. The box keeps its ordinary absolute offsets until an explicit name is given.	 Two names in scope, so auto keeps the left/top fallback near the bottom.
7	`position-area: top` longhand · CSS Anchor Positioning · Chrome yes Chrome supported	Places the absolute tip in the cell above the anchor: smaller Y than the anchor, X aligned to the anchor start edge. Paint ops move with the box.	 Core proof: tip Y above anchor Y, same start X. Anchor unmoved.
8	`position-area: none, static` longhand · CSS Anchor Positioning · Chrome yes Chrome supported	`none` keeps `left` and `top` offsets. A static box with `position-area` keeps its flow position and never moves.	 Dangling name plus none keeps offsets; static box ignores the property.
9	`position-try-fallbacks, order normal` longhands · CSS Anchor Positioning · Chrome yes Chrome supported	First fallback runs only when the base fails visibility. With `always` the base wins. With `normal` the document order wins.	 Top spills above the stage and right spills past it, so no-overflow hides the tip in both engines.
10	`position-try-order: most-inline-size` longhand · CSS Anchor Positioning · Chrome yes Chrome supported	Size keywords pick the largest passing `no-overflow` candidate on that axis. A wide candidate wins over a narrow one when both fit.	 Both sides fit, so the wider geometry wins on the inline axis.
11	`position-try, @position-try` shorthand plus at-rule · CSS Anchor Positioning · Chrome yes Chrome supported	Shorthand expands to order plus fallbacks. A dashed ident reads the area stored on `@position-try --above`. Unknown idents are skipped.	 Fallback --above resolves to the stored top area above the anchor.
12	`try-tactic flip-block` fallback tactic · CSS Anchor Positioning · Chrome yes Chrome supported	A tactic flips the chosen area across its axis after the area is known and before the final shift. Flipped Y lands on the opposite side.	 Plain bottom sits below; with the anchor near the bottom the base spills, so flip-block mirrors it above the anchor.

#	Property	What it should do	Effect (live)
13	`position-visibility: always, anchor-valid` longhand · CSS Anchor Positioning · Chrome yes Chrome supported	`always` keeps the base even off canvas with ops intact. `anchor-valid` with a dangling name keeps ordinary absolute placement and still paints.	 Always keeps paint intact; with explicit offsets the base is the fallback overlap. Dangling name falls back to left/top and paints.
14	`position-visibility: no-overflow, anchor-visible` longhand · CSS Anchor Positioning · Chrome partial Chrome partial: scroll hiding	`no-overflow` rejects candidates outside the viewport. `anchor-visible` is stored but equals `anchor-valid` here: no scroll offset exists, so no scrollport hiding.	 Same geometry as anchor-valid on this canvas. Scroll-linked hiding waits on host scroll work.

Source: blinkless anchor positioning one-canvas subset (8 properties plus @position-try) · Pattern: fixture-65 · 14 demonstrated rows · Needle: ANCHOR-POSITIONING · font-family "Liberation Sans"