Fixture 68: Mask Border, Regions, and Shapes Inside


The 26 properties of the v0.0.3 mask-border, regions, and shapes ledgers · descriptor, flow, and line-inset effects · font-family "Liberation Sans"

MASK-BORDER-REGIONS-SHAPES

One row per property, in three sections. The mask-border section records the frame on the element's blend group and paints no pixels here (the host applies the mask), so its effect cells show the declaration and the resolved shape of the data. The regions and shapes sections render live under `--engine blinkless`: named flows move content between boxes on the one canvas, exclusions reshape the lines beside a box, and shape-inside narrows the element's own lines. The default engine parses every declaration and ignores it with graceful degrade. No property in this fixture allocates a page; paged fragmentation stays a non-goal.

Mask border: descriptor on the blend group

Rows 1-13. The frame data (source bytes, slice, width, outset, repeat, mode) rides the group and composes into a frame raster the host applies as a soft mask; the frame box shows the masked frame. The unprefixed rows render under --engine blinkless; Chrome renders the -webkit-mask-box-image family (rows 8-13, plus the shared alias longhands the class rule carries).

#	Property / value	What it does	Effect
1	`mask-border` shorthand · source slice / width / outset repeat mode Partial: descriptor only	Expands into the six longhands. The used frame records on the element's blend group; no border-image cells are painted.	 host applies the mask; nothing painted here
2	`mask-border-source` none | url() | image-set() choosing url() Partial: descriptor only	Resolves the source bytes through the same resolver the first-wave mask uses. A gradient source stays rejected until the mask-source ledger lands.	
3	`mask-border-slice` 1-4 numbers or percentages, optional fill Partial: descriptor only	Cuts the source into the nine-slice grid; the fill keyword also records the center cell. Insets stay in source pixels.	
4	`mask-border-width` auto | 1-4 lengths or numbers Partial: descriptor only	Frame thickness in points on the descriptor. Percentage widths are rejected because the descriptor is written before the element box exists.	
5	`mask-border-outset` 1-4 lengths or numbers Partial: descriptor only	Expands the frame outward from the border box; recorded in points, like the border-image arithmetic it copies.	
6	`mask-border-repeat` stretch | repeat | round | space, 1-2 values Partial: descriptor only	Stores the repeat pair as a token; the host decides how to tile the frame.	
7	`mask-border-mode` alpha | luminance, initial alpha Partial: descriptor only	Stores the mode token; it is not baked into the bytes unless the first-wave SVG mask path already preprocessed them.	
8	`-webkit-mask-box-image` alias of mask-border Partial: descriptor only	Normalizes onto the standard shorthand; source order against the standard name follows the cascade.	

9	`-webkit-mask-box-image-source` alias of mask-border-source Partial: descriptor only	Same accept path as the standard source longhand.	
10	`-webkit-mask-box-image-slice` alias of mask-border-slice Partial: descriptor only	Same slice parsing, fill flag included.	
11	`-webkit-mask-box-image-width` alias of mask-border-width Partial: descriptor only	Same width rules, including the percentage rejection.	
12	`-webkit-mask-box-image-outset` alias of mask-border-outset Partial: descriptor only	Same outset rules.	
13	`-webkit-mask-box-image-repeat` alias of mask-border-repeat Partial: descriptor only	Same repeat token storage.	

Regions: named flow, tolerance, and wrap breaks

Rows 14-22. Named flows move content between boxes on the one canvas; exclusions reshape later lines; wrap breaks move line and flex geometry. No row allocates a page.

#	Property / value	What it does	Effect (live)
14	`flow-into` none | <custom-ident> [element | content] Implemented: one canvas	Names the element's content (or the element itself with the element keyword). The children leave normal flow and wait for a region.	source, flow-into: article content region, flow-from: article named flow words the words paint inside the right box
15	`flow-from` none | <custom-ident> Implemented: one canvas	Makes the element a region box that adopts the named flow's content and does not paint its own children.	source region, flow-from: story adopted words source box stays empty; region carries the words
16	`region-fragment` auto | break Implemented: one canvas	auto lets one child start in a region and continue in the next; break moves the whole child to the next region when it does not fit.	region 1 region 2, same flow break keeps a whole child on one region box
17	`flow-tolerance` normal | <length> | infinite, initial normal Implemented: masonry only	Masonry packing slack: normal is one em, a length is points, infinite keeps the shortest-column choice. Non-masonry grids ignore it.	a b infinite: b packs under a in column 1
18	`wrap-flow` auto | both | start | end | minimum | maximum | clear Implemented: one canvas	Turns a sized box into an exclusion that pushes later lines aside; auto means no exclusion.	exclusion box following lines shorten on both sides
19	`wrap-through` wrap | none, initial wrap Implemented: one canvas	none lets an element's lines use the full content width even when an earlier exclusion overlaps them.	exclusion wrap-through: none ignores this exclusion
20	`wrap-before` auto | line | avoid | avoid-line | flex | avoid-flex Implemented: line/flex	line forces a break before the element; avoid skips a soft wrap within one em of slack; flex starts a new flex line.	line one forced next line the span starts below, not inline
21	`wrap-after` auto | line | avoid | avoid-line | flex | avoid-flex Implemented: line/flex	line forces the following text onto the next line; avoid-line glues the next word across a soft wrap within slack.	ends here text after following text starts on the next line
22	`wrap-inside` auto | avoid | avoid-line | flex | avoid-flex Implemented: line/flex	avoid keeps the element's text on one line when the group fits the content width; a group that fits but not the remainder moves whole to the next line.	kept together when it fits tail the group moves as a unit, never splits mid-group

Shapes inside: line insets

Rows 23-26. shape-inside narrows the element's own lines before float exclusion runs; shape-padding shrinks that contour. The two decision-gated rows are stored no-ops.

#	Property / value	What it does	Effect (live)
23	`shape-inside` auto | outside-shape | circle() | ellipse() | inset() [|| shape-box] Implemented: lite subset	Tapers the element's own lines inside a circle, ellipse, or inset. Needs a definite content height; auto-height boxes stay full width.	inside lines narrow toward the middle of the box and widen again at the bottom, following the circle contour declared on this element. middle lines are shorter than the first line
24	`shape-padding` <length-percentage>, non-negative Implemented: with shape-inside	Shrinks the inside contour before it narrows the lines; a padding larger than the shape yields zero-width lines, never a page break.	the same circle with 10px of shape padding cuts the lines earlier, so each middle line is shorter than the same box without padding padding 10px versus the row above
25	`shape-image-threshold` decision gate: no url() image shapes Stored no-op	Kept unsupported: the shape-outside subset rejects url(), so there is no image contour to threshold. The recorded decision is not to add image shapes here.	this element declares the threshold; lines stay full width because no image shape exists in this engine. declared and ignored, no crash
26	`float-defer` <integer> | last | none, decision gate Stored no-op	Kept unsupported beyond the initial none: there is no page-float model, and the recorded decision is not to invent page boxes for it.	this element declares float-defer; the float behavior stays the initial none because the decision kept integer and last unsupported. declared and ignored, no crash

v0.0.3 ledgers: plans/v0.0.3/mask-border, plans/v0.0.3/regions, plans/v0.0.3/shapes. The mask-border rows are Partial by design (the host applies the frame); the regions and shapes rows are the one-canvas contract. Paged fragmentation stays a non-goal in every row.