

Table of Contents

Part a	1
Showing plots are different filters at w_{\max} and $w_{\max}/2$	2
Part b	4
Part c	6

Part a

```
f = phantom(256);
theta = linspace(0,177,60);
R = radon(f,theta);
backPro = iradon(R,theta,'linear','none',1,256);
figure;
subplot(3,3,1)
imshow(f,[]);
colorbar;
title('Phantom');
subplot(3,3,2)
imshow(R,[]);
colorbar;
title('Radon transform at given angles');
subplot(3,3,3)
imshow(backPro,[]);
colorbar;
title('Unfiltered Back Projection');
```



Showing plots are different filters at w_{\max} and $w_{\max}/2$

Ram Lak Filter

```
R_filt_rlk = myFilter(R,'ram-lak',1); % L = w_max
backPro_rlk_1 = iradon(R_filt_rlk,theta,'linear','none',1,256)/2;
R_filt_rlk = myFilter(R,'ram-lak',0.5); % L = w_max/2
backPro_rlk_2 = iradon(R_filt_rlk,theta,'linear','none',1,256)/2;

% Shepp Logan Filter
R_filt_shepp = myFilter(R,'shepp-logan',1); % L = w_max
backPro_shepp_1 = iradon(R_filt_shepp,theta,'linear','none',1,256)/2;
R_filt_shepp = myFilter(R,'shepp-logan',0.5); % L = w_max/2
backPro_shepp_2 = iradon(R_filt_shepp,theta,'linear','none',1,256)/2;

% Cosine Filter
R_filt_cos = myFilter(R,'cos',1); % L = w_max
backPro_cos_1 = iradon(R_filt_cos,theta,'linear','none',1,256)/2;
R_filt_cos = myFilter(R,'cos',0.5); % L = w_max/2
backPro_cos_2 = iradon(R_filt_cos,theta,'linear','none',1,256)/2;

subplot(3,3,4)
imshow(backPro_rlk_1,[]);
title('L = w_{max} Ramlak Filter');
```

```
colorbar;

subplot(3,3,5)
imshow(backPro_shepp_1,[]);
title('L = w_{max} Shepp Logan Filter');
colorbar;


subplot(3,3,6)
imshow(backPro_cos_1,[]);
title('L = w_{max} Cosine Filter');
colorbar;

subplot(3,3,7)
imshow(backPro_rlk_2,[]);
title('L = w_{max}/2 Ramlak Filter');
colorbar;

subplot(3,3,8)
imshow(backPro_shepp_2,[]);
title('L = w_{max}/2 Shepp Logan Filter');
colorbar;

subplot(3,3,9)
imshow(backPro_cos_2,[]);
title('L = w_{max}/2 Cosine Filter');
colorbar;
suptitle('Q2 - part a . Maximize the fig for better view');
```

Q2 - part a . Maximize the fig for better view



Part b

```
S0 = f;  
S1 = conv2 (f, fspecial ('gaussian', 11, 1), 'same');  
S5 = conv2 (f, fspecial ('gaussian', 51, 5), 'same');  
  
figure;  
subplot(1,3,1)  
imshow(S0,[]);  
title('S0');  
  
subplot(1,3,2)  
imshow(S1,[]);  
title('S1');  
  
subplot(1,3,3)  
imshow(S5,[]);  
title('S5');  
suptitle('Q2 Part b');  
  
% radon transforms  
Rd_S0 = radon(S0,theta);  
Rd_S1 = radon(S1,theta);  
Rd_S5 = radon(S5,theta);
```

```

% Backprojections
R0 = iradon(Rd_S0,theta,'linear','Ram-Lak',1,256);
R1 = iradon(Rd_S1,theta,'linear','Ram-Lak',1,256);
R5 = iradon(Rd_S5,theta,'linear','Ram-Lak',1,256);


rrmse_S0 = norm(S0 - R0,'fro')/norm(S0,'fro');
rrmse_S1 = norm(S1 - R1,'fro')/norm(S1,'fro');
rrmse_S5 = norm(S5 - R5,'fro')/norm(S5,'fro');

disp(strcat('RRMSE for S0: ', num2str(rrmse_S0)));
disp(strcat('RRMSE for S1: ', num2str(rrmse_S1)));
disp(strcat('RRMSE for S5: ', num2str(rrmse_S5)));
disp(' The RRMSE is least for S5 since it is the most blurred image.
Blurring results in attenuating high frequency components in the
image. The reconstruction error stems from the fact that the ram-lak
filter clips of frequencies higher than a certain threshold. Since
the most blurred image will have the most attenuated high frequency
components, the reconstruction error will be the least for it after
filtered backprojection using Ram Lak filter');

RRMSE for S0:0.29014
RRMSE for S1:0.12734
RRMSE for S5:0.019125
The RRMSE is least for S5 since it is the most blurred image.
Blurring results in attenuating high frequency components in the
image. The reconstruction error stems from the fact that the ram-lak
filter clips of frequencies higher than a certain threshold. Since
the most blurred image will have the most attenuated high frequency
components, the reconstruction error will be the least for it after
filtered backprojection using Ram Lak filter

```

Q2 Part b




Part c

```
L_arr = [1e-3:1e-3:1];

for i=1:1000
    R0 = iradon(Rd_S0,theta,'linear','Ram-Lak',L_arr(i),256);
    R1 = iradon(Rd_S1,theta,'linear','Ram-Lak',L_arr(i),256);
    R5 = iradon(Rd_S5,theta,'linear','Ram-Lak',L_arr(i),256);

    err_S0(i) = norm(S0 - R0,'fro')/norm(S0,'fro');
    err_S1(i) = norm(S1 - R1,'fro')/norm(S1,'fro');
    err_S5(i) = norm(S5 - R5,'fro')/norm(S5,'fro');
end

figure;
plot(err_S0);
hold on;
plot(err_S1);
hold on;
plot(err_S5);
legend('S0','S1','S5');
title('RRMSE plots for S1 S2 and S5 across different values of L - Q2  
Part c');
```



Published with MATLAB® R2015b