

Hyperparameter tuning, Batch Normalization, Programming Frameworks

10/10 points
(100%)

Quiz, 10 questions

✓ **Congratulations! You passed!**

Next Item



1 / 1
points

1.

If searching among a large number of hyperparameters, you should try values in a grid rather than random values, so that you can carry out the search more systematically and not rely on chance. True or False?



True



False



Correct



1 / 1
points

2.

Every hyperparameter, if set poorly, can have a huge negative impact on training, and so all hyperparameters are about equally important to tune well. True or False?



True



False



Correct

Yes. We've seen in lecture that some hyperparameters, such as the learning rate, are more critical than others.



1 / 1
points

3.

During hyperparameter search, whether you try to babysit one model ("Panda" strategy) or train a lot of models in parallel ("Caviar") is largely determined by:



Whether you use batch or mini-batch optimization



The presence of local minima (and saddle points) in your neural network

Hyperparameter tuning, Batch Normalization, Programming Frameworks



The amount of computational power you can access

Correct

10/10 points
(100%)

Quiz, 10 questions



The number of hyperparameters you have to tune



1 / 1
points

4.

If you think β

(hyperparameter for momentum) is between 0.9 and 0.99, which of the following is the recommended way to sample a value for β ?



```
1 r = np.random.rand()  
2 beta = r*0.09 + 0.9
```



```
1 r = np.random.rand()  
2 beta = 1-10**(- r - 1)
```



Correct



```
1 r = np.random.rand()  
2 beta = 1-10**(- r + 1)
```



```
1 r = np.random.rand()  
2 beta = r*0.9 + 0.09
```



1 / 1
points

5.

Finding good hyperparameter values is very time-consuming. So typically you should do it once at the start of the project, and try to find very good hyperparameters so that you don't ever have to revisit tuning them again. True or false?



True



False



Correct

Hyperparameter tuning, Batch Normalization, Programming Frameworks

10/10 points
(100%)

Quiz, 10 questions

In batch normalization as presented in the videos, if you apply it on the l th layer of your neural network, what are you normalizing?

☐ $W^{[l]}$

☐ $a^{[l]}$

☒ $z^{[l]}$



Correct

☐ $b^{[l]}$

1 / 1
points

7.

In the normalization formula $z_{norm}^{(i)} = \frac{z^{(i)} - \mu}{\sqrt{\sigma^2 + \epsilon}}$, why do we use epsilon?

☐ To speed up convergence

☒ To avoid division by zero



Correct

☐ To have a more accurate normalization

☐ In case μ is too small

1 / 1
points

8.

Which of the following statements about γ and β in Batch Norm are true?

☒ They set the mean and variance of the linear variable $z^{[l]}$ of a given layer.



Correct

Hyperparameter tuning, Batch Normalization, Programming Frameworks

Filtering, less likely to be used in a description or RMSprop, not just with gradient descent.

10/10 points
(100%)

Quiz, 10 questions

Correct

- ☐ The optimal values are $\gamma = \sqrt{\sigma^2 + \epsilon}$, and $\beta = \mu$.



Un-selected is correct

- ☐ β and γ are hyperparameters of the algorithm, which we tune via random sampling.



Un-selected is correct

- ☐ There is one global value of $\gamma \in \mathbb{R}$ and one global value of $\beta \in \mathbb{R}$ for each layer, and applies to all the hidden units in that layer.



Un-selected is correct



1 / 1
points

9.

After training a neural network with Batch Norm, at test time, to evaluate the neural network on a new example you should:

- ☐ If you implemented Batch Norm on mini-batches of (say) 256 examples, then to evaluate on one test example, duplicate that example 256 times so that you're working with a mini-batch the same size as during training.
- ☒ Perform the needed normalizations, use μ and σ^2 estimated using an exponentially weighted average across mini-batches seen during training.



Correct

- ☐ Use the most recent mini-batch's value of μ and σ^2 to perform the needed normalizations.
- ☐ Skip the step where you normalize using μ

[Math Processing Error] and σ^2

since a single test example cannot be normalized.

Hyperparameter tuning, Batch Normalization, Programming Frameworks

10/10 points
(100%)

Quiz, 10 questions



1 / 1
points

10.

Which of these statements about deep learning programming frameworks are true?
(Check all that apply)



A programming framework allows you to code up deep learning algorithms with typically fewer lines of code than a lower-level language such as Python.



Correct



Even if a project is currently open source, good governance of the project helps ensure that the it remains open even in the long term, rather than become closed or modified to benefit only one company.



Correct



Deep learning programming frameworks require cloud-based machines to run.



Un-selected is correct

