

✓ **Congratulations! You passed!**
TO PASS 80% or higher

Keep Learning

GRADE
100%

Practice Quiz: Lists

TOTAL POINTS 4

1. Given a list of filenames, we want to rename all the files with extension hpp to the extension h. To do this, we would like to generate a new list called newfilenames, consisting of the new filenames. Fill in the blanks in the code using any of the methods you've learned thus far, like a for loop or a list comprehension.

1 / 1 point

```
1 filenames = ["program.c", "stdio.hpp", "sample.hpp", "a.out", "math.hpp", "hpp.out"]
2 newfilenames=[]
3
4 for st in range(len(filenames)):
5     if "hpp" in filenames[st][-3:]:
6         newfilenames.append(filenames[st][:-2])
7     else:
8         newfilenames.append(filenames[st])
9
10 # Generate newfilenames as a list containing the new filenames
11 # using as many lines of code as your chosen method requires.
12
13
14 print(newfilenames)
15 # Should be ["program.c", "stdio.h", "sample.h", "a.out", "math.h", "hpp.out"]
16
```

Run

Reset

✓ **Correct**

Great work! You're starting to see the benefits of knowing how to operate with lists and strings.

2. The permissions of a file in a Linux system are split into three sets of three permissions: read, write, and execute for the owner, group, and others. Each of the three values can be expressed as an octal number summing each permission, with 4 corresponding to read, 2 to write, and 1 to execute. Or it can be written with a string using the letters r, w, and x or - when the permission is not granted. For example: 640 is read/write for the owner, read for the group, and no permissions for the others; converted to a string, it would be: "rw-r-----" 755 is read/write/execute for the owner, and read/execute for group and others; converted to a string, it would be: "rwxr-xr-x" Fill in the blanks to make the code convert a permission in octal format into a string format.

1 / 1 point

```
1 def octal_to_string(octal):
2     result = ""
3     value_letters = [(4,"r"),(2,"w"),(1,"x")]
4     # Iterate over each of the digits in octal
5     for p in [int(n) for n in str(octal)]:
6         # Check for each of the permissions values
7         for value, letter in value_letters:
8             if p >= value:
9                 result += letter
10                p -= value
11            else:
12                result += "-"
13    return result
14
15 print(octal_to_string(755)) # Should be rwxr-xr-x
16 print(octal_to_string(644)) # Should be rw-r--r--
17 print(octal_to_string(750)) # Should be rwxr-x---
18 print(octal_to_string(600)) # Should be rw-----
```

Run

Reset

✓ **Correct**

You nailed it! This is how we work with lists of tuples, how exciting is that!

3. Let's create a function that turns text into pig latin: a simple text transformation that modifies each word moving the first character to the end and appending "ay" to the end. For example, python ends up as ythonpay.

1 / 1 point

```
1 def pig_latin(text):
2     say = ""
3     # Separate the text into words
4     words = text.split(" ")
5     for word in words:
6         # Create the pig latin word and add it to the list
7         say+=word[1:]+word[0]+"ay "
8
9
10    # Turn the list back into a phrase
11    return say
12
13 print(pig_latin("hello how are you")) # Should be "ellohay owhay reaay ouyay"
14 print(pig_latin("programming in python is fun")) # Should be "rogrammingpay niay
    ythonpay siay unfay"
```

Run

Reset

✓ Correct

Nice! You're using some of the best string and list functions to make this work. Great job!

4. Tuples and lists are very similar types of sequences. What is the main thing that makes a tuple different from a list?

1 / 1 point

- ☐ A tuple is mutable
- ☐ A tuple contains only numeric characters
- ☒ A tuple is immutable
- ☐ A tuple can contain only one type of data at a time

✓ Correct

Awesome! Unlike lists, tuples are immutable, meaning they can't be changed.