

API Reference

Stock, Purchase, Sales & CRM Backend

Base URL	http://localhost:4000/api
Format	JSON over HTTP (application/json)
Authentication	None — POST /api/auth/login validates credentials; the app keeps the signed-in user client-side. No bearer token / API key.
Total Endpoints	61 across 14 route groups
Database	PostgreSQL via Prisma ORM
Version	1.0

Generated from the live backend source (backend/src/routes/*.js) — every endpoint, field and status code below reflects the code as it stands, not a hand-maintained spec.

Table of Contents

1. Authentication

POST /api/auth/login

2. Categories

GET /api/categories

POST /api/categories

PUT /api/categories/:id

DELETE /api/categories/:id

PATCH /api/categories/reorder

POST /api/categories/:id/sub-categories

3. Sub-Categories

PUT /api/sub-categories/:id

DELETE /api/sub-categories/:id

PATCH /api/sub-categories/reorder

4. Products

GET /api/products

POST /api/products

PUT /api/products/:id

DELETE /api/products/:id

5. Image Upload

POST /api/upload

6. Inventory

GET /api/inventory

GET /api/inventory/movements

POST /api/inventory/adjust

PUT /api/inventory/:productId

DELETE /api/inventory/movements/:id

7. Purchase Orders

GET /api/purchase-orders

POST /api/purchase-orders

PUT /api/purchase-orders/:id

PATCH /api/purchase-orders/:id/status

DELETE /api/purchase-orders/:id

8. Sales Orders

GET /api/sales-orders

POST /api/sales-orders

PUT /api/sales-orders/:id

PATCH /api/sales-orders/:id/status

DELETE /api/sales-orders/:id

9. Clients

GET /api/clients
POST /api/clients
PUT /api/clients/:id
DELETE /api/clients/:id

10. Transactions

GET /api/transactions
POST /api/transactions
PUT /api/transactions/:id
PATCH /api/transactions/:id/status
DELETE /api/transactions/:id

11. Employees (Users)

GET /api/users
POST /api/users
PUT /api/users/:id
PATCH /api/users/:id/status
DELETE /api/users/:id

12. Dashboard

GET /api/dashboard
GET /api/dashboard/notes
POST /api/dashboard/notes
PUT /api/dashboard/notes/:id
DELETE /api/dashboard/notes/:id

13. Stats (Summary Cards)

GET /api/stats/clients
GET /api/stats/products
GET /api/stats/inventory
GET /api/stats/purchase
GET /api/stats/sales
GET /api/stats/transactions
GET /api/stats/users
GET /api/stats/categories
GET /api/stats/reports

14. Settings

GET /api/settings
PUT /api/settings
POST /api/settings/password

1. Authentication

Signing in. No token is issued — the client keeps the returned user profile and sends no auth header on later requests.

POST `/api/auth/login`

Sign in

Validates an email/password pair against the users table (bcrypt-hashed) and returns the signed-in user's public profile.

REQUEST BODY (application/json)

Field	Type	Required	Description
email	string	Yes	Case-insensitive; matched exactly against users.email.
password	string	Yes	Compared against the stored bcrypt hash.

EXAMPLE REQUEST BODY

```
{
  "email": "admin@shc.com",
  "password": "shc@12345"
}
```

EXAMPLE RESPONSE

```
{
  "id": 1,
  "name": "Chinmay Modi",
  "email": "admin@shc.com",
  "role": "Admin"
}
```

STATUS CODES

Code	Meaning
200	Credentials matched — profile returned.
400	email or password missing from the body.
401	No user with that email, or the password did not match.

2. Categories

Product categories and their sub-categories. New/edited rows jump to the top of the list (sortOrder-based), so drag-to-reorder still works alongside it.

GET `/api/categories`

List categories

Returns every category, each with its subCategories embedded, ordered by sortOrder.

EXAMPLE RESPONSE

```
[
  {
    "id": 3,
    "name": "Ceramic Fiber Products",
    "description": "",
    "sortOrder": -2,
    "subCategories": [
      {
        "id": 7,
        "categoryId": 3,
        "name": "Blankets",
        "sortOrder": -1
      }
    ]
  }
]
```

STATUS CODES

Code	Meaning
200	Array of categories returned.

POST `/api/categories`

Create a category

Creates a category and places it above the current top row (sortOrder = min - 1) so it appears first.

REQUEST BODY (application/json)

Field	Type	Required	Description
name	string	Yes	Category name.
description	string	No	Defaults to "".

EXAMPLE REQUEST BODY

```
{
  "name": "Fire & Welding Protection",
  "description": "Fire blankets, welding curtains"
}
```

EXAMPLE RESPONSE

```
{
  "id": 12,
  "name": "Fire & Welding Protection",
  "description": "...",
  "sortOrder": -3,
  "subCategories": []
}
```

STATUS CODES

Code	Meaning
201	Category created.
400	name is required.

PUT /api/categories/:id

Update a category

Replaces name/description and moves the row to the top (same "last edited first" rule as create).

PATH PARAMETERS

Field	Type	Required	Description
id	integer	Yes	Category id.

REQUEST BODY (application/json)

Field	Type	Required	Description
name	string	Yes	
description	string	No	

STATUS CODES

Code	Meaning
200	Updated.
400	name is required.
404	Category not found.

DELETE /api/categories/:id

Delete a category

Cascades to its sub-categories (onDelete: Cascade in the schema). Products referencing it are not deleted.

PATH PARAMETERS

Field	Type	Required	Description
id	integer	Yes	

STATUS CODES

Code	Meaning
204	Deleted, no body.
404	Category not found.

PATCH

/api/categories/reorder

Reorder categories

Bulk-assigns sortOrder = array index for the given ids (drag-and-drop persistence). Returns the full list re-sorted.

REQUEST BODY (application/json)

Field	Type	Required	Description
orderedIds	integer []	Yes	Category ids in the desired display order.

EXAMPLE REQUEST BODY

```
{
  "orderedIds": [
    3,
    1,
    2
  ]
}
```

STATUS CODES

Code	Meaning
200	Reordered list returned.
400	orderedIds must be an array.

POST

/api/categories/:id/sub-categories

Create a sub-category

Adds a sub-category under the given category, placed above its current top row.

PATH PARAMETERS

Field	Type	Required	Description
id	integer	Yes	Parent category id.

REQUEST BODY (application/json)

Field	Type	Required	Description
name	string	Yes	

Field	Type	Required	Description
description	string	No	

STATUS CODES

Code	Meaning
201	Sub-category created.
400	name is required.
404	Parent category does not exist.

3. Sub-Categories

Standalone sub-category operations (creation lives under Categories above, since a sub-category always belongs to one).

PUT `/api/sub-categories/:id`

Update a sub-category

Renames/redescribes and moves it to the top of its parent category.

PATH PARAMETERS

Field	Type	Required	Description
id	integer	Yes	

REQUEST BODY (application/json)

Field	Type	Required	Description
name	string	Yes	
description	string	No	

STATUS CODES

Code	Meaning
200	Updated.
400	name is required.
404	Sub-category not found.

DELETE `/api/sub-categories/:id`

Delete a sub-category

PATH PARAMETERS

Field	Type	Required	Description
id	integer	Yes	

STATUS CODES

Code	Meaning
204	Deleted.
404	Sub-category not found.

PATCH `/api/sub-categories/reorder`

Reorder sub-categories within a category

REQUEST BODY (application/json)

Field	Type	Required	Description
categoryId	integer	Yes	Which category's sub-categories to reorder.
orderedIds	integer []	Yes	Sub-category ids in display order.

EXAMPLE REQUEST BODY

```
{
  "categoryId": 3,
  "orderedIds": [
    5,
    4,
    6
  ]
}
```

STATUS CODES

Code	Meaning
200	Reordered sub-categories for that category returned.
400	orderedIds must be an array.

4. Products

The product catalogue — every purchase/sale line and inventory row is ultimately a Product. Stock quantity is never edited here directly; see Inventory for that.

GET `/api/products`

List products

Every product with its category and sub-category embedded, newest/most-recently-edited first.

STATUS CODES

Code	Meaning
200	Array of products returned.

POST `/api/products`

Create a product

Creates a product. `currentStock` set here is a plain opening balance — it does not create a `stock_movements` row (use Inventory's `adjust` endpoint for an auditable opening balance instead).

REQUEST BODY (`application/json`)

Field	Type	Required	Description
<code>name</code>	string	Yes	Product name.
<code>sku</code>	string	Yes	Unique SKU / item code.
<code>categoryId</code>	integer	Yes	Must reference an existing category.
<code>subCategoryId</code>	integer	No	Optional; must belong to <code>categoryId</code> if set.
<code>unit</code>	string	Yes	e.g. "BOX", "KG", "PCS".
<code>sellingPrice</code>	number	Yes	
<code>costPrice</code>	number	Yes	
<code>currentStock</code>	integer	No	Opening stock. Defaults to 0. Not touched by later PUTs unless sent.
<code>minimumStock</code>	integer	No	Reorder point used to flag Low Stock. Defaults to 0.
<code>isActive</code>	boolean	No	Defaults to true.
<code>brand</code>	string	No	
<code>hsnCode</code>	string	No	
<code>description</code>	string	No	
<code>taxPercent</code>	number	No	Defaults to 18.0.
<code>stockLocation</code>	string	No	Defaults to "Main Warehouse".

Field	Type	Required	Description
densityVariants	string[]	No	Free-form variant lists shown on the product form.
boardVariants	string[]	No	
thicknessVariants	string[]	No	
reinforcementTypes	string[]	No	
otherSpecs	string	No	
modifiedBy	string	No	Audit field. Defaults to "Admin".

STATUS CODES

Code	Meaning
201	Product created.
400	name, sku, categoryId, sellingPrice, costPrice or unit missing.
409	SKU already exists.
404	categoryId or subCategoryId does not exist.

PUT

/api/products/:id

Update a product

Full replace of the writable fields (same shape as create).

PATH PARAMETERS

Field	Type	Required	Description
id	integer	Yes	

REQUEST BODY (application/json)

Field	Type	Required	Description
name	string	Yes	Product name.
sku	string	Yes	Unique SKU / item code.
categoryId	integer	Yes	Must reference an existing category.
subCategoryId	integer	No	Optional; must belong to categoryId if set.
unit	string	Yes	e.g. "BOX", "KG", "PCS".
sellingPrice	number	Yes	
costPrice	number	Yes	
currentStock	integer	No	Opening stock. Defaults to 0. Not touched by later PUTs unless sent.
minimumStock	integer	No	Reorder point used to flag Low Stock. Defaults to 0.
isActive	boolean	No	Defaults to true.

Field	Type	Required	Description
brand	string	No	
hsnCode	string	No	
description	string	No	
taxPercent	number	No	Defaults to 18.0.
stockLocation	string	No	Defaults to "Main Warehouse".
densityVariants	string[]	No	Free-form variant lists shown on the product form.
boardVariants	string[]	No	
thicknessVariants	string[]	No	
reinforcementTypes	string[]	No	
otherSpecs	string	No	
modifiedBy	string	No	Audit field. Defaults to "Admin".

STATUS CODES

Code	Meaning
200	Updated.
404	Product not found.
409	SKU already exists.

DELETE

/api/products/:id

Delete a product

Fails if the product has related purchase/sale line items or stock movements referencing it, per the schema's FK rules (those set productId to null on delete rather than blocking it, except where noted).

PATH PARAMETERS

Field	Type	Required	Description
id	integer	Yes	

STATUS CODES

Code	Meaning
204	Deleted.
404	Product not found.

5. Image Upload

Stores a product image on disk and hands back a relative URL to embed elsewhere (e.g. Product.imageUrl-style fields in the app).

POST

/api/upload

Upload an image

multipart/form-data with a single file field named "image". Saved to the server's uploads/ directory under a timestamp-randomised filename and served back statically from /uploads/....

REQUEST BODY (application/json)

Field	Type	Required	Description
image	file	Yes	Image file, max 5 MB. Non-image mimetypes are rejected.

EXAMPLE RESPONSE

```
{
  "url": "/uploads/1755999999999-482913765.png"
}
```

STATUS CODES

Code	Meaning
201	Stored — url is ready to use / persist.
400	No file uploaded, or the file was not an image / exceeded 5 MB.

6. Inventory

Read-only stock view (derived from Product + stock_movements) plus the two manual write paths: booking an adjustment and editing reorder settings. Purchases/Sales move stock automatically — see those sections.

GET `/api/inventory`

List inventory rows

One row per product, reshaped for the Inventory list: stock-in-hand, computed status (inStock / lowStock / outOfStock / inactive), and stock value (currentStock × costPrice).

EXAMPLE RESPONSE

```
[
  {
    "id": 42,
    "productId": 42,
    "sku": "CFB-1042",
    "name": "Ceramic Fiber Blanket 128 kg/m³",
    "category": "Ceramic Fiber Products",
    "unit": "BOX",
    "stockInHand": 612,
    "availableStock": 612,
    "minimumStock": 100,
    "costPrice": 250,
    "sellingPrice": 340,
    "stockValue": 153000,
    "stockLocation": "Main Warehouse",
    "isActive": true,
    "status": "inStock",
    "modifiedBy": "Chinmay Modi",
    "modifiedAt": "2026-07-10T14:40:00.000Z"
  }
]
```

STATUS CODES

Code	Meaning
200	Array of inventory rows.

GET `/api/inventory/movements`

Stock movement ledger

The stock_movements audit trail, newest first — optionally scoped to one product. Backs both the Item Details panel and the Transactions-style history views.

QUERY PARAMETERS

Field	Type	Required	Description
productId	integer	No	Restrict to one product's movements.
limit	integer	No	Max rows to return. Default 100, capped at 500.

EXAMPLE RESPONSE

```
[
  {
    "id": 501,
    "productId": 42,
    "type": "IN",
    "qty": 20,
    "refType": "purchase",
    "refId": 88,
    "reference": "PO-2024-10088",
    "note": "",
    "createdBy": "Chinmay Modi",
    "createdAt": "2026-07-10T14:40:00.000Z",
    "product": {
      "name": "Ceramic Fiber Blanket 128 kg/m³",
      "sku": "CFB-1042",
      "unit": "BOX"
    }
  }
]
```

STATUS CODES

Code	Meaning
200	Array of movement rows.

POST /api/inventory/adjust

Record a manual stock adjustment

The manual counterpart to purchase/sale stock moves — corrects a count, records damage/loss, or enters an opening balance. Books one stock_movements row (refType: "manual") and applies the delta to Product.currentStock in one transaction. Never lets a product go below 0.

REQUEST BODY (application/json)

Field	Type	Required	Description
productId	integer	Yes	
type	string	Yes	"IN" (adds stock) or "OUT" (removes stock).
qty	number	Yes	Must be greater than 0.
note	string	No	Shown as the adjustment's reason in the UI.
reference	string	No	Defaults to "Manual adjustment".
createdBy	string	No	Audit field. Defaults to "Admin".

EXAMPLE REQUEST BODY


```
{
  "productId": 42,
  "type": "IN",
  "qty": 5,
  "note": "Physical count correction",
  "createdBy": "Chinmay Modi"
}
```

EXAMPLE RESPONSE

```
{
  "movementId": 733,
  "item": {
    "id": 42,
    "productId": 42,
    "stockInHand": 617,
    "status": "inStock",
    "...": "..."
  }
}
```

STATUS CODES

Code	Meaning
201	Movement booked, updated inventory row returned.
400	productId missing, qty ≤ 0, or type is neither IN nor OUT.
404	Product not found.

PUT /api/inventory/:productId

Update reorder settings

The "Set Reorder Point Only" path — edits minimumStock / stockLocation / isActive without touching currentStock or the movement ledger at all.

PATH PARAMETERS

Field	Type	Required	Description
productId	integer	Yes	

REQUEST BODY (application/json)

Field	Type	Required	Description
minimumStock	integer	No	Must be ≥ 0.
stockLocation	string	No	
isActive	boolean	No	
modifiedBy	string	No	

STATUS CODES

Code	Meaning
200	Updated inventory row returned.
400	minimumStock is negative or not a number.
404	Product not found.

DELETE

/api/inventory/movements/:id

Undo a manual adjustment

Reverses exactly that movement's effect on currentStock and deletes the ledger row. Only movements with refType "manual" can be undone here — purchase/sale movements are reversed by deleting their order instead.

PATH PARAMETERS

Field	Type	Required	Description
id	integer	Yes	stock_movements row id (not a product id).

STATUS CODES

Code	Meaning
200	Undone; updated inventory row returned.
400	That movement belongs to a purchase/sale order, not a manual adjustment.
404	Movement not found.

7. Purchase Orders

Goods received from a supplier. Every linked line item adds stock automatically (stockService.applyStock, direction +1) in the same transaction as the order write.

GET `/api/purchase-orders`

List purchase orders

Every order with its items[], newest/most-recently-edited first.

STATUS CODES

Code	Meaning
200	Array of orders.

POST `/api/purchase-orders`

Create a purchase order

Creates the order and its items, then books one IN movement per product-linked line (qty totalled per product first). Atomic — if the stock write fails, the order is never created.

NOTE — items[] with a productId increase that product's currentStock immediately.

REQUEST BODY (application/json)

Field	Type	Required	Description
poNumber	string	Yes	Unique. Required on create, optional on update (kept if omitted).
supplier	string	Yes	
date	date (ISO)	Yes	
amount	number	No	Grand total; the app computes this from items client-side.
status	string	No	Pending Partial Received Cancelled. Defaults to Pending.
supplierAddress	string	No	
buyerGst	string	No	
pan	string	No	
invoiceNo	string	No	
invoiceDate	date (ISO)	No	
despatchThrough	string	No	
lrNo	string	No	
lrDate	date (ISO)	No	

Field	Type	Required	Description
vehicleNo	string	No	
freight	number	No	
placeOfSupply	string	No	
dueDate	date (ISO)	No	
items	object[]	Yes	See "items[]" — each drives a stock IN movement when productId is set.
modifiedBy	string	No	Audit field. Defaults to "Admin".

STATUS CODES

Code	Meaning
201	Order created, stock applied.
400	poNumber, supplier or date missing.
409	poNumber already exists.

PUT **/api/purchase-orders/:id**

Replace a purchase order

Reverses every stock movement the order previously created, deletes its old line items, then re-creates items and re-applies stock from the new body — all in one transaction. Effectively "delete the old effect, apply the new one".

PATH PARAMETERS

Field	Type	Required	Description
id	integer	Yes	

REQUEST BODY (application/json)

Field	Type	Required	Description
poNumber	string	Yes	Unique. Required on create, optional on update (kept if omitted).
supplier	string	Yes	
date	date (ISO)	Yes	
amount	number	No	Grand total; the app computes this from items client-side.
status	string	No	Pending Partial Received Cancelled. Defaults to Pending.
supplierAddress	string	No	
buyerGst	string	No	
pan	string	No	
invoiceNo	string	No	

Field	Type	Required	Description
invoiceDate	date (ISO)	No	
despatchThrough	string	No	
lrNo	string	No	
lrDate	date (ISO)	No	
vehicleNo	string	No	
freight	number	No	
placeOfSupply	string	No	
dueDate	date (ISO)	No	
items	object[]	Yes	See "items[]" — each drives a stock IN movement when productId is set.
modifiedBy	string	No	Audit field. Defaults to "Admin".

STATUS CODES

Code	Meaning
200	Replaced.
400	supplier or date missing.
404	Purchase order not found.
409	poNumber already exists.

PATCH

/api/purchase-orders/:id/status

Update order status

Status only — does not touch stock or line items.

PATH PARAMETERS

Field	Type	Required	Description
id	integer	Yes	

REQUEST BODY (application/json)

Field	Type	Required	Description
status	string	Yes	Pending Partial Received Cancelled.

STATUS CODES

Code	Meaning
200	Updated.
400	status missing.
404	Not found.

DELETE**/api/purchase-orders/:id**

Delete a purchase order

Reverses every stock movement it created (taking the received goods back out) before deleting the order and its items.

PATH PARAMETERS

Field	Type	Required	Description
id	integer	Yes	

STATUS CODES

Code	Meaning
204	Deleted, stock reversed.
404	Not found.

8. Sales Orders

Goods shipped to a client. Every linked line item removes stock automatically (direction -1) — rejected outright if any line would take a product below zero.

GET `/api/sales-orders`

List sales orders

Every order with its items[], newest/most-recently-edited first.

STATUS CODES

Code	Meaning
200	Array of orders.

POST `/api/sales-orders`

Create a sales order

Creates the order and its items, then books one OUT movement per product-linked line. If any product's combined line quantity exceeds its current stock, the whole write is rolled back and a 409 is returned with the exact shortfall per product.

NOTE — A 409 `InsufficientStock` response includes details: `[[productId, product, requested, available]]`.

REQUEST BODY (application/json)

Field	Type	Required	Description
<code>soNumber</code>	string	Yes	Unique. Required on create, optional on update.
<code>client</code>	string	Yes	
<code>date</code>	date (ISO)	Yes	
<code>amount</code>	number	No	
<code>status</code>	string	No	Confirmed Processing Shipped Delivered Cancelled.
<code>paymentStatus</code>	string	No	Pending Partial Paid Refunded.
<code>clientAddress</code>	string	No	
<code>buyerGstin</code>	string	No	
<code>pan</code>	string	No	
<code>invoiceNo</code>	string	No	
<code>invoiceDate</code>	date (ISO)	No	
<code>despatchedThrough</code>	string	No	
<code>destination</code>	string	No	

Field	Type	Required	Description
items	object[]	Yes	See "items[]" — each drives a stock OUT movement when productId is set.
modifiedBy	string	No	

EXAMPLE REQUEST BODY

```
{
  "soNumber": "SO-2024-10021",
  "client": "Vishal Aluminium Pvt. Ltd.",
  "date": "2026-07-12",
  "items": [
    {
      "productId": 42,
      "product": "Ceramic Fiber Blanket 128 kg/m³",
      "qty": 40,
      "unit": "BOX",
      "rate": 340
    }
  ]
}
```

STATUS CODES

Code	Meaning
201	Order created, stock removed.
400	soNumber, client or date missing.
409	soNumber already exists, OR insufficient stock on one or more lines.

PUT

/api/sales-orders/:id

Replace a sales order

Reverses the order's previous OUT movements (returning that stock), deletes the old line items, then re-creates items and re-applies the new OUT movements. Same 409-on-shortfall behaviour as create.

PATH PARAMETERS

Field	Type	Required	Description
id	integer	Yes	

REQUEST BODY (application/json)

Field	Type	Required	Description
soNumber	string	Yes	Unique. Required on create, optional on update.
client	string	Yes	
date	date (ISO)	Yes	
amount	number	No	
status	string	No	Confirmed Processing Shipped Delivered Cancelled.

Field	Type	Required	Description
paymentStatus	string	No	Pending Partial Paid Refunded.
clientAddress	string	No	
buyerGstin	string	No	
pan	string	No	
invoiceNo	string	No	
invoiceDate	date (ISO)	No	
despatchedThrough	string	No	
destination	string	No	
items	object[]	Yes	See "items[]" — each drives a stock OUT movement when productId is set.
modifiedBy	string	No	

STATUS CODES

Code	Meaning
200	Replaced.
400	client or date missing.
404	Not found.
409	soNumber conflict or insufficient stock.

PATCH /api/sales-orders/:id/status

Update order/payment status

Either or both fields may be sent; at least one is required. Does not touch stock.

PATH PARAMETERS

Field	Type	Required	Description
id	integer	Yes	

REQUEST BODY (application/json)

Field	Type	Required	Description
status	string	No	Confirmed Processing Shipped Delivered Cancelled.
paymentStatus	string	No	Pending Partial Paid Refunded.

STATUS CODES

Code	Meaning
200	Updated.
400	Neither status nor paymentStatus supplied.

Code	Meaning
404	Not found.

DELETE `/api/sales-orders/:id`

Delete a sales order

Reverses its OUT movements (putting the sold stock back) before deleting the order and its items.

PATH PARAMETERS

Field	Type	Required	Description
id	integer	Yes	

STATUS CODES

Code	Meaning
204	Deleted, stock restored.
404	Not found.

9. Clients

The company-wide client/customer list — shared by Sales, Purchase (as supplier autocomplete) and the standalone Clients module.

GET `/api/clients`

List clients

Every client, newest/most-recently-edited first.

STATUS CODES

Code	Meaning
200	Array of clients.

POST `/api/clients`

Create a client

REQUEST BODY (application/json)

Field	Type	Required	Description
<code>name</code>	string	Yes	
<code>code</code>	string	No	Auto-generated as CLT-#### (next free number) when omitted.
<code>clientType</code>	string	No	
<code>registrationType</code>	string	No	"Regular" (GST-registered) or "Unregistered/Consumer". Defaults to Regular.
<code>email</code>	string	No	
<code>phone</code>	string	No	
<code>altPhone</code>	string	No	
<code>gstIn</code>	string	No	
<code>pan</code>	string	No	
<code>clientSince</code>	date (ISO)	No	
<code>address</code>	string	No	Free-text display address. Auto-composed from regAddr1/regCity/regPin/regState when omitted.
<code>regAddr1</code>	string	No	
<code>regAddr2</code>	string	No	
<code>regCity</code>	string	No	
<code>regState</code>	string	No	

Field	Type	Required	Description
regPin	string	No	
regCountry	string	No	Defaults to "India".
shipSameAsRegistered	boolean	No	Defaults to true.
shipSameAsBilling	boolean	No	Defaults to false.
shipAddr1..shipCountry	string	No	Mirror the reg* fields; only used when shipSameAsRegistered is false.
billingMode	string	No	"shipping" "registered" "custom". Defaults to "shipping".
billAddr1..billCountry	string	No	Only used when billingMode is "custom".
paymentTerms	string	No	
priceList	string	No	
openingBalance	number	No	
creditLimit	number	No	
creditDays	integer	No	
contactPerson	string	No	
contactDesignation	string	No	
contactPhone	string	No	
contactEmail	string	No	
modifiedBy	string	No	

STATUS CODES

Code	Meaning
201	Created.
400	name is required.
409	That client code is already in use.

PUT **/api/clients/:id**

Update a client

PATH PARAMETERS

Field	Type	Required	Description
id	integer	Yes	

REQUEST BODY (application/json)

Field	Type	Required	Description
name	string	Yes	
code	string	No	Auto-generated as CLT-#### (next free number) when omitted.
clientType	string	No	
registrationType	string	No	"Regular" (GST-registered) or "Unregistered/Consumer". Defaults to Regular.
email	string	No	
phone	string	No	
altPhone	string	No	
gstIn	string	No	
pan	string	No	
clientSince	date (ISO)	No	
address	string	No	Free-text display address. Auto-composed from regAddr1/regCity/regPin/regState when omitted.
regAddr1	string	No	
regAddr2	string	No	
regCity	string	No	
regState	string	No	
regPin	string	No	
regCountry	string	No	Defaults to "India".
shipSameAsRegistered	boolean	No	Defaults to true.
shipSameAsBilling	boolean	No	Defaults to false.
shipAddr1..shipCountry	string	No	Mirror the reg* fields; only used when shipSameAsRegistered is false.
billingMode	string	No	"shipping" "registered" "custom". Defaults to "shipping".
billAddr1..billCountry	string	No	Only used when billingMode is "custom".
paymentTerms	string	No	
priceList	string	No	
openingBalance	number	No	
creditLimit	number	No	
creditDays	integer	No	
contactPerson	string	No	

Field	Type	Required	Description
contactDesignation	string	No	
contactPhone	string	No	
contactEmail	string	No	
modifiedBy	string	No	

STATUS CODES

Code	Meaning
200	Updated.
400	name is required.
404	Client not found.
409	Client code already in use.

DELETE `/api/clients/:id`

Delete a client

PATH PARAMETERS

Field	Type	Required	Description
id	integer	Yes	

STATUS CODES

Code	Meaning
204	Deleted.
404	Client not found.

10. Transactions

A lightweight goods-movement log shown on the Transactions page — separate from the stock_movements ledger behind Product.currentStock.

GET `/api/transactions`

List transactions

STATUS CODES

Code	Meaning
200	Array of transactions.

POST `/api/transactions`

Create a transaction

REQUEST BODY (application/json)

Field	Type	Required	Description
item	string	Yes	
type	string	No	"Inbound" "Outbound". Defaults to Inbound.
party	string	No	
poNumber	string	No	
date	date (ISO)	Yes	
status	string	No	Received Shipped Pending Delivered. Defaults to Pending.
notes	string	No	
modifiedBy	string	No	

STATUS CODES

Code	Meaning
201	Created.
400	item/date missing or type/status invalid.

PUT `/api/transactions/:id`

Update a transaction

PATH PARAMETERS

Field	Type	Required	Description
id	integer	Yes	

REQUEST BODY (application/json)

Field	Type	Required	Description
item	string	Yes	
type	string	No	"Inbound" "Outbound". Defaults to Inbound.
party	string	No	
poNumber	string	No	
date	date (ISO)	Yes	
status	string	No	Received Shipped Pending Delivered. Defaults to Pending.
notes	string	No	
modifiedBy	string	No	

STATUS CODES

Code	Meaning
200	Updated.
400	Validation failed.
404	Not found.

PATCH /api/transactions/:id/status

Update transaction status

PATH PARAMETERS

Field	Type	Required	Description
id	integer	Yes	

REQUEST BODY (application/json)

Field	Type	Required	Description
status	string	Yes	Received Shipped Pending Delivered.

STATUS CODES

Code	Meaning
200	Updated.
400	Invalid status.
404	Not found.

DELETE `/api/transactions/:id`

Delete a transaction

PATH PARAMETERS

Field	Type	Required	Description
<code>id</code>	integer	Yes	

STATUS CODES

Code	Meaning
204	Deleted.
404	Not found.

11. Employees (Users)

The employee list — shares the same `users` table as login, so an employee record is also that person's account. passwordHash is never returned by any endpoint here.

GET `/api/users`

List employees

Public fields only — id, code, name, email, role, phone, department, isActive, lastLoginAt, modifiedBy, modifiedAt, createdAt.

STATUS CODES

Code	Meaning
200	Array of employees.

POST `/api/users`

Create an employee

Also creates that person's login. The password is bcrypt-hashed before storage.

REQUEST BODY (application/json)

Field	Type	Required	Description
name	string	Yes	
email	string	Yes	Must look like a real email; unique.
role	string	No	Admin Manager Salesman Stock Manager Accountant. Invalid values fall back to Salesman.
phone	string	No	
department	string	No	
isActive	boolean	No	
password	string	No	Create: defaults to "shc@12345" if omitted. Update: only re-hashed if sent (otherwise unchanged).
code	string	No	Auto-generated as USR-#### when omitted.
modifiedBy	string	No	

STATUS CODES

Code	Meaning
201	Created.
400	name/email missing or email malformed.
409	That email or code is already in use.

PUT**/api/users/:id****Update an employee****PATH PARAMETERS**

Field	Type	Required	Description
id	integer	Yes	

REQUEST BODY (application/json)

Field	Type	Required	Description
name	string	Yes	
email	string	Yes	Must look like a real email; unique.
role	string	No	Admin Manager Salesman Stock Manager Accountant. Invalid values fall back to Salesman.
phone	string	No	
department	string	No	
isActive	boolean	No	
password	string	No	Create: defaults to "shc@12345" if omitted. Update: only re-hashed if sent (otherwise unchanged).
code	string	No	Auto-generated as USR-#### when omitted.
modifiedBy	string	No	

STATUS CODES

Code	Meaning
200	Updated.
400	Validation failed.
404	Not found.
409	Email/code already in use.

PATCH**/api/users/:id/status****Activate / deactivate an employee****PATH PARAMETERS**

Field	Type	Required	Description
id	integer	Yes	

REQUEST BODY (application/json)

Field	Type	Required	Description
isActive	boolean	Yes	

STATUS CODES

Code	Meaning
200	Updated.
400	isActive missing.
404	Not found.

DELETE**/api/users/:id**

Delete an employee

Refuses to delete the last remaining Admin account, so the system can never end up with zero admins.

PATH PARAMETERS

Field	Type	Required	Description
id	integer	Yes	

STATUS CODES

Code	Meaning
204	Deleted.
404	Not found.
409	Target is the last Admin account.

12. Dashboard

One consolidated snapshot endpoint for the home dashboard, plus CRUD for its Notes/To-do widget.

GET

/api/dashboard

Dashboard snapshot

Everything the dashboard renders in one call: summary tiles, 6-month purchase/sales/new-client series with month-over-month change, stock-value-by-category donut slices, the 6 most recent transactions, pending purchase deliveries, and the 5 lowest-stock products. Nothing here is invented — a metric with no honest baseline comes back null rather than a fake percentage.

EXAMPLE RESPONSE

```
{
  "summary": {
    "totalStockItems": 4820,
    "outOfStock": 27,
    "lowStock": 12,
    "duesFromClients": 812400,
    "topSellingProduct": "Ceramic Fiber Blanket 128 kg/m³",
    "todaysSales": 24500,
    "monthSales": 612000
  },
  "charts": {
    "purchases": {
      "series": [
        {
          "label": "Mar",
          "value": 120000
        }
      ],
      "changePct": 8.2
    },
    "sales": "...",
    "newClients": "..."
  },
  "categorySlices": [
    {
      "label": "Ceramic Fiber Products",
      "value": 900000,
      "percent": 42.1
    }
  ],
  "recentTransactions": [
    "..."
  ],
  "incomingDeliveries": [
    "..."
  ],
  "lowStockAlerts": [
    "..."
  ]
}
```

STATUS CODES

Code	Meaning
200	Snapshot returned.

GET

/api/dashboard/notes

List dashboard notes

QUERY PARAMETERS

Field	Type	Required	Description
userId	integer	No	Scope to one user's notes; omit for all.

STATUS CODES

Code	Meaning
200	Array of notes, ordered by sortOrder.

POST /api/dashboard/notes

Create a note

REQUEST BODY (application/json)

Field	Type	Required	Description
text	string	Yes	
userId	integer	No	Owning user.
done	boolean	No	Defaults to false.

STATUS CODES

Code	Meaning
201	Created, appended to the end.
400	text is required.

PUT /api/dashboard/notes/:id

Update a note

Either field may be sent.

PATH PARAMETERS

Field	Type	Required	Description
id	integer	Yes	

REQUEST BODY (application/json)

Field	Type	Required	Description
text	string	No	Cannot be sent empty.
done	boolean	No	

STATUS CODES

Code	Meaning
200	Updated.
400	text sent but empty.
404	Not found.

DELETE /api/dashboard/notes/:id

Delete a note

PATH PARAMETERS

Field	Type	Required	Description
id	integer	Yes	

STATUS CODES

Code	Meaning
204	Deleted.
404	Not found.

13. Stats (Summary Cards)

One GET per module, each returning that page's summary-card values plus a matching `trends` object (percent change vs. last month, or `null` when there's no honest baseline to compare against). Every list page's cards come from here — nothing is computed client-side or hardcoded.

GET `/api/stats/clients`

Clients summary

EXAMPLE RESPONSE

```
{
  "totalClients": 1037,
  "gstRegistered": 640,
  "unregistered": 397,
  "statesCovered": 18,
  "trends": {
    "totalClients": 3.2,
    "gstRegistered": 3.2,
    "unregistered": 3.2,
    "statesCovered": null
  },
  "topStates": [
    {
      "state": "Gujarat",
      "count": 412
    }
  ],
  "quickStats": {
    "avgOrderValue": 24600,
    "repeatClientsPct": 61
  },
  "newThisMonth": [
    {
      "id": 1040,
      "code": "CLT-1040",
      "name": "Vishal Aluminium Pvt. Ltd.",
      "state": "Gujarat"
    }
  ]
}
```

STATUS CODES

Code	Meaning
200	

GET `/api/stats/products`

Products summary

EXAMPLE RESPONSE

```
{
  "totalProducts": 512,
  "lowStock": 14,
  "outOfStock": 3,
  "totalValue": 4820000,
  "trends": {
    "totalProducts": 1.8,
    "lowStock": null,
    "outOfStock": null,
    "totalValue": null
  }
}
```

STATUS CODES

Code	Meaning
200	

GET **/api/stats/inventory**

Inventory summary

EXAMPLE RESPONSE

```
{
  "totalItems": 29,
  "inStock": 3,
  "lowStock": 4,
  "outOfStock": 1,
  "inactive": 0,
  "totalQty": 5231,
  "totalValue": 3250,
  "trends": {
    "totalItems": null,
    "movement": 12.4
  }
}
```

STATUS CODES

Code	Meaning
200	

GET **/api/stats/purchase**

Purchase summary

EXAMPLE RESPONSE

```
{
  "totalOrders": 88,
  "purchaseMTD": 612000,
  "amountPaid": 480000,
  "amountDue": 132000,
  "trends": {
    "totalOrders": 5.1,
    "purchaseMTD": 9.3,
    "amountPaid": null,
    "amountDue": null
  }
}
```

STATUS CODES

Code	Meaning
200	

GET **/api/stats/sales**

Sales summary

EXAMPLE RESPONSE

```
{
  "salesMTD": 612000,
  "totalOrders": 214,
  "amountDue": 812400,
  "receivedMTD": 480000,
  "totalSales": 6200000,
  "totalReceived": 5100000,
  "avgOrderValue": 28971,
  "trends": {
    "salesMTD": 7.4,
    "totalOrders": 4.2,
    "amountDue": null,
    "receivedMTD": 6.1
  }
}
```

STATUS CODES

Code	Meaning
200	

GET **/api/stats/transactions**

Transactions summary

EXAMPLE RESPONSE

```
{
  "totalTransactions": 312,
  "inbound": 180,
  "outbound": 132,
  "pending": 22,
  "delivered": 250,
  "trends": {
    "totalTransactions": 4.4,
    "inbound": null,
    "outbound": null,
    "pending": null
  }
}
```

STATUS CODES

Code	Meaning
200	

GET **/api/stats/users**

Employees summary

EXAMPLE RESPONSE

```
{
  "totalUsers": 12,
  "activeUsers": 11,
  "inactiveUsers": 1,
  "adminCount": 2,
  "roleBreakdown": [
    {
      "role": "Salesman",
      "count": 5
    }
  ],
  "trends": {
    "totalUsers": 8.3,
    "activeUsers": null,
    "inactiveUsers": null,
    "adminCount": null
  }
}
```

STATUS CODES

Code	Meaning
200	

GET **/api/stats/categories**

Categories summary

EXAMPLE RESPONSE

```
{
  "totalCategories": 9,
  "totalSubCategories": 27,
  "largest": {
    "name": "Ceramic Fiber Products",
    "productCount": 142
  },
  "trends": {
    "totalCategories": null,
    "totalSubCategories": null
  }
}
```

STATUS CODES

Code	Meaning
200	

GET **/api/stats/reports**

Reports page snapshot

Optionally scoped to a date range. netMovement is sales total minus purchase total for the range — a cash-movement figure, not accounting profit (no COGS/expenses modelled).

QUERY PARAMETERS

Field	Type	Required	Description
from	date (ISO)	No	Range start (inclusive).
to	date (ISO)	No	Range end (inclusive).

EXAMPLE RESPONSE

```
{
  "range": {
    "from": null,
    "to": null
  },
  "sales": {
    "orders": 214,
    "total": 6200000,
    "receivable": 812400,
    "averageOrderValue": 28971
  },
  "purchase": {
    "orders": 88,
    "total": 4100000,
    "payable": 132000
  },
  "netMovement": 2100000,
  "stock": {
    "products": 512,
    "totalValue": 4820000,
    "lowStock": 14,
    "outOfStock": 3
  },
  "clients": {
    "total": 1037
  },
  "topProducts": [
    {
      "product": "Ceramic Fiber Blanket 128 kg/m³",
      "qty": 3200
    }
  ],
  "topClients": [
    {
      "client": "Vishal Aluminium Pvt. Ltd.",
      "orders": 18,
      "total": 412000
    }
  ]
}
```

STATUS CODES

Code	Meaning
200	

14. Settings

Per-user profile and preferences — always scoped by `userId`, since there is no session token to infer it from.

GET `/api/settings`

Get a user's settings

QUERY PARAMETERS

Field	Type	Required	Description
<code>userId</code>	integer	Yes	

EXAMPLE RESPONSE

```
{
  "id": 1,
  "code": "USR-0001",
  "name": "Chinmay Modi",
  "email": "admin@shc.com",
  "role": "Admin",
  "phone": "",
  "department": "",
  "notifyLowStock": true,
  "notifyDelivery": true,
  "notifyPayment": false,
  "notifyWeekly": true,
  "twoFactor": false,
  "rowsPerPage": 10,
  "dateFormat": "MMM D, YYYY (Jul 18, 2026)"
}
```

STATUS CODES

Code	Meaning
200	
400	<code>userId</code> missing/invalid.
404	User not found.

PUT `/api/settings`

Update settings

Every field is optional — only the keys present in the body are changed.

QUERY PARAMETERS

Field	Type	Required	Description
<code>userId</code>	integer	Yes	Also accepted in the body.

REQUEST BODY (application/json)

Field	Type	Required	Description
name	string	No	
email	string	No	Must look like a real email.
phone	string	No	
notifyLowStock	boolean	No	
notifyDelivery	boolean	No	
notifyPayment	boolean	No	
notifyWeekly	boolean	No	
twoFactor	boolean	No	
rowsPerPage	integer	No	One of 5, 10, 20, 50, 100.
dateFormat	string	No	

STATUS CODES

Code	Meaning
200	Updated.
400	name empty / email invalid / rowsPerPage not in the allowed set.
404	User not found.
409	Email already in use.

POST /api/settings/password

Change password

Verifies currentPassword against the stored hash before allowing the change — otherwise anyone with the settings page open could reset it.

REQUEST BODY (application/json)

Field	Type	Required	Description
userId	integer	Yes	
currentPassword	string	Yes	
newPassword	string	Yes	At least 6 characters.

EXAMPLE RESPONSE

```
{
  "ok": true
}
```

STATUS CODES

Code	Meaning
200	Password changed.
400	Missing fields or newPassword too short.
401	currentPassword did not match.
404	User not found.

Every write accepts an optional `modifiedBy`` (or `createdBy``) field — the signed-in user's display name, sent by the app for the audit trail shown as "Modified By" in the UI. Falls back to "Admin" when omitted.