Design and perform CRUD operations on a for an online bookstore system.

```
SHOW DATABASES;

CREATE DATABASE bookshops;
use bookshops;

create table booklists(
book_id int primary key,
title varchar(50),
author varchar(50),
price int
);


INSERT INTO booklists(book_id,title,author,price)
VALUES
(1,'the life','henry',550),
(2,'7 habits','AB DE',700),
(3,'good life','mark',302),
(4,'way of galaxy','ranav',700),
```

```
(5,'the wale','markey',600);

SELECT title, price FROM booklists;

SELECT * FROM booklists
 WHERE price > 500;

UPDATE booklists SET author = 'KL Rahul'
WHERE book_id = 2;
UPDATE booklists SET price = 600
WHERE book_id = 3;
DELETE FROM booklists
 WHERE book_id = 4;

SELECT * FROM booklists;
```

Display all books

```sql
SHOW DATABASES;

CREATE DATABASE bookshops;
use bookshops;

create table booklists(
book_id int primary key,
title varchar(50),
author varchar(50),
price int
);

INSERT INTO booklists(book_id,title,author,price)
VALUES
(1,'the life','henry',550),
(2,'7 habits','AB DE',700),
(3,'good life','mark',302),
(4,'way of galaxy','ranav',700),
(5,'the wale','markey',600);

SELECT * FROM booklists
```

esult Grid | Filter Rows: | Edit: | Export

book_id	title	author	price
1	the life	henry	550
2	7 habits	AB DE	700
3	good life	mark	302
4	way of galaxy	ranav	700
5	the wale	markey	600
NULL	NULL	NULL	NULL

Display only book titles and prices

```sql
SHOW DATABASES;

CREATE DATABASE bookshops;
use bookshops;

create table booklists(
book_id int primary key,
title varchar(50),
author varchar(50),
price int
);

INSERT INTO booklists(book_id,title,author,price)
VALUES
(1,'the life','henry',550),
(2,'7 habits','AB DE',700),
(3,'good life','mark',302),
(4,'way of galaxy','ranav',700),
(5,'the wale','markey',600);

SELECT * FROM booklists;
SELECT title, price FROM booklists;
```

Result Grid | Filter Rows: | Export: | Wrap Cell Content:

title	price
the life	550
7 habits	700
good life	302
way of galaxy	700
the wale	600

Find books with price greater than a certain value (e.g., 500).

```sql
book_id int primary key,
title varchar(50),
author varchar(50),
price int
);


INSERT INTO booklists(book_id,title,author,price)
VALUES
(1,'the life','henry',550),
(2,'7 habits','AB DE',700),
(3,'good life','mark',302),
(4,'way of galaxy','ranav',700),
(5,'the wale','markey',600);

SELECT * FROM booklists;
SELECT title, price FROM booklists;

SELECT * FROM booklists
 WHERE price > 500;
```

Result Grid | Filter Rows: | Edit: | Export/Import:

book_id	title	author	price
1	the life	henry	550
2	7 habits	AB DE	700
4	way of galaxy	ranav	700
5	the wale	markey	600
NULL	NULL	NULL	NULL

- **Change the author name of a book**
- **Change the price of a specific book.**

```sql
INSERT INTO booklists(book_id,title,author,price)
VALUES
(1,'the life','henry',550),
(2,'7 habits','AB DE',700),
(3,'good life','mark',302),
(4,'way of galaxy','ranav',700),
(5,'the wale','markey',600);

SELECT title, price FROM booklists;

SELECT * FROM booklists
 WHERE price > 500;

UPDATE booklists SET author = 'KL Rahul'
WHERE book_id = 2;
UPDATE booklists SET price = 600
WHERE book_id = 3;

SELECT * FROM booklists;
```

Result Grid | Filter Rows: | Edit: | Export/Import: | Wra

book_id	title	author	price
1	the life	henry	550
2	7 habits	KL Rahul	700
3	good life	mark	600
4	way of galaxy	ranav	700
5	the wale	markey	600
NULL	NULL	NULL	NULL

Delete a book using book_id.

```
INSERT INTO booklists(book_id,title,author,price)
VALUES
(1,'the life','henry',550),
(2,'7 habits','AB DE',700),
(3,'good life','mark',302),
(4,'way of galaxy','ranav',700),
(5,'the wale','markey',600);

SELECT title, price FROM booklists;

SELECT * FROM booklists
 WHERE price > 500;

UPDATE booklists SET author = 'KL Rahul'
WHERE book_id = 2;
UPDATE booklists SET price = 600
WHERE book_id = 3;
DELETE FROM booklists
 WHERE book_id = 4;

SELECT * FROM booklists;
```

Result Grid | Filter Rows: | Edit: | Export/Impor

book_id	title	author	price
1	the life	henry	550
2	7 habits	KL Rahul	700
3	good life	mark	600
5	the wale	markey	600
NULL	NULL	NULL	NULL