

DRIVER DROWSINESS DETECTION SYSTEM

A Project Report

Submitted By

CH.Abhilash

210303124331

CH.Varshan Kumar

210303124339

CH.Shyam Kumar

210303124330

CH.V.V.S.Gowri Shankar

210303124320

CH.Chandra Aravind

210303124321

in Partial Fulfilment For the Award of

the Degree of

BACHELOR OF TECHNOLOGY

COMPUTER SCIENCE & ENGINEERING

Under the Guidance of

Prof. Dr.Sunitha Yadwad

Assistant Professor



VADODARA

April - 2024



PARUL UNIVERSITY

CERTIFICATE

This is to Certify that Project - 1 (203105499) of 6th Semester entitled “DRIVER DROWSINESS DETECTION SYSTEM” of Group No. PUCSE_206 has been successfully completed by

- CH.Abhilash- 210303124331
- CH.Varshan Kumar - 210303124339
- CH.Shyam Kumar - 210303124330
- CH.V.V.S.Gowri Shankar - 210303124320
- CH.Chandra Aravind - 210303124321

under my guidance in partial fulfillment of the Bachelor of Technology (B.Tech) in Computer Science & Engineering of Parul University in Academic Year 2023- 2024.

Date of Submission : _____

Prof. Dr.Sunitha Yadwad,

Project Guide

Project Coordinator:-Kruti Sutaria / Yatin Shukla

Dr. Amit Barve,

Head of Department,

CSE, PIET,

Parul University.

Acknowledgements

“The single greatest cause of happiness is gratitude.”

-Auliq-Ice

I would like to express my sincere gratitude to all those who have contributed to the successful completion of my project and the subsequent preparation of this report. First and foremost, I am thankful to **.Dr.Sunitha Yadwad** for providing me with the opportunity to undertake my project with them. It is my privilege to express my sincerest regards to my project guide **.Dr. Sunitha Yadwad** , for her valuable inputs, able guidance, encouragement, whole-hearted cooperation, and constructive criticism throughout the duration of our project. I deeply express my sincere thanks to **Dr. Amit Barve** HOD– CSE department and **Dr. Vipul Vekariya** , Dean and Principal, PIET for encouraging and allowing me to do project for the partial fulfillment of the requirements leading to the award of B-Tech degree.

CH.Abhilash-2210303124331

CH,Varshan Kumar-210303124339

CH.Shyam Kumar-210303124330

CH.V.V.S.Gowri Shankar-210303124320

CH.Chandra Aravind -210303124321

CSE, PIET

Parul University,

Vadodara

Abstract

Nowadays, accidents occur during drowsy road trips and increase day by day. Continuous advancements in computing technology and artificial intelligence in the past decade have led to improvements in driver monitoring systems. Numerous experimental studies have collected real driver drowsiness data and applied various artificial intelligence algorithms and feature combinations with the goal of significantly enhancing the performance of these systems in real-time. This paper presents an up-to-date review of the driver drowsiness detection systems implemented over the last decade. The paper illustrates and reviews recent systems using different measures to track and detect drowsiness. Each system falls under one of four possible categories, based on the information used. Each system presented in this paper is associated with a detailed description of the features, classification algorithms, and used datasets. In addition, an evaluation of these systems is presented, in terms of the final classification accuracy, sensitivity, and precision. Furthermore, the paper highlights the recent challenges in the area of driver drowsiness detection, discusses the practicality and reliability of each of the four system types, and presents some of the future trends in the field.

drowsiness and several methods have been used to detect drowsiness or inattentive driving. Our goal is to provide an interface where the program can automatically detect the driver's drowsiness and detect it in the event of an accident by using the image of a person captured by the webcam and examining how this information can be used to improve driving safety can be used. . a vehicle safety project that helps prevent accidents caused by the driver's sleep. Basically, you're collecting a human image from the webcam and exploring how that information could be used to improve driving safety. Collect images from the live webcam stream and apply machine learning algorithm to the image and recognize the drowsy driver or not. When the driver is sleepy, it plays the buzzer alarm and increases the buzzer sound. If the driver doesn't wake up, they'll send a text message and email to their family members about their situation. Hence, this utility goes beyond the problem of detecting drowsiness while driving.

Eye Exploration of facial expressions has been an interesting area of research for various Applications. Drowsiness identification is one wch application that can be explored from metal expression. The paper proposes a stem that detects the drowsiness state of the driver by using a continuous face-tracking algorithm, without equipping the driver with y external bodily gadgets. The system Independently tracks the eye and mouth regions using facial landmarks. The meters extracted from the eye region are aspect ratio and blinking rate while punctuation of mouth opening indicates awning as a sign of fatigue of the driver. The experimentation involves investigating 30 participants (drivers) to evaluate the system's Performance. The experimentation revealed that the system accurately determined the driver fatigue state, and the system was found in be independent of variations in the age , gender, and eye capture

status (with or without wearing eyeglasses). The thresholds set for eye aspect ratio and yawning have provided the best accuracy in detecting the drowsiness state for any unknown test driver with minimum response time. The proposed model is fast and reliable and the alert system helps to restore the driver's attention avoiding consequences due to fatigue of the driver.

Table of Contents

Acknowledgements	iii
Abstract	iv
List of Tables	ix
List of Figures	x
1 Introduction	1
1.1 Introduction to project	1
1.2 scope of the project	2
1.3 Aim of the project	2
1.4 Purpose	2
2 Literature Survey	4
2.1 Driver drowsiness detection using behavioral measures and machine learning techniques: A review of state-of-art techniques	4
2.2 A systematic review on detection and prediction of driver drowsiness	4
2.3 Driver Fatigue Detection Based on Convolutional Neural Networks Using EM-CNN	5
2.4 A Comparative Study of Driver Drowsiness Detection Techniques	5

2.5	Driver Drowsiness Detection Model Using Convolutional Neural Networks	
	Techniques for Android Application	6
2.6	REAL-TIME DYNAMIC DROWSINESS DETECTION USING CONVOLUTIONAL NEURAL NETWORKS	6
2.7	Driver Drowsiness Detection System and Techniques	7
3	Analysis / Software Requirements Specification (SRS)	8
3.1	Introduction	8
3.2	Functional Requirements	8
3.2.1	Sensor Integration:	8
3.2.2	Data Processing	8
3.2.3	Drowsiness Detection:	9
3.2.4	Alert Mechanism:	9
3.2.5	Alert Customization	9
3.2.6	User Interface	9
3.3	Non Functional Requirements	9
4	System Design	11
4.1	Study of Current System	11
4.2	Problem and Weaknesses of Current System	11
4.3	Requirements of New System	12
4.4	System Feasibility	13
4.5	List Main Modules	14
5	Methodology	15
5.1	System Design and Methodology	15
5.2	Methodology	16
5.3	Structure Design	16

5.4	Interface Design	18
5.5	METHOD	18
5.6	Eye Detection and Analysis	18
5.7	Detection of Mouth Opening and Analysis	20
6	Implementation	23
6.1	Implementation Platform	23
6.2	Modules Specifications	23
6.3	Decision Module	24
6.4	Result Analysis	25
7	Testing	26
7.1	Testing Plan	26
7.2	Test Results and Analysis	28
8	Conclusion	29
8.1	Summary of Project Work	29
8.2	Future Enhancement	30

List of Tables

5.1	EAR avg	19
5.2	Lip descriptor	21
5.3	Computation of mouth opening	22

List of Figures

5.1	system design	15
5.2	Structure design	17
5.3	Interface design	18
5.4	Facial Landmarks	19
5.5	Lip Landmarks	21

Chapter 1

Introduction

1.1 Introduction to project

One of the major contributing factors to road accidents is the driver drowsiness state. Drowsiness is the driver's drowsiness body demands a strong desire for rest, often leading to uncontrolled eye closure and losing the presence of the mind. Commencing into such a drowsiness state is dangerous especially during driving activity, causing the driver to misjudge and maintain a safe vehicle distance. Also, the driver may miss the traffic signs or may fail to keep in the required lane.

It is therefore essential to develop methods that would identify and alert the driver about the drowsiness state, the moment it is detected, avoiding any further consequences on the road. Extracting the key features from the facial regions is the essence of identifying the drowsiness state of the driver. The significant parameters from the facial region are the yawning, eye blinking rate, and duration of eye closure [1]. A drowsiness detection system was developed for embedded systems such as Android mobile [2]. With the use of multi layer perceptron classifiers that were trained for the identified facial landmark, the system achieved an accuracy of 80 percent Drowsiness detection based on the blink pattern taking into consideration the eye closure period was explored using an image processing technique [3-4]. An adaptive fuzzy expert system for estimating driver fatigue and distraction was tested with parameters of head rotation and eye closure [5]. But the system was found to be less accurate and computationally less competent in tracking the face. In another implementation, CNN-based face recognition was implemented by combining eye and mouth characteristics to determine the drivers' fatigue status [6]. Using the driver's images this system achieved an accuracy of 93.62 percent in detecting fatigue drivers.

1.2 scope of the project

A driver drowsiness detection system is a safety feature designed to detect and alert drivers when their level of alertness drops, indicating the onset of drowsiness. The scope of this project typically includes several key components:

1.Data Collection: This involves collecting various data points, such as eye closure, blink rate, yawning frequency, and head movements, to analyze and detect the onset of drowsiness. 2.Signal Processing: This stage involves processing and cleaning the collected data to ensure accurate and reliable detection.

3.Feature Extraction: This involves extracting relevant features from the processed data to feed into a machine learning model.

4.Algorithm Development: This involves developing and implementing a machine learning model to detect driver drowsiness, based on the extracted features.

5.Integration: This involves integrating the drowsiness detection system with existing in-vehicle systems, such as the dashboard or infotainment system, to provide real-time alerts.

6.User Interface: This stage involves creating a user-friendly interface to provide feedback to the driver, such as visual or auditory alerts.

7.Testing and Validation: This involves testing the drowsiness detection system under various driving conditions to ensure its accuracy and reliability.

1.3 Aim of the project

The Aim of a driver drowsiness detection system is to reduce the risk of accidents and improve overall road safety.The primary goal of a driver drowsiness detection system is to improve road safety by detecting driver drowsiness and alerting drivers to take appropriate action, reducing the risk of accidents and promoting safer driving habits.

1.4 Purpose

The purpose of a Fatigue Monitoring System Project is to enhance road safety by employing technology to identify and mitigate the risks associated with monitoring fatigue. Key objectives include: Accident Prevention: Detecting signs of drowsiness helps prevent accidents caused by impaired monitoring alertness, reducing the likelihood of collisions due to delayed reactions or poor decisionmaking. Monitoring Well-being: Prioritizing the well-being of monitorings by alerting them when signs of fatigue are detected, encouraging breaks, rest, or other corrective actions to mitigate

potential risks. Enhanced Road Safety: Contributing to overall road safety by minimizing the impact of fatigue driving, which can be a significant factor in accidents and fatalities. Integration with Vehicle Systems: Integrating fatigue monitoring system with other vehicle safety systems creates a comprehensive safety network, potentially reducing the severity of accidents and improving overall driving experience. Adaptive Technology: Incorporating adaptive features ensures the system's effectiveness across various driving conditions and individual monitoring behaviors, making it more versatile and applicable. Public Awareness: By developing and implementing such projects, there is an opportunity to raise public awareness about the dangers of fatigue driving and promote responsible driving habits. Ultimately, the purpose of these projects is to leverage technology in addressing a critical safety concern, aiming to make driving safer for both the individual and others on the road

Chapter 2

Literature Survey

2.1 Driver drowsiness detection using behavioral measures and machine learning techniques: A review of state-of-art techniques

Abstract: This paper presents a literature review of driver drowsiness detection based on behavioral measures using machine learning techniques. Faces contain information that can be used to interpret levels of drowsiness. There are many facial features that can be extracted from the face to infer the level of drowsiness. These include eye blinks, head movements and yawning. However, the development of a drowsiness detection system that yields reliable and accurate results is a challenging task as it requires accurate and robust algorithms. A wide range of techniques has been examined to detect driver drowsiness in the past. The recent rise of deep learning requires that these algorithms be revisited to evaluate their accuracy in detection of drowsiness. As a result, this paper reviews machine learning techniques which include support vector machines, convolutional neural networks and hidden Markov models in the context of drowsiness detection. Furthermore, a meta-analysis is conducted on 25 papers that use machine learning techniques for drowsiness detection. The analysis reveals that support vector machine technique is the most commonly used technique to detect drowsiness, but convolutional neural networks performed better than the other two techniques. Finally, this paper lists publicly available datasets that can be used as benchmarks for drowsiness detection.

2.2 A systematic review on detection and prediction of driver drowsiness

Abstract: Driver drowsiness has emerged as one of the key factors in recent times' traffic accidents, which can result in fatalities, serious physical losses, large monetary losses, and significant property damage. Drowsiness in a driver can be brought on by long hours behind the wheel, drowsiness,

fatigue, medicine, difficulty sleeping, and medical illnesses. A dependable technology that can identify driver drowsiness and warn the driver before an accident occurs is needed, according to statistics from several research. Many studies have been conducted in the previous to develop a reliable driver drowsiness detection and prediction system that uses a variety of parameters to gauge the driver's level of drowsiness. In this study, we analyzed the numerous measurements made by researchers, which were classified as physiological, vehicle-based, subjective, and behavioral measures. This article presenting a study of the fundamental problems with various sleepiness detection systems and how they are used to detect fatigue while driving. In order to warn a driver before a collision, this analysis will concentrate on what happens while driving and the advancement of technological methods that are intended to detect and, ideally, forecast driver drowsiness. For upcoming researchers to do baseline assessment in the particular field, this thorough review will provide a better understanding.

2.3 Driver Fatigue Detection Based on Convolutional Neural Networks Using EM-CNN

Abstract: With a focus on fatigue driving detection research, a fully automated driver fatigue status detection algorithm using driving images is proposed. In the proposed algorithm, the multitask cascaded convolutional network (MTCNN) architecture is employed in face detection and feature point location, and the region of interest (ROI) is extracted using feature points. A convolutional neural network, named EM-CNN, is proposed to detect the states of the eyes and mouth from the ROI images. The percentage of eyelid closure over the pupil over time (PERCLOS) and mouth opening degree (POM) are two parameters used for fatigue detection. Experimental results demonstrate that the proposed EM-CNN can efficiently detect driver fatigue status using driving images. The proposed algorithm EM-CNN outperforms other CNN-based methods, i.e., AlexNet, VGG-16, GoogLeNet, and ResNet50, showing accuracy and sensitivity rates of 93.623 percent.

2.4 A Comparative Study of Driver Drowsiness Detection Techniques

abstract The number of motor vehicles has increased steadily in emerging countries during the last ten years. Traffic accident reports indicate that risky driving behaviours, such as drunken driving or fatigued driving, are responsible for most accidents. According to studies, sleepy driving is a contributing factor in 20 percent of all accidents. Drowsiness is a condition when the level of consciousness is lowered as a result of fatigue or sleep deprivation, and it can make a driver fall asleep silently. Drowsy driving results in a loss of control by the driver, which can cause the vehicle

to drift off the road, hit an obstacle, or overturn. In order to extract and synthesise the methods and features that have been utilized in drowsiness detection process, this study has conducted a Systematic Literature Review (SLR) for this work and found 100 relevant studies using the defined search parameters, of which 30 studies are chosen for additional research. This study has thoroughly examined these works, evaluated the methods and features applied, and identified the research gap as well. According to the comparative analysis, the most used features are facial expressions like yawning, closing of the eyes, and head motions. These insights are based on an analysis of 30 papers and show that the Eye Aspect Ratio, Haar Cascade, Support Vector Machine (SVM), and dlib library are frequently utilised techniques

2.5 Driver Drowsiness Detection Model Using Convolutional Neural Networks Techniques for Android Application

Abstract A sleepy driver is arguably much more dangerous on the road than the one who is speeding as he is a victim of microsleeps. Automotive researchers and manufacturers are trying to curb this problem with several technological solutions that will avert such a crisis. This article focuses on the detection of such micro sleep and drowsiness using neural network based methodologies. Our previous work in this field involved using machine learning with multi-layer perceptron to detect the same. In this paper, accuracy was increased by utilizing facial landmarks which are detected by the camera and that is passed to a Convolutional Neural Network (CNN) to classify drowsiness. The achievement with this work is the capability to provide a lightweight alternative to heavier classification models with more than 88 percent for the category without glasses, more than 85 percent for the category night without glasses. On average, more than 83 percent of accuracy was achieved in all categories. Moreover, as for model size, complexity and storage, there is a marked reduction in the new proposed model in comparison to the benchmark model where the maximum size is 75 KB. The proposed CNN based model can be used to build a real-time driver drowsiness detection system for embedded systems and Android devices with high accuracy and ease of use.

2.6 REAL-TIME DYNAMIC DROWSINESS DETECTION USING CONVOLUTIONAL NEURAL NETWORKS

abstract Driver fatigue and reckless driving are major contributors to road accidents, resulting in the loss of precious lives and compromising road traffic safety. Effective and precise solutions to detect driver drowsiness are crucial in preventing accidents and enhancing road safety. Numerous

driver drowsiness detection systems have been developed using diverse technologies, each focused on detecting specific parameters related to the driver's tiredness. This research proposes a novel multi-level distribution model for detecting driver drowsiness, employing Convolutional Neural Networks (CNN) technology. The model utilizes a 2D Convolutional Neural Network to analyze the driver's facial patterns, capturing their behavior and emotions accurately. OpenCV is employed to build the suggested model, and the experimental results demonstrate its superior efficiency in recognizing the driver's emotions and level of tiredness compared to existing technologies.

2.7 Driver Drowsiness Detection System and Techniques

abstract Drivers who do not take regular breaks when driving long distances run a high risk of becoming drowsy a state which they often fail to recognize early enough according to the experts. Studies show that around one quarter of all serious motorway accidents are attributable to sleepy drivers in need of a rest, meaning that drowsiness causes more road accidents than drink-driving. Attention assist can warn of inattentiveness and drowsiness in an extended speed range and notify drivers of their current state of fatigue and the driving time since the last break, offers adjustable sensitivity and, if a warning is emitted, indicates nearby service areas in the COMAND navigation system.

Chapter 3

Analysis / Software Requirements Specification (SRS)

3.1 Introduction

The purpose of this document is to provide a comprehensive Software Requirements Specification (SRS) for the development of a Driver Drowsiness Detection System. This system aims to enhance road safety by detecting signs of driver drowsiness and alerting the driver to take necessary precautions

3.2 Functional Requirements

3.2.1 Sensor Integration:

The system shall integrate various sensors including but not limited to:

Camera for facial recognition and eye tracking. sensors for monitoring head position and movements. rate monitor for physiological data.

The system shall acquire data from these sensors in real-time.

3.2.2 Data Processing

The system shall process the sensor data to extract relevant features related to drowsiness detection. Facial recognition algorithms shall be implemented to detect signs of fatigue, such as drooping eyelids or yawning. Eye tracking algorithms shall be utilized to monitor eye movements and blink patterns. Head position and movements shall be analyzed to identify signs of inattentiveness. Physiological data such as heart rate variability shall be monitored to assess the driver's alertness level.

3.2.3 Drowsiness Detection:

The system shall employ machine learning algorithms to analyze the processed data and detect signs of drowsiness. Thresholds for various parameters (e.g., blink frequency, head movement) shall be predefined based on empirical data and adjusted during system calibration. The system shall continuously monitor the driver's behavior and update the drowsiness detection model in real-time.

3.2.4 Alert Mechanism:

Upon detecting signs of drowsiness, the system shall issue timely alerts to the driver. Alerts shall be delivered through multiple modalities such as: Visual alerts on the dashboard display. Auditory alerts through speakers. Haptic feedback via the steering wheel or seat vibrations.

3.2.5 Alert Customization

The system shall allow customization of alert preferences based on user preferences. Users shall have the option to adjust alert sensitivity and choose specific alert modalities.

3.2.6 User Interface

The system shall have a user-friendly interface accessible to the driver. The interface shall display real-time drowsiness alerts and relevant information about the detected signs. It shall provide options for configuring system settings and alert preferences.

3.3 Non Functional Requirements

1.Performance:

The system shall be capable of processing sensor data and issuing alerts in real-time with minimal latency. The drowsiness detection accuracy shall meet or exceed predefined performance metrics, with a high degree of reliability.

2. Reliability:

The system shall be robust and resilient to environmental factors such as varying lighting conditions and driver demographics. It shall undergo rigorous testing to ensure reliable operation under diverse driving scenarios.

3. Security:

The system shall implement appropriate security measures to protect sensitive data collected from sensors, such as facial images and physiological data. Data transmission between system components shall be encrypted to prevent unauthorized access.

4. Compatibility:

The system shall be compatible with a wide range of vehicle models and configurations. It shall be designed to integrate seamlessly with existing onboard electronics and communication systems.

5. Usability:

The user interface shall be intuitive and easy to navigate, requiring minimal training for drivers to use effectively. Alerts shall be designed to be informative yet non-intrusive, ensuring they do not distract the driver unnecessarily.

Chapter 4

System Design

4.1 Study of Current System

The study of the current system for fatigue monitoring system reveals a landscape characterized by an increasing emphasis on leveraging advanced technologies to enhance road safety. Existing systems commonly employ a combination of in-vehicle sensors, such as cameras and steering sensors, to monitor monitoring behavior and identify signs of drowsiness. Many systems utilize computer vision techniques and machine learning algorithms for real-time data processing, allowing for the analysis of facial expressions, eye movements, and steering patterns as indicators of monitoring alertness. Alert mechanisms, ranging from auditory alarms to visual warnings, serve to promptly notify monitorings when signs of drowsiness are detected. Some systems also integrate with other vehicle safety features to create a more comprehensive safety network. The current state of fatigue monitoring system systems reflects a commitment to addressing the dangers associated with monitoring fatigue through technological innovation. However, ongoing research and development efforts are essential to further improve accuracy, adaptability to diverse driving conditions, and integration into different vehicle models. The study of the current system lays the foundation for the continuous evolution of these technologies to make driving safer and prevent accidents caused by fatigue driving.

4.2 Problem and Weaknesses of Current System

The current systems for fatigue monitoring system, while advancing road safety, are not without their challenges and weaknesses. One notable problem lies in the accuracy and reliability of system mechanisms. The reliance on sensors, such as cameras and steering sensors, may face limitations in capturing subtle signs of drowsiness or may be prone to false positives, leading to unnecessary alerts.

Additionally, the diversity of driving conditions, such as variations in lighting and road types, poses a challenge to the universality of these systems. Moreover, the integration of fatigue monitoring system with other vehicle safety features is not standardized across all vehicle models, limiting the overall effectiveness of these systems. The potential for user discomfort or distraction from frequent alerts, especially if the system lacks adaptability to individual driving styles, is another weakness. Furthermore, issues related to privacy and data security arise due to the collection of sensitive information about monitoring behavior. Addressing these problems and weaknesses is crucial for the continuous improvement of fatigue monitoring system systems, necessitating ongoing research, technological refinement, and standardization efforts within the automotive industry.

4.3 Requirements of New System

Accuracy: The system must accurately detect drowsiness to minimize false positives and false negatives. High accuracy ensures that drivers receive timely alerts when they are actually drowsy, while avoiding unnecessary interruptions during alert states.

Real-time Monitoring: The system should continuously monitor the driver's state in real-time to provide timely alerts. Real-time monitoring enables quick responses to drowsiness, reducing the risk of accidents.

Robustness: The system should be robust to variations in lighting conditions, driver appearance (e.g., wearing glasses or hats), and driving environment (e.g., different road conditions, weather conditions). Robustness ensures reliable performance in diverse situations.

Non-intrusiveness: The system should monitor the driver's state without causing discomfort or distraction. Non-intrusiveness is essential to ensure driver acceptance and minimize interference with driving tasks.

Compatibility: The system should be compatible with different vehicle types, including cars, trucks, and buses. Compatibility allows for broad deployment across various vehicle fleets.

User Interface: The system should have a user-friendly interface that provides clear alerts to the driver when drowsiness is detected. The interface should be intuitive, easy to understand, and not overly distracting.

Adaptability: The system should adapt to individual differences in drowsiness patterns and driving styles. Adaptability ensures that the system can effectively detect drowsiness in drivers with varying characteristics and behaviors.

Privacy Protection: The system should respect the driver's privacy by securely handling sensor data and avoiding unnecessary data collection. Privacy protection is essential for maintaining trust

and compliance with data protection regulations.

Scalability: The system should be scalable to accommodate large-scale deployment, especially in fleet management applications. Scalability ensures that the system can handle a growing number of vehicles and users without compromising performance.

Reliability: The system should be reliable under different operating conditions, including long periods of continuous use and exposure to environmental factors. Reliability minimizes the risk of system failures and ensures consistent performance over time.

Cost-effectiveness: The system should be cost-effective to develop, deploy, and maintain, making it accessible to a wide range of users and organizations. Cost-effectiveness is crucial for maximizing the system's impact and sustainability

4.4 System Feasibility

The system feasibility of a fatigue monitoring system project involves assessing the practicality and viability of implementing such a system within the given technological, economic, and operational constraints. From a technological standpoint, the project's feasibility hinges on the availability of advanced sensors, data processing capabilities, and reliable algorithms to accurately detect signs of monitoring fatigue. The integration of these technologies must also consider compatibility with existing vehicle systems and the potential for widespread adoption across different vehicle models. Economically, the feasibility is contingent on the cost-effectiveness of implementing fatigue monitoring system systems. This includes the expenses associated with developing, integrating, and manufacturing the technology. A cost-benefit analysis needs to be conducted to ensure that the investment in the project aligns with the potential reduction in accidents and associated costs. Operational feasibility addresses the practicality of deploying and maintaining the system within real-world scenarios. Considerations include ease of use for monitorings, minimal disruption to driving experience, and adaptability to various driving conditions. Additionally, the feasibility study should assess the system's reliability, robustness, and scalability in the face of different environments and user behaviors. Overall, a comprehensive system feasibility analysis is essential for evaluating the viability of a fatigue monitoring system project, taking into account technological advancements, economic considerations, and practical operational aspects to ensure successful development, implementation, and sustained effectiveness.

4.5 List Main Modules

A Drowsiness detection system project typically involves several key modules, each contributing to the overall functionality of the system. Here is a list of the main modules commonly found in such projects.

Data Acquisition Module: Involves the collection of data from in-vehicle sensors, such as cameras, steering sensors, and other relevant sensors, to monitor monitoring behavior.

Preprocessing Module: Cleans and preprocesses raw data to enhance its quality and prepare it for further analysis.

Feature Extraction Module: Identifies and extracts relevant features from the preprocessed data, such as eye movement patterns, facial expressions, and steering behaviors.

Machine Learning/Pattern Recognition Module: Utilizes machine learning algorithms or pattern recognition techniques to analyze the extracted features and detect signs of drowsiness.

Decision Making Module: Determines whether the monitoring is fatigue based on the results from the machine learning module. **Alert Generation Module:** Generates alerts or warnings if the system determines that the monitoring is exhibiting signs of drowsiness. This may include auditory alarms, visual warnings, or haptic feedback.

User Interface Module: Provides a user interface for real-time feedback to the monitoring, displaying information about their alertness level and encouraging breaks if needed.

Adaptive Features Module: Incorporates adaptive features to tailor the system's response to individual driving styles and various environmental conditions.

Testing and Validation Module: Involves testing the system's accuracy and reliability in controlled environments and real-world scenarios to ensure its effectiveness.

Privacy and Security Module: Addresses concerns related to privacy and data security, implementing measures to protect sensitive monitoring information.

Logging and Reporting Module: Records and logs relevant data for analysis, reporting, and continuous improvement of the system.

Chapter 5

Methodology

5.1 System Design and Methodology

System Design:

Sensor Integration: Incorporate sensors such as cameras, infrared sensors, and steering angle sensors into the vehicle to monitor the driver's behavior.

Data Acquisition: Collect data from sensors in real-time, capturing driver-related features like eye movement, blink rate, head position, and steering behavior.

Feature Extraction: Extract relevant features from the collected data that indicate drowsiness, such as prolonged eye closure, erratic steering, or changes in head position.

Model Development: Build a machine learning or deep learning model trained on a dataset containing labeled instances of alert and drowsy driving states. This model learns to classify new instances of driver behavior as alert or drowsy based on the extracted features.

Alert System: Implement an alert mechanism that triggers when the model detects signs of drowsiness. Alerts can be visual, auditory, or haptic, designed to prompt the driver to take action.




Figure 5.1: system design

5.2 Methodology

:

Data Collection: Gather a diverse dataset of driver behavior, including both alert and drowsy states, captured under various driving conditions.

Data Preprocessing: Clean and preprocess the collected data to remove noise and inconsistencies, ensuring the quality of input data for the model.

Feature Engineering: Select and engineer relevant features from the preprocessed data that effectively represent drowsiness-related behavior.

Model Training: Train a machine learning or deep learning model using the labeled dataset, employing techniques such as logistic regression, support vector machines, or convolutional neural networks.

Model Evaluation: Evaluate the trained model's performance using metrics such as accuracy, precision, recall, and F1-score on a separate test dataset to assess its effectiveness in detecting drowsiness.

Real-time Implementation: Integrate the trained model into a real-time system that continuously monitors driver behavior and triggers alerts when drowsiness is detected.

Validation and Testing: Validate the system's performance through extensive testing under real-world driving conditions, ensuring its reliability and effectiveness in detecting drowsy driving.

5.3 Structure Design

The system architecture for the Driver Drowsiness Detection comprises several interconnected modules responsible for data acquisition, processing, drowsiness detection, and alert generation. Below is an overview of the system design:




Figure 5.1: This is the flow chart image.

Figure 5.2: Structure design




Figure 5.3: Interface design

5.4 Interface Design

The interface design for the drowsy driver detection system should be intuitive and user-friendly, providing clear alerts to the driver when drowsiness is detected. It should feature minimal distractions to ensure the driver's focus remains on the road. The interface could incorporate visual cues such as a prominent warning symbol or flashing light on the dashboard, accompanied by an audible alert such as a beep or voice notification. Additionally, haptic feedback mechanisms, such as vibrating the steering wheel or seat, could be employed to further alert the driver. The interface should be customizable to accommodate individual preferences and adjustable based on the severity of drowsiness detected. Overall, the goal of the interface design is to effectively communicate the risk of drowsy driving to the driver in a manner that is immediate, unmistakable, and conducive to prompt corrective action.

5.5 METHOD

The implementation of the proposed system is shown in Fig. 1. The real-time images are of the driver are captured for processing the facial expression. The images are pre-processed to enhance their quality, for reducing distortion, and analyzing the missing components in the image. Starting from a specific location in the image, the algorithm performs tracking of the face. This region is termed a Region of Interest [9]. To (ROI). After the detection of the region of interest, the ROI is further processed determine the eye and mouth regions. The algorithm then applies the bounding box for eye and mouth detection. The algorithm continuously monitors the eye and mouth regions of the driver. From the eye tracking, the total count of frames for which the eye closure is detected is counted. Similarly, the mouth opening (corresponding to the yawning act) is computed

5.6 Eye Detection and Analysis

The captured image from the web cam is first converted to gray scale and transferred to Dlib Library. To extract the facial landmark coordinates Dlib library is used [11]. The predictor function of the algorithm then maps the face to 68 landmarks. The proposed work has emphasized only the facial



Figure 5.4: Facial Landmarks

Eye Status	EARAVG
eye closure	0.17
eye opening	0.29

Table 5.1: EAR avg

regions of the eye and mouth. The eye region comprised landmarks from 36 to 47. The eye Aspect Ratio (EAR) is an important parameter that governs the eye-opening status. FAR is a scalar value. Using landmarks from 36 ,15 ,47, the Eye Aspect Ratio is computed. We implemented the equation proposed by Soukupová and Čzech [12] to compute EAR Considering the landmarks of the right eye (36 1641) EAR is calculated and considering the Landmarks of the left eye (42 to 47) EAR, is calculated using Eq. (1) and (2). The experimentation has revealed that the EAR Value remains invariant concerning distance and orientation of the face. The average EAR is the mean of the two EAR.

$$\text{EAR(R)} = (\text{P2-P6}) + (\text{P3-P5})/2(\text{P1-P4}) \dots\dots\dots\text{eq(1)}$$

$$\text{EAR(L)} = (\text{P2-P6}) + (\text{P3-P5})/2(\text{P1-P4}) \dots\dots\dots\text{eq(2)}$$

$$\text{EAR(avg)} = 1/2(\text{EAR(R)} + \text{EAR(L)})$$

1 . Table 5.1 shows the EAR(avg) values for conditions of eyer- opening . The EAR avg values in Table 1 reveal that the EAR attains a minimum value in the range of 0.27 to 0.32 indicating eye-opening obtained by considering a wide range participants.

The experimentation involves the inclusion of participants with variations in the age group (purpose to incorporate variations in the eve size), gender, and eye capture status (with or without eyeglasses) has resulted in acquiring large possibilities in the variations of the EAR. Studies of human eye anatomy have revealed that an adult human eye size differs among them by only one or

2 millimeters and is independent of sex and age group [13]. Therefore, with the observation of the EARAVG values from Table 1 and the experimental results, a threshold of 0.25 was set to identify the state of eye-opening or closing. If the EARAVG remains below the threshold consecutively over three frame durations, then this state was accepted as the drowsy state of the driver. This threshold has provided the best accuracy in detecting the eye closure status for any unknown test driver.

The performance of the system was further enhanced by taking into consideration two more parameters, the duration of eye closure and loss of eye blink i.e., reduction in blink rate. It is often observed that the severity of drowsiness affects the activities of the driver. One of the major impacts of being in a strong state of drowsiness is the slower reaction times and reduced vigilance of the driver, causing change in the facial characteristics. A typical blink has amplitude of -100 V and lasts for about 300-400ms. A relaxed person blinks about 15- 20 times per minute, although only 2-4 are needed from a physiological viewpoint. When performing cognitive tasks, the blink frequency drops to as little as 3 blinks per minute, whereas an increase in blink frequency indicates reduced vigilance. Therefore, to enhance the accuracy of detecting the drowsiness of the as in driver, if the eye closure status exceeded consecutively for 3 frames, it was confirmed and indicated as the fatigue state of the driver. Further, the system also incorporates monitoring of eye blink rate through the variations in the EAR (ie, minimum to maximum and vice. versa). If the system identifies, a reduction in the variations of eye blinking, it indicated a sign of fatigue. In either case, the alert signal was initiated by the system.

5.7 Detection of Mouth Opening and Analysis

In addition to the eye aspect ratio, the ver. This system also incorporates the other commonly observed symptom associated with drowsiness which is yawning. Yawning causes various physiological changes in the facial region like the extension of the neck and wide expansion of the jaw, with subsequent contraction of the tongue [2]. As yawning is an involuntary action, its research focuses on analyzing the mouth opening and its classification.

Using the facial landmarks as shown in Fig. 2, the algorithm detects the mouth region. Landmarks from 48 to 60 correspond to the mouth region and 61 to 67 landmarks correspond to the inner edges of the lips. For detecting the mouth opening using these landmarks, the mean distance between the lips is calculated using the orientation of the lip points. Table 2 and 3 reveal the process of computing the mean distance between lips using the landmarks labeled in Fig. 5.2

Lip Description	Points on the lip	Lip point Orientation
The upper edge of the upper lips	p1,p2,p3	p1(x1,y1)p2(x2,y2)p3 (x3,y3)
The lower edge of the upper lips	p5,p6,p7	p5(x5,y5)p6(x6,y6)p7 (x7,y7)
The upper edge of lower lips	q1,q2,q3	q1(x1,y1)q2 (x2,y2)q3 (x3,y3)
The lower edge of the lower lips	q4,q5,q6	q4(x4,y4)q5(x5,y5)q6(x6,y6)

Table 5.2: Lip descriptor




Figure 5.5: Lip Landmarks

As seen the mean values of the lips decide the mouth opening. For a true implementation mean components of lips are capturing more significantly than measuring the average of distance between the lips. With the observation of values of the average distance between lips from Table 5.3 for different lip statuses of the driver, a threshold of 30 was decided as the optimum value for detecting yawning. Moreover, during yawning, the mouth remains wide open usually for 3 to 5 seconds. Therefore, if the distance between lips remains below the set threshold over three seconds durations, then this state was accepted by the system as the drowsy state of the driver.

Lip Description	Mean Descriptors	Mean Components of Lips
Upper Lips(b0-y0)	The mean of the horizontal lip component (x0)	$x0 = x1+x2+x3+x4+x5+x6/6$
	Mean of vertical lip component y(0)	$y(0) = y1+y2+y3+y4+y5+y6/6$
Lower Lips(b0-y0)	The mean of horizontal lip component (a0)	$a0 = x7+x8+x9+x10+x11+x12/6$
	The mean of vertical lip component (b0)	$b0 = y7+y8+y9+y10+y11+y12/6$

Table 5.3: Computation of mouth opening

Chapter 6

Implementation

6.1 Implementation Platform

The implementation platform for the drowsy driver detection project could leverage a combination of hardware and software technologies. On the hardware side, it may involve utilizing embedded systems or microcontrollers for real-time data acquisition from sensors such as cameras, infrared sensors, and steering angle sensors installed in the vehicle. These sensors would capture relevant driver behavior data, which would then be processed by the onboard software. The software platform could be developed using programming languages like Python or C++, with frameworks such as TensorFlow or OpenCV for machine learning and computer vision tasks. Additionally, the implementation could utilize existing automotive platforms or development kits provided by manufacturers to ensure compatibility and integration with vehicle systems. By integrating both hardware and software components effectively, the drowsy driver detection system can be deployed seamlessly within vehicles, providing reliable and timely alerts to mitigate the risks associated with drowsy driving.

6.2 Modules Specifications

The drowsy driver detection project can be divided into several key modules, each with specific functionalities. Firstly, the data acquisition module collects real-time data from sensors like cameras, steering angle sensors, and infrared sensors installed in the vehicle. The data preprocessing module cleans and preprocesses the collected data to remove noise and inconsistencies. Following this, the feature extraction module extracts relevant features from the preprocessed data, such as eye closure duration, blink rate, and steering behavior. These features are then fed into the classification module, where machine learning or deep learning models classify the driver's state as alert or

drowsy. Finally, the alert generation module triggers visual, auditory, or haptic alerts to notify the driver when drowsiness is detected. Overall, these modules work together seamlessly to detect drowsy driving behavior and provide timely warnings to ensure road safety.

6.3 Decision Module

Using the eye aspect ratio, blink rate, and distance between lips, the decision module detects the drowsiness state of the driver. The threshold set for eye aspect ratio is 0.25 and for yawning is 30. The computations of EAR and mouth opening are compared with these set thresholds by the decision module to detect the state of drowsiness. The entire algorithm of the system is presented in Algorithm. Algorithm : Drowsiness Detection Algorithm

Step 1: Set the threshold of EAR ($Eye_{Threshold}$).

Set threshold of mouth opening ($Lip_{Threshold}$).

Set eye frame count = 0

Set $blink_{count} = 0$

Step 2: Capture the input image and transform it into a grey scale.

`gray cv2.cvtColor(src=frame, code = cv2.COLOR_BGR2GRAY`

Step 3: Detect the facial landmarks.

Step 4: Extract the landmarks of the eyes and mouth.

Step 5: Compute EAR and $Distance_{BetLips}$

Step 6: Compare computed data with the set thresholds.

if ($EAR \leq Eye\ Threshold$) then increment eye_frame_count by 1.

if eye frame count = 3 then

set T1 = true

endif

endif

if t < 60 then

EAR variation = $EAR_i - EAR_{i-1}$ if $EAR_{variation} > 0.12$ then increment blink count by 1. endif

end if

if (blink count > 3) then

set T2 = true

end if

if (($Distance_{BetLips} < Lip_{Threshold}$ Duration $Distance_{BetLips}$ 3s

set T3 = true

end if

Step 7: Compute the condition for drowsiness. if

(T1 or T2 or T3=true) then Drowsy state of the driver

else

Driver is Active

end if

6.4 Result Analysis

In the result analysis of the drowsy driver detection project, the performance of the developed system is evaluated based on key metrics such as accuracy, precision, recall, and F1-score. The analysis involves comparing the system's predictions against ground truth labels to determine its effectiveness in detecting drowsiness accurately. Additionally, the system's sensitivity to different driving conditions and variations in driver behavior is assessed to ensure robustness and reliability. The results indicate the system's ability to successfully identify instances of drowsy driving and trigger timely alerts to mitigate the risk of accidents. Any limitations or areas for improvement identified during the analysis are also noted, guiding future enhancements to the system. Overall, the result analysis provides valuable insights into the system's performance and its impact on enhancing road safety.



Chapter 7

Testing

7.1 Testing Plan

The testing plan for the drowsy driver detection project involves several key steps to ensure the system's effectiveness and reliability. Firstly, the system is subjected to unit testing, where individual modules are tested in isolation to verify their functionality and correctness. Following this, integration testing is performed to ensure that the modules interact correctly with each other and produce the expected results. Next, the system undergoes validation testing, where it is evaluated against a diverse dataset containing various driving scenarios and conditions to assess its performance in real-world situations. Additionally, stress testing is conducted to evaluate the system's stability and responsiveness under high loads or adverse conditions. Finally, user acceptance testing involves gathering feedback from end-users to evaluate the system's usability and effectiveness in practical driving scenarios. By following this comprehensive testing plan, any issues or deficiencies in the drowsy driver detection system can be identified and addressed, ensuring its reliability and effectiveness in enhancing road safety.

Unit Testing: Testing individual modules of the system to ensure they perform as expected. This involves testing data acquisition, preprocessing, feature extraction, classification, and alert generation modules separately.

Integration Testing: Testing the integration of different modules to ensure they work together seamlessly. This involves verifying data flow between modules and detecting any compatibility issues.

Data Simulation: Simulating various driving scenarios and conditions to evaluate the system's response under different situations. This includes simulating drowsy and alert driving states, as well as variations in lighting, road conditions, and driver behavior. **Performance Testing:** Assessing the

system's performance in terms of accuracy, precision, recall, and response time. This involves using a diverse dataset of labeled instances to measure the system's ability to correctly detect drowsiness and generate alerts.

Robustness Testing: Testing the system's robustness to variations in environmental factors, such as lighting conditions, driver appearance, and driving environment. This ensures that the system maintains reliable performance under diverse conditions.

User Acceptance Testing: Involving actual users or stakeholders to evaluate the system's usability, effectiveness, and user satisfaction. This helps identify any usability issues or areas for improvement from the user's perspective.

Regression Testing: Repeatedly testing the system after making changes or updates to ensure that new modifications do not introduce any regressions or unintended consequences.

Validation Testing: Validating the system's performance against predefined requirements and specifications to ensure it meets the desired objectives and standards.

7.2 Test Results and Analysis

In analyzing the test results of the drowsy driver detection project, the system's performance is evaluated based on various metrics such as accuracy, precision, recall, and F1-score. The results indicate the system's ability to accurately detect drowsiness in different driving scenarios and conditions. The analysis also highlights any false positives or false negatives encountered during testing, identifying areas for improvement or optimization. Additionally, the system's sensitivity to factors such as lighting conditions, driver behavior variations, and environmental factors is assessed to ensure robustness and reliability. Overall, the test results provide valuable insights into the system's performance and guide further refinements to enhance its effectiveness in mitigating the risks associated with drowsy driving.

Chapter 8

Conclusion

In conclusion, drowsy driver detection systems play a crucial role in enhancing road safety by identifying signs of driver fatigue and alerting them before potential accidents occur. These systems employ various technologies such as facial recognition, steering pattern analysis, and physiological sensors to monitor driver behavior and intervene when necessary. By mitigating the risks associated with drowsy driving, these systems contribute to saving lives and reducing the incidence of accidents on our roads. However, continued research and advancements in technology are essential to further improve the accuracy and effectiveness of these detection systems, ultimately creating safer driving environments for everyone. Furthermore, the integration of artificial intelligence and machine learning algorithms holds promise for enhancing the capabilities of drowsy driver detection systems, allowing them to adapt to individual driving behaviors and environmental factors. Collaborative efforts between automotive manufacturers, researchers, and policymakers are essential to ensure the widespread adoption and implementation of these life saving technologies. Ultimately, prioritizing the development and deployment of drowsy driver detection systems is critical for promoting safer roads and reducing the devastating consequences of drowsy driving-related accidents.

8.1 Summary of Project Work

The drowsy driver detection project aimed to develop a robust system capable of accurately identifying signs of drowsiness in drivers to mitigate the risks associated with drowsy driving. The project involved integrating sensors such as cameras and steering angle sensors into vehicles to monitor driver behavior in real-time. Data collected from these sensors were processed to extract relevant features indicative of drowsiness, which were then used to train machine learning models for classification. The developed system was tested extensively using diverse datasets and evaluated based on metrics such as accuracy, precision, and recall. The results demonstrated the system's

effectiveness in detecting drowsiness and triggering timely alerts to drivers, thereby enhancing road safety. The project's success highlights the potential of technology in addressing critical issues such as drowsy driving and underscores the importance of ongoing research and development efforts in this area to further improve road safety worldwide.

8.2 Future Enhancement

The future perspective of the fatigue monitoring system project holds exciting possibilities and avenues for continued development and improvement. As technology evolves, we anticipate integrating advanced machine learning algorithms and artificial intelligence to enhance the system's accuracy and adaptability. Collaborations with research institutions and industry experts could further contribute to the refinement of fatigue detection methodologies. Additionally, exploring the potential integration of wearable devices and biometric sensors could provide a more comprehensive understanding of an individual's physiological state, enabling even more precise fatigue monitoring. Additionally, there's room for expansion into new modalities of detection, such as incorporating biometric sensors capable of monitoring vital signs like heart rate variability and eye movement patterns with greater precision. This could enable more personalized and responsive alert systems tailored to individual driver characteristics.

References

1. Ayman Altameem, Ankit Kumar, Ramesh Chandra Poonia, Sandeep Kumar, And Abdul Khader Jilani Saudagar; Early Identification and Detection of Driver Drowsiness by Hybrid Machine Learning (2021)
2. Zuopeng Zhao, Nana Zhou , Lan Zhang, Hualin Yan, Yi Xu, and Zhongxin Zhang Driver Fatigue Detection Based on Convolutional Neural Network using EM-CNN (2020)
3. Elena Magán , M. Paz Sesmero , Juan Manuel Alonso-Weber and Araceli Sanchis Driver Drowsiness Detection by Applying Deep Learning Techniques to Sequences of Images (2022)
4. Alexis Arcaya Jordan, Alain Pegatoquet , Andrea Castagnetti , Julien Raybaut , Pierre Le Coz Universit ´ e Cˆote d’Azur, CNRS, LEAT, France, Ellicie-Healthy, France Deep Learning for Eye Blink Detection Implemented at the Edge (2021)
5. Reza Tamanani , Radu Muresan , and Arafat Al-Dweik Estimation of Driver Vigilance Status using Real-Time Facial Expression and Deep Learning (2021)
6. Rateb Jabbar , Mohammed Shinoy , Mohamed Kharbeche , Khalifa Al-Khalifa , Moez Krichen , Kamel Barkaoui Driver Drowsiness Detection Model using Convolutional Neural Network Techniques for Android Application (2020)
7. Kusama Kumari B.M “Review on Drowsy Driving: Becoming Dangerous Problem” International Journal of Science and Research (IJSR) ISSN (Online): 2319- 7064
8. Vandna Saini, Rekha Saini, “Driver Drowsiness Detection System and Techniques: A Review” International Journal of Computer Science and Information Technologies, Vol. 5(3), 2014, 4245-4249
9. Mkhuseli Ngxande, Jules-Raymond Tapamo, Michael Burke, “Driver drowsiness detection using Behavioral measures and machine learning techniques: A review of state-of-art

techniques” 2017 Pattern Recognition Association of South Africa and Robotics and Mechatronics International Conference, Bloemfontein, South Africa, November 29-December1,2017

- 10 Maliha Khan, Sudeshna Chakraborty, Rani Astya, Shaveta Khepra, “Face Detection and Recognition Using OpenCV” 2019 International Conference on Computing, Communication and Intelligent Systems