



Q:1 If you declare an array in a module and you want every procedures to access it, then declare it as\_\_\_\_\_

- a Private
- b Public
- c Private or public
- d None of these

Ans b

Q:2 When the form is first referenced in any manner by program, the triggered event is

- a Load
- b Initialize
- c Activate
- d None of these

Ans b

Q:3 In command button, the \_\_\_\_ symbol is used to make the button with shortcut key access.

- a %.
- b &.
- c #.
- d @.

Ans b

Q:4 \_\_\_\_\_ is property is used to hide the content in textbox with some symbols.

- a Name.
- b caption.
- c hidden.
- d pass word char.

Ans d

Q:5 \_\_\_\_\_ property is used to set the flow of control in between the multiple controls.

- a Index.
- b Tab Value.
- c Tab Index.
- d Value.

Ans c

Q:6 A complete repaint of a form or control can be enforced by \_\_\_\_\_ method.

- a refresh.
- b fresh.
- c show.



d hide.

Ans a

Q:7 \_\_\_\_\_ is used to link or embed object, display and manipulate data from other windows based applications.

a OLE.

b DLE.

c MLE.

d CLE.

Ans a

Q:8 The \_\_\_\_\_ event occurs when the form is closed by the user.

a load.

b click.

c double click.

d unload.

Ans d

Q:9 The \_\_\_\_\_ method is used to display a form object.

a show.

b hide.

c control.

d list.

Ans a

Q:10 A \_\_\_\_\_ is a window that contains application code and has other objects placed on it to create the user interface.

a code.

b object.

c form.

d explorer.

Ans c

Q:11 Visual basic project files are saved with an extension \_\_\_\_\_.

a .vbp

b .Imp

c .bvp

d .frm

Ans a

Q:12 Form files are saved with an extension \_\_\_\_\_.

a .frm.

b .prj.



c .vbp.

d .rfm.

Ans a

Q:13 The \_\_\_\_\_ box displays the name of the selected object associated with the form.

a object.

b list.

c combo.

d checkbox.

Ans a

Q:14 A \_\_\_\_\_ procedure is used to create and manipulate custom properties.

a mini.

b property.

c maxi.

d stored.

Ans b

Q:15 Writing code in \_\_\_\_\_ modules can create new objects.

a form.

b procedure.

c class.

d window.

Ans c

Q:16 In the following logic, the condition is check at the end of the loop.

a If.then.

b For.

c While.

d do\_While.

Ans d

Q:17 What properties are required to be specified for a menu item?

a Name

b Caption

c Both a and b

d None of these

Ans c

Q:18 \_\_\_\_\_ present a list of choices to the user.



- a Combo box
- b Rich text box
- c List box
- d None of these

Ans c

\_\_\_\_\_ displays the current drive and allows the user to select a different drive by using a drop down arrow.

- Q:19
- a DirectoryInfo
  - b DriveListBox
  - c FileListBox
  - d None of these

Ans b

\_\_\_\_\_ displays current directory with any subdirectories and allows the user to change directory.

- Q:20
- a FileListBox
  - b DirectoryInfo
  - c DriveListBox
  - d All of these

Ans b

\_\_\_\_\_ displays a list of the files in the current directory or subdirectory.

- Q:21
- a DriveListBox
  - b FileListBox
  - c DirectoryInfo
  - d None Of these

Ans b

Q:22 In GUI, \_\_\_\_\_ is a means of selecting one of several options.

- a Option button
- b Scroll bar
- c List box
- d Combo box

Ans a

Q:23 In declaration a variables \_\_\_\_\_ length of characters is allotted for a variable.

- a 32
- b 64
- c 255
- d 128

Ans c



Q:24 From the following \_\_\_\_\_ tool is used to display pictures in VB form.

- a picture.
- b shape.
- c list box.
- d check box.

Ans a

Q:25 In VB form, the name property can be named with alphabets; \_\_\_\_\_ is the maximum number of character allowed.

- a 20
- b 30
- c 40
- d 50

Ans c

Q:26 \_\_\_\_\_ do not return a value.

- a Sub procedure
- b Function procedure
- c Property procedures
- d All of these

Ans a

Q:27 \_\_\_\_\_ returns numeric code of a character.

- a Chr
- b Asc
- c Format
- d Space

Ans b

Q:28 \_\_\_\_\_ allows us to control the flow of our program's execution based on certain condition.

- a Looping
- b Array
- c Property
- d Control structure

Ans d

Q:29 \_\_\_\_\_ property designates the text appearing in the form's title bar.

- a Text
- b Name
- c Caption
- d None of these



Ans c

Q:30 The \_\_\_\_\_ number of events related to form execution.

- a 2
- b 6
- c 8
- d 12

Ans b

Q:31 The \_\_\_\_\_ is the function is used to display the picture using picture box.

- a picture( ).
- b load picture( ).
- c pic( ).
- d display picture( ).

Ans b

Q:32 The \_\_\_\_\_ concept is used to check for multiple conditions in VB.

- a for....loop.
- b if.
- c if elseif
- d while.

Ans c

Q:33 The method, which loads the form into memory and displays it on screen

- a Load
- b Show
- c Display
- d All of these

Ans b

Q:34 \_\_\_\_\_ method is used to delete items from a list box.

- a Remove
- b Clear
- c Remove item
- d Delete

Ans c

Q:35 RTF stands for \_\_\_\_\_

- a Rich Text Format
- b Rich Title Format
- c Row Text Format
- d Rich Text Function

Ans a



- Q:36 To load graphics on a control at runtime, we have to use the function\_\_\_\_\_.
- a LoadImage
  - b LoadPicture
  - c LoadGraphics
  - d None of these
- Ans b
- Q:37 The window in which the individual documents are displayed is called \_\_\_\_\_ window.
- a Main
  - b Child
  - c Parent
  - d Root
- Ans b
- Q:38 Which of the following keywords is used to keep track of active window.
- a this
  - b Current
  - c Me
  - d All of the above
- Ans c
- Q:39 In for\_loop operation \_\_\_\_ keyword is used to increment the value of variable for execution.
- a else.
  - b step.
  - c incr.
  - d select.
- Ans b
- Q:40 \_\_\_\_ is the keyword represents the end of the for\_loop in Visual basic.
- a next.
  - b end.
  - c close.
  - d stop.
- Ans a
- Q:41 The \_\_\_\_ type of operator is used for checking comparing values.
- a bits wise.
  - b logic.



- c relational.
- d arithmetic.

Ans c

Q:42 The \_\_\_\_ is a keyword is used to combine two conditions for checking at same time.

- a or.
- b and.
- c else.
- d loop.

Ans b

Q:43 \_\_\_\_\_ statement enables us to trap runtime error.

- a On Error
- b On runtime Error
- c Error
- d None of these

Ans a

Q:44 Which window shows information that results from debugging statements in our code

- a Watch window
- b Variables window
- c Locals window
- d Immediate window

Ans d

Q:45 \_\_\_\_\_ is the process of finding and removing errors

- a Checking
- b Debugging
- c Quick watch
- d Compiling

Ans b

Q:46 A \_\_\_\_\_ is a place in the code where the program temporarily stops

- a Break
- b Step over
- c Break point
- d Watch

Ans c

Q:47 To run / to install the Visual basic 6.0 minimum of \_\_\_\_ ram capacity.

- a 1 mb.





b 32 mb.  
c 64 mb.  
d 128 mb.  
Ans b

\_\_\_\_ option in project explorer window used display the coding of the program.  
Q:48  
a View object.  
b View code.  
c View source.  
d View design.  
Ans b

To open the property window for usage \_\_\_\_ shortcut key is used.  
Q:49  
a F3.  
b F2.  
c F5.  
d F4.  
Ans d

In visual basic form, the caption property content will reflect in \_\_\_\_ area.  
Q:50  
a status.  
b work.  
c title.  
d right.  
Ans c

The \_\_\_\_ property is used in VB for maximum form at run time.  
Q:51  
a window status.  
b caption.  
c name.  
d window resize.  
Ans a

The \_\_\_\_ is a shortcut key used to replace the content by specific data in coding window.  
Q:52  
a Ctrl + F.  
b Ctrl + H.  
c Ctrl + Z.  
d Ctrl + U.  
Ans b



\_\_\_\_\_ structure is for selectively executing a single block of statements from among multiple blocks of statements.

Q:53

- a Do case.
- b Select-case.
- c For Next.
- d Do While.

Ans b

The \_\_\_\_\_ statement first executes the statements and then tests the condition after each execution.

Q:54

- a do-until.
- b do-loop while.
- c select-case.
- d if endif.

Ans b

The \_\_\_\_\_ function with symbols representing the date and time is used to print the formatted dates and times.

Q:55

- a String.
- b Format.
- c Val.
- d date.

Ans b

\_\_\_\_\_ is the function used to compare two strings.

Q:56

- a Strinv.
- b StrComp.
- c CompStr.
- d String.

Ans b

The \_\_\_\_\_ function returns the intervals between two dates in terms of years, months or days.

Q:57

- a datediff.
- b dateiff.
- c diffdate.
- d dateinter.

Ans a

\_\_\_\_\_ argument is an integer called button.

Q:58

- a Second.
- b First.
- c Third.
- d Fourth.



Ans        b

Q:59        \_\_\_\_\_ event occurs when the user presses any mouse button.

- a        Mouse Up.
- b        Mouse Right.
- c        Mouse Left.
- d        MouseDown.

Ans        d

Q:60        In for\_loop concept in visual basic \_\_\_\_\_ keyword is used to come out the loop immediately.

- a        exit.
- b        out for.
- c        exit for.
- d        exit if.

Ans        c

Q:61        A text box can hold as many as \_\_\_\_\_ characters for a multi-line text

- a        42000
- b        48000
- c        23000
- d        32000

Ans        d

Q:62        \_\_\_\_\_ control is used to provide an identifiable grouping for other controls

- a        Frame
- b        Label
- c        List box
- d        Command button

Ans        a

Q:63        \_\_\_\_\_ property is used to set the maximum length of a text, a textbox can hold.

- a        Length
- b        Multiline
- c        Maxlength
- d        None of these

Ans        c

Q:64        \_\_\_\_\_ control is used to display text, but user cannot change it directly.

- a        Textbox



- b Labelbox
- c Listbox
- d Commandbutton
- Ans b

- In Visual Basic, a variable name cannot be more than \_\_\_\_\_
- Q:65 characters
- a 455
  - b 255
  - c 355
  - d 200
  - Ans b

- We can preserve the value of a local variable by making the variable\_\_\_\_\_
- Q:66
- a Private
  - b Public
  - c Static
  - d Implicit
  - Ans c

- \_\_\_\_\_ cannot be declared in a form or class module
- Q:67
- a Public constants
  - b Private constants
  - c Static constants
  - d None of these
  - Ans a

- \_\_\_\_\_ arrays can be resized at anytime
- Q:68
- a Dynamic
  - b Fixed
  - c Multidimensional
  - d Control array
  - Ans a

- \_\_\_\_\_ is a block of code that is executed in response to an event.
- Q:69
- a Function procedure
  - b Sub procedure
  - c property procedures
  - d All of the above
  - Ans b

- \_\_\_\_\_ function is used to return a copy of a string without leading spaces.
- Q:70
- a Ltrim



b Rtrim  
c Trim  
d All of the above  
Ans a

Q:71 All the following statements are true about variable scope except  
a Module  
b Global  
c Static  
d Local  
Ans c

The variables that does not change the value during execution of  
Q:72 program is \_\_\_\_\_  
a Numeric  
b Constant  
c String  
d None of the above  
Ans b

Q:73 What is the output of the following code?  
a MyString="Hello World"  
b LeftString=left(MyString,3)  
c Hel  
d Hello World  
Ans c

Q:74 \_\_\_\_\_ is a control related event.  
a Keydown  
b Load  
c Terminate  
d GotFocus  
Ans d

When the form is first referenced in any manner by program, the  
Q:75 triggered event is \_\_\_\_\_  
a Load  
b Initialize  
c Activate  
d None of these  
Ans b

Q:76 \_\_\_\_\_ returns or sets the number of characters selected.  
a Sellength



- b Selstart
- c Seltext
- d None of the above
- Ans a

- \_\_\_\_\_ property of an image control sizes the picture loaded to it.
- Q:77
- a Undeclared variable
  - b Text
  - c Image
  - d Declared variable
  - Ans d

- The \_\_\_\_\_ method is used to read a value of a property of control from container form file.
- Q:78
- a ReadProperty
  - b WriteProperty
  - c TextProperty
  - d ScanProperty
  - Ans a

- A An ActiveX EXE, otherwise called as an \_\_\_\_ server
- Q:79
- a inprocess
  - b out of process
  - c remote
  - d active
  - Ans b

- The \_\_\_\_\_ menu is used to add a new tool in the tools box.
- Q:80
- a Project
  - b File
  - c Edit
  - d View
  - Ans a

- A web browser control can accept \_\_\_\_\_ targets by default.
- Q:81
- a select and deselect shortcuts
  - b drag and drop shortcuts
  - c cut and paste shortcuts
  - d copy and paste shortcuts
  - Ans b

- The \_\_\_\_\_ control is always cleared if the users leave the page and then use the back button to return to the page.
- Q:82



- a password field
- b user field
- c text field
- d tab field

Ans a

Q:83 The \_\_\_\_\_ control is used for accepting multiple lines of standard text with a scroll bar attached.

- a frame area
- b text area
- c multiline area
- d label area

Ans b

Q:84 The \_\_\_\_\_ object to save a query definition in our application.

- a text
- b label
- c save
- d command

Ans d

Q:85 The \_\_\_\_\_, commonly known as stored procedures, perform an action on the database without returning a record set.

- a action query
- b select query
- c rollback query
- d commit query

Ans a

Q:86 The \_\_\_\_\_ method fills the combo box item.

- a add item
- b addition
- c list
- d addlist

Ans a

Q:87 \_\_\_\_\_ combines the features of the text box and list box

- a Picture box
- b Check box
- c Combo box
- d Option button

Ans c



Q:88 The \_\_\_\_ statement is used to change the control to specified location without any condition.

- a goto.
- b select.
- c else if.
- d while.

Ans a

Q:89 In list box concept \_\_\_\_ function is used to insert item to the list.

- a addlist().
- b additem().
- c addcount().
- d adddata().

Ans b

\_\_\_\_ function is used to delete all the data items be completely removed.

- a list().
- b listdel().
- c listclear().
- d listremove().

Ans c

\_\_\_\_\_ argument gives the status of the SHIFT, CTRL and ALT keys.

- a Second.
- b First.
- c Third.
- d Fourth.

Ans a

\_\_\_\_\_ and \_\_\_\_\_ functions are used to add predefined dialog boxes.

- a Input( ) and MsgBox( )
- b MsgBox( ) and Listbox( )
- c Combobox( ) and Input( )
- d Input( ) and Listbox( )

Ans a

The common Dialog is used as a \_\_\_\_\_ that lets the user select and saves files.

- a dialog box
- b msgbox
- c input box





d           listbox

Ans        a

\_\_\_\_\_ function specifies the file name and assigns the picture to the picture property.

Q:94

a           Unload picture

b           Load picture

c           Show picture

d           List picture

Ans        b

Q:95       \_\_\_\_\_ method sets the colour of an individual pixel.

a           Reset

b           Set

c           Point

d           Fixed

Ans        b

Q:96       The point method returns the \_\_\_\_\_ of a particular pixel.

a           color

b           position

c           coordinate

d           center point

Ans        a

\_\_\_\_\_ property is an integer value corresponding to the position of the scroll box in the scroll bar.

Q:97

a           Value

b           Change

c           Visible

d           None of the above

Ans        a

In visual basic the \_\_\_\_\_ value is equivalent to the vb YES NO button in message box.

Q:98

a           2

b           4

c           6

d           8

Ans        b

The \_\_\_\_\_ property of the file list box is updated according to the selected file type.

Q:99

a           fill

b           pattern



c list  
d select  
Ans b

Q:100 A \_\_\_\_\_ access file is like a database.  
a random  
b sequential  
c dynamic  
d static  
Ans a

Q:101 \_\_\_\_\_ files are accessed byte by byte.  
a Sequential  
b Dynamic  
c Binary  
d Random  
Ans c

\_\_\_\_\_ property can be used to copy, cut and paste from any text box that has focus.  
Q:102  
a Active control  
b ActiveX control  
c Active DAO  
d Active RDO  
Ans a

Any \_\_\_\_\_ typed in one text box can be cut, copied and pasted in the other text box.  
Q:103  
a label  
b data  
c text  
d word  
Ans c

\_\_\_\_\_ bugs are those that occur when we attempt to create the program executable file (EXE) or run the object.  
Q:104  
a Run time  
b Compile time  
c Intermediate time  
d Error time  
Ans b

The \_\_\_\_\_ in VB displays any required or optional parameters for methods.  
Q:105  
a optional info  
b auto incre info



c auto decre info  
d auto quick info  
Ans c

Q:106 The F5 is key pressed the \_\_\_\_ event of form is executed first.  
a activate.  
b got focus.  
c initialize.  
d paint procedure.  
Ans c

Q:107 In coding window the \_\_\_\_ shortcut key is used to find the particular character or code.  
a Ctrl + Q.  
b Ctrl + F.  
c Alt + F.  
d Alt + Q.  
Ans b

Q:108 The right hand drop down list box in the coding window is called \_\_\_\_ list box.  
a procedure.  
b event.  
c task.  
d content.  
Ans a

Q:109 The \_\_\_\_ shortcut is used to get the QuickInfo option in visual basic.  
a Ctrl + Q.  
b Ctrl + Z.  
c Ctrl + I.  
d Ctrl + F.  
Ans c

Q:110 In visual basic the, Visible property consists \_\_\_\_ state.  
a 6  
b 4  
c 2  
d 1  
Ans c

Q:111 The \_\_\_\_ data type is the default and standard type used in programming side.



- a variant.
- b string.
- c numeric.
- d byte.

Ans a

Q:112 In data type the \_\_\_\_ prefix used to represent the Boolean data.

- a bcl.
- b bln.
- c bct.
- d bty.

Ans b

Q:113 The \_\_\_\_ function returns a string stored in a variant data type.

- a Chr.
- b Str.
- c Char.
- d None of the above

Ans a

Q:114 The \_\_\_\_\_ displays a list of items from which a user can select one.

- a listbox
- b textbox
- c combobox
- d labelbox

Ans a

Q:115 \_\_\_\_\_ is a control used to display message and enter text.

- a ListBox
- b Combobox
- c Labelbox
- d TextBox

Ans d

Q:116 \_\_\_\_\_ control executes the timer events at specified intervals of time.

- a Timer
- b Clock
- c Frame
- d Digital

Ans a



- \_\_\_\_\_ control serves as a visual and functional container for controls.
- Q:117
- a ListBox
  - b Frame
  - c Combobox
  - d Labelbox
- Ans b
- \_\_\_\_\_ displays a text that the user cannot modify or interact with.
- Q:118
- a List
  - b Combo
  - c Label
  - d Text
- Ans b
- Hyper link is a web based object that is used to navigate to another document using the \_\_\_\_\_ method.
- Q:119
- a Navigate out
  - b Navigate to
  - c Navigate set
  - d Navigate in
- Ans b
- An \_\_\_\_\_ is an object that we place on a form to enable or enhance a users interaction with an application.
- Q:120
- a ActiveX control
  - b Module
  - c Procedure
  - d Control
- Ans a
- The \_\_\_\_\_ control is used to create a hierarchy that shows at least 2 or more levels of a database.
- Q:121
- a form view
  - b tool view
  - c level view
  - d tree view
- Ans d
- By default, the textbox control can hold text as \_\_\_\_\_
- Q:122
- a Multiple lines
  - b Single line
  - c Password character
  - d None of these



Ans        b

Q:123      What is the default range of horizontal scroll bar?

- a            0 to 32767
- b            -32768 to 32767
- c            -32768 to 0
- d            None of these

Ans        a

A \_\_\_\_\_ displays a list of items from which user can select one or more items.

Q:124

- a            Combo box
- b            List box
- c            Check box
- d            Scroll bar

Ans        b

\_\_\_\_\_ is a method which moves the focus to the specified control or form

Q:125

- a            Setfocus
- b            Gotfocus
- c            Lostfocus
- d            None of these

Ans        a

A \_\_\_\_\_ control is a frame that can contain of several panels, which inform the user of the status of an application. The control can hold upto 16 frames.

Q:126

- a            frame bar
- b            status bar
- c            list bar
- d            tool bar

Ans        b

A \_\_\_\_\_ control acts like the dividers in a note book or the labels on a group of file folders.

Q:127

- a            tool strip
- b            window strip
- c            control strip
- d            tab strip

Ans        d

Q:128      The changes are saved in a transaction using \_\_\_\_\_ operation.

- a            rollback
- b            truncate



c commit

d store

Ans c

\_\_\_\_\_ allows us to build a query in a graphical user interface without having to learn SQL.

Q:129 a Query designer

b Form designer

c Report designer

d Table designer

Ans a

Q:130 ComboBox contains a \_\_\_\_\_ and \_\_\_\_\_.

a textbox, listbox

b listbox, labelbox

c labelbox, textbox

d listbox, optionbox

Ans a

Q:131 MDI stands for \_\_\_\_\_.

a multiple document interface.

b multiple design interface.

c manipulated document interface.

d menu design interface.

Ans a

A \_\_\_\_\_ control is used to create applications that present information in rows and columns.

Q:132 a gridflex

b gridline

c flexline

d flexgrid

Ans d

The code in an application can be broken into logical components by \_\_\_\_\_ process.

Q:133 a procedural

b modular

c partitioning

d None of the above

Ans c

A \_\_\_\_\_ is a collection of object classes that model the structure of a relational database system.

Q:134 a ADO



b        DAO  
c        RDO  
d        DOA  
Ans     b

Q:135     The \_\_\_\_\_ object is a stored query definition, which is a  
precompiled SQL statement.  
a        QueryDef  
b        QueryFix  
c        QueryDif  
d        QueryFed  
Ans     a

Q:136     \_\_\_\_\_ queries are SQL statements that perform specific actions  
on the database.  
a        Action  
b        Fixed  
c        Unfixed  
d        Select  
Ans     a

Q:137     The \_\_\_\_\_ method creates a connection between the  
application and the ODBC database and assigns it to a database  
type object.  
a        FixedDatabase  
b        SelectDatabase  
c        CreateDatabase  
d        OpenDatabase  
Ans     d

Q:138     The Data control implements data access by using the \_\_\_\_\_.  
a        Microsoft Jet Database Engine  
b        Microsoft RDO  
c        Microsoft ADO  
d        Microsoft DAO  
Ans     a

Q:139     Visual basic Programming is an \_\_\_\_\_ driven programming  
concept.  
a        task.  
b        event.  
c        flow.  
d        exection.  
Ans     b





- Q:140 The \_\_\_\_\_ method of the connection object is used to run the queries against the database.
- a Open Resultset
  - b Close Resultset
  - c Fix Resultset
  - d Unfix Resultset
- Ans a
- 
- Q:141 \_\_\_\_\_ modules can be reused in many different applications.
- a Form modules
  - b Class modules
  - c Standard modules
  - d None of these
- Ans c
- 
- Q:142 Storage size of Byte datatype is \_\_\_\_\_.
- a 1 byte
  - b 2 byte
  - c 4 byte
  - d None of these
- Ans a
- 
- Q:143 The default property for a text box control is \_\_\_\_\_
- a Text
  - b Password char
  - c Multiline
  - d Enable
- Ans a
- 
- \_\_\_\_\_ property is used to return or sets a value that determines whether the control can respond to user-generated events.
- Q:144
- a Autosize
  - b Enable
  - c Visible
  - d Value
- Ans b
- 
- Q:145 \_\_\_\_\_ is a collection of files
- a Class
  - b Group
  - c Project
  - d All of the above
- Ans c



\_\_\_\_\_ shows the value of any variables within the scope of the current procedure.

Q:146

- a Immediate window
- b Locals window
- c Watches window
- d None of these

Ans b

\_\_\_\_\_ shows the property type as well as a short description of the property

Q:147

- a Object box
- b Description pane
- c Form layout window
- d Code editor

Ans b

\_\_\_\_\_ contains shortcuts to frequently performed actions.

Q:148

- a Context menu
- b Menu bar
- c Tool bar
- d Tool box

Ans a

\_\_\_\_\_ are objects that are placed on form objects.

Q:149

- a GUI
- b IDE
- c Controls
- d Project

Ans c

The TypeOf statement is used to find out \_\_\_\_\_

Q:150

- a Type of picture displayed
- b Type of object accessed in control collection
- c Type of button clicked
- d All of the above

Ans b

To attach a scroll bar to the textbox , the property of textbox should be set to:

Q:151

- a Multiline=True
- b Scrollbar=True
- c SingleLine=False
- d None of these

Ans a



Q:152 \_\_\_\_\_ method sets the colour of an individual pixel.

- a PSet
- b LSet
- c SSet
- d RSet

Ans a

Q:153 \_\_\_\_\_ method paints graphics at arbitrary locations.

- a Picture
- b PaintPicture
- c ImagePicture
- d Image

Ans b

\_\_\_\_\_ boxes are used to display information to the user and to prompt the user for the data needed to continue an application.

- a MsgBox
- b Inputbox
- c Listbox
- d Dialog

Ans d

A shape control is a visual element that contains several \_\_\_\_\_ shapes.

- a defined
- b predefined
- c lateral
- d formlevel

Ans b

Child forms are displayed within the \_\_\_\_\_ area of a MDI Form at run time.

- a internal
- b external
- c limited
- d unlimited

Ans a

The \_\_\_\_\_ property of controls collection returns the number of controls on the form.

- a countline
- b count
- c linecount
- d numbercount



Ans        b

Q:158        A \_\_\_\_\_ control in visual basic is used to create applications that present information in rows and columns.

- a        MSFlexGrid
- b        MSGridFlex
- c        MSGridLine
- d        MSLineGrid

Ans        a

Q:159        The various properties in property window are arranged in \_\_\_\_\_ order.

- a        Alphabetical
- b        Sequential
- c        Binary
- d        Descending

Ans        a

Q:160        In date data type the \_\_\_\_\_ byte is require for storing data.

- a        10
- b        6
- c        8
- d        2

Ans        c

Q:161        The \_\_\_\_\_ number of characters are allowed for naming the variables.

- a        128
- b        255
- c        64
- d        32

Ans        b

Q:162        Normally declared in the general section of the codes' windows using the \_\_\_\_\_ statement.

- a        dim
- b        int
- c        str
- d        val

Ans        a

Q:163        \_\_\_\_\_ allows a procedure to be repeated as many times as long as the processor could support

- a        looping



b reserved words  
c leywrods  
d data type  
Ans a

In multiple form based project the current form represented by  
Q:164 \_\_\_\_ keyword.  
a me.  
b load.  
c class.  
d form.  
Ans a

Like text box, \_\_\_\_\_ is another tool used for display / output the  
Q:165 information.  
a input box.  
b frame.  
c label.  
d message box.  
Ans d

Among the various properties of the tools in VB, in general \_\_\_\_\_  
Q:166 property is not supposed to change the value at maximum time.  
a caption.  
b name.  
c height.  
d color.  
Ans b

\_\_\_\_\_ property is used to hide the tool in run time by setting value  
Q:167 as false.  
a visible.  
b enabled.  
c hide.  
d delete.  
Ans a

SDI stands for \_\_\_\_\_.  
Q:168  
a Simple Document Interface.  
b Single Document Interface.  
c Sample Document Interface.  
d Simple Document Internal.  
Ans a



Q:169 \_\_\_\_\_ is a command used to come out of the loop.

- a break.
- b continue.
- c case.
- d elseif.

Ans a

The component option is used to insert new tool in to the toolbox,

Q:170 \_\_\_\_\_ menu is used.

- a file.
- b view.
- c project.
- d help.

Ans c

\_\_\_\_\_ boxes display information in a dialog box superimposed on the form.

- a Input.
- b Message.
- c Text.
- d List.

Ans b

Q:172 The integer data type is range form \_\_\_\_ .

- a -32,768 to 32,767
- b -33,768 to 33768
- c -2,147,483,648 to 2,147,483,648
- d -,147,483,648 to 3,147,483,648

Ans a

Q:173 \_\_\_\_\_ occurs when the user presses any mouse button.

- a MouseUp
- b MouseDown
- c MouseRight
- d MouseLeft

Ans b

Each menu control array element is identified by a unique index value, indicated in the \_\_\_\_\_ property box on the menu editor.

Q:174

- a number
- b index
- c array
- d value

Ans b



\_\_\_\_\_property of an Image control is used to automatically  
Q:175      resize a picture and place it inside the control.

- a      Stretch
- b      Image
- c      Resize
- d      Control

Ans      a

\_\_\_\_\_ is the process of clicking the mouse button in a control  
Q:176      and moving the mouse while holding down the mouse button.

- a      Dropping
- b      Cutting
- c      Moving
- d      Dragging

Ans      d

\_\_\_\_\_ function returns the intervals between two dates in  
Q:177      terms of years, months or days.

- a      DateDiff( )
- b      DateIn( )
- c      DateFix( )
- d      DiDate( )

Ans      a

\_\_\_\_\_ array size always remains the same.  
Q:178

- a      Fixed-size
- b      Dynamic
- c      Preserve
- d      Multidimension

Ans      a

The \_\_\_\_ keyword is used when we want Visual Basic to create a  
Q:179      new instance of the original object.

- a      constructor
- b      destructor
- c      preprocessor
- d      intermediate

Ans      b

In VB the order in which you create the controls is the order used  
Q:180      by using \_\_\_\_ key

- a      tab.



b        Spacebar.  
c        caps.  
d        scroll.  
Ans     a

Q:181    The event occurs when certain key of keyboard is pressed  
a        keyType  
b        keyPress  
c        KeyEnter  
d        None of these  
Ans     b

Q:182    A \_\_\_\_\_ is used to display information entered at design time,  
by a user at runtime ,or assigned within the code  
a        LabelBox  
b        TextBox  
c        ListBox  
d        ComboBox  
Ans     b

Q:183    \_\_\_\_\_ method adds a row to an MSFlexGrid.  
a        Add  
b        New  
c        Additem  
d        None of these  
Ans     c

Q:184    \_\_\_\_\_ indicates whether a particular condition is on or off.  
a        Combo box  
b        List box  
c        Check box  
d        Text box  
Ans     c

Q:185    \_\_\_\_\_ method is used to draw and fill boxes.  
a        Fill  
b        Draw  
c        Line  
d        Image  
Ans     c

Q:186    The \_\_\_\_\_ and \_\_\_\_\_ properties specify the current cell in a  
MSFlexGrid.  
a        row, col





b col, cols  
c row, rows  
d row, cell  
Ans a

Q:187 A \_\_\_\_\_ method is used to draw a variety of circular and elliptical shapes.  
a line  
b square  
c circle  
d shape  
Ans c

Q:188 A \_\_\_\_\_ dialog box does not allow the user to continue with other applications unless it is closed or unloaded.  
a modeless  
b modal  
c modalless  
d modalfull  
Ans b

Q:189 The \_\_\_\_\_ dialog box allows shifting of focus between the dialog box and another form without closing the dialog box.  
a modal  
b modalfull  
c modeless  
d modaladd  
Ans c

Q:190 \_\_\_\_\_ occurs when the user releases any mouse button.  
aMouseDown  
bMouseUp  
cMouseLeft  
dMouseRight  
Ans b

Q:191 MSDN Stands for \_\_\_\_\_  
a microsoft domain network  
b microsoft developer network  
c microsoft Dial netwrok  
d microsoft Dynamic network  
Ans b



\_\_\_\_\_ allows you to position the forms in your application using a small graphical representation of the screen.

Q:192

- a Debugging window
- b Form designer window
- c Property window
- d Form layout window

Ans

d

\_\_\_\_\_ is an example for control

Q:193

- a Form
- b Event
- c Method
- d Code editor

Ans

a

Frame Control acts as a \_\_\_\_\_.

Q:194

- a Method
- b Container
- c Event
- d Class

Ans

b

\_\_\_\_\_ property is used to check whether the object is active or deactivate.

Q:195

- a Visible
- b Enabled
- c Name
- d Dragmode

Ans

b

The default datatype for VB is \_\_\_\_\_

Q:196

- a Integer
- b Variant
- c String
- d Decimal

Ans

b

\_\_\_\_\_ loop repeats a group of statements for each item in a collection of objects or for each element of an array.

Q:197

- a While loop
- b Do Until loop
- c For each loop
- d Do while loop

Ans

c



Q:198 \_\_\_\_\_ is an action recognized by a form or the control.

- a Property
- b Event
- c Method
- d Procedure

Ans b

Q:199 \_\_\_\_\_ is one of the main building blocks in a VB application.

- a Form
- b Event
- c Procedure
- d Method

Ans a

\_\_\_\_\_ is used for finding out about objects, properties and methods.

- Q:200
- a Object browser
  - b Form layout window
  - c Code editor window
  - d None of the above

Ans a

A text box can hold as many as \_\_\_\_\_ characters for a single line text.

- Q:201
- a 2052
  - b 2048
  - c 2058
  - d 2047

Ans b

Q:202 Mouse down event takes place when you,

- a Click the left mouse button
- b Press the mouse button
- c Mouse is moved over the control
- d All of the above

Ans b

\_\_\_\_\_ is a meaningful name that takes the place of a number or string that does not change.

- Q:203
- a Variable
  - b Constant
  - c Event
  - d Datatype

Ans b



Q:204 \_\_\_\_\_ is a set of sequentially indexed elements having the same type of data.

- a Loop
- b Array
- c Variables
- d Objects

Ans b

Q:205 \_\_\_\_\_ is a built in function to return lower bound of an array

- a Lbound()
- b LRbound()
- c Lowbound()
- d None of these

Ans a

Q:206 \_\_\_\_\_ window is used to align the form execution in desired position or location.

- a form layout.
- b property.
- c project explorer.
- d coding.

Ans a

Q:207 In coding window, the programming statement has been written in the \_\_\_\_\_.

- a block.
- b group.
- c event.
- d property.

Ans c

Q:208 \_\_\_\_\_ event will execute automatically at the activation of the tool.

- a GotFocus
- b LostFocus
- c Enabled.
- d Click.

Ans a

Q:209 The \_\_\_\_\_ key is used as control key on moving around the form without mouse.

- a Spacebar.
- b enter.



- c shift
- d tab.

Ans d

Q:210 In command button the \_\_\_\_\_ property is used to change the label value for any content.

- a name.
- b font.
- c caption.
- d height.

Ans c

Q:211 In visual basic the \_\_\_\_\_ file consist of complete coding and form design.

- a project.
- b form.
- c class.
- d module.

Ans a

Q:212 The \_\_\_\_\_ and \_\_\_\_\_ properties should be set if the user wants the label to properly display variable length lines or varying numbers of lines.

- a autosize, wordwrap
- b autosize, wordart
- c autosize, wordart
- d autosize, wordwrap

Ans d

Q:213 If the user is interested in displaying multiple lines of text in a TextBox control, set the \_\_\_\_\_ property to true.

- a multiline
- b singleline
- c single
- d multi

Ans a

Q:214 Date and Time are internally stores as \_\_\_\_\_ in Visual Basic.

- a strings
- b numbers
- c characters
- d symbols

Ans b



Q:215 The \_\_\_\_\_ function in VB retrieves the date and time.

- a date
- b now
- c datediff
- d datenow

Ans b

The individual elements of an array are identified using an

Q:216 \_\_\_\_\_.

- a number
- b character
- c index
- d value

Ans c

\_\_\_\_\_ is named storage locations in memory, the value of which does not change during program execution.

- Q:217
- a Constant
  - b Variable
  - c Static
  - d Dynamic

Ans a

Variables of different data types when combined as a single variable to hold several relation informations are called a

Q:218 \_\_\_\_\_.

- a user-defined data type
- b user-undefined data type
- c user-declared data type
- d user-undeclared data type

Ans a

When we want to change the size of the array without losing the previous data we have to use \_\_\_\_\_ keyword with the ReDim statement.

- Q:219
- a preserve
  - b static
  - c dynamic
  - d permanent

Ans a

Q:220 A \_\_\_\_\_ variable is one that is declared inside a procedure.

- a global
- b external
- c local



d None of the above

Ans c

Q:221 A \_\_\_\_\_ variable is available to all the procedures in the module.

a procedure-level

b module-level.

c class-level

d object-level

Ans b

Q:222 \_\_\_\_\_ indicates that the function is applicable to the whole program

a private

b public

c local

d global

Ans b

Q:223 \_\_\_\_\_ are the operations that an object can perform.

a methods

b class

c objects

d variables

Ans a

Q:224 Event-driven languages are \_\_\_\_\_

a FORTRAN based

b Are used to write procedural languages

c OOP

d Designed to make programming GUI easier

Ans d

Q:225 Which of the following is not part of the IDE \_\_\_\_\_

a Code editor window

b General window

c Form layout window

d Properties window

Ans b

Q:226 The application name always appears in the \_\_\_\_\_

a Properties window

b Intermediate window

c Title bar

d Code window

Ans c



Q:227 In visual basic controls are also called as \_\_\_\_\_

- a Objects
- b Rules
- c Part of the menus
- d Code

Ans a

Q:228 The location of the form on the desktop during execution is determined by the \_\_\_\_\_

- a Form Designer window
- b Project Explorer window
- c Context Menu
- d Form Layout window

Ans d

Q:229 Visual Basic forms are identified by a \_\_\_\_\_

- a .frm suffix
- b .mak suffix
- c .for suffix
- d A special icon

Ans a

Q:230 The \_\_\_\_\_ control is used for checking the multiple option in given list

- a radio button
- b check box
- c list box
- d text box

Ans b

Q:231 Self Length Property is supported by \_\_\_\_\_ control in VB.

- a label.
- b text box.
- c command button.
- d option button.

Ans b

Q:232 \_\_\_\_\_ is a built in function to return the upper bound of an array

- a Upper()
- b ToUpper()
- c Ubound()
- d URbound()

Ans c





\_\_\_\_\_ statement is used to define a property procedure that assigns the value of a property.

Q:233

- a Property Let
- b Property Get
- c Property Set
- d None of these

Ans

a

If variables are not implicitly or explicitly type, they are assigned the type by default \_\_\_\_\_

Q:234

- a Character
- b Integer
- c Variant
- d None of these

Ans

c

All the following statements are true about variable names except

Q:235

- a The first character must be a letter
- b They may include letters, numbers, and underscore(\_)
- c Can be any length
- d You cannot use a reserved word.

Ans

c

\_\_\_\_\_ are used by VB to hold information needed by an application.

Q:236

- a Variables
- b Datatypes
- c Objects
- d Dim

Ans

a

The \_\_\_\_\_ allows direct exit from a For loop, Do loop, Sub procedure, or Function procedure.

Q:237

- a Exit
- b Exit for
- c Exit Do
- d Break

Ans

a

What method is used to clear the contents of MSFlexGrid control?

Q:238

- a Clr
- b Cls
- c RemoveItem



d Clear  
Ans d

\_\_\_\_\_ files contains bitmaps, strings, and other data that we can change without having to reedit and recompile the program code.

Q:239  
a Class file  
b Resource file  
c Forms  
d None of these  
Ans b

Q:240 Extension of ActiveX controls \_\_\_\_\_  
a .acx  
b .acv  
c .ocx  
d .oxc  
Ans c

Q:241 Extension of ActiveX designers\_\_\_\_\_.  
a .dsr  
b .axd  
c .adx  
d None of these  
Ans a

Q:242 \_\_\_\_\_ is used to select a particular record.  
a Dataprovider  
b Database  
c VDM  
d File pointer  
Ans d

\_\_\_\_\_ is a collection of code which translates application request into physical operation on datastore.  
Q:243  
a Database  
b Data provider  
c Interface  
d None of these  
Ans b

Q:244 \_\_\_\_\_ is a Microsoft product for windows platform  
a Jet database engine  
b ODBC  
c OLEDB  
d None of these



Ans a

\_\_\_\_\_ represents a user account with particular access permission in a particular workspace.

- a User
- b Workspace
- c Database
- d None of these

Ans a

Q:246 The \_\_\_\_ menu is used for executing the program in Visual basic.

- a run.
- b tools.
- c insert.
- d window.

Ans a

Q:247 In visual basic the declaration of variables is done by \_\_\_\_ key word.

- a int.
- b dim.
- c static
- d declare.

Ans b

Q:248 In visual basic \_\_\_\_ types of scroll bars available in visual basic.

- a two.
- b three.
- c four.
- d five.

Ans a

Q:249 While designing the visual basic there are \_\_\_\_ methods used for adding a tools in to form window.

- a five.
- b four.
- c three.
- d two.

Ans d

Q:250 In VB the main form consist of more than one sub form is called \_\_\_\_.

- a subordinate.



b child.  
c super.  
d second level.  
Ans b

Q:251 The \_\_\_\_ is shortcut key used for execution of visual basic program.  
a F7.  
b F2.  
c F5.  
d F9.  
Ans c

Q:252 Among the events in VB, the Load event is associated with \_\_\_\_ .  
a command button.  
b label.  
c text box.  
d form.  
Ans d

Q:253 The Data Report designer is broken into \_\_\_\_ different sections.  
a two.  
b six.  
c eight.  
d ten.  
Ans b

Q:254 \_\_\_\_\_ object contains information about an error occurred during a DAO operation  
a Error  
b ERR  
c Debugging  
d None of these  
Ans a

Q:255 Through the properties and methods of \_\_\_\_\_ object, we can set validation rules and return information about linked tables in DAO model.  
a Table def  
b Query def  
c User  
d None of these  
Ans a



- \_\_\_\_\_ object in DAO model represents objects like saved forms, modules, reports etc:
- Q:256
- a Fields
  - b Container
  - c Query def
  - d None of these
- Ans b
- UDA stands for \_\_\_\_\_.
- Q:257
- a Uniform Data Access
  - b Universal Data Address
  - c Universal Data Access
  - d Uniform Data Address
- Ans c
- \_\_\_\_\_ connectivity is independent of any DBMS or operating system
- Q:258
- a OLEDB
  - b ODBC
  - c DAO
  - d None of these
- Ans b
- \_\_\_\_\_ method used to load or import a text file or .rtf file into a rich text box.
- Q:259
- a Load
  - b Load file
  - c Import
  - d None of these
- Ans b
- \_\_\_\_\_ control provides all standard dialog boxes into our VB form
- Q:260
- a Common dialog control
  - b Rich text box
  - c Input box
  - d All of these
- Ans a
- \_\_\_\_\_ are called design time entities
- Q:261
- a Form
  - b Class
  - c Control
  - d None of these
- Ans b



Q:262 The \_\_\_\_\_ is a tool used for both the Input and output purpose.

- a command button.
- b text box.
- c label.
- d Combo box.

Ans b

\_\_\_\_\_ property is related with Command button specific for displaying picture

- a Down picture.
- b Picture.
- c Height.
- d Object.

Ans a

Q:264 \_\_\_\_\_ is a tool used in form window for grouping the option button.

- a Label.
- b Group.
- c Frame.
- d Shape.

Ans c

Q:265 The list of forms will display in tree like structure in \_\_\_\_\_ window.

- a form.
- b project explorer.
- c property.
- d form layout.

Ans b

Q:266 The \_\_\_\_\_ menu used for adding tools in to existing tools box.

- a file.
- b view.
- c project.
- d format.

Ans c

Q:267 \_\_\_\_\_ are called runtime entities.

- a Class
- b Object
- c Form



d Control  
Ans b

Q:268 In a class, \_\_\_\_\_ is used to pass value to the property.  
a Property Let procedure  
b Property Get procedure  
c Property Set procedure  
d None of these  
Ans a

Q:269 In a class, \_\_\_\_\_ is used to store data in a property and returns the property.  
a Property Let procedure  
b Property Get procedure  
c Property Set procedure  
d None of these  
Ans b

Q:270 In a class, \_\_\_\_\_ is used to pass object itself as a function argument.  
a Property Let procedure  
b Property Get procedure  
c Property Set procedure  
d None of these  
Ans c

Q:271 \_\_\_\_\_ is an event of a class  
a Initialize  
b Click  
c Got focus  
d None of these  
Ans a

Q:272 \_\_\_\_\_ event occurs when an object of a class is created  
a Initialize  
b Click  
c Got focus  
d None of these  
Ans a

Q:273 \_\_\_\_\_ event occurs when last reference to the class goes out of scope.  
a Initialize  
b Terminate  
c Got focus



d None of these  
Ans b

Q:274 \_\_\_\_\_ keyword is used to create an object for the class.  
a New  
b Create  
c Allocate  
d None of these  
Ans a

Q:275 \_\_\_\_\_ is a group of objects gathered together as a single object.  
a Collection  
b Form  
c Array  
d None of these  
Ans a

Q:276 In Visual basic more than one child \_\_\_\_\_ is allowed to add in project.  
a form.  
b window.  
c property.  
d codings.  
Ans a

Q:277 Status bar appears at the \_\_\_\_\_ of the MDI form.  
a top.  
b bottom.  
c left.  
d right.  
Ans b

Q:278 The \_\_\_\_\_ keyboard refers to current form in VB project.  
a me.  
b current.  
c form.  
d case.  
Ans a

Q:279 Scroll bar is of \_\_\_\_\_ types in Visual Basic for usage.  
a two.  
b four.  
c five.  
d six.





Ans a

Q:280 The width of any tool in visual basic can be changed at \_\_\_\_ time.

- a run.
- b debug.
- c design.
- d edit.

Ans c

Q:281 The Visual basic programming is \_\_\_\_\_ based programming concept in general.

- a CUI.
- b logical.
- c concept.
- d GUI.

Ans d

Q:282 \_\_\_\_\_ event occurs whenever the size of the form is changed.

- a Size
- b Change
- c Resize
- d Fixed

Ans c

Q:283 \_\_\_\_\_ method with \_\_\_\_\_ argument is used to cascade forms.

- a Arrange, VbCascade
- b Arrange, VbFill
- c Arrange, VbUnfill
- d Arrange, Cascade

Ans a

Q:284 \_\_\_\_\_ array size can be changed at run-time.

- a Preserve
- b Multidimensional
- c Fixed
- d Dynamic array

Ans d

Q:285 A specific object can be referenced by an object variable of that object type using the \_\_\_\_\_ keyword.

- a generic
- b static



c dynamic  
d ungeneric  
Ans a

Q:286 The role of the \_\_\_\_\_ is to free the space allocated in the constructor.  
a old  
b new  
c memory  
d object  
Ans b

Q:287 A \_\_\_\_\_ control variable can refer to any control on any form in an application.  
a reset  
b set  
c static  
d dynamic  
Ans b

Q:288 \_\_\_\_\_ can be built by adding custom properties to a Form and then they can be used as templates for new objects.  
a Objects  
b Controls  
c Tools  
d Classes  
Ans d

Q:289 Class modules have two events \_\_\_\_ and \_\_\_\_.  
a initialize, terminate  
b initialize, interrupt  
c terminate, interrupt  
d interrupt, exception  
Ans a

Q:290 By using \_\_\_\_\_ keyword we can create a collection.  
a New  
b Create  
c Allocate  
d None of these  
Ans a

Q:291 To find out the total number of items in a collection we can use \_\_\_\_\_ property.  
a Count  
b Find



c Add  
d None of these  
Ans a

Q:292 \_\_\_\_\_ is an important property of a file list box.  
a Pattern  
b File  
c Drive  
d None of these  
Ans a

Q:293 \_\_\_\_\_ is the important event of a timer control.  
a Timer  
b Click  
c Change  
d Got focus  
Ans a

\_\_\_\_\_ property is used to return the index of a selected item  
Q:294 in a listbox.  
a New index  
b List index  
c Index  
d Sel index  
Ans b

Q:295 \_\_\_\_\_ control returns Boolean value.  
a List box  
b Option button  
c Combo box  
d Scroll bar  
Ans b

Q:296 Which is true about the name and text property of a control?  
a They are the same when the control is first created.  
The text property changes to match any changes in the name property.  
b The name property changes to match any changes in the text property.  
They are never the same unless the programmer makes it that way.  
c They are never the same unless the programmer makes it that way.  
d They are never the same unless the programmer makes it that way.  
Ans a

Q:297 Which statement about objects is true?  
a One object is used to create one class.



- b One class is used to create one object.  
c One object can create many classes.  
d One class can create many objects.  
Ans d

- Q:298 In event-driven programming an event is generated by:  
a The system.  
b User's action.  
c The program itself.  
d All of the above.  
Ans d

- Q:299 Which two controls combined to form the ComboBox control?  
a ListBox and TextBox  
b ListBox and InputBox  
c ListBox and MsgBox  
d Label and TextBox  
Ans a

- \_\_\_\_\_ automates much of work involved in creating and deploying the files needed for our program to run on another computer  
Q:300  
a Package and deployment wizard  
b File systems  
c DLL  
d None of these  
Ans a

- The \_\_\_\_\_property of a form automatically sizes the picture loaded to it.  
Q:301  
a auto size.  
b default.  
c size.  
d height.  
Ans a

- While entering a new project \_\_\_\_\_ option to be select from the dialog box.  
Q:302  
a open exe.  
b standard exe.  
c activex exe.  
d activex dll .  
Ans b



Q:303 The \_\_\_\_\_ control used to insert image to the form.

- a text box.
- b shape.
- c option.
- d picture.

Ans d

Q:304 The Line method can be used to draw \_\_\_\_\_ shape in VB.

- a rectangle.
- b circle.
- c ellipse
- d oval

Ans a

Q:305 There can be only \_\_\_\_\_MDI form in an application.

- a four.
- b two.
- c one.
- d zero.

Ans c

\_\_\_\_\_ allows access to the client server databases on a network.

- a OLEDB
- b Jet database engine
- c ODBC
- d None of these

Ans c

\_\_\_\_\_ can access data from relational and non-relational databases.

- a OLEDB
- b Jet database engine
- c ODBC
- d None of these

Ans a

\_\_\_\_\_ method of recordset object can be used to allocate memory for a new blank record.

- a Addnew
- b Add
- c Edit
- d Update

Ans a



\_\_\_\_\_ is a special tool available in VB to access databases directly.

Q:309

- a VDM
- b DAO
- c ADO
- d None of these

Ans a

\_\_\_\_\_ is the top level object in DAO hierarchy.

Q:310

- a DB Engine
- b Database
- c Data provider
- d None of these

Ans a

\_\_\_\_\_ defines and manages the current user account.

Q:311

- a Workspace
- b Filepointer
- c Group
- d None of these

Ans a

\_\_\_\_\_ is a compressed file that is well suited to distribution on either disks or the internet.

Q:312

- a .CAB
- b .CBA
- c .PCB
- d None of these

Ans a

\_\_\_\_\_ allows you to define exactly what the startmenu group contains and what icons are used.

Q:313

- a Package and deployment wizard
- b File systems
- c DLL
- d None of these

Ans a

Through \_\_\_\_\_ controls we can access information in the databases.

Q:314

- a Data bound control
- b Data control
- c Wizard
- d Report

Ans a



Q:315 The \_\_\_\_\_ function returns the length of string.

- a length.
- b len.
- c strlen.
- d lenstr.

Ans b

\_\_\_\_\_ function returns a Variant (Long) specifying the position of the first occurrence of one string within another.

- a StrIn.
- b InStr.
- c StrVar.
- d VarStr.

Ans b

The value property of the scroll bar represents its current value which may be any integer between \_\_\_\_\_ and \_\_\_\_\_ value.

- a mini, maxi.
- b large, short.
- c high, low.
- d minimum, maximum.

Ans d

Q:318 A Combobox combines the feature of \_\_\_\_\_ and \_\_\_\_\_.

- a listbox,optionbutton.
- b textbox,checkbox.
- c listbox,scrollbar.
- d textbox, listbox.

Ans d

Q:319 \_\_\_\_\_ method removes list entries from a list box at run time.

- a Item remove.
- b Delete.
- c Remove item.
- d Erase.

Ans b

Q:320 Control arrays are added at run time using \_\_\_\_\_ statement.

- a unload object.
- b load object.



c form load.  
d form unload.  
Ans b

Q:321 \_\_\_\_\_ statement removes a control from an array.  
a Unload Object.  
b Load Object.  
c Form Load.  
d Form Unload.  
Ans a

\_\_\_\_\_ is displayed as a horizontal line between items on a menu  
Q:322 bar.  
a Horizontal Bar.  
b Separator Bar.  
c Vertical Bar.  
d Split Bar.  
Ans b

Check mark can be placed on a menu item using \_\_\_\_\_  
Q:323 property.  
a checked.  
b unchecked.  
c caption.  
d text.  
Ans a

\_\_\_\_\_ type of recordset creates a dynamic set of records that  
represents a database table or the results of a query containing  
fields from one or more tables.  
Q:324  
a Table type  
b Dynaset  
c Snapshot  
d All of the above  
Ans b

A disabled menu item does not appear in the \_\_\_\_ bar.  
Q:325  
a menu.  
b standard.  
c status.  
d title.  
Ans a

Q:326 A menu can include a maximum of \_\_\_\_ levels of sub menus.





- a 3
- b 4
- c 6
- d 8
- Ans c

Form\_Mouse Down ( ) procedure is executed when any mouse button is clicked in a free area of the \_\_\_\_\_.

- a window.
- b form.
- c screen.
- d None of the above.
- Ans b

Q:328 \_\_\_\_\_ is a tool used in visual basic to draw rectangle in the form.

- a Textbox.
- b Option button.
- c Command button.
- d Shape.
- Ans d

Q:329 In visual basic \_\_\_\_\_ is the extension to represent project file.

- a .frm.
- b .vbp.
- c .cls.
- d .vb.
- Ans b

Q:330 In default \_\_\_\_\_ numbers of tools exist in toolbox.

- a 20
- b 15
- c 10
- d 8
- Ans a

Q:331 \_\_\_\_\_ method removes a dialog box from view.

- a Display.
- b Disable.
- c Hide.
- d Enabled.
- Ans c



\_\_\_\_\_ type of recordset creates a set of records that represent a single database table that we can use to add change or delete records.

Q:332

- a Table type
- b Dynaset
- c Snapshot
- d All of the above

Ans a

\_\_\_\_\_ type of recordset creates a static copy of a set of records that we can use to find data or generate reports.

Q:333

- a Table type
- b Dynaset
- c Snapshot
- d All of the above

Ans c

\_\_\_\_\_ is a pointer in to a set of records.

Q:334

- a Cursor
- b File
- c BOF
- d EOF

Ans a

\_\_\_\_\_ is the capability to wrap all aspects of functionality and user interface into a single entity?

Q:335

- a Encapsulation
- b Data hiding
- c Abstraction
- d None of these

Ans a

All the features and benefits of using objects are wrapped up what Microsoft calls \_\_\_\_\_

Q:336

- a COM
- b CAM
- c CAP
- d None of these

Ans a

COM stands for \_\_\_\_\_

Q:337

- a Component Object Model
- b Class Object Model
- c Common Object Model
- d None of these



Ans a

Q:338 The main objective of the COM philosophy is \_\_\_\_\_

- a Reliability
- b Reusability
- c Abstraction
- d None of these

Ans b

Q:339 \_\_\_\_\_ procedures have return values.

- a Function
- b General
- c Sub
- d Event

Ans a

Q:340 \_\_\_\_\_ event occurs when a form loaded into the memory

- a Load
- b Initialize
- c Activate
- d None of the above

Ans a

Q:341 \_\_\_\_\_ event occurs when the form is set to nothing.

- a Terminate
- b Initialize
- c Activate
- d All of the above

Ans a

Q:342 In VB, arguments are passed by default by \_\_\_\_\_

- a Reference
- b Value
- c Object
- d None of these

Ans a

Q:343 VDM is available from \_\_\_\_\_ menu

- a Project
- b Tools
- c AddIns
- d None of these

Ans c



\_\_\_\_\_ method is used to retrieve a particular record on the  
Q:344 basis of a criteria  
a Move  
b Find  
c Add  
d None of these  
Ans b

When \_\_\_\_\_ is true then the file pointer will be above the first  
Q:345 record.  
a EOF  
b BOF  
c File  
d None of these  
Ans b

Which is not a valid Exit statement?  
Q:346  
a Exit Do  
b Exit For  
c Exit Sub  
d Exit Form  
Ans d

Which function should be used to validate that input is not a string  
Q:347 before performing arithmetic operations?  
a IsArithmetic  
b IsNotString  
c IsNumeric  
d IsString  
Ans c

What is the most number of states a CheckBox can have?  
Q:348  
a 0  
b 1  
c 2  
d 3  
Ans d

The scope of a variable refers to:  
Q:349  
a The length of the variable.  
b The name of the variable.  
c The accessibility of the variable.  
d The datatype of the variable.  
Ans c



Q:350 Variables are named storage locations in memory, the value of which does not change during program\_\_\_\_\_.  
a design.  
b execution.  
c debug.  
d All of the above.  
Ans b

Variables of different data types when combined as a single variable to hold several related information is called as \_\_\_\_\_  
Q:351 data types.  
a numeric.  
b user defined.  
c string.  
d byte.  
Ans b

Q:352 \_\_\_\_\_ function translates a numeric value to a variable.  
a Message.  
b Build In.  
c Val.  
d Mod.  
Ans c

Q:353 \_\_\_\_\_box provides a set of choices to the user.  
a List.  
b Command.  
c Combo.  
d Text.  
Ans a

Q:354 All the controls in an array will have the same \_\_\_\_\_.  
a Value.  
b properties.  
c address.  
d location  
Ans b

Q:355 The \_\_\_\_\_property in Visual basic is common for many a tools.  
a location.  
b place.  
c window status.  
d name.  
Ans d



Q:356 Option button can be grouped in a \_\_\_\_\_ control.

- a label.
- b text box.
- c frame.
- d check box.

Ans c

Q:357 A \_\_\_\_\_ bar appears in the top of the screen.

- a title.
- b menu.
- c tool.
- d debug.

Ans a

Q:358 In the statement, Dim Days(7) as String, what part of the array does the number 7 refer to?

- a Array name
- b Datatype
- c Lowerbound
- d Upperbound

Ans d

Q:359 Which menu object property places a check mark in the display of the menu text?

- a Check
- b Checked
- c CheckMark
- d CheckOn

Ans b

Q:360 Which symbol creates an access key in the text of a menu item?

- a @
- b &
- c \$
- d #

Ans b

Q:361 Which is not a standard dialog box?

- a ColorDialog
- b FontDialog
- c OpenFileDialog
- d ZoomDialog

Ans d



Q:362 A cell is an intersection of \_\_\_\_\_ and \_\_\_\_\_.

- a row, rows
- b row, column
- c column, column
- d row, line

Ans b

Q:363 \_\_\_\_\_ property is set to change the height of a cell.

- a Row
- b Column
- c Column height
- d Row height

Ans d

\_\_\_\_\_ kinds of rows and columns are created in the Ms Flex  
Q:364 Grid control.

- a Two
- b One
- c Three
- d Four

Ans a

\_\_\_\_\_ is a process involving a minimum of two independent  
Q:365 entries one being the client and the other is the server.

- a Client/Server Architecture
- b Client Architecture
- c Server Architecture
- d Network

Ans a

Q:366 The print command in Visual basic programming is used to \_\_\_\_.

- a give output
- b print the form content
- c display the content in form
- d find error

Ans c

\_\_\_\_\_ of the query designer interface displays the input sources  
Q:367 for querying.

- a Select
- b Diagram
- c Image
- d Result



Ans        b

Q:368        A \_\_\_\_\_ object represents a connection to a remote database used as a data source for the associated commands.

- a        connection
- b        RDO
- c        ADO
- d        fixed

Ans        a

Q:369        \_\_\_\_\_ control displays data that is calculated at runtime, using built-in functions, as the report is generated.

- a        Caption
- b        Text
- c        Connection
- d        Function

Ans        d

Q:370        \_\_\_\_\_ property is used to change the label value of command button.

- a        value.
- b        caption.
- c        text.
- d        name.

Ans        b

Q:371        Where is a single element of data stored?

- a        Field
- b        Record
- c        Table
- d        Both (a) and (b).

Ans        a

Q:372        Where is a collection of related data elements stored?

- a        Field
- b        Record
- c        Table
- d        Both (a) and (b).

Ans        b

Q:373        Which statement about objects is true?

- a        One object is used to create one class.
- b        One class is used to create one object.
- c        One object can create many classes.





d One class can create many objects.

Ans d

Q:374 Which is not a property of the Common control class?

- a Show
- b BackColor
- c Font
- d ForeColor

Ans a

Q:375 The important property of a scroll bar is \_\_\_\_\_

- a Value
- b Scroll
- c Change
- d None of these

Ans a

\_\_\_\_\_ method is used to forcibly set the CPU focus to a particular control.

- a Setfocus
- b Gotfocus
- c Lostfocus
- d None of the above

Ans a

\_\_\_\_\_ event occurs when the user presses a key from the keyboard.

- a Keydown
- b Keypress
- c Keyup
- d All of the above

Ans a

The button parameter used to identify the left mouse button is \_\_\_\_\_.

- a 1
- b 2
- c 3
- d 4

Ans a

The button parameter used to identify the right mouse button is \_\_\_\_\_.

- a 1
- b 2



c 3  
d 4  
Ans b

Q:380 \_\_\_\_\_ event occurs when the content of a control changes.  
a Load  
b Change  
c Got focus  
d None of these  
Ans b

Q:381 The default event of a text box is \_\_\_\_\_  
a Load  
b Change  
c Click  
d Gotfocus  
Ans b

\_\_\_\_\_ variables are not reinitialized each time Visual basic invokes a procedure and thus retains or preserves value even when a procedure ends.  
Q:382  
a Static.  
b Dynamic.  
c Virtual.  
d Currency.  
Ans a

Q:383 Code window consists of a \_\_\_\_\_ box and procedure list box.  
a object.  
b event.  
c tool.  
d message.  
Ans a

The \_\_\_\_\_ statement checks in the module for usage of any undeclared variables and reports an error to the user.  
Q:384  
a looping.  
b iteration.  
c dim.  
d external.  
Ans c



Dynamic arrays can be declared when the user may not know the \_\_\_\_\_ of the array at design time.

Q:385

- a exact column.
- b exact variable.
- c exact value.
- d exact size.

Ans d

\_\_\_\_\_ keyword is used to preserve the previously stored values of a dynamic array.

Q:386

- a Preserve
- b Redim
- c Dim
- d Static

Ans a

In event-driven programming an event is generated by:

Q:387

- a The system.
- b A user's action.
- c The program itself.
- d All of the above

Ans d

The important property of a timer control is \_\_\_\_\_

Q:388

- a Interval
- b Name
- c Timer
- d Time

Ans a

The only object that is not a collection and is not contained within another container in the DAO is \_\_\_\_\_

Q:389

- a Table def
- b DB Engine
- c Group
- d Workspace

Ans b

\_\_\_\_\_ control is used to represent the items in a hierarchical manner.

Q:390

- a Tree view
- b Grid view
- c Progress bar
- d None of these

Ans a



Inorder to add a new node into a tree view control we must use  
Q:391 \_\_\_\_\_ method.

- a Add
- b Additem
- c Addnode
- d None of these

Ans a

\_\_\_\_\_ represents the immediate parent node for the new  
Q:392 node in a tree view control.

- a Key
- b Relationship
- c Relative
- d Image

Ans c

\_\_\_\_\_ control specifies the progress of an operation based on  
Q:393 some time limits.

- a Status bar
- b Progress bar
- c Grid
- d None of these

Ans b

\_\_\_\_\_ control specifies current status of the form.  
Q:394

- a Status bar
- b Progress bar
- c Grid
- d None of these

Ans a

By using \_\_\_\_\_ property of a progress bar, we can display the  
Q:395 progress of an operation.

- a Time
- b Interval
- c Value
- d Progress

Ans c

\_\_\_\_\_ control displays current directory with any sub  
Q:396 directories and allows the user to change directly.

- a Directory list box
- b Drive list box
- c File list box
- d All of the above



Ans a

\_\_\_\_\_ control is used to execute a set of programs automatically at regular intervals without the interaction of user.

- a Scroll bar
- b Progress bar
- c Timer
- d File controls

Ans c

Q:398 \_\_\_\_\_ can act as a container for other controls

- a Picture box
- b Image box
- c List box
- d Combo box

Ans a

By using \_\_\_\_\_ property of Drive list box we can access the selected drive.

- a Pattern
- b Path
- c Drive
- d File

Ans c

\_\_\_\_\_ event occurs while the scroll box is moved by dragging the mouse.

- a Change
- b Scroll
- c Mouse move
- d None of these

Ans b

To insert a picture into a picturebox we can use \_\_\_\_\_ method.

- a Load
- b Load image
- c Load picture
- d None of these

Ans c

DHTML is based on the \_\_\_\_\_, which is the hierarchy of web page elements.

- a object document model
- b document object model



c model document object  
d document model object  
Ans b

\_\_\_\_\_ defines a line in the code window where VB suspends execution of application.  
Q:403  
a ErrorPoint  
b BreakPoint  
c CompilePoint  
d RunPoint  
Ans b

\_\_\_\_\_ returns a variant string containing a copy of a specified string without leading spaces and trailing spaces.  
Q:404  
a Ltrim( )  
b Rtrim( )  
c Midtrim( )  
d Trim ( )  
Ans d

\_\_\_\_\_ returns a date for a specified year, month and day.  
Q:405  
a DateSerial( )  
b DateDiff( )  
c DateInst( )  
d DateOust( )  
Ans a

\_\_\_\_\_ returns an integer containing the specified part of a given date.  
Q:406  
a DateDiff( )  
b DatePart( )  
c DateDiff( )  
d DateInst( )  
Ans b

Variables are used for storing values \_\_\_\_\_.  
Q:407  
a temporarily  
b permanently  
c constantly  
d variably  
Ans a

VB encounters a new variable it assigns the default variable type and value is called \_\_\_\_\_ declaration.  
Q:408  
a explicit  
b implicit



c external  
d internal  
Ans b

\_\_\_\_\_ statement removes the form from the display and releases its memory.  
Q:409  
a Unload  
b Load  
c Hide  
d Unhide  
Ans a

\_\_\_\_\_ is the property of a flexgrid to access the index of current row.  
Q:410  
a Index  
b New index  
c Row  
d Rowsel  
Ans c

\_\_\_\_\_ is used to display the data in a tabular format on the form  
Q:411  
a List  
b Table  
c Flexgrid  
d All of the above  
Ans c

One of the important method of a flexgrid control is \_\_\_\_\_  
Q:412  
a AddItem  
b Add  
c Remove  
d All of the above  
Ans a

\_\_\_\_\_ is the temporary buffer area which is used to store data temporarily.  
Q:413  
a Rich text  
b Text  
c Clipboard  
d Cursor  
Ans c

\_\_\_\_\_ method is used to retrieve the stored text from the clipboard.  
Q:414



- a Settext
- b Gettext
- c Input
- d Addtext
- Ans b

Q:415 The method which is used to clear a form control is \_\_\_\_\_

- a Clr
- b Clear
- c Cls
- d Null
- Ans c

Visual Basic is a tool that allows you to develop application in \_\_\_\_\_

- a Real time
- b Graphical User Interface
- c Character User Interface
- d None of these
- Ans b

Q:417 IDE stands for \_\_\_\_\_.

- a Internet Development Environment
- b Integrated Dual Environment
- c Integrated Development Environment
- d Integrated Desktop Environment
- Ans c

Which windows displays a list of all forms and modules making up your application?

- a Project window
- b Properties window
- c Form layout window
- d All of the above
- Ans a

Q:419 Properties can be viewed in two ways

- a Alphabetic and Categorized
- b Alphabetic and Numeric
- c Numeric and Alphanumeric
- d None of these
- Ans a

Q:420 Which of the following windows is the central to the development of Visual Basic applications?





- a Project window
- b Form window
- c Properties window
- d All of the above

Ans b

Q:421 Which of the following provides quick access to commonly used commands in the programming environment?

- a Toolbox
- b Object browser
- c Toolbar
- d None of these

Ans c

Q:422 In \_\_\_\_\_ window we can write code

- a Immediate window
- b Locals window
- c Code editor window
- d None of these

Ans c

Q:423 A Boolean datatype can store \_\_\_\_\_ bytes.

- a 2 byte
- b 4 byte
- c 1 byte
- d 8 byte

Ans a

Q:424 An object datatype can store \_\_\_\_\_ bytes

- a 1 byte
- b 2 byte
- c 4 byte
- d 8 byte

Ans c

Q:425 In \_\_\_\_\_ there is no need to declare a variable before using it.

- a Implicit declaration
- b Explicit declaration
- c Option Explicit
- d General Declarations

Ans a

Q:426 In \_\_\_\_\_ scope, variables are available only to the module in which they are declared.

- a Private



b        Public  
c        Module  
d        Static  
Ans     a

Q:427        \_\_\_\_\_ is the extension of a class module.  
a        .cls  
b        .cla  
c        .class  
d        None of these  
Ans     a

Q:428        \_\_\_\_\_ is the extension of the standard module.  
a        .bas  
b        .bsi  
c        .std  
d        .stn  
Ans     a

Q:429        One or more option button controls can be selected from \_\_\_\_\_ choices.  
a        multiple.  
b        single.  
c        dual.  
d        parallel.  
Ans     a

Q:430        \_\_\_\_\_ bar contains a set of tools to provide controls in the Form.  
a        Status.  
b        Tool  
c        Menu.  
d        Progress.  
Ans     c

Q:431        Debug window is the same as \_\_\_\_\_ window.  
a        procedure.  
b        object.  
c        form.  
d        code.  
Ans     d

Q:432        \_\_\_\_\_ is a data type that can be used to declare a text of maximum 10 million characters.  
a        String.



b        Numeric.  
c        ULong.  
d        Date.  
Ans     a

Q:433    A module-level is available to all the \_\_\_\_\_ in the module.  
a        data.  
b        procedures.  
c        event.  
d        task.  
Ans     b

Q:434    A \_\_\_\_\_ array is a group of controls that share the same name and type.  
a        control  
b        fixed  
c        static  
d        local  
Ans     a

Q:435    The \_\_\_\_\_ is a commonly used control, which enables the user to select a value by positioning it at the desired location.  
a        verticalbar  
b        horizontalbar  
c        scrollbar  
d        menubar  
Ans     c

Q:436    Tooltips can be added to a button by setting a text to the \_\_\_\_\_ property of the command button.  
a        tooltip  
b        menutip  
c        listtip  
d        nametip  
Ans     a

Q:437    The text color of a command button can be set using the \_\_\_\_\_ property.  
a        backcolor  
b        forecolor  
c        fillcolor  
d        listcolor  
Ans     b



- Q:438 A \_\_\_\_\_ is a set of menu items on a menu that share the same name and event procedure.
- a menu control array
  - b control array
  - c list array
  - d static array
- Ans a
- 
- Q:439 A \_\_\_\_\_ menu is a floating menu that is displayed over a form independent of the menu bar.
- a pop-down
  - b pop-right
  - c pop-up
  - d pop-left
- Ans c
- 
- Q:440 Which class is used for converting the data types?
- a System.Convert
  - b System.Transform
  - c System.Change
  - d None of these
- Ans a