

AJAX - PHP

- AJAX stands for Asynchronous JavaScript and XML. AJAX is a new technique for creating better, faster, and more interactive web applications with the help of XML, HTML, CSS, and JavaScript.
- Conventional web applications transmit information to and from the server using synchronous requests. It means you fill out a form, hit submit, and get directed to a new page with new information from the server.
- With AJAX, when submit is pressed, JavaScript will make a request to the server, interpret the results and update the current screen. In the purest sense, the user would never know that anything was even transmitted to the server.

The following example will demonstrate how a web page can communicate with a web server while a user types characters in an input field:

Start typing a name in the input field below:

First name:

Suggestions:

Explanation

In the example above, when a user types a character in the input field, a function called "showing()" is executed.

The onkeyup event triggers the function.

Here is the HTML code:

```
<html>
<head>
<script>
function showHint(str) {
  if (str.length == 0) {
    document.getElementById("txtHint").innerHTML = "";
    return;
  } else {
    var xmlhttp = new XMLHttpRequest();
    xmlhttp.onreadystatechange = function() {
      if (this.readyState == 4 && this.status == 200) {
        document.getElementById("txtHint").innerHTML = this.responseText;
      }
    };
    xmlhttp.open("GET", "gethint.php?q=" + str, true);
    xmlhttp.send();
  }
}
</script>
</head>
<body>

<p><b>Start typing a name in the input field below:</b></p>
<form action="">
  <label for="fname">First name:</label>
  <input type="text" id="fname" name="fname" onkeyup="showHint(this.value)">
</form>
<p>Suggestions: <span id="txtHint"></span></p>
</body>
</html>
```

Code explanation:

First, check if the input field is empty (`str.length == 0`). If it is, clear the content of the `txtHint` placeholder and exit the function.

Do the following, if the input field is not empty:

- Create an `XMLHttpRequest` object
- Create the function to be executed when the server response is ready
- Send the request off to a PHP file (`gethint.php`) on the server
- Notice that the `q` parameter is added to the url (`gethint.php?q="+str`)
- And the `str` variable holds the content of the input field

The PHP File - "gethint.php."

The PHP file checks an array of names, and returns the corresponding name(s) to the browser:

```

<?php
// Array with names
$a[] = "Anna";
$a[] = "Brittany";
$a[] = "Cinderella";
$a[] = "Diana";
$a[] = "Eva";
$a[] = "Fiona";
$a[] = "Gunda";
$a[] = "Hege";
$a[] = "Inga";
$a[] = "Johanna";
$a[] = "Kitty";
$a[] = "Linda";
$a[] = "Nina";
$a[] = "Ophelia";
$a[] = "Petunia";
$a[] = "Amanda";
$a[] = "Raquel";
$a[] = "Cindy";
$a[] = "Doris";
$a[] = "Eve";
$a[] = "Evita";
$a[] = "Sunniva";
$a[] = "Tove";
$a[] = "Unni";
$a[] = "Violet";
$a[] = "Liza";
$a[] = "Elizabeth";
$a[] = "Ellen";
$a[] = "Wenche";
$a[] = "Vicky";

// fetch q parameter from URL
$q = $_REQUEST["q"];

$hint = "";

// lookup all hints from array if $q is different from ""
if ($q != "") {
    $q = strtolower($q);
    $len=strlen($q);
    foreach($a as $name) {
        if (stristr($q, substr($name, 0, $len))) {
            if ($hint == "") {
                $hint = $name;
            } else {
                $hint .= ", $name";
            }
        }
    }
}

// It results in "no suggestion" if no hint was found or output correct values
echo $hint == "" ? "no suggestion" : $hint;
?>

```

Output:

Start typing a name in the input field below:

First name:

Suggestions: Anna, Amanda

← Prev

Next →

 For Videos Join Our Youtube Channel: [Join Now](#)

Feedback

- Send your Feedback to [\[email protected\]](#)

Help Others, Please Share



Learn Latest Tutorials

 Splunk tutorial Splunk	 SPSS tutorial SPSS	 Swagger tutorial Swagger	 T-SQL tutorial Transact-SQL	 Tumblr tutorial Tumblr
 React tutorial ReactJS	 Regex tutorial Regex	 Reinforcement learning tutorial Reinforcement Learning	 R Programming tutorial R Programming	 RxJS tutorial RxJS
 React Native tutorial React Native	 Python Design Patterns Python Design Patterns	 Python Pillow tutorial Python Pillow	 Python Turtle tutorial Python Turtle	 Keras tutorial Keras

Preparation