

SIMATS ENGINEERING

ASSESSMENT TOOL 2

COURSE NAME: COMPUTER NETWORKS
COURSE CODE: CSA07

COURSE OUTCOME COVERED

CO2: Configure IP addressing schemes, subnetting, and basic routing techniques using simulation tool, for efficient network design and topology. (BL3)

Assessment Tool Weightage: 30%

QUESTIONS: 5

Total Marks:50

Annexure A

Scenario-Based

Code of Conduct:

I C.Manoj Kumar(192472008)(Name / Reg No) certify that this submission is my original work and that I have adhered to the guidelines specified for this assessment.

I understand that any violation of academic integrity rules will result in disciplinary action.

Signature of the student:

Scenario-Based

1. A newly established Smart Campus is deploying a secure network infrastructure for its academic and administrative departments. The network administrator has been allocated the IP address block 192.168.100.0/24. Based on the expected number of devices, the following subnet masks have already been assigned:

School of Computing → /25

School of Electronics → /26

School of Mechanical Engineering → /27

As the network engineer, design the subnet allocation by performing the following tasks:

1. Determine the network address and broadcast address for each department.
2. Identify the valid host IP address range for each subnet.
3. Calculate the number of usable host addresses available in each subnet.
4. Determine the remaining unused IP address range within the given network block.

2. A multinational software company is expanding its headquarters and has been assigned the private IP block **10.10.0.0/16**. Different departments require different subnet sizes based on the number of employees. The network administrator has allocated the following subnet masks:

Software Development → /24

Quality Assurance → /25

Human Resources → /26

Executive Management → /27

As the network administrator, perform the following tasks:

1. Determine the **network address** and **broadcast address** for each department.
2. Identify the **valid range of host IP addresses**.
3. Calculate the **number of usable hosts** in each subnet.
4. Identify the **unused IP address range** remaining within the allocated IP block.

3. A smart hospital is migrating its network infrastructure from IPv4 to IPv6 to support thousands of connected medical devices and IoT sensors. The hospital has been assigned the IPv6 network:

2001:0db8:abcd:0000:0000:0000:0000/64

As the network engineer responsible for the migration, perform the following:

1. Convert the given IPv6 address into its **compressed notation**.
2. Expand the compressed address back into its **full hexadecimal representation**.
3. Identify the **network prefix** using the /64 prefix length.
4. Calculate the **total number of host addresses** supported within the subnet.
5. the total number of possible host addresses available within this network.

4. An Internet Service Provider (ISP) connects multiple customer networks through a core router. The router maintains the following routing table entries:

192.168.1.0/24

192.168.2.0/24

192.168.3.0/24

A packet arrives at the router with the destination IP address:

192.168.2.45

As the routing engineer, determine:

1. The **destination subnet** to which the packet belongs.
2. The **matching routing table entry**.
3. The **next-hop network/interface** used to forward the packet.

4. The **default route** that should be used if the destination does not match any routing table entry.

5. A company establishes two office departments connected through a Layer-3 router. The allocated subnet information is as follows:

Administration LAN → **192.168.10.0/26**

Finance LAN → **192.168.10.64/26**

The router interfaces are configured with:

Administration Gateway → **192.168.10.1**

Finance Gateway → **192.168.10.65**

As the network administrator, perform the following tasks:

1. Determine the **network address** and **broadcast address** for each LAN.
2. Identify the **valid host IP address range**.
3. Suggest suitable IP addresses for **three computers** in each LAN.
4. Identify the **default gateway** that hosts in each LAN should use for communication.

RUBRICS FOR CALCULATION

Scenario Based Assessment					
Criteria	Weightage (%)	Level 4 (Exemplary)	Level 3 (Proficient)	Level 2 (Developing)	Level 1 (Beginning)
Understanding of Scenario	20%	Demonstrates clear and complete understanding of the scenario and context	Shows good understanding with minor gaps	Partial understanding; misses key aspects	Misinterprets or fails to understand the scenario
Identification of Key Issues	20%	Accurately identifies all relevant issues and factors involved	Identifies most key issues with minor omissions	Identifies limited issues; some irrelevant points	Unable to identify key issues
Application of Concepts	25%	Applies appropriate concepts effectively to address the scenario	Applies concepts with minor errors	Limited or partially correct application	Unable to apply relevant concepts
Decision Making	20%	Makes well-reasoned, logical decisions with strong rationale	Makes reasonable decisions with some justification	Makes weak decisions with limited justification	No clear decisions made or rationale provided
Clarity of Response	15%	Response is clear, structured, and logically presented	Generally clear with minor issues	Somewhat unclear or poorly structured	Disorganized and difficult to understand

Question 1

Given Network: 192.168.100.0/24

Department	Prefix
------------	--------

School of Computing	/25
---------------------	-----

School of Electronics	/26
-----------------------	-----

School of Mechanical Engineering	/27
----------------------------------	-----

School of Computing (/25)

- Network Address: **192.168.100.0**
- Broadcast Address: **192.168.100.127**
- Valid Host Range: **192.168.100.1 – 192.168.100.126**
- Usable Hosts: **126**

School of Electronics (/26)

- Network Address: **192.168.100.128**
- Broadcast Address: **192.168.100.191**
- Valid Host Range: **192.168.100.129 – 192.168.100.190**
- Usable Hosts: **62**

School of Mechanical Engineering (/27)

- Network Address: **192.168.100.192**
- Broadcast Address: **192.168.100.223**
- Valid Host Range: **192.168.100.193 – 192.168.100.222**
- Usable Hosts: **30**

Remaining Unused IP Range

192.168.100.224 – 192.168.100.255

Question 2

Given Network: 10.10.0.0/16

Department	Prefix
------------	--------

Software Development	/24
----------------------	-----

Quality Assurance	/25
-------------------	-----

Human Resources	/26
-----------------	-----

Executive Management	/27
----------------------	-----

Software Development (/24)

- Network Address: **10.10.0.0**
- Broadcast Address: **10.10.0.255**
- Host Range: **10.10.0.1 – 10.10.0.254**
- Usable Hosts: **254**

Quality Assurance (/25)

- Network Address: **10.10.1.0**
- Broadcast Address: **10.10.1.127**
- Host Range: **10.10.1.1 – 10.10.1.126**
- Usable Hosts: **126**

Human Resources (/26)

- Network Address: **10.10.1.128**
- Broadcast Address: **10.10.1.191**
- Host Range: **10.10.1.129 – 10.10.1.190**
- Usable Hosts: **62**

Executive Management (/27)

- Network Address: **10.10.1.192**
- Broadcast Address: **10.10.1.223**
- Host Range: **10.10.1.193 – 10.10.1.222**
- Usable Hosts: **30**

Remaining Unused IP Range

10.10.1.224 – 10.10.255.255

Question 3

Given IPv6 Address

2001:0db8:abcd:0000:0000:0000:0000:0000/64

1. Compressed IPv6 Address

2001:db8:abcd::/64

2. Expanded IPv6 Address

2001:0db8:abcd:0000:0000:0000:0000:0000/64

3. Network Prefix

2001:db8:abcd:0000::/64

The first **64 bits** represent the network prefix.

4. Total Number of Host Addresses

Host bits = **128 – 64 = 64**

Number of Hosts

= **2⁶⁴**

= **18,446,744,073,709,551,616**

5. Total Possible Host Addresses

18,446,744,073,709,551,616 addresses

Question 4

Routing Table

- **192.168.1.0/24**
- **192.168.2.0/24**
- **192.168.3.0/24**

Destination IP

192.168.2.45

1. Destination Subnet

192.168.2.0/24

2. Matching Routing Table Entry

192.168.2.0/24

3. Next-Hop Network / Interface

The packet is forwarded through the router interface connected to the

192.168.2.0/24 network

4. Default Route

If no matching route exists,

0.0.0.0/0 (Default Route)

The packet is forwarded to the default gateway.

Question 5

Administration LAN

Network: **192.168.10.0/26**

Gateway: **192.168.10.1**

Finance LAN

Network: **192.168.10.64/26**

Gateway: **192.168.10.65**

Administration LAN

Network Address

192.168.10.0

Broadcast Address

192.168.10.63

Valid Host Range

192.168.10.1 – 192.168.10.62

Suggested IP Addresses

PC1 → **192.168.10.2**

PC2 → **192.168.10.3**

PC3 → **192.168.10.4**

Default Gateway

192.168.10.1

Finance LAN

Network Address

192.168.10.64

Broadcast Address

192.168.10.127

Valid Host Range

192.168.10.65 – 192.168.10.126

Suggested IP Addresses

PC1 → **192.168.10.66**

PC2 → **192.168.10.67**

PC3 → **192.168.10.68**

Default Gateway

192.168.10.65