

CONSTRUCTION NOTES:

1. ALL CONSTRUCTION AND MATERIALS USED SHALL BE IN CONFORMANCE WITH THE REQUIREMENTS OF ALL APPLICABLE CODES, STANDARDS AND REGULATIONS.
2. REFER TO STRUCTURAL, MECHANICAL, ELECTRICAL AND BUILDING SERVICES FOR COORDINATION OF WORK. THE WORK OF ALL DISCIPLINES SHALL BE CAREFULLY COORDINATED WITH THE OVERALL AESTHETIC APPEARANCE OF THE BUILDING. NOTES APPEAR ON VARIOUS SHEETS FOR SYSTEMS AND MATERIALS. DRAWINGS ARE TO BE APPLIED TO OTHER RELATED DRAWINGS AND DETAILS.
3. WHERE SPECIFIC DIMENSIONS, DETAILS, DESIGN INTENT CANNOT BE DETERMINED CONSULT WITH THE SUPERINTENDING OFFICER (S.O.) FOR CLARIFICATIONS AND DIRECTIONS BEFORE PROCEEDING WITH ANY WORKS.
4. ANY DISCREPANCIES EXISTING BETWEEN THE ARCHITECTURAL DRAWINGS AND DRAWINGS OF THE OTHER DISCIPLINES SHALL BE BROUGHT TO THE IMMEDIATE ATTENTION OF THE S.O. FOR CLARIFICATION BEFORE PROCEEDING WITH ANY WORK.
5. UNLESS NOTED OTHERWISE, ALL DIMENSIONS ARE GIVEN IN MILLIMETERS.
6. DIMENSIONS SHALL GOVERN. DO NOT SCALE DRAWINGS.
7. DIMENSIONS SHALL BE VERIFIED ON SITE BEFORE PROCEEDING WITH THE WORKS.
8. EXTERIOR WALLS ARE DIMENSIONED TO THE EXTERIOR FINISHED FACE OF THE WALL, UNLESS NOTED OTHERWISE.
9. UNLESS NOTED OTHERWISE, WALLS AND PARTITIONS ENCLOSING THE CORE OR OTHER SHAFTS (I.E STAIRS, LIFT SHAFTS, AND MECHANICAL SHAFTS WALL) ARE DIMENSIONED TO THE FACE OF THE WALL.
10. DOOR OPENINGS ARE GENERALLY DIMENSIONED TO CENTERLINE OF OPENING. DOOR OPENINGS THAT ARE NOT DIMENSIONALLY LOCATED SHOULD BE CENTERED BETWEEN WALLS OR POSITIONED WITH ONE JAMB AGAINST AN ADJACENT WALL OR COLUMN AS SHOWN ON THE PLANS AND/OR DETERMINED FROM THE DETAILS WITH SUFFICIENT ALLOWANCE FOR ARCHITRAVES OR OTHER TRIM ELEMENTS TO BE INSTALLED ONTO DOOR FRAMES.
11. UNLESS NOTED OTHERWISE WHERE AN ARCHITECTURAL FLOOR FINISH IS TO BE PROVIDED THE FLOOR ELEVATIONS ARE TO TOP OF FINISHED FLOOR. WHERE GRADIENT FALLS ARE REQUIRED FOR DRAINAGE, THE CONTRACTOR SHALL SUBMIT SHOP DRAWINGS TO THE S.O. FOR APPROVAL PRIOR TO CONSTRUCTION.
12. UNLESS NOTED OTHERWISE ROOF ELEVATIONS ARE TO TOP OF STRUCTURAL SLAB. WHERE GRADIENT FALLS ARE REQUIRED FOR DRAINAGE, THE CONTRACTOR SHALL SUBMIT SHOP DRAWINGS TO THE S.O. FOR APPROVAL PRIOR TO CONSTRUCTION.
13. UNLESS NOTED OTHERWISE ALL FASTENERS AND FASTENING DEVICES ARE TO BE CONCEALED. ALL SUCH DEVICES SHALL BE PROPERLY WASHERED OR OTHERWISE INSULATED TO PREVENT ELECTROLYTIC ACTION BETWEEN THE TWO DISIMILAR METALS. THE CONTRACTOR SHALL BE RESPONSIBLE FOR STRUCTURAL ADEQUACY OF ALL SUCH FASTENING/ FIXING DEVICES.
14. WHERE SERVICES ELEMENTS, EG, PIPES, DUCTS, CONDUITS, CABLE TRAYS, ETC. PENETRATE FIRE RATED FLOOR SLABS AND WALLS, THE PENETRATIONS ARE TO BE REINSTATED / INFILLED WITH SPECIFIED AND APPROVED MATERIALS / METHODS THAT PRESERVE THE INTEGRITY OF THE FIRE RATED ELEMENT BEING PENETRATED.
15. JOINTS OF ANY ELEMENT OF CONSTRUCTION WHICH ARE REQUIRED TO HAVE A FIRE RESISTANCE RATING SHALL BE TIGHT AND SHALL PREVENT THE PASSAGE OF SMOKE, FLAME AND/OR HEAT.
16. WHERE FIRE RATED WALLS ARE NOTED ON THE DRAWINGS, THE FIRE RATING SHALL APPLY TO THE ENTIRE PERIMETER ENCLOSURE OF THE ROOM/ SPACE AND FOR THE FULL LENGTH AND HEIGHT OF AREAS BEING SEPARATED. WHERE TWO SPACES REQUIRING FIRE RATING ARE ADJACENT, THE HIGHER RATING SHALL GOVERN.
17. DISSIMILAR METALS SHALL BE EFFECTIVELY ISOLATED FROM EACH OTHER TO PREVENT GALVANIC ACTION.
18. ALL PENETRATIONS THROUGH FLASHING SHALL BE SEALED WITH SEALANT.
19. THE FLAME SPREAD RATING FOR ALL MATERIALS SHALL CONFORM TO ALL APPLICABLE REGULATIONS.
20. PROVIDE ACCESS PANELS AS REQUIRED BY STATUTORY REQUIREMENTS AND AS REQUIRED FOR MECHANICAL, ELECTRIAL, HYDRAULIC, FIRE PROTECTION EQUIPMENT, SERVICING, MATINTENANCE AND INSPECTION. ALL ACCESS PANELS SHALL BE UNOBSTRUSIVE AND SHALL BE CONCEALED WHERE POSSIBLE. U.N.O. THE CONTRACTOR SHALL SUBMIT SHOP DRAWINGS FOR APPROVAL BEFORE THE CONSTRUCTION PROCESS.
21. A FINISH INDICATED FOR A WALL SHALL MEAN THE ENTIRE LENGTH OF WALL SHALL BE FINISHED AS INDICATED UNLESS NOTED OTHERWISE.
22. THE FOLLOWING SHALL NOT BE INSTALLED ON THE WORKS - MATERIALS WHICH ARE GENERALLY COMPRISED OF MINERAL FIBRES, EITHER MAN-MADE OR NATURALLY OCCURING, WHICH HAVE A DIAMETER OF 3 MICRONS OR LESS AND A LENGTH OF 200 MICRONS OR LESS OR WHICH CONTAIN ANY FIBRES NOT SEALED, ENCAPSULATED OR OTHERWISE STABILISED TO ENSURE THAT FIBRE MIGRATION IS PREVENTED.
23. UNLESS OTHERWISE SPECIFIED, ALL STRUCTURAL STEEL WORK SHALL BE PRIMED WITH ONE COAT OF EPOXY ZINC RICH PRIMER AND ONE COAT OF HIGH BUILD EPOXY MICACEOUS IRON OXIDE & 2 FINISHING COATS OF APPROVED POLYURETHANE PAINT.
24. CONTRACTOR TO COORDINATE AND COMPLY WITH AUTHORITIES REQUIREMENT.
25. THIS DRAWING SHALL BE READ IN CONJUNCTION WITH TENDER GENERAL REQUIREMENTS AND SPECIFICATIONS.
26. ALL DIMENSIONS TO STAIR TREAD TO FINISHED FACE OF TREAD.
27. REFER TO FINISHES SCHEDULE FOR FINISHES TO ROOMS.
28. REFERENCE TO SPECIALIST CONSULTANT SPECIFICATIONS, DRAWINGS / DETAILS, REQUIREMENTS READ AS A WHOLE.
29. OFFICE SYSTEM FURNITURE SUPPLY AND INSTALLATION WORKS SHALL BE BY A SEPARATE SPECIALIST CONTRACTOR.
30. CONTRACTOR TO SUBMIT ALL HANDRAILS/ RAILINGS/ SAFETY BARRIER/ FACADE TO BCA FOR APPROVAL.

NOTES:

1. ALL DIMENSIONS ARE IN MILLIMETRES UNLESS OTHERWISE STATED.
2. ALL LEVELS SHOWN ARE IN METRES.
3. HORIZONTAL DATUM PLOTTED IN SVY21 GRIDS.
4. VERTICAL DATUM ARE BASED ON THE SINGAPORE HEIGHT DATUM (SHD) OF 0.000m .
5. ON NO ACCOUNT MAY THIS DRAWING BE SCALED FROM.

FIRE LEGEND

- o FIRE EXTINGUISHER

 EXIT SIGN

 DIRECTIONAL EXIT SIGN

TENDER

T3	25/11/22	ISSUED FOR C4B TENDER (2ND STAGE)	PK	GOT
T2	22/07/22	ISSUED FOR ADDENDUM 2	PK	GOT
T1	20/05/22	ISSUED FOR TENDER C4B	PK	GOT
REV	DATE	DESCRIPTION	REVIEWED	AUTHORISED

CLIENT:



SINGAPORE'S
NATIONAL
WATER AGENCY

PROGRAMME MANAGER:



A JOINT VENTURE DELIVERING THE DTSS2 PROJECT

CONSULTANT:



CH2M HILL Singapore Pte Ltd

PROJECT TITLE:

TUAS WATER RECLAMATION PLANT (TWRP)
DTSS PHASE 2

DRAWING TITLE

OVERALL
GENERAL, CONSTRUCTION NOTES
FIRE LEGEND

DRAFTED: JS	DESIGNED: JS	SHEET SIZE: A1
DRAFTING CHECK: DW	DESIGN CHECK: PE	SCALE: AS SHOWN
DATE: 24/07/18	REVIEWED: PK	PBS: 131101
CONTRACT: C4B	DRAWING NUMBER: PUB-DTSS2-TWRP	
	SHEET NUMBER: WSW41-A-0001	REVISION: T3

THIS DRAWING IS COPYRIGHT