


ALUMINUM
DUCT

SOUND
ATTENUATION
LINER IF
SPECIFIED



SEAL ALL JOINTS
W/ WATERPROOF
MASTIC

STORM LAP
JOINT

ATTACH SUPPORT TO DUCT
W/ SST RIVETS OR SCREWS.
ISOLATE DUCT FROM SUPPORT
W/ 1.6mm NEOPRENE RUBBER
GASKET

ISOLATE DUCT FROM
ANGLE SUPPORT
W/ 1.6 mm NEOPRENE
RUBBER GASKET

ALUMINUM DUCT

L40mm x 40mm x 5mm
GALV AFTER
FABRICATION, TYP

BUILT-UP ROOF

SHEET METAL PAN,
FILL W/ PLASTIC
CEMENT

TYP > 5

AS
REQD

PL 6mm x 75mm x 75mm MIN FASTEN W/ (2)
10 WEDGE ANCHORS, FOR METAL DECK,
BOLT PLATE DIRECTLY TO DECK, PLATE
SHOULD COVER TWO RIBS OF DECK MIN

5 > TYP

NOTES :

ALL DIMENSIONS IN MILLIMETERS,
UNLESS OTHERWISE NOTED

ABOVE ROOF DUCTING AND SUPPORT

NTS

STANDARD DETAIL

15421

JACOBS