

DIMENSIONS IN MILLIMETERS													
NOMINAL PIPE SIZE (DIA)						SUPPORTING							
						PIPE				FLANGE			
	'A'	'B'	'C'	'D'	'E'	'F'	'G'	'H'	'J'	'F'	'G'	'H'	'J'
150	100	300	10	M16	150	115	155	305	250	160	230	405	330
200	100	300	10	M16	150	125	205	330	275	190	230	405	355
250	100	300	10	M16	150	155	230	380	300	225	330	455	380
300	100	300	10	M16	150	180	280	430	325	250	380	510	405
350	100	300	10	M16	150	205	305	430	350	275	405	535	430
400	100	300	10	M16	150	230	330	480	375	305	455	610	455
450	100	300	10	M16	150	255	355	510	400	330	485	610	485
500	125	300	10	M16	150	255	380	535	425	380	535	660	535
550	125	300	10	M16	150	305	455	610	450	405	585	710	560
600	125	300	10	M16	150	330	485	610	475	405	610	760	585
650	125	300	10	M20	150	355	535	685	500	455	660	815	610
750	125	300	10	M20	150	405	584	710	550	510	740	865	660
850	125	375	10	M20	150	455	660	815	600	560	840	990	740
900	150	375	10	M20	150	485	685	815	650	610	865	1015	760
1000	150	450	15	M24	200	535	785	915	675	685	990	1145	820
1200	150	450	15	M24	200	610	915	1070	775	760	1120	1270	940

NOTES:

1. THIS SCHEDULE IS TO BE USED WITH DETAILS 15519A AND 15519B.
2. GALVANISE PIPE SUPPORT AFTER FABRICATION.

SMALL DIA PIPE SADDLE SUPPORT - PIPE SCHEDULE

NTS

STANDARD DETAIL

15519C

JACOBS